



Filter Product Guide

Filtro Guía de Productos
Guide des produits de filtre
Filter-Spezifikationen Guide
Filtro Guida ai Prodotti
Filtro Guia de Produtos

Air



Lube




Fuel



Hydraulic



Cabin




Coolant



Transmission



FFWS



dimensions

outer diameter



filter families

alternatives

primary application

liquid filter kits

Introduction	2
Introduction • Introducción • Krafteinleitungen • Introductin	
Filter Performance Alternatives	7
Filtros con prestaciones alternativas • Alternatives des performances des filtres • Alternative filtrationsleistungen • Varie tipologie de filtrazione	
Shoptalk	15
tienda de hablar • Conseils d'entretien • negozio di parlare • Pflege-Tipps	
Filter Maintenance Kits.....	31
Filtro de kits de mantenimiento • Filter Kits de maintenance • Filter Wartungs-Kits • Filtro kit di manutenzione	
Product Descriptions	36
Descripción de producto • Les descriptions de produits • Produktbeschreibungen • Descrizione del Prodotto	
Liquid Filtration Heads & Filters.....	37
Jefes de filtración de líquidos y filtros • Filtration des liquides et des filtres chefs • Liquid Filtration Köpfe und Filter • Capi di filtraggio di liquidi e filtri	
Product Guide by Part Number	49
Especificaciones des los productos por número de pieza • Caractéristiques techniques par numéro de pièce • Productangaben nach Teilenummern • Specificazioni prodotto per disegno	
Products by Type & Dimension	291
Especificaciones des los productos por tip oy dimensiones • Caractéristiques techniques par type et dimensions • Productangaben nach Typen und Abmessungen • Specificazioni prodotto per tipo e dimensione	
Liquid Spin-ons by Thread Size	336

The data published has been gathered from multiple Donaldson locations. Not all items will be available in your area, so for availability check with your local Donaldson distribution outlet.

Thank you for choosing Donaldson Filters.

On-Line Catalog

- Catálogo electrónico •
- Catalogue en ligne •
- On-line Katalog •
- Catalogo online •

www.donaldson.com

Legal Notice

Donaldson assumes no responsibility for errors or omissions in this publication, in data distributed through our internet-based catalogs or other electronic media. The information (including text, images and links) presented could include technical or other inaccuracies and is provided "AS IS" by Donaldson solely as a convenience. This information is without any warranties, express or implied, including but not limited to warranties of merchantability, fitness for a particular purpose or non-infringement.

Please note that changes are periodically made to our data and Donaldson may change the products or services described at any time. You may want to contact your local Donaldson authorized representative for further information before relying on any information.

Original PowerCore® Air Filters


Replacement PowerCore Filters for OE applications are available now through your Donaldson distribution outlet.



Donaldson PSD

These products feature our original PowerCore technology. PowerCore filters can be easily recognized by their unique corrugated media and will have the original PowerCore identity.

Donaldson also has a line of PSD Air Cleaners with the Original PowerCore technology.



PowerCore
A DONALDSON FILTRATION TECHNOLOGY



Freightliner



Navistar



GM



Ford

Donaldson® **Endurance**

Air
Lube
Coolant

Extended Service Filters

When you need maximum protection, Donaldson offers a full line of extended service filters that deliver better engine protection, minimizing vehicle downtime and reducing long-term operating costs. Our extended service filters are a direct replacements to existing OE filters and require no system modifications or special maintenance.

Donaldson Endurance coolant filters if you're interested in extending the life of your filter or Donaldson Endurance PLUS if you're looking to extended the life of your standard coolant.

- Air Filters with Ultra-Web® Nanofiber Filtration Technology
- Extended Service Lube Filters with Synteq® Filtration Technology
- Extended Service Coolant Filters that extend the life of your standard coolant



Air Filters

Donaldson air filters are engineered to meet your exacting requirements and constructed of durable, heavy-duty materials.

Donaldson brand performance air filters give you consistent performance over the life of your engine.

Donaldson designs and supplies most original equipment air systems, so our replacement filters are designed to meet or exceed original equipment standards.

Donaldson air filters are a competitively priced solution for your scheduled maintenance program that allows you to advance to your engine's next scheduled service with full engine performance and protection.

Heavy-duty liners

Corrosion resistant, coated steel liners support the filter media during operation and maximizes airflow.

Beading

Applied to both inner and outer liners, beading is designed to stabilize the media and prevent pleat tip wear.

Radial seal filter seals


Radial seal filters slip easily on and off the outlet tube during installation and service.

Axial filter seals

Strong, pliable gasket ensures a leak-free seal when properly installed. The gasket won't harden or deteriorate over the useful life of the filter.


Pleatloc™ media spacing

Ensures uniform pleat spacing, keeps filter media from bunching during operation and promotes longer filter service life.



Complete Filtration Coverage

Donaldson's line of liquid filters are designed to meet the needs of the engine application. With greater efficiency, more capacity and long service life you get maximum engine protection. You can be certain that Donaldson filters will perform in the most demanding environments.



Lube Filters

Donaldson durable lube filters keep your equipment running at its best to let you focus on what's most important, getting your job done.



Liquid Filter Kits for Popular Engines

Kits are available for popular engine filters in multiple combinations - lube + fuel, lube + fuel + coolant and other combinations. Available kits detailed in the Liquid Maintenance Kits section.



Heads & Filters - Mix 'n' Match

For those of you spec'ing new systems or wanting to change out an existing lube, fuel, coolant or hydraulic system, these new pages show head assemblies and their matching filters.

To help make your selection easier, we've listed the rated flow by filters and provided the filtration performance attribute that allows you to make the proper choice for your system.

Fuel Filters

Our fuel filters provide clean, filtered fuel that prevents pump wear, injector clogging, premature engine wear and can boost fuel efficiency. Donaldson has a complete line of spin-on, and cartridge-style filters. They are compatible with petroleum-based, ULSD and OEM approved Biodiesel fuels.



Replacement Filters for Popular Fuel Systems

Fuel filtration solutions to protect engine components and extend equipment life.

Replacement Filters for Popular Fuel Systems

Racor Fuel Systems,
Stanadyne Fuel Manager
FM100 Fuel Systems,
DAVCO Fuel Pro 380/382
Elemax Cartridges, Cummins
Engines



Our fuel filtration accessory line has expanded to include Twist&Drain™ valves, sensor options and a clear drain bowl

to meet your water managements needs. Donaldson Twist&Drain™ valves turn the messy and complicated task of draining water from a fuel filter into a simple and easy process. Twist&Drain provides flexible water drain solutions for Cummins® and Racor® fuel systems.



Flexible Drain Options

Standard Valve

Threaded
Sensor Port

WIF Sensor
(Packard)

WIF Sensor
(Deutsch)



Features

- Self-venting
- Easy to grip
- Fewer turns to drain
- Integrated hose barb for draining water into container
- Attaches to spin-on or drain bowl

Options

- Optional clear drain bowl for visual inspection
- Integrated water-in-fuel (WIF) sensors for Cummins engines
- Threaded sensor port accepts existing OEM WIF sensors on Racor fuel systems

Stanadyne® and Fuel Manager® are registered trademarks of Stanadyne Corporation.
DAVCO®, Fuel Pro® and EleMax® are registered trademarks of DAVCO Technology, LLC.
Cummins® is a registered trademark of Cummins Inc.
Racor® is a registered trademark of Parker Hannifin Corporation.

Coolant Filtration

SCA and SCA+ Filters

A complete line of replacement filters for diesel engines with various amounts of chemical treatment are available.

Coolant Treatment Maintenance

Our 3-way, coolant test strip is an fast and easy method to use during routine maintenance to adequately diagnose and supplement your coolant chemicals.




If you need to supplement your coolant additive package, use SCA and SCA+ chemical treatment available in many sizes from a pint to 55 gallon drum.

Hydraulic/Transmission Filters

Donaldson filters for mobile hydraulic systems are designed to keep the fluid and system as clean as necessary by removing particulate matter and debris which could ultimately cause component wear or failure.

Donaldson has an extensive line of hydraulic and transmission filters and system accessories. With our extensive stock program, you can mix and match filters with head assemblies to design a custom filtration system.



Duramax HIGH PRESSURE SPIN-ON

Commonly recognized by our orange can, the Duramax® revolutionized the hydraulic industry when introduced in the 1970s.



Filter Performance Alternatives

Use this section to see what alternatives are available for a standard filter listed in this catalog. Look up the number in the first column and additional filters with different filter media will be listed in the second and third columns. Donaldson engineers work closely with original equipment manufacturers to design filtration systems for a particular vehicle/engine and its operating environment. Perhaps you are interested in protecting your engine and reducing your operating costs with extended life filters.



A **Donaldson Endurance™** designated filter is what we recommend if you're looking to extend filter service change intervals or looking for higher efficiency compared to a cellulose media filter.

A filter with **CELLULOSE** media meets typical original equipment performance requirements. In most cases, this filter performs the same as the one originally supplied with your engine or vehicle.

SYNTEQ™ filter media can be found in Donaldson lube, fuel and hydraulic filters. In all cases, the filter provides a higher level of filtration efficiency than filters with cellulose media.

There are air filters that are **CELLULOSE-LONG-LIFE**. Cellulose, long-life filters are ideal when you want to service your air filter by restriction measurement.

An air filter with **TREATED** media is designed for on-highway vehicles operating in high carbon environments.

An air filter with **HIGH PULSATION** media is generally used in one and two cylinder engine applications (gen sets) non-reciprocating air compressors where the air cleaner experiences excessive intake air pulsation.

An air filter with **FLAME RETARDANT** media contains UL approved media. UL approval indicates suitability for operating in flammable applications. Flame retardant filters have the Duraguard marking on the end cap of the filter.

Filter Part No.	Media Type	Alternative Filter 1 Part No.	Media Type	Alternative Filter 2 Part No.	Media Type
EAF5000	Donaldson Endurance™ Ultra-Web®	P181000	Standard	P182000	Long Life
EAF5001	Donaldson Endurance™ Ultra-Web®	P181001	Standard		
EAF5002	Donaldson Endurance™ Ultra-Web®	P181002	Standard	P182002	Long Life
EAF5007	Donaldson Endurance™ Ultra-Web®	P181007	Standard		
EAF5008	Donaldson Endurance™ Ultra-Web®	P181008	Standard		
EAF5014	Donaldson Endurance™ Ultra-Web®	P181014	Standard		
EAF5015	Donaldson Endurance™ Ultra-Web®	P181015	Standard		
EAF5016	Donaldson Endurance™ Ultra-Web®	P181016	Standard	P182016	Long Life
EAF5024	Donaldson Endurance™ Ultra-Web®	P129396	Treated Media		
EAF5025	Donaldson Endurance™ Ultra-Web®	P129472	Treated Media		
EAF5026	Donaldson Endurance™ Ultra-Web®	P141228	Standard		
EAF5027	Donaldson Endurance™ Ultra-Web®	P142100	Standard		
EAF5028	Donaldson Endurance™ Ultra-Web®	P181028	Standard		
EAF5029	Donaldson Endurance™ Ultra-Web®	P150694	Standard		
EAF5034	Donaldson Endurance™ Ultra-Web®	P181034	Standard	P182034	Long Life
EAF5035	Donaldson Endurance™ Ultra-Web®	P181035	Standard		
EAF5038	Donaldson Endurance™ Ultra-Web®	P181038	Standard	P182038	Long Life
EAF5039	Donaldson Endurance™ Ultra-Web®	P181039	Standard	P182039	Long Life
EAF5040	Donaldson Endurance™ Ultra-Web®	P181040	Standard	P182040	Long Life
EAF5041	Donaldson Endurance™ Ultra-Web®	P181041	Standard	P182041	Long Life
EAF5042	Donaldson Endurance™ Ultra-Web®	P181042	Standard	P182042	Long Life
EAF5043	Donaldson Endurance™ Ultra-Web®	P181043	Standard	P182043	Long Life
EAF5044	Donaldson Endurance™ Ultra-Web®	P181044	Standard	P182044	Long Life
EAF5046	Donaldson Endurance™ Ultra-Web®	P181046	Standard	P182046	Long Life
EAF5047	Donaldson Endurance™ Ultra-Web®	P150695	Standard		
EAF5048	Donaldson Endurance™ Ultra-Web®	P151028	Standard		

Filter Part No.	Media Type	Alternative Filter 1 Part No.	Media Type	Alternative Filter 2 Part No.	Media Type
EAF5049	Donaldson Endurance™ Ultra-Web®	P181049	Standard	P182049	Long Life
EAF5053	Donaldson Endurance™ Ultra-Web®	P153551	Standard		
EAF5054	Donaldson Endurance™ Ultra-Web®	P182054	Long Life		
EAF5055	Donaldson Endurance™ Ultra-Web®	P155842	Standard		
EAF5056	Donaldson Endurance™ Ultra-Web®	P181056	Standard		
EAF5057	Donaldson Endurance™ Ultra-Web®	P181057	Standard		
EAF5059	Donaldson Endurance™ Ultra-Web®	P182059	Long Life	P182059	Long Life
EAF5061	Donaldson Endurance™ Ultra-Web®	P522293	Standard		
EAF5065	Donaldson Endurance™ Ultra-Web®	P522874	Standard		
EAF5066	Donaldson Endurance™ Ultra-Web®	P526678	Standard		
EAF5067	Donaldson Endurance™ Ultra-Web®	P527484	Standard		
EAF5069	Donaldson Endurance™ Ultra-Web®	P527682	Standard		
EAF5074	Donaldson Endurance™ Ultra-Web®	P771003	Standard		
EAF5092	Donaldson Endurance™ Ultra-Web®	P181073	Standard	P182073	Long Life
EAF5095	Donaldson Endurance™ Ultra-Web®	P181095	Standard		
EAF5096	Donaldson Endurance™ Ultra-Web®	P181096	Standard		
EAF5097	Donaldson Endurance™ Ultra-Web®	P141317	Standard		
EAF5098	Donaldson Endurance™ Ultra-Web®	P540388	Standard		
EAF5099	Donaldson Endurance™ Ultra-Web®	P181099	Standard		
EAF5100	Donaldson Endurance™ Ultra-Web®	P534816	Standard		
EAF5101	Donaldson Endurance™ Ultra-Web®	P534925	Standard		
EAF5102	Donaldson Endurance™ Ultra-Web®	P181186	Standard		
EAF5104	Donaldson Endurance™ Ultra-Web®	P533235	Standard		
EAF5105	Donaldson Endurance™ Ultra-Web®	P532966	Standard		
EAF5106	Donaldson Endurance™ Ultra-Web®	P534096	Standard		
EAF5107	Donaldson Endurance™ Ultra-Web®	P549644	Standard		
EAF5108	Donaldson Endurance™ Ultra-Web®	P600676	Standard		
EAF5109	Donaldson Endurance™ Ultra-Web®	P533930	Standard		
EAF5110	Donaldson Endurance™ Ultra-Web®	P526756	Standard	P902296	Flame Retardant Media
EAF5112	Donaldson Endurance™ Ultra-Web®	P522451	Standard		
EAF5113	Donaldson Endurance™ Ultra-Web®	P145702	Standard		
EAF5114	Donaldson Endurance™ Ultra-Web®	P616691	Standard		
EAF5116	Donaldson Endurance™ Ultra-Web®	P777868	Standard		
EAF5117	Donaldson Endurance™ Ultra-Web®	P182066	Long Life		
EAF5123	Donaldson Endurance™ Ultra-Web®	P181034	Standard		
EAF5124	Donaldson Endurance™ Ultra-Web®	P140236	Standard		
EAF5126	Donaldson Endurance™ Ultra-Web®	P181070	Standard	P182070	Long Life
EAF5127	Donaldson Endurance™ Ultra-Web®	P181082	Standard	P182082	Long Life
EAF5128	Donaldson Endurance™ Ultra-Web®	P127308	Standard		
EAF5129	Donaldson Endurance™ Ultra-Web®	P781398	Standard		
EAF5130	Donaldson Endurance™ Ultra-Web®	P777409	Standard		
EAF5131	Donaldson Endurance™ Ultra-Web®	P771561	Standard		
EAF5132	Donaldson Endurance™ Ultra-Web®	P182078	Standard		
EAF5133	Donaldson Endurance™ Ultra-Web®	P777871	Standard		
EAF5134	Donaldson Endurance™ Ultra-Web®	P182052	Long Life		
EAF5135	Donaldson Endurance™ Ultra-Web®	P533938	Standard		
EAF5136	Donaldson Endurance™ Ultra-Web®	P124867	Standard		
EAF5137	Donaldson Endurance™ Ultra-Web®	P134353	Standard		
EAF5141	Donaldson Endurance™ Ultra-Web®	P500021	Standard		
EAF5142	Donaldson Endurance™ Ultra-Web®	P900509	Standard		
EAF5143	Donaldson Endurance™ Ultra-Web®	P902309	Standard		
EAF5147	Donaldson Endurance™ Ultra-Web®	P537355	Standard		

Filter		Alternative Filter 1		Alternative Filter 2	
Part No.	Media Type	Part No.	Media Type	Part No.	Media Type
EAF5148	Donaldson Endurance™ Ultra-Web®	P544741	Standard		
EAF5149	Donaldson Endurance™ Ultra-Web®	P544950	Standard		
EAF5150	Donaldson Endurance™ Ultra-Web®	P544301	Standard		
EAF5151	Donaldson Endurance™ Ultra-Web®	P544243	Standard		
EAF5152	Donaldson Endurance™ Ultra-Web®	P608306	Standard		
EAF5153	Donaldson Endurance™ Ultra-Web®	P609519	Standard		
EAF5154	Donaldson Endurance™ Ultra-Web®	P777579	Standard		
EAF5156	Donaldson Endurance™ Ultra-Web®	P781098	Standard		
EAF5157	Donaldson Endurance™ Ultra-Web®	P821938	Standard		
EAF5187	Donaldson Endurance™ Ultra-Web®	P181187	Standard		
EAF5188	Donaldson Endurance™ Ultra-Web®	P181188	Standard		
EAF5189	Donaldson Endurance™ Ultra-Web®	P181189	Standard		
EAF5194	Donaldson Endurance™ Ultra-Web®	P181017	Standard		
ECF4085	Donaldson Endurance™ Synteq™ Media	P554685	Standard		
ECF4088	Donaldson Endurance™ Plus	P554071	Standard		
ECF4089	Donaldson Endurance™ Plus	P552096	Standard		
EFF0047	Donaldson Endurance™ Synteq™ Media	P550959	Standard		
EFF7917	Donaldson Endurance™ Synteq™ Media	P556916	Standard	P556917	Standard
EFF9092	Donaldson Endurance™ Synteq™ Media	P555823	Standard		
ELF2500	Donaldson Endurance™ Plus	P552100	Standard	ELF3998	Donaldson Endurance™
ELF2501	Donaldson Endurance™ Plus	P559000	Standard	ELF7900	Donaldson Endurance™
ELF2502	Donaldson Endurance™ Plus	P554005	Standard	ELF7405	Donaldson Endurance™
ELF2504	Donaldson Endurance™ Plus	P551807	Standard	ELF7483	Donaldson Endurance™
ELF3998	Donaldson Endurance™ Synteq™ Media	P552100	Standard		
ELF7300	Donaldson Endurance™ Synteq™ Media	P553000	Standard		
ELF7345	Donaldson Endurance™ Synteq™ Media	P558616	Standard		
ELF7349	Donaldson Endurance™ Synteq™ Media	P558615	Standard		
ELF7367	Donaldson Endurance™ Synteq™ Media	P550367	Standard		
ELF7405	Donaldson Endurance™ Synteq™ Media	P554105	Standard (118 MM Dia)	P554005	Standard (135 MM Dia)
ELF7483	Donaldson Endurance™ Synteq™ Media	P553191	Standard		
ELF7670	Donaldson Endurance™ Synteq™ Media	P551670	Standard		
ELF7690	Donaldson Endurance™ Synteq™ Media	P550769	Standard		
ELF7739	Donaldson Endurance™ Synteq™ Media	P554004	Standard		
ELF7900	Donaldson Endurance™ Synteq™ Media	P559000	Standard		
ELF7917	Donaldson Endurance™ Synteq™ Media	P556917	Standard		
ELF7947	Donaldson Endurance™ Synteq™ Media	P550947	Standard		
P102745	Standard	P148970	High Pulsation		
P122510	Flame Retardant Media	P181050	Standard		
P122529	Flame Retardant Media	P181000	Standard	EAF5000	Donaldson Endurance™ Ultra-Web®
P124867	Standard	EAF5136	Donaldson Endurance™ Ultra-Web®		
P127172	Standard	P902282	Flame Retardant Media		
P127308	Standard	EAF5128	Donaldson Endurance™ Ultra-Web®		
P129396	Treated Media	P151097	Standard	EAF5024	Donaldson Endurance™ Ultra-Web®
P129472	Treated Media	EAF5025	Donaldson Endurance™ Ultra-Web®	P140822	Standard
P134353	Standard	EAF5137	Donaldson Endurance™ Ultra-Web®		
P140236	Standard	EAF5124	Donaldson Endurance™ Ultra-Web®		

Filter Part No.	Media Type	Alternative Filter 1 Part No.	Media Type	Alternative Filter 2 Part No.	Media Type
P140822	Standard	P129472	Treated Media		
P141228	Standard	EAF5026	Donaldson Endurance™ Ultra-Web®		
P141317	Standard	EAF5097	Donaldson Endurance™ Ultra-Web®		
P142100	Standard	EAF5027	Donaldson Endurance™ Ultra-Web®		
P145702	Standard	EAF5113	Donaldson Endurance™ Ultra-Web®		
P148043	Treated Media	P150694	Standard	EAF5029	Donaldson Endurance™ Ultra-Web®
P148044	Treated Media	P150692	Standard	EAF5073	Donaldson Endurance™ Ultra-Web®
P148573	High Pulsation	P181059	Standard	P182059	Long Life
P148586	High Pulsation	P181062	Standard	P182062	Long Life
P148932	Flame Retardant Media	P181062	Standard	P182062	Long Life
P148968	High Pulsation	P181054	Standard	P182054	Long Life
P148969	High Pulsation	P181050	Standard	P182050	Long Life
P148970	High Pulsation	P102745	Standard		
P150692	Standard	EAF5073	Donaldson Endurance™ Ultra-Web®	P148044	Treated Media
P150694	Standard	EAF5029	Donaldson Endurance™ Ultra-Web®	P149043	Treated Media
P150695	Standard	EAF5047	Donaldson Endurance™ Ultra-Web®		
P151028	Standard	EAF5048	Donaldson Endurance™ Ultra-Web®		
P151097	Standard	EAF5024	Donaldson Endurance™ Ultra-Web®	P129396	Treated Media
P153551	Standard	EAF5053	Donaldson Endurance™ Ultra-Web®	P154575	Treated Media
P153962	Treated Media	EAF5111	Donaldson Endurance™ Ultra-Web®	P153972	Standard
P153972	Standard	EAF5111	Donaldson Endurance™ Ultra-Web®	P153962	Treated Media
P154575	Treated Media	EAF5053	Donaldson Endurance™ Ultra-Web®	P153551	Standard
P155842	Standard	EAF5055	Donaldson Endurance™ Ultra-Web®		
P164200	Synteq™ Media	P559740	Standard		
P164203	Synteq™ Media	P550816	Standard		
P164205	Synteq™ Media	P556064	Standard		
P164207	Synteq™ Media	P556700	Standard		
P164241	Synteq™ Media	P555461	Standard		
P166375	Synteq™ Media Lube	P550132	Standard		
P166376	Synteq™ Media Hydraulic	P550951	Standard		
P166564	Synteq™ Media	P550035	Standard		
P169071	Synteq™ Media	P550008	Standard		
P181000	Standard	EAF5000	Donaldson Endurance™ Ultra-Web®	P182000	Long Life
P181001	Standard	EAF5001	Donaldson Endurance™ Ultra-Web®	P182001	Long Life
P181002	Standard	EAF5002	Donaldson Endurance™ Ultra-Web®	P182002	Long Life
P181007	Standard	EAF5007	Donaldson Endurance™ Ultra-Web®	P182007	Long Life
P181008	Standard	EAF5008	Donaldson Endurance™ Ultra-Web®	P182008	Long Life
P181014	Standard	EAF5014	Donaldson Endurance™ Ultra-Web®	P182014	Long Life
P181015	Standard	EAF5015	Donaldson Endurance™ Ultra-Web®	P182015	Long Life
P181016	Standard	EAF5016	Donaldson Endurance™ Ultra-Web®	P182016	Long Life
P181017	Standard	EAF5194	Donaldson Endurance™ Ultra-Web®		
P181019	Standard	EAF5019	Donaldson Endurance™ Ultra-Web®		
P181028	Standard	EAF5028	Donaldson Endurance™ Ultra-Web®	P182028	Long Life
P181031	Standard	P182031	Long Life		
P181032	Standard	P182032	Long Life		
P181033	Standard	P182033	Long Life		
P181034	Standard	EAF5034	Donaldson Endurance™ Ultra-Web®	P182034	Long Life
P181035	Standard	EAF5035	Donaldson Endurance™ Ultra-Web®	P182035	Long Life
P181036	Standard	P182036	Long Life		
P181037	Standard	P182037	Long Life		

Filter Part No.	Media Type	Alternative Filter 1		Alternative Filter 2	
		Part No.	Media Type	Part No.	Media Type
P181038	Standard	EAF5038	Donaldson Endurance™ Ultra-Web®	P182038	Long Life
P181039	Standard	EAF5039	Donaldson Endurance™ Ultra-Web®	P182039	Long Life
P181040	Standard	EAF5040	Donaldson Endurance™ Ultra-Web®	P182040	Long Life
P181041	Standard	EAF5041	Donaldson Endurance™ Ultra-Web®	P182041	Long Life
P181042	Standard	EAF5042	Donaldson Endurance™ Ultra-Web®	P182042	Long Life
P181043	Standard	EAF5043	Donaldson Endurance™ Ultra-Web®	P182043	Long Life
P181044	Standard	EAF5044	Donaldson Endurance™ Ultra-Web®	P182044	Long Life
P181045	Standard	P182045	Long Life		
P181046	Standard	EAF5046	Donaldson Endurance™ Ultra-Web®	P182046	Long Life
P181049	Standard	EAF5049	Donaldson Endurance™ Ultra-Web®	P182049	Long Life
P181050	Standard	P182050	Long Life	P122510	Flame Retardant Media
P181052	Standard	P182052	Long Life	P122514	Flame Retardant Media
P181054	Standard	P182054	Long Life	P148968	High Pulsation
P181056	Standard	EAF5056	Donaldson Endurance™ Ultra-Web®		
P181057	Standard	EAF5057	Donaldson Endurance™ Ultra-Web®		
P181059	Standard	P148573	High Pulsation	P182059	Long Life
P181062	Standard	P148586	High Pulsation	P182062	Long Life
P181063	Standard	P182063	Long Life		
P181064	Standard	P182064	Long Life		
P181068	Standard	P182068	Long Life		
P181070	Standard	P182070	Long Life	EAF5126	Donaldson Endurance™ Ultra-Web®
P181071	Standard	P182071	Long Life		
P181072	Standard	P182072	Long Life		
P181073	Standard	P182073	Long Life	EAF5092	Donaldson Endurance™
P181082	Standard	P182082	Long Life	EAF5127	Donaldson Endurance™ Ultra-Web®
P181095	Standard	EAF5095	Donaldson Endurance™ Ultra-Web®		
P181096	Standard	EAF5096	Donaldson Endurance™ Ultra-Web®		
P181099	Standard	EAF5099	Donaldson Endurance™ Ultra-Web®	P182099	Long Life
P181186	Standard	EAF5102	Donaldson Endurance™ Ultra-Web®		
P181187	Standard	EAF5187	Donaldson Endurance™ Ultra-Web®		
P181188	Standard	EAF5188	Donaldson Endurance™ Ultra-Web®		
P181189	Standard	EAF5189	Donaldson Endurance™ Ultra-Web®		
P182000	Long Life	EAF5000	Donaldson Endurance™ Ultra-Web®	P181000	Standard
P182001	Long Life	EAF5001	Donaldson Endurance™ Ultra-Web®	P181001	Standard
P182002	Long Life	EAF5002	Donaldson Endurance™ Ultra-Web®	P181002	Standard
P182007	Long Life	EAF5007	Donaldson Endurance™ Ultra-Web®	P181007	Standard
P182008	Long Life	EAF5008	Donaldson Endurance™ Ultra-Web®	P181008	Standard
P182014	Long Life	EAF5014	Donaldson Endurance™ Ultra-Web®	P181014	Standard
P182015	Long Life	EAF5015	Donaldson Endurance™ Ultra-Web®	P181015	Standard
P182016	Long Life	EAF5016	Donaldson Endurance™ Ultra-Web®	P181016	Standard
P182028	Long Life	EAF5028	Donaldson Endurance™ Ultra-Web®	P181028	Standard
P182031	Long Life	P181031	Standard		
P182032	Long Life	P181032	Standard		
P182033	Long Life	P181033	Standard		
P182034	Long Life	EAF5034	Donaldson Endurance™ Ultra-Web®	P181034	Standard
P182035	Long Life	EAF5035	Donaldson Endurance™ Ultra-Web®	P181035	Standard
P182036	Long Life	P181036	Standard		
P182037	Long Life	P181037	Standard		
P182038	Long Life	EAF5038	Donaldson Endurance™ Ultra-Web®	P181038	Standard
P182039	Long Life	EAF5039	Donaldson Endurance™ Ultra-Web®	P181039	Standard
P182040	Long Life	EAF5040	Donaldson Endurance™ Ultra-Web®	P181040	Standard
P182041	Long Life	EAF5041	Donaldson Endurance™ Ultra-Web®	P181041	Standard
P182042	Long Life	EAF5042	Donaldson Endurance™ Ultra-Web®	P181042	Standard

Filter Part No.	Media Type	Alternative Filter 1 Part No.	Media Type	Alternative Filter 2 Part No.	Media Type
P182043	Long Life	EAF5043	Donaldson Endurance™ Ultra-Web®	P181043	Standard
P182044	Long Life	EAF5044	Donaldson Endurance™ Ultra-Web®	P181044	Standard
P182045	Long Life	P181045	Standard		
P182046	Long Life	EAF5046	Donaldson Endurance™ Ultra-Web®	P181046	Standard
P182049	Long Life	EAF5049	Donaldson Endurance™ Ultra-Web®	P181049	Standard
P182050	Long Life	P181050	Standard	P122510	Flame Retardant Media
P182052	Long Life	EAF5134	Donaldson Endurance™ Ultra-Web®	P122514	Flame Retardant Media
P182054	Long Life	P181054	Standard	EAF5054	Donaldson Endurance™ Ultra-Web®
P182059	Long Life	P181059	Standard	EAF5059	Donaldson Endurance™ Ultra-Web®
P182062	Long Life	P181062	Standard		
P182063	Long Life	P181063	Standard		
P182064	Long Life	P181064	Standard	EAF5138	Donaldson Endurance™ Ultra-Web®
P182066	Standard	EAF5117	Donaldson Endurance™ Ultra-Web®		
P182068	Long Life	P181068	Standard		
P182070	Long Life	P181070	Standard	EAF5126	Donaldson Endurance™ Ultra-Web®
P182071	Long Life	P181071	Standard		
P182072	Long Life	P181072	Standard	P148967	High Pulsation
P182073	Long Life	P181073	Standard	EAF5092	Donaldson Endurance™
P182078	Standard	EAF5132	Donaldson Endurance™ Ultra-Web®		
P182082	Long-Life	P181082	Standard	EAF5127	Donaldson Endurance™ Ultra-Web®
P182095	Long Life	EAF5095	Donaldson Endurance™ Ultra-Web®	P181095	Standard
P182096	Long Life	EAF5096	Donaldson Endurance™ Ultra-Web®	P181096	Standard
P182099	Long Life	EAF5099	Donaldson Endurance™ Ultra-Web®	P181099	Standard
P500021	Standard	EAF5141	Donaldson Endurance™ Ultra-Web®		
P522293	Standard	EAF5061	Donaldson Endurance™ Ultra-Web®		
P522451	Standard	EAF5112	Donaldson Endurance™ Ultra-Web®		
P522874	Standard	EAF5065	Donaldson Endurance™ Ultra-Web®		
P526678	Standard	EAF5066	Donaldson Endurance™ Ultra-Web®		
P526756	Standard	EAF5110	Donaldson Endurance™ Ultra-Web®	P902296	Flame Retardant Media
P527484	Standard	EAF5067	Donaldson Endurance™ Ultra-Web®		
P527682	Standard	EAF5069	Donaldson Endurance™ Ultra-Web®		
P532410	Flame Retardant Media	P822768	Standard		
P532966	Standard	EAF5105	Donaldson Endurance™ Ultra-Web®		
P533235	Standard	EAF5104	Donaldson Endurance™ Ultra-Web®		
P533930	Standard	EAF5109	Donaldson Endurance™ Ultra-Web®		
P533938	Standard	EAF5135	Donaldson Endurance™ Ultra-Web®		
P534096	Standard	EAF5106	Donaldson Endurance™ Ultra-Web®		
P534816	Standard	EAF5100	Donaldson Endurance™ Ultra-Web®		
P534925	Standard	EAF5101	Donaldson Endurance™ Ultra-Web®		
P535770	Flame Retardant	P827653	Standard		
P536732	Long Life	P536733	Standard		
P536733	Standard	P536732	Long Life		
P537355	Standard	EAF5147	Donaldson Endurance™ Ultra-Web®		
P540388	Standard	EAF5098	Donaldson Endurance™ Ultra-Web®		
P544243	Standard	EAF5151	Donaldson Endurance™ Ultra-Web®		
P544301	Standard	EAF5150	Donaldson Endurance™ Ultra-Web®		
P544741	Standard	EAF5148	Donaldson Endurance™ Ultra-Web®		
P544950	Standard	EAF5149	Donaldson Endurance™ Ultra-Web®		
P549644	Standard	EAF5107	Donaldson Endurance™ Ultra-Web®		

Filter		Alternative Filter 1		Alternative Filter 2	
Part No.	Media Type	Part No.	Media Type	Part No.	Media Type
P550008	Standard	P169071	Synteq™ Media		
P550035	Standard	P166564	Synteq™ Media		
P550060	Paper Media	P550860	Felt Media		
P550061	Felt Media	P550861	Paper Media		
P550105	Standard	P558000	FFWS Twist&Drain™	P550104	Short
P550106	Drain Screw	P558000	FFWS Twist&Drain™		
P550115	Standard	P550215	H2O Absorbing		
P550117	Cellulose Media	P550300	Cotton Media		
P550132	Standard Lube	P166375	Synteq™ Media Lube	P550951	Standard
P550215	H2O Absorbing	P550115	Standard		
P550218	Standard	EFF9441	Donaldson Endurance™		
P550367	Standard	ELF7367	Donaldson Endurance™ Synteq™ Media		
P550485	Standard	P166481	Synteq™ Media		
P550730	Collection Bowl	P551767	Drain Valve		
P550769	Standard	ELF7690	Donaldson Endurance™ Synteq™ Media		
P550816	Standard	P164203	Synteq™ Media		
P550860	Felt Media	P550060	Paper Media		
P550861	Paper Media	P550061	Felt Media		
P550901	Treated Cellulose Twist&Drain™	P551000	Synteq™ Media with Twist&Drain™	P558000	Standard Twist&Drain™
P550947	Standard	ELF7947	Donaldson Endurance™ Synteq™ Media		
P550951	Standard Hydraulic	P166376	Synteq™ Media Media	P550132	Standard Lube
P550959	Standard	EFF0047	Donaldson Endurance™ Synteq™ Media		
P551000	Synteq™ Media	P550901	Treated Cellulose	P558000	Standard
P551022	FFWS Spin On With H2O Sensor-ISC	P552032	Reuse H2O Sensor		
P551670	Standard	ELF7670	Donaldson Endurance™ Synteq™ Media		
P551767	Drain Valve	P550730	Collection Bowl		
P551807	Standard	ELF7483	Donaldson Endurance™ Synteq™ Media		
P551808	High Efficiency Cellulose	ELF7405	Donaldson Endurance™		
P552032	Reuse H2O Sensor	P551003	FFWS Spin-on with H2O Sensor-ISM	P551022	FFWS Spin-on with H2O Sensor-ISC
P552096	Standard	ECF4089	Donaldson Endurance™ Plus		
P552100	Standard	ELF3998	Donaldson Endurance™ Synteq™ Media		
P553000	Standard	ELF7300	Donaldson Endurance™ Synteq™ Media		
P553191	Standard	ELF7483	Donaldson Endurance™ Synteq™ Media		
P554004	Standard	ELF7739	Donaldson Endurance™ Synteq™ Media		
P554005	Standard	ELF7405	Donaldson Endurance™ Synteq™ Media	P554105	Standard (118 MM Dia)
P554071	Standard	ECF4088	Donaldson Endurance™ Plus		
P554105	Standard	ELF7405	Donaldson Endurance™ Synteq™ Media	P554005	Standard (135 MM Dia)
P554685	Standard	ECF4085	Donaldson Endurance™ Synteq™ Media		
P555003	FFWS with Bowl	P558000	FFWS Twist&Drain™		
P555006	FFWS with Bowl	P555823	Standard		
P555461	Standard	P164241	Synteq™ Media		
P555823	Standard	EFF9092	Donaldson Endurance™ Synteq™ Media		
P556064	Standard	P164205	Synteq™ Media		
P556700	Standard	P164207	Synteq™ Media		
P556916	Standard	EFF7917	Donaldson Endurance™ Synteq™ Media		
P556917	Standard	EFF7917	Donaldson Endurance™ Synteq™ Media		

Filter Part No.	Media Type	Alternative Filter 1 Part No.	Media Type	Alternative Filter 2 Part No.	Media Type
P558000	Standard Twist&Drain™	P551000	Synteq™ Media Twist&Drain™	P550901	Treated Cellulose Twist&Drain™
P558615	Standard	ELF7349	Donaldson Endurance™ Synteq™ Media		
P558616	Standard	ELF7345	Donaldson Endurance™ Synteq™ Media		
P559000	Standard	ELF7900	Donaldson Endurance™ Synteq™ Media		
P559740	Standard	P164200	Synteq™ Media		
P600676	Standard	EAF5108	Donaldson Endurance™ Ultra-Web®		
P604457	Standard	P611858	Flame Retardant Media		
P608306	Standard	EAF5152	Donaldson Endurance™ Ultra-Web®		
P609218	Standard	P611859	Flame Retardant Media		
P609519	Standard	EAF5153	Donaldson Endurance™ Ultra-Web®		
P611858	Flame Retardant Media	P604457	Standard		
P611859	Flame Retardant Media	P609218	Standard		
P616691	Standard	EAF5114	Donaldson Endurance™ Ultra-Web®		
P771003	Standard	EAF5074	Donaldson Endurance™ Ultra-Web®		
P771529	Standard	P772529	Long Life		
P771561	Standard	EAF5131	Donaldson Endurance™ Ultra-Web®		
P772506	Air Primary	EAF5155	Donaldson Endurance™ Ultra-Web®		
P772529	Long Life	P771529	Standard		
P777409	Standard	EAF5130	Donaldson Endurance™ Ultra-Web®		
P777579	Standard	EAF5154	Donaldson Endurance™		
P777868	Standard	EAF5116	Donaldson Endurance™		
P777871	Standard	EAF5133	Donaldson Endurance™ Ultra-Web®		
P778674	Standard	P783117	Donaldson Endurance™ Ultra-Web®		
P781039	Standard	P783554	Flame Retardant Media		
P781098	Standard	EAF5156	Donaldson Endurance™ Ultra-Web®		
P781398	Standard	EAF5129	Donaldson Endurance™ Ultra-Web®		
P781746	Standard	P902297	Flame Retardant Media		
P783117	Donaldson Ultra-Web®	P778674	Standard		
P783554	Flame Retardant Media	P781039	Standard		
P786334	Donaldson Ultra-Web®	P777871	Standard		
P821938	Standard	EAF5157	Donaldson Endurance™ Ultra-Web®		
P827653	Standard	P535770	Flame Retardant Media		
P828889	Standard	EAF5091	Donaldson Endurance™ Ultra-Web®		
P831424	Flame Retardant Media	P821575	Standard		
P900509	Standard	EAF5142	Donaldson Endurance™ Ultra-Web®		
P902296	Flame Retardant Media	EAF5110	Donaldson Endurance™ Ultra-Web®	P526756	Standard
P902297	Flame Retardant Media	P781746	Standard		
P902309	Standard	EAF5143	Donaldson Endurance™ Ultra-Web®		

The following Shoptalk section contains maintenance tips, cost reduction ideas and product features and benefits.

If you're interested in having Shoptalk arrive to you by email or mail, please go to www.shoptalk.donaldson.com to sign up.

Simple facts for diesel engine owners

... catch-up on the latest information in one of two ways

Direct Mail Cards

If you haven't signed up to get your free subscription to Shoptalk, you have three options:

1. Fill out our online subscription form at www.shoptalk.donaldson.com.
2. Call us toll free at 866-759-4015 or directly at 952-887-3699.
3. Fill out the Order Form Reply Card included in the sample pack and drop it in the mail.



www.shoptalk.donaldson.com

The same information found in our cards is also available 24/7 from the Donaldson Engine+Vehicle web site. Go to www.shoptalk.donaldson.com!



General Topics

Will Using Aftermarket Filters or Mufflers Void My Warranty?	16
Do You Store or Warehouse Filters On-Site?	16
Filter Recycling	17
Industry Resource: The Filter Manufacturers Council ..	17

Liquid Filtration

We Set the Standard for Liquid Filtration Performance	17
Diesel Engine Liquid Test Kits	18
Watch Out for Dents on Liquid Filters!	19
They Say a Picture is Worth a Thousand Words	20
Watch Out for Old Compression Gaskets!	20
Using Donaldson Fuel Filters with Biodiesel	21
Don't Retighten a Lube Filter Once it Has Been Installed	21

Air Filtration

Worried About Water in Your Air Intake System?	22
Air Intake Accessories for All Conditions Available from Donaldson	22
Caution: Replace Damaged or Missing VacValves Immediately!	23
Want to Change Your Air Filter Less Often?	24
Take a Look at Air Filtration Efficiency and Dust Holding Capacity	25
All Nanofibers are Not Created Equal	25
Don't Throw Away a Good Filter Just Because it Might Look "Dirty"	26
Keep Those ECG Konepac™ Air Cleaner Latches Inspected	27
Dust Dumpa Solves Dust Expulsion Issues in High Dust Environments	27
Dust Dumpa	27
What's Donaldson's Position Air Filter Cleaning & Reuse?	28

Hydraulic Filtration

How Big is a Micron?	29
Minimize Water in Hydraulic Systems	29
Understanding the Beta Rating System	30
Compatibility of Donaldson Filter Media with Hydraulic Fluids	30

Shoptalk

Will Using Aftermarket Filters or Mufflers Void My Warranty?

Answer: Good News! No need to worry about voiding your warranty – you can use aftermarket products! You still need to follow your manufacturer’s recommend maintenance practices, but your warranty is protected under the Magnuson-Moss Warranty Act. Information on the Magnuson-Moss Warranty Act is available at www.ftc.gov/bcp/edu/pubs/business/adv/bus01.shtm.



In addition, Donaldson warrants its aftermarket products against failure due to defects in materials and workmanship for the period specified under Terms and Conditions for the particular product.

Do You Store or Warehouse Filters On-Site?

Whether it’s an empty trailer or building, it’s important to practice good storage and handling techniques when it comes to filters.

Before installing any filter on a piece of equipment make sure the filter is clean, unused and free of damage.

Filter Storage & Handling Tips

- Never store an air filter on a shelf without it being in a box or totally sealed from outside contaminant.
- When you see an open box of filters on the shelf, tape it shut - unless the filters inside the box are individually sealed.
- Handle filters with care to prevent filter damage; for example, don’t throw filters into the back of a truck.
- If transporting filters from one job site to another, don’t let them roll around on the floorboard or back of the truck that may cause damage.
- Metal storage shelves may cause condensation to form on filters if sitting directly on metal. Over time the filter may get rusty. Another good reason to store filters in boxes.
- If product box has layers of contaminant, take care that the contaminant doesn’t get on the new filter as you remove it from the box.
- Practice "first-in, first-out" with your inventory. When possible, always use the oldest inventory first.
- Make sure any labels with product information and manufacturing dates are visible to personnel pulling from the shelves.

Filter Recycling

Donaldson encourages all individuals and businesses to recycle their used oil filters. Recycling used oil filters helps divert waste from landfills while providing a valuable resource for recycling. We encourage you to check your local disposal regulations for proper disposal and recycling.

Industry Resource: The Filter Manufacturers Council

Established in 1971, the Filter Manufacturers Council represents North American manufacturers of vehicular and industrial filtration products. Initially developed to monitor regulatory and technological developments that affect the industry, the Council has since expanded its activities substantially.



www.filtercouncil.org

The Council has undertaken several environmental initiatives including partnering with states to promote the proper management of used oil filters. In addition, the operation of the hotline and web site provide valuable information regarding state regulations and companies that transport, process and recycle used oil filters.

Donaldson Company is a member of the Filter Manufacturers Council.


We Set the Standard for Liquid Filtration Performance



When you are looking for improved performance, look for Donaldson lube, fuel and hydraulic filters with synthetic media – they are easy to spot; they carry our Synteq™ brand name!

Synteq for Lube Filtration

When an application requires higher efficiency filtration than cellulose filter media can deliver, we use Synteq. Synteq captures more and smaller contaminant than cellulose.



The microscopic photo of our Synteq lube filter media shows the consistency in fiber size and composition. The black circle in the picture above represents the diameter of a 20 micron particle easily captured by the media.

Synteq for Fuel Filtration


Our newest filter media technology is specifically formulated for high performance water separation. Filters with this media provide a high level of protection to engine fuel pumps and injectors.

Cellulose Layer

This silicone treated cellulose layer provides improved water separation and dirt holding capacity performance. It captures the smallest contaminants circulating in the fuel.

Synthetic Layer

This layer consists of synthetic meltblown fibers that deliver maximum filtration capacity and optimum water separation. This layer is engineered to capture progressively finer contaminant and coalesce water droplets to enhance emulsified water separation performance.



Ref: Shoptalk Card F115220

Diesel Engine Liquid Test Kits

Lube Oil Test Kits


Today's maintenance personnel know that regular monitoring of the oil quality and coolant is key to reducing operating costs.

In diesel engine applications, oil analysis is a critical activity to safety extend your oil drain intervals with extended service filters, like our Donaldson Endurance line of products.

Oil analysis is critical to proper system and engine performance. Oil analysis service includes:

- Performing equipment tests
- Evaluating test results
- Providing detailed reports
- Specific maintenance recommendations

Interested in Extending Your Oil Drain Intervals?



Today's vehicle and engine owners know that regular monitoring of engine oil is key to reducing operating costs. Setting up an oil analysis program is a great way to monitor the cleanliness of your current oil. This will help determine if you can safely extend your drain intervals.

Combine our Donaldson Endurance™ oil analysis, the use of premium oil and Donaldson Endurance™ premium filtration products and you'll discover how you can safely extend drain intervals and prolong your engine and equipment life.



Donaldson Endurance Kit is Ideal when looking to extend oil drain intervals. Use Kit EOA7376



Use X007374 for routine oil analysis for diesel engines or hydraulic oil reports on wear metals and additives.

Kits for Fleets and Off-Road Vehicles and Equipment

- 1- OEM Drain use Kit X007374
- 2- Drain Development use Kit EOA7376

	1	2
Metals, ppm by wt	▲	▲
Viscosity, cSt.	▲	▲
Water %	▲	▲
Fuel % by Infrared	▲	
Fuel % by GC		▲
Soot by Infrared	▲	
Soot by LEM		▲
Glycol (Coolant)	▲	▲

Recommended Sampling Intervals

On-Road Engines

Diesel	10,000 miles / oil change
Gasoline	3,000 miles / oil change
LPG	3,000 miles / oil change
Non-Engines	20,000 miles / 500 hours

Off-Road Engines

Diesel	250 hours / oil change
Gasoline	150 hours / oil change
LPG	150 hours / oil change
Non-Engines	500 hours / monthly

Coolant Test Kit

Diesel engine manufacturers also recommend routine checks of the coolant to make sure your additive packages and coolant chemistry is in balance. The coolant test strip kit tests for freeze protection as well as the concentration of your supplemental coolant additive.

Proper Diesel Engine Coolant Maintenance Requirements:

1. Donaldson coolant filters
2. Low silicate antifreeze
3. Good quality water
4. Protective coolant additive
5. Chemical concentration testing



Our coolant chemistry test (X007684) includes complete test instructions, coolant filter and supplemental coolant additive information and twelve sealed test strips.

Test Kits for Hydraulic Oil

Our basic hydraulic oil kit reports TAN (total acid number), water in PPM and ISO particle count.

Hydraulic Oil Test Kit

- 1- Basic Use Kit X007374
- 2- Correct Drain and ISO use Kit X007377

	1	2
Metals, ppm by wt	◆	◆
Viscosity, cSt.	◆	◆
Water %	◆	
TAN (Total Acid #)		◆
Water, ppm		◆
ISO Particle Count		◆



Kit X007377 for basic hydraulic oil analysis

Recommended Sampling Interval

Marine Engines

Main	250 hours / monthly
Support	150 hours / oil change
Non-Engines	500 hours / monthly

Industrial / Stationary

Diesel Engines	500 hours / monthly
Nat Gas Engines	500 hours / monthly
Gas Turbines	250 hours / monthly
Compressors	250 hours / monthly
Steam Turbines	250 hours / monthly
Geared Drives	500 hours / monthly
Bearings	500 hours / monthly
Hydraulics	500 hours / monthly


Oil Sampling Accessories

These accessories can simplify your oil analysis during the normal maintenance routines.

- plastic tubing (P176433)
- sampling pump (P176431)
- quick sampling valve (P563212)




Sampling Pump (P176431) & Plastic Tubing (sold separately in 100 ft. rolls)



Quick Sampling Metal Valve for test point. 1/8" NPT (P563212)
Working Pressure 5800 psi / 400 bar

Watch Out for Dents on Liquid Filters!



Once the steel filter canister is dented, a concentration of stress in the canister material is created, making the canister more susceptible to fatigue.

Dents May Cause Cracks

Cracked filters can be caused by dents made during improper installation of liquid filters. Filters that are dented prior to or during installation should not be used. Filters dented after installation should be replaced immediately. The cost of replacing a dented filter is much less than the cost of the damages that could result from a dented filter that fails during service.

The fatigue to filters results from the pressure pulses within the system. The pressure is regulated by a pressure regulating valve. This valve is spring operated and intermittently opens and closes to regulate the pressure. Once the pressure exceeds the setting of the spring in the regulating valve, the valve will open and relieve pressure until the spring can expand and close the valve. This function is repeated continuously during the operation of the system, creating a pulsing effect. The canister of the filters is subjected to the same pulsation. However, unlike the spring in the pressure regulating valve, the canister material is susceptible to failure after such fatigue.

Filters are designed with a low carbon steel to resist fatigue and are formed so the stress created by the pulses in the system are equalized over the surface area of the canister. A dent provides an area of stress concentration where pressure pulses can greatly shorten the fatigue life of the canister.

If you receive filters that were dented prior to your receipt, you should contact customer support at 800-374-1374 for corrective action.

More information is available through the Filter Manufacturers Council at:
<http://www.filtercouncil.org/techdata/tsbs/97-8R1.html>

Ref: Shoptalk Card F115275

They Say a Picture is Worth a Thousand Words

Here's a listing of the common installation, drain and brand icons along with its definition shown on Donaldson liquid filters.



Do Not Use Tools



Clean Filter Base



Fill With Fuel




Fill With Oil
(hydraulic or lube)




Lubricate Gasket



Hand Tighten



Complete Tightening
(will include # of turns)



FFWS –
Open, Drain, Close



Disposal / Recycle
N. America Symbol



Dispose / Recycle
Europe Symbol

More information on installation symbols can be found at the Filter Manufacturers Council at www.filtercouncil.org/uploads///docs/TSB/English/99-3R1.pdf

Watch Out for Old Compression Gaskets!



When changing any filter that has a gasket — use caution as old gaskets may stick!

A compression seal is a means of preventing migration of liquids, gases or solid contaminants across a joint or opening in an assembly or housing. A seal not only prevents the escape of fluid from inside and foreign material from entering the system from outside, but it must provide for easy installation and removal. A new gasket is critical for proper filter function.

Remember ...

- Remove used gaskets and clean the sealing area thoroughly
- Always use a new gasket with a replacement filter
- Over-tightening the filter may damage the head
- Dispose of used filters properly

More information on compression gaskets can be found at the Filter Manufacturers Council at www.filtercouncil.org/uploads///docs/TSB/English/94-4R2.pdf

Using Donaldson Fuel Filters with Biodiesel



Donaldson fuel filtration products are compatible with OEM approved grades ASTM D 6571 Biodiesel and ULSD fuels.

Biodiesel is an alternative fuel that is rapidly growing in use. However, biodiesel received a bad reputation after the problems that occurred in 2005 when some states mandated the use of B2 biodiesel blend. One of the problems was a very short fuel filter life. Further research revealed that the problems encountered were due to the use of biodiesel that did not meet ASTM D 6751 specifications. The use of biodiesel that does not meet these specifications may cause problems within a fuel system.

Filter Plugging

Filter plugging problems can be prevented by effectively cleaning storage tanks before introducing biodiesel. Filter plugging can also be minimized by using low blends of biodiesel and/or ensuring the biodiesel that you are using is from a quality source meeting the ASTM D 6751 specifications. BQ-9000® is a quality certification for biodiesel suppliers who provide quality biodiesel meeting the ASTM D 6751 specification.

Using High Blends of Biodiesel

Filters that are used in special applications using high blends of biodiesel and those near B100 or unblended B100, should use solvent resistant sealing materials. Continued use of standard sealing materials commonly found on popular fuel filters could result in deterioration or swelling of the material, which may cause leaks.

Biodiesel, n. - a fuel comprised of mono-alkyl esters of long chain fatty acids derived from vegetable oils or animal fats, designated B100, and meeting the requirements of ASTM D 6751.

Biodiesel blend, n. - a blend of biodiesel meeting ASTM D 6751 with petroleum-based diesel fuel designated BXX, where XX is the volume percent of biodiesel.

More information on ULSD or Biodiesel can be found at www.biodiesel.org

Don't Retighten a Lube Filter Once it Has Been Installed



To avoid cross-threading DO NOT OVER TIGHTEN OR RETIGHTEN a filter.

Follow These Installation Instruction for Spin-On Engine Lube Filters

The spin-on engine lube filter is a commonly serviced component on your vehicle. To insure normal oil filter service life and to prevent oil leakage or possible internal engine damage, the following procedure should be followed when replacing spin-on engine lube filters.

1. Open hood, remove the oil fill cap and place cap on air filter cover or any other flat visible surface. (This will serve as a reminder that oil has not been added to the crankcase).
2. Remove the oil drain plug(s), drain the oil and reinstall/replace the drain plug(s). If drain plug(s) has a crush ring or gasket, check for damage. If damaged, replace the ring or gasket.
3. Remove the oil filter using an oil filter wrench, if necessary.
4. Clean mounting base, making sure the old oil filter gasket is not stuck to the base. Apply a light film of clean oil to the new filter gasket. Note: Never use grease to lubricate the gasket.
5. Screw the new filter on carefully, avoiding cross-threading. On turbocharged engines, it may be necessary to fill the filter with clean engine oil prior to installation. Check engine manufacturer's recommendations. After the sealing gasket contacts the mounting base, tighten the filter per the instructions found on the filter or filter box. DO NOT OVER TIGHTEN.
6. Fill the crankcase to the recommended level with oil as per the manufacturer's specifications and install the oil fill cap. Start the engine and insure that the engine oil pressure light goes out or the oil pressure comes up to normal on the oil pressure gauge.
7. Turn off the engine and check the dipstick reading per vehicle manufacturer's instructions. Add additional oil to engine, if needed.
8. Start the engine and check for oil leakage around the oil filter and drain plug.
9. Turn off the engine and close the hood.
10. Check local, state and federal regulations for the proper disposal of your used oil and filters.

More information is available through the Filters Manufacturers Council at: www.filtercouncil.org/uploads//docs/TSB/English/93-3R1.pdf

Worried About Water in Your Air Intake System?

Sometimes you can't help operating equipment in extreme moisture environments, but it's good to know a few things to help keep your air intake system running at top efficiency.



Typical Symptoms of Water Ingestion:

- High restriction indications
- Mud caked in the VacValve
- Wet, wavy air filter media
- System rust, corrosion and/or water damage
- Moisture-related environmental problems such as icing

Simple Tips to Keep Water Out of Your System:

- Check and clear the VacValve daily
- Make sure the air cleaner cover and filter are installed properly
- Inspect air intake system for any leaks

Caution: A water-soaked air filter will occasionally lock-up a restriction indicator!

A restriction indicator's "lock-up" restriction level is generally marked on the indicator itself. To check an indicator, remove it, wipe the base clean, then apply a small amount of vacuum. If the indicator locks up, it is okay. If not, replace the indicator.



Ref: Shoptalk Card F115234

Air Intake Accessories for All Conditions Available from Donaldson

When you need to...

Mount or install an air cleaner

- Mounting Bands
- Straight Pipe

Solve air intake water problems:

- Air Ram™ Inlet Hood
- In-line Moisture Skimmer
- In-line Moisture Separator
- Stack Top Moisture Eliminator

Pre-clean or protect air inlet from debris:

- Inlet Hoods
- TopSpin Pre-Cleaner
- Full-View Pre-Cleaner
- Donaspin™
- Air Ram™ Inlet Hood
- In-line Separator

Know when to service a filter:

- Restriction indicators - go-no-go, lock-up styles, electric, in-field manometers, safety filter indicator

Aspirate (or scavenge) an intake system:

- Donaspin™
- Exhaust Ejectors
- Air Stack Extension
- Ejector Check Valve

Improve dust evacuation from Vacuator™ Valves:

- Dust Dumpa

Connect intake components:

- Rubber Elbows and Connectors
- Clamps
- Aluminum Tubing
- Rubber and Silicone Hump/Reducers
- Charge Air Connectors


Ref: Donaldson Air Cleaner Catalog F110027



Caution: Replace Damaged or Missing VacValves Immediately!

For the longest filter service life, replace damaged or missing Vacuator Valves immediately!

If your valve is cracked, torn, remains open or is missing, dust particles that are normally expelled can deposit themselves onto the filter and will shorten air filter service life. *Replace it!*




The Vacuator™ Valve, standard on the majority of Donaldson air cleaners, is an important part of the functionality of the air cleaner during the pre-cleaning stage.

The Donaldson Vacuator Valve, also known as VacValve, is made in a variety of sizes and shapes to fit various applications. The Donaldson part number is molded into each part for easy identification.

On a standard air cleaner the dust cup, where pre-cleaned dust is collected, is normally under a slight vacuum when the engine is running.

The normal engine pulsing of the vacuum causes the VacValve to open and close. This action automatically expels any collected dust and water. The VacValve also unloads when the engine is stopped.



Shoptalk

Want to Change Your Air Filter Less Often?

Switch to a Donaldson Endurance™ air filter for your on-road vehicle. It will go twice the distance – we guarantee it!



Shoptalk

Donaldson® Endurance

Features & Benefits

- Increases engine protection, extends service intervals, and reduces operating costs
- Donaldson Endurance air filters use the same filtration technology as the M1 Abrams Tank - Ultra-Web® Nanofiber Filtration Technology
- Over 35 Donaldson Endurance air filter sizes are available for popular Donaldson air cleaners
- Calculate your savings over standard filters using our worksheet at www.donaldson.com/en/engine/support/datalibrary/000827.pdf

Look for the Blue Filters!
Ultra-Web® Nanofiber Filtration Technology can be found in Donaldson Endurance™ Air Filters and Donaldson PowerCore® Air Filters

On-Road Air Filters Cross Reference

Donaldson Standard	Primary Application	Donaldson Endurance
P129396	Ford FA560, CAT 2N1990	EAFF5024
P129472	Donaldson EBA09 A/C	EAFF5025
P141228	Donaldson EBA13 A/C	EAFF5026
P141317	Navistar	EAFF5097
P142100	Donaldson EBA13 A/C	EAFF5027
P150694	Donaldson ECG11 A/C	EAFF5029
P150695	Donaldson ECG11 A/C	EAFF5047
P151028	Fram CA2550	EAFF5048
P153551	Donaldson ECG11 A/C	EAFF5053
P155842	Donaldson ECG11 A/C	EAFF5055
P181007	Donaldson EBA13 A/C	EAFF5007
P181008	Donaldson EBA15 A/C	EAFF5008
P181014	Donaldson EBA13 A/C	EAFF5014
P181015	Donaldson EBB14 OR EBG14	EAFF5015
P181016	Donaldson EBA13	EAFF5016
P181027	Donaldson EBA11	EAFF5194
P181028	Donaldson EBB12 OR EBG12 A/C	EAFF5028
P181056	Donaldson EBB14 A/C	EAFF5056
P181095	Donaldson EBB16 A/C	EAFF5095
P181096	Donaldson EBB15 A/C	EAFF5096
P181099	Donaldson EBB16 A/C	EAFF5099
P181186	Vortex VF160R	EAFF5102
P181187	Ford E3TZ9601C	EAFF5187
P181188	IHC 588213C1	EAFF5188
P181189	Ford E2HZ9601B	EAFF5189
P522293	Donaldson EBA11 A/C	EAFF5061
P522874	MCI Bus 9G-3-37	EAFF5065
P526678	Freightliner	EAFF5066
P527484	GM 15619013, Ford F3HZ9601A	EAFF5067
P527682	Donaldson EPG15" A/C, Freightliner Navistar 3560734C1	EAFF5069
P533235	Navistar 2005895C1	EAFF5104
P533930	Kenworth T2000 through 10/1998	EAFF5109
P534096	Freightliner FLB, Peterbilt 385	EAFF5106
P534816	Kenworth, Peterbilt, DCI ERA13"	EAFF5100
P534925	Kenworth, Peterbilt, DCI ERA15"	EAFF5101
P540388	Volvo 8076195	EAFF5098
P549644	Kenworth T2000 11/1998 on, Peterbilt 2100	EAFF5107
P600676	Mack 57MD46M, 57MD48M, 81SF28	EAFF5108
P771003	Mack, RVI	EAFF5074


Off-Road Air Filters Cross Reference

Donaldson Standard	Primary Application	Donaldson Endurance
P181000	Donaldson FWA14, FWG14 A/C	EAFF5000
P181001	Donaldson FWA16, FWG16 A/C	EAFF5001
P181002	Donaldson FHG16 A/C	EAFF5002
P181034	Donaldson FHG12 A/C	EAFF5034
P181035	Donaldson FWA12, FWG12 A/C	EAFF5035
P181038	Donaldson SRG20, SRG29 A/C	EAFF5038
P181039	Donaldson STG16 A/C	EAFF5039
P181040	Donaldson SRG20, SRG29 A/C	EAFF5040
P181041	Donaldson STG14 A/C	EAFF5041
P181042	Donaldson STG16 A/C	EAFF5042
P181043	Donaldson FVG14 A/C	EAFF5043
P181044	Donaldson STG12 A/C	EAFF5044
P181046	Donaldson FHG14 A/C	EAFF5046
P181057	Donaldson FWD16 OR FVG16 A/C	EAFF5057
P181049	Donaldson FVG16 A/C	EAFF5049
P532966	Donaldson FRG11" A/C	EAFF5105
P608306	Donaldson SSG A/C	EAFF5152
P609519	Donaldson SSG A/C	EAFF5153

Ref: Shoptalk Card F115202 & Brochure F111010

Efficiency Matters – See the Difference!

These dust vials show the actual amount of dust that passes through the air filter media for every 1 kilogram of dust fed to the air filter, which is equivalent to 500 hours* of equipment operation.



* Estimate based upon typical medium dust operating conditions with 92% pre-cleaner efficiency. Actual results may vary.

Donaldson Ultra-Web® nanofiber filtration technology delivers cost saving benefits:

- Superior filtration
- Long filter life with submicron contaminant
- Highest efficiency
- Ideal for extended maintenance intervals
- Longer engine life

Don't leave engine protection to chance!


Use Donaldson Endurance™ air filters with the blue Ultra-Web® nanofiber media for maximum filtration efficiency and superior dust holding capacity.

All Nanofibers are Not Created Equal

Since Donaldson Torit first introduced Ultra-Web® nanofiber cartridge filters to industrial manufacturers 25 years ago, the technology has been continually advanced and perfected in the field to perform in all ambient conditions.

ULTRA-WEB®

High Efficiency Nanofiber Filters Built to Last



In 1993 Ultra-Web nanofiber technology was introduced into engine air filters.

Ultra-Web nanofiber filtration technology strikes just the right balance between the



strength of the fiber density of the web and the level of filtration. Ultra-Web nanofibers produce a very fine, continuous fiber that form a permanent web-like net that traps dust on the surface of the filter media.

Longer Filter Life

Ultra-Web technology is proven and perfected to last at least two times longer than conventional filters. What's the secret? Ultra-Web technology keeps particulate on the surface of the media. Filtration scientists attribute surface loading of dust with lower operating pressure drop over a much longer period of time.

Ultra-Web Nanofiber Technology

www.ultrawebisalwaysbetter.com



Don't Throw Away a Good Filter Just Because it Might Look "Dirty"



Although this air filter may look "dirty" – It can go plenty more miles. Installation of a restriction indicator can save you money and time.

Why Service By Restriction?

Proper air cleaner servicing will result in maximum engine protection against the ravages of dust. Proper servicing can also save you time and money by increasing filter life and dust cleaning efficiency.

By using proper filter restriction measurement tools you will use the full life of the filter at maximum efficiency. **DON'T BE FOOLED** by filter appearance: it should look dirty.



The only way to determine when a filter is plugged or plugging is to measure the restriction on the system with the engine working at max airflow.

Two of the most common air cleaner servicing problems are:

1. Over-servicing: the least efficient time in the life of the filter is when it is new. Filter elements increase in efficiency as dust builds up on the media.
2. Improper servicing: your engine is highly vulnerable to abrasive dust contaminants during the servicing process when the filter is removed from the housing. A leading cause of engine damage is due to careless servicing procedures.

Choose Restriction Measurement Tools that Best Fit Your Applications

Donaldson offers a variety of restriction measuring devices that help you get maximum filter utilization. All measure restriction in inches of water vacuum. All are resistant to vibration, breakage, weather, corrosion, dust and dirt to assure reliable filter restriction readings.



Continuous Reading devices show how much life is left in the filter:

- The Informer™
- Service Gauge for Instrument Panel

Go/No-Go restriction readings on heavy-duty vehicles:


- ServiSignal™
- Visual Restriction Indicator
- Electrical Indicator
- SafetySignal™ for safety filters

In-Field restriction readings on light and medium-duty vehicles:

- In-Field Service Gauge Kit

Ref: Shoptalk Card F115236 & Air Cleaner Catalog F110027

Keep Those ECG Konepac™ Air Cleaner Latches Inspected



ECG style air cleaners have three cover latches that need to perform correctly to ensure the element gasket is sealing properly. These latches should be checked for tightness and wear. To check for tightness, close all three latches, then open and close them one at a time. There should be good tension and should snap tightly when closed. If any latches seem loose or rattle, they should be replaced.



The spring clip and pin repair kit is X009291 and fits all ECG style air cleaners.



The most obvious place to check for wear is the spring latch tip (the part that hooks into the notch on the filter cover). The tip may become sharp and cut into the filter cover with extended wear. The tip may also wear to the point where it will not hook onto the filter cover at all. If any of these conditions are evident, the latch should be replaced.

Dust Dumpa Solves Dust Expulsion Issues in High Dust Environments

Ideally suited to equipment operating in mining, construction and quarrying. The Dust Dumpa reduces maintenance and saves you time and money.

- Improves dust evacuation from the air cleaner
- Clear tube allows for visual inspection of dust collection. Operations can perform walk around air cleaner inspection which saves time.
- Improves safety of the air cleaner inspection process by eliminating the need for ladders or elevated platforms for daily inspections
- Keeps operators and maintenance personnel away from the nuisance dust normally encountered during air cleaner servicing operations.
- Improves vehicle up time by minimizing pre/post-shift air cleaner inspections, thus facilitating increased air cleaner service intervals.
- Ships fully assembled
- Proper conversion requires drop down tube for every dust cup



Part No. X006562
(includes dust cup seal)

Dust Dumpa



Part No. X006561

When the Dust Dumpa kit (X006562) is installed on the dust cups on the lower assembly of a Donaldson S Series air cleaner, the rubber connector vibrates during normal vehicle operation and gravity expels the pre-cleaned dust.

The Dust Dumpa kit, X006561 (without the dust cup), is an add on to newer Donaldson air cleaners models including our PowerCore® PSD 10" and 12" and SSG Series.

For more information, see the intake accessories section of our air cleaner catalog or contact your local Donaldson distributor.

What's Donaldson's Position Air Filter Cleaning & Reuse?

Donaldson recommends servicing air filters by monitoring the air flow restriction levels in the intake system. DO NOT clean and reuse Donaldson filters.

Some vehicle owners and maintenance supervisors, concerned with lowering their operating costs, will clean and reuse their heavy-duty air filters. Before you decide whether cleaning or washing of air filters is appropriate for your vehicle or fleet, please consider these factors:

- Heavy-duty air filtration manufacturers do not recommend any type of cleaning process be used on their products. Donaldson, like other heavy duty air filter manufacturers, does not warrant the air filter once it has been cleaned.
- Filter dirt holding capacity is reduced 20-40% with each cleaning.
- Rather than cleaning or reusing filters, consider upgrading to an extended service filter and service the filter by restriction.
- There is a risk of dirt reaching the clean side of the filter while cleaning, plus possible filter damage from high pressure water or compressed air, makes cleaning or washing a gamble. Add the cost of cleaning to the danger of filter damage when determining the risk versus the value of filter cleaning process.
- Damaged filters should not be cleaned or reused. If a filter is damaged in service, investigate the source of damage and make corrections to avoid future damage.
- Reusing a cleaned heavy duty filter increases the likelihood of improper air cleaner servicing because of the shortened service life. Each time the air intake system is serviced, it is exposed to the chance of contamination.
- Never attempt to clean a safety filter. Replace it after three primary filter services.




How Big is a Micron?

Micron Sizes of Familiar Particles

Grain of table salt	100µm
Human hair	80µm
Lower limit of visibility	40µm
White blood cell	25µm
Talcum powder	10µm
Red blood cell	8µm
Bacteria	2µm
Silt	<5µm

How Big is a Micron?



Minimize Water in Hydraulic Systems

Water has a way of sneaking into hydraulic circuits and that means trouble.

Donaldson T.R.A.P. breathers actually exhale the moisture back out, which means you won't need to change the breather due to water saturation ... unlike desiccant filters that require frequent change-out.

Like the name suggests, it TRAPS water before it gets in, yet doesn't restrict air flow, and lets your hydraulic reservoir breathe.

Features and Benefits

- Minimize water in your system - T.R.A.P. breather strips moisture from the incoming air, allowing only dry air to enter the hydraulic circuits
- Maximize system uptime - Patented T.R.A.P. media regenerates its water holding capacity for longer service life
- Hydraulic reservoir can breathe - The T.R.A.P. doesn't restrict air flow



T.R.A.P. Parts Table

Connection	Max. Flow CFM	Material	Part No.	Indicator Style*
1" NPT	45 cfm	Glass-filled ABS	P566151	Opt'l Mechanical
1" NPT	45 cfm	Glass-filled ABS	P564669	Electronic
3/4" BSP	25 cfm	Epoxy coated steel	P566037	No
3/4" NPT	25 cfm	Epoxy coated steel	P565857	Opt'l Mechanical
Bayonet	25 cfm	Epoxy coated steel	P565858	No
Bayonet	45 cfm	Glass-filled ABS	P566156	No
Bayonet	45 cfm	Glass-filled ABS	P565616	Electronic

Mechanical Indicator Kit - P566168

Install kit between reservoir and T.R.A.P. breather. Lock-up style indicator with manual reset. Highly visible, bright red band shows when restriction limit is reached. Indicator setting, 20" H₂O.

Ref: Brochure F111221

Understanding the Beta Rating System

This information is provided as an aid to understanding fluid filter efficiency terminology based on current ISO, ANSI and NFPA test standards. It is not proprietary and may be reproduced or distributed in any manner for educational purposes.

What Is Beta Ratio?

Beta ratio (symbolized by β) is a formula used to calculate the filtration efficiency of a particular fluid filter using base data obtained from multi-pass testing.

In a multi-pass test, fluid is continuously injected with a uniform amount of contaminant (i.e., ISO medium test dust) then pumped through the filter unit being tested. Filter efficiency is determined by monitoring oil contamination levels upstream and downstream of the test filter at specific times. An automatic particle counter is used to determine the contamination level. Through this process an upstream to downstream particle count ratio is developed, known as the beta ratio.

The formula used to calculate the beta ratio is:

$$\text{Beta ratio}_{(x)} = \frac{\text{particle count in upstream oil}}{\text{particle count in downstream oil}}$$

where (x) is a given particle size

Indicates that testing was done with APC's calibrated with NIST fluid

$$\beta_{10(c)} = 1000$$

1000 times more particles upstream than downstream that are 10 μm and larger

Compatibility of Donaldson Filter Media with Hydraulic Fluids

While Donaldson has developed many formulations of media, they can be divided into two broad categories: natural fibers, usually cellulose, and synthetic or man-made fibers.

Fluid to be Filtered	Recommended Media
Petroleum-based	Synteq Cellulose
Phosphate Ester Diester	Synteq
Water Glycol	Synteq
Water-Oil Emulsion	Synteq
Biodegradable Fluid	Synteq
HWCF (high water content fluids)	Synteq
Coarse Filtration	Wire Mesh

A Note on Seals

- Filters with seals made of BunaN are appropriate for most applications involving petroleum oil and some high water content fluids. Filters with seals made of Viton® or Fluorel® (both fluoroelastomers) are required when using diesters, phosphate ester fluids. Donaldson offers both types. (Viton® is a registered trademark of DuPont Dow Elastomers, and Fluorel® is a registered trademark of 3M Company.)
- In Donaldson filters with fluorocarbon elastomer seals, epoxy potting is used to accommodate higher temperature environments and for compatibility with fluids such as phosphate ester and high water based fluids. The plastisol (heat cured) and urethane (self curing) potting materials used in other filters perform well with petroleum-based fluids.

Engine Liquid Filter Kits – Everything You Need in One Package!



For fleet owners that perform their own vehicle maintenance, our 'all-in-one' packaged engine liquid kit can simplify service, ordering and storage.

Features:

- Hundreds of pre-assembled engine filter kits to choose from
- Kits for popular engines and equipment
- Order just one part number instead of many
- Standard or extended service product kits available

Benefits:

- Simplified service and maintenance for popular engine and equipment brands
- Save on inventory and shelf space
- We make it easy by doing all the application and product searching for you



NOTE regarding kits that contain coolant filters:
The coolant products we sell are considered a Class 5 hazardous product (in the U.S.). Because of this classification, there are restrictions on shipping these products using small package carriers.

Engine Liquid Filter Kits

Carrier	32
Caterpillar	32
Cummins	32
Detroit Diesel	33
Mack	34
Mercedes	35
Moffett Engineering	35
Navistar	35
Sterling/Mercedes	35
Thermo King	35
Volvo	35

Carrier		Kit No: P559513	Cummins	
Kit No: P559559	Primary App: CARRIER	Primary App: CATERPILLAR ENGINES	Kit No: P559023	Primary App: CUMMINS ENGINES
Kit Contents Qty Description		Kit Contents Qty Description	Kit Contents Qty Description	
P550463 1 FUEL/WATER SEPARATOR CARTRIDGE		P550105 1 FUEL/WATER SEPARATOR SPIN-ON	P554071 1 COOLANT SPIN-ON	
P551712 1 FUEL/WATER SEPARATOR SPIN-ON		P555823 1 FUEL/WATER SEPARATOR SPIN-ON	P550105 1 FUEL/WATER SEPARATOR SPIN-ON	
P554005 1 LUBE SPIN-ON FULL FLOW		ELF7405 1 LUBE SPIN-ON FULL FLOW	P550777 1 LUBE SPIN-ON BYPASS	
			P551670 1 LUBE SPIN-ON FULL FLOW	
Kit No: P559615	Primary App: CARRIER REFRIGERATION UNITS	Kit No: P559578	Kit No: P559037	Primary App: CUMMINS ENGINES
Kit Contents Qty Description		Primary App: CATERPILLAR ENGINES	Kit Contents Qty Description	
P550453 1 LUBE CARTRIDGE		Kit Contents Qty Description	P554071 1 COOLANT SPIN-ON	
P550050 1 LUBE SPIN-ON BYPASS		P551712 1 FUEL/WATER SEPARATOR SPIN-ON	P550105 1 FUEL/WATER SEPARATOR SPIN-ON	
P554407 1 LUBE SPIN-ON FULL FLOW		P556915 1 FUEL/WATER SEPARATOR SPIN-ON	P553000 1 LUBE SPIN-ON COMBINATION	
		P554005 1 LUBE SPIN-ON FULL FLOW		
			Kit No: P559238	Primary App: CUMMINS ENGINES
Kit No: P559019	Primary App: CATERPILLAR ENGINES	Kit No: P559579	Kit Contents Qty Description	
Kit Contents Qty Description		Primary App: CATERPILLAR ENGINES	P553004 1 FUEL SPIN ON	
P554071 1 COOLANT SPIN-ON		Kit Contents Qty Description	P551329 1 FUEL/WATER SEPARATOR SPIN-ON	
P555823 1 FUEL/WATER SEPARATOR SPIN-ON		P552071 1 COOLANT SPIN-ON	P558615 1 LUBE SPIN-ON FULL FLOW	
P554005 1 LUBE SPIN-ON FULL FLOW		P551712 1 FUEL/WATER SEPARATOR SPIN-ON		
		P556915 1 FUEL/WATER SEPARATOR SPIN-ON	Kit No: P559303	Primary App: CUMMINS ENGINES
		P558000 1 FUEL/WATER SEPARATOR SPIN-ON	Kit Contents Qty Description	
		P554005 1 LUBE SPIN-ON FULL FLOW	P552071 1 COOLANT SPIN-ON	
			P551000 1 FUEL/WATER SEPARATOR SPIN-ON	
Kit No: P559027	Primary App: CATERPILLAR ENGINES	Kit No: P559582	P553000 1 LUBE SPIN-ON COMBINATION	
Kit Contents Qty Description		Primary App: CATERPILLAR ENGINES		
P550105 1 FUEL/WATER SEPARATOR SPIN-ON		Kit Contents Qty Description		
P555823 1 FUEL/WATER SEPARATOR SPIN-ON		P552071 1 COOLANT SPIN-ON		
P554005 1 LUBE SPIN-ON FULL FLOW		P550447 1 FUEL/WATER SEPARATOR CARTRIDGE		
		P555823 1 FUEL/WATER SEPARATOR SPIN-ON		
		P554005 1 LUBE SPIN-ON FULL FLOW		
			Kit No: P559411	Primary App: CUMMINS ENGINES
Kit No: P559088	Primary App: CATERPILLAR ENGINES	Kit No: P559586	Kit Contents Qty Description	
Kit Contents Qty Description		Primary App: CATERPILLAR ENGINES	P550440 1 FUEL SPIN-ON SECONDARY	
P554071 1 COOLANT SPIN-ON		Kit Contents Qty Description	P551329 1 FUEL/WATER SEPARATOR SPIN-ON	
P555823 1 FUEL/WATER SEPARATOR SPIN-ON		P551311 1 FUEL SPIN ON	P558615 1 LUBE SPIN-ON FULL FLOW	
P556915 1 FUEL/WATER SEPARATOR SPIN-ON		P551000 1 FUEL/WATER SEPARATOR SPIN-ON		
P554005 1 LUBE SPIN-ON FULL FLOW		P554005 1 LUBE SPIN-ON FULL FLOW		
			Kit No: P559468	Primary App: CUMMINS ENGINES
Kit No: P559097	Primary App: CATERPILLAR ENGINES	Kit No: P559606	Kit Contents Qty Description	
Kit Contents Qty Description		Primary App: CATERPILLAR ENGINES	P551000 1 FUEL/WATER SEPARATOR SPIN-ON	
P555823 1 FUEL/WATER SEPARATOR SPIN-ON		Kit Contents Qty Description	P553000 1 LUBE SPIN-ON COMBINATION	
P558000 1 FUEL/WATER SEPARATOR SPIN-ON		P551311 1 FUEL SPIN ON		
P554005 1 LUBE SPIN-ON FULL FLOW		P551746 1 FUEL/WATER SEPARATOR SPIN-ON		
		P550777 1 LUBE SPIN-ON BYPASS		
		P554005 1 LUBE SPIN-ON FULL FLOW		
			Kit No: P559562	Primary App: CUMMINS ENGINES
Kit No: P559288	Primary App: CATERPILLAR ENGINES	Kit No: P559619	Kit Contents Qty Description	
Kit Contents Qty Description		Primary App: CATERPILLAR ENGINES	P552071 1 COOLANT SPIN-ON	
P554071 1 COOLANT SPIN-ON		Kit Contents Qty Description	P551000 1 FUEL/WATER SEPARATOR SPIN-ON	
P551712 1 FUEL/WATER SEPARATOR SPIN-ON		P554685 1 COOLANT SPIN-ON	P559000 1 LUBE SPIN-ON COMBINATION	
P554005 1 LUBE SPIN-ON FULL FLOW		P551712 1 FUEL/WATER SEPARATOR SPIN-ON		
		P550105 1 FUEL/WATER SEPARATOR SPIN-ON		
		P554005 1 LUBE SPIN-ON FULL FLOW		
			Kit No: P559577	Primary App: CUMMINS ENGINES
Kit No: P559410	Primary App: CATERPILLAR ENGINES	Kit No: P559629	Kit Contents Qty Description	
Kit Contents Qty Description		Primary App: CATERPILLAR ENGINES	P554685 1 COOLANT SPIN-ON	
P554071 1 COOLANT SPIN-ON		Kit Contents Qty Description	P551000 1 FUEL/WATER SEPARATOR SPIN-ON	
P550105 1 FUEL/WATER SEPARATOR SPIN-ON		P551311 1 FUEL SPIN ON	P553000 1 LUBE SPIN-ON COMBINATION	
P555823 1 FUEL/WATER SEPARATOR SPIN-ON		P550796 1 FUEL/WATER SEPARATOR CARTRIDGE		
P554105 1 LUBE SPIN-ON FULL FLOW		P554005 1 LUBE SPIN-ON FULL FLOW		
			Kit No: P559581	Primary App: CUMMINS ENGINES
Kit No: P559480	Primary App: CATERPILLAR ENGINES	Kit No: P559635	Kit Contents Qty Description	
Kit Contents Qty Description		Primary App: CATERPILLAR ENGINES	P552071 1 COOLANT SPIN-ON	
P557440 1 FUEL SPIN ON		Kit Contents Qty Description	P550447 1 FUEL/WATER SEPARATOR CARTRIDGE	
P555823 1 FUEL/WATER SEPARATOR SPIN-ON		P551311 1 FUEL SPIN ON	P559000 1 LUBE SPIN-ON COMBINATION	
P554005 1 LUBE SPIN-ON FULL FLOW		P550202 1 FUEL/WATER SEPARATOR SPIN-ON		
		ELF7405 1 LUBE SPIN-ON FULL FLOW		

Kit No:	P559583
Primary App:	CUMMINS ENGINES
Kit Contents	Qty Description
P552071	1 COOLANT SPIN-ON
P550447	1 FUEL/WATER SEPARATOR CARTRIDGE
P551122	1 FUEL/WATER SEPARATOR SPIN-ON
P553000	1 LUBE SPIN-ON COMBINATION

Kit No:	P559589
Primary App:	CUMMINS ENGINES
Kit Contents	Qty Description
P552071	1 COOLANT SPIN-ON
P550467	1 FUEL/WATER SEPARATOR CARTRIDGE
P559000	1 LUBE SPIN-ON COMBINATION

Kit No:	P559595
Primary App:	CUMMINS ENGINES
Kit Contents	Qty Description
P552071	1 COOLANT SPIN-ON
P550463	1 FUEL/WATER SEPARATOR CARTRIDGE
P559000	1 LUBE SPIN-ON COMBINATION

Kit No:	P559597
Primary App:	CUMMINS ENGINES
Kit Contents	Qty Description
P550585	1 COOLANT SPIN-ON
P552200	1 FUEL SPIN-ON SECONDARY
P550106	1 FUEL/WATER SEPARATOR SPIN-ON
P559000	1 LUBE SPIN-ON COMBINATION

Kit No:	P559599
Primary App:	CUMMINS ENGINES
Kit Contents	Qty Description
P552074	1 COOLANT SPIN-ON
P558000	2 FUEL/WATER SEPARATOR SPIN-ON
P553000	2 LUBE SPIN-ON COMBINATION

Kit No:	P559600
Primary App:	CUMMINS ENGINES
Kit Contents	Qty Description
P552200	1 FUEL SPIN-ON SECONDARY
P552203	1 FUEL/WATER SEPARATOR SPIN-ON
P559000	1 LUBE SPIN-ON COMBINATION

Kit No:	P559609
Primary App:	CUMMINS ENGINES
Kit Contents	Qty Description
P552071	1 COOLANT SPIN-ON
P552200	1 FUEL SPIN-ON SECONDARY
P552203	1 FUEL/WATER SEPARATOR SPIN-ON
P559000	1 LUBE SPIN-ON COMBINATION

Kit No:	P559611
Primary App:	CUMMINS ENGINES
Kit Contents	Qty Description
P552071	1 COOLANT SPIN-ON
P550447	1 FUEL/WATER SEPARATOR CARTRIDGE
P551000	1 FUEL/WATER SEPARATOR SPIN-ON
P553000	1 LUBE SPIN-ON COMBINATION

Kit No:	P559612
Primary App:	CUMMINS ENGINES
Kit Contents	Qty Description
P552200	1 FUEL SPIN-ON SECONDARY
P550463	1 FUEL/WATER SEPARATOR CARTRIDGE
ELF7900	1 LUBE SPIN-ON FULL FLOW

Kit No:	P559617
Primary App:	CUMMINS ENGINES
Kit Contents	Qty Description
P550737	1 FUEL/WATER SEPARATOR CARTRIDGE
P559000	1 LUBE SPIN-ON COMBINATION

Kit No:	P559622
Primary App:	CUMMINS ENGINES
Kit Contents	Qty Description
P552126	1 COOLANT SPIN-ON
P552200	1 FUEL SPIN-ON SECONDARY
P550106	1 FUEL/WATER SEPARATOR SPIN-ON
P559000	1 LUBE SPIN-ON COMBINATION

Kit No:	P559636
Primary App:	CUMMINS ENGINES
Kit Contents	Qty Description
P552200	1 FUEL SPIN-ON SECONDARY
P552203	1 FUEL/WATER SEPARATOR SPIN-ON
ELF7900	1 LUBE SPIN-ON FULL FLOW

Kit No:	P559639
Primary App:	CUMMINS ENGINES
Kit Contents	Qty Description
P550585	1 COOLANT SPIN-ON
P552200	1 FUEL SPIN-ON SECONDARY
P552203	1 FUEL/WATER SEPARATOR SPIN-ON
P559000	1 LUBE SPIN-ON COMBINATION

Detroit Diesel

Kit No:	P559008
Primary App:	DETROIT DIESEL ENGINES
Kit Contents	Qty Description
P556916	1 FUEL SPIN-ON SECONDARY
P556915	1 FUEL/WATER SEPARATOR SPIN-ON
P551670	1 LUBE SPIN-ON FULL FLOW

Kit No:	P559101
Primary App:	DETROIT DIESEL ENGINES
Kit Contents	Qty Description
P556916	1 FUEL SPIN-ON SECONDARY
P556915	1 FUEL/WATER SEPARATOR SPIN-ON
ELF3998	2 LUBE SPIN-ON FULL FLOW

Kit No:	P559102
Primary App:	DETROIT DIESEL ENGINES
Kit Contents	Qty Description
P550467	1 FUEL/WATER SEPARATOR CARTRIDGE
P552100	2 LUBE SPIN-ON FULL FLOW

Kit No:	P559246
Primary App:	DETROIT DIESEL ENGINES
Kit Contents	Qty Description
P554071	1 COOLANT SPIN-ON
P556916	1 FUEL SPIN-ON SECONDARY
P558010	1 FUEL/WATER SEPARATOR SPIN-ON
P552100	2 LUBE SPIN-ON FULL FLOW

Kit No:	P559248
Primary App:	DETROIT DIESEL ENGINES
Kit Contents	Qty Description
P556916	1 FUEL SPIN-ON SECONDARY
P558010	1 FUEL/WATER SEPARATOR SPIN-ON
P552100	2 LUBE SPIN-ON FULL FLOW

Kit No:	P559250
Primary App:	DETROIT DIESEL ENGINES
Kit Contents	Qty Description
P556916	1 FUEL SPIN-ON SECONDARY
P558000	1 FUEL/WATER SEPARATOR SPIN-ON
P552100	2 LUBE SPIN-ON FULL FLOW

Kit No:	P559251
Primary App:	DETROIT DIESEL ENGINES
Kit Contents	Qty Description
P556916	1 FUEL SPIN-ON SECONDARY
P556915	1 FUEL/WATER SEPARATOR SPIN-ON
P552100	2 LUBE SPIN-ON FULL FLOW

Kit No:	P559299
Primary App:	DETROIT DIESEL ENGINES
Kit Contents	Qty Description
P554071	1 COOLANT SPIN-ON
P556916	1 FUEL SPIN-ON SECONDARY
P556915	1 FUEL/WATER SEPARATOR SPIN-ON
P552100	2 LUBE SPIN-ON FULL FLOW

Kit No:	P559466
Primary App:	DETROIT DIESEL ENGINES
Kit Contents	Qty Description
P552071	1 COOLANT SPIN-ON
P556916	1 FUEL SPIN-ON SECONDARY
P556915	1 FUEL/WATER SEPARATOR SPIN-ON
P552100	2 LUBE SPIN-ON FULL FLOW

Kit No:	P559593
Primary App:	DETROIT DIESEL ENGINES
Kit Contents	Qty Description
P554071	1 COOLANT SPIN-ON
P556916	1 FUEL SPIN-ON SECONDARY
P550730	1 FUEL/WATER SEPARATOR SPIN-ON
P552100	2 LUBE SPIN-ON FULL FLOW

Kit No:	P559601
Primary App:	DETROIT DIESEL ENGINES
Kit Contents	Qty Description
P556917	1 FUEL SPIN-ON SECONDARY
P558010	1 FUEL/WATER SEPARATOR SPIN-ON
ELF3998	2 LUBE SPIN-ON FULL FLOW

Kit No:	P559618
Primary App:	DETROIT DIESEL ENGINES
Kit Contents	Qty Description
P554685	1 COOLANT SPIN-ON
P550463	1 FUEL/WATER SEPARATOR CARTRIDGE
P552100	2 LUBE SPIN-ON FULL FLOW

Kit No:	P559620
Primary App:	DETROIT DIESEL ENGINES
Kit Contents	Qty Description
P554685	1 COOLANT SPIN-ON
P556916	1 FUEL SPIN-ON SECONDARY
P556915	1 FUEL/WATER SEPARATOR SPIN-ON
P552100	2 LUBE SPIN-ON FULL FLOW

Kit No:	P559637
Primary App:	DETROIT DIESEL ENGINES
Kit Contents	Qty Description
P550467	1 FUEL/WATER SEPARATOR CARTRIDGE
ELF3998	2 LUBE SPIN-ON FULL FLOW

<p>Kit No: P559474</p> <p>Primary App: DETROIT DIESEL SERIES 60 ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR CARTRIDGE</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	FUEL/WATER SEPARATOR CARTRIDGE	2	LUBE SPIN-ON FULL FLOW	<p>Kit No: P559002</p> <p>Primary App: MACK ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>FUEL SPIN-ON SECONDARY</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	FUEL SPIN-ON SECONDARY	1	FUEL/WATER SEPARATOR SPIN-ON	2	LUBE SPIN-ON FULL FLOW	<p>Kit No: P559608</p> <p>Primary App: MACK ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>FUEL SPIN-ON SECONDARY</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	FUEL SPIN-ON SECONDARY	1	FUEL/WATER SEPARATOR SPIN-ON	2	LUBE SPIN-ON FULL FLOW												
Qty	Description																																			
1	FUEL/WATER SEPARATOR CARTRIDGE																																			
2	LUBE SPIN-ON FULL FLOW																																			
Qty	Description																																			
1	FUEL SPIN-ON SECONDARY																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
2	LUBE SPIN-ON FULL FLOW																																			
Qty	Description																																			
1	FUEL SPIN-ON SECONDARY																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
2	LUBE SPIN-ON FULL FLOW																																			
Mack																																				
<p>Kit No: P559603</p> <p>Primary App: MACK</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR CARTRIDGE</td> </tr> <tr> <td>1</td> <td>LUBE CARTRIDGE</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	FUEL/WATER SEPARATOR CARTRIDGE	1	LUBE CARTRIDGE	2	LUBE SPIN-ON FULL FLOW	<p>Kit No: P559003</p> <p>Primary App: MACK ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>COOLANT SPIN-ON</td> </tr> <tr> <td>1</td> <td>FUEL SPIN-ON SECONDARY</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>3</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	COOLANT SPIN-ON	1	FUEL SPIN-ON SECONDARY	1	FUEL/WATER SEPARATOR SPIN-ON	3	LUBE SPIN-ON FULL FLOW	<p>Kit No: P559613</p> <p>Primary App: MACK ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>1</td> <td>LUBE CARTRIDGE</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	FUEL/WATER SEPARATOR SPIN-ON	1	FUEL/WATER SEPARATOR SPIN-ON	1	LUBE CARTRIDGE	2	LUBE SPIN-ON FULL FLOW						
Qty	Description																																			
1	FUEL/WATER SEPARATOR CARTRIDGE																																			
1	LUBE CARTRIDGE																																			
2	LUBE SPIN-ON FULL FLOW																																			
Qty	Description																																			
1	COOLANT SPIN-ON																																			
1	FUEL SPIN-ON SECONDARY																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
3	LUBE SPIN-ON FULL FLOW																																			
Qty	Description																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
1	LUBE CARTRIDGE																																			
2	LUBE SPIN-ON FULL FLOW																																			
<p>Kit No: P559031</p> <p>Primary App: MACK E7 ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>COOLANT SPIN-ON</td> </tr> <tr> <td>1</td> <td>FUEL SPIN-ON SECONDARY</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>1</td> <td>LUBE CARTRIDGE</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	COOLANT SPIN-ON	1	FUEL SPIN-ON SECONDARY	1	FUEL/WATER SEPARATOR SPIN-ON	1	LUBE CARTRIDGE	2	LUBE SPIN-ON FULL FLOW	<p>Kit No: P559222</p> <p>Primary App: MACK ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>FUEL SPIN-ON SECONDARY</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>1</td> <td>LUBE CARTRIDGE</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	FUEL SPIN-ON SECONDARY	1	FUEL/WATER SEPARATOR SPIN-ON	1	LUBE CARTRIDGE	2	LUBE SPIN-ON FULL FLOW	<p>Kit No: P559614</p> <p>Primary App: MACK ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>FUEL SPIN-ON SECONDARY</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>1</td> <td>LUBE CARTRIDGE</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	FUEL SPIN-ON SECONDARY	1	FUEL/WATER SEPARATOR SPIN-ON	1	LUBE CARTRIDGE	2	LUBE SPIN-ON FULL FLOW		
Qty	Description																																			
1	COOLANT SPIN-ON																																			
1	FUEL SPIN-ON SECONDARY																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
1	LUBE CARTRIDGE																																			
2	LUBE SPIN-ON FULL FLOW																																			
Qty	Description																																			
1	FUEL SPIN-ON SECONDARY																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
1	LUBE CARTRIDGE																																			
2	LUBE SPIN-ON FULL FLOW																																			
Qty	Description																																			
1	FUEL SPIN-ON SECONDARY																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
1	LUBE CARTRIDGE																																			
2	LUBE SPIN-ON FULL FLOW																																			
<p>Kit No: P559051</p> <p>Primary App: MACK E7 ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>COOLANT SPIN-ON</td> </tr> <tr> <td>1</td> <td>FUEL SPIN-ON SECONDARY</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>1</td> <td>LUBE CARTRIDGE</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	COOLANT SPIN-ON	1	FUEL SPIN-ON SECONDARY	1	FUEL/WATER SEPARATOR SPIN-ON	1	LUBE CARTRIDGE	2	LUBE SPIN-ON FULL FLOW	<p>Kit No: P559252</p> <p>Primary App: MACK ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>COOLANT SPIN-ON</td> </tr> <tr> <td>1</td> <td>FUEL SPIN-ON SECONDARY</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	COOLANT SPIN-ON	1	FUEL SPIN-ON SECONDARY	1	FUEL/WATER SEPARATOR SPIN-ON	2	LUBE SPIN-ON FULL FLOW	<p>Kit No: P559623</p> <p>Primary App: MACK ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>COOLANT SPIN-ON</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR CARTRIDGE</td> </tr> <tr> <td>1</td> <td>LUBE CARTRIDGE</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	COOLANT SPIN-ON	1	FUEL/WATER SEPARATOR CARTRIDGE	1	LUBE CARTRIDGE	2	LUBE SPIN-ON FULL FLOW		
Qty	Description																																			
1	COOLANT SPIN-ON																																			
1	FUEL SPIN-ON SECONDARY																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
1	LUBE CARTRIDGE																																			
2	LUBE SPIN-ON FULL FLOW																																			
Qty	Description																																			
1	COOLANT SPIN-ON																																			
1	FUEL SPIN-ON SECONDARY																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
2	LUBE SPIN-ON FULL FLOW																																			
Qty	Description																																			
1	COOLANT SPIN-ON																																			
1	FUEL/WATER SEPARATOR CARTRIDGE																																			
1	LUBE CARTRIDGE																																			
2	LUBE SPIN-ON FULL FLOW																																			
<p>Kit No: P559069</p> <p>Primary App: MACK E7 ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>COOLANT SPIN-ON</td> </tr> <tr> <td>1</td> <td>FUEL SPIN-ON SECONDARY</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>1</td> <td>LUBE CARTRIDGE</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	COOLANT SPIN-ON	1	FUEL SPIN-ON SECONDARY	1	FUEL/WATER SEPARATOR SPIN-ON	1	LUBE CARTRIDGE	2	LUBE SPIN-ON FULL FLOW	<p>Kit No: P559567</p> <p>Primary App: MACK ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>FUEL SPIN-ON SECONDARY</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>1</td> <td>LUBE CARTRIDGE</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	FUEL SPIN-ON SECONDARY	1	FUEL/WATER SEPARATOR SPIN-ON	1	LUBE CARTRIDGE	2	LUBE SPIN-ON FULL FLOW	<p>Kit No: P559625</p> <p>Primary App: MACK ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>1</td> <td>LUBE CARTRIDGE</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	FUEL/WATER SEPARATOR SPIN-ON	1	FUEL/WATER SEPARATOR SPIN-ON	1	LUBE CARTRIDGE	2	LUBE SPIN-ON FULL FLOW		
Qty	Description																																			
1	COOLANT SPIN-ON																																			
1	FUEL SPIN-ON SECONDARY																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
1	LUBE CARTRIDGE																																			
2	LUBE SPIN-ON FULL FLOW																																			
Qty	Description																																			
1	FUEL SPIN-ON SECONDARY																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
1	LUBE CARTRIDGE																																			
2	LUBE SPIN-ON FULL FLOW																																			
Qty	Description																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
1	LUBE CARTRIDGE																																			
2	LUBE SPIN-ON FULL FLOW																																			
<p>Kit No: P559546</p> <p>Primary App: MACK E7 ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>FUEL SPIN-ON SECONDARY</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>1</td> <td>LUBE CARTRIDGE</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	FUEL SPIN-ON SECONDARY	1	FUEL/WATER SEPARATOR SPIN-ON	1	LUBE CARTRIDGE	2	LUBE SPIN-ON FULL FLOW	<p>Kit No: P559584</p> <p>Primary App: MACK ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>COOLANT SPIN-ON</td> </tr> <tr> <td>1</td> <td>FUEL SPIN-ON SECONDARY</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>1</td> <td>LUBE CARTRIDGE</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	COOLANT SPIN-ON	1	FUEL SPIN-ON SECONDARY	1	FUEL/WATER SEPARATOR SPIN-ON	1	LUBE CARTRIDGE	2	LUBE SPIN-ON FULL FLOW	<p>Kit No: P559630</p> <p>Primary App: MACK ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>COOLANT SPIN-ON</td> </tr> <tr> <td>1</td> <td>FUEL SPIN-ON SECONDARY</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>1</td> <td>LUBE CARTRIDGE</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	COOLANT SPIN-ON	1	FUEL SPIN-ON SECONDARY	1	FUEL/WATER SEPARATOR SPIN-ON	1	LUBE CARTRIDGE	2	LUBE SPIN-ON FULL FLOW
Qty	Description																																			
1	FUEL SPIN-ON SECONDARY																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
1	LUBE CARTRIDGE																																			
2	LUBE SPIN-ON FULL FLOW																																			
Qty	Description																																			
1	COOLANT SPIN-ON																																			
1	FUEL SPIN-ON SECONDARY																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
1	LUBE CARTRIDGE																																			
2	LUBE SPIN-ON FULL FLOW																																			
Qty	Description																																			
1	COOLANT SPIN-ON																																			
1	FUEL SPIN-ON SECONDARY																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
1	LUBE CARTRIDGE																																			
2	LUBE SPIN-ON FULL FLOW																																			
<p>Kit No: P559547</p> <p>Primary App: MACK E7 ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>COOLANT SPIN-ON</td> </tr> <tr> <td>1</td> <td>FUEL SPIN-ON SECONDARY</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>1</td> <td>LUBE CARTRIDGE</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	COOLANT SPIN-ON	1	FUEL SPIN-ON SECONDARY	1	FUEL/WATER SEPARATOR SPIN-ON	1	LUBE CARTRIDGE	2	LUBE SPIN-ON FULL FLOW	<p>Kit No: P559587</p> <p>Primary App: MACK ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>COOLANT SPIN-ON</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>1</td> <td>LUBE CARTRIDGE</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	COOLANT SPIN-ON	1	FUEL/WATER SEPARATOR SPIN-ON	1	LUBE CARTRIDGE	2	LUBE SPIN-ON FULL FLOW	<p style="text-align: center;">Mercedes</p> <p>Kit No: P559585</p> <p>Primary App: MERCEDES ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>FUEL CARTRIDGE</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR CARTRIDGE</td> </tr> <tr> <td>1</td> <td>LUBE CARTRIDGE FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	FUEL CARTRIDGE	1	FUEL/WATER SEPARATOR CARTRIDGE	1	LUBE CARTRIDGE FULL FLOW				
Qty	Description																																			
1	COOLANT SPIN-ON																																			
1	FUEL SPIN-ON SECONDARY																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
1	LUBE CARTRIDGE																																			
2	LUBE SPIN-ON FULL FLOW																																			
Qty	Description																																			
1	COOLANT SPIN-ON																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
1	LUBE CARTRIDGE																																			
2	LUBE SPIN-ON FULL FLOW																																			
Qty	Description																																			
1	FUEL CARTRIDGE																																			
1	FUEL/WATER SEPARATOR CARTRIDGE																																			
1	LUBE CARTRIDGE FULL FLOW																																			
<p>Kit No: P559001</p> <p>Primary App: MACK ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>COOLANT SPIN-ON</td> </tr> <tr> <td>1</td> <td>FUEL SPIN-ON SECONDARY</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	COOLANT SPIN-ON	1	FUEL SPIN-ON SECONDARY	1	FUEL/WATER SEPARATOR SPIN-ON	2	LUBE SPIN-ON FULL FLOW	<p>Kit No: P559588</p> <p>Primary App: MACK ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>COALESCING FILTER</td> </tr> <tr> <td>1</td> <td>COOLANT SPIN-ON</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>1</td> <td>LUBE CARTRIDGE</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	COALESCING FILTER	1	COOLANT SPIN-ON	1	FUEL/WATER SEPARATOR SPIN-ON	1	FUEL/WATER SEPARATOR SPIN-ON	1	LUBE CARTRIDGE	2	LUBE SPIN-ON FULL FLOW	<p>Kit No: P559590</p> <p>Primary App: MERCEDES ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>FUEL CARTRIDGE</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>1</td> <td>LUBE CARTRIDGE FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	FUEL CARTRIDGE	1	FUEL/WATER SEPARATOR SPIN-ON	1	LUBE CARTRIDGE FULL FLOW		
Qty	Description																																			
1	COOLANT SPIN-ON																																			
1	FUEL SPIN-ON SECONDARY																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
2	LUBE SPIN-ON FULL FLOW																																			
Qty	Description																																			
1	COALESCING FILTER																																			
1	COOLANT SPIN-ON																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
1	LUBE CARTRIDGE																																			
2	LUBE SPIN-ON FULL FLOW																																			
Qty	Description																																			
1	FUEL CARTRIDGE																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
1	LUBE CARTRIDGE FULL FLOW																																			
<p>Kit No: P559607</p> <p>Primary App: MACK ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>FUEL SPIN-ON SECONDARY</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	FUEL SPIN-ON SECONDARY	1	FUEL/WATER SEPARATOR SPIN-ON	2	LUBE SPIN-ON FULL FLOW	<p>Kit No: P559607</p> <p>Primary App: MACK ENGINES</p> <p>Kit Contents</p> <table border="1"> <thead> <tr> <th>Qty</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>FUEL SPIN-ON SECONDARY</td> </tr> <tr> <td>1</td> <td>FUEL/WATER SEPARATOR SPIN-ON</td> </tr> <tr> <td>2</td> <td>LUBE SPIN-ON FULL FLOW</td> </tr> </tbody> </table>	Qty	Description	1	FUEL SPIN-ON SECONDARY	1	FUEL/WATER SEPARATOR SPIN-ON	2	LUBE SPIN-ON FULL FLOW																			
Qty	Description																																			
1	FUEL SPIN-ON SECONDARY																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
2	LUBE SPIN-ON FULL FLOW																																			
Qty	Description																																			
1	FUEL SPIN-ON SECONDARY																																			
1	FUEL/WATER SEPARATOR SPIN-ON																																			
2	LUBE SPIN-ON FULL FLOW																																			

Moffett Equipment		
Kit No:	P559573	
Primary App:	MOFFETT EQUIPMENT	
Kit Contents	Qty	Description
P181050	1	AIR PRIMARY, FINNED
P556245	1	FUEL CARTRIDGE
P171534	1	HYDRAULIC CARTRIDGE
P550148	1	HYDRAULIC SPIN-ON

Navistar		
Kit No:	P559009	
Primary App:	NAVISTAR ENGINES	
Kit Contents	Qty	Description
P552603	1	FUEL SPIN-ON SECONDARY
P555627	1	FUEL/WATER SEPARATOR SPIN-ON
P555616	2	LUBE SPIN-ON FULL FLOW

Kit No:	P559217	
Primary App:	NAVISTAR ENGINES	
Kit Contents	Qty	Description
P554071	1	COOLANT SPIN-ON
P552603	1	FUEL SPIN-ON SECONDARY
P555627	1	FUEL/WATER SEPARATOR SPIN-ON
P555616	2	LUBE SPIN-ON FULL FLOW

Sterling / Mercedes		
Kit No:	P559631	
Primary App:	STERLING/MERCEDES	
Kit Contents	Qty	Description
P550762	1	FUEL CARTRIDGE
P550747	1	FUEL/WATER SEPARATOR SPIN-ON
P550769	1	LUBE CARTRIDGE FULL FLOW

Thermoking		
Kit No:	P559638	
Primary App:	THERMOKING	
Kit Contents	Qty	Description
P553693	1	FUEL SPIN-ON SECONDARY
P552363	1	LUBE SPIN-ON BYPASS
P550162	1	LUBE SPIN-ON FULL FLOW

Kit No:	P559545	
Primary App:	THERMOKING REFRIGERATION UNITS	
Kit Contents	Qty	Description
P556285	1	FUEL BOX PRIMARY
P557264	1	FUEL/WATER SEPARATOR BOX
P557382	1	LUBE SPIN-ON COMBINATION

Volvo		
Kit No:	P559594	
Primary App:	VOLVO	
Kit Contents	Qty	Description
P554019	1	COOLANT SPIN-ON
P550529	1	FUEL SPIN ON
P550463	1	FUEL/WATER SEPARATOR CARTRIDGE
P550425	1	LUBE SPIN-ON BYPASS
P553191	2	LUBE SPIN-ON FULL FLOW

Kit No:	P559628	
Primary App:	VOLVO 20514654	
Kit Contents	Qty	Description
P555003	1	FUEL/WATER SEPARATOR SPIN-ON
P169982	1	GASKET

Kit No:	P559106	
Primary App:	VOLVO ENGINES	
Kit Contents	Qty	Description
P550529	1	FUEL SPIN ON
P550736	1	FUEL/WATER SEPARATOR CARTRIDGE
P550425	1	LUBE SPIN-ON BYPASS
P553191	2	LUBE SPIN-ON FULL FLOW

Kit No:	P559550	
Primary App:	VOLVO ENGINES	
Kit Contents	Qty	Description
P550372	1	FUEL SPIN ON
P550463	1	FUEL/WATER SEPARATOR CARTRIDGE
P550425	1	LUBE SPIN-ON BYPASS
P553191	2	LUBE SPIN-ON FULL FLOW

Kit No:	P559574	
Primary App:	VOLVO ENGINES	
Kit Contents	Qty	Description
P554019	1	COOLANT SPIN-ON
P550372	1	FUEL SPIN ON
P550425	1	LUBE SPIN-ON BYPASS
P553191	2	LUBE SPIN-ON FULL FLOW

Kit No:	P559575	
Primary App:	VOLVO ENGINES	
Kit Contents	Qty	Description
P550372	1	FUEL SPIN ON
P550425	1	LUBE SPIN-ON BYPASS
P553191	2	LUBE SPIN-ON FULL FLOW

Kit No:	P559576	
Primary App:	VOLVO ENGINES	
Kit Contents	Qty	Description
P550529	1	FUEL SPIN ON
P550425	1	LUBE SPIN-ON BYPASS
P553191	2	LUBE SPIN-ON FULL FLOW


Kit No:	P559616	
Primary App:	VOLVO ENGINES	
Kit Contents	Qty	Description
P550529	1	FUEL SPIN ON
P550463	1	FUEL/WATER SEPARATOR CARTRIDGE
P550425	1	LUBE SPIN-ON BYPASS
P551807	2	LUBE SPIN-ON FULL FLOW

Kit No:	P559626	
Primary App:	VOLVO ENGINES	
Kit Contents	Qty	Description
P552200	1	FUEL SPIN-ON SECONDARY
P550463	1	FUEL/WATER SEPARATOR CARTRIDGE
P559000	1	LUBE SPIN-ON COMBINATION

Kit No:	P559632	
Primary App:	VOLVO ENGINES	
Kit Contents	Qty	Description
P554019	1	COOLANT SPIN-ON
P550529	1	FUEL SPIN ON
P550463	1	FUEL/WATER SEPARATOR CARTRIDGE
P550425	1	LUBE SPIN-ON BYPASS
P551807	2	LUBE SPIN-ON FULL FLOW

English	Español	Français	German
Air Breather	Respiradero	filtre à air	Be- Entlüftungsfilter
Air Cleaner	Filtro de aire	Filtre à air	Luftfilter
Air Dryer	Secador de aire	Dessiccateur	Trockenmittelbox
Air Filter	Filtro de aire	Filtre à air	Luftfilter
Air Filter Kit	Juego de filtro de aire	Kit pour filtre à air	Luftfilter-Kit
Air Panel	Elemento de habitáculo	Panneau filtre à air	Kabinenfilter
Air Primary	Elemento principal de aire	Filtre à air Principal	Hauptelement
Air Safety	Elemento de filtro secundario	Élément de sécurité	Sicherheitselement
Air/Oil Separator	Desoleador	Séparateur air/huile	Ölabscheider
Breather	Respiradero	Filtre à air	Be-Entlüftungsfilter
Breather Adapter	Adaptador Para Respiradero	Adaptateur de filtre à air	Adapter für Be-Entlüftungsfilter
Cabin Air Filter	Filtro para cabina	Filtre de cabine	Kabinenfilter
Coalescing Filter	Filtro de condensación	Filtre coalescent	Koaleszenz-Filter
Coolant Cartridge	Cartucho para circuito refrigerante	Cartouche pour liquide de refroidissement	Kühlwasserfilter
Coolant Filter	Filtro para circuito refrigerante	Filtre pour liquide de refroidissement	Kühlwasserfilter
Coolant Spin-On	Filtro roscado para circuito refrigerante	Filtre à visser pour liquide de refroidissement	Kühlwasserfilter
Fuel Cartridge	Cartucho combustible	Cartouche à carburant	Kraftstofffilter
Fuel Filter	Filtro de combustible	Filtre à carburant	Kraftstofffilter
Fuel Filter Water Separator	Filtro separador agua/combustible	Filtre séparateur eau/carburant	Kraftstoff-Wasserabscheider
Fuel Spin-On	Filtro roscado de combustible	Filtre à carburant à visser	Kraftstofffilter
Gasket	Junta	Joint d'étanchéité	Dichtung
Hydraulic Assembly	Conjunto hidráulico	Filtre hyd. complet	Hydraulikfilter
Hydraulic Cartridge	Cartucho hidráulico	Cartouche hydraulique	Hydraulikfilter
Hydraulic Filter	Filtro hidráulico	Filtre hydraulique	Hydraulikfilter
Hydraulic Spin-On	Filtro roscado hidráulico	Filtre à visser hydraulique	Hydraulikfilter
Liquid Filter Kit	Filtros para líquidos	Kit filtre liquide	Filterkit
Lube By-pass	Filtro de aceite con derivación	Filtre à huile bypass	Ölfiter
Lube Cartridge	Cartucho de aceite	Cartouche Filtre à huile	Ölfiter
Lube Filter	Filtro de aceite	Filtre à huile	Ölfiter
Lube Spin-on	Filtro roscado de aceite	Filtre à visser huile	Ölfiter
O-Ring	Junta tórica	Joint torique	O-Ring
Pre-Cleaner	Préfiltre	Prefiltro	Vorfilter
Screen Element	Elemento pantalla	Élément écran	Bildschirm
Trans. Filter Kit.	Trans. Kit de Filtros	Kit filtre trans.	Getriebe-Filter-Kit
Transmission Filter	Filtro de transmisión	Filtre pour transmission	Getriebeölfiter
Vacuator Valve	Válvula de evacuación	Valve d'évacuation	Vakuator-Ventil
Vapor Emission Pad	Emisión de vapor del amortiguador	Protection d'émission de vapeur	
Washer Gasket	Arandela de goma	Rondelle d'étanchéité	Dichtung
Wing Nut	Tuerca mariposa	Écrou à oreilles	Flügelmutter

The following section features popular head assemblies and their matching filters for fuel, lube, coolant and hydraulic filtration.



Fuel Heads & Filters 38

- 15-30 gph / 57 -144 lph fuel flow range
- 40-160 gph / 151-606 lph fuel flow range
- 60-180 gph / 227-681 lph fuel flow range
- Up to 90 gph / 340 lph fuel flow range
- Selection for existing OE applications

Lube Heads & Filters..... 41

- Selection for existing OE applications includes extended service filter choices



Coolant Head, Mounting Bracket & SCA Filters 42

- This single head fits many coolant filters all with various amounts of coolant additive units. Extended service and time release filters are also available.
- Three- and four-ply coolant hoses in various diameter sizes are available.




Hydraulic Heads & Filters..... 43

- Two low pressure series - LPS04 and HBK05
- Low pressure filters are the most commonly used type of filter in hydraulic circuits, used most often as return line filters in applications with working pressures up to 1000 psi, depending upon model selected.
- Three Duramax® medium-pressure series - HMK03, HMK04, HMK05
- Donaldson's famous Duramax filters are the highest rated medium pressure filters available in a spin-on configuration.
- Duramax filters are reliable, sturdy, long-lived and easy to install. Most often used as return-line filters, they are designed for working pressures up to 1000 psi and static pressures up to 2000 psi.


Fuel Flow Range: 15-30 gph / 57 -144 lph

Head Assemblies



1/4"-18 NPT Ports (2)
Threaded Stud: M16 x 1.5
Length: 3.25" / 83 mm
Width: 3.25" / 83 mm

Part No. P560382



1/2"-20 UNF Ports (2)
Threaded Stud: M16 x 1.5
Length: 3.25" / 83 mm
Width: 3.25" / 83 mm

Part No. P562263



1/4"-18 NPT Ports (2)
Threaded Stud: M16 x 1.5
Length: 4.02" / 102 mm
Width: 3.10" / 79 mm

Part No. P174775

Filter Choices: (flow ranges listed are maximums) Outer Dia.: 3.02" (77 mm)



FFWS-Twist&Drain
20µ Efficiency @ 99%
15 gph / 57 lph
Length: 3.75" / 95 mm

Part No. P551039



FFWS-Twist&Drain
11µ Efficiency @ 99%
30 gph / 144 lph
Length: 5.55" / 141 mm

Part No. P550588



FFWS-Twist&Drain
25µ Efficiency @ 99%
30 gph / 144 lph
Length: 5.55" / 141 mm

Part No. P550248



Oil Mist Coalescer
2 CFM
Length: 2.57" / 65 mm
Part No. P566130

Fuel Flow Range: Up to 90 gph / 340 lph

Head Assemblies



1/2"-14 NPT Ports (4)
Threaded Stud:
m95 x 2.5 6H
Length: 5.06" / 129 mm
Width: 5.35" / 136 mm

Part No. P566308



1/2"-14 NPT Ports (4)
Air Relief Valve
Manual Priming Pump
Threaded Stud:
m95 x 2.5 6H
Length: 5.06" / 129 mm
Width: 5.35" / 136 mm

Part No. P566309

Filter Choices: (flow ranges listed are maximums) Outer Dia.: 3.82" (93 mm)



Filter
5µ Cellulose
90 gph / 340 lph
Length: 6.10" / 155 mm

Part No. P566310



Filter
10µ Cellulose
90 gph / 340 lph
Length: 6.10" / 155 mm

Part No. P566311



FFWS-Twist&Drain
20µ Cellulose
90 gph / 340 lph
Length: 6.10" / 155 mm

Part No. P566312

Twist&Drain - A Simple & Easy Drain Valve

Draining existing styles of fuel filter water separators can not only be messy, but can take more time to drain. If you're looking for a simple and quick way to eliminate the water from your fuel filter - consider installing a Donaldson filter system with a Twist&Drain valve.

- Large handle is easy to grasp and operate
- Free-flowing drain for fast water elimination
- Self-venting design allows water to evacuate in a quick, steady stream – not a slow drip (no need to open a secondary vent)
- Up to a single turn to begin draining



Fuel Flow Range: 40-160 gph / 151-606 lph

Head Assemblies

Filter Choices: (flow ranges listed are maximums)
Outer Dia.: 3.66" (93 mm)



1/2" NPT
 Threaded Stud: 1"-14
 Length: 3.70" / 94 mm
 Height: 2.40" / 61 mm

Part No. P562261



5/8" SAE
 Threaded Stud: 1"-14
 Length: 3.70" / 94 mm
 Height: 2.40" / 61 mm

Part No. P562262



FFWS
 25µ Efficiency @ 99%
 75 gph / 284 lph
 Length: 5.86" / 149 mm

Part No. P550691



FFWS
 10µ Efficiency @ 99%
 Synthetic Media
 100 gph / 378 lph
 Length: 7.34" / 187 mm

Part No. P551001



FFWS-Twist&Drain
 20µ Efficiency @ 99%
 90 gph / 341 lph
 Length: 7.34" / 187 mm

Part No. P558000



FFWS-Twist&Drain
 25µ Efficiency @ 99%
 100 gph / 378 lph
 Length: 8.36" / 212 mm

Part No. P552565



FFWS-Twist&Drain
 7µ Efficiency @ 99%
 120 gph / 454 lph
 Length: 9.67" / 246 mm

Part No. P550901



FFWS-Twist&Drain
 10µ Efficiency @ 99%
 Synteq® Media
 120 gph / 454 lph
 Length: 9.67" / 246 mm

Part No. P551000



Filter
 25µ Efficiency @ 99%
 40 gph / 151 lph
 Length: 4.21" / 107 mm

Part No. P550104



Filter
 25µ Efficiency @ 99%
 60 gph / 227 lph
 Length: 5.35" / 136 mm

Part No. P550105



Filter
 2µ Efficiency @ 99%
 100 gph / 378 lph
 Length: 6.87" / 174 mm

Part No. P551313



Filter
 3µ Efficiency @ 99%
 160 gph / 606 lph
 Length: 9.17" / 233 mm


Part No. P551311

Fuel Flow Range: 60-180 gph / 227-681 lph

Head Assembly

Filter Choices:

Outer Dia.: 4.25" (108 mm)



7/8"-14 Ports (2)
 Threaded Stud: 1 1/4"-12
 Length: 6.24" / 159 mm
 Width: 4.96" / 126 mm

Part No. P920682

Head has two inlet ports (on top) and two outlet ports (side) for design flexibility.



Filter
 15µ Efficiency @ 99%
 60 gph / 227 lph
 Length: 7.05" / 179 mm

Part No. P920711



FFWS
 25µ Efficiency @ 99%
 180 gph / 681 lph
 Length: 11.33" / 288 mm

Part No. P920683



FFWS
 10µ Cellulose
 180 gph / 681 lph
 Length: 11.33" / 288 mm

Part No. P925683



Electronic (12V or 24V DC) water level sensor

Part No. P920681

Replacement Fuel Heads and Filters for Popular OE Applications



Head Assembly

7/8" -14 NPT Ports (2)
Threaded Stud: 1 1/4-12 UNF
Length: 5.56" / 141 mm
Width: 4.73" / 120 mm

Part No. P174770

Filter Choices: (flow ranges listed are maximums)

Outer Dia.: 4.66" (118 mm)



FFWS
25µ Efficiency @ 99%
250 gph / 946 lph
Length: 12.36" / 314 mm

Part No. P550687



FFWS
10µ Efficiency @ 99%
250 gph / 946 lph
Length: 12.36" / 314 mm

Part No. P551006



3/8" -18 NPTF Ports (2)
Threaded Stud: 1 1/4-12 UNF
Length: 4.84" / 123 mm
Width: 4.73" / 120 mm

Part No. P174773



Filter
9µ Efficiency @ 99%
235 gph / 890 lph
Length: 10.24" / 260 mm

Part No. P550202



Filter
30µ Efficiency @ 99%
200 gph / 757 lph
Length: 8.94" / 118 mm

Part No. P550958



Head Assembly

3/8" -18 NPTF Ports (2)
Threaded Stud: 1 1/16-16 UNF
Length: 5.20" / 132 mm
Width: 4.73" / 120 mm

Part No. P174774

Filter Choices: (flow ranges listed are maximums)

Outer Dia.: 4.66" (118 mm)



Filter
16µ Efficiency @ 99%
250 gph / 946 lph
Length: 8.94" / 118 mm

Part No. P550959



Extended Service Filter
5µ Efficiency @ 99%
Synteq® Media
150 gph / 568 lph
Length: 8.94" / 118 mm

Part No. EFF0047



Head Assembly

1/4" NPTF Ports (3)
Threaded Stud: 13/16-12
Length: 3.85" / 98 mm
Width: 4.88" / 124 mm

Part No. P174785

Filter Choices: (flow ranges listed are maximums)

Outer Dia.: 3.66" (93 mm)



Filter
9µ Efficiency @ 99%
90 gph / 340 lph
Length: 6.85" / 174 mm

Part No. P556916



Filter
3µ Efficiency @ 99%
Length:
90 gph / 340 lph
Length: 6.85" / 174 mm

Part No. P556917



Filter
16µ Efficiency @ 99%
40 gph / 151 lph
Length: 4.21" / 107 mm

Part No. P550928



Extended Service Filter
5µ Efficiency @ 99%
Synteq® Media

60 gph / 227 lph
Length: 6.85" / 174 mm

Part No. EFF7917

Replacement Lube Heads and Filters for Popular OE Applications



Head Assembly

3/4"-14 NPTF Ports (2)
By-pass Valve: 25 psi / 172 kPa
Threaded Stud: 1"-12 UNF 2A
Height: 2.40"/ 61 mm
Width: 3.74" / 95 mm

Part No. P561134

Filter Choices: (flow ranges listed are maximums)
Outer Dia.: 3.66" (193 mm)




Filter
20 μ Efficiency @ 50%
20 gpm, / 76 lpm
Length: 6.85"/ 174 mm

Part No. P553712



Filter
20 μ Efficiency @ 50%
15 gpm, / 57 lpm
Length:
5.35"/136 mm
Part No. P555680



Head Assembly

3/8"NPT Ports (2)
By-pass valve: 25 psi / 172 kPa
Threaded Stud: 1 3/8"-16 UN2A
Length: 5.20"/132 mm
Width: 4.73" / 120 mm

Part No. P174777

Filter Choices: (flow ranges listed are maximums)
Outer Dia.: 4.66" (118 mm)



By-pass Filter
14 μ Efficiency @ 50%
7.5 gpm, / 28 lpm
Length: 10.24" / 260 mm

Part No. P550777



Head Assembly

1-1/4 NPT Ports (2)
Threaded Stud: 1-1/2"-12
Width: 5.52"/ 140 mm
Bypass Valve: 40 psid

Part No. P174780

Filter Choices: (flow ranges listed are maximums)
Outer Dia.: 4.66" (118 mm)



Filter
14 μ Efficiency @ 50%
45 gpm, / 170 lpm
Length: 10.24"/ 260 mm

Part No. P551670



Extended Service Filter
15 μ Efficiency @ 99%
Synteq Media
45 gpm, / 170 lpm
Length: 10.24"/ 260 mm

Part No. ELF7670



Mounting Head Adapter

Threaded Stud: 1-1/2 - 12 UNF-2A
Height: 1.73"/ 44 mm
Width: 5.20"/132 mm

Part No. P174779



Extended Service Filter
15 μ Efficiency @ 99%
Synteq Media
25 gpm, / 95 lpm
Length: 6.22"/ 158 mm

Part No. ELF7947



Head Assembly

1-5/8"-12 Ports (2)
Threaded Stud: 2-1/4"-12
Width: 5.00" / 127 mm

Part No. P174783

Filter Choices: (flow ranges listed are maximums)
Outer Dia.: 4.66" (118 mm)



Filter
22 μ Efficiency @ 99%
50 gpm, / 184 lpm
Length: 11.70"/ 297 mm

Part No. P553000



Filter
15 μ Efficiency @ 99%
35 gpm, / 132 lpm
Length: 8.90"/ 227 mm

Part No. P553548



Extended Service Filter
15 μ Efficiency @ 99%
Synteq® Media
50 gpm, / 184 lpm
Length: 11.70"/ 297 mm

Part No. EFF7300

Coolant Head & Filters

The Donaldson remote mount head is designed to fit all our spin-on filters with a 11/16"-16 threads. The bracket can be mounted to the head of the fire wall or some off-engine location.



Head Assembly

3/8" NPTF Ports (2)
 Threaded Stud: 11/16-16"
 Length: 3.60"/91 mm
 Width: 3.60"/91 mm

Part No. P174766

Filter Choices:

Outer Dia.: 3.66" (93 mm)



**Units
 Printed on
 Filter**

0	P554685
4	P554071
6	P554072
8	P554073
12	P554074
15	P554075

SCA Filter No.



Mounting Bracket
 Part No. P174767



Extended Service Filters 150,000 mile / 195,000 km service interval

Non-chemical filters will go the distance of your coolant; for Organic Additive Technology and Extended Service Coolant Users

Type	Filter Part No.
Non Chemical	ECF4085
Time Release	ECF4088


Coolant Hose

3-ply hose is reinforced with three layers of polyester fabric and coated with a unique silicone elastomer.

4-ply hose is reinforced with an added layer of polyester fabric and provides even greater resistance to abrasion and rubbing.

Size (inner dia.) in mm	Part No.	Nominal O.D. in mm	Recommended Clamp Lined Constant Torque
0.63 16	P171371	0.95 24	P532921 N/A
0.75 19	P171372	1.08 27	P532923 N/A
0.88 22	P171373	1.20 30	P532923 N/A
1.00 25	P171374	1.33 34	P532923 N/A
1.13 29	P171375	1.45 37	P532924 N/A
1.25 32	P171376	1.90 48	P532924 N/A
1.38 35	P171377	1.70 43	P115200 N/A
1.50 38	P171378	1.83 46	P115200 N/A
1.63 41	P171379	1.95 50	P115200 N/A
1.75 44	P171380	2.08 53	P115200 N/A
2.00 51	P171381	2.33 59	P115200 P532925
2.25 57	P171382	2.58 66	P115201 P532925
2.38 60	P171383	2.70 69	P115201 P532925
2.50 64	P171384	2.83 72	P115201 P532925
2.63 67	P171385	2.95 75	P143422 P532925
2.75 70	P171386	3.08 78	P143422 P532926
3.00 76	P171387	3.33 85	P143422 P532926
3.50 89	P171388	4.83 123	P115202 P532927
4.00 102	P171389	4.33 110	P115203 P532928

Size (inner dia.) in mm	Part No.	Nominal O.D. in mm	Recommended Clamp Lined Constant Torque
1.00 25	P171390	1.40 36	P532924 N/A
1.50 38	P171391	1.90 48	P115200 N/A
2.00 51	P171392	2.40 61	P115201 P532925
2.25 57	P171393	2.65 67	P115201 P532925
2.50 64	P171394	2.89 73	P115201 P532925
2.75 70	P171395	3.15 80	P143422 P532926



Designed to withstand extremes in operating temperatures ranging from -65°F to 350°F (-54°C to 177°C).

Hydraulic - Low Pressure Family LPS04



LPS04 Series Specifications

Product Family	Flow Range	Pressure (NFPA/3.10.17)		Porting Types
		Working	Static	
LPS04	0-30 gpm 0-114 l/min	150 psi 1034 kPa 10.3 bar	300 psi 2070 kPa 20.7 bar	1/2", 3/4" NPT, or SAE-8 (1/2"), SAE-12 (3/4") O-Ring

Where and Why Use

Low pressure filters are the most commonly used type of filter in hydraulic circuits, used most often as return line filters in applications with working pressures up to 1000 psi, depending upon model selected.

Mix 'n Match...

Select the head and filter combination to build a filter system to suit your specifications

Head Choices for LPS04

Port Size	Bypass Range	Gauge ports (drill, tap, plug)	Gauge Port Location	Donaldson Part No.
1/2" NPT	15 psi / 103.4 kPa / 1.34 bar	(2) 1/8" NPT	upstream side	P563288
3/4" NPT	25 psi / 172.5 kPa / 1.72 bar	(2) 1/8" NPT	upstream side	P561131
	5 psi / 34.5 kPa / .34 bar	(2) 1/8" NPT	downstream side	P561132
	25 psi / 172.5 kPa / 1.72 bar	none	na	P561134
	5 psi / 34.5 kPa / .34 bar	none	na	P561135
	none	none	na	P561136
	15 psi / 103.4 kPa / 1.34 bar	none	na	P563278
SAE-12	none	none	na	P561133
	none	(1) SAE-4	upstream side, LH	P561137
	5 psi / 34.5 kPa / .34 bar	none	na	P561140
	25 psi / 172.5 kPa / 1.72 bar	none	na	P561141
	15 psi / 103.4 kPa / 1.34 bar	none	na	P563279
	25 psi / 172.5 kPa / 1.72 bar	(2) 1/8" NPT	upstream side	P563280
	15 psi / 103.4 kPa / 1.34 bar	none	M6 mtg. Thrds	P563287
SAE-8	25 psi / 172.5 kPa / 1.72 bar	none	na	P561138

Spin-on Filter Choices

Media Type	B _{x(c)} = 200	B _{x(c)} = 1000	Length (in./mm)	Donaldson Part No.
Cellulose		24	5.35/136	P565061
Cellulose		23	5.35/136	P562198
Cellulose		23	7.87/200	P565059
Cellulose	32		5.35/136	P562199
Cellulose	32		7.87/200	P565060
Synteq		9	7.87/200	P564357
Synteq		10	5.35/136	P560693
Synteq		10	7.87/200	P179089
Synteq		23	5.35/136	P560694
Synteq		6	5.35/136	P564967
Water absorbing*	32		5.35/136	P565062
Wire Mesh	150		5.35/136	P550274

* Absorbs Approx. 6 oz/170 ml of water @ 20 psid

Hydraulic - Low Pressure Family HBK05



HBK05 Series Specifications

Product Family	Flow Range	Pressure (NFPA/3.10.17)		Porting Types
		Working	Static	
HBK05	0-60 gpm	150 psi	250 psi	SAE-20 (1¼") O-Ring, or 1¼" NPT
	0-227 l/min	1034 kPa	1724 kPa	
		10.3 bar	17.2 bar	

Where and Why Use

Low pressure filters are the most commonly used type of filter in hydraulic circuits, used most often as return line filters in applications with working pressures up to 1000 psi, depending upon model selected.

Mix 'n Match...

Select the head and filter combination to build a filter system to suit your specifications

Head Assemblies

Port Size	Bypass Rating	Indicator Style & Location	Part No.
1¼" NPT	25 psi / 172 kPa	Visual, Both Sides	P166418
1¼" NPT	5 psi / 34 kPa	Visual, Both Sides	P166665
SAE-20 O-Ring	25 psi / 172 kPa	Visual, Both Sides	P166439

Donaldson uses the inlet port as the reference point. "Left side," for instance, means that the indicator mounts on the side of the filter head that is on your left when you **face the inlet port**.

Spin-on Filter Choices

B _{x(c)} = 1000	Length		Part No.
	(in.)	(mm)	
<3µm	10.7	271	P167796 with Viton Seal
6µm	6.7	170	P169430
	10.7	271	P167832
9µm	6.7	170	P167162
	10.7	271	P165762
10µm	6.7	170	P165875
	10.7	271	P165876
13µm	6.7	170	P167944 with Viton Seal
	10.7	271	P167945 with Viton Seal
23µm	6.7	170	P165877
	10.7	271	P165878
>50µm	6.7	170	P165879
	10.7	271	P165880

Hydraulic - Original Duramax® HMK03

HMK03 Series Specifications

Product Family	Flow Range	Pressure (NFPA/t3.10.17)		Porting Types
		Working	Static	
HMK03	0-25 gpm 0-95 l/min	1000 psi 6895 kPa 69 bar	2000 psi 13790 kPa 137.9 bar	SAE-12 O-Ring

Where and Why Use

Donaldson's famous Duramax® filters are the highest rated medium pressure filters available in a spin-on configuration. Duramax® are reliable, sturdy, long-lived and easy to install. Most often used as return-line filters, they are designed for working pressures up to 1000 psi and static pressures up to 2000 psi.



Mix 'n Match...

Select the head and filter combination to build a filter system to suit your specifications

Head Assemblies

Port Size	Bypass Rating	Indicator	Head Part No.
SAE-12	No Bypass	None*	P170327
¾" O-Ring	50 psi	None*	P170773
	345 kPa	Visual*	P179460

*Head is machined to accept optional electrical indicators. See Indicator list at right for the available choices.

Spin-on Filter Choices

Media Type	B _{x(0)} = 1000	Length		Part No.	Seal Material
		(in.)	(mm)		
Synteq	6µm	5.5	140	P170306	BunaN
		9.5	242	P170307	BunaN
Synteq	9µm	5.5	140	P170308	BunaN
		9.5	242	P170309	BunaN
Synteq	10µm	9.5	242	P176107	BunaN
Synteq	14µm	9.5	242	P173702	BunaN
Synteq	20µm	5.5	140	P170310	BunaN
		9.5	242	P170311	BunaN
Synteq	23µm	5.5	140	P170312	BunaN
		9.5	242	P170313	BunaN
Cellulose	23µm	5.5	140	P170480 ¹	BunaN
		9.5	242	P170089 ¹	BunaN

¹ This filter not recommended for use with the "No Bypass" head assembly P170327



Synteq® is Donaldson's synthetic filter media that was specially developed for liquid filtration. Its low-friction, high-flow properties result in consistently low differential pressure over the life of the filter.

Donaldson designed this consistently-shaped fiber pattern to control fiber size, pore size, and flow patterns throughout the media mat. The result is a media with predictable filtration efficiencies, maximum dirt holding capacity, and low pressure drop.

Synteq filter media is compatible with petroleum based fluids, most phosphate esters, water oil emulsions, and HWCF (high water content fluids).

Hydraulic - Original Duramax® HMK04



HMK04 Series Specifications

Product Family	Flow Range	Pressure (NFPA/t3.10.17)		Porting Types
		Working	Static	
HMK04	0-35 gpm 0-132 l/min	500 psi 3448 kPa 34.5 bar	1000 psi 6895 kPa 69 bar	SAE-12, -16 O-Ring or 1" NPT, 3/4" NP

Where and Why Use

Donaldson's famous Duramax® filters are the highest rated medium pressure filters available in a spin-on configuration. Duramax® are reliable, sturdy, long-lived and easy to install. Most often used as return-line filters, they are designed for working pressures up to 1000 psi and static pressures up to 2000 psi.

Mix 'n Match...

Select the head and filter combination to build a filter system to suit your specifications

Notes

Donaldson uses the inlet port as the reference point. "Left side," for instance, means that the indicator mounts on the side of the filter head that is on your left when you face the inlet port. The filter head snout/post must be lubricated before spinning on a new filter to prevent thread damage.

Head Assemblies

Port Size	Bypass Rating	Standard Indicator Style & Location ^{1,2}	Indicator Options	Head Part No.	
3/4" NPT	25 psi / 172 kPa	None	None	P169317	
		D (Visual), Left Side	None	P169310	
	SAE-12 O-Ring	25 psi / 172 kPa	None	None	P167473
No Bypass	No Bypass	D (Visual), Left Side (25 psi)	None	P169320	
		None	None	P165434	
		D (Visual), Left Side (50 psi)	None	P173750	
SAE-12 O-Ring (3 ports)	50 psi / 345 kPa	A (Electrical)	B,C	P167529	
1" NPT	25 psi / 172 kPa	D (Visual), both sides	A, B, C	P166086	
		None	None	P169309	
		D (Visual), Left Side	None	P166416	
SAE-16 O-Ring	15 psi / 100 kPa	None	A	P176569	
SAE-16 O-Ring	25 psi / 172 kPa	None	None	P163681	
		D (Visual), Left Side	None	P166417	
		D (Visual), both sides	A, B, C	P166088	
		E (Electrical)	None	P176568	
		A (Electrical)	B, C	P165537	
		No Bypass	D (Visual), Both Sides (25 psi)	A, B, C	P166664
		A (Electrical)	B, C	P166902	
		50 psi	D (Visual, Right Side)	All	P179381
		No Bypass	None	None	P164667
		50 psi / 345 kPa	None	None	P167201
SAE-16 O-Ring	5 psi	A (Electrical)	B, C	P166862	
		D (Visual), Both Sides	All	P564850	
1" NPT	No Bypass	D (Visual), Left Side (25 psiD)	None	P564484	
1" NPT	25 psi	D (Visual), Left Side (25 psiD)	None	P564485	

Spin-on Filter Choices

B_{x(C)} = 1000	Media Technology	Length (in.) (mm)		Part Number
<3µm	Synteq	9.4	240	P165185 with Viton Seal
6µm	Synteq	9.4	240	P167590
9µm	Synteq	6.0	52	P165354
		9.4	240	P165332
10µm	Synteq	6.0	152	P176565
		9.4	240	P176566
24µm	Synteq	6.0	152	P164385
		9.4	240	P177047
20µm	Synteq	6.0	152	P163542
300 psi collapse		9.4	240	P163555
20µm	Synteq	6.0	152	P164375
		9.4	240	P164378
13µm	Synteq	9.4	240	P164056 with Viton Seal
33µm	Synteq	6.0	152	P164381
		9.4	240	P164384
23µm	Synteq	6.0	152	P164381
		9.4	240	P164384
22µm	Synteq	9.4	240	P164059 with Viton Seal
>50µm	Synteq	6.0	152	P165335
		9.4	240	P165338
na	Water Removal	9.4	240	P560584

Synteq® is Donaldson's synthetic filter media that was specially developed for liquid filtration. Its low-friction, high-flow properties result in consistently low differential pressure over the life of the filter.




Donaldson designed this consistently-shaped fiber pattern to control fiber size, pore size, and flow patterns throughout the media mat. The result is a media with predictable filtration efficiencies, maximum dirt holding capacity, and low pressure drop.

Synteq filter media is compatible with petroleum based fluids, most phosphate esters, water oil emulsions, and HWCF (high water content fluids).

Filter Seals

Filters with seals made of BunaN are appropriate for most applications involving petroleum oil. Filters with seals made of Viton (a fluoroelastomer) are required when using diester, phosphate ester fluids, water glycol, water/oil emulsions and HWCF (high water content fluids) over 150°F. Donaldson offers both types.

Service Indicator Choices for HMK Series



Electric Models¹

Use with Bypass Valve Pressure of:	Indicator Part No.	Style³	Description
5 psi / 34.5 kPa	P163642	A	Single post DC.
15 psi / 103 kPa	P163601	A	Single post DC.
25 psi / 172.5 kPa	P163839	A	Single post DC.
25 psi / 172.5 kPa	P162400	A	Single post DC.
25 psi / 172.5 kPa	P171143	B	DC 2-wire.
25 psi / 172.5 kPa	P173944	C	AC/DC 3-wire.
50 psi / 345 kPa	P165194	A	Single post DC.
50 psi / 345 kPa	P167455	A	Single post DC.
50 psi / 345 kPa	P171087	B	DC 2-wire.
50 psi / 345 kPa	P170926	E	DC 2-wire.
50 psi / 345 kPa	P173893	F	DC 3-wire.
50 psi / 345 kPa	P174396	C	AC/DC 3-wire.

Visual Models (non-electric)²

Use with Bypass Valve Pressure of:	Indicator Part No.	Style³
15 psi / 103 kPa	P162642	D
25 psi / 172. kPa	P162696	D
50 psi / 345 kPa	P167580	D
n/a (blank plate)	P165984	n/a

NOTE: PSI is marked on the face of the visual indicators.

Indicator Notes

¹ All electric models have a maximum operating temperature of 250°F/ 121°C.

² All non-electric models have a maximum operating temperature of 180°F/ 82°C.

³ Indicator styles are illustrated above.

Hydraulic - Original Duramax® HMK05



HMK05 Series Specifications

Product Family	Flow Range	Pressure (NFPA/t3.10.17)		Porting Types
		Working	Static	
HMK05	0-50 gpm 189 l/min	350 psi 2413 kPa 24 bar	800 psi 5516 kPa 55 bar	SAE-20 O-Ring or 1¼" NPT

Where and Why Use

Donaldson's famous Duramax® filters are the highest rated medium pressure filters available in a spin-on configuration. Duramax are reliable, sturdy, long-lived and easy to install. Most often used as return-line filters, they are designed for working pressures up to 1000 psi and static pressures up to 2000 psi.

Mix 'n Match...

Select the head and filter combination to build a filter system to suit your specifications

Head Assemblies

Port Size	Bypass Rating	Standard Indicator Style & Location ¹	Indicator Options ²	Part No.	
1¼" NPT	25 psi / 182 kPa	D (Visual), Both Sides (25 psi)	A, B, C, E, F	P167294	
		A (Electrical) (25 psi)	A, B, C, E, F	P167621	
1¼" NPT	25 psi	D (Visual), Left Side (25 psi)	D	P167622	
SAE-20	25 psi	D (Visual), Both Sides (25 psi)	A, B, C, E, F	P165973	
O-Ring	50 psi	D (Visual), Left Side	A, B, C, E, F	P561885	
		Blank Plate Right Side, Elect Port Plugged			
		172 kPa	None	None	P167619
		No Bypass	D (Visual), Both Sides (25 psi)	A, B, C, E, F	P166663
		No Bypass	D (Visual), Right Side (25 psi)	D	P564486
No Bypass	D (Visual), Both Sides (50 psi)	A, B, C, E, F	P564858		

See previous page for indicator options.

Spin-On Filters for HMK05

Media Type	B _{x(c)} = 1000	Length (in./mm)	Part No.
Synteq	<3µm	14.2/361	P564468
Synteq	6µm	11.6/294	P170906
		11.6/294	P1712732 Viton
Synteq	9µm	11.6/294	P165675
		11.6/294	P1712742 Viton
		14.2/361	P179763
Synteq	10µm	11.6/294	P176567
Synteq	14µm	14.2/361	P170949
Synteq	20µm	11.6/294	P165659
		11.6/294	P1712752 Viton
		11.6/294	P165569
Synteq	23µm	11.6/294	P165569
		11.6/294	P1712762 Viton
		14.2/361	P173789
Synteq	>50µm	11.6/294	P165672
		14.2/361	P170546

Filter Seals

Filters with seals made of BunaN are appropriate for most applications involving petroleum oil. Filters with seals made of Viton (a fluoroelastomer) are required when using diester, phosphate ester fluids, water glycol, water/oil emulsions and HWCF (high water content fluids) over 150°F. Donaldson offers both types.

Notes

Donaldson uses the inlet port as the reference point. "Left side," for instance, means that the indicator mounts on the side of the filter head that is on your left when you face the inlet port. The filter head snout/post must be lubricated before spinning on a new filter to prevent thread damage.

Use this alpha-numerically sorted section with small pictures to confirm or verify a Donaldson filter is the proper replacement filter for your equipment. Donaldson part numbers are not the easiest to use or remember. The table below may help you become more familiar with our part numbering system. Asterisk (*) denotes parts featured in this section. Check your local Donaldson distributor for availability and pricing.

Donaldson Engine Aftermarket Part Numbers

Part numbers beginning with...
 Números de parte que comienzan con:
 Numéros De Pièces Débutant Avec:

English	Español	Français
A-D* Air Cleaners/Housing	Filtros de Aire/Carcasas	Boîtiers des Filtres à Air
E* Donaldson Endurance™ Filters, Air Cleaners/Housing	Donaldson Endurance™, Filtros de Aire/Carcasas	Donaldson Endurance™, Boîtiers des Filtres à Air
G Air Cleaners/Housing	Filtros de Aire/Carcasas	Boîtiers des Filtres à Air
H Intake/Exhaust Accessories	Accesorios de Silenciadores	Accessoires de Silencieux
J Exhaust Accessories	Accesorios de Escape	Accessoires d'Échappements
K Hydraulic Assemblies	Sistemas Hidráulicos	Systèmes Hydrauliques
M Mufflers, Silencers, Silent Partner™	Silenciadores, Silent Partner™	Silencieux, Silent Partner™
P* (P00-P18, P27, P50-P56, P60-P61, P76-P92) Replacement parts, including filters, service parts, air/oil separators, (P20-P22, P27) Exhaust Accessories	(P00-P18, P27, P50-P56, P60, P76-P92) Repuestos que incluyen filtros, piezas de servicio, separadores de aire/aceite, (P20-P22, P27) Accesorios de Escape	(P00-P18, P27, P52-P56, P60, P76-P92) Pièces de rechange, incluant filtres, pièces de service, séparateurs d'air/d'huile
R* Filters	Filtros	Filtres
S* Breathers/Crankcase Filtration	Respiradero/Filtración Carter	Reniflards/Filtre Carter
X* Kits (Filter maintenance kits are P559xxx)	Kits (Agrupados de filtros son P559xxx)	Accessoires d'Admission, Trousses de Filtre (les troussees d'entretien pour filtres sont P559xxx)

If Staying Current is Important to You, Consider Using Our On-line Tools






















On-line Product Details / Specifications

















Type in a Donaldson part number in the search window on our public web site. Your results screen will return choices from various countries and results from *ecatalogs* or literature. The image on the left is an example of details available on *ecatalogs* for a Donaldson Duramax spin-on filter.


















On-line Attribute Search



















The "attribute search" on our public web site gives you the ability to search for up to four attributes for more flexible and customized search.





































	<p>Part Number: B085001 Description: AIR PRIMARY, DURALITE Primary App: AIR CLEANER, DURALITE ECB 08* Dimensions: Outer Diameter: 8.50" (216 mm) Outlet Diameter: 3.00" (76 mm) Length: 11.00" (279 mm) Outlet Length: 1.38" (35 mm)</p>		<p>Part Number: B105020 Description: AIR PRIMARY, DURALITE Primary App: MARINE OR OTHER HIGH MOISTURE ENVIRONMENTS Dimensions: Outer Diameter: 10.50" (267 mm) Outlet Diameter: 4.00" (102 mm) Length: 10.50" (267 mm) Outlet Length: 1.38" (35 mm)</p>
	<p>Part Number: B085008 Description: AIR PRIMARY, DURALITE Primary App: AIR CLEANER, DURALITE ECB 08* Dimensions: Outer Diameter: 8.75" (222 mm) Outlet Diameter: 3.00" (76 mm) Length: 8.50" (216 mm) Outlet Length: 1.38" (35 mm)</p>		<p>Part Number: B120376 Description: AIR PRIMARY, DURALITE Primary App: DETROIT DIESEL 0180941002 Dimensions: Outer Diameter: 12.50" (318 mm) Outlet Diameter: 8.00" (203 mm) Length: 15.75" (400 mm) Outlet Length: 1.89" (48 mm)</p>
	<p>Part Number: B085011 Description: AIR PRIMARY, DURALITE Primary App: CUMMINS 2912986, HERCULES B085008 & 40000642 Dimensions: Outer Diameter: 8.50" (216 mm) Outlet Diameter: 4.00" (102 mm) Length: 11.00" (279 mm) Outlet Length: 1.38" (35 mm)</p>		<p>Part Number: B120439 Description: AIR PRIMARY, DURALITE Primary App: MTU ENGINES Dimensions: Outer Diameter: 12.48" (317 mm) Length: 15.75" (400 mm)</p>
	<p>Part Number: B085046 Description: AIR PRIMARY, DURALITE Primary App: MARINE OR OTHER HIGH MOISTURE ENVIRONMENTS Dimensions: Outer Diameter: 8.50" (216 mm) Outlet Diameter: 4.00" (102 mm) Length: 11.00" (279 mm) Outlet Length: 1.38" (35 mm)</p>		<p>Part Number: B125003 Description: AIR PRIMARY, DURALITE Primary App: DEUTZ ALLIS 900025380434, DIVERSIFIED Dimensions: Outer Diameter: 12.50" (318 mm) Outlet Diameter: 5.00" (127 mm) Length: 15.00" (381 mm) Outlet Length: 1.38" (35 mm)</p>
	<p>Part Number: B085048 Description: AIR PRIMARY, DURALITE Primary App: MARINE OR OTHER HIGH MOISTURE ENVIRONMENTS Dimensions: Outer Diameter: 8.50" (216 mm) Outlet Diameter: 3.00" (76 mm) Length: 11.00" (279 mm) Outlet Length: 1.38" (35 mm)</p>		<p>Part Number: B125005 Description: AIR PRIMARY, DURALITE Primary App: LEROI 43867 Dimensions: Outer Diameter: 12.50" (318 mm) Outlet Diameter: 5.50" (140 mm) Length: 9.00" (229 mm) Outlet Length: 1.38" (35 mm)</p>
	<p>Part Number: B085056 Description: AIR PRIMARY, DURALITE Primary App: MAN 51083040015 Dimensions: Outer Diameter: 7.72" (196 mm) Outlet Diameter: 5.98" (152 mm) Length: 10.23" (260 mm)</p>		<p>Part Number: B125011 Description: AIR PRIMARY, DURALITE Primary App: AIR PRIMARY, DURALITE Dimensions: Outer Diameter: 12.50" (318 mm) Outlet Diameter: 5.00" (127 mm) Length: 8.97" (228 mm)</p>
	<p>Part Number: B105002 Description: AIR PRIMARY, DURALITE Primary App: GENERAC, SPARTAN MOTORS Dimensions: Outer Diameter: 10.50" (267 mm) Outlet Diameter: 5.00" (127 mm) Length: 15.00" (381 mm) Outlet Length: 1.38" (35 mm)</p>		<p>Part Number: C045001 Description: AIR PRIMARY, DURALITE Primary App: DEUTZ ALLIS 1356376 & 71356376, FMC 309093 Dimensions: Outer Diameter: 1.50" (38 mm) Outlet Diameter: 1.50" (38 mm) Length: 4.50" (114 mm) Outlet Length: 1.38" (35 mm)</p>
	<p>Part Number: B105006 Description: AIR PRIMARY, DURALITE Primary App: CUMMINS 3912986, ISUZU X14210031, LEROI 438671 Dimensions: Outer Diameter: 10.50" (267 mm) Outlet Diameter: 4.00" (102 mm) Length: 10.50" (267 mm) Outlet Length: 1.38" (35 mm)</p>		<p>Part Number: C045002 Description: AIR PRIMARY, DURALITE Primary App: AIR CLEANER, DURALITE ECC 04* Dimensions: Outer Diameter: 4.50" (114 mm) Outlet Diameter: 1.50" (38 mm) Length: 8.00" (203 mm) Outlet Length: 1.38" (35 mm)</p>
	<p>Part Number: C055002 Description: AIR PRIMARY, DURALITE Primary App: GEHL CO 75986 & 79388, GENERAC CORP 73912 Dimensions: Outer Diameter: 5.50" (140 mm) Outlet Diameter: 1.75" (44 mm) Length: 7.00" (178 mm) Outlet Length: 1.38" (35 mm)</p>		<p>Part Number: C055002 Description: AIR PRIMARY, DURALITE Primary App: GEHL CO 75986 & 79388, GENERAC CORP 73912 Dimensions: Outer Diameter: 5.50" (140 mm) Outlet Diameter: 1.75" (44 mm) Length: 7.00" (178 mm) Outlet Length: 1.38" (35 mm)</p>

 <p>Part Number: C055003 Description: AIR PRIMARY, DURALITE Primary App: DEUTZ ALLIS 900025380434, MURPHY DIESEL MD43843 Dimensions: Outer Diameter: 5.50" (140 mm) Outlet Diameter: 1.75" (44 mm) Length: 4.00" (102 mm) Outlet Length: 1.38" (35 mm)</p>	 <p>Part Number: C085003 Description: AIR PRIMARY, DURALITE Primary App: LISTER DIESEL 000-03043, TIPPECANOE 3919046 Dimensions: Outer Diameter: 8.50" (216 mm) Outlet Diameter: 3.00" (76 mm) Length: 5.00" (127 mm) Outlet Length: 1.38" (35 mm)</p>
 <p>Part Number: C065001 Description: AIR PRIMARY, DURALITE Primary App: E-Z GO CART 21959G1, JACOBSEN 330811 Dimensions: Outer Diameter: 6.50" (165 mm) Outlet Diameter: 2.00" (51 mm) Length: 4.00" (102 mm) Outlet Length: 1.38" (35 mm)</p>	 <p>Part Number: C085004 Description: AIR PRIMARY, DURALITE Primary App: CUMMINS 3908719, LEROI 438672 Dimensions: Outer Diameter: 8.50" (216 mm) Outlet Diameter: 3.00" (76 mm) Length: 9.50" (241 mm) Outlet Length: 1.38" (35 mm)</p>
 <p>Part Number: C065002 Description: AIR PRIMARY, DURALITE Primary App: FIAT-ALLIS 73253611 Dimensions: Outer Diameter: 6.50" (165 mm) Outlet Diameter: 1.93" (49 mm) Length: 7.50" (190 mm) Outlet Length: 1.38" (35 mm)</p>	 <p>Part Number: C085005 Description: AIR PRIMARY, DURALITE Primary App: LEROI 43867 Dimensions: Outer Diameter: 8.50" (216 mm) Outlet Diameter: 2.43" (62 mm) Length: 5.00" (127 mm) Outlet Length: 1.38" (35 mm)</p>
 <p>Part Number: C065003 Description: AIR PRIMARY, DURALITE Primary App: YANMAR Dimensions: Outer Diameter: 6.50" (165 mm) Outlet Diameter: 2.25" (57 mm) Length: 5.00" (127 mm) Outlet Length: 1.38" (35 mm)</p>	 <p>Part Number: C085006 Description: AIR PRIMARY, DURALITE Primary App: ISUZU X14210031 Dimensions: Outer Diameter: 8.50" (216 mm) Outlet Diameter: 2.43" (62 mm) Length: 9.50" (241 mm) Outlet Length: 1.38" (35 mm)</p>
 <p>Part Number: C065015 Description: AIR PRIMARY, DURALITE Primary App: CARRIER TRANSICOLD 30-01077-01/16781 Dimensions: Outer Diameter: 6.50" (165 mm) Outlet Diameter: 2.00" (51 mm) Length: 9.00" (229 mm) Outlet Length: 1.38" (35 mm)</p>	 <p>Part Number: C085041 Description: AIR PRIMARY, DURALITE Primary App: SAME AS C085004 WITH INNER LINER ADDED Dimensions: Outer Diameter: 8.50" (216 mm) Outlet Diameter: 3.00" (76 mm) Length: 9.50" (241 mm) Outlet Length: 1.38" (35 mm)</p>
 <p>Part Number: C065051 Description: AIR PRIMARY, DURALITE Primary App: THERMOKING 117400 Dimensions: Outer Diameter: 6.58" (167 mm) Outlet Diameter: 1.30" (33 mm) Length: 10.00" (254 mm)</p>	 <p>Part Number: C085043 Description: AIR PRIMARY, DURALITE Primary App: SAME AS C085006 WITH INNER LINER ADDED Dimensions: Outer Diameter: 8.50" (216 mm) Outlet Diameter: 2.50" (64 mm) Length: 9.50" (241 mm) Outlet Length: 1.38" (35 mm)</p>
 <p>Part Number: C085001 Description: AIR PRIMARY, DURALITE Primary App: BRODERSON 60012047 Dimensions: Outer Diameter: 8.50" (216 mm) Outlet Diameter: 2.50" (64 mm) Length: 4.00" (102 mm) Outlet Length: 1.38" (35 mm)</p>	 <p>Part Number: C085061 Description: AIR PRIMARY, DURALITE Primary App: MTU 160942802 Dimensions: Outer Diameter: 8.50" (216 mm) Outlet Diameter: 3.00" (76 mm) Length: 11.51" (292 mm)</p>
 <p>Part Number: C085002 Description: AIR PRIMARY, DURALITE Primary App: FIAT ALLIS 73253613, GENERAC CORP 73267 Dimensions: Outer Diameter: 8.50" (216 mm) Outlet Diameter: 2.43" (62 mm) Length: 6.50" (165 mm) Outlet Length: 1.38" (35 mm)</p>	 <p>Part Number: C105003 Description: AIR PRIMARY, DURALITE Primary App: LEROI 438673 Dimensions: Outer Diameter: 10.50" (267 mm) Outlet Diameter: 3.93" (100 mm) Length: 6.00" (152 mm) Outlet Length: 1.38" (35 mm)</p>
 <p>Part Number: C105004 Description: AIR PRIMARY, DURALITE Primary App: GRIMMER-SCHMIDT, CUMMINS Dimensions: Outer Diameter: 10.50" (267 mm) Outlet Diameter: 4.00" (102 mm) Length: 10.50" (267 mm) Outlet Length: 1.38" (35 mm)</p>	 <p>Part Number: C105004 Description: AIR PRIMARY, DURALITE Primary App: GRIMMER-SCHMIDT, CUMMINS Dimensions: Outer Diameter: 10.50" (267 mm) Outlet Diameter: 4.00" (102 mm) Length: 10.50" (267 mm) Outlet Length: 1.38" (35 mm)</p>

 <p>Part Number: C105017 Description: AIR PRIMARY, DURALITE Primary App: SAME AS C105004 WITH INNER LINER ADDED Dimensions: Outer Diameter: 10.50" (267 mm) Outlet Diameter: 4.00" (102 mm) Length: 10.50" (267 mm) Outlet Length: 1.38" (35 mm)</p>	 <p>Part Number: D065008 Description: AIR PRIMARY, DURALITE Primary App: FREIGHTLINER, THERMOKING 11-5978 Dimensions: Outer Diameter: 6.50" (165 mm) Outlet Diameter: 2.00" (51 mm) Length: 9.00" (229 mm) Outlet Length: 1.38" (35 mm)</p>
 <p>Part Number: C105028 Description: AIR PRIMARY, DURALITE Primary App: JOHN DEERE RE63779A Dimensions: Outer Diameter: 10.50" (267 mm) Outlet Diameter: 4.00" (102 mm) Length: 6.00" (152 mm) Outlet Length: 1.38" (35 mm)</p>	 <p>Part Number: E500667 Description: AIR PRIMARY, FINNED Primary App: KOMATSU 848101113 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 2.47" (63 mm) Length: 5.71" (145 mm) Gasket ID: 3.09" (79 mm)</p>
 <p>Part Number: C125004 Description: AIR PRIMARY, DURALITE Primary App: FIAT ALLIS 73253513, PERKINS Dimensions: Outer Diameter: 12.50" (318 mm) Outlet Diameter: 5.00" (127 mm) Length: 11.00" (279 mm) Outlet Length: 1.38" (35 mm)</p>	 <p>Part Number: EAF5000 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON FWA14, FWG14 A/C Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.72" (171 mm) Length: 12.00" (305 mm) Gasket OD: 0.53" (13 mm)</p>
 <p>Part Number: C125017 Description: AIR PRIMARY, DURALITE Primary App: JOHN DEERE RE64564 Dimensions: Outer Diameter: 12.50" (318 mm) Outlet Diameter: 5.00" (127 mm) Length: 11.00" (279 mm) Outlet Length: 1.38" (35 mm)</p>	 <p>Part Number: EAF5001 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON FWA16, FWG16 A/C Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.72" (196 mm) Length: 14.00" (356 mm) Gasket OD: 0.53" (13 mm)</p>
<p>Part Number: C125020 Description: AIR PRIMARY, DURALITE Primary App: MTU 140948002 Dimensions: Outer Diameter: 12.50" (318 mm) Outlet Diameter: 5.00" (127 mm) Length: 8.01" (204 mm)</p>	 <p>Part Number: EAF5002 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON FHG16 A/C Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 18.00" (457 mm) Gasket OD: 0.66" (17 mm)</p>
 <p>Part Number: D045003 Description: AIR PRIMARY, DURALITE Primary App: INGERSOLL RAND 8524575 Dimensions: Outer Diameter: 4.50" (114 mm) Outlet Diameter: 1.50" (38 mm) Length: 4.50" (114 mm) Outlet Length: 1.38" (35 mm)</p>	 <p>Part Number: EAF5007 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON EBA13 A/C Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 21.82" (554 mm)</p>
 <p>Part Number: D045004 Description: AIR PRIMARY, DURALITE Primary App: JOHN DEERE AM101283 Dimensions: Outer Diameter: 4.50" (114 mm) Outlet Diameter: 1.50" (38 mm) Length: 6.00" (152 mm) Outlet Length: 1.38" (35 mm)</p>	 <p>Part Number: EAF5008 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON EBA15 A/C Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 22.00" (559 mm)</p>
 <p>Part Number: D055004 Description: AIR PRIMARY, DURALITE Primary App: GEHL CO 77628, JOHN DEERE AM100258 Dimensions: Outer Diameter: 5.50" (140 mm) Outlet Diameter: 1.75" (44 mm) Length: 7.00" (178 mm) Outlet Length: 1.38" (35 mm)</p>	 <p>Part Number: EAF5014 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON EBA13 A/C Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 15.00" (381 mm)</p>
 <p>Part Number: D065003 Description: AIR PRIMARY, DURALITE Primary App: FREIGHTLINER, TELEDYNE Dimensions: Outer Diameter: 6.50" (165 mm) Outlet Diameter: 2.00" (51 mm) Length: 4.00" (102 mm) Outlet Length: 1.38" (35 mm)</p>	 <p>Part Number: EAF5015 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON EBB14 OR EBG14 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.72" (196 mm) Length: 18.00" (457 mm)</p>

	<p>Part Number: EAF5016 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON EBA13 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 26.00" (660 mm)</p>		<p>Part Number: EAF5039 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON STG16 A/C Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 17.88" (454 mm) Gasket OD: 0.90" (23 mm)</p>
	<p>Part Number: EAF5024 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON EBA11 Konepac Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.95" (177 mm) Length: 28.00" (711 mm) Gasket OD: 7.50" (190 mm) Gasket ID: 3.96" (101 mm)</p>		<p>Part Number: EAF5040 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON SRG20, SRG29 A/C Dimensions: Outer Diameter: 17.58" (447 mm) Inner Diameter: 12.22" (310 mm) Length: 23.03" (585 mm) Gasket OD: 0.90" (23 mm)</p>
	<p>Part Number: EAF5025 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON EBA09 KONEPAC Dimensions: Outer Diameter: 8.66" (220 mm) Inner Diameter: 5.21" (132 mm) Length: 28.00" (711 mm) Gasket OD: 5.74" (146 mm) Gasket ID: 2.21" (56 mm)</p>		<p>Part Number: EAF5041 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON STG14 A/C Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 16.00" (406 mm)</p>
	<p>Part Number: EAF5026 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON EBA13 KONEPAC Dimensions: Outer Diameter: 12.75" (324 mm) Inner Diameter: 8.32" (211 mm) Length: 28.00" (711 mm) Gasket OD: 9.81" (249 mm) Gasket ID: 5.38" (137 mm)</p>		<p>Part Number: EAF5042 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON STG16 A/C Dimensions: Outer Diameter: 14.68" (373 mm) Inner Diameter: 10.34" (263 mm) Length: 23.88" (607 mm) Gasket OD: 0.90" (23 mm)</p>
	<p>Part Number: EAF5027 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON EBA13 KONEPAC Dimensions: Outer Diameter: 12.75" (324 mm) Inner Diameter: 8.32" (211 mm) Length: 23.99" (609 mm) Gasket OD: 9.81" (249 mm) Gasket ID: 5.38" (137 mm)</p>		<p>Part Number: EAF5043 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON FVG14 A/C Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 19.88" (505 mm) Gasket OD: 0.90" (23 mm)</p>
	<p>Part Number: EAF5028 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON EBB12 OR EBG12 A/C Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 16.00" (406 mm)</p>		<p>Part Number: EAF5044 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON STG12 A/C Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 13.76" (350 mm) Gasket OD: 0.90" (23 mm)</p>
	<p>Part Number: EAF5034 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON FHG12 A/C Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.85" (123 mm) Length: 13.00" (330 mm)</p>		<p>Part Number: EAF5046 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON FHG14 A/C Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.73" (171 mm) Length: 16.00" (406 mm) Gasket OD: 0.66" (17 mm)</p>
	<p>Part Number: EAF5035 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON FWA12, FWG12 A/C Dimensions: Outer Diameter: 9.22" (234 mm) Inner Diameter: 4.84" (123 mm) Length: 10.00" (254 mm) Gasket OD: 0.53" (13 mm)</p>		<p>Part Number: EAF5048 Description: AIR PRIMARY, ULTRA-WEB® Primary App: FRAM CA2550 Dimensions: Outer Diameter: 9.50" (241 mm) Inner Diameter: 6.89" (175 mm) Length: 27.44" (697 mm)</p>
	<p>Part Number: EAF5038 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON SRG20, SRG29 A/C Dimensions: Outer Diameter: 17.62" (448 mm) Inner Diameter: 11.07" (281 mm) Length: 23.06" (586 mm) Gasket OD: 0.90" (23 mm)</p>		<p>Part Number: EAF5049 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON FVG16 A/C Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 24.28" (617 mm) Gasket OD: 0.94" (24 mm)</p>

	<p>Part Number: EAF5056 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON EBB14 A/C Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.72" (196 mm) Length: 15.19" (386 mm) Gasket OD: 0.66" (17 mm)</p>		<p>Part Number: EAF5096 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON EBB15 A/C Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.72" (196 mm) Length: 15.00" (381 mm)</p>
	<p>Part Number: EAF5057 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON FWD16 OR FVG16 A/C Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 17.03" (433 mm) Gasket OD: 0.94" (24 mm)</p>		<p>Part Number: EAF5098 Description: AIR PRIMARY, ULTRA-WEB® RS Primary App: Volvo 8076195 Dimensions: Outer Diameter: 13.09" (332 mm) Inner Diameter: 7.69" (195 mm) Length: 15.94" (405 mm)</p>
	<p>Part Number: EAF5061 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON EBA11 A/C Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.95" (177 mm) Length: 28.00" (711 mm) Gasket OD: 7.50" (190 mm) Gasket ID: 3.96" (101 mm)</p>		<p>Part Number: EAF5099 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON EBB16 A/C Dimensions: Outer Diameter: 13.84" (352 mm) Inner Diameter: 7.47" (190 mm) Length: 18.06" (459 mm)</p>
	<p>Part Number: EAF5065 Description: AIR PRIMARY, ULTRA-WEB® Primary App: MCI BUS 9G-3-37 Dimensions: Outer Diameter: 15.09" (383 mm) Inner Diameter: 8.70" (221 mm) Length: 15.34" (390 mm) Gasket OD: 0.75" (19 mm)</p>		<p>Part Number: EAF5100 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON ERA13 A/C, FREIGHTLINER, PETERBILT Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.78" (172 mm) Length: 23.44" (595 mm) Gasket OD: 11.40" (290 mm)</p>
	<p>Part Number: EAF5066 Description: AIR PRIMARY, ULTRA-WEB® Primary App: FREIGHTLINER Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.15" (131 mm) Length: 14.49" (368 mm)</p>		<p>Part Number: EAF5101 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON ERA15 AIR CLNR, KENWORTH, PETERBILT Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 7.44" (189 mm) Length: 25.44" (646 mm) Gasket OD: 13.06" (332 mm)</p>
	<p>Part Number: EAF5067 Description: AIR PRIMARY, ULTRA-WEB® Primary App: GM 15619013, FORD F3HZ9601A Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.15" (131 mm) Length: 12.28" (312 mm)</p>		<p>Part Number: EAF5102 Description: AIR PRIMARY, ULTRA-WEB® Primary App: VORTOX Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 26.00" (660 mm) Gasket OD: 0.53" (13 mm)</p>
	<p>Part Number: EAF5069 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON EPG15 A/C Dimensions: Outer Diameter: 13.09" (332 mm) Inner Diameter: 6.78" (172 mm) Length: 14.76" (375 mm)</p>		<p>Part Number: EAF5104 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON EPG15 AIR CLEANER, NAVISTAR Dimensions: Outer Diameter: 13.06" (332 mm) Inner Diameter: 6.78" (172 mm) Length: 18.15" (461 mm)</p>
	<p>Part Number: EAF5074 Description: AIR PRIMARY, ULTRA-WEB® Primary App: MACK, RVI Dimensions: Outer Diameter: 8.66" (220 mm) Inner Diameter: 5.20" (132 mm) Length: 15.00" (381 mm) Gasket OD: 9.72" (247 mm) Gasket ID: 3.03" (77 mm)</p>		<p>Part Number: EAF5105 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON EPG11 AIR CLEANER, FREIGHTLINER FLN Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.15" (131 mm) Length: 18.50" (470 mm)</p>
	<p>Part Number: EAF5095 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON EBB16 A/C Dimensions: Outer Diameter: 13.84" (352 mm) Inner Diameter: 9.47" (241 mm) Length: 15.50" (394 mm)</p>		<p>Part Number: EAF5106 Description: AIR PRIMARY, ULTRA-WEB® RS Primary App: FREIGHTLINER COE Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.80" (147 mm) Length: 23.03" (585 mm)</p>

	<p>Part Number: EAF5107 Description: AIR PRIMARY, ULTRA-WEB® RS Primary App: KW T2000 FROM 11/98 Dimensions: Outer Diameter: 11.10" (282 mm) Inner Diameter: 6.77" (172 mm) Length: 15.15" (385 mm)</p>		<p>Part Number: EAF5150 Description: AIR PRIMARY, ULTRA-WEB® RS Primary App: DONALDSON ERA15 RADIAL SEAL AIRCLEANER Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 7.44" (189 mm) Length: 25.38" (645 mm)</p>
	<p>Part Number: EAF5108 Description: AIR PRIMARY, ULTRA-WEB® RS Primary App: MACK 57MD46M Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.80" (147 mm) Length: 25.04" (636 mm)</p>		<p>Part Number: EAF5151 Description: AIR PRIMARY, ULTRA-WEB® RS Primary App: PETERBILT, DONALDSON ERA15 Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 7.44" (189 mm) Length: 21.38" (543 mm)</p>
	<p>Part Number: EAF5109 Description: AIR PRIMARY, ULTRA-WEB® RS Primary App: KWT2000 THRU 10/98 Dimensions: Outer Diameter: 11.48" (292 mm) Inner Diameter: 5.80" (147 mm) Length: 15.15" (385 mm)</p>		<p>Part Number: EAF5152 Description: AIR PRIMARY, ULTRA-WEB® RS Primary App: DONALDSON SSG SERIES RADIAL SEAL AIR CLEANERS Dimensions: Outer Diameter: 17.76" (451 mm) Inner Diameter: 11.46" (291 mm) Length: 24.06" (611 mm)</p>
	<p>Part Number: EAF5112 Description: AIR PRIMARY, ULTRA-WEB® Primary App: KOMATSU 6114-80-7101-P, 600-181-2500 Dimensions: Outer Diameter: 9.73" (247 mm) Inner Diameter: 5.67" (144 mm) Length: 12.56" (319 mm)</p>		<p>Part Number: EAF5153 Description: AIR PRIMARY, ULTRA-WEB® RS Primary App: DONALDSON SSG SERIES RADIAL SEAL AIR CLEANERS Dimensions: Outer Diameter: 17.76" (451 mm) Inner Diameter: 11.46" (291 mm) Length: 29.25" (743 mm)</p>
	<p>Part Number: EAF5114 Description: AIR PRIMARY, ULTRA-WEB® RS Primary App: MACK 57MD320M Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.80" (147 mm) Length: 25.04" (636 mm)</p>	<p>Part Number: EAF5156 Description: AIR PRIMARY, ULTRA-WEB® Primary App: Donaldson FRG18 Dimensions: Outer Diameter: 14.29" (363 mm) Inner Diameter: 8.98" (228 mm) Length: 24.41" (620 mm)</p>	
	<p>Part Number: EAF5116 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON ENDURANCE Dimensions: Outer Diameter: 12.31" (313 mm) Inner Diameter: 6.99" (178 mm) Length: 20.08" (510 mm)</p>		<p>Part Number: EAF5187 Description: AIR PRIMARY, ULTRA-WEB® Primary App: FORD E3TZ9601C Dimensions: Outer Diameter: 11.68" (297 mm) Inner Diameter: 8.11" (206 mm) Length: 5.00" (127 mm)</p>
	<p>Part Number: EAF5127 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON FTG13" AIR CLEANERS Dimensions: Outer Diameter: 10.86" (276 mm) Inner Diameter: 6.50" (165 mm) Length: 20.00" (508 mm)</p>		<p>Part Number: EAF5188 Description: AIR PRIMARY, ULTRA-WEB® Primary App: IHC 588213C1 Dimensions: Outer Diameter: 11.68" (297 mm) Inner Diameter: 8.11" (206 mm) Length: 7.00" (178 mm)</p>
	<p>Part Number: EAF5147 Description: AIR PRIMARY, ULTRA-WEB® RS Primary App: DONALDSON ERA11 AIR CLNR, FRTLNR CLASSIC Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.16" (131 mm) Length: 24.61" (625 mm)</p>	<p>Part Number: EAF5189 Description: AIR PRIMARY, ULTRA-WEB® Primary App: FORD Dimensions: Outer Diameter: 13.84" (352 mm) Inner Diameter: 6.69" (170 mm) Length: 10.00" (254 mm)</p>	
	<p>Part Number: EAF5148 Description: AIR PRIMARY, ULTRA-WEB® RS Primary App: DONALDSON ERA11 RADIAL SEAL AIRCLEANER Dimensions: Outer Diameter: 9.64" (245 mm) Inner Diameter: 5.15" (131 mm) Length: 21.42" (544 mm)</p>	<p>Part Number: EAF5194 Description: AIR PRIMARY, ULTRA-WEB® Primary App: DONALDSON EBA11 A/C Dimensions: Outer Diameter: 8.84" (225 mm) Inner Diameter: 5.84" (148 mm) Length: 28.00" (711 mm)</p>	
	<p>Part Number: EAF5149 Description: AIR PRIMARY, ULTRA-WEB® RS Primary App: DONALDSON ERA13 RADIAL SEAL AIRCLEANER Dimensions: Outer Diameter: 11.10" (282 mm) Inner Diameter: 5.82" (148 mm) Length: 21.19" (538 mm)</p>	<p>Part Number: ECF4081 Description: COOLANT SPIN-ON Primary App: EXTENDED SERVICE 150K NON CHEMICAL COOLANT FILTER, VOLVO Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: M16 x 1.5 Length: 4.20" (107 mm)</p>	

	<p>Part Number: ECF4085 Description: COOLANT SPIN-ON Primary App: EXTENDED SERVICE 150K NON CHEMICAL COOLANT FILTER Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 11/16-16 Length: 5.33" (135 mm) Efficiency 99% @ 14 Micron</p>		<p>Part Number: ELF2501 Description: LUBE SPIN-ON FULL FLOW Primary App: EXTENDED SERVICE PRE EPA 2007 COMPLIANT CUMMINS ISX, ISM ENGINES Dimensions: Outer Diameter: 4.67" (119 mm) Thread Size: M95 x 2.5 Length: 11.70" (297 mm) Gasket OD: 4.64" (118 mm) Gasket ID: 3.97" (101 mm) Efficiency 99% @ 15 Micron</p>
	<p>Part Number: ECF4086 Description: COOLANT SPIN-ON Primary App: EXTENDED SERVICE 150K NON CHEMICAL COOLANT FILTER, VOLVO Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: M16 x 1.5 Length: 5.35" (136 mm) Efficiency 99% @ 14 Micron</p>		<p>Part Number: ELF2502 Description: LUBE SPIN-ON FULL FLOW Primary App: EXTENDED SERVICE PRE EPA 2007 COMPLIANT CATERPILLAR ENGINES Dimensions: Outer Diameter: 5.33" (135 mm) Thread Size: 1 1/2-16 Length: 12.13" (308 mm) Gasket OD: 4.33" (110 mm) Gasket ID: 3.93" (100 mm) Efficiency 99% @ 15 Micron</p>
	<p>Part Number: ECF4088 Description: COOLANT SPIN-ON Primary App: EXTENDED SERVICE 150K COOLANT WITH CHEMICAL Dimensions: Outer Diameter: 3.67" (93 mm) Thread Size: 11/16-16 Length: 5.35" (136 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Efficiency 99% @ 14 Micron</p>		<p>Part Number: ELF2504 Description: LUBE SPIN-ON FULL FLOW Primary App: EXTENDED SERVICE FOR PRE EPA 2007 COMPLIANT MACK, VOLVO Dimensions: Outer Diameter: 4.23" (107 mm) Thread Size: 1 1/8-16 Length: 10.31" (262 mm) Gasket OD: 3.89" (99 mm) Gasket ID: 3.54" (90 mm) Efficiency 99% @ 22 Micron</p>
	<p>Part Number: ECF4089 Description: COOLANT SPIN-ON Primary App: EXTENDED SERVICE 150K COOLANT, VOLVO Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: M16 x 1.5 Length: 5.35" (136 mm) Efficiency 99% @ 14 Micron</p>		<p>Part Number: ELF3998 Description: LUBE SPIN-ON FULL FLOW Primary App: DETROIT DIESEL SERIES 60 ENGINES Dimensions: Outer Diameter: 4.65" (118 mm) Thread Size: 1 5/8-12 Length: 10.24" (260 mm) Gasket OD: 4.31" (109 mm) Gasket ID: 3.84" (98 mm) Efficiency 99% @ 15 Micron</p>
	<p>Part Number: EFF0047 Description: FUEL SPIN-ON SECONDARY Primary App: DETROIT DIESEL ENGINES Dimensions: Outer Diameter: 4.67" (119 mm) Thread Size: 1 1/16-16 Length: 8.94" (227 mm) Gasket OD: 4.32" (110 mm) Gasket ID: 3.85" (98 mm) Efficiency 99% @ 5 Micron</p>		<p>Part Number: ELF7300 Description: LUBE SPIN-ON COMBINATION Primary App: CUMMINS ENGINES Dimensions: Outer Diameter: 4.65" (118 mm) Thread Size: 2 1/4-12 Length: 11.75" (298 mm) Gasket OD: 4.68" (119 mm) Gasket ID: 4.00" (102 mm) Efficiency 99% @ 15 Micron</p>
	<p>Part Number: EFF7917 Description: FUEL SPIN-ON SECONDARY Primary App: DETROIT DIESEL 23530645 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 13/16-12 Length: 6.85" (174 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.05" (77 mm) Efficiency 99% @ 5 Micron</p>		<p>Part Number: ELF7345 Description: LUBE SPIN-ON FULL FLOW Primary App: CUMMINS 4B 3.9 SERIES LUBE Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-16 Length: 5.35" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 15 Micron</p>
	<p>Part Number: EFF9092 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CAT ENGINES Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: 1-14 Length: 10.31" (262 mm) Gasket OD: 2.82" (72 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 5 Micron</p>		<p>Part Number: ELF7349 Description: LUBE SPIN-ON FULL FLOW Primary App: CUMMINS 4B & 6B SERIES LUBE Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-16 Length: 6.85" (174 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 15 Micron</p>
	<p>Part Number: ELF2500 Description: LUBE SPIN-ON FULL FLOW Primary App: EXTENDED SERVICE PRE EPA 2007 COMPLIANT DETROIT DIESEL SERIES 60, 50 ENGINES Dimensions: Outer Diameter: 4.65" (118 mm) Thread Size: 1 5/8-12 Length: 10.24" (260 mm) Gasket OD: 4.33" (110 mm) Gasket ID: 3.87" (98 mm) Efficiency 99% @ 15 Micron</p>		<p>Part Number: ELF7367 Description: LUBE SPIN-ON FULL FLOW Primary App: NAVISTAR 1819452C1 Dimensions: Outer Diameter: 5.33" (135 mm) Thread Size: M36 x 1.5 Length: 12.13" (308 mm) Gasket OD: 4.29" (109 mm) Gasket ID: 3.89" (99 mm) Relief Valve Setting: 26-30 PSI (1.8-2.1 Bar)</p>



Part Number: **ELFW7405**
 Description: **LUBE SPIN-ON FULL FLOW**
 Primary App: **CAT ENGINES**
 Dimensions: Outer Diameter: 4.65" (118 mm)
 Thread Size: 1 1/2-16
 Length: 11.73" (298 mm)
 Gasket OD: 4.32" (110 mm)
 Gasket ID: 3.85" (98 mm)
 Efficiency 99% @ 15 Micron



Part Number: **ELFW7483**
 Description: **LUBE SPIN-ON FULL FLOW**
 Primary App: **MACK/VOLVO ENGINES**
 Dimensions: Outer Diameter: 4.25" (108 mm)
 Thread Size: 1 1/8-16
 Length: 10.31" (262 mm)
 Gasket OD: 3.88" (99 mm)
 Gasket ID: 3.55" (90 mm)
 Efficiency 99% @ 15 Micron



Part Number: **ELFW670**
 Description: **LUBE SPIN-ON FULL FLOW**
 Primary App: **CUMMINS AND DETROIT DIESEL ENGINES**
 Dimensions: Outer Diameter: 4.65" (118 mm)
 Thread Size: 1 1/2-12
 Length: 10.24" (260 mm)
 Gasket OD: 4.31" (109 mm)
 Gasket ID: 3.84" (98 mm)
 Efficiency 99% @ 15 Micron



Part Number: **ELFW690**
 Description: **LUBE CARTRIDGE**
 Primary App: **MERCEDES**
 Dimensions: Outer Diameter: 4.76" (121 mm)
 Inner Diameter: 0.56" (14 mm)
 Length: 10.37" (264 mm)



Part Number: **ELFW739**
 Description: **LUBE SPIN-ON FULL FLOW**
 Primary App: **CAT ENGINES**
 Dimensions: Outer Diameter: 4.25" (108 mm)
 Thread Size: 1 1/8-16
 Length: 10.31" (262 mm)
 Gasket OD: 3.88" (99 mm)
 Gasket ID: 3.55" (90 mm)
 Efficiency 99% @ 15 Micron



Part Number: **ELFW900**
 Description: **LUBE SPIN-ON FULL FLOW**
 Primary App: **CUMMINS SIGNATURE & ISM ENGINES**
 Dimensions: Outer Diameter: 4.65" (118 mm)
 Thread Size: M95 x 2.5
 Length: 11.70" (297 mm)
 Gasket OD: 4.68" (119 mm)
 Gasket ID: 4.00" (102 mm)
 Efficiency 99% @ 15 Micron



Part Number: **ELFW947**
 Description: **LUBE SPIN-ON FULL FLOW**
 Primary App: **DETROIT DIESEL ENGINES**
 Dimensions: Outer Diameter: 4.65" (118 mm)
 Thread Size: 1 1/2-12
 Length: 6.22" (158 mm)
 Gasket OD: 4.31" (109 mm)
 Gasket ID: 3.84" (98 mm)
 Efficiency 99% @ 15 Micron



Part Number: **P015835**
 Description: **AIR PRIMARY**
 Primary App: **IHC, PACCAR**
 Dimensions: Outer Diameter: 6.84" (174 mm)
 Inner Diameter: 4.24" (108 mm)
 Length: 8.00" (203 mm)




Part Number: **P015837**
 Description: **AIR PRIMARY**
 Primary App: **FWD OSHKOSH**
 Dimensions: Outer Diameter: 9.21" (234 mm)
 Inner Diameter: 6.60" (168 mm)
 Length: 10.00" (254 mm)



Part Number: **P015838**
 Description: **AIR PRIMARY**
 Primary App: **FWD OSHKOSH**
 Dimensions: Outer Diameter: 10.40" (264 mm)
 Inner Diameter: 7.79" (198 mm)
 Length: 12.00" (305 mm)



Part Number: **P017665**
 Description: **AIR PRIMARY**
 Primary App: **IHC, MACK, TEREX, WABCO**
 Dimensions: Outer Diameter: 8.40" (213 mm)
 Inner Diameter: 5.78" (147 mm)
 Length: 9.00" (229 mm)
 Bolt Hole Diameter: 0.53" (13 mm)



Part Number: **P041028**
 Description: **AIR PANEL**
 Primary App: **AIRMAZE 126063001**
 Dimensions: Width: 12.00" (305 mm)
 Depth: 2.19" (56 mm)
 Height: 6.00" (152 mm)



Part Number: **P042343**
 Description: **AIR PRIMARY**
 Primary App: **AIR MAZE CD1628500826, IHC**
 Dimensions: Outer Diameter: 12.56" (319 mm)
 Inner Diameter: 7.51" (191 mm)
 Length: 26.88" (683 mm)
 Bolt Hole Diameter: 0.72" (18 mm)



Part Number: **P042345**
 Description: **AIR SAFETY**
 Primary App: **AIR MAZE CD1628500827, IHC**
 Dimensions: Outer Diameter: 7.38" (187 mm)
 Inner Diameter: 6.12" (155 mm)
 Length: 25.38" (645 mm)



Part Number: **P101038**
 Description: **AIR PRIMARY, FINNED**
 Primary App: **GMC MURPHY DIESEL**
 Dimensions: Outer Diameter: 7.93" (201 mm)
 Inner Diameter: 3.57" (91 mm)
 Length: 12.00" (305 mm)
 Gasket ID: 4.12" (105 mm)
 Minor OD: 0.53" (13 mm)



Part Number: **P102052**
 Description: **AIR PANEL, ENGINE**
 Primary App: **CAT 5L-6389**
 Dimensions: Width: 19.50" (495 mm)
 Depth: 2.19" (56 mm)
 Height: 19.50" (495 mm)



Part Number: **P102745**
 Description: **AIR PRIMARY, FINNED**
 Primary App: **FWG04, CLARK, TORO, ADVANCE MACHINE**
 Dimensions: Outer Diameter: 3.26" (83 mm)
 Length: 7.00" (178 mm)
 Gasket ID: 1.97" (50 mm)
 Minor OD: 0.42" (11 mm)

	<p>Part Number: P103688 Description: AIR PANEL, VENTILATION Primary App: CAT, GMC, WHITE MOTOR Dimensions: Width: 24.00" (610 mm) Depth: 2.19" (56 mm) Height: 24.00" (610 mm)</p>		<p>Part Number: P109761 Description: AIR PANEL, VENTILATION Primary App: GARDNER DENVER 5018729 Dimensions: Width: 33.00" (838 mm) Depth: 2.19" (56 mm) Height: 4.00" (102 mm)</p>
	<p>Part Number: P104445 Description: AIR PRIMARY, FINNED Primary App: FIAT ALLIS 73039921 Dimensions: Outer Diameter: 7.93" (201 mm) Inner Diameter: 3.57" (91 mm) Length: 13.00" (330 mm) Gasket ID: 5.38" (137 mm) Minor OD: 0.53" (13 mm)</p>		<p>Part Number: P111098 Description: AIR PANEL, ENGINE Primary App: CAT 6L-4714 Dimensions: Width: 24.00" (610 mm) Depth: 2.19" (56 mm) Height: 24.00" (610 mm)</p>
	<p>Part Number: P105919 Description: AIR PANEL, VENTILATION Primary App: CAT 6L-8485 Dimensions: Width: 15.00" (381 mm) Depth: 2.19" (56 mm) Height: 15.00" (381 mm)</p>		<p>Part Number: P112212 Description: AIR SAFETY Primary App: WHITE FARM 165807A, IHC Dimensions: Outer Diameter: 3.35" (85 mm) Inner Diameter: 2.27" (58 mm) Length: 13.00" (330 mm)</p>
	<p>Part Number: P105958 Description: AIR PANEL, VENTILATION Primary App: BUCYRUS ERIE, UNIT RIG Dimensions: Width: 10.00" (254 mm) Depth: 2.19" (56 mm) Height: 10.00" (254 mm)</p>		<p>Part Number: P112671 Description: AIR PANEL, VENTILATION Primary App: CAT, CRENLO, THERMOKING Dimensions: Width: 10.00" (254 mm) Depth: 2.19" (56 mm) Height: 17.00" (432 mm)</p>
	<p>Part Number: P106680 Description: AIR PANEL, VENTILATION Primary App: JOHN DEERE, IHC, CASE, ALLIS CHALMERS Dimensions: Width: 7.50" (190 mm) Depth: 2.19" (56 mm) Height: 28.00" (711 mm)</p>		<p>Part Number: P112775 Description: AIR PANEL, VENTILATION Primary App: EXCEL, OWATONNA, STEIGER, IHC Dimensions: Width: 5.00" (127 mm) Depth: 2.19" (56 mm) Height: 38.00" (965 mm)</p>
	<p>Part Number: P106965 Description: AIR PANEL, VENTILATION Primary App: ALLIS CHALMERS, TEREX, LETOURNEAU Dimensions: Width: 11.00" (279 mm) Depth: 2.19" (56 mm) Height: 11.00" (279 mm)</p>		<p>Part Number: P113247 Description: AIR PANEL, VENTILATION Primary App: CAT, VERSATILE, WHITE FARM Dimensions: Width: 7.00" (178 mm) Depth: 2.19" (56 mm) Height: 23.50" (597 mm)</p>
	<p>Part Number: P107266 Description: AIR VEE-PAC Primary App: GMC 9034697 Dimensions: Width: 18.00" (457 mm) Depth: 10.84" (275 mm) Length: 30.94" (786 mm) D: 4.57" (116 mm)</p>		<p>Part Number: P113330 Description: AIR PANEL, VENTILATION Primary App: FEMCO CABS, GM 25043797, IR 57059404 Dimensions: Width: 5.00" (127 mm) Depth: 2.19" (56 mm) Height: 24.00" (610 mm)</p>
	<p>Part Number: P108158 Description: AIR PRIMARY Primary App: IHC 702244C1 Dimensions: Outer Diameter: 7.02" (178 mm) Inner Diameter: 4.39" (112 mm) Length: 19.76" (502 mm)</p>		<p>Part Number: P113343 Description: AIR SAFETY Primary App: JOHN DEERE, WHITE FARM Dimensions: Outer Diameter: 4.57" (116 mm) Inner Diameter: 3.49" (89 mm) Length: 15.00" (381 mm)</p>
	<p>Part Number: P108736 Description: AIR PRIMARY, FINNED Primary App: MF 1032762M91 Dimensions: Outer Diameter: 4.08" (104 mm) Inner Diameter: 2.49" (63 mm) Length: 9.00" (229 mm) Gasket ID: 2.58" (66 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P113395 Description: AIR PRIMARY Primary App: FORD C8HZ9601C Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.85" (123 mm) Length: 11.00" (279 mm) Bolt Hole Diameter: 0.66" (17 mm)</p>

	<p>Part Number: P113407 Description: AIR PANEL, VENTILATION Primary App: TEREX, WHITE FARM Dimensions: Width: 7.50" (190 mm) Depth: 2.19" (56 mm) Height: 20.00" (508 mm)</p>		<p>Part Number: P114500 Description: AIR SAFETY Primary App: MF 1037735M91, IHC 529852R5 Dimensions: Outer Diameter: 3.41" (87 mm) Inner Diameter: 2.93" (74 mm) Length: 14.00" (356 mm)</p>
	<p>Part Number: P113703 Description: AIR PRIMARY Primary App: CASE L35975 Dimensions: Outer Diameter: 6.08" (154 mm) Inner Diameter: 3.49" (89 mm) Length: 14.00" (356 mm) Bolt Hole Diameter: 0.66" (17 mm)</p>		<p>Part Number: P114637 Description: AIR PRIMARY Primary App: DONALDSON FVG05 AIR CLEANER Dimensions: Outer Diameter: 4.51" (115 mm) Inner Diameter: 2.54" (65 mm) Length: 14" (355 mm) Gasket OD: 3.52" (89 mm) Gasket ID: 3.15" (80 mm)</p>
	<p>Part Number: P113720 Description: AIR PRIMARY Primary App: CAT, WABCO Dimensions: Outer Diameter: 3.12" (79 mm) Inner Diameter: 1.50" (38 mm) Length: 3.25" (83 mm) Gasket ID: 1.62" (41 mm)</p>		<p>Part Number: P114931 Description: AIR SAFETY Primary App: EUCLID, TEREX, WABCO, CLARK Dimensions: Outer Diameter: 8.64" (219 mm) Inner Diameter: 7.06" (179 mm) Length: 16.66" (423 mm)</p>
	<p>Part Number: P113946 Description: AIR PANEL, VENTILATION Primary App: JOHN DEERE, FARMHAND Dimensions: Width: 15.00" (381 mm) Depth: 2.19" (56 mm) Height: 15.00" (381 mm)</p>		<p>Part Number: P115051 Description: AIR PANEL, VENTILATION Primary App: CRENLO 80255 Dimensions: Width: 5.25" (133 mm) Depth: 2.19" (56 mm) Height: 18.50" (470 mm)</p>
	<p>Part Number: P114101 Description: AIR VEE-PAC Primary App: UNIT RIG 902000 Dimensions: Width: 18.00" (457 mm) Depth: 10.84" (275 mm) Length: 35.44" (900 mm) D: 4.57" (116 mm)</p>		<p>Part Number: P115070 Description: AIR SAFETY Primary App: DONALDSON SRG20, WABCO, LETOURNEAU, UNIT RIG Dimensions: Outer Diameter: 10.86" (276 mm) Inner Diameter: 8.18" (208 mm) Length: 21.68" (551 mm)</p>
	<p>Part Number: P114229 Description: AIR PANEL, VENTILATION Primary App: UNIVERSAL SILENCER Dimensions: Width: 19.38" (492 mm) Depth: 2.19" (56 mm) Height: 24.38" (619 mm)</p>		<p>Part Number: P115690 Description: AIR PANEL, VENTILATION Primary App: JOHN DEERE AH80920 Dimensions: Width: 6.12" (155 mm) Depth: 2.19" (56 mm) Height: 37.00" (940 mm)</p>
	<p>Part Number: P114241 Description: AIR PRIMARY Primary App: ATLAS COPCO, WORTHINGTON Dimensions: Outer Diameter: 7.63" (194 mm) Inner Diameter: 4.29" (109 mm) Length: 16.00" (406 mm)</p>		<p>Part Number: P115889 Description: AIR PRIMARY Primary App: JOHN DEERE A30508, IHC 627127C1 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 6.38" (162 mm)</p>
	<p>Part Number: P114249 Description: AIR PRIMARY Primary App: DONALDSON FVG06 Dimensions: Outer Diameter: 5.43" (138 mm) Inner Diameter: 2.85" (73 mm) Gasket OD: 4.06" (103 mm) Gasket ID: 3.68" (93 mm)</p>		<p>Part Number: P116446 Description: AIR SAFETY Primary App: BUCYRUS ERIE, IR, ONAN, SULLAIR Dimensions: Outer Diameter: 8.24" (209 mm) Inner Diameter: 7.12" (181 mm) Length: 22.00" (559 mm)</p>
	<p>Part Number: P114326 Description: AIR PANEL, VENTILATION Primary App: WHITE FARM 7760810 Dimensions: Width: 11.00" (279 mm) Depth: 2.19" (56 mm) Height: 23.50" (597 mm)</p>		<p>Part Number: P117049 Description: AIR PANEL, VENTILATION Primary App: CRENLO, WHITE FARM Dimensions: Width: 7.00" (178 mm) Depth: 2.19" (56 mm) Height: 47.00" (1194 mm)</p>

	<p>Part Number: P117109 Description: AIR PANEL, VENTILATION Primary App: CLARK, HESSTON, HUPP Dimensions: Width: 6.50" (165 mm) Depth: 2.19" (56 mm) Height: 33.00" (838 mm)</p>		<p>Part Number: P118785 Description: AIR SAFETY Primary App: CLARK, MASSEY FERGUSON Dimensions: Outer Diameter: 2.46" (62 mm) Inner Diameter: 1.91" (49 mm) Length: 8.26" (210 mm)</p>
	<p>Part Number: P117327 Description: AIR PRIMARY Primary App: UNIT RIG 23486, WHITE MOTOR 027090093 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 13.00" (330 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 8.12" (206 mm)</p>		<p>Part Number: P118951 Description: AIR PANEL, VENTILATION Primary App: CAB VENT PANEL Dimensions: Width: 16.00" (406 mm) Depth: 2.19" (56 mm) Height: 24.00" (610 mm)</p>
	<p>Part Number: P117383 Description: AIR PRIMARY Primary App: LINCOLN ELECTRIC M122841 Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.73" (171 mm) Length: 12.00" (305 mm) Bolt Hole Diameter: 0.53" (13 mm) Gasket ID: 9.56" (242 mm)</p>		<p>Part Number: P119135 Description: AIR PRIMARY, FINNED Primary App: MASSEY FERGUSON, NEW HOLLAND Dimensions: Outer Diameter: 5.23" (133 mm) Inner Diameter: 3.65" (93 mm) Length: 15.00" (381 mm) Gasket ID: 3.95" (100 mm) Minor OD: 0.66" (17 mm)</p>
	<p>Part Number: P117624 Description: AIR PRIMARY, FINNED Primary App: CASE A43264 Dimensions: Outer Diameter: 7.92" (201 mm) Inner Diameter: 5.31" (135 mm) Length: 13.00" (330 mm) Gasket ID: 6.36" (162 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P119136 Description: AIR PRIMARY Primary App: MASSEY FERGUSON 1428748M91 Dimensions: Outer Diameter: 6.09" (155 mm) Inner Diameter: 3.47" (88 mm) Length: 15.00" (381 mm)</p>
	<p>Part Number: P117781 Description: AIR SAFETY Primary App: DONALDSON SRG, WABCO, LETOURNEAU, UNIT RIG Dimensions: Outer Diameter: 11.87" (301 mm) Inner Diameter: 10.25" (260 mm) Length: 22.02" (559 mm)</p>		<p>Part Number: P119184 Description: AIR PRIMARY Primary App: GMC Dimensions: Outer Diameter: 13.84" (352 mm) Inner Diameter: 11.23" (285 mm) Length: 7.00" (178 mm) Bolt Hole Diameter: 0.53" (13 mm) Gasket ID: 11.57" (294 mm)</p>
	<p>Part Number: P118157 Description: AIR PRIMARY Primary App: EUCLID, TEREX Dimensions: Outer Diameter: 13.84" (352 mm) Inner Diameter: 11.23" (285 mm) Length: 14.00" (356 mm) Bolt Hole Diameter: 0.53" (13 mm)</p>		<p>Part Number: P119370 Description: AIR SAFETY Primary App: DONALDSON STG14 DONACLONE AIR CLEANER Dimensions: Outer Diameter: 7.64" (194 mm) Inner Diameter: 6.04" (153 mm) Length: 15.00" (381 mm)</p>
	<p>Part Number: P118216 Description: AIR SAFETY Primary App: IHC 627976C1 Dimensions: Outer Diameter: 6.39" (162 mm) Inner Diameter: 5.29" (134 mm) Length: 20.00" (508 mm)</p>		<p>Part Number: P119371 Description: AIR SAFETY Primary App: DONALDSON STG12 DONACLONE AIR CLEANER Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 4.86" (123 mm) Length: 12.00" (305 mm)</p>
	<p>Part Number: P118342 Description: AIR PRIMARY Primary App: CASE, CLARK, SULLAIR Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 2.64" (67 mm) Length: 8.00" (203 mm)</p>		<p>Part Number: P119372 Description: AIR SAFETY Primary App: DONALDSON FHG16 CYCLOPAC Dimensions: Outer Diameter: 7.28" (185 mm) Inner Diameter: 6.20" (157 mm) Length: 17.70" (450 mm)</p>
	<p>Part Number: P118343 Description: AIR PRIMARY, FINNED Primary App: IHC Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.85" (123 mm) Length: 10.00" (254 mm) Gasket ID: 6.38" (162 mm) Minor OD: 0.53" (13 mm)</p>		<p>Part Number: P119373 Description: AIR SAFETY Primary App: DONALDSON FHG14 CYCLOPAC Dimensions: Outer Diameter: 6.39" (162 mm) Inner Diameter: 5.29" (134 mm) Length: 16.00" (406 mm)</p>









	<p>Part Number: P119374 Description: AIR SAFETY Primary App: DONALDSON FHG12 CYCLOPAC Dimensions: Outer Diameter: 4.58" (116 mm) Inner Diameter: 3.48" (88 mm) Length: 13.00" (330 mm)</p>		<p>Part Number: P119778 Description: AIR SAFETY Primary App: DONALDSON FHG09 CYCLOPAC Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 3.65" (93 mm) Length: 15.00" (381 mm)</p>
	<p>Part Number: P119375 Description: AIR SAFETY Primary App: DONALDSON FHG10 CYCLOPAC Dimensions: Outer Diameter: 4.58" (116 mm) Inner Diameter: 3.48" (88 mm) Length: 15.65" (398 mm)</p>		<p>Part Number: P119791 Description: AIR SAFETY Primary App: OLIVER 303003477 Dimensions: Outer Diameter: 3.36" (85 mm) Inner Diameter: 2.93" (74 mm) Length: 11.00" (279 mm)</p>
	<p>Part Number: P119410 Description: AIR SAFETY Primary App: DONALDSON FHG08 CYCLOPAC Dimensions: Outer Diameter: 3.37" (86 mm) Inner Diameter: 2.90" (74 mm) Length: 14.00" (356 mm)</p>		<p>Part Number: P120307 Description: AIR SAFETY Primary App: ADVANCE, CARRIER, CASE, NEW HOLLAND Dimensions: Outer Diameter: 2.46" (62 mm) Inner Diameter: 1.91" (49 mm) Length: 13.00" (330 mm)</p>
	<p>Part Number: P119417 Description: AIR PRIMARY Primary App: IHC, FREIGHTLINER, WABCO Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 11.00" (279 mm) Gasket OD: 5.94" (151 mm)</p>		<p>Part Number: P120320 Description: AIR PANEL, VENTILATION Primary App: EATON 219479, CAT 8P5343 Dimensions: Width: 6.00" (152 mm) Depth: 2.19" (56 mm) Height: 23.50" (597 mm)</p>
	<p>Part Number: P119492 Description: AIR PRIMARY Primary App: JOHN DEERE AL19152 Dimensions: Outer Diameter: 4.53" (115 mm) Inner Diameter: 2.50" (64 mm) Length: 13.11" (333 mm)</p>		<p>Part Number: P120484 Description: AIR SAFETY Primary App: WHITE FARM Dimensions: Outer Diameter: 4.16" (106 mm) Inner Diameter: 3.65" (93 mm) Length: 14.55" (370 mm)</p>
	<p>Part Number: P119539 Description: AIR SAFETY Primary App: DONALDSON FHG06 CYCLOPAC Dimensions: Outer Diameter: 2.95" (75 mm) Inner Diameter: 2.40" (61 mm) Length: 14.00" (356 mm)</p>		<p>Part Number: P120949 Description: AIR SAFETY Primary App: CLARK 6598222 Dimensions: Outer Diameter: 2.46" (62 mm) Inner Diameter: 1.91" (49 mm) Length: 8.26" (210 mm)</p>
	<p>Part Number: P119595 Description: AIR PRIMARY Primary App: IHC, MACK, PACCAR Dimensions: Outer Diameter: 11.59" (294 mm) Inner Diameter: 8.98" (228 mm) Length: 10.00" (254 mm) Gasket OD: 6.19" (157 mm)</p>		<p>Part Number: P121036 Description: AIR PANEL, VENTILATION Primary App: IHC, CASE Dimensions: Width: 6.00" (152 mm) Depth: 2.19" (56 mm) Height: 38.00" (965 mm)</p>
	<p>Part Number: P119596 Description: AIR PRIMARY Primary App: CLARK, IHC, WABCO Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 7.79" (198 mm) Length: 10.00" (254 mm) Gasket OD: 5.25" (133 mm) Gasket ID: 9.00" (228 mm)</p>		<p>Part Number: P121240 Description: AIR PRIMARY, FINNED Primary App: KUBOTA Dimensions: Outer Diameter: 3.26" (83 mm) Inner Diameter: 1.68" (43 mm) Length: 7.00" (178 mm) Gasket OD: 3.00" (76 mm) Gasket ID: 2.50" (64 mm) Minor OD: 0.42" (11 mm)</p>
	<p>Part Number: P119720 Description: AIR PRIMARY Primary App: WHITE MOTOR Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.73" (171 mm) Length: 13.00" (330 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 7.62" (193 mm)</p>		<p>Part Number: P121351 Description: AIR PANEL, VENTILATION Primary App: PACCAR, DART Dimensions: Width: 15.00" (381 mm) Depth: 2.19" (56 mm) Height: 20.00" (508 mm)</p>


	<p>Part Number: P121378 Description: AIR PANEL, VENTILATION Primary App: MASSEY FERGUSON 529760M1 Dimensions: Width: 6.00" (152 mm) Depth: 2.19" (56 mm) Height: 47.00" (1194 mm)</p>		<p>Part Number: P123007 Description: AIR SAFETY Primary App: JOY 360628321, RENAULT RVI 5010094145 Dimensions: Outer Diameter: 6.39" (162 mm) Inner Diameter: 5.29" (134 mm) Length: 15.00" (381 mm)</p>
	<p>Part Number: P121557 Description: AIR PRIMARY Primary App: MASSEY FERGUSON 1041845M91 Dimensions: Outer Diameter: 7.93" (201 mm) Inner Diameter: 5.32" (135 mm) Length: 13.00" (330 mm)</p>		<p>Part Number: P123065 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FWG04 A/C, UL APPROVED Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 1.67" (42 mm) Length: 7.00" (178 mm) Gasket OD: 3.00" (76 mm) Gasket ID: 2.50" (64 mm) Minor OD: 0.42" (11 mm)</p>
	<p>Part Number: P121922 Description: AIR PRIMARY Primary App: FORD, MACK WHITE MOTOR Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 12.00" (305 mm) Bolt Hole Diameter: 0.53" (13 mm) Gasket ID: 10.12" (257 mm)</p>		<p>Part Number: P123159 Description: AIR PRIMARY, FINNED Primary App: MASSEY FERGUSON 1043326M91 Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 2.64" (67 mm) Length: 11.00" (279 mm) Gasket ID: 3.95" (100 mm) Minor OD: 0.66" (17 mm)</p>
	<p>Part Number: P122115 Description: AIR PANEL, VENTILATION Primary App: CLARK, FIAT ALLIS Dimensions: Width: 6.50" (165 mm) Depth: 2.19" (56 mm) Height: 23.50" (597 mm)</p>		<p>Part Number: P123160 Description: AIR SAFETY Primary App: CLARK, MASSEY FERGUSON, ALLIS CHALMERS Dimensions: Outer Diameter: 2.59" (66 mm) Inner Diameter: 2.15" (55 mm) Length: 10.00" (254 mm)</p>
	<p>Part Number: P122425 Description: AIR SAFETY Primary App: IHC, KOEHRING, KOMATSU Dimensions: Outer Diameter: 7.64" (194 mm) Inner Diameter: 6.04" (153 mm) Length: 17.00" (432 mm)</p>		<p>Part Number: P123229 Description: AIR PANEL, VENTILATION Primary App: DEUTZ 70257109 Dimensions: Width: 12.00" (305 mm) Depth: 2.19" (56 mm) Height: 16.00" (406 mm)</p>
	<p>Part Number: P122492 Description: AIR PRIMARY, FINNED Primary App: CASE, CLARK Dimensions: Outer Diameter: 6.09" (155 mm) Inner Diameter: 3.48" (88 mm) Length: 12.00" (305 mm) Gasket ID: 4.45" (113 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P123230 Description: AIR SAFETY Primary App: JOHN DEERE AR61988, CASE A44286 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 4.24" (108 mm) Length: 5.82" (148 mm)</p>
	<p>Part Number: P122510 Description: AIR PRIMARY, FINNED Primary App: FLAME RETARDANT, UL APPROVED Dimensions: Outer Diameter: 4.08" (104 mm) Inner Diameter: 2.49" (63 mm) Length: 10.00" (254 mm) Gasket ID: 2.58" (66 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P123347 Description: AIR PRIMARY Primary App: DONALDSON ECG10 AIR CLEANER Dimensions: Outer Diameter: 8.04" (204 mm) Inner Diameter: 6.06" (154 mm) Length: 11.00" (279 mm) Gasket ID: 5.38" (137 mm)</p>
	<p>Part Number: P122514 Description: AIR PRIMARY, FINNED Primary App: FLAME RETARDANT, UL APPROVED Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 2.64" (67 mm) Length: 11.00" (279 mm) Gasket ID: 3.95" (100 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P123440 Description: AIR PANEL, VENTILATION Primary App: EATON BERGSTROM Dimensions: Width: 8.00" (203 mm) Depth: 2.19" (56 mm) Height: 17.00" (432 mm)</p>
	<p>Part Number: P122605 Description: AIR PRIMARY, FINNED Primary App: WHITE Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 5.73" (146 mm) Length: 12.00" (305 mm) Gasket OD: 8.88" (225 mm)</p>		<p>Part Number: P123827 Description: AIR PRIMARY Primary App: DDA GEN SETS 3-71, 4-71, 6-71 Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.85" (123 mm) Length: 13.00" (330 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 9.12" (231 mm)</p>

	<p>Part Number: P123828 Description: AIR SAFETY Primary App: DDA GEN SETS 3-71, 4-71, 6-71 Dimensions: Outer Diameter: 4.60" (117 mm) Inner Diameter: 3.48" (88 mm) Length: 12.28" (312 mm) Gasket OD: 4.37" (111 mm) Gasket ID: 4.00" (102 mm)</p>		<p>Part Number: P124860 Description: AIR SAFETY Primary App: TEREX 9031711 Dimensions: Outer Diameter: 7.64" (194 mm) Inner Diameter: 6.04" (153 mm) Length: 18.00" (457 mm)</p>
	<p>Part Number: P123990 Description: AIR PRIMARY Primary App: ROOF DRILL DUST COLLECTOR Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 3.48" (88 mm) Length: 13.00" (330 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 4.76" (121 mm)</p>		<p>Part Number: P124862 Description: AIR SAFETY Primary App: DONALDSON FVG14 CYCLOFLOW AIR CLEANER Dimensions: Outer Diameter: 7.64" (194 mm) Inner Diameter: 6.04" (153 mm) Length: 21.00" (533 mm)</p>
	<p>Part Number: P124046 Description: AIR SAFETY Primary App: FORD, CASE IR Dimensions: Outer Diameter: 5.70" (145 mm) Inner Diameter: 4.58" (116 mm) Length: 17.00" (432 mm)</p>		<p>Part Number: P124866 Description: AIR SAFETY Primary App: DONALDSON FVG16 CYCLOFLOW AIR CLEANER Dimensions: Outer Diameter: 8.64" (219 mm) Inner Diameter: 7.06" (179 mm) Length: 18.00" (457 mm)</p>
	<p>Part Number: P124047 Description: AIR SAFETY Primary App: DONALDSON FTG13 A/C, CLARK 1991853 Dimensions: Outer Diameter: 6.39" (162 mm) Inner Diameter: 5.29" (134 mm) Length: 19.00" (483 mm)</p>		<p>Part Number: P124867 Description: AIR PRIMARY Primary App: DONALDSON FVG16 CYCLOFLOW AIR CLEANER Dimensions: Outer Diameter: 13.84" (352 mm) Inner Diameter: 9.47" (241 mm) Length: 20.00" (508 mm) Bolt Hole Diameter: 0.94" (24 mm) Gasket ID: 9.88" (251 mm)</p>
	<p>Part Number: P124366 Description: AIR SAFETY Primary App: IR 35254895 Dimensions: Outer Diameter: 8.64" (219 mm) Inner Diameter: 7.06" (179 mm) Length: 14.00" (356 mm)</p>		<p>Part Number: P124868 Description: AIR SAFETY Primary App: DONALDSON FVG16 CYCLOFLOW AIR CLEANER Dimensions: Outer Diameter: 8.64" (219 mm) Inner Diameter: 7.06" (179 mm) Length: 20.66" (525 mm)</p>
	<p>Part Number: P124370 Description: AIR PRIMARY Primary App: IR 35254903 Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 15.00" (381 mm) Bolt Hole Diameter: 0.94" (24 mm) Gasket ID: 9.88" (251 mm)</p>		<p>Part Number: P125310 Description: AIR VEE-PAC Primary App: GAS TURBINE ENGINE VPAC Dimensions: Width: 14.00" (356 mm) Depth: 6.21" (158 mm) Length: 36.12" (917 mm) D: 3.57" (91 mm)</p>
	<p>Part Number: P124548 Description: AIR SAFETY Primary App: CASE A44805 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 4.24" (108 mm) Length: 8.00" (203 mm)</p>		<p>Part Number: P126227 Description: AIR PANEL, VENTILATION Primary App: EATON 2-17922 Dimensions: Width: 6.00" (152 mm) Depth: 2.19" (56 mm) Height: 25.50" (648 mm)</p>
	<p>Part Number: P124767 Description: AIR SAFETY Primary App: DYNAPAC, IR, DRESSER Dimensions: Outer Diameter: 3.41" (87 mm) Inner Diameter: 2.90" (74 mm) Length: 10.00" (254 mm)</p>		<p>Part Number: P126318 Description: AIR PRIMARY Primary App: ALLIS CHALMERS 269244 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 18.00" (457 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 6.38" (162 mm)</p>
	<p>Part Number: P124837 Description: AIR SAFETY Primary App: JOHN DEERE AT31227, OLIVER, IHC Dimensions: Outer Diameter: 4.58" (116 mm) Inner Diameter: 3.48" (88 mm) Length: 11.00" (279 mm)</p>		

	<p>Part Number: P126321 Description: AIR SAFETY Primary App: ALLIS CHALMERS 279245 Dimensions: Outer Diameter: 5.95" (151 mm) Inner Diameter: 4.85" (123 mm) Length: 16.00" (406 mm)</p>		<p>Part Number: P127914 Description: AIR PRIMARY, FINNED Primary App: FORD DOHZ9601D, MOTORCRAFT FA78 Dimensions: Outer Diameter: 9.22" (234 mm) Inner Diameter: 4.84" (123 mm) Length: 10.00" (254 mm) Gasket ID: 5.42" (138 mm) Minor OD: 0.53" (13 mm)</p>
	<p>Part Number: P126984 Description: AIR SAFETY Primary App: HITACHI 79081328 Dimensions: Outer Diameter: 2.95" (75 mm) Inner Diameter: 0.69" (18 mm) Length: 10.98" (279 mm)</p>		<p>Part Number: P127915 Description: AIR PRIMARY, FINNED Primary App: FORD DOHZ9601B, MOTORCRAFT FA76 Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.73" (171 mm) Length: 10.00" (254 mm) Gasket ID: 9.56" (243 mm) Minor OD: 0.66" (17 mm)</p>
	<p>Part Number: P127075 Description: AIR PRIMARY Primary App: JOHN DEERE AT39124, IHC 1150719C1 Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.85" (123 mm) Length: 12.00" (305 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 6.38" (162 mm)</p>		<p>Part Number: P128252 Description: AIR PRIMARY Primary App: CASE, CLARK Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 14.00" (356 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 6.38" (162 mm)</p>
	<p>Part Number: P127308 Description: AIR PRIMARY Primary App: DONALDSON FTG15 AIR CLEANER Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 24.00" (610 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 8.12" (206 mm)</p>		<p>Part Number: P128408 Description: AIR SAFETY Primary App: DONALDSON STG16 DONACLONE AIR CLEANER Dimensions: Outer Diameter: 10.24" (260 mm) Inner Diameter: 9.12" (232 mm) Length: 22.00" (559 mm)</p>
	<p>Part Number: P127309 Description: AIR SAFETY Primary App: DONALDSON FTG15 CYCLOPAC Dimensions: Outer Diameter: 7.28" (185 mm) Inner Diameter: 6.20" (157 mm) Length: 23.00" (584 mm)</p>		<p>Part Number: P128487 Description: AIR PRIMARY Primary App: International Trucks Dimensions: Outer Diameter: 8.25" (209 mm) Inner Diameter: 5.75" (146 mm) Length: 10.50" (267 mm)</p>
	<p>Part Number: P127313 Description: AIR SAFETY Primary App: LEROI 437382 Dimensions: Outer Diameter: 7.28" (185 mm) Inner Diameter: 6.20" (157 mm) Length: 18.00" (457 mm)</p>		<p>Part Number: P128781 Description: AIR PRIMARY Primary App: LOCOMOTIVE Dimensions: Outer Diameter: 12.75" (324 mm) Inner Diameter: 8.42" (214 mm) Length: 23.00" (584 mm)</p>
	<p>Part Number: P127315 Description: AIR SAFETY Primary App: ISUZU 2-90646-920-0, CLARK, TIMBERJACK Dimensions: Outer Diameter: 5.70" (145 mm) Inner Diameter: 4.58" (116 mm) Length: 12.00" (305 mm)</p>		<p>Part Number: P128810 Description: AIR PANEL, VENTILATION Primary App: VENT PANEL Dimensions: Width: 5.00" (127 mm) Depth: 2.19" (56 mm) Height: 26.00" (660 mm)</p>
	<p>Part Number: P127784 Description: AIR PRIMARY, FINNED Primary App: WHITE FARM 312990561 Dimensions: Outer Diameter: 6.09" (155 mm) Inner Diameter: 3.48" (88 mm) Length: 13.00" (330 mm) Gasket ID: 4.75" (121 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P129396 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON EBA11 KONEPAC-TREATED W/COVER GASKET Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.95" (177 mm) Length: 28.00" (711 mm) Gasket OD: 7.50" (190 mm) Gasket ID: 3.96" (101 mm)</p>
	<p>Part Number: P127787 Description: AIR SAFETY Primary App: DEUTZ, HESSTON Dimensions: Outer Diameter: 3.41" (87 mm) Inner Diameter: 2.93" (74 mm) Length: 12.00" (305 mm)</p>		<p>Part Number: P129472 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON EBA09 KONEPAC-TREATED W/CVR GASKET Dimensions: Outer Diameter: 8.66" (220 mm) Inner Diameter: 5.21" (132 mm) Length: 28.00" (711 mm) Gasket OD: 5.74" (146 mm) Gasket ID: 2.21" (56 mm)</p>

















 <p>Part Number: P129862 Description: AIR PANEL, VENTILATION Primary App: ALLIS CHALMERS 577226 Dimensions: Width: 7.00" (178 mm) Depth: 2.19" (56 mm) Height: 26.00" (660 mm)</p>	 <p>Part Number: P130770 Description: AIR PRIMARY, FINNED Primary App: JOHN DEERE AT27824 Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.85" (123 mm) Length: 13.00" (330 mm) Gasket ID: 7.62" (194 mm) Minor OD: 0.66" (17 mm)</p>
<p>Part Number: P130083 Description: AIR SAFETY Primary App: STEIGER Dimensions: Outer Diameter: 8.66" (220 mm) Inner Diameter: 7.05" (179 mm) Length: 16.66" (423 mm)</p>	 <p>Part Number: P130772 Description: AIR SAFETY Primary App: JOHN DEERE AR70107 Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 4.86" (123 mm) Length: 18.00" (457 mm)</p>
 <p>Part Number: P130747 Description: AIR PRIMARY Primary App: KOMATSU 11T-76-13310, DCI ETD DRILL DUST COLLCTR Dimensions: Outer Diameter: 7.93" (201 mm) Inner Diameter: 3.57" (91 mm) Length: 16.00" (406 mm)</p>	 <p>Part Number: P130776 Description: AIR SAFETY Primary App: DEERE AL27159, FIAT 1909129, SAME 2.4249.050.4 Dimensions: Outer Diameter: 3.00" (76 mm) Inner Diameter: 2.40" (61 mm) Length: 11.00" (279 mm)</p>
 <p>Part Number: P130760 Description: AIR PRIMARY, FINNED Primary App: JOHN DEERE AE31723 AR84228 Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 3.26" (83 mm) Length: 12.00" (305 mm) Gasket ID: 3.95" (100 mm) Minor OD: 0.66" (17 mm)</p>	 <p>Part Number: P130884 Description: AIR PRIMARY Primary App: GMC 2014573 Dimensions: Outer Diameter: 8.84" (225 mm) Inner Diameter: 5.48" (139 mm) Length: 14.00" (356 mm)</p>
 <p>Part Number: P130761 Description: AIR PRIMARY, FINNED Primary App: IHC 924779C2 Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 3.26" (83 mm) Length: 12.00" (305 mm) Gasket ID: 3.25" (83 mm) Minor OD: 0.66" (17 mm)</p>	 <p>Part Number: P130959 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON EBA09, CARBON TREATED W/CVR GASKET Dimensions: Outer Diameter: 8.66" (220 mm) Inner Diameter: 5.21" (132 mm) Length: 15.00" (381 mm) Gasket OD: 5.74" (146 mm) Gasket ID: 2.21" (56 mm)</p>
 <p>Part Number: P130763 Description: AIR PRIMARY, FINNED Primary App: JOHN DEERE AT33363 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 4.24" (108 mm) Length: 10.00" (254 mm) Gasket ID: 5.08" (129 mm) Minor OD: 0.66" (17 mm)</p>	 <p>Part Number: P131231 Description: AIR PANEL, VENTILATION Primary App: GARDNER DENVER EQUIPMENT Dimensions: Width: 9.00" (229 mm) Depth: 2.19" (56 mm) Height: 32.00" (813 mm)</p>
 <p>Part Number: P130764 Description: AIR PRIMARY Primary App: JOHN DEERE AT35155, IHC 634269C1 Dimensions: Outer Diameter: 7.93" (201 mm) Inner Diameter: 5.32" (135 mm) Length: 12.00" (305 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 6.38" (162 mm)</p>	 <p>Part Number: P131280 Description: AIR PRIMARY Primary App: IHC 627975C2, JOHN DEERE AT49022 Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.72" (171 mm) Length: 20.00" (508 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 9.56" (242 mm)</p>
 <p>Part Number: P130766 Description: AIR PRIMARY Primary App: JOHN DEERE AR46481 Dimensions: Outer Diameter: 6.08" (154 mm) Inner Diameter: 3.49" (89 mm) Length: 12.00" (305 mm) Bolt Hole Diameter: 0.66" (17 mm)</p>	 <p>Part Number: P131283 Description: AIR PRIMARY Primary App: IHC 529851R2 Dimensions: Outer Diameter: 6.08" (154 mm) Inner Diameter: 3.49" (89 mm) Length: 15.00" (381 mm)</p>
 <p>Part Number: P130769 Description: AIR PRIMARY Primary App: JOHN DEERE AL27160 Dimensions: Outer Diameter: 4.08" (104 mm) Inner Diameter: 2.49" (63 mm) Length: 7.00" (178 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 2.62" (67 mm)</p>	 <p>Part Number: P131321 Description: AIR PRIMARY Primary App: IHC 547159R2 Dimensions: Outer Diameter: 4.08" (104 mm) Inner Diameter: 1.50" (38 mm) Length: 6.02" (153 mm) Bolt Hole Diameter: 0.25" (6 mm) Gasket ID: 3.09" (79 mm)</p>




	<p>Part Number: P131331 Description: AIR PRIMARY, FINNED Primary App: IHC 690049C2 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 3.49" (89 mm) Length: 15.00" (381 mm) Gasket ID: 4.45" (113 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P131395 Description: AIR PRIMARY Primary App: IHC 932391C2, WHITE FARM 303108724 Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 5.86" (149 mm) Length: 18.00" (457 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 7.52" (191 mm)</p>
	<p>Part Number: P131335 Description: AIR SAFETY Primary App: IHC 932390C1, WHITE FARM 303108716 Dimensions: Outer Diameter: 5.70" (145 mm) Inner Diameter: 4.58" (116 mm) Length: 16.00" (406 mm)</p>		<p>Part Number: P131397 Description: AIR PRIMARY Primary App: IHC 935694C1 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 6.38" (162 mm)</p>
	<p>Part Number: P131336 Description: AIR SAFETY Primary App: IHC 627935C1, CASE A47146 Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 4.86" (123 mm) Length: 10.00" (254 mm)</p>		<p>Part Number: P131404 Description: AIR PRIMARY Primary App: IHC 346779R91 Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 14.00" (356 mm) Bolt Hole Diameter: 0.53" (13 mm)</p>
	<p>Part Number: P131337 Description: AIR SAFETY Primary App: IHC 935693C1, JOHN DEERE AE30507 Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 4.86" (123 mm) Length: 14.00" (356 mm)</p>		<p>Part Number: P132349 Description: AIR SAFETY Primary App: FORD Dimensions: Outer Diameter: 7.28" (185 mm) Inner Diameter: 6.20" (157 mm) Length: 15.65" (398 mm)</p>
	<p>Part Number: P131338 Description: AIR SAFETY Primary App: IHC 672020C1 Dimensions: Outer Diameter: 7.64" (194 mm) Inner Diameter: 6.04" (153 mm) Length: 12.00" (305 mm)</p>		<p>Part Number: P132447 Description: AIR PANEL, VENTILATION Primary App: CLARK 793320-3 Dimensions: Width: 16.00" (406 mm) Depth: 2.19" (56 mm) Height: 26.00" (660 mm)</p>
	<p>Part Number: P131343 Description: AIR PRIMARY Primary App: IHC 680587C2 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 18.00" (457 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 8.12" (206 mm)</p>		<p>Part Number: P132448 Description: AIR PANEL, VENTILATION Primary App: CASE F64318 Dimensions: Width: 7.00" (178 mm) Depth: 2.19" (56 mm) Height: 38.00" (965 mm)</p>
	<p>Part Number: P131348 Description: AIR PRIMARY Primary App: IHC 627934C1 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.03" (153 mm) Length: 12.00" (305 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 6.38" (162 mm)</p>		<p>Part Number: P132935 Description: AIR PRIMARY, FINNED Primary App: CASE A47032 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 4.24" (108 mm) Length: 14.00" (356 mm) Gasket ID: 5.42" (138 mm) Minor OD: 0.66" (17 mm)</p>
	<p>Part Number: P131359 Description: AIR PRIMARY, FINNED Primary App: IHC 383731R93 Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 2.64" (67 mm) Length: 14.00" (356 mm) Gasket ID: 3.95" (100 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P132939 Description: AIR SAFETY Primary App: CASE A47033 Dimensions: Outer Diameter: 4.16" (106 mm) Inner Diameter: 3.65" (93 mm) Length: 13.00" (330 mm)</p>
	<p>Part Number: P131394 Description: AIR SAFETY Primary App: JOHN DEERE AT44378 Dimensions: Outer Diameter: 3.36" (85 mm) Inner Diameter: 2.90" (74 mm) Length: 11.00" (279 mm)</p>		<p>Part Number: P133044 Description: AIR SAFETY Primary App: STEIGER 01-3898 Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 22.00" (559 mm)</p>







	<p>Part Number: P133045 Description: AIR PRIMARY Primary App: STEIGER 01-3899 Dimensions: Outer Diameter: 8.64" (219 mm) Inner Diameter: 7.06" (179 mm) Length: 20.66" (525 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 7.50" (191 mm)</p>		<p>Part Number: P133712 Description: AIR PRIMARY Primary App: FRAM CA240PLHD Dimensions: Outer Diameter: 9.63" (245 mm) Inner Diameter: 5.11" (130 mm) Length: 11.60" (295 mm)</p>
	<p>Part Number: P133138 Description: AIR SAFETY Primary App: ATLAS 3216708202, CAT 100-6849, FIAT 1930790 Dimensions: Outer Diameter: 4.57" (116 mm) Inner Diameter: 3.46" (88 mm) Length: 15.00" (381 mm)</p>		<p>Part Number: P133713 Description: AIR PRIMARY Primary App: IHC, BROS Dimensions: Outer Diameter: 8.89" (226 mm) Inner Diameter: 4.33" (110 mm) Length: 10.00" (254 mm)</p>
	<p>Part Number: P133179 Description: AIR SAFETY Primary App: ALLIS CHALMERS 259793, FIAT ALLIS 73116280 Dimensions: Outer Diameter: 7.64" (194 mm) Inner Diameter: 6.04" (153 mm) Length: 18.00" (457 mm)</p>		<p>Part Number: P133714 Description: AIR PRIMARY Primary App: DUST COLLECTORS Dimensions: Outer Diameter: 16.62" (422 mm) Inner Diameter: 12.03" (306 mm) Length: 24.00" (610 mm)</p>
	<p>Part Number: P133701 Description: AIR PRIMARY Primary App: VORTOX VF-135A Dimensions: Outer Diameter: 10.37" (263 mm) Inner Diameter: 5.63" (143 mm) Length: 10.00" (254 mm) Bolt Hole Diameter: 0.53" (13 mm) Gasket ID: 6.25" (158 mm)</p>		<p>Part Number: P133765 Description: AIR PRIMARY Primary App: JOHN DEERE AR54336, AR79941 Dimensions: Outer Diameter: 7.32" (186 mm) Inner Diameter: 3.96" (101 mm) Length: 14.88" (378 mm) Bolt Hole Diameter: 0.39" (10 mm)</p>
	<p>Part Number: P133702 Description: AIR PRIMARY Primary App: UNITED 250C3S, HYSTER, TOWMOTOR, IHC Dimensions: Outer Diameter: 3.50" (89 mm) Inner Diameter: 2.08" (53 mm) Length: 10.35" (263 mm)</p>		<p>Part Number: P134353 Description: AIR PRIMARY Primary App: CLARK 1991959 Dimensions: Outer Diameter: 10.86" (276 mm) Inner Diameter: 6.50" (165 mm) Length: 15.00" (381 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 7.52" (191 mm)</p>
	<p>Part Number: P133703 Description: AIR PRIMARY Primary App: UNITED 250C13S, IHC, WAYNE Dimensions: Outer Diameter: 5.44" (138 mm) Inner Diameter: 3.21" (82 mm) Length: 17.00" (432 mm) Gasket ID: 3.95" (100 mm)</p>		<p>Part Number: P134354 Description: AIR SAFETY Primary App: JOHN DEERE T52224, TIMBERJACK Dimensions: Outer Diameter: 6.39" (162 mm) Inner Diameter: 5.29" (134 mm) Length: 14.00" (356 mm)</p>
	<p>Part Number: P133705 Description: AIR PRIMARY Primary App: IHC, MACK Dimensions: Outer Diameter: 8.06" (205 mm) Inner Diameter: 5.78" (147 mm) Length: 4.00" (102 mm) Bolt Hole Diameter: 0.22" (6 mm)</p>		<p>Part Number: P134960 Description: AIR PRIMARY Primary App: WHITE FARM 303216535 Dimensions: Outer Diameter: 9.14" (232 mm) Inner Diameter: 5.28" (134 mm) Length: 17.00" (432 mm) Bolt Hole Diameter: 0.90" (23 mm)</p>
	<p>Part Number: P133706 Description: AIR PRIMARY Primary App: UNITED 250C4S, IHC, TOWMOTOR Dimensions: Outer Diameter: 4.42" (112 mm) Inner Diameter: 2.21" (56 mm) Length: 12.25" (311 mm) Gasket ID: 3.09" (79 mm)</p>		<p>Part Number: P136254 Description: AIR PRIMARY Primary App: JOHN DEERE AR43941 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 3.49" (89 mm) Length: 12.00" (305 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 3.95" (100 mm)</p>
	<p>Part Number: P133709 Description: AIR PRIMARY Primary App: IR 40070 Dimensions: Outer Diameter: 16.62" (422 mm) Inner Diameter: 12.03" (306 mm) Length: 16.00" (406 mm)</p>		<p>Part Number: P136255 Description: AIR PRIMARY Primary App: JOHN DEERE AR79679 Dimensions: Outer Diameter: 9.08" (231 mm) Inner Diameter: 5.24" (133 mm) Length: 16.75" (425 mm) Bolt Hole Diameter: 0.39" (10 mm) Gasket ID: 6.24" (158 mm)</p>




















	<p>Part Number: P136258 Description: AIR PRIMARY, FINNED Primary App: JOHN DEERE AH19848 Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 2.64" (67 mm) Length: 9.00" (229 mm) Gasket ID: 3.95" (100 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P136835 Description: AIR PRIMARY Primary App: WHITE MOTOR 027000805 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.72" (196 mm) Length: 19.47" (495 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 9.52" (250 mm)</p>
	<p>Part Number: P136390 Description: AIR PRIMARY Primary App: UNITED 250C5S, IHC, FORD Dimensions: Outer Diameter: 4.42" (112 mm) Inner Diameter: 2.21" (56 mm) Length: 10.35" (263 mm) D: 1.00" (25 mm) Gasket ID: 3.09" (79 mm)</p>		<p>Part Number: P136836 Description: AIR PRIMARY Primary App: VORTOX VF100A Dimensions: Outer Diameter: 7.32" (186 mm) Inner Diameter: 3.54" (90 mm) Length: 10.00" (254 mm) Bolt Hole Diameter: 0.53" (13 mm) Gasket ID: 5.42" (138 mm)</p>
	<p>Part Number: P136398 Description: AIR PRIMARY Primary App: AIR MAZE 200746-07, CUMMINS 169365 Dimensions: Outer Diameter: 9.60" (244 mm) Inner Diameter: 5.04" (128 mm) Length: 7.29" (185 mm) Gasket ID: 7.30" (185 mm)</p>		<p>Part Number: P136837 Description: AIR PRIMARY Primary App: VORTOX VF160A Dimensions: Outer Diameter: 11.83" (300 mm) Inner Diameter: 7.15" (182 mm) Length: 12.80" (325 mm) Bolt Hole Diameter: 0.53" (13 mm) Gasket ID: 9.00" (228 mm)</p>
	<p>Part Number: P136400 Description: AIR PRIMARY, SPECIAL Primary App: POLYESTER OUTER WRAP FOR P136412 Dimensions: Width: 10.50" (267 mm) Height: 28.00" (711 mm)</p>		<p>Part Number: P136847 Description: AIR PRIMARY Primary App: CASE Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.03" (153 mm) Length: 12.00" (305 mm)</p>
	<p>Part Number: P136401 Description: AIR SAFETY Primary App: AIR MAZE CD916500830, JOHN DEERE Dimensions: Outer Diameter: 3.87" (98 mm) Inner Diameter: 3.16" (80 mm) Length: 13.00" (330 mm)</p>		<p>Part Number: P137285 Description: AIR PRIMARY, KONEPAC™ Primary App: SAME TRACTOR Dimensions: Outer Diameter: 3.69" (94 mm) Inner Diameter: 2.52" (64 mm) Length: 13.07" (332 mm) Gasket OD: 1.89" (48 mm)</p>
	<p>Part Number: P136405 Description: AIR PRIMARY Primary App: AIR MAZE CD1120501830, JOHN DEERE Dimensions: Outer Diameter: 9.06" (230 mm) Inner Diameter: 4.87" (124 mm) Length: 19.38" (492 mm) Bolt Hole Diameter: 0.39" (10 mm) Gasket ID: 6.24" (158 mm)</p>		<p>Part Number: P137293 Description: AIR PRIMARY, KONEPAC™ Primary App: SAME TRACTOR Dimensions: Outer Diameter: 5.87" (149 mm) Inner Diameter: 3.14" (80 mm) Length: 13.03" (331 mm) Gasket OD: 6.93" (176 mm)</p>
	<p>Part Number: P136406 Description: AIR SAFETY Primary App: AIR MAZE CD1120501826, JOHN DEERE Dimensions: Outer Diameter: 4.66" (118 mm) Inner Diameter: 3.97" (101 mm) Length: 16.50" (419 mm) Bolt Hole Diameter: 0.66" (17 mm)</p>		<p>Part Number: P137523 Description: AIR PANEL, VENTILATION Primary App: CRENLO Dimensions: Width: 7.00" (178 mm) Depth: 2.19" (56 mm) Height: 15.00" (381 mm)</p>
	<p>Part Number: P136646 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON EBA09 KONEPAC UNTREATED, MACK, GMC Dimensions: Outer Diameter: 8.66" (220 mm) Inner Diameter: 5.21" (132 mm) Length: 15.00" (381 mm) Gasket OD: 5.74" (146 mm) Gasket ID: 2.21" (56 mm)</p>		<p>Part Number: P137640 Description: AIR SAFETY Primary App: IHC 482644C1 Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 4.86" (123 mm) Length: 13.50" (343 mm)</p>
	<p>Part Number: P136828 Description: AIR PRIMARY Primary App: UNITED 250C14S, HOUGH, HYSTER Dimensions: Outer Diameter: 6.92" (176 mm) Inner Diameter: 4.44" (113 mm) Length: 9.00" (229 mm) Gasket ID: 5.42" (138 mm)</p>		<p>Part Number: P137641 Description: AIR SAFETY Primary App: IHC 482645C1 Dimensions: Outer Diameter: 7.64" (194 mm) Inner Diameter: 6.04" (153 mm) Length: 15.50" (394 mm) Bolt Hole Diameter: 0.66" (17 mm)</p>



















	<p>Part Number: P137957 Description: AIR PRIMARY Primary App: BULK CONVEYING EQUIPMENT Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.03" (153 mm) Length: 13.00" (330 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 6.38" (162 mm)</p>		<p>Part Number: P141228 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON EBA13 KONEPAC AIR CLEANER Dimensions: Outer Diameter: 12.75" (324 mm) Inner Diameter: 8.32" (211 mm) Length: 28.00" (711 mm) Gasket OD: 9.81" (249 mm) Gasket ID: 5.38" (137 mm)</p>
	<p>Part Number: P138428 Description: AIR PRIMARY, KONEPAC™ Primary App: LEYLAND-DAF ACU3994, RENAULT 5000807395 Dimensions: Outer Diameter: 8.66" (220 mm) Inner Diameter: 5.21" (132 mm) Length: 19.29" (490 mm) Gasket OD: 0.59" (15 mm)</p>		<p>Part Number: P141278 Description: AIR SAFETY Primary App: DONALDSON NDL Cyclopac A/C R804518 Dimensions: Outer Diameter: 2.46" (62 mm) Inner Diameter: 1.94" (49 mm) Length: 9.00" (229 mm)</p>
	<p>Part Number: P138722 Description: AIR SAFETY Primary App: DONALDSON FTG AIR CLEANER G130043 Dimensions: Outer Diameter: 6.40" (163 mm) Inner Diameter: 5.29" (134 mm) Length: 18.50" (470 mm)</p>		<p>Part Number: P141317 Description: AIR PRIMARY, KONEPAC™ Primary App: IHC 574844C1 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.95" (177 mm) Length: 22.00" (559 mm) Gasket OD: 7.50" (190 mm) Gasket ID: 3.96" (101 mm)</p>
	<p>Part Number: P139293 Description: AIR SAFETY Primary App: O&K HR120C EXCAVATOR Dimensions: Outer Diameter: 7.64" (194 mm) Inner Diameter: 6.04" (153 mm) Length: 21.65" (550 mm)</p>		<p>Part Number: P141319 Description: AIR SAFETY Primary App: JOHN DEERE AR79680 Dimensions: Outer Diameter: 4.66" (118 mm) Inner Diameter: 3.97" (101 mm) Length: 14.00" (356 mm)</p>
	<p>Part Number: P140131 Description: AIR PRIMARY Primary App: DEUTZ 2165031, KHD 42216-5034 Dimensions: Outer Diameter: 5.00" (127 mm) Inner Diameter: 2.52" (64 mm) Length: 11.22" (285 mm) Bolt Hole Diameter: 0.33" (8 mm) Gasket ID: 2.87" (73 mm)</p>		<p>Part Number: P141320 Description: AIR PANEL, VENTILATION Primary App: JOHN DEERE AT57640, AT73529 Dimensions: Width: 5.00" (127 mm) Depth: 2.19" (56 mm) Height: 29.50" (749 mm)</p>
	<p>Part Number: P140132 Description: AIR PRIMARY Primary App: DEUTZ 2241034 Dimensions: Outer Diameter: 7.80" (198 mm) Inner Diameter: 4.08" (104 mm) Length: 14.39" (366 mm) Bolt Hole Diameter: 0.33" (8 mm) Gasket ID: 4.96" (126 mm)</p>		<p>Part Number: P141339 Description: AIR PRIMARY, KONEPAC™ Primary App: IHC 574845C1 Dimensions: Outer Diameter: 8.66" (220 mm) Inner Diameter: 5.21" (132 mm) Length: 22.00" (559 mm) Gasket OD: 5.74" (146 mm) Gasket ID: 2.21" (56 mm)</p>
	<p>Part Number: P140277 Description: AIR PANEL, VENTILATION Primary App: WAUKESHA 169180G Dimensions: Width: 19.50" (495 mm) Depth: 2.19" (56 mm) Height: 25.50" (648 mm)</p>		<p>Part Number: P142100 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON EBA13 KONEPAC-TREATED Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.32" (211 mm) Length: 24.00" (610 mm) Gasket OD: 9.80" (249 mm) Gasket ID: 5.38" (137 mm)</p>
	<p>Part Number: P140681 Description: AIR PRIMARY Primary App: MARINE, FLAME RETARDANT, UL APPROVED Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.73" (171 mm) Length: 12.00" (305 mm) Bolt Hole Diameter: 0.53" (13 mm) Gasket ID: 9.56" (242 mm)</p>		<p>Part Number: P142792 Description: AIR PANEL, ENGINE Primary App: FARR PAMIC P-4, UNITED F-4 Dimensions: Width: 5.95" (151 mm) Depth: 7.79" (198 mm) Height: 5.95" (151 mm)</p>
	<p>Part Number: P140822 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON EBA09 KONEPAC-STANDARD (REV. FLOW) Dimensions: Outer Diameter: 8.66" (220 mm) Inner Diameter: 5.21" (132 mm) Length: 28.00" (711 mm) Gasket OD: 5.74" (146 mm) Gasket ID: 2.21" (56 mm)</p>		<p>Part Number: P142793 Description: AIR PANEL, ENGINE Primary App: FARR PAMIC P-6, UNITED F-6 Dimensions: Width: 5.95" (151 mm) Depth: 7.79" (198 mm) Height: 8.25" (210 mm)</p>


















	<p>Part Number: P142794 Description: AIR PANEL, ENGINE Primary App: FARR PAMIC P-9, UNITED F-9 Dimensions: Width: 8.25" (210 mm) Depth: 7.79" (198 mm) Height: 8.25" (210 mm)</p>		<p>Part Number: P142802 Description: AIR PANEL, ENGINE Primary App: FARR PAMIC P-24-38, UNITED F-24-38 Dimensions: Width: 8.25" (210 mm) Depth: 7.79" (198 mm) Height: 19.78" (502 mm)</p>
	<p>Part Number: P142795 Description: AIR PANEL, ENGINE Primary App: FARR PAMIC P-12, UNITED F-12 Dimensions: Width: 8.15" (207 mm) Depth: 7.79" (198 mm) Height: 10.48" (266 mm)</p>		<p>Part Number: P142803 Description: AIR PANEL, ENGINE Primary App: FARR PAMIC P-32, UNITED F-32 Dimensions: Width: 10.50" (267 mm) Depth: 7.79" (198 mm) Height: 19.75" (502 mm)</p>
	<p>Part Number: P142796 Description: AIR PANEL, ENGINE Primary App: FARR PAMIC P-12-26, UNITED F-12-26 Dimensions: Width: 5.95" (151 mm) Depth: 7.79" (198 mm) Height: 15.09" (383 mm)</p>		<p>Part Number: P142804 Description: AIR PANEL, ENGINE Primary App: FARR PAMIC P-36, UNITED F-36 Dimensions: Width: 15.19" (386 mm) Depth: 7.79" (198 mm) Height: 15.19" (386 mm)</p>
	<p>Part Number: P142797 Description: AIR PANEL, ENGINE Primary App: FARR PAMIC P-16, UNITED F-16 Dimensions: Width: 10.50" (267 mm) Depth: 7.79" (198 mm) Height: 10.50" (267 mm)</p>		<p>Part Number: P142805 Description: AIR PANEL, ENGINE Primary App: FARR PAMIC P-40, UNITED F-40 Dimensions: Width: 12.84" (326 mm) Depth: 7.79" (198 mm) Height: 19.74" (501 mm)</p>
	<p>Part Number: P142798 Description: AIR PANEL, ENGINE Primary App: FARR PAMIC P-16-28, UNITED F-16-28 Dimensions: Width: 5.95" (151 mm) Depth: 7.79" (198 mm) Height: 19.75" (502 mm)</p>		<p>Part Number: P142806 Description: AIR PANEL, ENGINE Primary App: FARR PAMIC P-48, UNITED F-48 Dimensions: Width: 15.14" (385 mm) Depth: 7.79" (198 mm) Height: 19.74" (501 mm)</p>
	<p>Part Number: P142799 Description: AIR PANEL, ENGINE Primary App: FARR PAMIC P-18, UNITED F-18 Dimensions: Width: 8.28" (210 mm) Depth: 7.79" (198 mm) Height: 15.15" (385 mm)</p>		<p>Part Number: P142807 Description: AIR PANEL, ENGINE Primary App: FARR PAMIC P-64, UNITED F-64 Dimensions: Width: 18.74" (476 mm) Depth: 7.79" (198 mm) Height: 18.74" (476 mm)</p>
	<p>Part Number: P142800 Description: AIR PANEL, ENGINE Primary App: FARR PAMIC P-20, UNITED F-20 Dimensions: Width: 10.53" (267 mm) Depth: 7.79" (198 mm) Height: 12.78" (325 mm)</p>		<p>Part Number: P142810 Description: AIR PANEL, ENGINE Primary App: FARR DYNACELL T-519 Dimensions: Width: 19.00" (483 mm) Depth: 5.00" (127 mm) Height: 19.00" (483 mm)</p>
	<p>Part Number: P142801 Description: AIR PANEL, ENGINE Primary App: FARR PAMIC P-24, UNITED F-24 Dimensions: Width: 10.50" (267 mm) Depth: 7.79" (198 mm) Height: 15.09" (383 mm)</p>		<p>Part Number: P142811 Description: AIR PANEL, ENGINE Primary App: FARR DYNACELL T-519D Dimensions: Width: 19.00" (483 mm) Depth: 5.00" (127 mm) Height: 19.00" (483 mm)</p>

















	<p>Part Number: P142812 Description: AIR PANEL, ENGINE Primary App: FARR DYNACELL T-528 Dimensions: Width: 19.00" (483 mm) Depth: 5.00" (127 mm) Height: 28.50" (724 mm)</p>		<p>Part Number: P145755 Description: AIR SAFETY Primary App: JOHN DEERE AR80653 Dimensions: Outer Diameter: 5.14" (131 mm) Inner Diameter: 4.05" (103 mm) Length: 15.65" (398 mm) Bolt Hole Diameter: 0.66" (17 mm)</p>
	<p>Part Number: P142813 Description: AIR PANEL, ENGINE Primary App: FARR DYNACELL T-528D Dimensions: Width: 14.31" (363 mm) Depth: 8.00" (203 mm) Height: 23.25" (591 mm)</p>		<p>Part Number: P145756 Description: AIR PRIMARY Primary App: JOHN DEERE AR80652 Dimensions: Outer Diameter: 9.08" (231 mm) Inner Diameter: 5.24" (133 mm) Length: 19.38" (492 mm) Bolt Hole Diameter: 0.39" (10 mm) Gasket ID: 6.24" (158 mm)</p>
	<p>Part Number: P145649 Description: AIR PRIMARY Primary App: BOBCAT 6598492 Dimensions: Outer Diameter: 5.26" (134 mm) Inner Diameter: 2.64" (67 mm) Length: 11.00" (279 mm)</p>		<p>Part Number: P145859 Description: AIR PRIMARY Primary App: TEREX 9039992 Dimensions: Outer Diameter: 11.87" (301 mm) Inner Diameter: 10.25" (260 mm) Length: 17.66" (449 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket OD: 11.46" (291 mm)</p>
	<p>Part Number: P145700 Description: AIR PRIMARY Primary App: KOMATSU Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.73" (171 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 9.56" (242 mm)</p>		<p>Part Number: P145891 Description: AIR PRIMARY Primary App: GAS TURBINES, TORIT 8PP2134700 Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 26.00" (660 mm)</p>
	<p>Part Number: P145701 Description: AIR SAFETY Primary App: KOMATSU 6127-81-7413 Dimensions: Outer Diameter: 7.28" (185 mm) Inner Diameter: 6.20" (157 mm) Length: 17.70" (450 mm) Bolt Hole Diameter: 0.66" (17 mm)</p>		<p>Part Number: P146555 Description: AIR PANEL, VENTILATION Primary App: GAS TURBINE PANEL W/PLEAT SPACERS Dimensions: Width: 19.50" (495 mm) Depth: 5.19" (132 mm) Height: 19.50" (495 mm)</p>
	<p>Part Number: P145702 Description: AIR PRIMARY Primary App: KOMATSU, DONALDSON EGB14 AIR CLEANER Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.72" (196 mm) Length: 18.00" (457 mm) Bolt Hole Diameter: 0.93" (24 mm) Gasket ID: 10.12" (257 mm)</p>		<p>Part Number: P148018 Description: AIR PANEL Primary App: AMERICAN LINCOLN 8-24-04070 Dimensions: Width: 19.68" (500 mm) Depth: 2.19" (56 mm) Height: 23.94" (608 mm)</p>
	<p>Part Number: P145703 Description: AIR SAFETY Primary App: KOMATSU Dimensions: Outer Diameter: 4.58" (116 mm) Inner Diameter: 3.48" (88 mm) Length: 14.72" (374 mm) Bolt Hole Diameter: 0.66" (17 mm)</p>		<p>Part Number: P148043 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON ECG11 KONEPAC-TREATED AIR CLEANER Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.95" (177 mm) Length: 28.00" (711 mm) Gasket OD: 7.50" (190 mm) Gasket ID: 3.96" (101 mm)</p>
	<p>Part Number: P145704 Description: AIR PRIMARY Primary App: KOMATSU 6691817210 Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.85" (123 mm) Length: 15.00" (381 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 7.62" (193 mm)</p>		<p>Part Number: P148044 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON ECG09 KONEPAC-TREATED AIR CLEANER Dimensions: Outer Diameter: 8.66" (220 mm) Inner Diameter: 5.21" (132 mm) Length: 28.00" (711 mm) Gasket OD: 5.74" (146 mm) Gasket ID: 2.21" (56 mm)</p>
	<p>Part Number: P145709 Description: AIR PANEL, VENTILATION Primary App: STOLPER 1020597 Dimensions: Width: 11.00" (279 mm) Depth: 2.19" (56 mm) Height: 26.00" (660 mm)</p>		<p>Part Number: P148113 Description: AIR PRIMARY, FINNED Primary App: KUBOTA W/TOKYO ROKI AIR CLEANER Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 1.79" (45 mm) Length: 7.00" (178 mm) Gasket ID: 1.98" (50 mm) Minor OD: 0.42" (11 mm)</p>

















	<p>Part Number: P148573 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FHG08 CYCLOPAC AIR CLEANER Dimensions: Outer Diameter: 6.08" (154 mm) Inner Diameter: 3.49" (89 mm) Length: 15.00" (381 mm) Gasket ID: 4.45" (113 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P150135 Description: AIR PANEL, VENTILATION Primary App: CAT 4N-0015 Dimensions: Width: 15.00" (381 mm) Depth: 5.19" (132 mm) Height: 15.62" (397 mm)</p>
	<p>Part Number: P148586 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FHG06 CYCLOPAC AIR CLEANER Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 3.26" (83 mm) Length: 15.00" (381 mm) Gasket ID: 3.95" (100 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P150348 Description: AIR PANEL, VENTILATION Primary App: AMERICAN LINCOLN Dimensions: Width: 23.44" (595 mm) Depth: 2.19" (56 mm) Height: 11.94" (303 mm)</p>
	<p>Part Number: P148645 Description: AIR PANEL Primary App: AMERICAN LINCOLN 8-24-04071 Dimensions: Width: 23.94" (608 mm) Depth: 2.19" (56 mm) Height: 25.69" (653 mm)</p>		<p>Part Number: P150464 Description: AIR PRIMARY Primary App: SPEC. BLAST HOLE DRILL DUST COLL. Dimensions: Outer Diameter: 7.93" (201 mm) Inner Diameter: 3.57" (91 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 6.38" (162 mm)</p>
	<p>Part Number: P148932 Description: AIR PRIMARY, FINNED Primary App: HYSTER 336567 Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 3.25" (83 mm) Length: 15.00" (381 mm) Gasket ID: 3.95" (100 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P150692 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON ECG09 KONEPAC-STANDARD Dimensions: Outer Diameter: 8.66" (220 mm) Inner Diameter: 5.21" (132 mm) Length: 28.00" (711 mm) Gasket OD: 5.74" (146 mm) Gasket ID: 2.21" (56 mm)</p>
	<p>Part Number: P148966 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FW06 CYCLOPAC AIR CLEANER Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 2.64" (67 mm) Length: 11.00" (279 mm) Gasket ID: 3.95" (100 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P150693 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON ECG09 KONEPAC Dimensions: Outer Diameter: 8.66" (220 mm) Inner Diameter: 5.20" (132 mm) Length: 28.02" (712 mm) Gasket OD: 7.16" (182 mm) Gasket ID: 3.70" (94 mm)</p>
	<p>Part Number: P148968 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FW08 CYCLOPAC AIR CLEANER Dimensions: Outer Diameter: 6.08" (154 mm) Inner Diameter: 3.49" (89 mm) Length: 12.00" (305 mm) Gasket ID: 4.45" (113 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P150694 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON ECG11 KONEPAC - STANDARD Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.95" (177 mm) Length: 28.00" (711 mm) Gasket OD: 7.50" (190 mm) Gasket ID: 3.96" (101 mm)</p>
	<p>Part Number: P148969 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FW05 CYCLOPAC AIR CLEANER Dimensions: Outer Diameter: 4.08" (104 mm) Inner Diameter: 2.49" (63 mm) Length: 10.00" (254 mm) Gasket ID: 2.58" (66 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P150695 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON ECG11 KONEPAC Dimensions: Outer Diameter: 10.62" (270 mm) Inner Diameter: 6.69" (170 mm) Length: 28.02" (712 mm) Gasket OD: 9.21" (234 mm) Gasket ID: 5.22" (133 mm)</p>
	<p>Part Number: P148970 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FW04 CYCLOPAC AIR CLEANER Dimensions: Outer Diameter: 3.26" (83 mm) Inner Diameter: 1.68" (43 mm) Length: 7.00" (178 mm) Gasket OD: 3.00" (76 mm) Gasket ID: 2.50" (64 mm) Minor OD: 0.42" (11 mm)</p>		<p>Part Number: P150706 Description: AIR PRIMARY Primary App: IVECO TRUCK 4249-1619 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 3.49" (89 mm) Length: 14.00" (356 mm) D: 0.66" (17 mm) Gasket ID: 4.75" (121 mm)</p>
			<p>Part Number: P151028 Description: AIR PRIMARY Primary App: FRAM CA2550 Dimensions: Outer Diameter: 9.50" (241 mm) Inner Diameter: 6.89" (175 mm) Length: 27.44" (697 mm) Gasket ID: 8.12" (206 mm)</p>

















	<p>Part Number: P151097 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON EBA11 KONEPAC-STANDARD Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.95" (177 mm) Length: 28.00" (711 mm) Gasket OD: 7.50" (190 mm) Gasket ID: 3.96" (101 mm)</p>		<p>Part Number: P155842 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON SHORT ECG11 A/C, GMC 15527863 Dimensions: Outer Diameter: 10.62" (270 mm) Inner Diameter: 6.69" (170 mm) Length: 20.02" (509 mm) Gasket OD: 9.18" (233 mm) Gasket ID: 5.22" (133 mm)</p>
	<p>Part Number: P151098 Description: AIR PRIMARY Primary App: FLXIBLE BUS 14158154 Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 16.00" (406 mm) Gasket ID: 10.12" (257 mm)</p>		<p>Part Number: P158050 Description: AIR SAFETY Primary App: DONALDSON FVG16-0313, WHITE MOTOR Dimensions: Outer Diameter: 7.64" (194 mm) Inner Diameter: 6.04" (153 mm) Length: 15.00" (381 mm)</p>
	<p>Part Number: P151951 Description: AIR PRIMARY Primary App: MAN 81.08304.0024 Dimensions: Outer Diameter: 8.93" (227 mm) Inner Diameter: 4.56" (116 mm) Length: 14.50" (368 mm) Gasket ID: 5.42" (138 mm)</p>		<p>Part Number: P158333 Description: AIR PANEL, VENTILATION Primary App: CASE/IH 131413C1 Dimensions: Width: 6.00" (152 mm) Depth: 2.19" (56 mm) Height: 38.00" (965 mm)</p>
	<p>Part Number: P153551 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON SHORT ECG11 KONEPAC SERIES-STD Dimensions: Outer Diameter: 10.62" (270 mm) Inner Diameter: 6.69" (170 mm) Length: 22.02" (559 mm) Gasket OD: 9.21" (234 mm) Gasket ID: 5.22" (133 mm)</p>		<p>Part Number: P158661 Description: AIR SAFETY Primary App: CAT 2S-1285 Dimensions: Outer Diameter: 4.78" (121 mm) Inner Diameter: 3.62" (92 mm) Length: 12.08" (307 mm) Bolt Circle Diameter: 5.88" (149 mm)</p>
	<p>Part Number: P153962 Description: AIR PRIMARY Primary App: FLXIBLE BUS 97-5349-1 Dimensions: Outer Diameter: 13.84" (352 mm) Inner Diameter: 9.47" (241 mm) Length: 16.00" (406 mm) Gasket ID: 10.70" (272 mm)</p>		<p>Part Number: P158662 Description: AIR SAFETY Primary App: CAT 2S-1286 Dimensions: Outer Diameter: 6.31" (160 mm) Inner Diameter: 4.63" (118 mm) Length: 13.08" (332 mm) Bolt Circle Diameter: 7.69" (195 mm)</p>
	<p>Part Number: P153972 Description: AIR PRIMARY Primary App: FLXIBLE BUS 97-5409-1 Dimensions: Outer Diameter: 13.84" (352 mm) Inner Diameter: 9.47" (241 mm) Length: 16.00" (406 mm) Gasket ID: 10.70" (272 mm)</p>		<p>Part Number: P158663 Description: AIR SAFETY Primary App: CAT 2S-1287 Dimensions: Outer Diameter: 6.31" (160 mm) Inner Diameter: 4.63" (118 mm) Length: 16.15" (410 mm) Bolt Circle Diameter: 7.69" (195 mm)</p>
	<p>Part Number: P154575 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON SHORT ECG11 KONEPAC SERIES Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.95" (177 mm) Length: 22.00" (559 mm) Gasket OD: 7.50" (190 mm) Gasket ID: 3.96" (101 mm)</p>		<p>Part Number: P158664 Description: AIR SAFETY Primary App: CAT 2S-1284 Dimensions: Outer Diameter: 3.80" (97 mm) Inner Diameter: 2.64" (67 mm) Length: 10.08" (256 mm) Bolt Circle Diameter: 5.25" (133 mm)</p>
<p>Shape</p>  <p>Cross Section</p> 	<p>Part Number: P154686 Description: GASKET Primary App: DONALDSON KONEPAC 11" AIR CLEANER Dimensions: Inlet Diameter: 10.79" (274 mm) C: 0.69" (18 mm)</p>		<p>Part Number: P158665 Description: AIR SAFETY Primary App: CAT 3S-4745 Dimensions: Outer Diameter: 8.70" (221 mm) Inner Diameter: 7.00" (178 mm) Length: 15.28" (388 mm) Flange Diameter: 12.00" (305 mm)</p>
	<p>Part Number: P154927 Description: AIR PRIMARY, SPECIAL Primary App: FARR ECOII #71338-002, UNITED F-ECOII 11X24 Dimensions: Width: 11.00" (279 mm) Length: 25.75" (654 mm) Rated Flow HR: 1200.00 CFM (33.98 CMM) Restriction HR: 6.00 In H2O (152 mm H2O)</p>		<p>Part Number: P158666 Description: AIR SAFETY Primary App: CAT 4S-8834 Dimensions: Outer Diameter: 7.70" (196 mm) Inner Diameter: 6.00" (152 mm) Length: 8.78" (223 mm) Flange Diameter: 10.20" (259 mm)</p>



















	<p>Part Number: P158668 Description: AIR SAFETY Primary App: CAT 4S-8340 Dimensions: Outer Diameter: 7.70" (196 mm) Inner Diameter: 6.00" (152 mm) Length: 13.38" (340 mm) Flange Diameter: 10.20" (259 mm)</p>		<p>Part Number: P158854 Description: AIR PANEL, VENTILATION Primary App: JOHN DEERE AR61903 Dimensions: Width: 7.50" (190 mm) Depth: 2.83" (72 mm) Height: 28.00" (711 mm)</p>
	<p>Part Number: P158669 Description: AIR SAFETY Primary App: CAT 9S-9972 Dimensions: Outer Diameter: 6.28" (160 mm) Inner Diameter: 4.59" (117 mm) Length: 12.96" (329 mm) Flange Diameter: 9.06" (230 mm)</p>		<p>Part Number: P158893 Description: AIR PANEL, VENTILATION Primary App: FMC 304973 Dimensions: Width: 6.00" (152 mm) Depth: 2.19" (56 mm) Height: 30.00" (762 mm)</p>
	<p>Part Number: P158670 Description: AIR SAFETY Primary App: CAT 1P-7360 Dimensions: Outer Diameter: 7.46" (189 mm) Inner Diameter: 5.99" (152 mm) Length: 13.38" (340 mm) Flange Diameter: 10.20" (259 mm)</p>		<p>Part Number: P159036 Description: AIR SAFETY Primary App: KOMATSU Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 3.82" (97 mm) Length: 13.00" (330 mm)</p>
	<p>Part Number: P158671 Description: AIR SAFETY Primary App: CAT 4N-0313 Dimensions: Outer Diameter: 3.35" (85 mm) Inner Diameter: 2.27" (58 mm) Length: 10.00" (254 mm)</p>		<p>Part Number: P159548 Description: AIR PRIMARY Primary App: FORD D8NN9B618AA Dimensions: Outer Diameter: 9.14" (232 mm) Inner Diameter: 5.78" (147 mm) Length: 18.00" (457 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 7.00" (178 mm)</p>
	<p>Part Number: P158675 Description: AIR SAFETY Primary App: CAT 7N-1308, 1P-8482 Dimensions: Outer Diameter: 8.46" (215 mm) Inner Diameter: 6.99" (178 mm) Length: 15.28" (388 mm) Flange Diameter: 11.38" (289 mm)</p>		<p>Part Number: P160078 Description: HYDRAULIC CARTRIDGE Primary App: INSLEY 471351, DONALDSON HEK11 ASSEMBLY Dimensions: Outer Diameter: 7.44" (189 mm) Inner Diameter: 4.85" (123 mm) Length: 22.00" (559 mm) Efficiency 50% @ 149 Micron</p>
	<p>Part Number: P158676 Description: AIR SAFETY Primary App: CAT 7N-9027 Dimensions: Outer Diameter: 3.99" (101 mm) Inner Diameter: 2.32" (59 mm) Length: 5.07" (129 mm) Bolt Circle Diameter: 5.25" (133 mm)</p>		<p>Part Number: P160105 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HAK05 ASSEMBLY Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 5.00" (127 mm) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P158677 Description: AIR SAFETY Primary App: CAT 6N-6444 Dimensions: Outer Diameter: 8.46" (215 mm) Inner Diameter: 6.99" (178 mm) Length: 11.97" (304 mm) Flange Diameter: 11.38" (289 mm)</p>		<p>Part Number: P160116 Description: HYDRAULIC CARTRIDGE Primary App: OLD DOM D100-436-2, JOY 1816389, DCI HAK05/HDK06 Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 16.00" (406 mm) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P158678 Description: AIR SAFETY Primary App: CAT 943 WHEEL/TRACK LDR, #8N-4901 Dimensions: Outer Diameter: 4.60" (117 mm) Inner Diameter: 3.59" (91 mm) Length: 12.00" (305 mm) Bolt Circle Diameter: 5.88" (149 mm)</p>		<p>Part Number: P160516 Description: HYDRAULIC CARTRIDGE Primary App: CASE, GROVE, GARD/DENV, LOED CORP Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 16.00" (406 mm) Efficiency 50% @ 15 Micron</p>
	<p>Part Number: P158852 Description: AIR PRIMARY Primary App: FORD E6HZ9601A Dimensions: Outer Diameter: 7.93" (201 mm) Inner Diameter: 5.32" (135 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 6.38" (162 mm)</p>		
















	<p>Part Number: P160558 Description: HYDRAULIC CARTRIDGE Primary App: CLARK 888936,FMC #76J1505P, DONALDSON HAK05 Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 8.00" (203 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 13 Micron</p>		<p>Part Number: P161222 Description: HYDRAULIC CARTRIDGE Primary App: TAYLOR MACHINE 4044-318, DCI HHK05-RETURN Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 16.00" (406 mm) Efficiency 50% @ 149 Micron</p>
	<p>Part Number: P160605 Description: HYDRAULIC CARTRIDGE Primary App: EATON, I/R, HARNISCHFEGER #46Z419, DCI HAK05 Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 5.00" (127 mm) Efficiency 50% @ 15 Micron</p>		<p>Part Number: P161269 Description: HYDRAULIC STRAINER Primary App: DONALDSON HSK02 ASSBLY Dimensions: Outer Diameter: 3.75" (95 mm) Inner Diameter: 0.71" (18 mm) Length: 0.22" (5 mm) Efficiency 50% @ 175 Micron</p>
	<p>Part Number: P160616 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HDK06 ASSEMBLY Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 16.00" (406 mm) Efficiency 50% @ 15 Micron</p>		<p>Part Number: P161365 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HFK08 ASSEMBLY Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 3.41" (87 mm) Length: 18.00" (457 mm) Efficiency 50% @ 20 Micron Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P160700 Description: HYDRAULIC CARTRIDGE Primary App: JOY 1800108, SULLAIR 241185, DCI HAK05/HDK06 ASY Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 16.00" (406 mm) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P161402 Description: HYDRAULIC CARTRIDGE Primary App: GENERAL USAGE Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 8.00" (203 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P160807 Description: HYDRAULIC CARTRIDGE Primary App: IOWA MFG. 4517550903, DONALDSON HHK05-SUCTION Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 16.00" (406 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 35 Micron</p>		<p>Part Number: P161413 Description: HYDRAULIC CARTRIDGE Primary App: IR 35294024, DONALDSON HHK05-RETURN Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 8.00" (203 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P160896 Description: HYDRAULIC CARTRIDGE Primary App: CLARK, MARATHON LETOURNEAU #4068355 Dimensions: Outer Diameter: 7.44" (189 mm) Inner Diameter: 4.85" (123 mm) Length: 22.00" (559 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 35 Micron</p>		<p>Part Number: P161571 Description: HYDRAULIC CARTRIDGE Primary App: IR 52263209, DONALDSON HAK05 Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 16.00" (406 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 37 Micron</p>
	<p>Part Number: P161010 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HEK11 ASSBLY Dimensions: Outer Diameter: 7.44" (189 mm) Inner Diameter: 4.85" (123 mm) Length: 18.00" (457 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 35 Micron</p>		<p>Part Number: P161632 Description: HYDRAULIC CARTRIDGE Primary App: AMER H&D 1015077 Dimensions: Outer Diameter: 7.44" (189 mm) Inner Diameter: 4.85" (123 mm) Length: 18.00" (457 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P161016 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HAK05, HDK06 ASSEMBLIES, 1/2 MEDIA Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 16.00" (406 mm) Efficiency 99% @ 2 Micron</p>		<p>Part Number: P161650 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HHK05 ASSBLY Dimensions: Outer Diameter: 4.39" (112 mm) Inner Diameter: 2.44" (62 mm) Length: 8.00" (203 mm)</p>
	<p>Part Number: P161908 Description: HYDRAULIC CARTRIDGE Primary App: IOWA MFG 45177-509-03, AMER H&D 1205450 Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 10.00" (254 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 35 Micron</p>		


















	<p>Part Number: P161917 Description: HYDRAULIC CARTRIDGE Primary App: DRILTECH #318553 Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 13.00" (330 mm) Efficiency 50% @ 74 Micron</p>		<p>Part Number: P162855 Description: HYDRAULIC CARTRIDGE Primary App: CASE N6665 Dimensions: Outer Diameter: 4.39" (112 mm) Inner Diameter: 2.44" (62 mm) Length: 12.25" (311 mm)</p>
	<p>Part Number: P161969 Description: HYDRAULIC CARTRIDGE Primary App: AMER H&D 1206666 Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 13.00" (330 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 35 Micron</p>		<p>Part Number: P162953 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HPK03 ASSBLY Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.73" (44 mm) Length: 8.00" (203 mm) Efficiency 50% @ 4 Micron Efficiency 99% @ 16 Micron</p>
	<p>Part Number: P162104 Description: HYDRAULIC CARTRIDGE Primary App: GARDNER DENVER 2109093 Dimensions: Outer Diameter: 4.39" (112 mm) Inner Diameter: 2.44" (62 mm) Length: 8.00" (203 mm) Efficiency 50% @ 15 Micron</p>		<p>Part Number: P162955 Description: HYDRAULIC CARTRIDGE Primary App: HPK03 ELEMENT Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.74" (44 mm) Length: 8.00" (203 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P162181 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HHK05 ASSBLY Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 13.00" (330 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 35 Micron</p>		<p>Part Number: P162957 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HPK03 ASSBLY Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.73" (44 mm) Length: 8.00" (203 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 35 Micron</p>
	<p>Part Number: P162205 Description: HYDRAULIC SPIN-ON Primary App: IHC 1103452C2, Dimensions: Outer Diameter: 5.00" (127 mm) Thread Size: 3-8 Length: 8.81" (224 mm) Gasket OD: 5.00" (127 mm) Gasket ID: 4.50" (114 mm) Efficiency 50% @ 15 Micron</p>		<p>Part Number: P163172 Description: HYDRAULIC CARTRIDGE Primary App: DRILTECH, SULLAIR Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 8.00" (203 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 37 Micron</p>
	<p>Part Number: P162233 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HPK04 ASSEMBLY Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 8.03" (204 mm) Efficiency 50% @ 74 Micron</p>		<p>Part Number: P163244 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HPK03 ASSBLY Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.73" (44 mm) Length: 8.00" (203 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 17 Micron</p>
	<p>Part Number: P162368 Description: HYDRAULIC CARTRIDGE Primary App: CASE 116427, DONALDSON HAK05 ASSY Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 8.00" (203 mm) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P163315 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CAT 8T-7478, DONALDSON HMK04 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 5.97" (152 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P162766 Description: HYDRAULIC SPIN-ON Primary App: M/F 1053870M91, CHARLYNN 5610, DCI HBK04 ASSY Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 1 1/4-12 Length: 5.37" (136 mm) Gasket OD: 2.84" (72 mm) Gasket ID: 2.47" (63 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P163322 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CASE D89909, DONALDSON HMK04 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 15 Micron</p>



















	<p>Part Number: P16333 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CLARK 6598903, DONALDSON HMK04 ASSY Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 4 Micron</p>		<p>Part Number: P163434 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CASE D120594, FIAT ALLIS 73131887, DCI HMK04 Dimensions: Outer Diameter: 3.70" (94 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 4 Micron</p>
	<p>Part Number: P163324 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CASE N7332, IR #50995034, DONALDSON HMK04 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P163435 Description: HYDRAULIC SPIN-ON Primary App: IHC 1106643-C1, 1106643-C2 Dimensions: Outer Diameter: 5.00" (127 mm) Thread Size: 3-8 Length: 12.25" (311 mm) Gasket OD: 5.00" (127 mm) Gasket ID: 4.50" (114 mm) Efficiency 50% @ 15 Micron</p>
	<p>Part Number: P163405 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK04 ASSY Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 5.97" (152 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 4 Micron</p>		<p>Part Number: P163437 Description: HYDRAULIC CARTRIDGE Primary App: PUROLATOR, INGERSOLL RAND Dimensions: Outer Diameter: 4.00" (102 mm) Inner Diameter: 1.06" (27 mm) Length: 6.00" (152 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 35 Micron</p>
	<p>Part Number: P163412 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: IHC 1272051C1, DONALDSON HMK04 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 5.97" (152 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 5 Micron</p>		<p>Part Number: P163438 Description: HYDRAULIC CARTRIDGE Primary App: PUROLATOR, INGERSOLL RAND Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 1.75" (44 mm) Length: 7.12" (181 mm) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P163419 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CLARK 6599543, TRAILMOBILE 1035485, DCI HMK04 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 5.97" (152 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P163439 Description: HYDRAULIC CARTRIDGE Primary App: PUROLATOR, INGERSOLL RAND, GARDNER/DENVER Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 1.75" (44 mm) Length: 7.12" (181 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 35 Micron</p>
	<p>Part Number: P163425 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CASE L36242, KOEHRING 31252006, DONALDSON HMK04 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P163446 Description: HYDRAULIC CARTRIDGE Primary App: BUCYRUS ERIE #741572 Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 3.96" (101 mm) Length: 11.92" (303 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 13 Micron</p>
	<p>Part Number: P163428 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: IR 39136650, DONALDSON HMK04 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 5.97" (152 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P163447 Description: HYDRAULIC CARTRIDGE Primary App: HYSTER S-44643-2 Dimensions: Outer Diameter: 4.00" (102 mm) Inner Diameter: 1.56" (40 mm) Length: 14.81" (376 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 35 Micron</p>
	<p>Part Number: P163448 Description: HYDRAULIC CARTRIDGE Primary App: HYSTER, WABCO VS7413 Dimensions: Outer Diameter: 5.07" (129 mm) Inner Diameter: 3.34" (85 mm) Length: 9.00" (229 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 17 Micron</p>		<p>Part Number: P163448 Description: HYDRAULIC CARTRIDGE Primary App: HYSTER, WABCO VS7413 Dimensions: Outer Diameter: 5.07" (129 mm) Inner Diameter: 3.34" (85 mm) Length: 9.00" (229 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 17 Micron</p>

















	<p>Part Number: P163472 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HEK11 ASSEMBLY Dimensions: Outer Diameter: 7.44" (189 mm) Inner Diameter: 4.85" (123 mm) Length: 22.00" (559 mm) Efficiency 99% @ 2 Micron</p>		<p>Part Number: P163945 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HFK08 ASSEMBLY Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 3.41" (87 mm) Length: 18.00" (457 mm) Efficiency 50% @ 149 Micron</p>
	<p>Part Number: P163496 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CAT 090-2900, HYSTER 3006174, DONALDSON HMK04 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 5.97" (152 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 15 Micron</p>		<p>Part Number: P164056 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK04 ASSEMBLY Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 5 Micron</p>
	<p>Part Number: P163542 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CASE A165029, DONALDSON HMK04 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 5.97" (152 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 5 Micron</p>		<p>Part Number: P164059 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK04 ASSEMBLY Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 15 Micron</p>
	<p>Part Number: P163555 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: KOEHRING 853531235, DONALDSON HMK04 ASSY Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 5 Micron</p>		<p>Part Number: P164164 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUS4H Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 4.45" (113 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P163558 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: HAWKER SIDDLEY #10030972, DONALDSON HMK04 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P164166 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUS8H, DONALDSON HMK03/HPK04 ASSY Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 8.03" (204 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P163567 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: HYSTER 398886, DONALDSON HMK04 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P164168 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUS13H Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 12.76" (324 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P163903 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER KS7 Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.61" (41 mm) Length: 9.02" (229 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P164170 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUS16H, DONALDSON HMK04 ASSY Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 16.67" (423 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P163910 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER KS15 Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.61" (41 mm) Length: 9.02" (229 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P164172 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUT4H Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 4.45" (113 mm) Efficiency 50% @ 7 Micron Efficiency 99% @ 22 Micron</p>

















	<p>Part Number: P164174 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUT8H, DONALDSON HPK03/HPK04 ASSY Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 8.20" (208 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P164217 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8300FUT8H Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 4.12" (105 mm) Length: 8.13" (207 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P164176 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUT13H Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 12.93" (328 mm) Efficiency 50% @ 7 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P164219 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8300FUS16H Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 4.17" (106 mm) Length: 16.77" (426 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P164178 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUT16H, PUROLATOR 9313214, DCI HPK04 Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 16.84" (428 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P164221 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8300FUS16H Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 4.17" (106 mm) Length: 16.77" (426 mm) Efficiency 50% @ 7 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P164200 Description: HYDRAULIC CARTRIDGE Primary App: CAT 9M-9740, 2M-3943, 1M-9156 Dimensions: Outer Diameter: 4.00" (102 mm) Inner Diameter: 2.30" (58 mm) Length: 9.25" (235 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 16 Micron</p>		<p>Part Number: P164223 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9400FUS13H Dimensions: Outer Diameter: 3.75" (95 mm) Inner Diameter: 2.21" (56 mm) Length: 12.76" (324 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P164203 Description: HYDRAULIC CARTRIDGE Primary App: CAT 4J-0816 Dimensions: Outer Diameter: 3.34" (85 mm) Inner Diameter: 1.86" (47 mm) Length: 9.00" (229 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 16 Micron</p>		<p>Part Number: P164225 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9400FUT13H Dimensions: Outer Diameter: 3.75" (95 mm) Inner Diameter: 2.21" (56 mm) Length: 12.76" (324 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P164205 Description: HYDRAULIC CARTRIDGE Primary App: CAT 4J-6064, 4J-0806, 2J-1560 Dimensions: Outer Diameter: 5.07" (129 mm) Inner Diameter: 3.34" (85 mm) Length: 9.00" (229 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 16 Micron</p>		<p>Part Number: P164227 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9400FUS26H, DONALDSON HPK05 ASSY Dimensions: Outer Diameter: 3.75" (95 mm) Inner Diameter: 2.21" (56 mm) Length: 25.53" (648 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P164207 Description: HYDRAULIC CARTRIDGE Primary App: CAT 7J-0670 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 4.23" (107 mm) Length: 9.00" (229 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 16 Micron</p>		<p>Part Number: P164229 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9400FUT26H, DONALDSON HPK05 ASSY Dimensions: Outer Diameter: 3.75" (95 mm) Inner Diameter: 2.21" (56 mm) Length: 25.53" (648 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P164215 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8300FUS8H Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 4.12" (105 mm) Length: 8.13" (207 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P164241 Description: HYDRAULIC CARTRIDGE Primary App: CAT 9J-0750, 9J-5461, GMC 25012355 Dimensions: Outer Diameter: 5.07" (129 mm) Inner Diameter: 3.34" (85 mm) Length: 11.00" (279 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 16 Micron</p>
	<p>Part Number: P164266 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HHK05 ASSEMBLY Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 16.00" (406 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 17 Micron</p>		<p>Part Number: P164266 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HHK05 ASSEMBLY Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 16.00" (406 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 17 Micron</p>

	<p>Part Number: P164270 Description: HYDRAULIC CARTRIDGE Primary App: IHC 940241C2 Dimensions: Outer Diameter: 7.44" (189 mm) Inner Diameter: 4.85" (123 mm) Length: 18.00" (457 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 35 Micron</p>	<p>Part Number: P164368 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUT4Z Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 4.62" (117 mm)</p>
	<p>Part Number: P164277 Description: HYDRAULIC CARTRIDGE Primary App: HYSTER 320006 Dimensions: Outer Diameter: 4.00" (102 mm) Inner Diameter: 1.56" (40 mm) Length: 14.81" (376 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 13 Micron</p>	 <p>Part Number: P164375 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CLARK 6630977, DONALDSON HMK04 ASSY Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 5.97" (152 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 5 Micron</p>
	<p>Part Number: P164348 Description: HYDRAULIC SPIN-ON Primary App: IR 35327824, CHARLYNN 5604, DCI HBK04 ASSY Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 1 1/4-12 Length: 5.37" (136 mm) Gasket OD: 2.84" (72 mm) Gasket ID: 2.47" (63 mm) Efficiency 50% @ 25 Micron</p>	 <p>Part Number: P164378 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: ADVANCE 496209, KOEHRING 853531244 (DCI HMK04) Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 5 Micron</p>
	<p>Part Number: P164351 Description: HYDRAULIC SPIN-ON Primary App: GARDNER DENVER 2109648, DONALDSON HBK04 ASSY Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 1 1/4-12 Length: 8.69" (221 mm) Gasket OD: 2.84" (72 mm) Gasket ID: 2.47" (63 mm) Efficiency 50% @ 10 Micron</p>	 <p>Part Number: P164381 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CASE X724693, DONALDSON HMK04 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 5.97" (152 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 7 Micron</p>
	<p>Part Number: P164352 Description: HYDRAULIC SPIN-ON Primary App: IR 35296920, DONALDSON HBK04 ASSEMBLY Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 1 1/4-12 Length: 8.69" (221 mm) Gasket OD: 2.84" (72 mm) Gasket ID: 2.47" (63 mm) Efficiency 50% @ 25 Micron</p>	 <p>Part Number: P164384 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CASE N9025, CAT 9T-5916, DEERE AH114973 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P164364 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUS4Z Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 4.45" (113 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 16 Micron</p>	 <p>Part Number: P164405 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HFK08 ASSBLY Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 3.41" (87 mm) Length: 18.00" (457 mm) Efficiency 99% @ 2 Micron</p>
	<p>Part Number: P164365 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUS8Z, DONALDSON HPK03 ASSY Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 8.03" (204 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 16 Micron</p>	 <p>Part Number: P164413 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HEK11 HYD ASSY Dimensions: Outer Diameter: 7.44" (189 mm) Inner Diameter: 4.85" (123 mm) Length: 22.00" (559 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 37 Micron</p>
	<p>Part Number: P164367 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUS16Z, DONALDSON HPK04 ASSY Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 16.67" (423 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 16 Micron</p>	 <p>Part Number: P164556 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 922625 Dimensions: Outer Diameter: 2.44" (62 mm) Inner Diameter: 1.00" (25 mm) Length: 5.00" (127 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 35 Micron</p>
















	<p>Part Number: P164561 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9400FUS39H Dimensions: Outer Diameter: 3.75" (95 mm) Inner Diameter: 2.18" (55 mm) Length: 38.52" (978 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P164596 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUN13H Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 12.76" (324 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P164565 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8300FUS39H Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 4.16" (106 mm) Length: 38.62" (981 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 16 Micron</p>		<p>Part Number: P164598 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUN16H, DONALDSON HPK04 ASSY Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 16.67" (423 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P164574 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8300FUN8H Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 4.12" (105 mm) Length: 8.13" (207 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P164601 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUN8Z, DONALDSON HPK04 ASSY Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 8.03" (204 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P164576 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8300FUN16H Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 4.17" (106 mm) Length: 16.77" (426 mm)</p>		<p>Part Number: P164603 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FKN16Z Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 16.67" (423 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P164580 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8300FUN8Z, PARKER 927862 Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 4.12" (105 mm) Length: 8.13" (207 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P164697 Description: HYDRAULIC CARTRIDGE Primary App: DEERE AT78046, GROVE 7437800011, DCI HAK05/HKD06 Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 16.00" (406 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 16 Micron</p>
	<p>Part Number: P164583 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9400FUN13H Dimensions: Outer Diameter: 3.75" (95 mm) Inner Diameter: 2.21" (56 mm) Length: 12.76" (324 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P164699 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HAK05 & HDK06 ASSEMBLY Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 16.00" (406 mm) Efficiency 50% @ 7 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P164585 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9400FUN26H, DONALDSON HPK05 ASSY Dimensions: Outer Diameter: 3.75" (95 mm) Inner Diameter: 2.21" (56 mm) Length: 25.53" (648 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P164701 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HFK08 ASSEMBLY Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 3.41" (87 mm) Length: 18.00" (457 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 16 Micron</p>
	<p>Part Number: P164592 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUN4H Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 4.45" (113 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P164703 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HFK08 ASSEMBLY Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 3.41" (87 mm) Length: 18.00" (457 mm) Efficiency 50% @ 7 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P164594 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUN8H, DONALDSON HPK03 ASSY Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 8.03" (204 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		

	<p>Part Number: P164707 Description: HYDRAULIC CARTRIDGE Primary App: GROVE #7437000168, DONALDSON HEK11 ASSY Dimensions: Outer Diameter: 7.44" (189 mm) Inner Diameter: 4.85" (123 mm) Length: 22.00" (559 mm) Efficiency 50% @ 7 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P164906 Description: HYDRAULIC CARTRIDGE Primary App: JOHN DEERE AR98098 Dimensions: Outer Diameter: 4.61" (117 mm) Inner Diameter: 2.19" (56 mm) Length: 7.79" (198 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P164810 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER JS-7 Dimensions: Outer Diameter: 3.53" (90 mm) Inner Diameter: 1.61" (41 mm) Length: 9.02" (229 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P164917 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8500FUS8H Dimensions: Outer Diameter: 3.76" (96 mm) Inner Diameter: 1.72" (44 mm) Length: 8.05" (204 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 16 Micron</p>
	<p>Part Number: P164812 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER J10 OR J25 Dimensions: Outer Diameter: 3.53" (90 mm) Inner Diameter: 1.61" (41 mm) Length: 9.02" (229 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P164919 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8500FUS13H Dimensions: Outer Diameter: 3.76" (96 mm) Inner Diameter: 1.72" (44 mm) Length: 12.80" (325 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P164814 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER AS-7, A-3 Dimensions: Outer Diameter: 2.99" (76 mm) Inner Diameter: 1.04" (26 mm) Length: 4.75" (121 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P164921 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8500FUS26H Dimensions: Outer Diameter: 3.76" (96 mm) Inner Diameter: 1.72" (44 mm) Length: 25.57" (649 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P164816 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER A10 OR A25 Dimensions: Outer Diameter: 2.99" (76 mm) Inner Diameter: 1.04" (26 mm) Length: 4.75" (121 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P165006 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9020FUS4H, DONALDSON HPK02 ASSY Dimensions: Outer Diameter: 1.77" (45 mm) Inner Diameter: 1.00" (25 mm) Length: 4.31" (109 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P164852 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8400FUS16H, HARNISCHFEGER 1046Z493 Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 3.28" (83 mm) Length: 16.77" (426 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P165015 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9020FUS8H, DONALDSON HPK02 ASSY Dimensions: Outer Diameter: 1.77" (45 mm) Inner Diameter: 1.00" (25 mm) Length: 7.94" (202 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P164853 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8400FUS26H Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 3.28" (83 mm) Length: 25.62" (651 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P165041 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9020FUN4H, DONALDSON HPK02 ASSY Dimensions: Outer Diameter: 1.77" (45 mm) Inner Diameter: 1.00" (25 mm) Length: 4.31" (109 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P164884 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HHK05 ASSBLY Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 13.00" (330 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P165043 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9020FUN8H, DONALDSON HPK02 ASSY Dimensions: Outer Diameter: 1.77" (45 mm) Inner Diameter: 1.00" (25 mm) Length: 7.94" (202 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P164904 Description: HYDRAULIC CARTRIDGE Primary App: JOHN DEERE AR94510 Dimensions: Outer Diameter: 4.61" (117 mm) Inner Diameter: 2.19" (56 mm) Length: 7.79" (198 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 17 Micron</p>		<p>Part Number: P165043 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9020FUN8H, DONALDSON HPK02 ASSY Dimensions: Outer Diameter: 1.77" (45 mm) Inner Diameter: 1.00" (25 mm) Length: 7.94" (202 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>



















	<p>Part Number: P165112 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 922792, 901535 Dimensions: Outer Diameter: 2.73" (69 mm) Inner Diameter: 1.68" (43 mm) Length: 5.56" (141 mm) Efficiency 50% @ 20 Micron Efficiency 99% @ 40 Micron</p>		<p>Part Number: P165160 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8500FUN13H Dimensions: Outer Diameter: 3.76" (96 mm) Inner Diameter: 1.72" (44 mm) Length: 12.80" (325 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P165136 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9020FUT4H, DONALDSON HPK02 ASSY Dimensions: Outer Diameter: 1.77" (45 mm) Inner Diameter: 1.00" (25 mm) Length: 4.31" (109 mm) Efficiency 50% @ 7 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P165162 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8500FUN26H Dimensions: Outer Diameter: 3.76" (96 mm) Inner Diameter: 1.72" (44 mm) Length: 25.57" (649 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P165138 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9020FUT8H, DONALDSON HPK02 ASSY Dimensions: Outer Diameter: 1.77" (45 mm) Inner Diameter: 1.00" (25 mm) Length: 7.94" (202 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P165166 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8500FUN13H Dimensions: Outer Diameter: 3.76" (96 mm) Inner Diameter: 1.72" (44 mm) Length: 12.80" (325 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P165142 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8400FUN16H Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 3.28" (83 mm) Length: 16.77" (426 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P165168 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8500FUN26H Dimensions: Outer Diameter: 3.76" (96 mm) Inner Diameter: 1.72" (44 mm) Length: 25.57" (649 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P165144 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8400FUN26H Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 3.28" (83 mm) Length: 25.62" (651 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P165171 Description: HYDRAULIC CARTRIDGE Primary App: CLARK 2515079 Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 3.41" (87 mm) Length: 18.00" (457 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P165149 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8400FUT8H Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 3.28" (83 mm) Length: 8.13" (207 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P165185 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK04 ASSEMBLY Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 99% @ 2 Micron</p>
	<p>Part Number: P165151 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8400FUT16H Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 3.28" (83 mm) Length: 16.77" (426 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P165231 Description: HYDRAULIC CARTRIDGE Primary App: JOHN DEERE RE11889 Dimensions: Outer Diameter: 4.61" (117 mm) Inner Diameter: 2.19" (56 mm) Length: 5.29" (134 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 16 Micron</p>
	<p>Part Number: P165158 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8500FUN8H Dimensions: Outer Diameter: 3.76" (96 mm) Inner Diameter: 1.72" (44 mm) Length: 8.05" (204 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P165233 Description: HYDRAULIC CARTRIDGE Primary App: JOHN DEERE AR99661 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.63" (67 mm) Length: 7.83" (199 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>


















	<p>Part Number: P165238 Description: HYDRAULIC CARTRIDGE Primary App: CAT 4T-3131 Dimensions: Outer Diameter: 4.00" (102 mm) Inner Diameter: 2.30" (58 mm) Length: 9.25" (235 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P165319 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HPK03,HPK04 ASSEMBLIES Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 8.03" (204 mm) Efficiency 50% @ 20 Micron Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P165239 Description: HYDRAULIC CARTRIDGE Primary App: CAT 4T-3132 Dimensions: Outer Diameter: 5.07" (129 mm) Inner Diameter: 3.34" (85 mm) Length: 9.00" (229 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P165332 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK04 ASSEMBLY Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 2 Micron</p>
	<p>Part Number: P165240 Description: HYDRAULIC CARTRIDGE Primary App: CAT 4T-3133 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 4.23" (107 mm) Length: 9.00" (229 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 13 Micron</p>		<p>Part Number: P165335 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK04 ASSY Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 5.97" (152 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P165242 Description: HYDRAULIC CARTRIDGE Primary App: FIAT ALLIS #73125853 Dimensions: Outer Diameter: 5.07" (129 mm) Inner Diameter: 3.35" (85 mm) Length: 9.00" (229 mm)</p>		<p>Part Number: P165338 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK04 ASSEMBLY Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P165243 Description: HYDRAULIC SPIN-ON Primary App: CASE D59062 Dimensions: Outer Diameter: 3.88" (99 mm) Thread Size: 1 5/16-12 Length: 5.75" (146 mm) Gasket OD: 3.51" (89 mm) Gasket ID: 3.23" (82 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P165354 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK04 ASSEMBLY Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 5.97" (152 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 2 Micron</p>
	<p>Part Number: P165249 Description: HYDRAULIC CARTRIDGE Primary App: IR 39123229, 39123237 Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 16.00" (406 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 35 Micron</p>		<p>Part Number: P165378 Description: HYDRAULIC CARTRIDGE Primary App: GROVE, HARNISHFEGER, DONALDSON HAK05 Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 13.00" (330 mm) Efficiency 50% @ 7 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P165251 Description: HYDRAULIC CARTRIDGE Primary App: TIMBERJACK 841153100 Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 1.98" (50 mm) Length: 8.00" (203 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P165449 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HEK11 ASSEMBLY Dimensions: Outer Diameter: 7.44" (189 mm) Inner Diameter: 4.85" (123 mm) Length: 22.00" (559 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 13 Micron</p>
	<p>Part Number: P165314 Description: HYDRAULIC CARTRIDGE Primary App: GENERAL HIGH PERF CARTRIDGE Dimensions: Outer Diameter: 4.50" (114 mm) Inner Diameter: 2.24" (57 mm) Length: 9.53" (242 mm) Efficiency 50% @ 7 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P165569 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CAT, CLARK, IHC, HYSTER, DCI HMK05 & HMK25 ASSY Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 11.63" (295 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm) Efficiency 50% @ 10 Micron</p>

	<p>Part Number: P165584 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9650FUN8H Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 8.37" (213 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P165672 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: LEROI 438931, DONALDSON HMK05 & HMK25 ASSY Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 11.63" (295 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P165585 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9650FUS8H Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 8.37" (213 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P165675 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK05 & HMK25 ASSEMBLY Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 11.63" (295 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm) Efficiency 50% @ 2 Micron</p>
	<p>Part Number: P165586 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9650FUT8H Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 8.37" (213 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P165705 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CHAMPION 37104, CLARK 965899, DCI HMK05,HMK25 Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 11.63" (295 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm) Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P165587 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9650FUN16H Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 16.67" (423 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P165744 Description: HYDRAULIC CARTRIDGE Primary App: WABCO PB4545 Dimensions: Outer Diameter: 5.07" (129 mm) Inner Diameter: 3.34" (85 mm) Length: 18.50" (470 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 17 Micron</p>
	<p>Part Number: P165588 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9650FUS16H Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 16.67" (423 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P165762 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7500SKN8H, DONALDSON HBK05 ASSY Dimensions: Outer Diameter: 5.08" (129 mm) Thread Size: 1 1/2-16 Length: 10.66" (271 mm) Gasket OD: 5.05" (128 mm) Gasket ID: 4.71" (120 mm) Efficiency 50% @ 2 Micron</p>
	<p>Part Number: P165589 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9650FUT16H Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 16.67" (423 mm) Efficiency 50% @ 7 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P165786 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 922787(x2) & 926849 Connector Dimensions: Outer Diameter: 5.62" (143 mm) Inner Diameter: 3.72" (95 mm) Length: 24.19" (614 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P165626 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HAK05 ASSEMBLY Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 8.00" (203 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P165875 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7500SUS4H, DONALDSON HBK05 ASSY Dimensions: Outer Diameter: 5.08" (129 mm) Thread Size: 1 1/2-16 Length: 6.66" (169 mm) Gasket OD: 5.05" (128 mm) Gasket ID: 4.71" (120 mm) Efficiency 50% @ 2 Micron</p>
	<p>Part Number: P165628 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HAK05 & HDK06 ASSEMBLY Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 16.00" (406 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P165876 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7500SUS8H, HC7500SUK8H, DCI HBK05 ASSY Dimensions: Outer Diameter: 5.08" (129 mm) Thread Size: 1 1/2-16 Length: 10.66" (271 mm) Gasket OD: 5.05" (128 mm) Gasket ID: 4.71" (120 mm) Efficiency 50% @ 2 Micron</p>
	<p>Part Number: P165659 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CASE N9086, DONALDSON HMK05, HMK25 ASSEMBLY Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 11.63" (295 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm) Efficiency 50% @ 5 Micron</p>		

	<p>Part Number: P165877 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7500SUT4H, ZINGA SE-25, DCI HBK05 ASSY Dimensions: Outer Diameter: 5.08" (129 mm) Thread Size: 1 1/2-16 Length: 6.66" (169 mm) Gasket OD: 5.05" (128 mm) Gasket ID: 4.71" (120 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P166246 Description: HYDRAULIC CARTRIDGE Primary App: IR 35330133 Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 16.00" (406 mm) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P165878 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7500SUT8H, DONALDSON HBK05 ASSY Dimensions: Outer Diameter: 5.08" (129 mm) Thread Size: 1 1/2-16 Length: 10.66" (271 mm) Gasket OD: 5.05" (128 mm) Gasket ID: 4.71" (120 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P166254 Description: TRANSMISSION CARTRIDGE Primary App: DDA, GMC #23018850 (CLEANUP) Dimensions: Outer Diameter: 4.30" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 12.76" (324 mm) Efficiency 50% @ 2 Micron</p>
	<p>Part Number: P165879 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7500SUK4H, DONALDSON HBK05 ASSY Dimensions: Outer Diameter: 5.08" (129 mm) Thread Size: 1 1/2-16 Length: 6.66" (169 mm) Gasket OD: 5.05" (128 mm) Gasket ID: 4.71" (120 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P166255 Description: TRANSMISSION CARTRIDGE Primary App: DDA, GMC #23018851 Dimensions: Outer Diameter: 3.12" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 12.76" (324 mm) Efficiency 50% @ 5 Micron</p>
	<p>Part Number: P165880 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7500SUK8H, DONALDSON HBK05 ASSY Dimensions: Outer Diameter: 5.08" (129 mm) Thread Size: 1 1/2-16 Length: 10.66" (271 mm) Gasket OD: 5.05" (128 mm) Gasket ID: 4.71" (120 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P166375 Description: TRANSMISSION CARTRIDGE Primary App: GM 53, 71, 92 SERIES, DD 5573014 Dimensions: Outer Diameter: 4.30" (109 mm) Inner Diameter: 1.40" (36 mm) Length: 8.90" (226 mm) Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P166135 Description: TRANSMISSION CARTRIDGE Primary App: DET. DIESEL, GMC #23018853, 23049374 (CLEAN UP) Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 2.18" (55 mm) Length: 16.68" (424 mm) Efficiency 50% @ 2 Micron</p>		<p>Part Number: P166446 Description: HYDRAULIC CARTRIDGE Primary App: KOEHRING 7055098, 4313252, 301955098 Dimensions: Outer Diameter: 6.50" (165 mm) Inner Diameter: 3.54" (90 mm) Length: 15.12" (384 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 16 Micron</p>
	<p>Part Number: P166136 Description: TRANSMISSION CARTRIDGE Primary App: DETROIT DIESEL, GMC #23018852 Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 2.18" (55 mm) Length: 16.68" (424 mm) Efficiency 50% @ 5 Micron</p>		<p>Part Number: P166460 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HAK05 ASSEMBLY Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 8.00" (203 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 16 Micron</p>
	<p>Part Number: P166167 Description: TRANSMISSION CARTRIDGE Primary App: DDA #5574978, 2-53, 3-53 ENGINES Dimensions: Outer Diameter: 4.30" (109 mm) Inlet Diameter: 1.41" (36 mm) Length: 5.70" (145 mm)</p>		<p>Part Number: P166461 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HAK05 ASSEMBLY Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 8.00" (203 mm) Efficiency 50% @ 7 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P166204 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 908649 Dimensions: Outer Diameter: 5.62" (143 mm) Inner Diameter: 3.72" (95 mm) Length: 12.00" (305 mm) Efficiency 50% @ 20 Micron Efficiency 99% @ 40 Micron</p>		<p>Part Number: P166462 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HFK08 ASSEMBLY Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 3.41" (87 mm) Length: 18.00" (457 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>

	<p>Part Number: P166474 Description: HYDRAULIC CARTRIDGE Primary App: KOEHRING 288B1984 Dimensions: Outer Diameter: 6.50" (165 mm) Inner Diameter: 3.00" (76 mm) Length: 18.50" (470 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 16 Micron</p>		<p>Part Number: P167181 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9021FUT4Z, DCI HPK02 ASSY Dimensions: Outer Diameter: 1.75" (44 mm) Inner Diameter: 1.00" (25 mm) Length: 4.44" (113 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P166481 Description: LUBE CARTRIDGE FULL FLOW Primary App: CAT 5S-0485 Dimensions: Outer Diameter: 5.07" (129 mm) Inner Diameter: 3.34" (85 mm) Length: 9.00" (229 mm) Efficiency 99% @ 22 Micron</p>		<p>Part Number: P167182 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9021FUP8Z, DCI HPK02 ASSEMBLY Dimensions: Outer Diameter: 1.75" (44 mm) Inner Diameter: 1.00" (25 mm) Length: 8.12" (206 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P166549 Description: HYDRAULIC CARTRIDGE Primary App: TROJAN 2092442 Dimensions: Outer Diameter: 5.07" (129 mm) Inner Diameter: 3.35" (85 mm) Length: 9.00" (229 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P167183 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9021FUT8Z, DCI HPK02 ASSY Dimensions: Outer Diameter: 1.75" (44 mm) Inner Diameter: 1.00" (25 mm) Length: 8.12" (206 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P166564 Description: LUBE SPIN-ON FULL FLOW Primary App: GM CAR & TRUCK Dimensions: Outer Diameter: 3.73" (95 mm) Thread Size: 13/16-16 Length: 5.37" (136 mm) Gasket OD: 3.45" (88 mm) Gasket ID: 3.00" (76 mm) Efficiency 99% @ 22 Micron</p>		<p>Part Number: P167184 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9601FUP4Z, HC9601FUP4H Dimensions: Outer Diameter: 3.12" (79 mm) Inner Diameter: 1.70" (43 mm) Length: 4.55" (116 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P166597 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HAK05 ASSEMBLY Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 2.44" (62 mm) Length: 16.00" (406 mm) Efficiency 50% @ 20 Micron Efficiency 99% @ 40 Micron</p>		<p>Part Number: P167185 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9601FUP8H Dimensions: Outer Diameter: 3.12" (79 mm) Inner Diameter: 1.70" (43 mm) Length: 8.20" (208 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P166901 Description: HYDRAULIC CARTRIDGE Primary App: HFK08 ELEMENT (SPECIAL APPLICATION) Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 3.41" (87 mm) Length: 18.00" (457 mm)</p>		<p>Part Number: P167186 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9601FUT8H, DONALDSON HPK04 ASSEMBLY Dimensions: Outer Diameter: 3.12" (79 mm) Inner Diameter: 1.70" (43 mm) Length: 8.20" (208 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P167162 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7500SUN4H, DONALDSON HBK05 ASSY Dimensions: Outer Diameter: 5.08" (129 mm) Thread Size: 1 1/2-16 Length: 6.66" (169 mm) Gasket OD: 5.05" (128 mm) Gasket ID: 4.71" (120 mm) Efficiency 50% @ 2 Micron</p>		<p>Part Number: P167187 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9601FUP16H, DONALDSON HYDRAULIC ASSEMBLY Dimensions: Outer Diameter: 3.12" (79 mm) Inner Diameter: 1.70" (43 mm) Length: 16.81" (427 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P167180 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9021FUP4Z, DCI HPK02 ASSY Dimensions: Outer Diameter: 1.75" (44 mm) Inner Diameter: 1.00" (25 mm) Length: 4.44" (113 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P167188 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9601FUT16H, DONALDSON HYDRAULIC ASSEMBLY Dimensions: Outer Diameter: 3.12" (79 mm) Inner Diameter: 1.70" (43 mm) Length: 16.81" (427 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>

	<p>Part Number: P167270 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9801FUP4Z Dimensions: Outer Diameter: 2.00" (51 mm) Inner Diameter: 0.94" (24 mm) Length: 4.56" (116 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P167425 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER K25 HYD APPL Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.61" (41 mm) Length: 9.02" (229 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P167410 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER K10, KK10 HYD APPL Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.61" (41 mm) Length: 9.02" (229 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P167514 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER K-3 Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.61" (41 mm) Length: 9.02" (229 mm) Efficiency 50% @ 4 Micron Efficiency 99% @ 16 Micron</p>
	<p>Part Number: P167411 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9601FUP13H, DONALDSON HYDRAULIC ASSEMBLY Dimensions: Outer Diameter: 3.12" (79 mm) Inner Diameter: 1.70" (43 mm) Length: 12.95" (329 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P167516 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER J-10 Dimensions: Outer Diameter: 3.53" (90 mm) Inner Diameter: 1.61" (41 mm) Length: 9.02" (229 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P167412 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9601FUT13H, DONALDSON HYDRAULIC ASSEMBLY Dimensions: Outer Diameter: 3.12" (79 mm) Inner Diameter: 1.70" (43 mm) Length: 12.95" (329 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P167518 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER J-3 Dimensions: Outer Diameter: 3.53" (90 mm) Inner Diameter: 1.61" (41 mm) Length: 9.02" (229 mm) Efficiency 50% @ 4 Micron Efficiency 99% @ 16 Micron</p>
	<p>Part Number: P167413 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9801FUT4H, DONALDSON HYDRAULIC ASSEMBLY Dimensions: Outer Diameter: 2.00" (51 mm) Inner Diameter: 0.94" (24 mm) Length: 4.56" (116 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P167520 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER A-3 Dimensions: Outer Diameter: 3.00" (76 mm) Inner Diameter: 1.04" (26 mm) Length: 4.75" (121 mm) Efficiency 50% @ 4 Micron Efficiency 99% @ 16 Micron</p>
	<p>Part Number: P167414 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9801FUP8H, DONALDSON HYDRAULIC ASSEMBLY Dimensions: Outer Diameter: 2.00" (51 mm) Inner Diameter: 0.94" (24 mm) Length: 8.23" (209 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P167522 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER A-10 Dimensions: Outer Diameter: 3.00" (76 mm) Inner Diameter: 1.04" (26 mm) Length: 4.75" (121 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P167415 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9801FUT8H, DONALDSON HYDRAULIC ASSEMBLY Dimensions: Outer Diameter: 2.00" (51 mm) Inner Diameter: 0.94" (24 mm) Length: 8.23" (209 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>	<p>Shape  Cross Section </p>	<p>Part Number: P167574 Description: GASKET COVER Primary App: 500, 750 BYPASS HOUSINGS BEVELED X SECTION Dimensions: Inlet Diameter: 8.47" (215 mm) C: 0.25" (6 mm)</p>
	<p>Part Number: P167417 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9801FUT13Z Dimensions: Outer Diameter: 2.00" (51 mm) Inner Diameter: 0.94" (24 mm) Length: 12.87" (327 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>	<p>Shape  Cross Section </p>	<p>Part Number: P167575 Description: GASKET, COVER Primary App: 500, 750 BYPASS HOUSINGS SQUARE X SECTION Dimensions: Outer Diameter: 4.30" (109 mm) Inlet Diameter: 8.00" (203 mm) Length: 0.27" (7 mm)</p>

	<p>Part Number: P167590 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK04 ASSEMBLY Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P167838 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9020FUP8H, DONALDSON HPK02 ASSY Dimensions: Outer Diameter: 1.77" (45 mm) Inner Diameter: 1.00" (25 mm) Length: 7.94" (202 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P167766 Description: HYDRAULIC CARTRIDGE Primary App: CLARK 233333 Dimensions: Outer Diameter: 5.93" (151 mm) Inner Diameter: 2.16" (55 mm) Length: 17.00" (432 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 35 Micron</p>		<p>Part Number: P167841 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9400FUP26H, DONALDSON HPK05 ASSY Dimensions: Outer Diameter: 3.75" (95 mm) Inner Diameter: 2.21" (56 mm) Length: 25.53" (648 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P167796 Description: HYDRAULIC SPIN-ON Primary App: DONALDSON HBK05 ASSEMBLY Dimensions: Outer Diameter: 5.06" (129 mm) Thread Size: 1 1/2-16 Length: 10.66" (271 mm) Gasket OD: 5.05" (128 mm) Gasket ID: 4.71" (120 mm) Efficiency 99% @ 2 Micron</p>		<p>Part Number: P167842 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUP8H, DONALDSON HPK03 ASSY Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.68" (43 mm) Length: 8.03" (204 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P167829 Description: HYDRAULIC SPIN-ON Primary App: ALLISON AT500, MT600 TRANSMISSION #23042062 Dimensions: Outer Diameter: 3.72" (95 mm) Thread Size: 1 1/2-16 Length: 5.82" (148 mm) Gasket OD: 3.45" (88 mm) Gasket ID: 2.97" (75 mm)</p>		<p>Part Number: P167843 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9601FUT4H, PARKER 927169 Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: 1.72" (44 mm) Length: 4.61" (117 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P167830 Description: HYDRAULIC SPIN-ON Primary App: JOY 01228337-0020 Dimensions: Outer Diameter: 3.75" (95 mm) Thread Size: 1 1/2-16 Length: 5.82" (148 mm) Gasket OD: 3.45" (88 mm) Gasket ID: 2.97" (75 mm) Efficiency 50% @ 9 Micron</p>		<p>Part Number: P167847 Description: HYDRAULIC CARTRIDGE Primary App: JOHN DEERE AT67960 Dimensions: Outer Diameter: 2.90" (74 mm) Inner Diameter: 1.13" (29 mm) Length: 7.39" (188 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P167832 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7500SUP8H, DONALDSON HBK05 ASSY Dimensions: Outer Diameter: 5.08" (129 mm) Thread Size: 1 1/2-16 Length: 10.66" (271 mm) Gasket OD: 5.05" (128 mm) Gasket ID: 4.71" (120 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P167886 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8900FDN13H Dimensions: Outer Diameter: 3.75" (95 mm) Inner Diameter: 2.21" (56 mm) Length: 12.76" (324 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P167835 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8300FUP16H Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 4.17" (106 mm) Length: 16.77" (426 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P167888 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8900FUS13H Dimensions: Outer Diameter: 3.75" (95 mm) Inner Diameter: 2.21" (56 mm) Length: 12.76" (324 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P167836 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8300FUP39H Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 4.12" (105 mm) Length: 38.62" (981 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P167889 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8900FUT8H Dimensions: Outer Diameter: 3.75" (95 mm) Inner Diameter: 2.21" (56 mm) Length: 8.01" (203 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P167890 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8900FUT13H Dimensions: Outer Diameter: 3.75" (95 mm) Inner Diameter: 2.21" (56 mm) Length: 12.76" (324 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P167890 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8900FUT13H Dimensions: Outer Diameter: 3.75" (95 mm) Inner Diameter: 2.21" (56 mm) Length: 12.76" (324 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>



Part Number: P167891
HYDRAULIC CARTRIDGE
 Description: PALL HC8900FUT16H
 Primary App: Outer Diameter: 3.75" (95 mm)
 Dimensions: Inner Diameter: 2.21" (56 mm)
 Length: 16.68" (424 mm)
 Efficiency 50% @ 10 Micron
 Efficiency 99% @ 22 Micron



Part Number: P167942
HYDRAULIC CARTRIDGE
 Description: PALL HC8900FDN16H
 Primary App: Outer Diameter: 3.75" (95 mm)
 Dimensions: Inner Diameter: 2.21" (56 mm)
 Length: 16.68" (424 mm)
 Efficiency 50% @ 2 Micron
 Efficiency 99% @ 5 Micron



Part Number: P167943
HYDRAULIC CARTRIDGE
 Description: PALL HC8900FUS16H
 Primary App: Outer Diameter: 3.75" (95 mm)
 Dimensions: Inner Diameter: 2.21" (56 mm)
 Length: 16.68" (424 mm)
 Efficiency 50% @ 2 Micron
 Efficiency 99% @ 10 Micron



Part Number: P167944
HYDRAULIC SPIN-ON
 Description: DONALDSON HBK05 ASSEMBLY
 Primary App: Outer Diameter: 4.87" (124 mm)
 Dimensions: Thread Size: 1 1/2-16
 Length: 6.66" (169 mm)
 Gasket OD: 5.05" (128 mm)
 Gasket ID: 4.71" (120 mm)
 Efficiency 50% @ 5 Micron



Part Number: P167945
HYDRAULIC SPIN-ON
 Description: DONALDSON HBK05 ASSEMBLY
 Primary App: Outer Diameter: 4.78" (121 mm)
 Dimensions: Thread Size: 1 1/2-16
 Length: 10.66" (271 mm)
 Gasket OD: 5.05" (128 mm)
 Gasket ID: 4.71" (120 mm)
 Efficiency 50% @ 5 Micron



Part Number: P169012
STRAINER
 Description: SEH-5-1/2-100
 Primary App: Outer Diameter: 2.63" (67 mm)
 Dimensions: Thread Size: 1/2 NPT
 Length: 3.10" (79 mm)
 Efficiency 50% @ 149 Micron



Part Number: P169013
STRAINER
 Description: SEH-8-3/4-100
 Primary App: Outer Diameter: 2.63" (67 mm)
 Dimensions: Thread Size: 3/4 NPT
 Length: 3.55" (90 mm)
 Efficiency 50% @ 149 Micron



Part Number: P169014
STRAINER
 Description: SEH-10-1-100
 Primary App: Outer Diameter: 2.63" (67 mm)
 Dimensions: Thread Size: 1 NPT
 Length: 5.35" (136 mm)
 Efficiency 50% @ 149 Micron



Part Number: P169015
STRAINER
 Description: SEH-20-1.1/4-100
 Primary App: Outer Diameter: 3.38" (86 mm)
 Dimensions: Thread Size: 1 1/4 NPT
 Length: 6.85" (174 mm)
 Efficiency 50% @ 149 Micron



Part Number: P169016
STRAINER
 Description: SEH-30-1.1/2-100
 Primary App: Outer Diameter: 3.38" (86 mm)
 Dimensions: Thread Size: 1 1/2 NPT
 Length: 8.01" (203 mm)
 Efficiency 50% @ 149 Micron



Part Number: P169017
STRAINER
 Description: SEH-50-1.1/2-100
 Primary App: Outer Diameter: 3.94" (100 mm)
 Dimensions: Thread Size: 1 1/2 NPT
 Length: 9.85" (250 mm)
 Efficiency 50% @ 149 Micron



Part Number: P169018
STRAINER
 Description: SEH-50-2-100
 Primary App: Outer Diameter: 3.94" (100 mm)
 Dimensions: Thread Size: 2 NPT
 Length: 9.85" (250 mm)
 Efficiency 50% @ 149 Micron



Part Number: P169019
STRAINER
 Description: SEC-75-2.1/2-100
 Primary App: Outer Diameter: 5.12" (130 mm)
 Dimensions: Thread Size: 2 1/2 NPT
 Length: 10.10" (257 mm)
 Efficiency 50% @ 149 Micron










Part Number: P169020
STRAINER
 Description: SEC-100-3-100
 Primary App: Outer Diameter: 5.12" (130 mm)
 Dimensions: Thread Size: 3 NPT
 Length: 11.78" (299 mm)
 Efficiency 50% @ 149 Micron



































Part Number: P169071
LUBE SPIN-ON FULL FLOW
 Description: HIGH EFFICIENCY VERSION OF P550008
 Primary App: Outer Diameter: 3.67" (93 mm)
 Dimensions: Thread Size: 3/4-16
 Length: 5.32" (135 mm)
 Gasket OD: 2.85" (72 mm)
 Gasket ID: 2.47" (63 mm)
 Relief Valve Setting: 8-11 PSI (0.60-0.80 Bar)
 Efficiency 99% @ 22 Micron




















Part Number: P169077
HYDRAULIC SPIN-ON
 Description: Case 1329214C1
 Primary App: Outer Diameter: 5.08" (129 mm)
 Dimensions: Thread Size: 1 1/2-16
 Length: 10.66" (271 mm)
 Gasket OD: 5.05" (128 mm)
 Gasket ID: 4.71" (120 mm)
 Efficiency 50% @ 2 Micron

	<p>Part Number: P169078 Description: HYDRAULIC SPIN-ON Primary App: JOHN DEERE AM102723 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 4.47" (114 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 10 Micron</p>	<p>Part Number: P169392 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7400SUP8H, HC7400SUN8H Dimensions: Outer Diameter: 3.72" (95 mm) Thread Size: 1 1/2-16 Length: 8.02" (204 mm) Gasket OD: 3.45" (88 mm) Gasket ID: 2.97" (75 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P169079 Description: HYDRAULIC CARTRIDGE Primary App: JOHN DEERE AT67957 Dimensions: Outer Diameter: 2.90" (74 mm) Inner Diameter: 1.12" (28 mm) Length: 3.62" (92 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>	<p>Part Number: P169393 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7400SUT8H, HC7400SUS8H, HC7400SUK8H Dimensions: Outer Diameter: 3.75" (95 mm) Thread Size: 1 1/2-16 Length: 8.02" (204 mm) Gasket OD: 3.45" (88 mm) Gasket ID: 2.97" (75 mm) Efficiency 50% @ 9 Micron</p>
	<p>Part Number: P169083 Description: HYDRAULIC SPIN-ON Primary App: IR 39138433 Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 1 1/4-12 Length: 8.76" (223 mm) Gasket OD: 2.84" (72 mm) Gasket ID: 2.47" (63 mm) Efficiency 50% @ 10 Micron</p>	<p>Part Number: P169400 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HYDRAULIC ASSEMBLY Dimensions: Outer Diameter: 3.68" (93 mm) Inner Diameter: 1.75" (44 mm) Length: 9.25" (235 mm) Efficiency 50% @ 20 Micron Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P169084 Description: HYDRAULIC SPIN-ON Primary App: Case A176594 Dimensions: Outer Diameter: 5.08" (129 mm) Thread Size: 1 1/2-16 Length: 10.66" (271 mm) Gasket OD: 5.05" (128 mm) Gasket ID: 4.71" (120 mm) Efficiency 50% @ 5 Micron</p>	<p>Part Number: P169424 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9651FUP8H Dimensions: Outer Diameter: 3.12" (79 mm) Inner Diameter: 1.70" (43 mm) Length: 8.20" (208 mm) Efficiency 99% @ 3 Micron</p>
<p>Part Number: P169091 Description: FUEL SPIN-ON SECONDARY Primary App: DET. DIESEL, GM 6438840 Dimensions: Outer Diameter: 3.67" (93 mm) Thread Size: 13/16-12 Length: 6.89" (175 mm) Gasket OD: 3.49" (89 mm) Gasket ID: 3.12" (79 mm)</p>	<p>Part Number: P169425 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9651FUP16H Dimensions: Outer Diameter: 3.12" (79 mm) Inner Diameter: 1.70" (43 mm) Length: 17.06" (433 mm) Efficiency 99% @ 3 Micron</p>	
	<p>Part Number: P169096 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CAT 6L-7440, 1P-2299, 8L-9740 Dimensions: Outer Diameter: 3.67" (93 mm) Thread Size: 1-14 Length: 6.95" (177 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (62 mm) Efficiency 99% @ 5 Micron</p>	<p>Part Number: P169426 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9651FUT8H Dimensions: Outer Diameter: 3.12" (79 mm) Inner Diameter: 1.70" (43 mm) Length: 8.20" (208 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P169341 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER KS1 Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.61" (41 mm) Length: 9.02" (229 mm) Efficiency 99% @ 3 Micron</p>	<p>Part Number: P169429 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9020FUP4H, DONALDSON HPK02 ASSY Dimensions: Outer Diameter: 1.77" (45 mm) Inner Diameter: 1.00" (25 mm) Length: 4.31" (109 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P169344 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER KS3 Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.61" (41 mm) Length: 9.02" (229 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>	<p>Part Number: P169430 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7500SUP4H, DONALDSON HBK05 ASSY Dimensions: Outer Diameter: 5.08" (129 mm) Thread Size: 1 1/2-16 Length: 6.66" (169 mm) Gasket OD: 5.05" (128 mm) Gasket ID: 4.71" (120 mm) Efficiency 99% @ 3 Micron</p>

	<p>Part Number: P169431 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUP4H Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.68" (43 mm) Length: 4.45" (113 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P169444 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER JS-3 Dimensions: Outer Diameter: 3.53" (90 mm) Inner Diameter: 1.61" (41 mm) Length: 9.02" (229 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P169432 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUP13H Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.68" (43 mm) Length: 12.76" (324 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P169445 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9800FUP4H Dimensions: Outer Diameter: 1.97" (50 mm) Inner Diameter: 0.94" (24 mm) Length: 4.45" (113 mm)</p>
	<p>Part Number: P169433 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9600FUP16H, DONALDSON HPK04 ASSY Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.68" (43 mm) Length: 16.67" (423 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P169446 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9800FUN4H Dimensions: Outer Diameter: 1.99" (51 mm) Inner Diameter: 0.96" (24 mm) Length: 4.31" (109 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P169434 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9400FUP13H Dimensions: Outer Diameter: 3.75" (95 mm) Inner Diameter: 2.21" (56 mm) Length: 12.76" (324 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P169447 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9800FUS4H Dimensions: Outer Diameter: 1.97" (50 mm) Inner Diameter: 0.96" (24 mm) Length: 4.31" (109 mm)</p>
	<p>Part Number: P169435 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9650FUP8H Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.68" (43 mm) Length: 8.03" (204 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P169448 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9800FUP8H Dimensions: Outer Diameter: 1.99" (51 mm) Inner Diameter: 0.96" (24 mm) Length: 7.94" (202 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P169436 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9650FUP16H Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.68" (43 mm) Length: 16.67" (423 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P169449 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9800FUS8H Dimensions: Outer Diameter: 1.99" (51 mm) Inner Diameter: 0.96" (24 mm) Length: 7.94" (202 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P169437 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8400FUP8H Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 3.28" (83 mm) Length: 8.13" (207 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P169450 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9800FUT8H Dimensions: Outer Diameter: 1.99" (51 mm) Inner Diameter: 0.96" (24 mm) Length: 7.94" (202 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P169438 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8400FUP16H Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 3.28" (83 mm) Length: 16.77" (426 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P169452 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9800FUN13H Dimensions: Outer Diameter: 1.99" (51 mm) Inner Diameter: 0.96" (24 mm) Length: 12.93" (328 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P169443 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER JS-1 Dimensions: Outer Diameter: 3.53" (90 mm) Inner Diameter: 1.61" (41 mm) Length: 9.02" (229 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P169453 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9800FUS13H Dimensions: Outer Diameter: 1.99" (51 mm) Inner Diameter: 0.94" (24 mm) Length: 12.91" (328 mm)</p>

	<p>Part Number: P169477 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER A-25 Dimensions: Outer Diameter: 3.00" (76 mm) Inner Diameter: 1.04" (26 mm) Length: 4.75" (121 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P169559 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 924791 Dimensions: Outer Diameter: 3.68" (93 mm) Inner Diameter: 1.75" (44 mm) Length: 18.31" (465 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 17 Micron</p>
	<p>Part Number: P169478 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER J-25 Dimensions: Outer Diameter: 3.53" (90 mm) Inner Diameter: 1.61" (41 mm) Length: 9.02" (229 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P169560 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 924792 Dimensions: Outer Diameter: 3.68" (93 mm) Inner Diameter: 1.75" (44 mm) Length: 18.31" (465 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P169553 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 924448, 924451 Dimensions: Outer Diameter: 3.68" (93 mm) Inner Diameter: 1.75" (44 mm) Length: 9.00" (229 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P169561 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 924794 Dimensions: Outer Diameter: 3.68" (93 mm) Inner Diameter: 1.75" (44 mm) Length: 18.31" (465 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P169554 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 924449 Dimensions: Outer Diameter: 3.68" (93 mm) Inner Diameter: 1.75" (44 mm) Length: 9.00" (229 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 17 Micron</p>		<p>Part Number: P169562 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 924795 Dimensions: Outer Diameter: 3.68" (93 mm) Inner Diameter: 1.75" (44 mm) Length: 18.31" (465 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P169555 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 924450 Dimensions: Outer Diameter: 3.68" (93 mm) Inner Diameter: 1.75" (44 mm) Length: 9.00" (229 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P169797 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9800FUT4H Dimensions: Outer Diameter: 1.99" (51 mm) Inner Diameter: 0.96" (24 mm) Length: 4.31" (109 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P169556 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 924452 Dimensions: Outer Diameter: 3.68" (93 mm) Inner Diameter: 1.75" (44 mm) Length: 9.00" (229 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P169798 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9800FUN8H Dimensions: Outer Diameter: 1.99" (51 mm) Inner Diameter: 0.96" (24 mm) Length: 7.94" (202 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P169557 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 924453 Dimensions: Outer Diameter: 3.68" (93 mm) Inner Diameter: 1.75" (44 mm) Length: 9.00" (229 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P170061 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 987141, 924467 Dimensions: Outer Diameter: 5.62" (143 mm) Inner Diameter: 3.72" (95 mm) Length: 12.00" (305 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P169558 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 924790, 924793 Dimensions: Outer Diameter: 3.68" (93 mm) Inner Diameter: 1.75" (44 mm) Length: 18.31" (465 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P170062 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 987121 Dimensions: Outer Diameter: 5.62" (143 mm) Inner Diameter: 3.72" (95 mm) Length: 12.00" (305 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>

	<p>Part Number: P170063 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 908648 Dimensions: Outer Diameter: 5.62" (143 mm) Inner Diameter: 3.72" (95 mm) Length: 12.00" (305 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P170090 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 926372, 926325 Dimensions: Outer Diameter: 4.42" (112 mm) Inner Diameter: 1.66" (42 mm) Length: 9.00" (229 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P170065 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 922625 Dimensions: Outer Diameter: 2.44" (62 mm) Inner Diameter: 1.02" (26 mm) Length: 5.00" (127 mm) Efficiency 50% @ 20 Micron Efficiency 99% @ 40 Micron</p>		<p>Part Number: P170092 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 926326 Dimensions: Outer Diameter: 4.42" (112 mm) Inner Diameter: 1.66" (42 mm) Length: 9.00" (229 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P170066 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 922624 Dimensions: Outer Diameter: 2.44" (62 mm) Inner Diameter: 1.02" (26 mm) Length: 5.00" (127 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P170095 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 907233 Dimensions: Outer Diameter: 3.60" (91 mm) Inner Diameter: 1.91" (49 mm) Length: 7.40" (188 mm) Efficiency 50% @ 20 Micron Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P170068 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 922623, 922622 Dimensions: Outer Diameter: 2.44" (62 mm) Inner Diameter: 1.02" (26 mm) Length: 5.00" (127 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P170096 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 907234 Dimensions: Outer Diameter: 3.60" (91 mm) Inner Diameter: 1.91" (49 mm) Length: 7.40" (188 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P170069 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 922621 Dimensions: Outer Diameter: 2.44" (62 mm) Inner Diameter: 1.02" (26 mm) Length: 5.00" (127 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P170098 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 924588, 983061 Dimensions: Outer Diameter: 3.60" (91 mm) Inner Diameter: 1.91" (49 mm) Length: 7.40" (188 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P170073 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 925835 Dimensions: Outer Diameter: 2.44" (62 mm) Inner Diameter: 1.02" (26 mm) Length: 9.25" (235 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P170099 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 976191 Dimensions: Outer Diameter: 3.60" (91 mm) Inner Diameter: 1.91" (49 mm) Length: 7.40" (188 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P170084 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 925836, 925837 Dimensions: Outer Diameter: 2.44" (62 mm) Inner Diameter: 1.02" (26 mm) Length: 9.25" (235 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P170102 Description: HYDRAULIC CARTRIDGE Primary App: HILCO PL-718-26 Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 2.60" (66 mm) Length: 18.00" (457 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P170085 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 925838 Dimensions: Outer Diameter: 2.44" (62 mm) Inner Diameter: 1.02" (26 mm) Length: 9.25" (235 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P170103 Description: HYDRAULIC CARTRIDGE Primary App: HILCO PL-718-19, PL-718-302 Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 2.60" (66 mm) Length: 18.00" (457 mm) Efficiency 50% @ 7 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P170089 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK03 ASSEMBLY Dimensions: Outer Diameter: 3.13" (80 mm) Thread Size: 2-12 Length: 9.52" (242 mm) Gasket OD: 3.13" (80 mm) Gasket ID: 1.86" (47 mm) Efficiency 50% @ 10 Micron</p>		



Part Number: P170306
DESCRIPTION: HYDRAULIC SPIN-ON, DURAMAX®
Primary App: DONALDSON HMK03 ASSEMBLY
Dimensions:
 Outer Diameter: 3.13" (80 mm)
 Thread Size: 2-12
 Length: 5.52" (140 mm)
 Gasket OD: 3.13" (80 mm)
 Gasket ID: 1.86" (47 mm)
 Efficiency 99% @ 3 Micron



Part Number: P170480
DESCRIPTION: HYDRAULIC SPIN-ON, DURAMAX®
Primary App: DONALDSON HMK03 ASSEMBLY
Dimensions:
 Outer Diameter: 3.13" (80 mm)
 Thread Size: 2-12
 Length: 5.52" (140 mm)
 Gasket OD: 3.13" (80 mm)
 Gasket ID: 1.86" (47 mm)
 Efficiency 50% @ 10 Micron



Part Number: P170307
DESCRIPTION: HYDRAULIC SPIN-ON, DURAMAX®
Primary App: DONALDSON HMK03 ASSEMBLY
Dimensions:
 Outer Diameter: 3.13" (80 mm)
 Thread Size: 2-12
 Length: 9.52" (242 mm)
 Gasket OD: 3.13" (80 mm)
 Gasket ID: 1.86" (47 mm)
 Efficiency 99% @ 3 Micron



Part Number: P170481
DESCRIPTION: HYDRAULIC CARTRIDGE
Primary App: PALL HC8800FDN16H
Dimensions:
 Outer Diameter: 3.39" (86 mm)
 Inner Diameter: 1.96" (50 mm)
 Length: 16.67" (423 mm)
 Efficiency 50% @ 2 Micron
 Efficiency 99% @ 5 Micron



Part Number: P170308
DESCRIPTION: HYDRAULIC SPIN-ON, DURAMAX®
Primary App: DONALDSON HMK03 ASSEMBLY
Dimensions:
 Outer Diameter: 3.13" (80 mm)
 Thread Size: 2
 Length: 5.52" (140 mm)
 Gasket OD: 3.13" (80 mm)
 Gasket ID: 1.86" (47 mm)
 Efficiency 50% @ 2 Micron



Part Number: P170546
DESCRIPTION: HYDRAULIC SPIN-ON, DURAMAX®
Primary App: HMK05/25 ELEMENT, 14.24" LONG, # 20 MEDIA
Dimensions:
 Outer Diameter: 4.77" (121 mm)
 Thread Size: 1 3/4-12
 Length: 14.24" (362 mm)
 Gasket OD: 3.39" (86 mm)
 Gasket ID: 3.11" (79 mm)



Part Number: P170309
DESCRIPTION: HYDRAULIC SPIN-ON, DURAMAX®
Primary App: DONALDSON HMK03 ASSEMBLY
Dimensions:
 Outer Diameter: 3.13" (80 mm)
 Thread Size: 2-12
 Length: 9.52" (242 mm)
 Gasket OD: 3.13" (80 mm)
 Gasket ID: 1.86" (47 mm)
 Efficiency 50% @ 2 Micron



Part Number: P170586
DESCRIPTION: HYDRAULIC CARTRIDGE
Primary App: HYCON 0060D003BHHC
Dimensions:
 Outer Diameter: 1.85" (47 mm)
 Inner Diameter: 0.87" (22 mm)
 Length: 3.31" (84 mm)
 Efficiency 99% @ 3 Micron



Part Number: P170310
DESCRIPTION: HYDRAULIC SPIN-ON, DURAMAX®
Primary App: DONALDSON HMK03 ASSEMBLY
Dimensions:
 Outer Diameter: 3.13" (80 mm)
 Thread Size: 2-12
 Length: 5.52" (140 mm)
 Gasket OD: 3.13" (80 mm)
 Gasket ID: 1.86" (47 mm)
 Efficiency 50% @ 5 Micron



Part Number: P170587
DESCRIPTION: HYDRAULIC CARTRIDGE
Primary App: HYCON 0060D010BHHC
Dimensions:
 Outer Diameter: 1.85" (47 mm)
 Inner Diameter: 0.87" (22 mm)
 Length: 3.31" (84 mm)
 Efficiency 50% @ 2 Micron
 Efficiency 99% @ 10 Micron



Part Number: P170311
DESCRIPTION: HYDRAULIC SPIN-ON, DURAMAX®
Primary App: DONALDSON HMK03 ASSEMBLY
Dimensions:
 Outer Diameter: 3.13" (80 mm)
 Thread Size: 2-12
 Length: 9.52" (242 mm)
 Gasket OD: 3.13" (80 mm)
 Gasket ID: 1.86" (47 mm)
 Efficiency 50% @ 5 Micron



Part Number: P170588
DESCRIPTION: HYDRAULIC CARTRIDGE
Primary App: HYCON 0110D003BHHC
Dimensions:
 Outer Diameter: 1.85" (47 mm)
 Inner Diameter: 0.87" (22 mm)
 Length: 6.06" (154 mm)
 Efficiency 99% @ 3 Micron



Part Number: P170312
DESCRIPTION: HYDRAULIC SPIN-ON, DURAMAX®
Primary App: DONALDSON HMK03 ASSEMBLY
Dimensions:
 Outer Diameter: 3.13" (80 mm)
 Thread Size: 2-12
 Length: 5.52" (140 mm)
 Gasket OD: 3.13" (80 mm)
 Gasket ID: 1.86" (47 mm)
 Efficiency 50% @ 10 Micron








Part Number: P170589
DESCRIPTION: HYDRAULIC CARTRIDGE
Primary App: HYCON 0110D010BHHC
Dimensions:
 Outer Diameter: 1.85" (47 mm)
 Inner Diameter: 0.87" (22 mm)
 Length: 6.06" (154 mm)
 Efficiency 50% @ 2 Micron
 Efficiency 99% @ 10 Micron



































Part Number: P170313
DESCRIPTION: HYDRAULIC SPIN-ON, DURAMAX®
Primary App: DONALDSON HMK03 ASSEMBLY
Dimensions:
 Outer Diameter: 3.13" (80 mm)
 Thread Size: 2-12
 Length: 9.52" (242 mm)
 Gasket ID: 1.86" (47 mm)
 Efficiency 50% @ 10 Micron

































Part Number: P170590
DESCRIPTION: HYDRAULIC CARTRIDGE
Primary App: HYCON 0160D003BHHC
Dimensions:
 Outer Diameter: 2.72" (69 mm)
 Inner Diameter: 1.34" (34 mm)
 Length: 4.53" (115 mm)
 Efficiency 99% @ 3 Micron

	<p>Part Number: P170591 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0160D010BHHC Dimensions: Outer Diameter: 2.72" (69 mm) Inner Diameter: 1.34" (34 mm) Length: 4.53" (115 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P170599 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0030D010BN Dimensions: Outer Diameter: 1.38" (35 mm) Inner Diameter: 0.48" (12 mm) Length: 3.70" (94 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P170592 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0240D003BHHC Dimensions: Outer Diameter: 2.72" (69 mm) Inner Diameter: 1.34" (34 mm) Length: 6.85" (174 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P170600 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0060D005BNHC Dimensions: Outer Diameter: 1.85" (47 mm) Inner Diameter: 0.87" (22 mm) Length: 3.31" (84 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P170593 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0240D010BHHC Dimensions: Outer Diameter: 2.72" (69 mm) Inner Diameter: 1.34" (34 mm) Length: 6.85" (174 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P170601 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0060D010BNHC Dimensions: Outer Diameter: 1.85" (47 mm) Inner Diameter: 0.87" (22 mm) Length: 3.31" (84 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P170594 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0330D003BHHC Dimensions: Outer Diameter: 3.56" (90 mm) Inner Diameter: 1.89" (48 mm) Length: 6.42" (163 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P170602 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0110D005BNHC Dimensions: Outer Diameter: 1.85" (47 mm) Inner Diameter: 0.87" (22 mm) Length: 6.02" (153 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P170595 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0330D010BHHC Dimensions: Outer Diameter: 3.56" (90 mm) Inner Diameter: 1.89" (48 mm) Length: 6.42" (163 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P170604 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0110D010BNHC Dimensions: Outer Diameter: 1.85" (47 mm) Inner Diameter: 0.87" (22 mm) Length: 6.02" (153 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P170596 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0660D003BHHC Dimensions: Outer Diameter: 3.56" (90 mm) Inner Diameter: 1.89" (48 mm) Length: 12.95" (329 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P170605 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0160D005BNHC Dimensions: Outer Diameter: 2.72" (69 mm) Inner Diameter: 1.34" (34 mm) Length: 4.53" (115 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P170597 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0660D010BHHC Dimensions: Outer Diameter: 3.56" (90 mm) Inner Diameter: 1.89" (48 mm) Length: 12.95" (329 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P170606 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0160D010BNHC Dimensions: Outer Diameter: 2.72" (69 mm) Inner Diameter: 1.34" (34 mm) Length: 4.53" (115 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P170598 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0030D005BNHC Dimensions: Outer Diameter: 1.38" (35 mm) Inner Diameter: 0.48" (12 mm) Length: 3.70" (94 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P170607 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0240D005BNHC Dimensions: Outer Diameter: 2.72" (69 mm) Inner Diameter: 1.34" (34 mm) Length: 6.85" (174 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>



















	<p>Part Number: P170608 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0240D010BNHC Dimensions: Outer Diameter: 2.72" (69 mm) Inner Diameter: 1.34" (34 mm) Length: 6.85" (174 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P170617 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0240R010BNHC, STAUFF RE070G10B Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 1.35" (34 mm) Length: 7.99" (203 mm) Relief Valve Setting: 43 PSI (2.96 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P170609 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0330D005BNHC Dimensions: Outer Diameter: 3.56" (90 mm) Inner Diameter: 1.90" (48 mm) Length: 6.42" (163 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P170618 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0330R010BNHC, STAUFF RE090G10B Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.81" (46 mm) Length: 7.70" (195 mm) Relief Valve Setting: 44 PSI (3.03 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P170610 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0330D010BNHC Dimensions: Outer Diameter: 3.56" (90 mm) Inner Diameter: 1.90" (48 mm) Length: 6.42" (163 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P170619 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0660R010BNHC, STAUFF RE160G10B Dimensions: Outer Diameter: 4.49" (114 mm) Inner Diameter: 2.70" (69 mm) Length: 13.11" (333 mm) Relief Valve Setting: 43 PSI (2.96 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P170611 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0660D005BNHC Dimensions: Outer Diameter: 3.56" (90 mm) Inner Diameter: 1.90" (48 mm) Length: 12.95" (329 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P170620 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 1300R010BNHC, STAUFF RE300G10B Dimensions: Outer Diameter: 5.63" (143 mm) Inner Diameter: 3.80" (97 mm) Length: 19.02" (483 mm) Relief Valve Setting: 43 PSI (2.96 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P170612 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0660D010BNHC Dimensions: Outer Diameter: 3.56" (90 mm) Inner Diameter: 1.90" (48 mm) Length: 12.95" (329 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P170737 Description: TRANSMISSION CARTRIDGE Primary App: ALLISON TRANS 23040988, PALL HC8200FDN8H Dimensions: Outer Diameter: 3.09" (79 mm) Inner Diameter: 1.52" (39 mm) Length: 8.03" (204 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P170613 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0060R010BNHC, STAUFF RE014G10B Dimensions: Outer Diameter: 2.03" (52 mm) Inner Diameter: 0.87" (22 mm) Length: 4.06" (103 mm) Relief Valve Setting: 43 PSI (2.96 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P170885 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0950R005BNHC Dimensions: Outer Diameter: 5.63" (143 mm) Inner Diameter: 3.78" (96 mm) Length: 14.30" (363 mm) Relief Valve Setting: 43 PSI (2.96 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P170614 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0110R010BNHC, STAUFF RE030G10B Dimensions: Outer Diameter: 2.03" (52 mm) Inner Diameter: 0.87" (22 mm) Length: 6.71" (170 mm) Relief Valve Setting: 43 PSI (2.96 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P170886 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 1300R003BNHC Dimensions: Outer Diameter: 5.63" (143 mm) Inner Diameter: 3.78" (96 mm) Length: 18.99" (482 mm) Relief Valve Setting: 43 PSI (2.96 Bar) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P170615 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0160R010BNHC, STAUFF RE045G10B Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 1.35" (34 mm) Length: 5.67" (144 mm) Relief Valve Setting: 43 PSI (2.96 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P170888 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0660R003BNHC Dimensions: Outer Diameter: 4.49" (114 mm) Inner Diameter: 2.70" (69 mm) Length: 13.11" (333 mm) Relief Valve Setting: 43 PSI (2.96 Bar) Efficiency 99% @ 3 Micron</p>






	<p>Part Number: P170889 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0160R005BNHC Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 1.35" (34 mm) Length: 5.67" (144 mm) Relief Valve Setting: 43 PSI (2.96 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P171046 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8310FKT39H, HC8300FDT39H Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 4.12" (105 mm) Length: 35.68" (906 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P170890 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 1300R020BNHC Dimensions: Outer Diameter: 5.63" (143 mm) Inner Diameter: 3.78" (96 mm) Length: 18.99" (482 mm) Relief Valve Setting: 43 PSI (2.96 Bar) Efficiency 99% @ 20 Micron</p>		<p>Part Number: P171047 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8310FKN39H, HC8300FDN39H Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 4.12" (105 mm) Length: 35.68" (906 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P170891 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0950R010BNHC Dimensions: Outer Diameter: 5.63" (143 mm) Inner Diameter: 3.80" (97 mm) Length: 14.29" (363 mm) Relief Valve Setting: 43 PSI (2.96 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P171048 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8310FKP39H, HC8300FDP39H Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 4.12" (105 mm) Length: 35.68" (906 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P170906 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HYD ASSY, DONALDSON HMK05 Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 11.63" (295 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P171053 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8310FKS16H, HC8300FDS16H Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 4.12" (105 mm) Length: 13.83" (351 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P170949 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CASE IH 1971728C1, MAGNUM AG TRACTORS Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 14.24" (362 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm) Efficiency 50% @ 4 Micron</p>		<p>Part Number: P171054 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8310FKT16H, HC8300FDT16H Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 4.12" (105 mm) Length: 13.83" (351 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P170950 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: JOHN DEERE AH128449, 90 SERIES COMBINES Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 7 Micron</p>		<p>Part Number: P171055 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8310FKN16H, HC8300FDN16H Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 4.12" (105 mm) Length: 13.83" (351 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P171037 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9901FUT26H, HYCON H9901/26-010BH, HPK05 Dimensions: Outer Diameter: 3.80" (97 mm) Inner Diameter: 2.19" (56 mm) Length: 25.90" (658 mm) Efficiency 99% @ 20 Micron</p>		<p>Part Number: P171056 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8310FKP16H, HC8300FDP16H Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 4.12" (105 mm) Length: 13.83" (351 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P171045 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8310FKS39H, HC8310FDS39H, HC8310FDS39Z Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 4.12" (105 mm) Length: 35.68" (906 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 16 Micron</p>		<p>Part Number: P171239 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 924456 Dimensions: Outer Diameter: 3.68" (93 mm) Inner Diameter: 1.75" (44 mm) Length: 9.00" (229 mm) Efficiency 50% @ 74 Micron</p>

	<p>Part Number: P171241 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 909303 Dimensions: Outer Diameter: 5.62" (143 mm) Inner Diameter: 3.72" (95 mm) Length: 12.00" (305 mm) Efficiency 50% @ 74 Micron</p>		<p>Part Number: P171276 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK05/HMK25 HYD ASSY Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 11.63" (295 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm) Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P171243 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 909309 Dimensions: Outer Diameter: 5.62" (143 mm) Inner Diameter: 3.72" (95 mm) Length: 12.00" (305 mm) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P171279 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HEK11 HYD ASSBLY Dimensions: Outer Diameter: 7.44" (189 mm) Inner Diameter: 4.85" (123 mm) Length: 22.00" (559 mm) Efficiency 50% @ 20 Micron Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P171244 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 922972 Dimensions: Outer Diameter: 2.84" (72 mm) Inner Diameter: 2.44" (62 mm) Length: 6.50" (165 mm) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P171298 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: KAWASAKI WHL LDR 65 & 115, 3098170080 Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 7 Micron</p>
	<p>Part Number: P171245 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 922973 Dimensions: Outer Diameter: 2.84" (72 mm) Inner Diameter: 2.44" (62 mm) Length: 6.50" (165 mm) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P171310 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER C3, CS3, D3 Dimensions: Outer Diameter: 2.69" (68 mm) Inner Diameter: 1.01" (26 mm) Length: 4.56" (116 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P171248 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 924739 Dimensions: Outer Diameter: 2.73" (69 mm) Inner Diameter: 1.68" (43 mm) Length: 8.69" (221 mm) Efficiency 50% @ 74 Micron</p>		<p>Part Number: P171311 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER C10, D10, CS7 Dimensions: Outer Diameter: 2.69" (68 mm) Inner Diameter: 1.01" (26 mm) Length: 4.56" (116 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P171273 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK05/HMK25 HYD ASSY Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 11.63" (295 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P171312 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER C25, D25 Dimensions: Outer Diameter: 2.69" (68 mm) Inner Diameter: 1.01" (26 mm) Length: 4.56" (116 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P171274 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK05/HMK25 HYD ASSY Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 11.63" (295 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm) Efficiency 50% @ 2 Micron</p>		<p>Part Number: P171314 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER CC3, DD3, CCS3 Dimensions: Outer Diameter: 2.69" (68 mm) Inner Diameter: 1.01" (26 mm) Length: 9.31" (236 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P171275 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK05/HMK25 HYD ASSY Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 11.63" (295 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm) Efficiency 50% @ 5 Micron</p>		<p>Part Number: P171315 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER CC10, DD10, CCS7 Dimensions: Outer Diameter: 2.69" (68 mm) Inner Diameter: 1.01" (26 mm) Length: 9.31" (236 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>











	<p>Part Number: P171316 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER CC25, DD25 Dimensions: Outer Diameter: 2.69" (68 mm) Inner Diameter: 1.01" (26 mm) Length: 9.31" (236 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P171505 Description: HYDRAULIC CARTRIDGE Primary App: UFI 7602300 Dimensions: Outer Diameter: 2.05" (52 mm) Inner Diameter: 1.00" (25 mm) Length: 2.60" (66 mm) Efficiency 50% @ 60 Micron</p>
	<p>Part Number: P171412 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 924589, 982131 Dimensions: Outer Diameter: 3.60" (91 mm) Inner Diameter: 1.91" (49 mm) Length: 15.30" (389 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>	<p>Part Number: P171510 Description: HYDRAULIC CARTRIDGE Primary App: SAUER SUNDSTRAND 1511003 Dimensions: Outer Diameter: 2.24" (57 mm) Inner Diameter: 0.87" (22 mm) Length: 2.91" (74 mm)</p>	
	<p>Part Number: P171413 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 976211 Dimensions: Outer Diameter: 3.60" (91 mm) Inner Diameter: 1.91" (49 mm) Length: 15.30" (389 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>	<p>Part Number: P171516 Description: HYDRAULIC CARTRIDGE Primary App: LOESING 14 0180 Dimensions: Outer Diameter: 2.24" (57 mm) Inner Diameter: 0.87" (22 mm) Length: 3.74" (95 mm)</p>	
	<p>Part Number: P171454 Description: HYDRAULIC CARTRIDGE Primary App: HARNISCHEFFGER 45Z459 Dimensions: Outer Diameter: 4.39" (112 mm) Inner Diameter: 2.22" (56 mm) Length: 14.47" (368 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 35 Micron</p>		<p>Part Number: P171519 Description: HYDRAULIC CARTRIDGE Primary App: F.B.O. CR5002 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.18" (30 mm) Length: 2.95" (29 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
<p>Part Number: P171500 Description: HYDRAULIC CARTRIDGE Primary App: FBO CR30 Dimensions: Outer Diameter: 2.05" (52 mm) Inner Diameter: 1.02" (26 mm) Length: 2.64" (67 mm)</p>		<p>Part Number: P171520 Description: HYDRAULIC CARTRIDGE Primary App: CR 50/03 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.14" (29 mm) Length: 2.95" (75 mm)</p>	
	<p>Part Number: P171501 Description: HYDRAULIC CARTRIDGE Primary App: LHA TIE08BTA10 Dimensions: Outer Diameter: 2.05" (52 mm) Inner Diameter: 1.02" (26 mm) Length: 2.64" (67 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P171521 Description: HYDRAULIC CARTRIDGE Primary App: HITACHI 71316541 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.18" (30 mm) Length: 2.95" (75 mm) Efficiency 50% @ 10 Micron</p>
<p>Part Number: P171502 Description: HYDRAULIC CARTRIDGE Primary App: F.B.O. CRC003 Dimensions: Outer Diameter: 2.05" (52 mm) Inner Diameter: 1.00" (25 mm) Length: 2.59" (66 mm)</p>			<p>Part Number: P171522 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 848101079 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.14" (29 mm) Length: 2.95" (75 mm) Efficiency 50% @ 30 Micron</p>
	<p>Part Number: P171503 Description: HYDRAULIC CARTRIDGE Primary App: FBO CR30/1, DONALDSON FHK/FSK Dimensions: Outer Diameter: 2.05" (52 mm) Inner Diameter: 1.00" (25 mm) Length: 2.64" (67 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P171523 Description: HYDRAULIC CARTRIDGE Primary App: SAUER SUNDSTRAND 1511011 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.14" (29 mm) Length: 2.95" (75 mm)</p>
<p>Part Number: P171504 Description: HYDRAULIC CARTRIDGE Primary App: FBO CR30/3, DONALDSON FHK/FSK Dimensions: Outer Diameter: 2.05" (52 mm) Inner Diameter: 1.00" (25 mm) Length: 2.64" (67 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 30 Micron</p>			<p>Part Number: P171524 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK/FSK ASSY Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.14" (29 mm) Length: 3.23" (82 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 90 Micron</p>
	<p>Part Number: P171504 Description: HYDRAULIC CARTRIDGE Primary App: FBO CR30/3, DONALDSON FHK/FSK Dimensions: Outer Diameter: 2.05" (52 mm) Inner Diameter: 1.00" (25 mm) Length: 2.64" (67 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 30 Micron</p>		<p>Part Number: P171525 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK/FSK ASSY Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.14" (29 mm) Length: 3.23" (82 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>










	<p>Part Number: P171526 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK/FSK ASSY Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.14" (29 mm) Length: 3.23" (82 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P171534 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK/FSK ASSY Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.14" (29 mm) Length: 5.04" (128 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 30 Micron</p>
	<p>Part Number: P171527 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK/FSK ASSY, FBO CR60/1 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.14" (29 mm) Length: 3.23" (82 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P171535 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK/FSK ASSY Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.14" (29 mm) Length: 5.04" (128 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 60 Micron</p>
	<p>Part Number: P171528 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK/FSK ASSY, FBO CR60/3 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.14" (29 mm) Length: 3.23" (82 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 30 Micron</p>		<p>Part Number: P171536 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK ASSY Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.61" (41 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 90 Micron</p>
	<p>Part Number: P171529 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK/FSK ASSY Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.14" (29 mm) Length: 3.23" (82 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 60 Micron</p>		<p>Part Number: P171537 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK ASSY Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.61" (41 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P171530 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK/FSK ASSY Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.14" (29 mm) Length: 5.04" (128 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 90 Micron</p>		<p>Part Number: P171538 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK ASSY Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.61" (41 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P171531 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK/FSK ASSY Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.14" (29 mm) Length: 5.04" (128 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P171539 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK ASSY, FBO CR180/1 Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.61" (41 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P171532 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK/FSK ASSY Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.14" (29 mm) Length: 5.04" (128 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P171540 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK ASSY, FBO CR180/3 Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.61" (41 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 30 Micron</p>
	<p>Part Number: P171533 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK/FSK ASSY, FBO CR100/1 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.14" (29 mm) Length: 5.04" (128 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P171541 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK ASSY Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.61" (41 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 60 Micron</p>
			<p>Part Number: P171542 Description: HYDRAULIC CARTRIDGE Primary App: CR 201 Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.61" (41 mm) Length: 9.84" (250 mm)</p>









	<p>Part Number: P171545 Description: HYDRAULIC CARTRIDGE Primary App: VAN HOOL 10708572 Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.61" (41 mm) Length: 9.84" (250 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P171556 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FIK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.05" (52 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P171546 Description: HYDRAULIC CARTRIDGE Primary App: FBO CR201/3 Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.61" (41 mm) Length: 9.84" (250 mm) Efficiency 50% @ 30 Micron</p>		<p>Part Number: P171557 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FIK ASSY, FBO CR325/1 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.05" (52 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P171549 Description: HYDRAULIC CARTRIDGE Primary App: F.B.O. CR25002 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.05" (52 mm) Length: 5.35" (136 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 99% @ 10 Micron</p>		<p>Part Number: P171558 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FIK ASSY, FBO CR325/3 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.05" (52 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 30 Micron</p>
	<p>Part Number: P171550 Description: HYDRAULIC CARTRIDGE Primary App: CR 250/03 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.04" (52 mm) Length: 5.39" (137 mm)</p>		<p>Part Number: P171559 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FIK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.05" (52 mm) Length: 7.99" (203 mm)</p>
	<p>Part Number: P171551 Description: HYDRAULIC CARTRIDGE Primary App: FBO CR250/1 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.05" (52 mm) Length: 5.35" (136 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P171560 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK, FIK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 90 Micron</p>
	<p>Part Number: P171552 Description: HYDRAULIC CARTRIDGE Primary App: FBO CR250/3 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.05" (52 mm) Length: 5.35" (136 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 30 Micron</p>		<p>Part Number: P171561 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK, FIK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P171553 Description: HYDRAULIC CARTRIDGE Primary App: F.B.O. CR2506 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.05" (52 mm) Length: 5.35" (136 mm) Relief Valve Setting: 22 PSI (1.52 Bar)</p>		<p>Part Number: P171562 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK, FIK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P171554 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FIK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.05" (52 mm) Length: 7.99" (203 mm)</p>		<p>Part Number: P171563 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK, FIK ASSY, FBO CR330/1 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P171555 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FIK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.05" (52 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P171564 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK, FIK ASSY, FBO CR330/1 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
















	<p>Part Number: P171564 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK, FIK ASSY, FBO CR330/3 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 30 Micron</p>		<p>Part Number: P171573 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FIK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 9.84" (250 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P171565 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK, FIK ASSY, INTANK RETURN ASSY'S Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 60 Micron</p>		<p>Part Number: P171574 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FIK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 9.84" (250 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P171566 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 7.99" (203 mm) Efficiency 50% @ 90 Micron</p>		<p>Part Number: P171575 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FIK ASSY, FBO CR600/1 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 9.84" (250 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P171567 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P171576 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FIK ASSY, FBO CR600/3 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 9.84" (250 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 30 Micron</p>
	<p>Part Number: P171568 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P171577 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FIK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 9.84" (250 mm) Relief Valve Setting: 22 PSI (1.52 Bar)</p>
	<p>Part Number: P171569 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P171578 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FIK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 16.02" (407 mm)</p>
	<p>Part Number: P171570 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 7.99" (203 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P171579 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FIK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.58" (66 mm) Length: 15.74" (400 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P171571 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FHK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 7.99" (203 mm)</p>		<p>Part Number: P171580 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FIK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.58" (66 mm) Length: 15.74" (400 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P171572 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FIK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 9.84" (250 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 90 Micron</p>		

















	<p>Part Number: P171581 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FIK ASSY, FBO CR800/1 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.58" (66 mm) Length: 15.74" (400 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P171600 Description: HYDRAULIC CARTRIDGE Primary App: SAUER SUNDSTRAND 1511120 Dimensions: Outer Diameter: 4.41" (112 mm) Inner Diameter: 1.81" (46 mm) Length: 7.09" (180 mm)</p>
	<p>Part Number: P171582 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FIK ASSY, FBO CR800/3 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 15.74" (400 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 30 Micron</p>	<p>Part Number: P171601 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 848100068 Dimensions: Outer Diameter: 4.41" (112 mm) Inner Diameter: 1.81" (46 mm) Length: 7.09" (180 mm)</p>	<p>Part Number: P171602 Description: HYDRAULIC SPIN-ON Primary App: UCC MXR8550 Dimensions: Outer Diameter: 3.78" (96 mm) Thread Size: G 3/4 Length: 5.83" (149 mm)</p>
	<p>Part Number: P171583 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FIK ASSY Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 15.74" (400 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 60 Micron</p>		<p>Part Number: P171603 Description: HYDRAULIC SPIN-ON Primary App: EPPENSTEINER 7SL45K25 Dimensions: Outer Diameter: 3.78" (96 mm) Thread Size: G 3/4 Length: 5.86" (149 mm)</p>
	<p>Part Number: P171585 Description: HYDRAULIC CARTRIDGE Primary App: F.B.O. CR12502 Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.61" (41 mm) Length: 6.66" (169 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P171606 Description: HYDRAULIC SPIN-ON Primary App: EPPENSTEINER 7SL45P25 Dimensions: Outer Diameter: 3.78" (96 mm) Thread Size: G 3/4 Length: 5.86" (149 mm)</p>
	<p>Part Number: P171587 Description: HYDRAULIC CARTRIDGE Primary App: F.B.O. CR1251 Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.61" (41 mm) Length: 6.65" (169 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P171608 Description: HYDRAULIC SPIN-ON Primary App: UFI 8001900 Dimensions: Outer Diameter: 3.78" (96 mm) Thread Size: 3/4-BSP Length: 8.22" (209 mm)</p>
	<p>Part Number: P171588 Description: HYDRAULIC CARTRIDGE Primary App: PUROLATOR LI2692 Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.61" (41 mm) Length: 6.65" (169 mm) Efficiency 50% @ 30 Micron</p>		<p>Part Number: P171609 Description: HYDRAULIC SPIN-ON Primary App: UFI 8002000 Dimensions: Outer Diameter: 3.78" (96 mm) Thread Size: 3/4-BSP Length: 8.22" (209 mm)</p>
	<p>Part Number: P171591 Description: HYDRAULIC CARTRIDGE Primary App: PUROLATOR LI2692 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.55" (65 mm) Length: 5.35" (136 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P171613 Description: HYDRAULIC SPIN-ON Primary App: DONALDSON Europe FBK05 Series Dimensions: Outer Diameter: 4.96" (126 mm) Thread Size: G 1 1/4 Length: 7.05" (179 mm)</p>
<p>Part Number: P171595 Description: HYDRAULIC CARTRIDGE Primary App: FBO CR 220/6 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 5.35" (136 mm)</p>		<p>Part Number: P171616 Description: HYDRAULIC SPIN-ON Primary App: SPIN ON ELEMENT FOR FBK05 Dimensions: Outer Diameter: 4.96" (126 mm) Thread Size: 1 1/4-12 Length: 7.04" (179 mm)</p>	
<p>Part Number: P171596 Description: HYDRAULIC CARTRIDGE Primary App: LOMBARDINI 04102360 Dimensions: Outer Diameter: 4.41" (112 mm) Inner Diameter: 1.81" (46 mm) Length: 7.09" (180 mm)</p>		<p>Part Number: P171616 Description: HYDRAULIC SPIN-ON Primary App: SPIN ON ELEMENT FOR FBK05 Dimensions: Outer Diameter: 4.96" (126 mm) Thread Size: 1 1/4-12 Length: 7.04" (179 mm)</p>	
<p>Part Number: P171599 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 848101060 Dimensions: Outer Diameter: 4.41" (112 mm) Inner Diameter: 1.81" (46 mm) Length: 7.09" (180 mm)</p>		<p>Part Number: P171616 Description: HYDRAULIC SPIN-ON Primary App: SPIN ON ELEMENT FOR FBK05 Dimensions: Outer Diameter: 4.96" (126 mm) Thread Size: 1 1/4-12 Length: 7.04" (179 mm)</p>	












<p>Part Number: P171620 Description: HYDRAULIC SPIN-ON Primary App: DONALDSON ITALY FRCA/FACA SPIN-ON ASSY'S Dimensions: Outer Diameter: 5.04" (128 mm) Thread Size: 1 1/4-12 Length: 9.29" (236 mm) Gasket OD: 4.25" (108 mm) Gasket ID: 3.86" (98 mm) Efficiency 50% @ 10 Micron</p>	<p>Part Number: P171654 Description: HYDRAULIC CARTRIDGE Primary App: C 40/3 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.38" (35 mm) Length: 3.35" (85 mm)</p>
 <p>Part Number: P171621 Description: HYDRAULIC SPIN-ON Primary App: EPPENSTEINER 7SL130P25 Dimensions: Outer Diameter: 4.96" (126 mm) Thread Size: 1 1/4 BSP Length: 9.25" (235 mm)</p>	 <p>Part Number: P171656 Description: HYDRAULIC CARTRIDGE Primary App: MP FILTRAI CU40M60 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.37" (35 mm) Length: 3.34" (85 mm) Efficiency 50% @ 60 Micron</p>
 <p>Part Number: P171625 Description: HYDRAULIC SPIN-ON Primary App: TTE-15-10 TANK TOP SPIN ON Dimensions: Outer Diameter: 3.78" (96 mm) Thread Size: G 3/4 Length: 5.83" (148 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 10 Micron</p>	 <p>Part Number: P171657 Description: HYDRAULIC CARTRIDGE Primary App: TECNO CORP TR1218 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.37" (35 mm) Length: 5.11" (130 mm) Efficiency 50% @ 90 Micron</p>
<p>Part Number: P171635 Description: HYDRAULIC SPIN-ON Primary App: TT15/30/60 TANK BREATHERS Dimensions: Outer Diameter: 5.03" (128 mm) Thread Size: G 1 1/4 Length: 7.04" (179 mm) Relief Valve Setting: 21.75 PSI (1.50 Bar)</p>	<p>Part Number: P171658 Description: HYDRAULIC CARTRIDGE Primary App: C 100/02 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.38" (35 mm) Length: 5.12" (130 mm)</p>
 <p>Part Number: P171640 Description: HYDRAULIC SPIN-ON Primary App: TTE-60-10 Dimensions: Outer Diameter: 4.96" (126 mm) Thread Size: G 1 1/4 Length: 9.29" (236 mm) Gasket OD: 4.25" (108 mm) Gasket ID: 3.86" (98 mm)</p>	 <p>Part Number: P171660 Description: HYDRAULIC CARTRIDGE Primary App: FBO C100/1 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.38" (35 mm) Length: 5.12" (130 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
<p>Part Number: P171644 Description: HYDRAULIC CARTRIDGE Primary App: C 25/02 Dimensions: Height: 2.76" (70 mm) Outer Diameter: 1.97" (50 mm) Inner Diameter: 1.02" (26/29 mm) Length: 2.76" (70 mm)</p>	 <p>Part Number: P171663 Description: HYDRAULIC CARTRIDGE Primary App: TECNO COMP TR1217 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.37" (35 mm) Length: 5.11" (130 mm) Efficiency 50% @ 60 Micron</p>
 <p>Part Number: P171646 Description: HYDRAULIC CARTRIDGE Primary App: FBO C25/1 Dimensions: Outer Diameter: 2.05" (52 mm) Inner Diameter: 1.14" (29 mm) Length: 2.76" (70 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>	<p>Part Number: P171665 Description: HYDRAULIC CARTRIDGE Primary App: C 250/02 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.05" (52 mm) Length: 8.27" (210 mm)</p>
<p>Part Number: P171651 Description: HYDRAULIC CARTRIDGE Primary App: C 40/02 Dimensions: Height: 3.35" (85 mm) Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.38" (35 mm) Length: 3.35" (85 mm)</p>	<p>Part Number: P171666 Description: HYDRAULIC CARTRIDGE Primary App: C 250/03 Dimensions: Outer Diameter: 3.94" (100 mm) Inner Diameter: 2.05" (52 mm) Length: 8.27" (210 mm)</p>
 <p>Part Number: P171653 Description: HYDRAULIC CARTRIDGE Primary App: C40/1 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.38" (35 mm) Length: 3.35" (85 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>	 <p>Part Number: P171667 Description: HYDRAULIC CARTRIDGE Primary App: C250/1 Dimensions: Outer Diameter: 3.94" (100 mm) Inner Diameter: 2.05" (52 mm) Length: 8.27" (210 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P171668 Description: HYDRAULIC CARTRIDGE Primary App: c 250/3 Dimensions: Outer Diameter: 3.94" (100 mm) Inner Diameter: 2.05" (52 mm) Length: 8.27" (210 mm)</p>


<p>Part Number: P171670 Description: HYDRAULIC CARTRIDGE Primary App: C250/6 Dimensions: Outer Diameter: 3.93" (100 mm) Inner Diameter: 2.05" (52 mm) Length: 8.27" (210 mm)</p>	<p>Part Number: P171706 Description: HYDRAULIC CARTRIDGE Primary App: AGCO 3792287M1 Dimensions: Outer Diameter: 1.73" (44 mm) Inner Diameter: 0.87" (22 mm) Length: 3.54" (90 mm)</p>
<p>Part Number: P171671 Description: HYDRAULIC CARTRIDGE Primary App: C630 Dimensions: Outer Diameter: 5.39" (137 mm) Inner Diameter: 2.99" (76 mm) Length: 9.84" (250 mm)</p>	<p>Part Number: P171707 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP037.2A06A, FBO CM180/01 Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.87" (22 mm) Length: 6.93" (176 mm)</p>
<p>Part Number: P171672 Description: HYDRAULIC CARTRIDGE Primary App: C 630/02 Dimensions: Outer Diameter: 5.39" (137 mm) Inner Diameter: 2.99" (76 mm) Length: 9.84" (250 mm)</p>	<p>Part Number: P171709 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP037.2A25A, FBO CM180/03 Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.87" (22 mm) Length: 6.93" (176 mm)</p>
 <p>Part Number: P171674 Description: HYDRAULIC CARTRIDGE Primary App: C630/1 Dimensions: Outer Diameter: 5.39" (137 mm) Inner Diameter: 2.99" (76 mm) Length: 9.84" (250 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>	 <p>Part Number: P171713 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP065.1A06NA, FBO CM230/01 Dimensions: Outer Diameter: 1.81" (46 mm) Inner Diameter: 1.02" (26 mm) Length: 3.43" (87 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
<p>Part Number: P171675 Description: HYDRAULIC CARTRIDGE Primary App: C 630/3 Dimensions: Outer Diameter: 5.39" (137 mm) Inner Diameter: 2.99" (76 mm) Length: 9.84" (250 mm)</p>	 <p>Part Number: P171714 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP065.1A10NA, FBO CM230/02 Dimensions: Outer Diameter: 1.81" (46 mm) Inner Diameter: 1.02" (26 mm) Length: 3.43" (87 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
<p>Part Number: P171677 Description: HYDRAULIC CARTRIDGE Primary App: C630/6 Dimensions: Outer Diameter: 5.39" (137 mm) Inner Diameter: 2.99" (76 mm) Length: 9.84" (250 mm)</p>	 <p>Part Number: P171715 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP065.1A25NA, FBO CM230/03 Dimensions: Outer Diameter: 1.81" (46 mm) Inner Diameter: 1.02" (26 mm) Length: 3.43" (87 mm) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>
<p>Part Number: P171681 Description: HYDRAULIC CARTRIDGE Primary App: FBO C200/1 Dimensions: Outer Diameter: 3.94" (100 mm) Inner Diameter: 2.05" (52 mm) Length: 4.72" (120 mm)</p>	<p>Part Number: P171732 Description: HYDRAULIC CARTRIDGE Primary App: LOESING 140156 Dimensions: Outer Diameter: 2.13" (54 mm) Inner Diameter: 1.06" (27 mm) Length: 3.43" (87 mm)</p>
 <p>Part Number: P171701 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP037.1A06A, FBO CM140/01 Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.89" (23 mm) Length: 3.54" (90 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>	 <p>Part Number: P171733 Description: HYDRAULIC CARTRIDGE Primary App: CASE 76028203 Dimensions: Outer Diameter: 2.13" (54 mm) Inner Diameter: 1.06" (27 mm) Length: 3.43" (87 mm)</p>
 <p>Part Number: P171702 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP037.1A10A, FBO CM140/02 Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.89" (23 mm) Length: 3.54" (90 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>	 <p>Part Number: P171734 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP135.1A03NA, FBO 452.51 Dimensions: Outer Diameter: 2.13" (54 mm) Inner Diameter: 1.08" (27 mm) Length: 4.80" (122 mm) Efficiency 99% @ 3 Micron</p>
 <p>Part Number: P171703 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP037.1A25A, FBO CM180/03 Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.89" (23 mm) Length: 3.54" (90 mm) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>	

	<p>Part Number: P171735 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP135.1A10NA, FBO 452.52 Dimensions: Outer Diameter: 2.13" (54 mm) Inner Diameter: 1.08" (27 mm) Length: 4.80" (122 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P171744 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP320.2A10NA, FBO 455.52 Dimensions: Outer Diameter: 3.07" (78 mm) Inner Diameter: 1.59" (40 mm) Length: 9.45" (240 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P171736 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP135.1A25NA, FBO 452.53 Dimensions: Outer Diameter: 2.13" (54 mm) Inner Diameter: 1.08" (27 mm) Length: 4.80" (122 mm) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P171745 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP320.2A25NA, FBO 455.53 Dimensions: Outer Diameter: 3.07" (78 mm) Inner Diameter: 1.59" (40 mm) Length: 9.45" (240 mm) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P171737 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP135.2A03NA, FBO 453.51 Dimensions: Outer Diameter: 2.13" (54 mm) Inner Diameter: 1.08" (27 mm) Length: 9.06" (230 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P171746 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP320.3A03NA, FBO 456.51 Dimensions: Outer Diameter: 3.07" (78 mm) Inner Diameter: 1.59" (40 mm) Length: 14.96" (380 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P171738 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP135.2A10NA, FBO 453.52 Dimensions: Outer Diameter: 2.13" (54 mm) Inner Diameter: 1.08" (27 mm) Length: 9.06" (226 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P171747 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP320.3A10NA, FBO 456.52 Dimensions: Outer Diameter: 3.07" (78 mm) Inner Diameter: 1.59" (40 mm) Length: 14.96" (380 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P171739 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP135.2A25NA, FBO 453.53 Dimensions: Outer Diameter: 2.13" (54 mm) Inner Diameter: 1.08" (27 mm) Length: 9.06" (230 mm) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P171748 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP320.3A25NA, FBO 456.53 Dimensions: Outer Diameter: 3.07" (78 mm) Inner Diameter: 1.59" (40 mm) Length: 14.96" (380 mm) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P171741 Description: HYDRAULIC CARTRIDGE Primary App: F.B.O. 45452 Dimensions: Outer Diameter: 3.07" (78 mm) Inner Diameter: 1.66" (42 mm) Length: 5.51" (140 mm)</p>		<p>Part Number: P171772 Description: HYDRAULIC CARTRIDGE Primary App: CLC 5/01 Dimensions: Outer Diameter: 1.14" (29 mm) Inner Diameter: 0.63" (16 mm) Length: 2.76" (70 mm)</p>
	<p>Part Number: P171742 Description: HYDRAULIC CARTRIDGE Primary App: FBO 45453 Dimensions: Outer Diameter: 3.07" (78 mm) Inner Diameter: 1.59" (40 mm) Length: 5.51" (140 mm) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P171773 Description: HYDRAULIC CARTRIDGE Primary App: FBO LC5/02 Dimensions: Outer Diameter: 1.12" (28 mm) Inner Diameter: 0.61" (15 mm) Length: 2.75" (70 mm) Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P171743 Description: HYDRAULIC CARTRIDGE Primary App: MP PRODUCTS HP320.2A03NA, FBO 455.51 Dimensions: Outer Diameter: 3.07" (78 mm) Inner Diameter: 1.59" (40 mm) Length: 9.45" (240 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P171783 Description: HYDRAULIC CARTRIDGE Primary App: LIEBHERR 510619208 Dimensions: Outer Diameter: 2.13" (54 mm) Length: 1.97" (50 mm)</p>
			<p>Part Number: P171784 Description: HYDRAULIC CARTRIDGE Primary App: LIEBHERR 510659990 Dimensions: Outer Diameter: 3.39" (86 mm) Length: 2.36" (60 mm)</p>
			<p>Part Number: P171785 Description: HYDRAULIC CARTRIDGE Primary App: SAUER SUNDSTRAND 1511163 Dimensions: Outer Diameter: 4.33" (110 mm) Length: 3.23" (82 mm)</p>





















<p>Part Number: P171789 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON ST3D120 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 0.31" (8 mm) Length: 7.87" (200 mm)</p>	 <p>Part Number: P171802 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TX310 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 1.77" (45 mm) Length: 5.91" (150 mm) Efficiency 50% @ 25 Micron</p>
 <p>Part Number: P171794 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON ST260 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 1.77" (45 mm) Length: 4.17" (106 mm) Efficiency 50% @ 60 Micron</p>	 <p>Part Number: P171803 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TX3D10 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 1.77" (45 mm) Length: 7.87" (200 mm) Efficiency 50% @ 25 Micron</p>
 <p>Part Number: P171795 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON ST360 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 1.77" (45 mm) Length: 5.91" (150 mm) Efficiency 50% @ 60 Micron</p>	 <p>Part Number: P171804 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TX3E10 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 0.31" (8 mm) Length: 11.81" (300 mm)</p>
 <p>Part Number: P171796 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON ST3D60 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 0.31" (8 mm) Length: 7.87" (200 mm)</p>	 <p>Part Number: P171805 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXX410 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 2.52" (64 mm) Length: 7.48" (190 mm) Efficiency 50% @ 25 Micron</p>
 <p>Part Number: P171797 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON ST3E60 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 0.31" (8 mm) Length: 11.81" (300 mm)</p>	 <p>Part Number: P171806 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXX510 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 2.52" (64 mm) Length: 10.24" (260 mm) Efficiency 50% @ 25 Micron</p>
 <p>Part Number: P171798 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON ST460 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 0.39" (10 mm) Length: 7.48" (190 mm)</p>	 <p>Part Number: P171807 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXX5A10 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 2.52" (64 mm) Length: 18.31" (465 mm) Efficiency 50% @ 25 Micron</p>
 <p>Part Number: P171799 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON ST560 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 0.39" (10 mm) Length: 10.24" (260 mm)</p>	 <p>Part Number: P171808 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON MB2 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 1.77" (45 mm) Length: 4.17" (106 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
<p>Part Number: P171800 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON ST5A60 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 0.39" (10 mm) Length: 18.31" (465 mm)</p>	 <p>Part Number: P171809 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON MB3 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 1.77" (45 mm) Length: 5.91" (150 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
 <p>Part Number: P171801 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TX210 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 0.31" (8 mm) Length: 4.17" (106 mm)</p>	

















	<p>Part Number: P171810 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON MB3D Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 1.77" (45 mm) Length: 7.87" (200 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P171818 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXW3K-CC25 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 1.77" (45 mm) Length: 11.81" (300 mm) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P171811 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON MB3E Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 1.77" (45 mm) Length: 11.81" (300 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P171819 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXW4-CC25 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 2.52" (64 mm) Length: 7.48" (190 mm) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P171812 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXX4-10 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 2.52" (64 mm) Length: 7.48" (190 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P171820 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXW5-CC25 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 2.52" (64 mm) Length: 10.24" (260 mm) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P171813 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXX5-10 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 2.52" (64 mm) Length: 10.24" (260 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P171821 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXW5A-CC25 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 0.39" (10 mm) Length: 18.31" (465 mm)</p>
	<p>Part Number: P171814 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXX5A-10 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 2.52" (64 mm) Length: 18.30" (465 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P171822 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXW2-CC10 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 1.77" (45 mm) Length: 4.17" (106 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P171815 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXW2-CC25 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 0.31" (8 mm) Length: 4.17" (106 mm)</p>		<p>Part Number: P171823 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXW3-CC10 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 1.77" (45 mm) Length: 5.91" (150 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P171816 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXW3-CC25 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 1.77" (45 mm) Length: 5.91" (150 mm) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P171824 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXW3D-CC10 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 1.77" (45 mm) Length: 7.87" (200 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P171817 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXW3D-CC25 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 1.77" (45 mm) Length: 7.87" (200 mm) Efficiency 50% @ 9 Micron</p>		<p>Part Number: P171825 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXW3E-CC10 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 1.77" (45 mm) Length: 11.81" (300 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>

















	<p>Part Number: P171826 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXW4-CC10 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 2.52" (64 mm) Length: 7.48" (190 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P171837 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FSK ASSY Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.57" (40 mm) Length: 8.27" (210 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P171827 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXW5-CC10 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 2.52" (64 mm) Length: 10.24" (260 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P171839 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FSK ASSY Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.87" (22 mm) Length: 6.38" (162 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P171828 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FRK ASSY, FAIREY ARLON TXW5A-CC10 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 2.52" (64 mm) Length: 18.30" (465 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P171840 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FSK ASSY Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.57" (40 mm) Length: 8.27" (210 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
<p>Part Number: P171829 Description: HYDRAULIC CARTRIDGE Primary App: CR30 Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.87" (22 mm) Length: 3.82" (97 mm)</p>	<p>Part Number: P171829 Description: HYDRAULIC CARTRIDGE Primary App: CR30 Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.87" (22 mm) Length: 3.82" (97 mm)</p>	<p>Part Number: P171841 Description: HYDRAULIC CARTRIDGE Primary App: CR20/03 Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.87" (22 mm) Length: 3.82" (97 mm)</p>	<p>Part Number: P171841 Description: HYDRAULIC CARTRIDGE Primary App: CR20/03 Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.87" (22 mm) Length: 3.82" (97 mm)</p>
<p>Part Number: P171830 Description: HYDRAULIC CARTRIDGE Primary App: CR40 Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.87" (22 mm) Length: 6.38" (162 mm)</p>	<p>Part Number: P171830 Description: HYDRAULIC CARTRIDGE Primary App: CR40 Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.87" (22 mm) Length: 6.38" (162 mm)</p>	<p>Part Number: P171842 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FSK ASSY Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.87" (22 mm) Length: 6.38" (162 mm)</p>	<p>Part Number: P171842 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FSK ASSY Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.87" (22 mm) Length: 6.38" (162 mm)</p>
	<p>Part Number: P171831 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FSK ASSY Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.65" (42 mm) Length: 8.27" (210 mm)</p>	<p>Part Number: P171843 Description: HYDRAULIC CARTRIDGE Primary App: FSK04 INTANK SERIES Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 0.87" (22 mm) Length: 1.65" (42 mm) Efficiency 99% @ 25 Micron</p>	<p>Part Number: P171843 Description: HYDRAULIC CARTRIDGE Primary App: FSK04 INTANK SERIES Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 0.87" (22 mm) Length: 1.65" (42 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P171833 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FSK ASSY Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.87" (22 mm) Length: 6.38" (162 mm)</p>	<p>Part Number: P171845 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FSK ASSY Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.87" (22 mm) Length: 6.38" (162 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>	<p>Part Number: P171845 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FSK ASSY Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.87" (22 mm) Length: 6.38" (162 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P171834 Description: HYDRAULIC CARTRIDGE Primary App: FBO 150/6 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.57" (40 mm) Length: 8.27" (210 mm) Efficiency 50% @ 60 Micron</p>	<p>Part Number: P171846 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FSK ASSY Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.57" (40 mm) Length: 8.27" (210 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>	<p>Part Number: P171846 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FSK ASSY Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.57" (40 mm) Length: 8.27" (210 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P171836 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON FSK ASSY Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.87" (22 mm) Length: 6.38" (162 mm)</p>		<p>Part Number: P171861 Description: STRAINER Primary App: SUCTION STRAINER Dimensions: Outer Diameter: 2.05" (52 mm) Thread Size: G2 Length: 3.03" (77 mm)</p>
<p>Part Number: P171899 Description: HYDRAULIC CARTRIDGE Primary App: MASSEY FERGUSON 2754335M1 Dimensions: Outer Diameter: 5.51" (140 mm) Thread Size: G2 Length: 8.66" (220 mm)</p>	<p>Part Number: P171899 Description: HYDRAULIC CARTRIDGE Primary App: MASSEY FERGUSON 2754335M1 Dimensions: Outer Diameter: 5.51" (140 mm) Thread Size: G2 Length: 8.66" (220 mm)</p>	<p>Part Number: P171899 Description: HYDRAULIC CARTRIDGE Primary App: MASSEY FERGUSON 2754335M1 Dimensions: Outer Diameter: 5.51" (140 mm) Thread Size: G2 Length: 8.66" (220 mm)</p>	<p>Part Number: P171899 Description: HYDRAULIC CARTRIDGE Primary App: MASSEY FERGUSON 2754335M1 Dimensions: Outer Diameter: 5.51" (140 mm) Thread Size: G2 Length: 8.66" (220 mm)</p>







<p>Part Number: P171906 Description: HYDRAULIC CARTRIDGE Primary App: FIOA 600/3 Dimensions: Outer Diameter: 5.51" (140 mm) Thread Size: G2-1/2 Length: 12.48" (317 mm)</p>	 <p>Part Number: P172464 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXX8A-CC10 Dimensions: Outer Diameter: 4.96" (126 mm) Length: 11.42" (290 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
<p>Part Number: P171907 Description: HYDRAULIC CARTRIDGE Primary App: FIOA 600/6 Dimensions: Outer Diameter: 5.51" (140 mm) Thread Size: G2-1/2 Length: 12.48" (317 mm)</p>	 <p>Part Number: P172465 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXX8A-CC25 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 3.62" (92 mm) Length: 11.42" (290 mm) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>
<p>Part Number: P171910 Description: STRAINER Primary App: FIOA 800/3 Dimensions: Outer Diameter: 5.51" (140 mm) Thread Size: G3 Length: 12.48" (317 mm)</p>	 <p>Part Number: P172466 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXX8C-10 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 3.62" (92 mm) Length: 18.90" (480 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
<p>Part Number: P172386 Description: BREATHER Primary App: (FS 7/4 Dimensions: Outer Diameter: 2.83" (72 mm) Thread Size: G 1/2 Inner Diameter: 2.52" (64 mm) Radius: 2.91" (74 mm)</p>	 <p>Part Number: P172467 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXW8C-CC10 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 0.39" (10 mm) Length: 18.90" (480 mm) Efficiency 50% @ 2 Micron</p>
<p>Part Number: P172433 Description: HYDRAULIC CARTRIDGE Primary App: FIAT 45482667 Dimensions: Outer Diameter: 1.57" (40 mm) Length: 1.34" (34 mm)</p>	 <p>Part Number: P172468 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXW8C-CC25 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 3.62" (92 mm) Length: 18.90" (480 mm) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>
<p>Part Number: P172448 Description: HYDRAULIC CARTRIDGE Primary App: CR 95/03 Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: 1.18" (30 mm) Length: 5.04" (128 mm)</p>	 <p>Part Number: P173008 Description: HYDRAULIC CARTRIDGE Primary App: SAUER SUNDSTRAND 1511150 Dimensions: Outer Diameter: 2.20" (56 mm) Inner Diameter: 1.27" (32 mm) Length: 7.00" (178 mm) Efficiency 50% @ 5 Micron</p>
 <p>Part Number: P172460 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXX6A-10 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 3.62" (92 mm) Length: 8.31" (211 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>	<p>Part Number: P173009 Description: HYDRAULIC CARTRIDGE Primary App: SAUER SUNDSTRAND 1511151 Dimensions: Outer Diameter: 2.20" (56 mm) Inner Diameter: 1.27" (32 mm) Length: 7.00" (178 mm) Efficiency 50% @ 10 Micron</p>
 <p>Part Number: P172461 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXX6A-CC10 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 0.39" (10 mm) Length: 8.31" (211 mm)</p>	 <p>Part Number: P173027 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 270Z1FFA Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 1.26" (32 mm) Length: 3.90" (99 mm) Efficiency 99% @ 3 Micron</p>
 <p>Part Number: P172462 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXX6A-CC25 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 0.39" (10 mm) Length: 8.31" (211 mm)</p>	 <p>Part Number: P173028 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 270Z101A Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 1.26" (32 mm) Length: 3.90" (99 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
 <p>Part Number: P172463 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXX8A-10 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 3.62" (92 mm) Length: 11.42" (290 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>	

	<p>Part Number: P173029 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 270Z105A Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 1.26" (32 mm) Length: 3.90" (99 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P173038 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 370L110A Dimensions: Outer Diameter: 3.66" (93 mm) Inner Diameter: 1.89" (48 mm) Length: 3.90" (99 mm) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P173030 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 270Z110A Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 1.26" (32 mm) Length: 3.90" (99 mm) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P173039 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 370Z2FFA Dimensions: Outer Diameter: 3.66" (93 mm) Inner Diameter: 1.89" (48 mm) Length: 7.87" (200 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P173031 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 270Z2FFA Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 1.26" (32 mm) Length: 9.13" (232 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P173040 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 370L201A Dimensions: Outer Diameter: 3.66" (93 mm) Inner Diameter: 1.89" (48 mm) Length: 7.87" (200 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P173032 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 270L201A Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 1.26" (32 mm) Length: 9.13" (232 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P173041 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 370L205A Dimensions: Outer Diameter: 3.66" (93 mm) Inner Diameter: 1.89" (48 mm) Length: 7.87" (200 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P173033 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 270L205A Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 1.26" (32 mm) Length: 9.13" (232 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P173042 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 370L210A Dimensions: Outer Diameter: 3.66" (93 mm) Inner Diameter: 1.89" (48 mm) Length: 7.87" (200 mm) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P173034 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 270L210A Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 1.26" (32 mm) Length: 9.13" (232 mm) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P173043 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 370Z3FFA Dimensions: Outer Diameter: 3.66" (93 mm) Inner Diameter: 1.89" (48 mm) Length: 12.60" (320 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P173035 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 370Z1FFA Dimensions: Outer Diameter: 3.36" (85 mm) Inner Diameter: 1.90" (48 mm) Length: 3.90" (99 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P173044 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 370L301A Dimensions: Outer Diameter: 3.66" (93 mm) Inner Diameter: 1.89" (48 mm) Length: 12.60" (320 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P173036 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 370L101A Dimensions: Outer Diameter: 3.66" (93 mm) Inner Diameter: 1.89" (48 mm) Length: 3.90" (99 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P173045 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 370L305A Dimensions: Outer Diameter: 3.66" (93 mm) Inner Diameter: 1.89" (48 mm) Length: 12.60" (320 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P173037 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 370L105A, 370Z122A Dimensions: Outer Diameter: 3.66" (93 mm) Inner Diameter: 1.89" (48 mm) Length: 3.90" (99 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P173046 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 370L310A Dimensions: Outer Diameter: 3.66" (93 mm) Inner Diameter: 1.89" (48 mm) Length: 12.60" (320 mm) Efficiency 50% @ 9 Micron Efficiency 99% @ 25 Micron</p>

	<p>Part Number: P173048 Description: HYDRAULIC CARTRIDGE Primary App: EXMAN 173048 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.14" (29 mm) Length: 6.65" (169 mm) Efficiency 50% @ 30 Micron</p>		<p>Part Number: P173074 Description: HYDRAULIC CARTRIDGE Primary App: CASE 1930810 Dimensions: Outer Diameter: 5.51" (140 mm) Length: 10.12" (257 mm)</p>
	<p>Part Number: P173049 Description: HYDRAULIC CARTRIDGE Primary App: FBO CR180/1 Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.44" (37 mm) Length: 11.77" (299 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P173080 Description: HYDRAULIC CARTRIDGE Primary App: MASSEY FERGUSON 3712404M1 Dimensions: Outer Diameter: 1.42" (36 mm) Length: 5.20" (132 mm)</p>
	<p>Part Number: P173052 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXX6A10 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 0.39" (10 mm) Length: 8.31" (211 mm)</p>		<p>Part Number: P173081 Description: HYDRAULIC CARTRIDGE Primary App: O & K 1717467 Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 3.94" (100 mm) Length: 25.40" (645 mm) Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P173055 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXX8A10 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 3.62" (92 mm) Length: 11.42" (290 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P173091 Description: HYDRAULIC CARTRIDGE Primary App: FIAT 79082402 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 16.02" (407 mm)</p>
	<p>Part Number: P173056 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON ST8A60 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 0.39" (10 mm) Length: 11.42" (290 mm)</p>		<p>Part Number: P173093 Description: HYDRAULIC CARTRIDGE Primary App: CASE 1930836 Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 3.35" (85 mm) Length: 8.98" (228 mm)</p>
	<p>Part Number: P173057 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON ST8C120 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 3.62" (92 mm) Length: 18.90" (480 mm) Efficiency 50% @ 90 Micron</p>		<p>Part Number: P173094 Description: HYDRAULIC CARTRIDGE Primary App: CASE 01930875 Dimensions: Outer Diameter: 5.91" (150 mm) Inner Diameter: 3.35" (85 mm) Length: 9.25" (235 mm)</p>
	<p>Part Number: P173058 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON MB8C Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 3.62" (92 mm) Length: 18.90" (480 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P173096 Description: HYDRAULIC CARTRIDGE Primary App: ATLAS WEYHAUSEN 1691052 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 3.62" (92 mm) Length: 15.35" (390 mm)</p>
	<p>Part Number: P173060 Description: HYDRAULIC CARTRIDGE Primary App: FAI 848101112 Dimensions: Outer Diameter: 3.94" (100 mm) Inner Diameter: 2.32" (59 mm) Length: 7.01" (178 mm) Efficiency 50% @ 30 Micron</p>		<p>Part Number: P173097 Description: HYDRAULIC CARTRIDGE Primary App: EUCLID 11026936 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 3.62" (92 mm) Length: 15.35" (390 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P173062 Description: HYDRAULIC SPIN-ON Primary App: FBO CA160/1R Dimensions: Outer Diameter: 5.03" (128 mm) Thread Size: 1 1/4-12 Length: 7.04" (179 mm)</p>		<p>Part Number: P173098 Description: HYDRAULIC CARTRIDGE Primary App: FIN FILTER FFPA1109810 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 3.62" (92 mm) Length: 15.35" (390 mm) Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P173065 Description: HYDRAULIC CARTRIDGE Primary App: TOYOTA 485696 Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 2.56" (65 mm) Length: 7.99" (203 mm) Efficiency 50% @ 30 Micron</p>		<p>Part Number: P173100 Description: HYDRAULIC CARTRIDGE Primary App: CRS430/6 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 0.39" (10 mm) Length: 15.35" (390 mm)</p>

<p>Part Number: P173133 Description: HYDRAULIC SPIN-ON Primary App: HYSTER 1382725 Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 1 3/8-12 Length: 9.45" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm)</p>	 <p>Part Number: P173166 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0240R005BNHC Dimensions: Outer Diameter: 2.89" (74 mm) Inner Diameter: 1.35" (34 mm) Length: 7.99" (203 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
<p>Part Number: P173138 Description: HYDRAULIC CARTRIDGE Primary App: EXMAN 173138 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.00" (25 mm) Length: 8.22" (209 mm) Efficiency 50% @ 10 Micron</p>	 <p>Part Number: P173167 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0240R020BNHC Dimensions: Outer Diameter: 2.89" (74 mm) Inner Diameter: 1.35" (34 mm) Length: 7.99" (203 mm) Efficiency 99% @ 20 Micron</p>
 <p>Part Number: P173158 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0060R005BNHC Dimensions: Outer Diameter: 2.03" (52 mm) Inner Diameter: 0.94" (24 mm) Length: 4.06" (103 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>	 <p>Part Number: P173168 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0330R003BNHC Dimensions: Outer Diameter: 3.72" (95 mm) Inner Diameter: 1.90" (48 mm) Length: 7.68" (195 mm) Efficiency 99% @ 3 Micron</p>
 <p>Part Number: P173159 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0060R020BNHC Dimensions: Outer Diameter: 2.03" (52 mm) Inner Diameter: 0.87" (22 mm) Length: 4.06" (103 mm) Efficiency 99% @ 20 Micron</p>	 <p>Part Number: P173169 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0330R005BNHC Dimensions: Outer Diameter: 3.72" (95 mm) Inner Diameter: 1.90" (48 mm) Length: 7.68" (195 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
 <p>Part Number: P173161 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0110R005BNHC Dimensions: Outer Diameter: 2.05" (52 mm) Inner Diameter: 0.94" (24 mm) Length: 6.73" (171 mm)</p>	 <p>Part Number: P173170 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0330R020BNHC Dimensions: Outer Diameter: 3.72" (95 mm) Inner Diameter: 1.90" (48 mm) Length: 7.68" (195 mm) Efficiency 99% @ 20 Micron</p>
 <p>Part Number: P173162 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0110R020BNHC Dimensions: Outer Diameter: 2.03" (52 mm) Inner Diameter: 0.87" (22 mm) Length: 6.73" (171 mm) Efficiency 99% @ 20 Micron</p>	 <p>Part Number: P173171 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0500R003BNHC Dimensions: Outer Diameter: 3.72" (95 mm) Inner Diameter: 1.90" (48 mm) Length: 10.67" (276 mm) Efficiency 99% @ 3 Micron</p>
 <p>Part Number: P173163 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0160R003BNHC Dimensions: Outer Diameter: 2.89" (74 mm) Inner Diameter: 1.35" (34 mm) Length: 5.67" (144 mm) Efficiency 99% @ 3 Micron</p>	 <p>Part Number: P173172 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0500R005BNHC Dimensions: Outer Diameter: 3.72" (95 mm) Inner Diameter: 1.90" (48 mm) Length: 10.87" (276 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
 <p>Part Number: P173164 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0160R020BNHC Dimensions: Outer Diameter: 2.89" (74 mm) Inner Diameter: 1.35" (34 mm) Length: 5.67" (144 mm) Efficiency 99% @ 20 Micron</p>	 <p>Part Number: P173173 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0500R010BNHC Dimensions: Outer Diameter: 3.72" (95 mm) Inner Diameter: 1.90" (48 mm) Length: 10.87" (276 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
 <p>Part Number: P173165 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0240R003BNHC Dimensions: Outer Diameter: 2.89" (74 mm) Inner Diameter: 1.35" (34 mm) Length: 8.00" (203 mm) Efficiency 99% @ 3 Micron</p>	 <p>Part Number: P173174 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0500R020BNHC Dimensions: Outer Diameter: 3.72" (95 mm) Inner Diameter: 1.90" (48 mm) Length: 10.87" (276 mm) Efficiency 99% @ 20 Micron</p>

	<p>Part Number: P173175 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0660R005BNHC Dimensions: Outer Diameter: 4.50" (114 mm) Inner Diameter: 2.70" (69 mm) Length: 13.11" (333 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P173189 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0060D003BNHC Dimensions: Outer Diameter: 1.88" (48 mm) Inner Diameter: 0.87" (22 mm) Length: 3.31" (84 mm)</p>
	<p>Part Number: P173176 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0660R020BNHC Dimensions: Outer Diameter: 4.50" (114 mm) Inner Diameter: 2.70" (69 mm) Length: 13.11" (333 mm) Efficiency 99% @ 20 Micron</p>		<p>Part Number: P173190 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0060D020BNHC Dimensions: Outer Diameter: 1.88" (48 mm) Inner Diameter: 0.87" (22 mm) Length: 3.27" (83 mm)</p>
	<p>Part Number: P173178 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0850R005BNHC Dimensions: Outer Diameter: 4.50" (114 mm) Inner Diameter: 2.70" (69 mm) Length: 16.22" (412 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P173191 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0110D003BNHC Dimensions: Outer Diameter: 1.88" (48 mm) Inner Diameter: 0.87" (22 mm) Length: 6.02" (153 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P173179 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0850R010BNHC Dimensions: Outer Diameter: 4.50" (114 mm) Inner Diameter: 2.70" (69 mm) Length: 16.22" (412 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P173192 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC/HYCON 0110D020BNHC Dimensions: Outer Diameter: 1.88" (48 mm) Inner Diameter: 0.87" (22 mm) Length: 6.02" (153 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P173180 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0850R020BNHC Dimensions: Outer Diameter: 4.50" (114 mm) Inner Diameter: 2.70" (69 mm) Length: 16.22" (412 mm) Efficiency 99% @ 20 Micron</p>		<p>Part Number: P173193 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0160D003BNHC Dimensions: Outer Diameter: 2.75" (70 mm) Inner Diameter: 1.35" (34 mm) Length: 4.53" (115 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P173182 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0950R020BNHC Dimensions: Outer Diameter: 5.65" (143 mm) Inner Diameter: 3.80" (97 mm) Length: 14.29" (363 mm) Efficiency 99% @ 20 Micron</p>		<p>Part Number: P173194 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0160D020BNHC Dimensions: Outer Diameter: 2.75" (70 mm) Inner Diameter: 1.35" (34 mm) Length: 4.53" (115 mm) Efficiency 99% @ 20 Micron</p>
	<p>Part Number: P173185 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0030D003BNHC Dimensions: Outer Diameter: 1.38" (35 mm) Inner Diameter: 0.48" (12 mm) Length: 3.70" (94 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P173195 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0240D003BNHC Dimensions: Outer Diameter: 2.75" (70 mm) Inner Diameter: 1.35" (34 mm) Length: 6.81" (173 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P173187 Description: HYDRAULIC CARTRIDGE Primary App: INTERNORMEN 020030D10VG30 Dimensions: Outer Diameter: 1.38" (35 mm) Inner Diameter: 0.48" (12 mm) Length: 3.70" (94 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P173196 Description: HYDRAULIC CARTRIDGE Primary App: LIEBHERR 7364597 Dimensions: Outer Diameter: 2.72" (69 mm) Inner Diameter: 1.34" (34 mm) Length: 6.85" (174 mm)</p>
	<p>Part Number: P173188 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0030D020BNHC, LIEBHERR 7362910 Dimensions: Outer Diameter: 1.38" (35 mm) Inner Diameter: 0.48" (12 mm) Length: 3.70" (94 mm) Efficiency 99% @ 20 Micron</p>		<p>Part Number: P173197 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0330D003BNHC Dimensions: Outer Diameter: 3.57" (91 mm) Inner Diameter: 1.90" (48 mm) Length: 6.38" (162 mm) Efficiency 99% @ 3 Micron</p>
			<p>Part Number: P173199 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC/HYCON 0660D003BNHC Dimensions: Outer Diameter: 3.57" (91 mm) Inner Diameter: 1.90" (48 mm) Length: 12.91" (328 mm) Efficiency 99% @ 3 Micron</p>

	<p>Part Number: P173200 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0660D020BNHC Dimensions: Outer Diameter: 3.57" (91 mm) Inner Diameter: 1.90" (48 mm) Length: 12.91" (328 mm) Efficiency 99% @ 20 Micron</p>		<p>Part Number: P173476 Description: HYDRAULIC CARTRIDGE Primary App: BAIK TRADING 131500005 Dimensions: Outer Diameter: 1.97" (50 mm) Inner Diameter: 2.50" (64 mm) Length: 11.02" (280 mm)</p>
	<p>Part Number: P173207 Description: HYDRAULIC CARTRIDGE Primary App: HITACHI, 4227353, JOHN DEERE TH101885, TH111010, Dimensions: Outer Diameter: 4.41" (112 mm) Inner Diameter: 2.72" (69 mm) Length: 17.24" (438 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P173478 Description: HYDRAULIC CARTRIDGE Primary App: AGCO 3716334H1 Dimensions: Outer Diameter: 2.36" (60 mm) Length: 8.82" (224 mm)</p>
	<p>Part Number: P173211 Description: HYDRAULIC CARTRIDGE Primary App: RENAULT V.I. 7701015558 Dimensions: Outer Diameter: 2.64" (67 mm) Inner Diameter: 1.00" (25 mm) Length: 4.33" (110 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P173481 Description: HYDRAULIC CARTRIDGE Primary App: LIEBHERR7367204 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 1.57" (40 mm) Length: 7.72" (196 mm) Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P173237 Description: HYDRAULIC CARTRIDGE Primary App: EXMAN HO1914 Dimensions: Outer Diameter: 5.91" (150 mm) Inner Diameter: 3.74" (95 mm) Length: 17.71" (450 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P173482 Description: HYDRAULIC CARTRIDGE Primary App: LIEBHERR 7366869 Dimensions: Outer Diameter: 5.98" (152 mm) Inner Diameter: 3.54" (90 mm) Length: 32.68" (830 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P173238 Description: HYDRAULIC CARTRIDGE Primary App: HITACHI 4207841 Dimensions: Outer Diameter: 2.01" (51 mm) Inner Diameter: 0.91" (23 mm) Length: 5.73" (146 mm) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P173483 Description: HYDRAULIC CARTRIDGE Primary App: LIEBHERR 7211198 Dimensions: Outer Diameter: 5.98" (152 mm) Inner Diameter: 3.35" (85 mm) Length: 16.34" (415 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P173334 Description: HYDRAULIC CARTRIDGE Primary App: CR600/02 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 9.84" (250 mm)</p>		<p>Part Number: P173484 Description: HYDRAULIC CARTRIDGE Primary App: LIEBHERR 7366101 Dimensions: Outer Diameter: 5.98" (152 mm) Inner Diameter: 3.35" (85 mm) Length: 24.57" (624 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P173370 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 848001080 Dimensions: Outer Diameter: 3.98" (101 mm) Thread Size: G2 Length: 9.65" (245 mm)</p>		<p>Part Number: P173485 Description: HYDRAULIC CARTRIDGE Primary App: CATERPILLAR, DEMAG Dimensions: Outer Diameter: 4.65" (118 mm) Inner Diameter: 2.32" (59 mm) Length: 6.50" (165 mm) Efficiency 50% @ 27 Micron</p>
	<p>Part Number: P173416 Description: HYDRAULIC CARTRIDGE Primary App: CR220/3RF Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 5.35" (136 mm)</p>		<p>Part Number: P173486 Description: HYDRAULIC CARTRIDGE Primary App: ARGO P3062051 Dimensions: Outer Diameter: 2.32" (59 mm) Inner Diameter: 1.04" (26 mm) Length: 7.87" (200 mm) Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P173417 Description: HYDRAULIC CARTRIDGE Primary App: CR500/3RF Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 7.99" (203 mm)</p>		<p>Part Number: P173488 Description: HYDRAULIC CARTRIDGE Primary App: ARGO P2093301 Dimensions: Outer Diameter: 3.50" (89 mm) Inner Diameter: 1.97" (50 mm) Length: 12.99" (330 mm) Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P173418 Description: HYDRAULIC CARTRIDGE Primary App: CR100/3RF Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.14" (29 mm) Length: 5.04" (128 mm)</p>		

	<p>Part Number: P173489 Description: HYDRAULIC CARTRIDGE Primary App: ARGO P2092301 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 1.97" (50 mm) Length: 8.94" (227 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P173583 Description: HYDRAULIC CARTRIDGE Primary App: VICKERS 361992, 941060 Dimensions: Outer Diameter: 4.00" (102 mm) Inner Diameter: 2.90" (74 mm) Length: 6.25" (159 mm) Efficiency 50% @ 30 Micron</p>
	<p>Part Number: P173490 Description: HYDRAULIC CARTRIDGE Primary App: LIEBHERR 7360470 Dimensions: Outer Diameter: 3.94" (100 mm) Inner Diameter: 2.48" (63 mm) Length: 18.27" (464 mm) Efficiency 99% @ 25 Micron</p>		<p>Part Number: P173584 Description: HYDRAULIC CARTRIDGE Primary App: VICKERS 361741, 941062 Dimensions: Outer Diameter: 4.00" (102 mm) Inner Diameter: 2.90" (74 mm) Length: 6.25" (159 mm) Efficiency 50% @ 74 Micron</p>
	<p>Part Number: P173491 Description: HYDRAULIC CARTRIDGE Primary App: LIEBHERR 7002504 Dimensions: Outer Diameter: 3.94" (100 mm) Inner Diameter: 1.85" (47 mm) Length: 13.74" (349 mm)</p>		<p>Part Number: P173585 Description: HYDRAULIC CARTRIDGE Primary App: VICKERS 378991, 941064 Dimensions: Outer Diameter: 5.50" (140 mm) Inner Diameter: 4.03" (102 mm) Length: 8.63" (219 mm) Efficiency 50% @ 149 Micron</p>
	<p>Part Number: P173521 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: JOHN DEERE RE38965 Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 11.63" (295 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P173596 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 901493, ROSAEN 10-S-20C Dimensions: Outer Diameter: 2.75" (70 mm) Inner Diameter: 1.69" (43 mm) Length: 2.25" (57 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P173573 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HFK08 ASSEMBLY Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 3.41" (87 mm) Length: 18.00" (457 mm) Efficiency 50% @ 44 Micron</p>		<p>Part Number: P173597 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 901494, ROSAEN 10-S-10C Dimensions: Outer Diameter: 2.75" (70 mm) Inner Diameter: 1.69" (43 mm) Length: 2.25" (57 mm) Efficiency 50% @ 10 Micron</p>
<p>Part Number: P173578 Description: HYDRAULIC CARTRIDGE Primary App: KATO TRACKED CRANE Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.69" (43 mm) Length: 4.21" (107 mm)</p>		<p>Part Number: P173613 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 909293, ROSAEN 51/52 CF74W Dimensions: Outer Diameter: 4.25" (108 mm) Inner Diameter: 3.12" (79 mm) Length: 9.50" (241 mm) Efficiency 50% @ 74 Micron</p>	
	<p>Part Number: P173579 Description: HYDRAULIC CARTRIDGE Primary App: VICKERS 361739, 941054 Dimensions: Outer Diameter: 2.44" (62 mm) Inner Diameter: 1.53" (39 mm) Length: 3.69" (94 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 40 Micron</p>		<p>Part Number: P173617 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 908643, ROSAEN 51/52 RF20C Dimensions: Outer Diameter: 4.25" (108 mm) Inner Diameter: 3.12" (79 mm) Length: 9.50" (241 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P173580 Description: HYDRAULIC CARTRIDGE Primary App: VICKERS 361990, 941052 Dimensions: Outer Diameter: 2.44" (62 mm) Inner Diameter: 1.53" (39 mm) Length: 3.69" (94 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P173618 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 908642 Dimensions: Outer Diameter: 4.25" (108 mm) Inner Diameter: 3.12" (79 mm) Length: 9.50" (241 mm) Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P173581 Description: HYDRAULIC CARTRIDGE Primary App: VICKERS 361991, 941056 Dimensions: Outer Diameter: 4.00" (102 mm) Inner Diameter: 2.90" (74 mm) Length: 6.25" (159 mm) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P173618 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 908642 Dimensions: Outer Diameter: 4.25" (108 mm) Inner Diameter: 3.12" (79 mm) Length: 9.50" (241 mm) Efficiency 50% @ 10 Micron</p>



Part Number: P173689
HYDRAULIC SPIN-ON, DURAMAX®
 Description: CASE IH D149921
 Primary App: Outer Diameter: 4.77" (121 mm)
 Dimensions: Thread Size: 1 3/8-12
 Length: 11.63" (295 mm)
 Gasket OD: 2.76" (70 mm)
 Gasket ID: 2.48" (63 mm)
 Efficiency 50% @ 10 Micron



Part Number: P173702
HYDRAULIC SPIN-ON, DURAMAX®
 Description: Ag Chem Equipment 714122
 Primary App: Outer Diameter: 3.13" (80 mm)
 Dimensions: Thread Size: 2-12
 Length: 9.52" (242 mm)
 Gasket OD: 3.13" (80 mm)
 Gasket ID: 1.86" (47 mm)
 Efficiency 50% @ 4 Micron



Part Number: P173736
HYDRAULIC SPIN-ON, DURAMAX®
 Description: SAUER SUNDSTRAND 9700810
 Primary App: Outer Diameter: 3.82" (97 mm)
 Dimensions: Thread Size: 1 3/8-12
 Length: 5.97" (152 mm)
 Gasket OD: 2.82" (72 mm)
 Gasket ID: 2.42" (61 mm)
 Efficiency 50% @ 5 Micron



Part Number: P173737
HYDRAULIC SPIN-ON, DURAMAX®
 Description: SAUER SUNDSTRAND 8700068
 Primary App: Outer Diameter: 3.82" (97 mm)
 Dimensions: Thread Size: 1 3/8-12
 Length: 9.44" (240 mm)
 Gasket OD: 2.76" (70 mm)
 Gasket ID: 2.48" (63 mm)
 Efficiency 50% @ <3 Micron



Part Number: P173738
HYDRAULIC SPIN-ON
 Description: CLARK 2792962, 2782050
 Primary App: Outer Diameter: 3.82" (97 mm)
 Dimensions: Thread Size: 7/8-14
 Length: 5.97" (152 mm)
 Gasket OD: 2.76" (70 mm)
 Gasket ID: 2.48" (63 mm)
 Relief Valve Setting: 50 PSI (3.45 Bar)
 Efficiency 50% @ 7 Micron



Part Number: P173739
HYDRAULIC SPIN-ON, DURAMAX®
 Description: CLARK 2799807
 Primary App: Outer Diameter: 3.82" (97 mm)
 Dimensions: Thread Size: 7/8-14
 Length: 3.93" (100 mm)
 Gasket OD: 2.76" (70 mm)
 Gasket ID: 2.48" (63 mm)
 Relief Valve Setting: 50 PSI (3.45 Bar)
 Efficiency 50% @ 7 Micron



Part Number: P173740
HYDRAULIC CARTRIDGE
 Description: CATERPILLAR 1103024
 Primary App: Outer Diameter: 0.16" (4 mm)
 Dimensions: Inner Diameter: 0.04" (1 mm)
 Length: 0.39" (10 mm)



Part Number: P173760
HYDRAULIC CARTRIDGE
 Description: HYCON 0660R010P
 Primary App: Outer Diameter: 3.76" (96 mm)
 Dimensions: Inner Diameter: 2.70" (69 mm)
 Length: 13.11" (333 mm)
 Relief Valve Setting: 43 PSI (2.96 Bar)
 Efficiency 50% @ 10 Micron



Part Number: P173780
HYDRAULIC CARTRIDGE
 Description: SCHROEDER KM150, JM150
 Primary App: Outer Diameter: 3.53" (90 mm)
 Dimensions: Inner Diameter: 1.62" (41 mm)
 Length: 9.02" (229 mm)
 Efficiency 50% @ 149 Micron



Part Number: P173781
HYDRAULIC CARTRIDGE
 Description: SCHROEDER KM60, JM60
 Primary App: Outer Diameter: 3.53" (90 mm)
 Dimensions: Inner Diameter: 1.62" (41 mm)
 Length: 9.02" (229 mm)
 Efficiency 50% @ 74 Micron



Part Number: P173789
HYDRAULIC SPIN-ON, DURAMAX®
 Description: HMK05/25 ELEMENT, 14.24" L.G., 22 MICRON ABSOLUTE
 Primary App: Outer Diameter: 4.77" (121 mm)
 Dimensions: Thread Size: 1 3/4-12
 Length: 14.24" (362 mm)
 Gasket OD: 3.39" (86 mm)
 Gasket ID: 3.11" (79 mm)



Part Number: P173910
STRAINER
 Description: SEH-8-3/4-100-RV3
 Primary App: Outer Diameter: 2.63" (67 mm)
 Dimensions: Thread Size: 3/4-14
 Length: 3.55" (90 mm)
 Relief Valve Setting: 3 PSI (0.21 Bar)
 Efficiency 50% @ 149 Micron



Part Number: P173911
STRAINER
 Description: SEH-10-1-100-RV3
 Primary App: Outer Diameter: 2.63" (67 mm)
 Dimensions: Thread Size: 1 NPT
 Length: 5.35" (136 mm)
 Relief Valve Setting: 3 PSI (0.21 Bar)
 Efficiency 50% @ 149 Micron



Part Number: P173912
STRAINER
 Description: SEH-20-1.1/4-100-RV3
 Primary App: Outer Diameter: 3.38" (86 mm)
 Dimensions: Thread Size: 1 1/4 NPT
 Length: 6.85" (174 mm)
 Relief Valve Setting: 3 PSI (0.21 Bar)
 Efficiency 50% @ 149 Micron



















Part Number: P173913
STRAINER
 Description: SEH-30-1.1/2-100-RV3
 Primary App: Outer Diameter: 3.38" (86 mm)
 Dimensions: Thread Size: 1 1/2 NPT
 Length: 8.01" (203 mm)
 Relief Valve Setting: 3 PSI (0.21 Bar)
 Efficiency 50% @ 149 Micron



































Part Number: P173914
STRAINER
 Description: SEH-50-1.1/2-100-RV3
 Primary App: Outer Diameter: 3.94" (100 mm)
 Dimensions: Thread Size: 1 1/2 NPT
 Length: 9.85" (250 mm)
 Relief Valve Setting: 3 PSI (0.21 Bar)
 Efficiency 50% @ 149 Micron


























Part Number: P173915
STRAINER
 Description: SEH-50-2-100-RV3
 Primary App: Outer Diameter: 3.94" (100 mm)
 Dimensions: Thread Size: 2 NPT
 Length: 9.85" (250 mm)
 Relief Valve Setting: 3 PSI (0.21 Bar)
 Efficiency 50% @ 149 Micron














	<p>Part Number: P173916 Description: STRAINER Primary App: SEC-75-2.1/2-100-RV3 Dimensions: Outer Diameter: 5.12" (130 mm) Thread Size: 2 1/2 NPT Length: 10.10" (257 mm) Relief Valve Setting: 3 PSI (0.21 Bar) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P174249 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER KKS7 Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.62" (41 mm) Length: 18.25" (464 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P173917 Description: STRAINER Primary App: SEC-100-3-100-RV3 Dimensions: Outer Diameter: 5.12" (130 mm) Thread Size: 3 NPT Length: 11.78" (299 mm) Relief Valve Setting: 3 PSI (0.21 Bar) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P174250 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER KKS7 Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.62" (41 mm) Length: 27.81" (706 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P173943 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK05, HMK25 SERIES Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 11.63" (295 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P174260 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER KKS15 Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.62" (41 mm) Length: 18.25" (464 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P174243 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER KK10 Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.62" (41 mm) Length: 18.25" (464 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P174268 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER KKS15 Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.62" (41 mm) Length: 27.81" (706 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P174244 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER KK25 Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.62" (41 mm) Length: 18.25" (464 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P174290 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG-050-DH Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 1.87" (47 mm) Length: 5.56" (141 mm) Efficiency 50% @ 20 Micron Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P174245 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER KKS1 Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.62" (41 mm) Length: 18.25" (464 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P174292 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG-050-HH Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 1.87" (47 mm) Length: 5.56" (141 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P174247 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER KKS3 Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.62" (41 mm) Length: 18.25" (464 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P174293 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG-050-JH, PG-050-CH Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 1.87" (47 mm) Length: 5.56" (141 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P174248 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER KKS3 Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.62" (41 mm) Length: 27.81" (706 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P174294 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG-080-DH Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 1.87" (47 mm) Length: 10.12" (257 mm) Efficiency 50% @ 20 Micron Efficiency 99% @ 40 Micron</p>






















	<p>Part Number: P174295 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG-080-GH Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 1.87" (47 mm) Length: 10.12" (257 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P174525 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8900FKP16H, HC8900FKP16Z Dimensions: Outer Diameter: 3.75" (95 mm) Inner Diameter: 2.22" (56 mm) Length: 16.68" (424 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P174296 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG-080-HH Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 1.87" (47 mm) Length: 10.12" (257 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P174527 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8800FKN8H Dimensions: Outer Diameter: 3.39" (86 mm) Inner Diameter: 1.96" (50 mm) Length: 8.03" (204 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P174297 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG-080-JH, PG-080-CH Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 1.87" (47 mm) Length: 10.12" (257 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P174531 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8800FKP13H Dimensions: Outer Diameter: 3.39" (86 mm) Inner Diameter: 1.96" (50 mm) Length: 12.76" (324 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P174298 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG-120-DH Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 1.87" (47 mm) Length: 14.62" (371 mm) Efficiency 50% @ 20 Micron Efficiency 99% @ 40 Micron</p>		<p>Part Number: P174533 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8800FKS13H Dimensions: Outer Diameter: 3.39" (86 mm) Inner Diameter: 1.96" (50 mm) Length: 12.76" (324 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P174299 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG-120-GH Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 1.87" (47 mm) Length: 14.62" (371 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P174534 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8800FKT13H Dimensions: Outer Diameter: 3.39" (86 mm) Inner Diameter: 1.96" (50 mm) Length: 12.76" (324 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P174300 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG-120-HH Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 1.87" (47 mm) Length: 14.62" (371 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P174535 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8800FKP16H Dimensions: Outer Diameter: 3.39" (86 mm) Inner Diameter: 1.96" (50 mm) Length: 16.67" (423 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P174301 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG-120-JH, PG-120-CH Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 1.87" (47 mm) Length: 14.62" (371 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P174536 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8800FKS16H Dimensions: Outer Diameter: 3.39" (86 mm) Inner Diameter: 1.96" (50 mm) Length: 16.67" (423 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P174524 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8900FKP13H, HC8900FKP13Z Dimensions: Outer Diameter: 3.75" (95 mm) Inner Diameter: 2.22" (56 mm) Length: 12.76" (324 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P174537 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8800FKT16H Dimensions: Outer Diameter: 3.39" (86 mm) Inner Diameter: 1.96" (50 mm) Length: 16.67" (423 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>

	<p>Part Number: P174538 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8200FKP8H Dimensions: Outer Diameter: 3.38" (86 mm) Inner Diameter: 1.53" (39 mm) Length: 8.03" (204 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P174552 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: NEW HOLLAND 9842392, JOHN DEERE M124541 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 7.88" (200 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.39" (61 mm) Efficiency 50% @ 4 Micron</p>
	<p>Part Number: P174539 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8200FKS8H Dimensions: Outer Diameter: 3.38" (86 mm) Inner Diameter: 1.53" (39 mm) Length: 8.03" (204 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P174565 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXW3-CC3 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 0.32" (8 mm) Length: 5.91" (150 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P174542 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8200FKN13H Dimensions: Outer Diameter: 3.50" (89 mm) Inner Diameter: 1.53" (39 mm) Length: 12.78" (325 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P174566 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXW3D-CC3 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 0.32" (8 mm) Length: 7.87" (200 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P174544 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8200FKT13H Dimensions: Outer Diameter: 3.50" (89 mm) Inner Diameter: 1.53" (39 mm) Length: 12.78" (325 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P174567 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXW3E-CC3 Dimensions: Outer Diameter: 2.82" (72 mm) Inner Diameter: 0.32" (8 mm) Length: 11.80" (300 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P174545 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8200FKP16H Dimensions: Outer Diameter: 3.50" (89 mm) Inner Diameter: 1.53" (39 mm) Length: 16.68" (424 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P174568 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXW4-CC3 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 0.41" (10 mm) Length: 7.48" (190 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P174546 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8200FKN16H Dimensions: Outer Diameter: 3.50" (89 mm) Inner Diameter: 1.53" (39 mm) Length: 16.68" (424 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P174569 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXW5-CC3 Dimensions: Outer Diameter: 4.18" (106 mm) Inner Diameter: 0.41" (10 mm) Length: 10.29" (261 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P174547 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8200FKS16H Dimensions: Outer Diameter: 3.50" (89 mm) Inner Diameter: 1.53" (39 mm) Length: 16.68" (424 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P174570 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXW5A-CC3 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 0.41" (10 mm) Length: 18.31" (465 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P174548 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC8200FKT16H Dimensions: Outer Diameter: 3.50" (89 mm) Inner Diameter: 1.53" (39 mm) Length: 16.68" (424 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>		<p>Part Number: P174572 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXW8A-CC3 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 0.41" (10 mm) Length: 11.42" (290 mm) Efficiency 99% @ 3 Micron</p>

	<p>Part Number: P174573 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXW8C-CC3 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 0.41" (10 mm) Length: 18.90" (480 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P174790 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC6400FKN8H Dimensions: Outer Diameter: 3.39" (86 mm) Inner Diameter: 1.74" (44 mm) Length: 8.06" (205 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P174610 Description: HYDRAULIC CARTRIDGE Primary App: ZINGA RE-409-10 Dimensions: Outer Diameter: 3.94" (100 mm) Inner Diameter: 1.95" (50 mm) Length: 9.11" (231 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P174791 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC6400FKN13H Dimensions: Outer Diameter: 3.39" (86 mm) Inner Diameter: 1.74" (44 mm) Length: 12.86" (327 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P174611 Description: HYDRAULIC CARTRIDGE Primary App: ZINGA RE-409-25 Dimensions: Outer Diameter: 3.94" (100 mm) Inner Diameter: 1.95" (50 mm) Length: 9.11" (231 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P174792 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC6400FKN16H Dimensions: Outer Diameter: 3.39" (86 mm) Inner Diameter: 1.74" (44 mm) Length: 16.86" (428 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P174622 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER KS1V Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.62" (41 mm) Length: 9.02" (229 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P174793 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC6400FKN26H Dimensions: Outer Diameter: 3.39" (86 mm) Inner Diameter: 1.74" (44 mm) Length: 25.66" (652 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P174623 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER KS3V Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.62" (41 mm) Length: 9.02" (229 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>		<p>Part Number: P174914 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 932410, IL2 STYLE Dimensions: Outer Diameter: 3.68" (93 mm) Inner Diameter: 1.74" (44 mm) Length: 18.78" (477 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P174624 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER KS7V Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.62" (41 mm) Length: 9.02" (229 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 16 Micron</p>		<p>Part Number: P174915 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 932409, IL2 STYLE HOUSING Dimensions: Outer Diameter: 3.68" (93 mm) Inner Diameter: 1.74" (44 mm) Length: 9.09" (231 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P174675 Description: HYDRAULIC SPIN-ON Primary App: CLARK 4202525 Dimensions: Outer Diameter: 3.71" (94 mm) Thread Size: 2-16 Length: 5.97" (152 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Relief Valve Setting: 30-50 PSI (2.10-3.50 Bar) Efficiency 50% @ 7 Micron</p>	<p>Shape  Cross Section </p>	<p>Part Number: P174997 Description: GASKET, LIQUID FILTER Primary App: OPTIONAL GASKET USED WITH P555603 Dimensions: Outlet Diameter: 5.50" (140 mm) Inlet Diameter: 5.20" (132 mm) Cross Section: 0.13" (3 mm)</p>
	<p>Part Number: P174749 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 924455 Dimensions: Outer Diameter: 3.68" (93 mm) Inner Diameter: 1.75" (44 mm) Length: 9.00" (229 mm) Efficiency 50% @ 44 Micron</p>		<p>Part Number: P175101 Description: HYDRAULIC CARTRIDGE Primary App: ARGO P3051011 Dimensions: Outer Diameter: 1.81" (46 mm) Inner Diameter: 0.80" (20 mm) Length: 4.05" (103 mm) Efficiency 50% @ 25 Micron</p>
			<p>Part Number: P175104 Description: HYDRAULIC CARTRIDGE Primary App: ARGO P3052062 Dimensions: Outer Diameter: 1.81" (46 mm) Inner Diameter: 0.80" (20 mm) Length: 7.87" (200 mm) Efficiency 50% @ 10 Micron</p>

	<p>Part Number: P175108 Description: HYDRAULIC CARTRIDGE Primary App: ARGO P3062052 Dimensions: Outer Diameter: 2.36" (60 mm) Inner Diameter: 1.12" (28 mm) Length: 7.91" (201 mm) Efficiency 50% @ 25 Micron</p>	<p>Part Number: P175334 Description: STRAINER Primary App: FIOA 50/250 Dimensions: Outer Diameter: 2.95" (75 mm) Thread Size: 3/4 NPT Length: 3.27" (83 mm) Overall Length: 3.74" (95 mm)</p>
	<p>Part Number: P175111 Description: HYDRAULIC CARTRIDGE Primary App: ARGO P2072301 Dimensions: Outer Diameter: 2.52" (64 mm) Inner Diameter: 1.10" (28 mm) Length: 8.98" (228 mm) Efficiency 50% @ 10 Micron</p>	<p>Part Number: P175335 Description: STRAINER Primary App: FIOA 85/250 Dimensions: Outer Diameter: 3.74" (95 mm) Thread Size: 1 NPT Length: 3.27" (83 mm) Overall Length: 3.74" (95 mm)</p>
	<p>Part Number: P175112 Description: HYDRAULIC CARTRIDGE Primary App: ARGO V3072308 Dimensions: Outer Diameter: 2.52" (64 mm) Inner Diameter: 1.16" (29 mm) Length: 9.09" (231 mm)</p>	<p>Part Number: P175336 Description: STRAINER Primary App: FIOA 90/250 Dimensions: Outer Diameter: 2.95" (75 mm) Thread Size: 1 NPT Length: 5.16" (131 mm) Overall Length: 5.55" (141 mm)</p>
	<p>Part Number: P175115 Description: HYDRAULIC CARTRIDGE Primary App: ARGO P2092022 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 1.69" (43 mm) Length: 7.67" (195 mm) Efficiency 50% @ 10 Micron</p>	<p>Part Number: P175337 Description: STRAINER Primary App: FIOA 130/250 Dimensions: Outer Diameter: 3.74" (95 mm) Thread Size: 1 1/4 NPT Length: 6.77" (172 mm) Overall Length: 10.98" (279 mm)</p>
	<p>Part Number: P175120 Description: HYDRAULIC CARTRIDGE Primary App: ARGO V2121708 Dimensions: Outer Diameter: 4.61" (117 mm) Inner Diameter: 3.34" (85 mm) Length: 6.41" (163 mm) Efficiency 99% @ 25 Micron</p>	<p>Part Number: P175338 Description: HYDRAULIC CARTRIDGE Primary App: DMIC, DSL-1500N Dimensions: Outer Diameter: 3.74" (95 mm) Thread Size: 1-1/2NPT Length: 7.99" (203 mm)</p>
<p>Part Number: P175142 Description: STRAINER Primary App: FAL, JOHN DEERE AZ61599 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.10" (28 mm) Length: 5.75" (146 mm)</p>	<p>Part Number: P175339 Description: STRAINER Primary App: FIOA 2" NPT Dimensions: Outer Diameter: 5.51" (140 mm) Thread Size: 2 NPT Length: 8.07" (205 mm) Overall Length: 8.66" (220 mm)</p>	
<p>Part Number: P175143 Description: HYDRAULIC CARTRIDGE Primary App: FAL, RENAULT VI 6005007631 Dimensions: Outer Diameter: 2.72" (69 mm) Inner Diameter: 1.50" (38 mm) Length: 5.71" (145 mm)</p>	<p>Part Number: P175340 Description: STRAINER Primary App: FIOA 175/250 Dimensions: Outer Diameter: 3.39" (86 mm) Thread Size: 1 1/2 NPT Length: 5.12" (130 mm) Overall Length: 5.59" (142 mm)</p>	
<p>Part Number: P175181 Description: HYDRAULIC INLINE Primary App: FAL RENAULT 7700032634 Dimensions: Outer Diameter: 2.71" (69 mm) Inlet Size: 1.53 Overall Length: 5.74" (146 mm) Outlet Size: 1.57 (40) Efficiency 50% @ 160 Micron</p>	<p>Part Number: P175342 Description: STRAINER Primary App: FIOA 600/250 Dimensions: Outer Diameter: 5.51" (140 mm) Thread Size: 2 1/2 NPT Length: 11.85" (301 mm) Overall Length: 12.44" (316 mm)</p>	
<p>Part Number: P175238 Description: HYDRAULIC CARTRIDGE Primary App: CR100/02 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.65" (42 mm) Length: 5.08" (129 mm)</p>	<p>Part Number: P175343 Description: STRAINER Primary App: FIOA 3"NPT Dimensions: Outer Diameter: 5.51" (140 mm) Thread Size: 3 NPT Length: 11.85" (301 mm) Overall Length: 12.48" (317 mm)</p>	
<p>Part Number: P175238 Description: HYDRAULIC CARTRIDGE Primary App: CR100/02 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.65" (42 mm) Length: 5.08" (129 mm)</p>	<p>Part Number: P175357 Description: HYDRAULIC CARTRIDGE Primary App: FIAT 21800444 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 7.99" (203 mm)</p>	

<p>Part Number: P175466 Description: STRAINER Primary App: Case Loaders 570, 580, 590 series Dimensions: Outer Diameter: 5.51" (140 mm) Thread Size: G2 Length: 8.66" (220 mm)</p>	 <p>Part Number: P176220 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HAK05 ASSY Dimensions: Outer Diameter: 4.39" (112 mm) Inner Diameter: 2.44" (62 mm) Length: 8.00" (203 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
<p>Part Number: P175485 Description: HYDRAULIC CARTRIDGE Primary App: CATERPILLAR 1487159 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.50" (38 mm) Length: 5.32" (135 mm)</p>	 <p>Part Number: P176221 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HAK05, HDK06 ASSY Dimensions: Outer Diameter: 4.39" (112 mm) Inner Diameter: 2.44" (62 mm) Length: 16.00" (406 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
 <p>Part Number: P176107 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK03 ASSY'S Dimensions: Outer Diameter: 3.11" (79 mm) Thread Size: 2-12 Length: 9.52" (242 mm) Gasket OD: 3.13" (80 mm) Gasket ID: 1.86" (47 mm) Efficiency 50% @ 2 Micron</p>	 <p>Part Number: P176222 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HFK08 ASSY Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 3.41" (87 mm) Length: 18.00" (457 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
 <p>Part Number: P176202 Description: HYDRAULIC CARTRIDGE Primary App: HILCO PL718 Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 3.19" (81 mm) Length: 18.00" (457 mm) Efficiency 99% @ 3 Micron</p>	 <p>Part Number: P176223 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HEK11 ASSY Dimensions: Outer Diameter: 7.44" (189 mm) Inner Diameter: 4.86" (123 mm) Length: 22.00" (559 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
 <p>Part Number: P176203 Description: HYDRAULIC CARTRIDGE Primary App: HILCO PL718 Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 3.19" (81 mm) Length: 18.00" (457 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>	 <p>Part Number: P176324 Description: HYDRAULIC SPIN-ON Primary App: SULLAIR 250025525 Dimensions: Outer Diameter: 4.63" (118 mm) Thread Size: 1 1/4 BSP Length: 6.27" (159 mm) Gasket OD: 4.33" (110 mm) Gasket ID: 3.85" (98 mm) Efficiency 99% @ 25 Micron</p>
 <p>Part Number: P176204 Description: HYDRAULIC CARTRIDGE Primary App: HILCO PL718 Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 3.19" (81 mm) Length: 18.00" (457 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 16 Micron</p>	 <p>Part Number: P176325 Description: HYDRAULIC SPIN-ON Primary App: SULLAIR 250025526 Dimensions: Outer Diameter: 4.63" (118 mm) Thread Size: 1 1/4 BSP Length: 11.27" (286 mm) Gasket OD: 4.33" (110 mm) Gasket ID: 3.85" (98 mm) Efficiency 99% @ 25 Micron</p>
 <p>Part Number: P176205 Description: HYDRAULIC CARTRIDGE Primary App: HILCO PL718 Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 3.19" (81 mm) Length: 18.00" (457 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 22 Micron</p>	 <p>Part Number: P176417 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON HEK11 FILTER ASSY'S, # 2 MEDIA Dimensions: Outer Diameter: 7.44" (189 mm) Inner Diameter: 4.85" (123 mm) Length: 22.00" (559 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 5 Micron</p>
 <p>Part Number: P176207 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: NEW HOLLAND 9706161 Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 7.60" (193 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm) Efficiency 50% @ 4 Micron</p>	 <p>Part Number: P176565 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK04 ASSY'S Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 5.97" (152 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 2 Micron</p>
 <p>Part Number: P176208 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CAT 9T-6636 Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 7.60" (193 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm) Efficiency 50% @ 10 Micron</p>	

	<p>Part Number: P176566 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK04 ASSY'S Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 2 Micron</p>		<p>Part Number: P177001 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0110D020BNHC Dimensions: Outer Diameter: 1.85" (47 mm) Inner Diameter: 0.87" (22 mm) Length: 6.02" (153 mm) Efficiency 99% @ 20 Micron</p>
	<p>Part Number: P176567 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK05, HMK25 ASSY'S Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 11.63" (295 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm) Efficiency 50% @ 2 Micron</p>		<p>Part Number: P177002 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0240D020BNHC Dimensions: Outer Diameter: 2.72" (69 mm) Inner Diameter: 1.34" (34 mm) Length: 6.81" (173 mm) Efficiency 99% @ 20 Micron</p>
	<p>Part Number: P176635 Description: HYDRAULIC CARTRIDGE Primary App: AP556.52 Dimensions: Length: 14.96" (380 mm) Outer Diameter: 3.07" (78 mm) Inner Diameter: 1.58" (40 mm)</p>		<p>Part Number: P177003 Description: HYDRAULIC CARTRIDGE Primary App: HYCON 0330D020BNHC Dimensions: Outer Diameter: 3.56" (90 mm) Inner Diameter: 1.89" (48 mm) Length: 6.42" (163 mm) Efficiency 99% @ 20 Micron</p>
	<p>Part Number: P176779 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: FIAT 85802793 Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 11.62" (295 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm)</p>		<p>Part Number: P177040 Description: HYDRAULIC CARTRIDGE KIT Primary App: Marathon 417-2125 Dimensions: Efficiency 50% @ 2 Micron</p>
	<p>Part Number: P176792 Description: HYDRAULIC CARTRIDGE Dimensions: Inner Diameter: 1.22" (31 mm) Outer Diameter: 3.86" (86 mm) Length: 7.01" (178 mm)</p>		<p>Part Number: P177047 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: JOHN DEERE T175002 Dimensions: Outer Diameter: 3.71" (94 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 4 Micron</p>
	<p>Part Number: P176892 Description: HYDRAULIC CARTRIDGE Primary App: HITACHI 1930877 Dimensions: Outer Diameter: 5.51" (140 mm) Length: 15.75" (400 mm)</p>		<p>Part Number: P177293 Description: HYDRAULIC CARTRIDGE Primary App: CASE 79106101 Dimensions: Outer Diameter: 3.98" (101 mm) Thread Size: 1 NPT Length: 9.92" (252 mm)</p>
	<p>Part Number: P176903 Description: STRAINER Primary App: FAL Dimensions: Outer Diameter: 2.91" (74 mm) Inlet Diameter: 0.71" (18 mm) Length: 3.94" (100 mm) Overall Length: 5.75" (146 mm)</p>		<p>Part Number: P177345 Description: LUBE SPIN-ON FULL FLOW Primary App: Komatsu Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-16 Length: 5.35" (136 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm)</p>
	<p>Part Number: P176904 Description: STRAINER Primary App: FAL Dimensions: Outer Diameter: 3.15" (80 mm) Inlet Diameter: 2.01" (51 mm) Length: 7.01" (178 mm)</p>		<p>Part Number: P177349 Description: LUBE SPIN-ON FULL FLOW Primary App: CUMMINS 4B & 6B SERIES LUBE Dimensions: Outer Diameter: 3.66" (923 mm) Length: 6.85" (174 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm)</p>
	<p>Part Number: P176906 Description: HYDRAULIC CARTRIDGE Primary App: CLC1 Dimensions: Inner Diameter: 0.32" (8 mm) Outer Diameter: 0.41" (11 mm) Length: 0.87" (22 mm)</p>		<p>Part Number: P177402 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 848001062 Dimensions: Outer Diameter: 2.95" (75 mm) Thread Size: G2 Length: 7.09" (180 mm)</p>
	<p>Part Number: P176947 Description: HYDRAULIC CARTRIDGE Primary App: AP472 Dimensions: Outer Diameter: 1.97" (50 mm) Inner Diameter: 0.94" (24 mm) Length: 4.45" (113 mm)</p>		<p>Part Number: P177424 Description: HYDRAULIC CARTRIDGE Primary App: CALABRESE EUROTEC 102261 Dimensions: Outer Diameter: 4.45" (113 mm) Length: 7.91" (201 mm)</p>
	<p>Part Number: P176950 Description: HYDRAULIC CARTRIDGE Dimensions: Outer Diameter: 3.54" (90 mm) Inner Diameter: 1.16" (30 mm) Length: 7.05" (179 mm)</p>		

<p>Part Number: P177577 Description: HYDRAULIC CARTRIDGE Primary App: CASE 79091691 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 9.84" (250 mm)</p>	 <p>Part Number: P179518 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CAT 108-1153, MELROE 6670207, N-HOLLAND 9821388 Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 11.63" (295 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm) Efficiency 50% @ 4 Micron</p>
<p>Part Number: P177655 Description: HYDRAULIC CARTRIDGE Primary App: NEW HOLLAND 1930878 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.14" (29 mm) Length: 6.65" (169 mm)</p>	 <p>Part Number: P179763 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK05, HMK25 Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 12.64" (321 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm)</p>
<p>Part Number: P177661 Description: HYDRAULIC CARTRIDGE Primary App: NEW HOLLAND 1930874 Dimensions: Outer Diameter: 4.41" (112 mm) Inner Diameter: 1.42" (36 mm) Length: 7.32" (186 mm)</p>	 <p>Part Number: P181000 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FWA14 OR FWG14 CYCLOPAC A/C Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.73" (171 mm) Length: 12.00" (305 mm) Gasket ID: 9.56" (243 mm) Minor OD: 0.53" (13 mm)</p>
 <p>Part Number: P178619 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: JOHN DEERE RE55801 Dimensions: Outer Diameter: 3.71" (94 mm) Thread Size: 1 3/8-12 Length: 4.47" (114 mm) Gasket OD: 2.82" (72 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 20 Micron</p>	 <p>Part Number: P181001 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FWA16 OR FWG16 CYCLOPAC A/C Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 14.00" (356 mm) Gasket ID: 10.12" (257 mm) Minor OD: 0.53" (13 mm)</p>
 <p>Part Number: P178729 Description: HYDRAULIC CARTRIDGE Primary App: HILCO Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 2.60" (66 mm) Length: 18.00" (457 mm) Gasket ID: 2.65" (67 mm)</p>	 <p>Part Number: P181002 Description: AIR PRIMARY Primary App: DONALDSON FHG16 CYCLOPAC A/C Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 18.00" (457 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 10.12" (257 mm)</p>
 <p>Part Number: P179075 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: HMK05/HMK25 SPIN-ON, WATER REMOVAL Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 11.63" (295 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm)</p>	 <p>Part Number: P181003 Description: AIR PRIMARY Primary App: DONALDSON EBA11 A/C, MACK, PACCAR Dimensions: Outer Diameter: 8.84" (225 mm) Inner Diameter: 5.48" (139 mm) Length: 22.00" (559 mm) Gasket OD: 7.76" (197 mm) Gasket ID: 7.00" (178 mm)</p>
 <p>Part Number: P179089 Description: HYDRAULIC SPIN-ON Primary App: DONALDSON LPS04 SPIN-ON Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 7.87" (200 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 50% @ 2 Micron</p>	 <p>Part Number: P181004 Description: AIR PRIMARY Primary App: DONALDSON EBA15 A/C, COMBUSTION AIR MACK 57MD31 Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 14.00" (356 mm) Gasket ID: 10.12" (257 mm)</p>
 <p>Part Number: P179342 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CASE IH 254686A1 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 13/16-16 Length: 5.97" (152 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Relief Valve Setting: 50 PSI (3.45 Bar) Efficiency 50% @ 7 Micron</p>	 <p>Part Number: P181005 Description: AIR PRIMARY Primary App: DONALDSON EBA15 A/C, COOLING AIR MACK 57MD21 Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 8.00" (203 mm) Gasket ID: 10.70" (272 mm)</p>
 <p>Part Number: P179343 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: CATERPILLAR 6E6408, NEW HOLLAND 86018758 Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/8-12 Length: 11.63" (295 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm)</p>	 <p>Part Number: P181007 Description: AIR PRIMARY Primary App: DONALDSON EBA13 A/C, STANDARD Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 21.82" (554 mm) Gasket ID: 8.12" (206 mm)</p>

















	<p>Part Number: P181008 Description: AIR PRIMARY Primary App: DONALDSON EBA15 AIR CLEANER Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 22.00" (559 mm) Gasket ID: 10.12" (257 mm)</p>		<p>Part Number: P181017 Description: AIR PRIMARY Primary App: DONALDSON EBA11 A/C Dimensions: Outer Diameter: 8.84" (225 mm) Inner Diameter: 5.48" (139 mm) Length: 28.00" (711 mm) Gasket ID: 7.00" (178 mm)</p>
	<p>Part Number: P181009 Description: AIR PRIMARY Primary App: DONALDSON EBA15 A/C Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 26.00" (660 mm) Gasket ID: 10.12" (257 mm)</p>		<p>Part Number: P181018 Description: AIR PRIMARY Primary App: DONALDSON EBB14 A/C, FORD D5HZ9601A Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 16.00" (406 mm) Gasket ID: 8.12" (206 mm)</p>
	<p>Part Number: P181010 Description: AIR PRIMARY Primary App: GMC PACCAR W/DONALDSON FWG16 A/C Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 14.00" (356 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket OD: 9.76" (247 mm) Gasket ID: 9.00" (228 mm)</p>		<p>Part Number: P181019 Description: AIR PRIMARY Primary App: DONALDSON EBB12 A/C, IHC 478974C1 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 11.90" (302 mm) Gasket OD: 8.88" (226 mm) Gasket ID: 8.12" (206 mm)</p>
	<p>Part Number: P181011 Description: AIR PRIMARY Primary App: DONALDSON EBA16 AIR CLEANER Dimensions: Outer Diameter: 13.84" (352 mm) Inner Diameter: 9.48" (241 mm) Length: 26.00" (660 mm) Gasket ID: 10.70" (272 mm)</p>		<p>Part Number: P181021 Description: AIR PRIMARY Primary App: DONALDSON EBB12 A/C, GMC 2009007 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 10.00" (254 mm) Bolt Hole Diameter: 0.62" (16 mm) Gasket OD: 8.88" (226 mm) Gasket ID: 8.12" (206 mm)</p>
	<p>Part Number: P181012 Description: AIR PRIMARY Primary App: DONALDSON EBA16 A/C-STANDARD, GMC Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 19.00" (483 mm) Gasket ID: 10.70" (272 mm)</p>		<p>Part Number: P181023 Description: AIR PRIMARY, FINNED Primary App: FORD D0HZ9601A MOTORCRAFT FA573 Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.73" (171 mm) Length: 16.00" (406 mm) Gasket ID: 9.56" (243 mm) Minor OD: 0.66" (17 mm)</p>
	<p>Part Number: P181013 Description: AIR PRIMARY, FINNED Primary App: FORD D0HZ9601F MOTORCRAFT F186 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.72" (196 mm) Length: 10.00" (254 mm) Gasket ID: 10.12" (257 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P181024 Description: AIR PRIMARY, FINNED Primary App: MOTORCRAFT FA560, CAT 2N1990 Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.85" (123 mm) Length: 8.00" (203 mm) Gasket OD: 6.72" (171 mm) Gasket ID: 5.42" (138 mm) Minor OD: 0.66" (17 mm)</p>
	<p>Part Number: P181014 Description: AIR PRIMARY Primary App: DONALDSON EBA13 A/C, FORD D5HZ9601D Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 15.00" (381 mm) Gasket OD: 8.88" (226 mm) Gasket ID: 8.12" (206 mm)</p>		<p>Part Number: P181025 Description: AIR PRIMARY Primary App: DONALDSON EBA15 A/C, MACK 57MD29301 Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 14.00" (356 mm)</p>
	<p>Part Number: P181015 Description: AIR PRIMARY Primary App: DONALDSON EBB14 OR EGB14 A/C, IHC 476743C1 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 18.00" (457 mm) Gasket ID: 9.70" (246 mm)</p>		<p>Part Number: P181028 Description: AIR PRIMARY Primary App: DONALDSON EBB12 OR EGB12 A/C, IHC 476741C1 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 16.00" (406 mm) Gasket OD: 8.88" (226 mm) Gasket ID: 8.12" (206 mm)</p>
	<p>Part Number: P181016 Description: AIR PRIMARY Primary App: DONALDSON EBA13 A/C, WHITE, FREIGHTLINER Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 26.00" (660 mm) Gasket ID: 8.12" (206 mm)</p>		

	<p>Part Number: P181030 Description: AIR PRIMARY Primary App: DONALDSON EBB14, 8.2L NAT& 8.2L TURBO, FORD, GM Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 7.00" (178 mm) Gasket ID: 9.88" (251 mm)</p>		<p>Part Number: P181039 Description: AIR PRIMARY Primary App: DONALDSON STG16 DONACLONE A/C Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 18.00" (457 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 9.88" (251 mm)</p>
	<p>Part Number: P181031 Description: AIR PRIMARY Primary App: DONALDSON SBG16 DONACLONE A/C Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 14.00" (356 mm) Bolt Hole Diameter: 0.53" (13 mm)</p>		<p>Part Number: P181040 Description: AIR PRIMARY Primary App: DONALDSON SRG20/29 Donaclone w/10" DIA. Outlets Dimensions: Outer Diameter: 17.58" (447 mm) Inner Diameter: 12.22" (310 mm) Length: 23.03" (585 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 14.00" (356 mm)</p>
	<p>Part Number: P181032 Description: AIR PRIMARY Primary App: DONALDSON SBG14 DONACLONE A/C Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 10.00" (254 mm) Bolt Hole Diameter: 0.53" (13 mm)</p>		<p>Part Number: P181041 Description: AIR PRIMARY Primary App: DONALDSON STG14 DONACLONE A/C Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 8.12" (206 mm)</p>
	<p>Part Number: P181033 Description: AIR PRIMARY Primary App: DONALDSON SBG12 DONACLONE Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.96" (177 mm) Length: 9.00" (229 mm) Bolt Hole Diameter: 0.53" (13 mm)</p>		<p>Part Number: P181042 Description: AIR PRIMARY Primary App: DONALDSON STG16 DONACLONE Dimensions: Outer Diameter: 14.68" (373 mm) Inner Diameter: 10.34" (263 mm) Length: 24.02" (610 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 11.00" (279 mm)</p>
	<p>Part Number: P181034 Description: AIR PRIMARY Primary App: DONALDSON FHG12 CYCLOPAC A/C Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.85" (123 mm) Length: 13.00" (330 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 7.62" (194 mm)</p>		<p>Part Number: P181043 Description: AIR PRIMARY Primary App: DONALDSON FVG14 CYCLOFLOW A/C Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 20.00" (508 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 8.12" (206 mm)</p>
	<p>Part Number: P181035 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FWA12 OR FWG12 CYCLOPAC A/C Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.85" (123 mm) Length: 10.00" (254 mm) Gasket ID: 7.62" (194 mm) Minor OD: 0.53" (13 mm)</p>		<p>Part Number: P181044 Description: AIR PRIMARY Primary App: DONALDSON STG12 DONACLONE A/C Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 14.00" (356 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 6.38" (162 mm)</p>
	<p>Part Number: P181036 Description: AIR PRIMARY Primary App: DONALDSON SBG16 DONACLONE, CAT 6L-3313 Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.53" (13 mm)</p>		<p>Part Number: P181045 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FWA10 OR FWG10 CYCLOPAC A/C Dimensions: Outer Diameter: 7.93" (201 mm) Inner Diameter: 4.57" (116 mm) Length: 10.00" (254 mm) Gasket ID: 6.38" (162 mm) Minor OD: 0.53" (13 mm)</p>
	<p>Part Number: P181037 Description: AIR PRIMARY Primary App: DONALDSON SBG14 DONACLONE Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 13.00" (330 mm) Bolt Hole Diameter: 0.53" (13 mm)</p>		<p>Part Number: P181046 Description: AIR PRIMARY Primary App: DONALDSON FHG14 CYCLOPAC A/C Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.73" (171 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 9.56" (243 mm)</p>
	<p>Part Number: P181038 Description: AIR PRIMARY Primary App: DONALDSON SRG20/29 DONACLONE W/8" DIA. OUTLETS Dimensions: Outer Diameter: 17.58" (447 mm) Inner Diameter: 11.07" (281 mm) Length: 23.06" (586 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 14.00" (356 mm)</p>		<p>Part Number: P181047 Description: AIR PRIMARY Primary App: DONALDSON FVG16 A/C, TEREX 9059569 Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 22.03" (560 mm) Bolt Hole Diameter: 0.94" (24 mm) Gasket ID: 9.88" (251 mm)</p>

	<p>Part Number: P181048 Description: AIR PRIMARY Primary App: DONALDSON SRG20 A/C, TEREX 9059570 Dimensions: Outer Diameter: 17.58" (447 mm) Inner Diameter: 12.22" (310 mm) Length: 19.03" (483 mm) Bolt Hole Diameter: 0.42" (11 mm) Gasket ID: 14.00" (356 mm)</p>		<p>Part Number: P181057 Description: AIR PRIMARY Primary App: DONALDSON FWD16 OR FVG16, WHITE, FREIGHTLINER Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 17.03" (433 mm) Bolt Hole Diameter: 0.94" (24 mm) Gasket ID: 9.88" (251 mm)</p>
	<p>Part Number: P181049 Description: AIR PRIMARY Primary App: DONALDSON FVG16 CYCLOFLOW A/C Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 24.03" (610 mm) Bolt Hole Diameter: 0.94" (24 mm) Gasket ID: 9.88" (251 mm)</p>		<p>Part Number: P181058 Description: AIR PRIMARY Primary App: DONALDSON EBA16 A/C, PACCAR Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 23.00" (584 mm) Gasket ID: 10.70" (272 mm)</p>
	<p>Part Number: P181050 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FWA05 OR FWG05 CYCLOPAC Dimensions: Outer Diameter: 4.08" (104 mm) Inner Diameter: 2.49" (63 mm) Length: 10.00" (254 mm) Gasket ID: 2.58" (65 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P181059 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FHG08 CYCLOPAC A/C Dimensions: Outer Diameter: 6.08" (154 mm) Inner Diameter: 3.49" (89 mm) Length: 15.00" (381 mm) Gasket ID: 4.45" (113 mm) Minor OD: 0.66" (17 mm)</p>
	<p>Part Number: P181052 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FWA06 OR FWG06 CYCLOPAC Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 2.64" (67 mm) Length: 11.00" (279 mm) Gasket ID: 3.95" (100 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P181060 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FWD16 A/C, WHITE, FREIGHTLINER Dimensions: Outer Diameter: 13.84" (352 mm) Inner Diameter: 7.48" (190 mm) Length: 12.00" (305 mm)</p>
	<p>Part Number: P181053 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FWD16 CYCLOPAC, DETROIT DIESEL Dimensions: Outer Diameter: 13.84" (352 mm) Inner Diameter: 9.47" (241 mm) Length: 18.00" (457 mm) Gasket ID: 10.70" (272 mm)</p>		<p>Part Number: P181061 Description: AIR PRIMARY Primary App: DONALDSON EBA16 A/C, GMC 717714 Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 25.00" (635 mm) Gasket ID: 10.70" (272 mm)</p>
	<p>Part Number: P181054 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FWA08 OR FWG08 CYCLOPAC Dimensions: Outer Diameter: 6.08" (154 mm) Inner Diameter: 3.49" (89 mm) Length: 12.00" (305 mm) Gasket ID: 4.45" (113 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P181062 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FHG06 CYCLOPAC A/C Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 3.26" (83 mm) Length: 15.00" (381 mm) Gasket ID: 3.95" (100 mm) Minor OD: 0.66" (17 mm)</p>
	<p>Part Number: P181055 Description: AIR PRIMARY Primary App: DONALDSON FVG16 A/C, WHITE, FREIGHTLINER Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 19.06" (484 mm) Gasket ID: 9.88" (251 mm)</p>		<p>Part Number: P181063 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FHG09 CYCLOPAC A/C Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 5.32" (135 mm) Length: 16.00" (406 mm) Gasket ID: 5.42" (138 mm) Minor OD: 0.66" (17 mm)</p>
	<p>Part Number: P181056 Description: AIR PRIMARY Primary App: DONALDSON EBB A/C, FRAM, IHC, WHITE Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.72" (196 mm) Length: 15.19" (386 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 9.56" (243 mm)</p>		<p>Part Number: P181064 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FHG10 CYCLOPAC Dimensions: Outer Diameter: 7.93" (201 mm) Inner Diameter: 5.32" (135 mm) Length: 16.00" (406 mm) Gasket ID: 6.36" (162 mm) Minor OD: 0.66" (17 mm)</p>
	<p>Part Number: P181065 Description: AIR PRIMARY Primary App: DONALDSON EAD16 A/C, CUMMINS Dimensions: Outer Diameter: 13.84" (352 mm) Inner Diameter: 7.48" (190 mm) Length: 18.02" (458 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket OD: 8.88" (226 mm) Gasket ID: 8.12" (206 mm)</p>		

	<p>Part Number: P181066 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FWA16 A/C, PACCAR Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 14.00" (356 mm) Gasket ID: 10.12" (257 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P181077 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FHG14 A/C, JOY, COLT Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.73" (171 mm) Length: 15.00" (381 mm) Gasket ID: 9.56" (243 mm) Minor OD: 0.66" (17 mm)</p>
	<p>Part Number: P181068 Description: AIR PRIMARY Primary App: DONALDSON SBG08 DONACLONE A/C Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 4.24" (108 mm) Length: 9.00" (229 mm)</p>		<p>Part Number: P181078 Description: AIR PRIMARY Primary App: DONALDSON FVG14 CYCLOFLOW A/C Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 23.00" (584 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket OD: 8.88" (226 mm) Gasket ID: 8.12" (206 mm)</p>
	<p>Part Number: P181070 Description: AIR PRIMARY Primary App: DONALDSON FTG11 CYCLOPAC A/C Dimensions: Outer Diameter: 9.14" (232 mm) Inner Diameter: 5.78" (147 mm) Length: 18.00" (457 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket OD: 7.00" (178 mm) Gasket ID: 6.25" (159 mm)</p>		<p>Part Number: P181079 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FHG16 A/C, JOY, COLT Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 18.00" (457 mm) Gasket ID: 10.12" (257 mm) Minor OD: 0.66" (17 mm)</p>
	<p>Part Number: P181071 Description: AIR PRIMARY Primary App: DONALDSON SBG10 DONACLONE A/C Dimensions: Outer Diameter: 8.40" (213 mm) Inner Diameter: 5.79" (147 mm) Length: 11.00" (279 mm) Bolt Hole Diameter: 0.53" (13 mm)</p>		<p>Part Number: P181080 Description: AIR PRIMARY Primary App: DONALDSON FTG11 CYCLOPAC, NISSAN 16546-Z9004 Dimensions: Outer Diameter: 9.14" (232 mm) Inner Diameter: 5.78" (147 mm) Length: 13.00" (330 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket OD: 7.00" (178 mm) Gasket ID: 6.25" (159 mm)</p>
	<p>Part Number: P181072 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FHG05 CYCLOPAC A/C Dimensions: Outer Diameter: 4.08" (104 mm) Inner Diameter: 2.49" (63 mm) Length: 14.00" (356 mm) Gasket ID: 2.58" (65 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P181082 Description: AIR PRIMARY Primary App: DONALDSON FTG13 CYCLOPAC A/C Dimensions: Outer Diameter: 10.86" (276 mm) Inner Diameter: 6.50" (165 mm) Length: 20.00" (508 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 7.62" (194 mm)</p>
	<p>Part Number: P181073 Description: AIR PRIMARY Primary App: DONALDSON FTG15 CYCLOPAC A/C Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 19.00" (483 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 8.12" (206 mm)</p>		<p>Part Number: P181084 Description: AIR PRIMARY Primary App: DONALDSON EAD11 A/C, MACK 57MD31 Dimensions: Outer Diameter: 8.84" (225 mm) Inner Diameter: 5.48" (139 mm) Length: 7.00" (178 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket OD: 7.76" (194 mm) Gasket ID: 7.00" (178 mm)</p>
	<p>Part Number: P181074 Description: AIR PRIMARY Primary App: DONALDSON EBA13 A/C, MACK 57MD29305 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.96" (177 mm) Length: 11.00" (279 mm) Gasket OD: 8.88" (226 mm) Gasket ID: 8.12" (206 mm)</p>		<p>Part Number: P181086 Description: AIR PRIMARY Primary App: MANN & HUMMEL C15165 Dimensions: Outer Diameter: 5.83" (148 mm) Inner Diameter: 2.83" (72 mm) Length: 12.80" (325 mm) Bolt Hole Diameter: 0.33" (8 mm) Gasket ID: 3.15" (80 mm)</p>
	<p>Part Number: P181076 Description: AIR PRIMARY Primary App: DONALDSON EAD16 A/C, FORD D5HZ9601B Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 10.12" (257 mm)</p>		<p>Part Number: P181087 Description: AIR PRIMARY Primary App: MANN & HUMMEL C23440 Dimensions: Outer Diameter: 8.93" (227 mm) Inner Diameter: 4.56" (116 mm) Length: 14.61" (371 mm) Bolt Hole Diameter: 0.41" (10 mm) Gasket ID: 5.82" (148 mm)</p>

	<p>Part Number: P181088 Description: AIR PRIMARY Primary App: MANN & HUMMEL C17225/3 Dimensions: Outer Diameter: 6.47" (164 mm) Inner Diameter: 3.41" (87 mm) Length: 13.38" (340 mm) Bolt Hole Diameter: 0.33" (8 mm) Gasket ID: 4.13" (105 mm)</p>		<p>Part Number: P181098 Description: AIR PRIMARY Primary App: UNITED 250D31S, GMC 2034763 Dimensions: Outer Diameter: 8.84" (225 mm) Inner Diameter: 5.48" (139 mm) Length: 21.60" (549 mm) Gasket OD: 7.76" (194 mm) Gasket ID: 7.00" (178 mm)</p>
	<p>Part Number: P181089 Description: AIR PRIMARY Primary App: MANN & HUMMEL C15165/3 Dimensions: Outer Diameter: 5.83" (148 mm) Inner Diameter: 2.83" (72 mm) Length: 12.80" (325 mm) Bolt Hole Diameter: 0.33" (8 mm) Gasket ID: 3.15" (80 mm)</p>		<p>Part Number: P181099 Description: AIR PRIMARY Primary App: DONALDSON EBB16, IHC, GMC Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 18.06" (459 mm) Height: 16.06" (408 mm) Gasket ID: 9.88" (178 mm)</p>
	<p>Part Number: P181090 Description: AIR PRIMARY Primary App: DONALDSON EGB10 A/C, TEREX 9059575 Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.85" (123 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 6.38" (162 mm)</p>		<p>Part Number: P181100 Description: AIR PRIMARY Primary App: CUMMINS, FLEETGUARD AF263 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 16.00" (406 mm)</p>
	<p>Part Number: P181091 Description: AIR PRIMARY Primary App: DONALDSON EGB12 A/C, JOHN DEERE AR70106 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 20.00" (508 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 6.38" (162 mm)</p>		<p>Part Number: P181102 Description: AIR PRIMARY Primary App: CAT 7M-9045, 7W-5316 Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.73" (171 mm) Length: 16.06" (408 mm) Gasket OD: 10.64" (270 mm) Gasket ID: 9.88" (178 mm)</p>
	<p>Part Number: P181092 Description: AIR PRIMARY Primary App: DONALDSON EGB09 A/C, TEREX 9059577 Dimensions: Outer Diameter: 7.63" (194 mm) Inner Diameter: 4.29" (109 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 6.38" (162 mm)</p>		<p>Part Number: P181103 Description: AIR PRIMARY Primary App: CAT 4M-8047, 7W-5389, SFTY-P533803 w/holes 9" Dimensions: Outer Diameter: 9.22" (234 mm) Inner Diameter: 4.84" (123 mm) Length: 12.00" (305 mm) Gasket OD: 8.88" (226 mm) Gasket ID: 8.12" (206 mm)</p>
	<p>Part Number: P181093 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FHG08 A/C, MASSEY FERG 1096468M91 Dimensions: Outer Diameter: 6.08" (154 mm) Inner Diameter: 3.49" (89 mm) Length: 11.00" (279 mm) Gasket ID: 4.75" (121 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P181104 Description: AIR PRIMARY Primary App: CAT 4M-9334, 7W-5317 Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.73" (171 mm) Length: 13.00" (330 mm) Gasket OD: 10.64" (270 mm) Gasket ID: 9.88" (178 mm)</p>
	<p>Part Number: P181095 Description: AIR PRIMARY Primary App: DONALDSON EBB16 A/C, VOLVO/WHITE 22005-3201 Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 15.50" (394 mm) Gasket ID: 9.88" (251 mm)</p>		<p>Part Number: P181105 Description: AIR PRIMARY Primary App: CAT 4M-9378 Dimensions: Outer Diameter: 8.40" (213 mm) Inner Diameter: 4.04" (103 mm) Length: 10.00" (254 mm) Gasket OD: 8.06" (205 mm) Gasket ID: 7.30" (185 mm)</p>
	<p>Part Number: P181096 Description: AIR PRIMARY Primary App: DONALDSON EBB15 A/C, VOLVO/WHITE 22005-3202 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 15.00" (381 mm) Gasket ID: 9.00" (229 mm)</p>		<p>Part Number: P181106 Description: AIR PRIMARY Primary App: CAT 4L-9852 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 11.75" (298 mm) Gasket OD: 10.00" (254 mm) Gasket ID: 9.24" (234 mm)</p>
	<p>Part Number: P181097 Description: AIR PRIMARY Primary App: UNITED 250D32S, GMC 2034764 Dimensions: Outer Diameter: 8.84" (225 mm) Inner Diameter: 5.48" (139 mm) Length: 27.50" (698 mm) Gasket ID: 7.00" (178 mm)</p>		<p>Part Number: P181107 Description: AIR PRIMARY Primary App: CAT 4L-9851 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 7.75" (197 mm) Gasket OD: 10.00" (254 mm) Gasket ID: 9.24" (234 mm)</p>

	<p>Part Number: P181108 Description: AIR PRIMARY Primary App: CAT 4L-9853 Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 11.75" (298 mm) Gasket OD: 13.44" (341 mm) Gasket ID: 12.66" (321 mm)</p>		<p>Part Number: P181124 Description: AIR PRIMARY Primary App: CAT 1W-2516, 7W-5216 Dimensions: Outer Diameter: 12.49" (317 mm) Inner Diameter: 9.13" (232 mm) Length: 18.50" (470 mm) Gasket OD: 12.32" (313 mm) Gasket ID: 11.30" (287 mm)</p>
	<p>Part Number: P181109 Description: AIR PRIMARY Primary App: CAT 5L-1203 Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 17.75" (451 mm) Gasket OD: 13.44" (341 mm) Gasket ID: 12.66" (321 mm)</p>		<p>Part Number: P181125 Description: AIR PRIMARY Primary App: CAT 7N-9028 Dimensions: Outer Diameter: 8.40" (213 mm) Inner Diameter: 4.04" (103 mm) Length: 5.35" (136 mm) Gasket OD: 8.06" (205 mm) Gasket ID: 7.30" (185 mm)</p>
	<p>Part Number: P181113 Description: AIR PRIMARY Primary App: CAT 4S-8833 Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 9.31" (236 mm) Bolt Hole Diameter: 0.94" (24 mm) Gasket OD: 12.33" (313 mm) Gasket ID: 11.57" (293 mm)</p>		<p>Part Number: P181126 Description: AIR PRIMARY Primary App: CAT 8N-6309 Dimensions: Outer Diameter: 19.29" (490 mm) Inner Diameter: 12.93" (328 mm) Length: 9.84" (250 mm) Gasket ID: 16.85" (428 mm)</p>
	<p>Part Number: P181114 Description: AIR PRIMARY Primary App: CAT 4S-8337 Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 14.04" (357 mm) Bolt Hole Diameter: 0.94" (24 mm) Gasket OD: 12.33" (313 mm) Gasket ID: 11.57" (293 mm)</p>		<p>Part Number: P181128 Description: AIR PRIMARY Primary App: CAT 8M-3120 Dimensions: Outer Diameter: 4.25" (108 mm) Inner Diameter: 1.56" (40 mm) Length: 4.50" (114 mm) Gasket ID: 1.55" (39 mm)</p>
	<p>Part Number: P181115 Description: AIR PRIMARY Primary App: CAT 5S-4282 Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 15.68" (398 mm) Bolt Hole Diameter: 0.94" (24 mm) Gasket ID: 12.84" (326 mm)</p>		<p>Part Number: P181129 Description: AIR PRIMARY Primary App: CAT 6P-6664 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 4.24" (108 mm) Length: 12.00" (305 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 4.75" (121 mm)</p>
	<p>Part Number: P181118 Description: AIR PRIMARY Primary App: CAT 1P-7716, 7W-5495 Dimensions: Outer Diameter: 11.49" (292 mm) Inner Diameter: 8.12" (206 mm) Length: 13.00" (330 mm) Gasket OD: 11.14" (283 mm) Gasket ID: 10.36" (263 mm)</p>		<p>Part Number: P181130 Description: AIR PRIMARY Primary App: CAT 2V-0036 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 4.24" (108 mm) Length: 9.00" (229 mm) Gasket ID: 5.42" (138 mm)</p>
	<p>Part Number: P181119 Description: AIR PRIMARY Primary App: CAT 4N-0326 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 3.48" (88 mm) Length: 12.00" (305 mm) Bolt Hole Diameter: 0.66" (17 mm)</p>		<p>Part Number: P181131 Description: AIR PRIMARY Primary App: CAT 7G-8116 Dimensions: Outer Diameter: 6.08" (154 mm) Inner Diameter: 3.49" (89 mm) Length: 7.00" (178 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 4.75" (121 mm)</p>
	<p>Part Number: P181120 Description: AIR PRIMARY Primary App: CAT 1P-8483, 7W-5313 Dimensions: Outer Diameter: 12.49" (317 mm) Inner Diameter: 7.72" (196 mm) Length: 15.00" (381 mm) Gasket OD: 12.32" (313 mm) Gasket ID: 11.30" (287 mm)</p>		<p>Part Number: P181132 Description: AIR PRIMARY Primary App: CAT 9G-1518 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 4.24" (108 mm) Length: 9.00" (229 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 5.42" (138 mm)</p>
	<p>Part Number: P181123 Description: AIR PRIMARY Primary App: CAT 7N-1225 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 9.00" (229 mm) Gasket OD: 8.88" (226 mm) Gasket ID: 8.12" (206 mm)</p>		<p>Part Number: P181133 Description: AIR PRIMARY Primary App: CAT 4L-8463 Dimensions: Outer Diameter: 10.25" (260 mm) Inner Diameter: 5.51" (140 mm) Length: 12.00" (305 mm)</p>















	<p>Part Number: P181134 Description: AIR PRIMARY Primary App: CAT 4L-8464 Dimensions: Outer Diameter: 12.00" (305 mm) Inner Diameter: 7.29" (185 mm) Length: 15.00" (381 mm)</p>		<p>Part Number: P181165 Description: AIR PRIMARY Primary App: VOLVO 6872683 Dimensions: Outer Diameter: 7.80" (198 mm) Inner Diameter: 4.44" (113 mm) Length: 20.00" (508 mm) Bolt Hole Diameter: 0.41" (10 mm) Gasket ID: 5.42" (138 mm)</p>
	<p>Part Number: P181136 Description: AIR PRIMARY Primary App: IHC 472099C1 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 17.25" (438 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket OD: 10.32" (262 mm) Gasket ID: 9.56" (243 mm)</p>		<p>Part Number: P181166 Description: AIR PRIMARY Primary App: ROOF VACUUM DUST COLL. Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 26.00" (660 mm) Gasket ID: 10.12" (257 mm)</p>
	<p>Part Number: P181137 Description: AIR PRIMARY Primary App: MERCEDES-BENZ 0010947904, KHD 422165059 Dimensions: Outer Diameter: 9.49" (241 mm) Inner Diameter: 5.19" (132 mm) Length: 19.00" (483 mm) Bolt Hole Diameter: 0.44" (11 mm) Gasket ID: 6.25" (159 mm)</p>		<p>Part Number: P181183 Description: AIR PRIMARY Primary App: STEIGER 90-4203T1 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 21.00" (533 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 8.12" (206 mm)</p>
	<p>Part Number: P181139 Description: AIR PRIMARY Primary App: KOMATSU Dimensions: Outer Diameter: 9.62" (244 mm) Inner Diameter: 5.26" (134 mm) Length: 15.00" (381 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 8.68" (220 mm)</p>		<p>Part Number: P181185 Description: AIR PRIMARY Primary App: DONALDSON LONG EBB16 A/C Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 21.02" (534 mm) Gasket ID: 9.88" (251 mm)</p>
	<p>Part Number: P181141 Description: AIR PRIMARY Primary App: KOMATSU 600-181-9220 Dimensions: Outer Diameter: 8.24" (209 mm) Inner Diameter: 4.20" (107 mm) Length: 12.58" (320 mm)</p>		<p>Part Number: P181186 Description: AIR PRIMARY Primary App: VORTOX VF160R Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 26.00" (660 mm) Bolt Hole Diameter: 0.53" (13 mm) Gasket OD: 10.88" (276 mm) Gasket ID: 10.12" (257 mm)</p>
	<p>Part Number: P181142 Description: AIR PRIMARY Primary App: KOMATSU Dimensions: Outer Diameter: 8.42" (214 mm) Inner Diameter: 4.21" (107 mm) Length: 16.25" (413 mm) Gasket OD: 8.38" (213 mm) Gasket ID: 7.62" (194 mm)</p>		<p>Part Number: P181187 Description: AIR PRIMARY Primary App: FORD E3TZ9601C Dimensions: Outer Diameter: 11.68" (297 mm) Inner Diameter: 8.12" (206 mm) Length: 5.00" (127 mm)</p>
	<p>Part Number: P181146 Description: AIR PRIMARY Primary App: DONALDSON ECG11 AC, MACK, GMC Dimensions: Outer Diameter: 8.84" (225 mm) Inner Diameter: 5.48" (139 mm) Length: 28.00" (711 mm) Gasket ID: 7.00" (178 mm)</p>		<p>Part Number: P181188 Description: AIR PRIMARY Primary App: IHC 588213C1 Dimensions: Outer Diameter: 11.68" (297 mm) Inner Diameter: 8.12" (206 mm) Length: 7.00" (178 mm)</p>
	<p>Part Number: P181147 Description: AIR PRIMARY Primary App: DONALDSON EBB16 A/C, MACK Dimensions: Outer Diameter: 13.84" (352 mm) Inner Diameter: 7.48" (190 mm) Length: 22.06" (560 mm) Gasket ID: 9.88" (251 mm)</p>		<p>Part Number: P181189 Description: AIR PRIMARY Primary App: FORD E2HZ9601B Dimensions: Outer Diameter: 13.84" (352 mm) Inner Diameter: 7.48" (190 mm) Length: 10.00" (254 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 9.56" (243 mm)</p>
	<p>Part Number: P181163 Description: AIR PRIMARY Primary App: JOHN DEERE AT65296 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 3.49" (89 mm) Length: 12.00" (305 mm) Bolt Hole Diameter: 0.66" (17 mm)</p>		<p>Part Number: P181191 Description: AIR PRIMARY Primary App: MITSUBISHI ME033603 Dimensions: Outer Diameter: 8.70" (221 mm) Inner Diameter: 5.36" (136 mm) Length: 17.40" (442 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 5.80" (147 mm)</p>

	<p>Part Number: P181193 Description: AIR PRIMARY Primary App: CAT 4W-5716 Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 18.00" (457 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 9.88" (251 mm)</p>		<p>Part Number: P182003 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181003 Dimensions: Outer Diameter: 8.84" (225 mm) Inner Diameter: 5.48" (139 mm) Length: 22.00" (559 mm)</p>
	<p>Part Number: P181200 Description: AIR PRIMARY Primary App: GMC Brigadere w/CAT 3208T Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 10.00" (254 mm) Gasket ID: 9.00" (229 mm)</p>		<p>Part Number: P182007 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181007 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 21.82" (554 mm) Gasket ID: 8.12" (206 mm)</p>
	<p>Part Number: P181204 Description: AIR PRIMARY Primary App: FORD DINN-9601-A Dimensions: Outer Diameter: 6.68" (170 mm) Inner Diameter: 3.75" (95 mm) Length: 14.75" (375 mm) Bolt Hole Diameter: 0.43" (11 mm)</p>		<p>Part Number: P182008 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181008 Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 22.00" (559 mm) Gasket ID: 10.12" (257 mm)</p>
	<p>Part Number: P181205 Description: AIR PRIMARY Primary App: IHC 537337R1, AIR MAZE C01017502826 Dimensions: Outer Diameter: 8.38" (213 mm) Inner Diameter: 4.56" (116 mm) Length: 15.00" (381 mm)</p>		<p>Part Number: P182014 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181014 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 15.00" (381 mm) Gasket ID: 8.12" (206 mm)</p>
	<p>Part Number: P181208 Description: AIR SAFETY Primary App: FORD DINN-9R500-A Dimensions: Outer Diameter: 3.62" (92 mm) Inner Diameter: 2.94" (75 mm) Length: 13.69" (348 mm)</p>		<p>Part Number: P182015 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181015 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 18.00" (457 mm) Gasket ID: 9.70" (246 mm)</p>
	<p>Part Number: P181210 Description: AIR PRIMARY Primary App: CAT D10N 7W-9853 Dimensions: Outer Diameter: 14.28" (363 mm) Inner Diameter: 9.92" (252 mm) Length: 18.00" (457 mm) Gasket OD: 13.86" (352 mm) Gasket ID: 13.10" (332 mm)</p>		<p>Part Number: P182016 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181016 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 26.00" (660 mm) Gasket ID: 8.12" (206 mm)</p>
	<p>Part Number: P182000 Description: AIR PRIMARY, FINNED Primary App: LONG LIFE VERSION OF P181000 Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.73" (171 mm) Length: 12.00" (305 mm) Gasket ID: 9.56" (243 mm) Minor OD: 0.53" (13 mm)</p>		<p>Part Number: P182028 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181028 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 16.00" (406 mm) Gasket ID: 8.12" (206 mm)</p>
	<p>Part Number: P182001 Description: AIR PRIMARY, FINNED Primary App: LONG LIFE VERSION OF P181001 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 14.00" (356 mm) Gasket ID: 10.12" (257 mm) Minor OD: 0.53" (13 mm)</p>		<p>Part Number: P182031 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181031 Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 14.00" (356 mm) Bolt Hole Diameter: 0.53" (13 mm)</p>
	<p>Part Number: P182002 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181002 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 18.00" (457 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 10.12" (257 mm)</p>		<p>Part Number: P182032 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181032 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 10.00" (254 mm) Bolt Hole Diameter: 0.53" (13 mm)</p>










	<p>Part Number: P182033 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181033 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.96" (177 mm) Length: 9.00" (229 mm) Bolt Hole Diameter: 0.53" (13 mm)</p>		<p>Part Number: P182042 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181042 Dimensions: Outer Diameter: 14.68" (373 mm) Inner Diameter: 10.34" (263 mm) Length: 23.88" (607 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 11.00" (279 mm)</p>
	<p>Part Number: P182034 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181034 Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.85" (123 mm) Length: 13.00" (330 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 7.62" (194 mm)</p>		<p>Part Number: P182043 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181043 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.72" (196 mm) Length: 20.00" (508 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 8.12" (206 mm)</p>
	<p>Part Number: P182035 Description: AIR PRIMARY, FINNED Primary App: LONG LIFE VERSION OF P181035 Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.85" (123 mm) Length: 10.00" (254 mm) Gasket ID: 7.62" (194 mm) Minor OD: 0.53" (13 mm)</p>		<p>Part Number: P182044 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181044 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 14.00" (356 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 6.38" (162 mm)</p>
	<p>Part Number: P182036 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181036 Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.53" (13 mm)</p>		<p>Part Number: P182045 Description: AIR PRIMARY, FINNED Primary App: LONG LIFE VERSION OF P181045 Dimensions: Outer Diameter: 7.93" (201 mm) Inner Diameter: 3.57" (91 mm) Length: 10.00" (254 mm) Gasket ID: 6.36" (162 mm) Minor OD: 0.53" (13 mm)</p>
	<p>Part Number: P182037 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181037 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 13.00" (330 mm) Bolt Hole Diameter: 0.53" (13 mm)</p>		<p>Part Number: P182046 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181046 Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.73" (171 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 9.56" (243 mm)</p>
	<p>Part Number: P182038 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181038 Dimensions: Outer Diameter: 17.62" (448 mm) Inner Diameter: 11.07" (281 mm) Length: 23.06" (586 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 14.00" (356 mm)</p>		<p>Part Number: P182048 Description: AIR PRIMARY Primary App: TEREX 9059570, DRESSER VE1013, VE1195, DCI SRG20 Dimensions: Outer Diameter: 17.58" (447 mm) Inner Diameter: 12.22" (310 mm) Length: 19.03" (483 mm) Bolt Hole Diameter: 0.42" (11 mm) Gasket ID: 14.00" (356 mm)</p>
	<p>Part Number: P182039 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181039 Dimensions: Outer Diameter: 13.84" (352 mm) Inner Diameter: 9.47" (241 mm) Length: 18.00" (457 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 9.88" (251 mm)</p>		<p>Part Number: P182049 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181049 Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 24.03" (610 mm) Bolt Hole Diameter: 0.94" (24 mm) Gasket ID: 9.88" (251 mm)</p>
	<p>Part Number: P182040 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181040 Dimensions: Outer Diameter: 17.58" (447 mm) Inner Diameter: 12.22" (310 mm) Length: 23.03" (585 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 14.00" (356 mm)</p>		<p>Part Number: P182050 Description: AIR PRIMARY, FINNED Primary App: LONG LIFE VERSION OF P181050 Dimensions: Outer Diameter: 4.08" (104 mm) Inner Diameter: 2.49" (63 mm) Length: 10.00" (254 mm) Gasket ID: 2.58" (65 mm) Minor OD: 0.66" (17 mm)</p>
	<p>Part Number: P182041 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181041 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 8.12" (206 mm)</p>		<p>Part Number: P182052 Description: AIR PRIMARY, FINNED Primary App: LONG LIFE VERSION OF P181052 Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 2.64" (67 mm) Length: 11.00" (279 mm) Gasket ID: 3.95" (100 mm) Minor OD: 0.66" (17 mm)</p>

















	<p>Part Number: P182054 Description: AIR PRIMARY, FINNED Primary App: LONG LIFE VERSION OF P181054 Dimensions: Outer Diameter: 6.08" (154 mm) Inner Diameter: 3.49" (89 mm) Length: 12.00" (305 mm) Gasket ID: 4.45" (113 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P182072 Description: AIR PRIMARY, FINNED Primary App: LONG LIFE VERSION OF P181072 Dimensions: Outer Diameter: 4.08" (104 mm) Inner Diameter: 2.49" (63 mm) Length: 14.00" (356 mm) Gasket ID: 2.58" (65 mm) Minor OD: 0.66" (17 mm)</p>
	<p>Part Number: P182055 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181055 Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 19.06" (484 mm) Gasket ID: 9.88" (251 mm)</p>		<p>Part Number: P182078 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181078 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.72" (196 mm) Length: 23.00" (584 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 8.12" (206 mm)</p>
	<p>Part Number: P182059 Description: AIR PRIMARY, FINNED Primary App: LONG LIFE VERSION OF P181059 Dimensions: Outer Diameter: 6.08" (154 mm) Inner Diameter: 3.49" (89 mm) Length: 15.00" (381 mm) Gasket ID: 4.45" (113 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P182080 Description: AIR PRIMARY Primary App: ISUZU 2-90646-930-0 LONG LIFE VERSION OF P181080 Dimensions: Outer Diameter: 9.14" (232 mm) Inner Diameter: 5.78" (147 mm) Length: 13.00" (330 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 6.25" (159 mm)</p>
	<p>Part Number: P182062 Description: AIR PRIMARY, FINNED Primary App: LONG LIFE VERSION OF P181062 Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 3.26" (83 mm) Length: 15.00" (381 mm) Gasket ID: 3.95" (100 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P182082 Description: AIR PRIMARY Primary App: Donaldson FTG13 CYCLOPAC A/C Dimensions: Outer Diameter: 10.86" (276 mm) Inner Diameter: 6.50" (165 mm) Length: 20.00" (508 mm) Gasket ID: 7.62" (194 mm)</p>
	<p>Part Number: P182063 Description: AIR PRIMARY, FINNED Primary App: LONG LIFE VERSION OF P181063 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 4.22" (107 mm) Length: 16.00" (406 mm) Gasket ID: 5.42" (138 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P182090 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181090 Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.85" (123 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 6.36" (162 mm)</p>
	<p>Part Number: P182064 Description: AIR PRIMARY, FINNED Primary App: LONG LIFE VERSION OF P181064 Dimensions: Outer Diameter: 7.93" (201 mm) Inner Diameter: 5.32" (135 mm) Length: 16.00" (406 mm) Gasket ID: 6.36" (162 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P182091 Description: AIR PRIMARY Primary App: FIAT 1930791, HANOMAG 3074306M1 Dimensions: Outer Diameter: 10.43" (265 mm) Inner Diameter: 6.02" (153 mm) Length: 20.00" (508 mm)</p>
	<p>Part Number: P182068 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181068 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 4.24" (108 mm) Length: 9.00" (229 mm)</p>		<p>Part Number: P182092 Description: AIR PRIMARY Primary App: FIAT 1930725, HANOMAG 3074304M1, 3074305M1 Dimensions: Outer Diameter: 7.63" (194 mm) Inner Diameter: 4.29" (109 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket OD: 7.14" (181 mm)</p>
	<p>Part Number: P182070 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181070 Dimensions: Outer Diameter: 9.14" (232 mm) Inner Diameter: 5.78" (147 mm) Length: 18.00" (457 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 6.25" (159 mm)</p>		<p>Part Number: P182095 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181095 Dimensions: Outer Diameter: 13.83" (351 mm) Inner Diameter: 9.49" (241 mm) Length: 15.50" (394 mm) Gasket ID: 9.88" (251 mm)</p>
	<p>Part Number: P182071 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181071 Dimensions: Outer Diameter: 8.40" (213 mm) Inner Diameter: 5.79" (147 mm) Length: 11.00" (279 mm) Bolt Hole Diameter: 0.53" (13 mm)</p>		<p>Part Number: P182096 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181096 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 15.00" (381 mm) Gasket ID: 9.00" (229 mm)</p>













	<p>Part Number: P182099 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P181099 Dimensions: Outer Diameter: 13.84" (352 mm) Inner Diameter: 7.48" (190 mm) Length: 18.06" (459 mm) Gasket ID: 9.88" (251 mm)</p>	<p>Part Number: P50007 Description: AIR PRIMARY Primary App: IHC, DODGE, FORD, JEEP, MELROE Dimensions: Outer Diameter: 1.39" (35 mm) Inner Diameter: 0.50" (13 mm) Length: 1.86" (48 mm)</p>
	<p>Part Number: P185002 Description: AIR PRIMARY, ULTRA-WEB® Primary App: Donaldson FHG16 A/C Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.72" (196 mm) Length: 18.00" (457 mm) Gasket ID: 10.12" (257 mm) Minor OD: 0.66" (17 mm)</p>	<p>Part Number: P500008 Description: AIR PRIMARY Primary App: MITSUBISHI MD603932 Dimensions: Outer Diameter: 8.03" (204 mm) Inner Diameter: 0" (0 mm) Length: 6.93" (176 mm)</p>
	<p>Part Number: P228498 Description: AIR PANEL Primary App: DPF PULSE CLEANER Dimensions: Width: 8.91" (227 mm) Depth: 1.82" (46 mm) Height: 11.27" (287 mm)</p>	 <p>Part Number: P500010 Description: AIR PRIMARY, OVAL Primary App: MITSUBISHI Dimensions: D: 9.92" (252 mm) E: 3.01" (76 mm)</p>
	<p>Part Number: P270332 Description: AIR PRIMARY Primary App: INDUSTRIAL BLOWER Dimensions: Outer Diameter: 8.40" (213 mm) Inner Diameter: 5.79" (147 mm) Length: 9.00" (229 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 7.00" (178 mm)</p>	 <p>Part Number: P500014 Description: AIR PRIMARY Primary App: MITSUBISHI ME017242 Dimensions: Outer Diameter: 7.09" (180 mm) Inner Diameter: 3.70" (94 mm) Length: 8.62" (219 mm)</p>
	<p>Part Number: P270333 Description: AIR PRIMARY Primary App: INDUSTRIAL BLOWER Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 2.64" (67 mm) Length: 6.00" (152 mm) Bolt Hole Diameter: 0.53" (13 mm)</p>	<p>Part Number: P500015 Description: AIR PRIMARY Primary App: TOYOTA 17801-23020, 17801-23030, 17801-31060 Dimensions: Outer Diameter: 6.41" (163 mm) Inner Diameter: 3.00" (76 mm) Length: 4.17" (106 mm)</p>
	<p>Part Number: P270336 Description: AIR PRIMARY Primary App: INDUSTRIAL BLOWER Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 20.00" (508 mm) Bolt Hole Diameter: 0.89" (23 mm) Gasket ID: 8.12" (206 mm)</p>	 <p>Part Number: P500016 Description: AIR PRIMARY Primary App: TOYOTA 17801-13010, 17801-33011 Dimensions: Outer Diameter: 7.32" (186 mm) Inner Diameter: 4.29" (109 mm) Length: 2.19" (56 mm)</p>
	<p>Part Number: P500004 Description: AIR PRIMARY Primary App: MITSUBISHI MD603014 Dimensions: Outer Diameter: 9.84" (250 mm) Inner Diameter: 7.56" (192 mm) Length: 2.40" (61 mm)</p>	 <p>Part Number: P500017 Description: AIR PRIMARY Primary App: TOYOTA 17801-48010, 17801-48011 Dimensions: Outer Diameter: 7.64" (194 mm) Inner Diameter: 3.35" (85 mm) Length: 5.71" (145 mm)</p>
	<p>Part Number: P500005 Description: AIR PRIMARY Primary App: MITSUBISHI MD604880 Dimensions: Outer Diameter: 10.64" (270 mm) Inner Diameter: 7.95" (202 mm) Length: 2.13" (54 mm)</p>	 <p>Part Number: P500020 Description: AIR PRIMARY Primary App: TOYOTA 17801-54010 Dimensions: Outer Diameter: 7.32" (186 mm) Inner Diameter: 3.07" (78 mm) Length: 4.92" (125 mm)</p>
	<p>Part Number: P500006 Description: AIR PRIMARY Primary App: MITSUBISHI MD604802 Dimensions: Outer Diameter: 10.04" (255 mm) Inner Diameter: 7.20" (183 mm) Length: 2.24" (57 mm)</p>	 <p>Part Number: P500021 Description: AIR PRIMARY Primary App: TOYOTA 17801-31050, ISUZU 9942320590 Dimensions: Outer Diameter: 6.09" (155 mm) Inner Diameter: 3.38" (86 mm) Length: 7.76" (197 mm)</p>
		 <p>Part Number: P500024 Description: AIR PRIMARY Primary App: TOYOTA 1780-156020 Dimensions: Outer Diameter: 7.64" (194 mm) Inner Diameter: 3.35" (85 mm) Length: 5.71" (145 mm)</p>



















	<p>Part Number: P500026 Description: AIR PANEL, ENGINE Primary App: TOYOTA 17801-16020 Dimensions: Width: 9.84" (250 mm) Depth: 6.14" (156 mm) Height: 1.61" (41 mm)</p>		<p>Part Number: P500065 Description: AIR PRIMARY Primary App: GM, HONDA Dimensions: Outer Diameter: 9.05" (230 mm) Inner Diameter: 6.58" (167 mm) Length: 2.58" (66 mm)</p>
	<p>Part Number: P500027 Description: AIR PRIMARY Primary App: TOYOTA 17801-35030 Dimensions: Outer Diameter: 6.27" (159 mm) Inner Diameter: 3.00" (76 mm) Length: 5.67" (144 mm)</p>		<p>Part Number: P500070 Description: AIR PRIMARY, OVAL Primary App: HONDA 17220PH4601 Dimensions: Width: 13.54" (344 mm) Height: 8.50" (216 mm) Length: 1.67" (42 mm)</p>
	<p>Part Number: P500028 Description: AIR PRIMARY Primary App: TOYOTA 17801-54100 Dimensions: Outer Diameter: 5.28" (134 mm) Inner Diameter: 3.03" (77 mm) Length: 11.02" (280 mm) Bolt Hole Diameter: 0.05" (1 mm)</p>		<p>Part Number: P500071 Description: AIR PRIMARY Primary App: HONDA Dimensions: Outer Diameter: 10.62" (270 mm) Inner Diameter: 7.95" (202 mm) Length: 1.65" (42 mm)</p>
	<p>Part Number: P500042 Description: AIR PRIMARY Primary App: HINO 17801-2200 Dimensions: Outer Diameter: 8.50" (216 mm) Inner Diameter: 5.39" (137 mm) Length: 12.40" (315 mm)</p>		<p>Part Number: P500078 Description: AIR PRIMARY Primary App: MAZDA R20523603 Dimensions: Outer Diameter: 6.10" (155 mm) Inner Diameter: 3.11" (79 mm) Length: 5.90" (150 mm) D: 9.04" (230 mm)</p>
	<p>Part Number: P500044 Description: AIR PRIMARY Primary App: HINO, HITACHI Dimensions: Outer Diameter: 9.06" (230 mm) Inner Diameter: 4.76" (121 mm) Length: 13.00" (330 mm)</p>		<p>Part Number: P500081 Description: AIR PRIMARY Primary App: NISSAN 16546-18000 Dimensions: Height: 2.00" (51 mm)</p>
	<p>Part Number: P500046 Description: AIR PRIMARY Primary App: HINO 178012830, 178012890A Dimensions: Outer Diameter: 10.75" (273 mm) Inner Diameter: 6.38" (162 mm) Length: 13.91" (353 mm)</p>	<p>Part Number: P500083 Description: AIR PRIMARY Primary App: NISSAN 16546-76000 Dimensions: Outer Diameter: 4.98" (126 mm) Inner Diameter: 0.28" (7 mm) Length: 6.65" (169 mm) Bolt Hole Diameter: 0.39" (10 mm)</p>	
	<p>Part Number: P500048 Description: AIR PRIMARY Primary App: SUZUKI 1378067022 Dimensions: Outer Diameter: 4.74" (120 mm) Inner Diameter: 2.60" (66 mm) Length: 5.20" (132 mm)</p>		<p>Part Number: P500094 Description: AIR PRIMARY Primary App: KOMATSU 6001817210 Dimensions: Outer Diameter: 7.07" (180 mm) Inner Diameter: 3.98" (101 mm) Length: 11.77" (299 mm)</p>
	<p>Part Number: P500056 Description: AIR PRIMARY Primary App: SUZUKI 1378083000 Dimensions: Outer Diameter: 7.24" (184 mm) Inner Diameter: 4.64" (118 mm) Length: 3.98" (101 mm)</p>		<p>Part Number: P500096 Description: AIR SAFETY Primary App: KOMATSU 6001817360 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.12" (54 mm) Length: 9.33" (237 mm)</p>
	<p>Part Number: P500063 Description: AIR PANEL, ENGINE Primary App: ISUZU 8941516143 Dimensions: Width: 6.63" (169 mm) Depth: 11.10" (282 mm) Height: 1.34" (34 mm)</p>		<p>Part Number: P500099 Description: AIR PRIMARY Primary App: KOMATSU Dimensions: Outer Diameter: 9.64" (245 mm) Inner Diameter: 5.20" (132 mm) Length: 8.82" (224 mm)</p>
	<p>Part Number: P500064 Description: AIR PRIMARY Primary App: ISUZU 8943349060 Dimensions: Outer Diameter: 6.06" (154 mm) Inner Diameter: 3.13" (80 mm) Length: 5.94" (151 mm)</p>		<p>Part Number: P500100 Description: AIR PRIMARY Primary App: KOMATSU 6675817231 Dimensions: Outer Diameter: 9.64" (245 mm) Inner Diameter: 5.11" (130 mm) Length: 8.82" (224 mm)</p>

	<p>Part Number: P500101 Description: AIR SAFETY Primary App: KOMATSU 6675817030 Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 3.82" (97 mm) Length: 17.60" (447 mm)</p>	<p>Part Number: P500169 Description: AIR PRIMARY Primary App: Nissan 16546 96007 Dimensions: Outer Diameter: 7.95" (202 mm) Inner Diameter: 4.37" (111 mm) Length: 16.85" (428 mm)</p>
	<p>Part Number: P500102 Description: AIR PRIMARY Primary App: KOMATSU 6675817011 Dimensions: Outer Diameter: 9.65" (245 mm) Inner Diameter: 3.81" (97 mm) Length: 18.14" (461 mm) Gasket ID: 0.51" (13 mm)</p>	<p>Part Number: P500170 Description: AIR PRIMARY Primary App: Nissan 16546-96018 Dimensions: Outer Diameter: 8.86" (225 mm) Inner Diameter: 6.22" (158 mm) Length: 12.52" (318 mm)</p>
	<p>Part Number: P500110 Description: AIR PRIMARY Primary App: ISUZU 5-14215-030-0, 5142150060 Dimensions: Outer Diameter: 6.10" (155 mm) Inner Diameter: 3.10" (79 mm) Length: 10.43" (265 mm)</p>	<p>Part Number: P500171 Description: AIR SAFETY Primary App: Nissan 16546-96100 Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 4.76" (121 mm) Length: 11.61" (295 mm)</p>
	<p>Part Number: P500111 Description: AIR PRIMARY Primary App: NISSAN Dimensions: Outer Diameter: 10.03" (255 mm) Inner Diameter: 6.26" (159 mm) Length: 16.46" (418 mm)</p>	<p>Part Number: P500174 Description: AIR SAFETY Primary App: Volvo 3979928 Dimensions: Outer Diameter: 6.61" (168 mm) Inner Diameter: 5.23" (133 mm) Length: 17.32" (440 mm) Efficiency @ 99% Percent</p>
	<p>Part Number: P500120 Description: AIR PRIMARY Primary App: MITSUBISHI MD620563 Dimensions: Outer Diameter: 6.10" (155 mm) Inner Diameter: 3.39" (86 mm) Length: 7.48" (190 mm) Bolt Hole Diameter: 0.51" (13 mm)</p>	<p>Part Number: P500175 Description: AIR PRIMARY Primary App: Hino 17801-2980 Dimensions: Outer Diameter: 8.97" (228 mm) Inner Diameter: 4.92" (125 mm) Length: 13.34" (339 mm) Rated Flow: 282.51 CFM (8 CMM)</p>
	<p>Part Number: P500124 Description: AIR PRIMARY Primary App: TOYOTA 1042216-M91 Dimensions: Outer Diameter: 8.62" (219 mm) Inner Diameter: 4.27" (108 mm) Length: 4.70" (119 mm)</p>	<p>Part Number: P500177 Description: AIR SAFETY Primary App: Hino 17801-3190 Dimensions: Outer Diameter: 7.28" (185 mm) Inner Diameter: 6.19" (157 mm) Length: 12.86" (326 mm)</p>
	<p>Part Number: P500125 Description: AIR PRIMARY Primary App: TOYOTA 17801-67060 Dimensions: Outer Diameter: 8.62" (219 mm) Inner Diameter: 4.25" (108 mm) Length: 5.67" (144 mm)</p>	<p>Part Number: P500178 Description: AIR PRIMARY Primary App: Hino 17801-3180 Dimensions: Outer Diameter: 12.12" (308 mm) Inner Diameter: 7.71" (196 mm) Length: 14.21" (361 mm)</p>
	<p>Part Number: P500146 Description: AIR PRIMARY, SPECIAL Primary App: ATCO 3214623900 Dimensions: Outer Diameter: 4.51" (115 mm) Inner Diameter: 2.81" (72 mm) Length: 23.70" (602 mm) Efficiency @ 99%</p>	<p>Part Number: P500179 Description: AIR PRIMARY Primary App: Isuzu 2-90646-910-0 Dimensions: Outer Diameter: 8.70" (221 mm) Inner Diameter: 5.34" (136 mm) Length: 13.02" (330 mm)</p>
	<p>Part Number: P500149 Description: AIR PRIMARY, SPECIAL Primary App: Fleetguard AF25772 Dimensions: Outer Diameter: 4.51" (115 mm) Inner Diameter: 2.28" (58 mm) Length: 23.70" (602 mm) Efficiency @ 99%</p>	<p>Part Number: P500182 Description: AIR PRIMARY Primary App: Yanmar 10510012570 Dimensions: Outer Diameter: 3.64" (93 mm) Inner Diameter: 1.38" (35 mm) Length: 3.98" (101 mm)</p>
	<p>Part Number: P500168 Description: AIR PRIMARY Primary App: NISSAN 1654696005 Dimensions: Outer Diameter: 3.98" (101 mm) Inner Diameter: 4.37" (111 mm) Length: 12.99" (330 mm)</p>	<p>Part Number: P500183 Description: AIR PRIMARY Primary App: Yanmar 10530012570 Dimensions: Outer Diameter: 4.41" (112 mm) Inner Diameter: 1.69" (43 mm) Length: 4.76" (121 mm)</p>
		<p>Part Number: P500184 Description: AIR PRIMARY Primary App: Yanmar 10550012570 Dimensions: Outer Diameter: 4.74" (120 mm) Inner Diameter: 2.08" (53 mm) Length: 4.76" (121 mm)</p>

<p>Part Number: P500185 Description: AIR PRIMARY Primary App: Mercedes A0040943504 Dimensions: Outer Diameter: 10.47" (266 mm) Inner Diameter: 6.14" (156 mm) Length: 19.49" (494 mm) Efficiency @ 99% Percent</p>	 <p>Part Number: P500203 Description: AIR PANEL Primary App: KOMATSU 77Z9-70-0020 Dimensions: Width: 7.83" (199 mm) Depth: 0.76" (20 mm) Length: 11.94" (304 mm) Efficiency @ 99%</p>
<p>Part Number: P500191 Description: AIR PRIMARY Primary App: MITSUBISHI ME017246 Dimensions: Outer Diameter: 9.17" (233 mm) Inner Diameter: 4.64" (118 mm) Length: 10.29" (262 mm) Efficiency @ 99% Percent</p>	<p>Part Number: P500204 Description: AIR PANEL, VENTILATION Primary App: KOMATSU 77Z9-70-0010 Dimensions: Width: 7.83" (199 mm) Depth: 0.76" (20 mm) Length: 7.97" (203 mm) Efficiency @ 99%</p>
<p>Part Number: P500193 Description: AIR PRIMARY Primary App: YANMAR 114250-12581 Dimensions: Outer Diameter: 4.13" (105 mm) Inner Diameter: 2.13" (54 mm) Length: 1.79" (46 mm) Efficiency @ 99% Percent</p>	<p>Part Number: P500940 Description: AIR PRIMARY Primary App: LUNGONG LOADERS Dimensions: Outer Diameter: 9.14" (232 mm)</p>
 <p>Part Number: P500194 Description: AIR PANEL, VENTILATION Primary App: Volvo 11703979 Dimensions: Width: 4.84" (123 mm) Depth: 1.73" (44 mm) Length: 17.13" (435 mm) Efficiency @ 99% Percent</p>	 <p>Part Number: P502007 Description: LUBE SPIN-ON FULL FLOW Primary App: MITSUBISHI MD135737, 30A4000100 Dimensions: Outer Diameter: 2.68" (68 mm) Thread Size: M20 x 1.5 Length: 3.34" (85 mm) Gasket OD: 2.67" (68 mm) Gasket ID: 2.15" (55 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 20 Micron</p>
 <p>Part Number: P500195 Description: AIR PANEL, VENTILATION Primary App: Volvo 11703980 Dimensions: Width: 11.26" (286 mm) Height: 2.44" (62 mm) Length: 19.13" (486 mm) Efficiency @ 99% Percent</p>	 <p>Part Number: P502008 Description: LUBE SPIN-ON COMBINATION Primary App: MITSUBISHI ME013307, ME013343 Dimensions: Outer Diameter: 4.21" (107 mm) Thread Size: M26 x 1.5 Length: 5.90" (150 mm) Gasket OD: 2.87" (73 mm) Gasket ID: 2.19" (56 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Efficiency 50% @ 20 Micron</p>
 <p>Part Number: P500196 Description: BREATHER Primary App: VOLVO 11707077 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 2.48" (63 mm) Length: 2.88" (73 mm) Efficiency @ 99% Percent</p>	 <p>Part Number: P502009 Description: LUBE SPIN-ON FULL FLOW Primary App: MITSUBISHI MD136466 Dimensions: Outer Diameter: 3.15" (80 mm) Thread Size: M20 x 1.5 Length: 2.52" (64 mm) Gasket OD: 2.48" (63 mm) Gasket ID: 2.03" (52 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Efficiency 50% @ 20 Micron</p>
<p>Part Number: P500197 Description: AIR PRIMARY, RADIALSEAL Primary App: Hino 178013450 Dimensions: Outer Diameter: 10.90" (277 mm) Inner Diameter: 6.85" (174 mm) Length: 14.21" (361 mm) Efficiency @ 99% Percent</p>	 <p>Part Number: P502010 Description: LUBE SPIN-ON FULL FLOW Primary App: MITSUBISHI MD322508 Dimensions: Outer Diameter: 3.00" (76 mm) Thread Size: M20 x 1.5 Length: 2.52" (64 mm) Gasket OD: 2.48" (63 mm) Gasket ID: 2.03" (52 mm)</p>
<p>Part Number: P500198 Description: AIR SAFETY, RADIALSEAL Primary App: Hino 178013460 Dimensions: Outer Diameter: 6.81" (173 mm) Inner Diameter: 5.03" (128 mm) Length: 13.97" (355 mm) Efficiency @ 99% Percent</p>	<p>Part Number: P502015 Description: LUBE SPIN-ON FULL FLOW Primary App: TOYOTA 9091503001, 9091510001 Dimensions: Outer Diameter: 2.56" (65 mm) Thread Size: 3/4-16 Length: 2.80" (71 mm) Gasket OD: 2.46" (62 mm) Gasket ID: 1.94" (49 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 20 Micron</p>
<p>Part Number: P500200 Description: AIR PRIMARY, RADIALSEAL Primary App: Mitsubishi ME294400 Dimensions: Outer Diameter: 7.08" (180 mm) Inner Diameter: 3.66" (93 mm) Length: 8.70" (221 mm) Efficiency @ 99%</p>	
<p>Part Number: P500202 Description: AIR PRIMARY Primary App: Furukawa 08841201041 Dimensions: Outer Diameter: 7.92" (201 mm) Inner Diameter: 3.56" (90 mm) Length: 19.68" (500 mm) Efficiency @ 99%</p>	

	<p>Part Number: P502016 Description: LUBE SPIN-ON FULL FLOW Primary App: TOYOTA 9091503002, 9091520001 Dimensions: Outer Diameter: 2.91" (74 mm) Thread Size: 3/4-16 Length: 3.31" (84 mm) Relief Valve Setting: 12 PSI (.882 Bar) Efficiency 99% @ 50 Micron</p>		<p>Part Number: P502039 Description: LUBE SPIN-ON FULL FLOW Primary App: ISUZU 8944309830 Dimensions: Outer Diameter: 3.54" (90 mm) Thread Size: M20 x 1.5 Length: 3.93" (100 mm) Gasket OD: 3.43" (87 mm) Gasket ID: 3.01" (76 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P502017 Description: LUBE SPIN-ON COMBINATION Primary App: TOYOTA 90915-03003, 90915-30001 Dimensions: Outer Diameter: 3.93" (100 mm) Thread Size: M24 x 1.5 Length: 3.30" (84 mm) Gasket OD: 3.15" (80 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Efficiency 50% @ 5 Micron</p>		<p>Part Number: P502042 Description: LUBE SPIN-ON COMBINATION Primary App: ISUZU 8970967770, 2906548000, 97148270 Dimensions: Outer Diameter: 4.88" (124 mm) Thread Size: 1 1/2-12 Length: 4.72" (120 mm) Gasket OD: 4.59" (116 mm) Gasket ID: 3.86" (98 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Efficiency 50% @ 16 Micron</p>
	<p>Part Number: P502019 Description: LUBE SPIN-ON FULL FLOW Primary App: TOYOTA 9091503004 Dimensions: Outer Diameter: 2.56" (65 mm) Thread Size: 3/4-16 Length: 3.54" (90 mm) Gasket OD: 2.46" (62 mm) Gasket ID: 1.94" (49 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P502043 Description: LUBE SPIN-ON COMBINATION Primary App: ISUZU 8943604271 Dimensions: Outer Diameter: 3.54" (90 mm) Thread Size: M26 x 1.5 Length: 4.92" (125 mm) Gasket OD: 3.44" (87 mm) Gasket ID: 3.00" (76 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P502020 Description: LUBE SPIN-ON FULL FLOW Primary App: TOYOTA Dimensions: Outer Diameter: 3.15" (80 mm) Thread Size: 3/4-16 Length: 3.15" (80 mm) Gasket OD: 2.48" (63 mm) Gasket ID: 2.20" (56 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P502046 Description: LUBE SPIN-ON COMBINATION Primary App: ISUZU, 8943381811 Dimensions: Outer Diameter: 4.88" (124 mm) Thread Size: 1 1/2-12 Length: 4.72" (120 mm) Gasket OD: 4.59" (116 mm) Gasket ID: 3.86" (98 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P502022 Description: LUBE SPIN-ON FULL FLOW Primary App: ATLAS COPCO, BMW, DAIHATSU, SUZUKI Dimensions: Outer Diameter: 3.15" (80 mm) Thread Size: 3/4-16 Length: 2.95" (75 mm) Gasket OD: 2.48" (63 mm) Gasket ID: 2.03" (52 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 20 Micron</p>		<p>Part Number: P502047 Description: LUBE SPIN-ON FULL FLOW Primary App: ISUZU 94314263 Dimensions: Outer Diameter: 2.68" (68 mm) Thread Size: M20 x 1.5 Length: 3.35" (85 mm) Gasket OD: 2.58" (66 mm) Gasket ID: 2.15" (55 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P502024 Description: LUBE SPIN-ON FULL FLOW Primary App: BRIGGS & STRATON 492932, SUZUKI, DAIHATSU, MAZDA Dimensions: Outer Diameter: 2.68" (68 mm) Thread Size: 3/4-16 Length: 2.56" (65 mm) Gasket OD: 2.56" (65 mm) Gasket ID: 2.20" (56 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 20 Micron</p>		<p>Part Number: P502048 Description: LUBE SPIN-ON FULL FLOW Primary App: HONDA 15400-PA6-305 Dimensions: Outer Diameter: 3.54" (90 mm) Thread Size: M22 x 1.5 Length: 3.18" (81 mm) Gasket OD: 2.52" (64 mm) Gasket ID: 2.27" (58 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P502025 Description: LUBE SPIN-ON FULL FLOW Primary App: DAIHATSU 1560187309000 Dimensions: Outer Diameter: 3.54" (90 mm) Thread Size: M 20 x 1.5 Length: 4.92" (125 mm)</p>		<p>Part Number: P502049 Description: LUBE SPIN-ON FULL FLOW Primary App: HONDA 15400-PR3-004 Dimensions: Outer Diameter: 3.15" (80 mm) Thread Size: M20 x 1.5 Length: 3.15" (80 mm) Gasket OD: 2.49" (63 mm) Gasket ID: 2.00" (51 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P502032 Description: LUBE SPIN-ON COMBINATION Primary App: ISUZU 8941432050 Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: 1-12 Length: 5.14" (131 mm) Gasket OD: 2.90" (74 mm) Gasket ID: 2.15" (55 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P502050 Description: LUBE SPIN-ON FULL FLOW Primary App: Honda 15400-PH1-F03 Dimensions: Outer Diameter: 2.99" (76 mm) Thread Size: M20 x 1.5 Length: 3.44" (88 mm)</p>

	<p>Part Number: P502051 Description: LUBE SPIN-ON FULL FLOW Primary App: HONDA 15400-PH1-014, 15400-PK1-003 Dimensions: Outer Diameter: 3.15" (80 mm) Thread Size: M20 x 1.5 Length: 3.94" (100 mm) Gasket OD: 2.48" (63 mm) Gasket ID: 1.81" (46 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 37 Micron</p>		<p>Part Number: P502063 Description: LUBE SPIN-ON FULL FLOW Primary App: MAZDA JEY014302 Dimensions: Outer Diameter: 2.68" (68 mm) Thread Size: M20 x 1.5 Length: 3.35" (85 mm) Gasket OD: 2.58" (66 mm) Gasket ID: 2.15" (55 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P502056 Description: LUBE SPIN-ON FULL FLOW Primary App: MAZDA 145623802, 145623802A, RF0323802 Dimensions: Outer Diameter: 3.16" (80 mm) Thread Size: M20 x 1.5 Length: 5.64" (143 mm) Gasket OD: 2.50" (64 mm) Gasket ID: 2.28" (58 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P502067 Description: LUBE SPIN-ON FULL FLOW Primary App: NISSAN, MAZDA, MITSUBISHI Dimensions: Outer Diameter: 2.68" (68 mm) Thread Size: M20 x 1.5 Length: 2.56" (65 mm) Gasket OD: 2.56" (65 mm) Gasket ID: 2.19" (56 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P502057 Description: LUBE SPIN-ON BYPASS Primary App: MAZDA FEY014302 Dimensions: Outer Diameter: 2.68" (68 mm) Thread Size: M20 x 1.5 Length: 3.35" (85 mm) Gasket OD: 2.56" (65 mm) Gasket ID: 3.03" (77 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P502068 Description: LUBE SPIN-ON COMBINATION Primary App: NISSAN 1520840L00, 1520820N00 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 5.08" (129 mm) Gasket OD: 2.87" (73 mm) Gasket ID: 2.00" (51 mm)</p>
	<p>Part Number: P502058 Description: LUBE SPIN-ON COMBINATION Primary App: DAIHATSU, ISUZU, MAZDA Dimensions: Outer Diameter: 3.58" (91 mm) Thread Size: M26 x 1.5 Length: 4.92" (125 mm) Gasket OD: 3.43" (87 mm) Gasket ID: 3.00" (76 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P502069 Description: LUBE SPIN-ON FULL FLOW Primary App: NISSAN 1520801B10 Dimensions: Outer Diameter: 3.15" (80 mm) Thread Size: 3/4-16 Length: 2.72" (69 mm) Gasket OD: 2.46" (62 mm) Gasket ID: 2.00" (51 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P502060 Description: LUBE SPIN-ON FULL FLOW Primary App: MAZDA TFY014302 Dimensions: Outer Diameter: 3.96" (101 mm) Thread Size: 1-12 Length: 4.92" (125 mm) Gasket OD: 3.92" (100 mm) Gasket ID: 3.48" (88 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 20 Micron</p>		<p>Part Number: P502070 Description: LUBE SPIN-ON FULL FLOW Primary App: NISSAN 1520853J00 Dimensions: Outer Diameter: 2.56" (65 mm) Thread Size: 3/4-16 Length: 3.35" (85 mm) Gasket OD: 2.46" (62 mm) Gasket ID: 2.06" (52 mm)</p>
	<p>Part Number: P502061 Description: LUBE SPIN-ON COMBINATION Primary App: MAZDA VSY114302 Dimensions: Outer Diameter: 4.02" (102 mm) Thread Size: M26 x 1.5 Length: 4.92" (125 mm) Gasket OD: 3.35" (85 mm) Gasket ID: 2.17" (55 mm) Efficiency 99% @ 37 Micron</p>		<p>Part Number: P502071 Description: LUBE SPIN-ON FULL FLOW Primary App: SUBARU 15208AA020 Dimensions: Outer Diameter: 3.15" (80 mm) Thread Size: M 20 x 1.5 Length: 2.76" (70 mm)</p>
	<p>Part Number: P502062 Description: LUBE SPIN-ON FULL FLOW Primary App: KIA Dimensions: Outer Diameter: 2.68" (68 mm) Thread Size: M20 x 1.5 Length: 2.56" (65 mm) Gasket OD: 2.58" (66 mm) Gasket ID: 2.17" (55 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P502072 Description: LUBE SPIN-ON FULL FLOW Primary App: MOTORCRAFT Dimensions: Outer Diameter: 3.64" (92 mm) Thread Size: M22 x 1.5 Length: 5.47" (139 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 20 Micron</p>
			<p>Part Number: P502075 Description: LUBE SPIN-ON FULL FLOW Primary App: Purflux LS152B Dimensions: Outer Diameter: 3.34" (86 mm) Thread Size: M18 x 1.5 Length: 3.46" (88 mm)</p>

	<p>Part Number: P502076 Description: LUBE SPIN-ON FULL FLOW Primary App: PEUGEOT 110951 Dimensions: Outer Diameter: 3.43" (87 mm) Thread Size: M20 x 1.5 Length: 3.50" (89 mm) Gasket OD: 3.33" (85 mm) Gasket ID: 2.81" (71 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P502092 Description: LUBE SPIN-ON FULL FLOW Primary App: PROTON Dimensions: Outer Diameter: 3.52" (89 mm) Thread Size: M20 x 1.5 Length: 3.23" (82 mm) Gasket OD: 2.44" (62 mm) Gasket ID: 1.98" (50 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P502080 Description: LUBE SPIN-ON FULL FLOW Primary App: MITSUBISHI 32B4000100 Dimensions: Outer Diameter: 4.02" (102 mm) Thread Size: 1-12 Length: 5.91" (150 mm) Gasket OD: 3.91" (99 mm) Gasket ID: 3.46" (88 mm) Relief Valve Setting: 13-19 PSI (.9-1.3 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 20 Micron</p>		<p>Part Number: P502093 Description: LUBE SPIN-ON COMBINATION Primary App: CATERPILLAR 5I7950 Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: M32 x 1.5 Length: 8.77" (223 mm) Gasket OD: 4.02" (102 mm) Gasket ID: 3.62" (92 mm) Relief Valve Setting: 25-31 PSI (1.80-2.20 Bar) Stand Pipe: Yes Y/N Anti Drain Valve: Yes Y/N Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P502081 Description: LUBE SPIN-ON FULL FLOW Primary App: MITSUBISHI 3754001101 Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: 1 1/2-12 Length: 10.42" (265 mm) Gasket OD: 4.02" (102 mm) Gasket ID: 3.42" (87 mm) Efficiency 50% @ 16 Micron</p>		<p>Part Number: P502098 Description: LUBE SPIN-ON FULL FLOW Primary App: Ford Dimensions: Outer Diameter: 3.15" (80 mm) Thread Size: M 20 x 1.5 Length: 2.95" (75 mm)</p>
	<p>Part Number: P502083 Description: LUBE SPIN-ON FULL FLOW Primary App: MITSUBISHI 3743802400 Dimensions: Outer Diameter: 4.45" (113 mm) Thread Size: 1 1/8-16 Length: 6.73" (171 mm) Gasket OD: 2.93" (74 mm) Gasket ID: 2.54" (65 mm) Efficiency 99% @ 48 Micron</p>		<p>Part Number: P502107 Description: LUBE SPIN-ON FULL FLOW Primary App: ECHLIN OF18 Dimensions: Outer Diameter: 3.00" (76 mm) Thread Size: 3/4-16 Length: 3.46" (88 mm) Gasket OD: 2.80" (71 mm) Gasket ID: 2.50" (64 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P502085 Description: LUBE SPIN-ON FULL FLOW Primary App: MITSUBISHI 32A4000100 Dimensions: Outer Diameter: 4.21" (107 mm) Thread Size: 1-12 Length: 3.96" (101 mm) Gasket OD: 3.90" (99 mm) Gasket ID: 3.46" (88 mm) Relief Valve Setting: 18-24 PSI (1.30-1.70 Bar) Anti Drain Valve: Yes Efficiency 50% @ 20 Micron</p>		<p>Part Number: P502113 Description: FUEL CARTRIDGE Primary App: MITSUBISHI 3166201031 Dimensions: Outer Diameter: 2.83" (72 mm) Inner Diameter: 0.43" (11 mm) Length: 1.73" (44 mm) Efficiency 99% @ 30 Micron</p>
	<p>Part Number: P502088 Description: LUBE SPIN-ON FULL FLOW Primary App: NISSAN 15201Z9000, 15201Z9002, 15201Z9003 Dimensions: Outer Diameter: 4.33" (110 mm) Thread Size: 1 1/8-16 Length: 6.73" (171 mm) Gasket OD: 3.90" (99 mm) Gasket ID: 3.46" (88 mm) Efficiency 50% @ 16 Micron</p>		<p>Part Number: P502114 Description: FUEL CARTRIDGE Primary App: MITSUBISHI ME046010 Dimensions: Outer Diameter: 3.62" (92 mm) Inner Diameter: 0.73" (19 mm) Length: 5.51" (140 mm) Efficiency 99% @ 30 Micron</p>
	<p>Part Number: P502089 Description: LUBE SPIN-ON FULL FLOW Primary App: NISSAN Dimensions: Outer Diameter: 4.33" (110 mm) Thread Size: 3/4-16 Length: 4.82" (123 mm) Gasket OD: 2.44" (62 mm) Gasket ID: 2.95" (75 mm)</p>		<p>Part Number: P502115 Description: FUEL CARTRIDGE Primary App: MITSUBISHI MA125373 Dimensions: Outer Diameter: 1.38" (35 mm) Inner Diameter: 1.73" (44 mm) Length: 0.45" (11 mm) Efficiency 99% @ 30 Micron</p>
	<p>Part Number: P502091 Description: LUBE SPIN-ON FULL FLOW Primary App: GM 5576054, AC PF35 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 13/16-16 Length: 5.47" (139 mm)</p>		<p>Part Number: P502116 Description: FUEL CARTRIDGE Primary App: MITSUBISHI ME971550, ME971553 Dimensions: Outer Diameter: 3.58" (91 mm) Inner Diameter: 0.59" (15 mm) Length: 5.43" (138 mm) Efficiency 99% @ 30 Micron</p>
	<p>Part Number: P502091 Description: LUBE SPIN-ON FULL FLOW Primary App: GM 5576054, AC PF35 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 13/16-16 Length: 5.47" (139 mm)</p>		<p>Part Number: P502118 Description: FUEL CARTRIDGE Primary App: TOYOTA 0423456010 Dimensions: Outer Diameter: 2.95" (75 mm) Inner Diameter: 0.63" (16 mm) Length: 2.60" (66 mm) Efficiency 99% @ 30 Micron</p>



Part Number: **P502131**
 Description: **FUEL CARTRIDGE**
 Primary App: MANN B405C
 Dimensions: Outer Diameter: 4.25" (108 mm)
 Inner Diameter: 0.78" (20 mm)
 Length: 6.73" (171 mm)
 Efficiency 50% @ 20 Micron



Part Number: **P502132**
 Description: **FUEL CARTRIDGE**
 Primary App: MANN EK405, P1018/1
 Dimensions: Outer Diameter: 3.86" (98 mm)
 Inner Diameter: 0.87" (22 mm)
 Length: 6.35" (161 mm)
 Gasket OD: 1.50" (38 mm)
 Gasket ID: 0.70" (18 mm)
 Efficiency 99% @ 30 Micron



Part Number: **P502133**
 Description: **FUEL CARTRIDGE**
 Primary App: YANMAR
 Dimensions: Outer Diameter: 1.38" (35 mm)
 Inner Diameter: 0.47" (12 mm)
 Length: 3.81" (97 mm)
 Efficiency 50% @ 12 Micron



Part Number: **P502134**
 Description: **FUEL CARTRIDGE**
 Primary App: YANMAR 10450055710
 Dimensions: Outer Diameter: 1.38" (35 mm)
 Inner Diameter: 0.43" (11 mm)
 Length: 2.44" (62 mm)
 Efficiency 50% @ 16 Micron



Part Number: **P502135**
 Description: **FUEL CARTRIDGE**
 Primary App: YANMAR 10599155710
 Dimensions: Outer Diameter: 1.38" (35 mm)
 Inner Diameter: 0.47" (12 mm)
 Length: 3.43" (87 mm)
 Efficiency 50% @ 12 Micron



Part Number: **P502136**
 Description: **FUEL CARTRIDGE**
 Primary App: CAT 5S7645
 Dimensions: Outer Diameter: 1.12" (28 mm)
 Inner Diameter: G 8-36" (G 8-36 mm)



Part Number: **P502138**
 Description: **FUEL CARTRIDGE**
 Primary App: KUBOTA 15231-43563, 15231-43560
 Dimensions: Outer Diameter: 1.14" (29 mm)
 Inner Diameter: 0.51" (13 mm)
 Length: 3.35" (85 mm)
 Efficiency 50% @ 12 Micron



Part Number: **P502142**
 Description: **FUEL/WATER SEPARATOR SPIN-ON**
 Primary App: MITSUBISHI MB433425, TCM 20801-02131
 Dimensions: Outer Diameter: 3.16" (80 mm)
 Thread Size: M20 x 1.5
 Length: 4.72" (120 mm)
 Gasket OD: 3.06" (78 mm)
 Gasket ID: 2.48" (63 mm)
 Efficiency 50% @ 10 Micron



Part Number: **P502143**
 Description: **FUEL/WATER SEPARATOR SPIN-ON**
 Primary App: MITSUBISHI 3446200300
 Dimensions: Outer Diameter: 3.15" (80 mm)
 Thread Size: M20 x 1.5
 Length: 3.93" (100 mm)
 Gasket OD: 2.76" (70 mm)
 Gasket ID: 2.52" (64 mm)
 Efficiency 50% @ 10 Micron



Part Number: **P502149**
 Description: **FUEL/WATER SEPARATOR SPIN-ON**
 Primary App: DAIHATSU 2330387308000
 Dimensions: Outer Diameter: 3.90" (99 mm)
 Thread Size: M20 x 1.5
 Length: 5.43" (138 mm)
 Gasket OD: 2.81" (71 mm)
 Gasket ID: 2.19" (56 mm)
 F: 2.00" (51 mm)
 Efficiency 50% @ 10 Micron



Part Number: **P502157**
 Description: **FUEL/WATER SEPARATOR SPIN-ON**
 Primary App: MAZDA
 Dimensions: Outer Diameter: 3.72" (95 mm)
 Thread Size: M20 x 1.5
 Length: 4.72" (120 mm)
 Gasket OD: 2.81" (71 mm)
 Gasket ID: 1.97" (50 mm)
 Efficiency 50% @ 10 Micron



Part Number: **P502158**
 Description: **FUEL/WATER SEPARATOR SPIN-ON**
 Primary App: MAZDA 145623570A
 Dimensions: Outer Diameter: 3.72" (95 mm)
 Thread Size: M20 x 1.5
 Length: 5.17" (131 mm)
 Gasket OD: 3.62" (92 mm)
 Gasket ID: 2.81" (71 mm)
 F: 2.00" (51 mm)
 Efficiency 50% @ 10 Micron



Part Number: **P502161**
 Description: **FUEL CARTRIDGE**
 Primary App: YANMAR 12910055650, KUBOTA 15521-43160
 Dimensions: Outer Diameter: 1.97" (50 mm)
 Inner Diameter: 0.79" (20 mm)
 Length: 3.50" (89 mm)
 Efficiency 50% @ 16 Micron




















Part Number: **P502163**
 Description: **FUEL/WATER SEPARATOR SPIN-ON**
 Primary App: NISSAN 16403Z9000, 16403Z9005
 Dimensions: Outer Diameter: 3.15" (80 mm)
 Thread Size: 3/4-16
 Length: 4.50" (114 mm)
 Gasket OD: 2.50" (64 mm)
 Gasket ID: 2.11" (54 mm)
 Efficiency 50% @ 10 Micron














Part Number: **P502166**
 Description: **FUEL CARTRIDGE**
 Primary App: YANMAR 12455055700, KUBOTA 16271-43560
 Dimensions: Outer Diameter: 1.38" (35 mm)
 Inner Diameter: 0.43" (11 mm)
 Length: 3.39" (86 mm)
 Efficiency 50% @ 16 Micron



Part Number: **P502167**
 Description: **FUEL/WATER SEPARATOR SPIN-ON**
 Primary App: NISSAN 16405-01170
 Dimensions: Outer Diameter: 3.15" (80 mm)
 Thread Size: 3/4-16
 Length: 6.89" (175 mm)
 Gasket OD: 2.59" (66 mm)
 Gasket ID: 2.00" (51 mm)
 F: 2.00" (51 mm)
 Efficiency 50% @ 10 Micron

	<p>Part Number: P502169 Description: FUEL CARTRIDGE Primary App: LEYLAND ABU9642, MAZDA SL07-23570 Dimensions: Outer Diameter: 3.44" (87 mm) Inner Diameter: 0.75" (19 mm) Length: 3.41" (87 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P502186 Description: LUBE CARTRIDGE FULL FLOW Primary App: TOYOTA Dimensions: Outer Diameter: 4.84" (123 mm) Inner Diameter: 0.79" (20 mm) Length: 5.43" (138 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P502170 Description: HYDRAULIC CARTRIDGE Primary App: HITACHI 3502410N Dimensions: Outer Diameter: 3.54" (90 mm) Inner Diameter: 1.93" (49 mm) Length: 10.91" (277 mm) ID Width: 1.83" (46 mm)</p>		<p>Part Number: P502189 Description: LUBE CARTRIDGE FULL FLOW Primary App: HINO Dimensions: Outer Diameter: 3.35" (85 mm) Inner Diameter: 0.90" (23 mm) Length: 5.08" (129 mm)</p>
	<p>Part Number: P502172 Description: HYDRAULIC CARTRIDGE Primary App: HITACHI 4159320 Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 1.41" (36 mm) Length: 4.45" (113 mm)</p>		<p>Part Number: P502190 Description: LUBE CARTRIDGE FULL FLOW Primary App: HINO 15607-1351 Dimensions: Outer Diameter: 4.80" (122 mm) Inner Diameter: 0.67" (17 mm) Length: 8.62" (219 mm) Efficiency 50% @ 5 Micron</p>
	<p>Part Number: P502177 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: FSA FF2028, RYCO Z169A Dimensions: Outer Diameter: 3.15" (80 mm) Thread Size: 3/4-16 Length: 3.31" (84 mm) Gasket OD: 2.48" (63 mm) Gasket ID: 1.76" (45 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P502191 Description: LUBE CARTRIDGE FULL FLOW Primary App: HINO 156071341, 15607-1340 Dimensions: Outer Diameter: 4.80" (122 mm) Inner Diameter: 0.67" (17 mm) Length: 9.80" (249 mm) Efficiency 50% @ 5 Micron</p>
	<p>Part Number: P502178 Description: HYDRAULIC CARTRIDGE Primary App: CAT 3S3875 Dimensions: Outer Diameter: 3.36" (85 mm) Inner Diameter: 1.81" (46 mm) Length: 9.06" (230 mm)</p>		<p>Part Number: P502193 Description: LUBE CARTRIDGE FULL FLOW Primary App: ISUZU Dimensions: Outer Diameter: 2.85" (72 mm) Inner Diameter: 1.30" (33 mm) Length: 5.39" (137 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P502179 Description: LUBE CARTRIDGE FULL FLOW Primary App: MITSUBISHI 3134012030 Dimensions: Outer Diameter: 3.62" (92 mm) Inner Diameter: 0.69" (18 mm) Length: 4.33" (110 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P502194 Description: LUBE CARTRIDGE FULL FLOW Primary App: ISUZU 13240085, Dimensions: Outer Diameter: 3.35" (85 mm) Inner Diameter: 1.57" (40 mm) Length: 5.63" (143 mm) Efficiency 50% @ 16 Micron</p>
	<p>Part Number: P502180 Description: LUBE CARTRIDGE FULL FLOW Primary App: MITSUBISHI 3144012030 Dimensions: Outer Diameter: 3.62" (92 mm) Inner Diameter: 0.69" (18 mm) Length: 6.30" (160 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P502196 Description: FUEL CARTRIDGE Primary App: ISUZU 13240045 Dimensions: Outer Diameter: 2.95" (75 mm) Inner Diameter: 0.75" (19 mm) Length: 6.97" (177 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P502183 Description: LUBE CARTRIDGE FULL FLOW Primary App: MITSUBISHI ME021073 Dimensions: Outer Diameter: 3.97" (101 mm) Inner Diameter: 1.20" (30 mm) Length: 9.21" (234 mm)</p>		<p>Part Number: P502200 Description: LUBE CARTRIDGE FULL FLOW Primary App: ISUZU 1132401170 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 1.34" (34 mm) Length: 7.60" (193 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P502184 Description: LUBE CARTRIDGE FULL FLOW Primary App: MITSUBISHI 68937310012 Dimensions: Outer Diameter: 4.48" (114 mm) Inner Diameter: 2.84" (72 mm) Length: 10.83" (275 mm) Efficiency 50% @ 16 Micron</p>		<p>Part Number: P502202 Description: LUBE CARTRIDGE FULL FLOW Primary App: ISUZU 1878103720 Dimensions: Outer Diameter: 3.54" (90 mm) Inner Diameter: 1.92" (49 mm) Length: 4.09" (104 mm) Gasket OD: 1.93" (49 mm) Efficiency 50% @ 20 Micron</p>

	<p>Part Number: P502203 Description: LUBE CARTRIDGE FULL FLOW Primary App: NISSAN 1520876225 Dimensions: Outer Diameter: 3.11" (79 mm) Inner Diameter: 1.56" (40 mm) Length: 5.35" (136 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P502226 Description: FUEL CARTRIDGE Primary App: ISUZU 1132401940 Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.07" (27 mm) Length: 3.72" (95 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P502205 Description: LUBE CARTRIDGE FULL FLOW Primary App: NISSAN 1527499025 Dimensions: Outer Diameter: 4.33" (110 mm) Inner Diameter: 2.04" (52 mm) Length: 8.11" (206 mm) Efficiency 50% @ 16 Micron</p>		<p>Part Number: P502231 Description: HYDRAULIC SPIN-ON Primary App: Altas Copco 1202804000 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: M20 x 1.5 Length: 8.40" (214 mm) Relief Valve Setting: 14.21 PSI (0.98 Bar)</p>
	<p>Part Number: P502206 Description: LUBE CARTRIDGE FULL FLOW Primary App: NISSAN 1527499128 Dimensions: Outer Diameter: 3.94" (100 mm) Inner Diameter: 1.56" (40 mm) Length: 7.19" (183 mm) Efficiency 50% @ 16 Micron</p>		<p>Part Number: P502233 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: MITSUBISHI ME150631 Dimensions: Outer Diameter: 4.21" (107 mm) Thread Size: 1 1/8-16 Length: 7.88" (200 mm)</p>
	<p>Part Number: P502215 Description: HYDRAULIC CARTRIDGE Primary App: KOBELCO R36P0019 Dimensions: Outer Diameter: 1.67" (42 mm) Inner Diameter: 0.94" (24 mm) Length: 3.31" (84 mm)</p>		<p>Part Number: P502234 Description: LUBE SPIN-ON FULL FLOW Primary App: Mazda WL51-14-302 Dimensions: Outer Diameter: 3.94" (100 mm) Thread Size: M 24 x 1.5 Length: 4.72" (120 mm)</p>
	<p>Part Number: P502222 Description: LUBE SPIN-ON FULL FLOW Primary App: FIAT 74741272 Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: M30 x 2 Length: 5.62" (143 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Anti Drain Valve: Yes Y/N Efficiency 50% @ 16 Micron</p>		<p>Part Number: P502235 Description: LUBE SPIN-ON FULL FLOW Primary App: Mazda 23390-64480 Dimensions: Outer Diameter: 3.54" (90 mm) Thread Size: 3/4" x 16 Length: 5.12" (130 mm)</p>
	<p>Part Number: P502223 Description: LUBE CARTRIDGE FULL FLOW Primary App: MANN H20211 Dimensions: Outer Diameter: 7.64" (194 mm) Inner Diameter: 4.65" (118 mm) Length: 6.71" (170 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P502244 Description: HYDRAULIC STRAINER Primary App: Hitachi 4210224 Dimensions: Outer Diameter: 5.90" (150 mm) Inner Diameter: 3.43" (87 mm) Length: 5.32" (135 mm)</p>
	<p>Part Number: P502224 Description: LUBE CARTRIDGE FULL FLOW Primary App: MANN H20211 Dimensions: Outer Diameter: 7.64" (194 mm) Inner Diameter: 4.65" (118 mm) Length: 6.71" (170 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P502245 Description: HYDRAULIC CARTRIDGE Primary App: Hitachi 4225846 Dimensions: Outer Diameter: 3.50" (90 mm) Inner Diameter: 1.92" (49 mm) Length: 13.50" (344 mm)</p>
	<p>Part Number: P502224 Description: HYDRAULIC SPIN-ON Primary App: FORD FONNB486BB, NEW HOLLAND 82005016 Dimensions: Outer Diameter: 5.35" (136 mm) Thread Size: 1 3/4-16 Length: 9.57" (243 mm) Gasket OD: 4.29" (109 mm) Gasket ID: 3.90" (99 mm) Relief Valve Setting: 18-24 PSI (1.30-1.70 Bar)</p>		<p>Part Number: P502269 Description: HYDRAULIC CARTRIDGE Primary App: Hitachi 4448401 Dimensions: Outer Diameter: 4.39" (112 mm) Inner Diameter: 2.24" (57 mm) Length: 19.05" (484 mm)</p>
	<p>Part Number: P502225 Description: LUBE CARTRIDGE FULL FLOW Primary App: LEYLAND 11K243 Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.91" (49 mm) Length: 7.05" (179 mm) Efficiency 50% @ 16 Micron</p>		<p>Part Number: P502270 Description: HYDRAULIC CARTRIDGE Primary App: HITACHI 4448402, 4443773 Dimensions: Outer Diameter: 6.14" (156 mm) Inner Diameter: 3.86" (98 mm) Length: 16.97" (431 mm)</p>
			<p>Part Number: P502304 Description: FUEL SPIN-ON SECONDARY Primary App: Detroit 23518530 Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: 13/16-12 Length: 10.43" (265 mm)</p>
			<p>Part Number: P502329 Description: FUEL IN-LINE Primary App: Suzuki 1541080000 Dimensions: Outer Diameter: 2.36" (60 mm) Height: 3.81" (97 mm)</p>













<p>Part Number: P502332 Description: LUBE CARTRIDGE Primary App: Hino 15607-1080 Dimensions: Outer Diameter: 4.72" (120 mm) Length: 8.07" (205 mm)</p>	<p>Part Number: P502364 Description: LUBE SPIN-ON COMBINATION Primary App: HINO 156072190 Dimensions: Outer Diameter: 4.72" (120 mm) Thread Size: 1 1/2-16 Length: 8.27" (210 mm)</p>
<p>Part Number: P502352 Description: LUBE CARTRIDGE Primary App: Isuzu 1-13240234-0 Dimensions: Outer Diameter: 5.11" (130 mm) Length: 7.46" (190 mm) Inner Diameter: 0.67" (17 mm)</p>	<p>Part Number: P502365 Description: LUBE CARTRIDGE Primary App: ISUZU 1132402170 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 1.92" (49 mm) Length: 7.05" (179 mm)</p>
<p>Part Number: P502353 Description: LUBE CARTRIDGE Primary App: ISUZU 1-13240233-0 Dimensions: Outer Diameter: 4.05" (103 mm) Length: 7.04" (179 mm)</p>	<p>Part Number: P502367 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: Marine Caterpillar 1P2299 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1" - 14 Length: 6.86" (174 mm)</p>
<p>Part Number: P502355 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: Racor R60-PHS-30 Dimensions: Outer Diameter: 4.24" (108 mm) Thread Size: 7/8 - 14 Length: 4.62" (118 mm)</p>	<p>Part Number: P502368 Description: LUBE CARTRIDGE KIT Primary App: MITSUBISHI ME356701 (ME354630 + ME354632) Dimensions: Outer Diameter: 4.92" (125 mm) Inner Diameter: 0.61" (16 mm) Length: 8.20" (208 mm)</p>
<p>Part Number: P502356 Description: FUEL CARTRIDGE Primary App: Yanmar 41650502340 Dimensions: Outer Diameter: 4.33" (110 mm) Inner Diameter: 2.04" (52 mm) Length: 7.51" (191 mm)</p>	<p>Part Number: P502369 Description: LUBE CARTRIDGE FULL FLOW Primary App: Mitsubishi ME354630 Dimensions: Outer Diameter: 4.92" (125 mm) Inner Diameter: 2.28" (58 mm) Length: 5.64" (144 mm)</p>
<p>Part Number: P502357 Description: HYDRAULIC CARTRIDGE Primary App: Yanmar 41650501140 Dimensions: Outer Diameter: 5.03" (128 mm) Inner Diameter: 2.22" (56 mm) Length: 10.39" (264 mm)</p>	<p>Part Number: P502370 Description: LUBE CARTRIDGE Primary App: Mitsubishi ME354632 Dimensions: Outer Diameter: 4.92" (125 mm) Inner Diameter: 0.61" (16 mm) Length: 6.33" (161 mm)</p>
<p>Part Number: P502358 Description: LUBE CARTRIDGE Primary App: Yanmar 14861635522 Dimensions: Outer Diameter: 4.61" (117 mm) Inner Diameter: 1.89" (48 mm) Length: 8.70" (221 mm)</p>	<p>Part Number: P502371 Description: FUEL CARTRIDGE Primary App: MITSUBISHI ME165323 Dimensions: Outer Diameter: 3.70" (94 mm) Inner Diameter: 0.86" (22 mm) Length: 5.11" (130 mm)</p>
<p>Part Number: P502359 Description: LUBE SPIN-ON BYPASS Primary App: Yanmar 14863335400 Dimensions: Outer Diameter: 4.92" (125 mm) Thread Size: 1 3/8-16 Length: 9.84" (250 mm)</p>	<p>Part Number: P502373 Description: LUBE CARTRIDGE Primary App: Hino 15607-1360 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 1.92" (49 mm) Length: 4.05" (103 mm)</p>
<p>Part Number: P502360 Description: FUEL CARTRIDGE Primary App: Yanmar 10537055710 Dimensions: Outer Diameter: 1.15" (29 mm) Inner Diameter: 0.30" (8 mm) Length: 3.31" (84 mm)</p>	<p>Part Number: P502374 Description: LUBE SPIN-ON COMBINATION Primary App: Isuzu 8-97019468-0 Dimensions: Outer Diameter: 4.01" (102 mm) Thread Size: 1" - 12 Length: 5.90" (150 mm) Relief Valve Setting: Yes Anti Drain Valve: Yes</p>
<p>Part Number: P502361 Description: LUBE SPIN-ON BYPASS Primary App: Yanmar 12408535112 Dimensions: Outer Diameter: 3.15" (80 mm) Thread Size: M20 X 1.5</p>	<p>Part Number: P502376 Description: LUBE SPIN-ON COMBINATION Primary App: Isuzu 8-97116126-0 Dimensions: Outer Diameter: 4.33" (110 mm) Thread Size: M36 x 2 Length: 6.91" (176 mm) Relief Valve Setting: Yes</p>
<p>Part Number: P502362 Description: FUEL CARTRIDGE Primary App: Yanmar 41650502320 Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 1.38" (35 mm) Length: 3.50" (89 mm)</p>	<p>Part Number: P502377 Description: FUEL CARTRIDGE Primary App: Mitsubishi ME305031 Dimensions: Outer Diameter: 3.70" (94 mm) Inner Diameter: 1.02" (26 mm) Length: 5.11" (130 mm)</p>
<p>Part Number: P502363 Description: LUBE SPIN-ON FULL FLOW Primary App: Hitachi 4658521, 4448336, 4484495, 4622562 Dimensions: Outer Diameter: 4.72" (120 mm) Thread Size: 1 1/2-12 Length: 8.26" (210 mm)</p>	

<p>Part Number: P502378 Description: FUEL CARTRIDGE Primary App: MITSUBISHI ME222135 Dimensions: Outer Diameter: 3.70" (94 mm) Inner Diameter: 1.02" (26 mm) Length: 3.34" (85 mm)</p>	<p>Part Number: P502391 Description: FUEL CARTRIDGE Primary App: Hino 23401-1690 Dimensions: Outer Diameter: 3.58" (91 mm) Inner Diameter: 0.75" (19 mm) Length: 5.13" (131 mm)</p>
<p>Part Number: P502380 Description: LUBE CARTRIDGE Primary App: AIRMAN 4354100100 Dimensions: Outer Diameter: 1.61" (41 mm) Inner Diameter: 0.97" (25 mm) Length: 1.29" (33 mm) Efficiency @ 99% Percent</p>	<p>Part Number: P502392 Description: FUEL BOX PRIMARY Primary App: DEUTZ 0319822, VOLVO 14514238 Dimensions: Length: 3.46" (88 mm) Depth: 3.46" (88 mm) Height: 2.00" (51 mm)</p>
<p>Part Number: P502381 Description: FUEL SPIN ON Primary App: Komatsu 600-311-3510 Dimensions: Outer Diameter: 4.64" (118 mm) Thread Size: 1 1/4-12 Length: 11.25" (286 mm)</p>	<p>Part Number: P502401 Description: LUBE SPIN-ON FULL FLOW Primary App: Fleetguard LF3325 Dimensions: Outer Diameter: 4.64" (118 mm) Thread Size: 1 1/2-12 Length: 11.25" (286 mm)</p>
<p>Part Number: P502382 Description: HYDRAULIC SPIN-ON Primary App: HITACHI 4205684 Dimensions: Outer Diameter: 4.99" (127 mm) Thread Size: M48 x 2 Length: 6.85" (174 mm)</p>	<p>Part Number: P502403 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: AM version for MTU 0020922801 Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: M32 x 1.5 Length: 10.31" (262 mm)</p>
<p>Part Number: P502383 Description: FUEL CARTRIDGE Primary App: MANN B405C Dimensions: Outer Diameter: 4.25" (108 mm) Inner Diameter: 0.83" (21 mm) Length: 6.46" (164 mm)</p>	<p>Part Number: P502404 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: MTU 0020920601, 8690920031 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 5.72" (146 mm)</p>
<p>Part Number: P502384 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: YANMAR 127695-55630 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-14 Length: 6.85" (174 mm)</p>	<p>Part Number: P502405 Description: LUBE CARTRIDGE Primary App: MITSUBISHI 054238 Dimensions: Outer Diameter: 5.12" (130 mm) Inner Diameter: 0.62" (16 mm) Length: 6.37" (162 mm)</p>
<p>Part Number: P502385 Description: LUBE SPIN-ON FULL FLOW Primary App: YANMAR 126677-35400 Dimensions: Outer Diameter: 4.92" (125 mm) Thread Size: 1 1/2-12 Length: 9.84" (250 mm)</p>	<p>Part Number: P502406 Description: FUEL CARTRIDGE Primary App: YANMAR 17108155910 Dimensions: Inner Diameter: 0.43" (11 mm) Outer Diameter: 1.38" (35 mm) Length: 1.85" (47 mm)</p>
<p>Part Number: P502386 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: YANMAR 129470-55703 Dimensions: Outer Diameter: 3.14" (80 mm) Thread Size: M20 x 1.5 Length: 2.95" (75 mm)</p>	<p>Part Number: P502407 Description: HYDRAULIC SPIN-ON Primary App: Renault VI 5010372044 Dimensions: Outer Diameter: 3.55" (90 mm) Thread Size: M20 x 1.5 Length: 2.60" (66 mm)</p>
<p>Part Number: P502387 Description: LUBE CARTRIDGE Primary App: YANMAR 118093-73780 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 1.93" (49 mm) Length: 7.08" (180 mm)</p>	<p>Part Number: P502408 Description: LUBE SPIN-ON FULL FLOW Primary App: Mitsubishi ME656613 Dimensions: Outer Diameter: 3.77" (96 mm) Thread Size: 3/4-16 Length: 3.93" (100 mm)</p>
<p>Part Number: P502389 Description: LUBE CARTRIDGE Primary App: Hino 15607-2260 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 1.93" (49 mm) Length: 7.08" (180 mm)</p>	<p>Part Number: P502411 Description: FUEL CARTRIDGE Primary App: Hilco LP114A3786P03 Dimensions: Inner Diameter: 2.63" (67 mm) Outer Diameter: 6.09" (155 mm) Length: 17.85" (454 mm)</p>
<p>Part Number: P502390 Description: LUBE CARTRIDGE Primary App: Hino 15607-2281 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 0.67" (17 mm) Length: 8.14" (207 mm)</p>	<p>Part Number: P502412 Description: FUEL CARTRIDGE Primary App: Hilco PL71805CC Dimensions: Inner Diameter: 2.63" (67 mm) Outer Diameter: 6.09" (155 mm) Length: 17.85" (454 mm)</p>

<p>Part Number: P502413 Description: LUBE SPIN-ON FULL FLOW Primary App: Hino 15607-2250 Dimensions: Outer Diameter: 4.01" (102 mm) Thread Size: 1" x 12 Length: 5.90" (150 mm) Anti Drain Valve: Yes</p>	<p>Part Number: P503370 Description: AIR SAFETY Primary App: Hino 17801-3370 Dimensions: Outer Diameter: 4.37" (111 mm) Length: 12.75" (324 mm)</p>
<p>Part Number: P502414 Description: FUEL CARTRIDGE Primary App: Hino 23304-78110 Dimensions: Outer Diameter: 4.11" (104 mm) Inner Diameter: 1.14" (29 mm) Length: 4.35" (111 mm)</p>	<p>Part Number: P505061 Description: AIR PRIMARY Primary App: Mazda SLA213Z40 Dimensions: Outer Diameter: 7.75" (197 mm) Length: 8.09" (205 mm)</p>
<p>Part Number: P502418 Description: FUEL SPIN ON Primary App: Nissan 16405-V5710 Dimensions: Outer Diameter: 3.01" (77 mm) Thread Size: 3/4-16 Length: 5.31" (135 mm)</p>	<p>Part Number: P505951 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: ISUZU ENGINES Dimensions: Outer Diameter: 3.24" (82 mm) Thread Size: 3/4-16 Length: 3.20" (81 mm)</p>
<p>Part Number: P502420 Description: FUEL CARTRIDGE Primary App: PERKINS 26550005 Dimensions: Outer Diameter: 3.34" (85 mm) Inner Diameter: 0.75" (19 mm) Length: 2.80" (71 mm)</p>	<p>Part Number: P505957 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: Volvo 11110474 Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: 1-14 Length: 8.03" (204 mm)</p>
<p>Part Number: P502421 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: Fleetguard FS19636 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: M20 x 1.5 Length: 7.37" (187 mm)</p>	<p>Part Number: P505960 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: Mitsubishi ME132526 Dimensions: Outer Diameter: 3.86" (98 mm) Thread Size: M20 X 1.5 Length: 5.46" (139 mm)</p>
<p>Part Number: P502425 Description: FUEL CARTRIDGE Primary App: S234011682 Dimensions: Outer Diameter: 3.54" (90 mm) Inner Diameter: 0.74" (19 mm) Length: 4.33" (110 mm)</p>	<p>Part Number: P505973 Description: FUEL CARTRIDGE Primary App: TOYOTA HILUX Dimensions: Outer Diameter: 3.28" (83 mm) Inner Diameter: 0.35" (9 mm) Length: 3.00" (76 mm)</p>
<p>Part Number: P502426 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: HINO FD8J/FG8J/GH8J(9/2006-), MKB37(E-4) S234011730 Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.07" (27 mm) Length: 7.44" (189 mm)</p>	<p>Part Number: P505976 Description: AIR PRIMARY Primary App: Perkins 135326205 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 3.23" (82 mm) Length: 10.11" (257 mm)</p>
<p>Part Number: P502427 Description: FUEL CARTRIDGE Primary App: Isuzu 8980370110 Dimensions: Outer Diameter: 3.93" (100 mm) Inner Diameter: 0.46" (12 mm) Length: 3.77" (96 mm)</p>	<p>Part Number: P505978 Description: LUBE CARTRIDGE Primary App: NISSAN 15208-2W200 Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 0.93" (24 mm) Length: 4.02" (102 mm)</p>
<p>Part Number: P502443 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 2086071122 Dimensions: Outer Diameter: 7.09" (180 mm) Inner Diameter: 4.33" (110 mm) Length: 7.87" (200 mm)</p>	<p>Part Number: P505979 Description: AIR PANEL Primary App: Toyota 1780130040 Dimensions: Width: 9.02" (229 mm) Depth: 2.05" (52 mm) Length: 12.17" (309 mm)</p>
<p>Part Number: P502444 Description: LUBE SPIN-ON FULL FLOW Primary App: HYUNDAI 26312-83C10 Dimensions: Outer Diameter: 5.35" (136 mm) Thread Size: M46 x 2 Length: 10.03" (255 mm) Gasket OD: 4.30" (109 mm) Gasket ID: 3.92" (100 mm)</p>	<p>Part Number: P505981 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: Cummins 3843447 Dimensions: Outer Diameter: 3.72" (94 mm) Length: 3.79" (96 mm)</p>
<p>Part Number: P503360 Description: AIR PRIMARY Primary App: Hino 17801-3360 Dimensions: Outer Diameter: 8.39" (213 mm) Length: 13.22" (336 mm)</p>	<p>Part Number: P505982 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: Volvo 20514654 Dimensions: Outer Diameter: 3.79" (96 mm) Length: 5.59" (142 mm)</p>
	<p>Part Number: P505983 Description: AIR PANEL Primary App: Toyota Landcruiser 4WD 17801-51010 Dimensions: Width: 12.08" (307 mm) Depth: 2.04" (52 mm) Height: 8.97" (228 mm)</p>



<p>Part Number: P505988 Description: LUBE CARTRIDGE Primary App: LUBE FLTR CART TOYOTA L/L/C V8 Dimensions: Outer Diameter: 2.75" (70 mm) Inner Diameter: 1.10" (28 mm) Length: 4.56" (116 mm)</p>	 <p>Part Number: P520620 Description: AIR PRIMARY Primary App: TIPTON, FLEETGUARD AF1907M Dimensions: Outer Diameter: 10.41" (264 mm) Inner Diameter: 6.03" (153 mm) Length: 26.00" (660 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 8.12" (206 mm)</p>
<p>Part Number: P505997 Description: AIR PRIMARY Primary App: KUBOTA ENGINES Dimensions: Outer Diameter: 4.72" (120 mm) Inner Diameter: 2.08" (53 mm) Height: 1.82" (46 mm) Efficiency @ 99%</p>	 <p>Part Number: P520925 Description: AIR PRIMARY Primary App: DONALDSON EBB09, FORD F0HZ9601A, MTRCRFT FA1078 Dimensions: Outer Diameter: 7.32" (186 mm) Inner Diameter: 5.40" (137 mm) Length: 23.00" (584 mm) Bolt Hole Diameter: 0.39" (10 mm) Gasket ID: 6.56" (167 mm)</p>
<p>Part Number: P505998 Description: AIR PRIMARY, RADIALSEAL Primary App: NISSAN NAVARA Dimensions: Outer Diameter: 5.77" (148 mm) Inlet Diameter: 2.42" (62 mm) Length: 8.74" (224 mm) Efficiency @ 99% Percent</p>	 <p>Part Number: P521055 Description: AIR PRIMARY Primary App: FREIGHTLINER OFF HWY TRUCK Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 8.12" (206 mm)</p>
<p>Part Number: P505999 Description: AIR PANEL Primary App: MITSUBISHI MR404847 Dimensions: Width: 9.29" (236 mm) Depth: 2.05" (52 mm) Length: 14.25" (362 mm)</p>	 <p>Part Number: P521598 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON EBA13 KONEPAC, KENWORTH, PETERBILT Dimensions: Outer Diameter: 11.83" (300 mm) Inner Diameter: 7.37" (187 mm) Length: 24.00" (610 mm) Gasket OD: 9.81" (249 mm) Gasket ID: 5.38" (137 mm)</p>
<p>Part Number: P506000 Description: AIR PRIMARY Primary App: COMPRESSOR Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 3.11" (79 mm) Length: 4.84" (123 mm)</p>	 <p>Part Number: P521685 Description: AIR PRIMARY, WRAP Primary App: CATERPILLAR 8N-2555 Dimensions: Width: 20.10" (511 mm) Length: 9.84" (250 mm)</p>
 <p>Part Number: P520450 Description: AIR PANEL, VENTILATION Primary App: CAT 5G-1913 Dimensions: Width: 8.00" (203 mm) Depth: 2.19" (56 mm) Height: 16.00" (406 mm)</p>	 <p>Part Number: P521686 Description: AIR PRIMARY, WRAP Primary App: CATERPILLAR 4W-7103 Dimensions: Width: 22.90" (582 mm) Length: 23.97" (609 mm)</p>
 <p>Part Number: P520510 Description: AIR PRIMARY Primary App: UAC 250C124 MF 1094056M91 Dimensions: Outer Diameter: 5.31" (135 mm) Inner Diameter: 2.22" (56 mm) Length: 10.50" (267 mm) Bolt Hole Diameter: 0.75" (19 mm) Gasket OD: 3.60" (91 mm) Gasket ID: 3.00" (76 mm)</p>	 <p>Part Number: P521692 Description: AIR SAFETY Primary App: VOLVO V1114450 Dimensions: Outer Diameter: 8.24" (209 mm) Inner Diameter: 7.12" (181 mm) Length: 13.00" (330 mm)</p>
 <p>Part Number: P520511 Description: AIR SAFETY Primary App: JAC 250C126S MF 1094269M1 Dimensions: Outer Diameter: 2.10" (53 mm) Inner Diameter: 1.90" (48 mm) Length: 10.25" (260 mm)</p>	 <p>Part Number: P521847 Description: AIR SAFETY Primary App: CAT 8N-6883 Dimensions: Outer Diameter: 6.31" (160 mm) Inner Diameter: 4.63" (118 mm) Length: 16.15" (410 mm) Flange Diameter: 9.06" (230 mm)</p>
 <p>Part Number: P520582 Description: AIR SAFETY Primary App: STEIGER 90-4204T1 Dimensions: Outer Diameter: 7.64" (194 mm) Inner Diameter: 6.04" (153 mm) Length: 20.00" (508 mm)</p>	



	<p>Part Number: P522293 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON EBA11 KONEPAC Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.95" (177 mm) Length: 28.00" (711 mm) Gasket OD: 7.50" (190 mm) Gasket ID: 3.96" (101 mm)</p>		<p>Part Number: P524348 Description: AIR PRIMARY Primary App: INT'L 180287R91, AMERICAN LAFRANCE, MERCEDES Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 4.62" (117 mm) Length: 8.56" (217 mm)</p>
	<p>Part Number: P522449 Description: AIR PRIMARY Primary App: KOMATSU 600-181-7300 Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 3.26" (83 mm) Length: 11.00" (279 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 3.76" (96 mm)</p>		<p>Part Number: P524350 Description: AIR PRIMARY Primary App: FORD 6CYL-300, C40Z9601A Dimensions: Outer Diameter: 8.12" (206 mm) Inner Diameter: 6.62" (168 mm) Length: 3.25" (83 mm)</p>
	<p>Part Number: P522450 Description: AIR SAFETY Primary App: KOMATSU 6114-80-7101-S Dimensions: Outer Diameter: 5.56" (141 mm) Inner Diameter: 4.20" (107 mm) Length: 10.57" (268 mm)</p>		<p>Part Number: P524351 Description: AIR PRIMARY Primary App: GM 6CYL-292, V8-305, JEEP Dimensions: Outer Diameter: 9.69" (246 mm) Inner Diameter: 8.19" (208 mm) Length: 3.53" (90 mm)</p>
	<p>Part Number: P522451 Description: AIR PRIMARY Primary App: KOMATSU 6114-80-7101-P, 600-181-2500 Dimensions: Outer Diameter: 9.73" (247 mm) Inner Diameter: 5.66" (144 mm) Length: 12.56" (319 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 8.68" (220 mm)</p>		<p>Part Number: P524355 Description: AIR PRIMARY Primary App: GM V8-305, V8-350, V8-454 Dimensions: Outer Diameter: 12.00" (305 mm) Inner Diameter: 9.88" (251 mm) Length: 3.46" (88 mm)</p>
	<p>Part Number: P522452 Description: AIR SAFETY Primary App: KOMATSU 600-181-6740-S, 600-181-6730 Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 4.13" (105 mm) Length: 15.83" (402 mm)</p>		<p>Part Number: P524357 Description: AIR PRIMARY Primary App: FORD V8-460 C8A29601A Dimensions: Outer Diameter: 13.28" (337 mm) Inner Diameter: 11.28" (287 mm) Length: 2.78" (71 mm)</p>
	<p>Part Number: P522874 Description: AIR PRIMARY Primary App: MCI BUS 9G-3-37 Dimensions: Outer Diameter: 15.09" (383 mm) Inner Diameter: 8.70" (221 mm) Length: 15.34" (390 mm) Bolt Hole Diameter: 0.75" (19 mm) Gasket ID: 9.00" (229 mm)</p>		<p>Part Number: P524358 Description: AIR PRIMARY Primary App: FORD C8TZ9601A Dimensions: Outer Diameter: 10.87" (276 mm) Inner Diameter: 9.00" (229 mm) Length: 2.21" (56 mm)</p>
	<p>Part Number: P522926 Description: AIR PRIMARY Primary App: FORD E8HZ9601A Dimensions: Outer Diameter: 13.84" (352 mm) Inner Diameter: 7.48" (190 mm) Length: 7.00" (178 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 9.56" (243 mm)</p>		<p>Part Number: P524360 Description: AIR PRIMARY Primary App: GM V8-366, V8-427 6423239 Dimensions: Outer Diameter: 11.31" (287 mm) Inner Diameter: 8.56" (217 mm) Length: 5.56" (141 mm)</p>
	<p>Part Number: P523048 Description: AIR SAFETY Primary App: CAT 8N-2556 Dimensions: Outer Diameter: 12.82" (326 mm) Inner Diameter: 10.14" (258 mm) Length: 9.81" (249 mm)</p>		<p>Part Number: P524362 Description: AIR PRIMARY Primary App: INT'L 364302C91, 446661-C1 Dimensions: Outer Diameter: 12.62" (321 mm) Inner Diameter: 9.75" (248 mm) Length: 5.00" (127 mm)</p>
	<p>Part Number: P524344 Description: AIR PRIMARY Primary App: VOLVO/WHITE V1115700 Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 15.75" (400 mm) Gasket ID: 9.88" (251 mm)</p>		<p>Part Number: P524366 Description: AIR PRIMARY Primary App: FORD V8-370, V8-429 Dimensions: Outer Diameter: 12.62" (321 mm) Inner Diameter: 9.75" (248 mm) Length: 5.51" (140 mm)</p>

















	<p>Part Number: P524367 Description: AIR PRIMARY Primary App: FORD V8-370, V8-475 Dimensions: Outer Diameter: 12.60" (320 mm) Inner Diameter: 8.35" (212 mm) Length: 5.50" (140 mm)</p>		<p>Part Number: P524391 Description: AIR PRIMARY Primary App: DODGE 6CYL-225, V8-318, AMC, CHRYSLER, JEEP Dimensions: Outer Diameter: 10.25" (260 mm) Inner Diameter: 7.62" (194 mm) Length: 2.75" (70 mm)</p>
	<p>Part Number: P524368 Description: AIR PRIMARY Primary App: INT'L 446661C1,C2 Dimensions: Outer Diameter: 11.65" (296 mm) Inner Diameter: 8.31" (211 mm) Length: 5.00" (127 mm)</p>		<p>Part Number: P524392 Description: BREATHER, CYLINDRICAL Primary App: BENDIX AIR COMPRESSOR Dimensions: Outer Diameter: 3.00" (76 mm) Inner Diameter: 1.62" (41 mm) Length: 1.37" (35 mm)</p>
	<p>Part Number: P524369 Description: AIR PRIMARY Primary App: GM V8-305, V8-350, V8-454, CHEV Dimensions: Outer Diameter: 12.00" (305 mm) Inner Diameter: 9.88" (251 mm) Length: 5.47" (139 mm)</p>		<p>Part Number: P524738 Description: AIR PRIMARY Primary App: FORD CARGO 7.8 E7HZ-9601-B Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 7.62" (194 mm)</p>
	<p>Part Number: P524373 Description: AIR PRIMARY Primary App: GM V8-379, 8997189 Dimensions: Outer Diameter: 13.88" (353 mm) Inner Diameter: 11.61" (295 mm) Length: 4.05" (103 mm)</p>		<p>Part Number: P524815 Description: AIR SAFETY Primary App: FORD TRUCKS WITH DONALDSON FHD16 AIR CLEANER Dimensions: Outer Diameter: 8.48" (215 mm) Inner Diameter: 6.20" (157 mm) Length: 9.65" (245 mm)</p>
	<p>Part Number: P524374 Description: AIR PRIMARY Primary App: CHEV LUV, TOYOTA, DATSUN, GM Dimensions: Outer Diameter: 10.16" (258 mm) Inner Diameter: 7.91" (201 mm) Length: 2.36" (60 mm)</p>		<p>Part Number: P524831 Description: AIR PRIMARY Primary App: GM 2067009 Dimensions: Outer Diameter: 9.50" (241 mm) Inner Diameter: 6.89" (175 mm) Length: 27.44" (697 mm) Gasket ID: 8.12" (206 mm)</p>
	<p>Part Number: P524382 Description: AIR PANEL, ENGINE Primary App: CHRYSLER 4227087 Dimensions: Width: 5.30" (135 mm) Depth: 1.62" (41 mm) Height: 8.07" (205 mm)</p>		<p>Part Number: P524835 Description: AIR PANEL, ENGINE Primary App: FARR DYNACELL T512 Dimensions: Width: 11.50" (292 mm) Depth: 5.00" (127 mm) Height: 15.00" (381 mm)</p>
	<p>Part Number: P524386 Description: AIR PRIMARY Primary App: GM 1982+ MODELS Dimensions: Outer Diameter: 8.50" (216 mm) Inner Diameter: 6.97" (177 mm) Length: 2.46" (62 mm)</p>		<p>Part Number: P524837 Description: AIR PRIMARY, SPECIAL Primary App: FARR ECOII #71338-001, UNITED F-ECOII-9X24 Dimensions: Width: 9.75" (248 mm) Length: 24.00" (610 mm) Rated Flow HR: 1000.00 CFM (28.32 CMM) Restriction HR: 7.00 In H2O (178 mm H2O)</p>
	<p>Part Number: P524388 Description: BREATHER, CYLINDRICAL Primary App: GM, BENDIX AIR COMPRESSORS Dimensions: Outer Diameter: 2.80" (71 mm) Inner Diameter: 1.30" (33 mm) Length: 1.01" (26 mm)</p>		<p>Part Number: P524838 Description: AIR PRIMARY, SPECIAL Primary App: FARR ECOII #71338-003, UNITED F-ECOII-13X24 Dimensions: Width: 13.50" (343 mm) Length: 24.00" (610 mm) Rated Flow HR: 1400.00 CFM (39.64 CMM) Restriction HR: 7.00 In H2O (178 mm H2O)</p>
	<p>Part Number: P524390 Description: AIR PRIMARY Primary App: CHRYSLER 1739548 Dimensions: Outer Diameter: 8.25" (210 mm) Inner Diameter: 6.50" (165 mm) Length: 3.00" (76 mm)</p>		<p>Part Number: P525026 Description: AIR PANEL, VENTILATION Primary App: CAT 7T-1890 Dimensions: Width: 5.35" (136 mm) Depth: 2.83" (72 mm) Height: 26.18" (665 mm)</p>



















	<p>Part Number: P525129 Description: AIR SAFETY Primary App: CAT 7W-9567 Dimensions: Outer Diameter: 10.03" (255 mm) Inner Diameter: 8.14" (207 mm) Length: 18.03" (458 mm) Flange Diameter: 12.09" (307 mm)</p>		<p>Part Number: P526413 Description: BREATHER, CYLINDRICAL Primary App: CUMMINS 255963 Dimensions: Outer Diameter: 2.88" (73 mm) Inner Diameter: 1.41" (36 mm) Length: 2.72" (69 mm)</p>
	<p>Part Number: P525130 Description: AIR PANEL, ENGINE Primary App: FORD F100/F150 TRUCKS Dimensions: Width: 5.86" (149 mm) Depth: 1.65" (42 mm) Height: 12.87" (327 mm)</p>		<p>Part Number: P526415 Description: AIR PRIMARY Primary App: CAT 4W-5228 Dimensions: Outer Diameter: 14.68" (373 mm) Inner Diameter: 10.34" (263 mm) Length: 24.00" (610 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 11.00" (279 mm)</p>
	<p>Part Number: P525423 Description: AIR PRIMARY Primary App: DONALDSON CYCLOPAC AIR CLEANER MODEL:G080502 Dimensions: Outer Diameter: 6.09" (155 mm) Inner Diameter: 3.48" (88 mm) Length: 15.00" (381 mm)</p>		<p>Part Number: P526416 Description: AIR PRIMARY Primary App: JOHN DEERE AT75036 Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 4.86" (123 mm) Length: 11.00" (279 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 5.00" (127 mm)</p>
	<p>Part Number: P525943 Description: AIR PRIMARY Primary App: CASE A171255 Dimensions: Outer Diameter: 9.91" (252 mm) Inner Diameter: 6.05" (154 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 6.38" (162 mm)</p>		<p>Part Number: P526428 Description: AIR PRIMARY Primary App: KOMASTU 600-181-1580 Dimensions: Outer Diameter: 10.87" (276 mm) Inner Diameter: 6.50" (165 mm) Length: 15.00" (381 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 7.62" (194 mm)</p>
	<p>Part Number: P525944 Description: AIR SAFETY Primary App: CASE A171256 Dimensions: Outer Diameter: 5.95" (151 mm) Inner Diameter: 4.85" (123 mm) Length: 14.00" (356 mm)</p>		<p>Part Number: P526432 Description: AIR SAFETY Primary App: KOMATSU 600-181-1680, DCI-NDL R800088 Dimensions: Outer Diameter: 6.40" (163 mm) Inner Diameter: 5.28" (134 mm) Length: 13.75" (349 mm)</p>
	<p>Part Number: P526407 Description: AIR SAFETY Primary App: CASE AG EQUIPMENT Dimensions: Outer Diameter: 5.56" (141 mm) Inner Diameter: 4.42" (112 mm) Length: 15.63" (397 mm)</p>		<p>Part Number: P526433 Description: AIR PRIMARY Primary App: MITSUBISHI ME063135, ME063130 Dimensions: Outer Diameter: 10.87" (276 mm) Inner Diameter: 6.50" (165 mm) Length: 15.00" (381 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 7.62" (194 mm)</p>
	<p>Part Number: P526408 Description: AIR SAFETY Primary App: CASE AG EQUIPMENT, IHC 537337R1 Dimensions: Outer Diameter: 4.47" (114 mm) Inner Diameter: 3.43" (87 mm) Length: 14.00" (356 mm)</p>		<p>Part Number: P526488 Description: AIR PRIMARY Primary App: CUMMINS 209892 Dimensions: Outer Diameter: 9.62" (244 mm) Inner Diameter: 5.00" (127 mm) Length: 6.38" (162 mm)</p>
	<p>Part Number: P526410 Description: AIR PRIMARY Primary App: CASE AG EQUIPMENT Dimensions: Outer Diameter: 9.00" (229 mm) Inner Diameter: 5.69" (145 mm) Length: 16.00" (406 mm) Gasket ID: 6.12" (155 mm)</p>		<p>Part Number: P526489 Description: AIR PRIMARY Primary App: WHITE 3108661 Dimensions: Outer Diameter: 9.56" (243 mm) Inner Diameter: 4.07" (103 mm) Length: 14.75" (375 mm) Bolt Hole Diameter: 0.39" (10 mm)</p>
	<p>Part Number: P526411 Description: AIR PRIMARY Primary App: LIFT TRUCK Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 4.24" (108 mm) Length: 4.65" (118 mm) Gasket ID: 5.62" (143 mm)</p>		<p>Part Number: P526491 Description: AIR SAFETY Primary App: IHC 702847C1 Dimensions: Outer Diameter: 9.98" (253 mm) Inner Diameter: 5.48" (139 mm) Length: 20.28" (515 mm)</p>



















	<p>Part Number: P526492 Description: AIR PRIMARY Primary App: IHC 925761C1 Dimensions: Outer Diameter: 9.98" (253 mm) Inner Diameter: 5.48" (139 mm) Length: 20.28" (515 mm)</p>		<p>Part Number: P526505 Description: AIR PRIMARY Primary App: FORD D6NN-9601-B Dimensions: Outer Diameter: 5.31" (135 mm) Inner Diameter: 3.08" (78 mm) Length: 14.69" (373 mm)</p>
	<p>Part Number: P526493 Description: AIR SAFETY Primary App: IHC 925762C1 Dimensions: Outer Diameter: 5.42" (138 mm) Inner Diameter: 4.02" (102 mm) Length: 19.25" (489 mm) Bolt Hole Diameter: 0.64" (16 mm)</p>		<p>Part Number: P526507 Description: AIR PRIMARY Primary App: IHC 702642-C1, GMC 8994975 Dimensions: Outer Diameter: 5.38" (137 mm) Inner Diameter: 4.12" (105 mm) Length: 15.69" (399 mm) Bolt Hole Diameter: 0.64" (16 mm)</p>
	<p>Part Number: P526496 Description: AIR PRIMARY Primary App: CASE A43734 Dimensions: Outer Diameter: 11.62" (295 mm) Inner Diameter: 7.19" (183 mm) Length: 7.25" (184 mm)</p>		<p>Part Number: P526509 Description: AIR PRIMARY Primary App: MF 1044273M91 Dimensions: Outer Diameter: 11.50" (292 mm) Inner Diameter: 7.25" (184 mm) Length: 15.68" (398 mm) Bolt Hole Diameter: 0.39" (10 mm)</p>
	<p>Part Number: P526497 Description: AIR PRIMARY Primary App: CASE A43735 Dimensions: Outer Diameter: 6.75" (171 mm) Inner Diameter: 5.56" (141 mm) Length: 6.00" (152 mm) Bolt Hole Diameter: 0.39" (10 mm)</p>		<p>Part Number: P526510 Description: AIR SAFETY Primary App: MF 1044274M91 Dimensions: Outer Diameter: 6.88" (175 mm) Inner Diameter: 5.42" (138 mm) Length: 13.94" (354 mm)</p>
	<p>Part Number: P526498 Description: AIR SAFETY Primary App: IHC 631422C1 Dimensions: Outer Diameter: 3.88" (99 mm) Inner Diameter: 2.50" (64 mm) Length: 11.75" (298 mm)</p>		<p>Part Number: P526511 Description: AIR SAFETY Primary App: MF 1051373M91 Dimensions: Outer Diameter: 7.33" (186 mm) Inner Diameter: 6.12" (155 mm) Length: 20.87" (530 mm)</p>
	<p>Part Number: P526499 Description: AIR PRIMARY Primary App: IHC 631421C1 Dimensions: Outer Diameter: 7.33" (186 mm) Inner Diameter: 4.00" (102 mm) Length: 14.25" (362 mm) Bolt Hole Diameter: 0.39" (10 mm)</p>		<p>Part Number: P526512 Description: AIR PRIMARY Primary App: MF 1051374M91 Dimensions: Outer Diameter: 12.50" (318 mm) Inner Diameter: 7.50" (190 mm) Length: 22.25" (565 mm) Bolt Hole Diameter: 0.39" (10 mm)</p>
	<p>Part Number: P526500 Description: AIR PRIMARY Primary App: FORD D6NN-9601-A Dimensions: Outer Diameter: 5.31" (135 mm) Inner Diameter: 3.08" (78 mm) Length: 11.25" (286 mm) Bolt Hole Diameter: 0.45" (11 mm)</p>		<p>Part Number: P526678 Description: AIR PRIMARY, RADIALSEAL Primary App: FREIGHTLINER Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.15" (131 mm) Length: 14.49" (368 mm)</p>
	<p>Part Number: P526501 Description: AIR SAFETY Primary App: FORD D6NN-9R500-A Dimensions: Outer Diameter: 2.94" (75 mm) Inner Diameter: 2.38" (60 mm) Length: 9.94" (252 mm)</p>		<p>Part Number: P526749 Description: AIR PRIMARY Primary App: CASE K945043 Dimensions: Outer Diameter: 6.08" (154 mm) Inner Diameter: 4.11" (104 mm) Length: 10.45" (265 mm) Bolt Hole Diameter: 0.66" (17 mm)</p>
	<p>Part Number: P526504 Description: AIR SAFETY Primary App: FORD D6NN-9R-500B Dimensions: Outer Diameter: 2.94" (75 mm) Inner Diameter: 2.38" (60 mm) Length: 13.38" (340 mm)</p>		<p>Part Number: P526753 Description: AIR PRIMARY Primary App: MITSUBISHI MB-0120389 Dimensions: Outer Diameter: 9.40" (239 mm) Inner Diameter: 5.78" (147 mm) Length: 5.18" (132 mm)</p>





	<p>Part Number: P526756 Description: AIR PRIMARY Primary App: TOYOTA 1780168020 Dimensions: Outer Diameter: 8.62" (219 mm) Inner Diameter: 4.29" (109 mm) Length: 5.67" (144 mm)</p>		<p>Part Number: P527566 Description: AIR PRIMARY Primary App: FORD, DONALDSON EGB16 A/C Dimensions: Outer Diameter: 13.84" (352 mm) Inner Diameter: 9.47" (241 mm) Length: 13.03" (331 mm) Gasket ID: 9.88" (251 mm)</p>
	<p>Part Number: P526801 Description: AIR PRIMARY, FINNED Primary App: KUBOTA 15852-11080, CASE 1585211080 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 1.67" (42 mm) Length: 7.00" (178 mm) Gasket ID: 2.20" (56 mm) Minor OD: 0.42" (11 mm)</p>		<p>Part Number: P527586 Description: AIR CLEANER, DISPOSABLE Primary App: FREIGHTLINER, FARR ECOII CM #78105 Dimensions: Body Diameter: 11.00" (279 mm) Inlet Diameter: 8.00" (203 mm) Length: 24.00" (610 mm) Gasket OD: 18.50" (470 mm) Inlet Location: 6.00" (152 mm) Inlet Length: 8.88" (226 mm) Rated Flow MR: 1000.00 CFM (28.32 CMM) Restriction MR: 8.00 In H2O (203 mm H2O)</p>
	<p>Part Number: P526839 Description: AIR SAFETY Primary App: CASE IH 510B LDR, TD8 CRWLR, #1129112C1 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 2.91" (74 mm) Length: 14.00" (356 mm)</p>		<p>Part Number: P527595 Description: AIR PANEL, VENTILATION Primary App: CAT 6T-988, MIDSIZE CRAWLERS & LOADERS Dimensions: Width: 5.91" (150 mm) Depth: 2.19" (56 mm) Height: 21.26" (540 mm)</p>
	<p>Part Number: P526840 Description: AIR PRIMARY, FINNED Primary App: CASE IH 510B LDR, TD8 CRWLR, #1129111C1 Dimensions: Outer Diameter: 6.80" (173 mm) Inner Diameter: 4.24" (108 mm) Length: 15.00" (381 mm) Gasket ID: 4.45" (113 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P527596 Description: AIR PRIMARY Primary App: HINO 17801-2480B Dimensions: Outer Diameter: 9.14" (232 mm) Inner Diameter: 5.78" (147 mm) Length: 18.00" (457 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 6.25" (159 mm)</p>
	<p>Part Number: P526864 Description: AIR SAFETY Primary App: CASE K200380 Dimensions: Outer Diameter: 2.94" (75 mm) Inner Diameter: 1.88" (48 mm) Length: 9.64" (245 mm)</p>		<p>Part Number: P527680 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSONEPG11, Ford F3HZ-9R500-A, MTRCFT FA1120 Dimensions: Outer Diameter: 5.30" (135 mm) Inner Diameter: 3.78" (96 mm) Length: 11.82" (300 mm)</p>
	<p>Part Number: P526873 Description: AIR PRIMARY Primary App: CLARK IR, THERMOKING, YALE & TOWNE Dimensions: Outer Diameter: 4.38" (111 mm) Inner Diameter: 3.00" (76 mm) Length: 7.00" (178 mm)</p>		<p>Part Number: P527682 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON EPG15" AIR CLEANER Dimensions: Outer Diameter: 13.08" (332 mm) Inner Diameter: 6.78" (172 mm) Length: 14.76" (375 mm)</p>
	<p>Part Number: P526966 Description: AIR PRIMARY Primary App: FORD F1HZ0601A, MOTORCRAFT FA1076 Dimensions: Outer Diameter: 7.32" (186 mm) Inner Diameter: 5.40" (137 mm) Length: 13.38" (340 mm) Bolt Hole Diameter: 0.39" (10 mm) Gasket ID: 5.82" (148 mm)</p>		<p>Part Number: P527683 Description: AIR SAFETY, RADIALSEAL Primary App: AIR SAFETY, RADIALSEAL Dimensions: Outer Diameter: 6.89" (175 mm) Inner Diameter: 5.32" (135 mm) Length: 14.23" (361 mm)</p>
	<p>Part Number: P527484 Description: AIR PRIMARY, RADIALSEAL Primary App: GM TRUCK #15619013, FORD F3HZ9601A, MTCFT FA1119 Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.15" (131 mm) Length: 12.28" (312 mm)</p>		<p>Part Number: P527957 Description: AIR SAFETY Primary App: FORD, DONALDSON EGB 16 A/C Dimensions: Outer Diameter: 8.24" (209 mm) Inner Diameter: 7.12" (181 mm) Length: 9.00" (229 mm)</p>
	<p>Part Number: P527530 Description: AIR SAFETY Primary App: CAT 4W-6691, 7W-6754, LIFT TRUCKS Dimensions: Outer Diameter: 3.99" (101 mm) Inner Diameter: 2.32" (59 mm) Length: 5.18" (132 mm) Flange Diameter: 6.69" (170 mm)</p>		

	<p>Part Number: P528206 Description: AIR PRIMARY Primary App: JOHN DEERE AM30800 Dimensions: Outer Diameter: 4.39" (112 mm) Inner Diameter: 3.00" (76 mm) Length: 2.34" (59 mm)</p>		<p>Part Number: P528226 Description: AIR PANEL, ENGINE Primary App: MOTORCRAFT FA1071, FA971 Dimensions: Width: 7.88" (200 mm) Depth: 1.54" (39 mm) Height: 7.03" (179 mm)</p>
	<p>Part Number: P528215 Description: AIR PRIMARY Primary App: ONAN Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 4.75" (121 mm) Length: 3.00" (76 mm)</p>		<p>Part Number: P528228 Description: AIR PANEL, ENGINE Primary App: FORD E5TE9601AB, MTRCRFT FA1032 Dimensions: Width: 7.59" (193 mm) Depth: 1.51" (38 mm) Height: 11.28" (287 mm)</p>
	<p>Part Number: P528216 Description: AIR PRIMARY Primary App: FORD B7A9601C Dimensions: Outer Diameter: 9.43" (240 mm) Inner Diameter: 6.87" (174 mm) Length: 3.62" (92 mm)</p>		<p>Part Number: P528231 Description: AIR PRIMARY Primary App: IHC 385168R2 Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 4.75" (121 mm) Length: 1.88" (48 mm)</p>
	<p>Part Number: P528219 Description: AIR PRIMARY Primary App: VORTOX VF120A Dimensions: Outer Diameter: 8.88" (226 mm) Inner Diameter: 5.00" (127 mm) Length: 10.25" (260 mm)</p>		<p>Part Number: P528234 Description: BREATHER, CYLINDRICAL Primary App: CHRYSLER 1929429 Dimensions: Outer Diameter: 3.30" (84 mm) Inner Diameter: 1.97" (50 mm) Length: 3.25" (83 mm)</p>
	<p>Part Number: P528220 Description: AIR PRIMARY Primary App: ONAN 140-0495 Dimensions: Outer Diameter: 4.50" (114 mm) Inner Diameter: 3.00" (76 mm) Length: 3.34" (85 mm)</p>		<p>Part Number: P528235 Description: AIR PRIMARY Primary App: PUROLATOR AF71 Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 3.25" (83 mm) Length: 4.00" (102 mm) Bolt Hole Diameter: 0.25" (6 mm)</p>
	<p>Part Number: P528221 Description: AIR PRIMARY Primary App: PETTER JF35/6 Dimensions: Outer Diameter: 5.50" (140 mm) Inner Diameter: 3.25" (83 mm) Length: 4.50" (114 mm)</p>		<p>Part Number: P528464 Description: AIR PANEL, ENGINE Primary App: BROOKS & PERKINS SWEEPERS 300390, 305645 Dimensions: Width: 15.00" (381 mm) Depth: 2.19" (56 mm) Height: 20.00" (508 mm)</p>
	<p>Part Number: P528224 Description: AIR PANEL, ENGINE Primary App: GM 25043334, AC A875C Dimensions: Width: 4.22" (107 mm) Depth: 1.58" (40 mm) Height: 9.44" (240 mm)</p>		<p>Part Number: P528465 Description: AIR PANEL, ENGINE Primary App: BROOKS & PERKINS SWEEPERS 300391, 305646 Dimensions: Width: 18.00" (457 mm) Depth: 2.19" (56 mm) Height: 20.00" (508 mm)</p>
	<p>Part Number: P528225 Description: AIR PANEL, ENGINE Primary App: CHRYSLER 4241042, FORD E4FZ9601A, E59Z9601A Dimensions: Width: 5.26" (134 mm) Depth: 10.68" (271 mm) Height: 1.65" (42 mm)</p>		<p>Part Number: P528708 Description: BREATHER Primary App: VOLVO 1082111, 15868821 Dimensions: Outer Diameter: 3.31" (84 mm) Inner Diameter: 1.02" (26 mm) Length: 2.66" (68 mm)</p>

















	<p>Part Number: P528722 Description: AIR PRIMARY Primary App: FARR ECO II 71338-004 (SHORT) Dimensions: Outer Diameter: 13.50" (343 mm) Inner Diameter: 7.00" (178 mm) Length: 18.00" (457 mm) Rated Flow HR: 1500.00 CFM (42.48 CMM) Restriction HR: 7.00 In H2O (178 mm H2O)</p>		<p>Part Number: P530634 Description: AIR PRIMARY Primary App: TECUMSEH 35066, DEERE AM100137, GRAVELY 21333 Dimensions: Outer Diameter: 4.25" (108 mm) Inner Diameter: 2.00" (51 mm) Length: 6.14" (156 mm)</p>
	<p>Part Number: P529240 Description: AIR SAFETY Primary App: JOHN DEERE AR85241, DRESSER 1249056H1 Dimensions: Outer Diameter: 6.39" (162 mm) Inner Diameter: 5.29" (134 mm) Length: 17.00" (432 mm)</p>		<p>Part Number: P530635 Description: AIR PRIMARY Primary App: KOHLER 4708301, IHC 11721C1 Dimensions: Outer Diameter: 6.98" (177 mm) Inner Diameter: 5.58" (142 mm) Length: 1.84" (47 mm)</p>
	<p>Part Number: P529241 Description: AIR PRIMARY Primary App: JOHN DEERE AR85242, DRESSER 1249055H1 Dimensions: Outer Diameter: 10.87" (276 mm) Inner Diameter: 6.50" (165 mm) Length: 18.00" (457 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 7.62" (194 mm)</p>		<p>Part Number: P530639 Description: AIR PRIMARY Primary App: DEERE M47494, KOHLER 4708303 Dimensions: Outer Diameter: 6.92" (176 mm) Inner Diameter: 5.50" (140 mm) Length: 2.55" (65 mm)</p>
	<p>Part Number: P529548 Description: AIR SAFETY, RADIALSEAL FREIGHTLINER Primary App: FREIGHTLINER Dimensions: Outer Diameter: 5.30" (135 mm) Inner Diameter: 3.78" (96 mm) Length: 14.02" (356 mm)</p>		<p>Part Number: P530641 Description: AIR PRIMARY Primary App: KOHLER 277138 Dimensions: Outer Diameter: 6.02" (153 mm) Inner Diameter: 4.61" (117 mm) Length: 4.06" (103 mm)</p>
	<p>Part Number: P529552 Description: AIR PRIMARY Primary App: CATERPILLAR #105-9741 Dimensions: Outer Diameter: 22.00" (559 mm) Inner Diameter: 15.64" (397 mm) Length: 24.00" (610 mm) Gasket ID: 17.46" (444 mm)</p>		<p>Part Number: P530642 Description: AIR PRIMARY Primary App: ONAN 140-1228, VOLKSWAGEN 125129605 Dimensions: Outer Diameter: 8.00" (203 mm) Inner Diameter: 6.50" (165 mm) Length: 2.17" (55 mm)</p>
	<p>Part Number: P530355 Description: AIR PRIMARY Primary App: DODGE PICKUPS WITH CUMMINS 5.9 TURBO DIESEL Dimensions: Outer Diameter: 7.98" (203 mm) Inner Diameter: 4.64" (118 mm) Length: 9.28" (236 mm) Bolt Hole Diameter: 0.38" (10 mm) Gasket OD: 6.80" (172 mm) Gasket ID: 5.60" (142 mm)</p>		<p>Part Number: P530643 Description: AIR PRIMARY Primary App: ONAN 140-1891 Dimensions: Outer Diameter: 3.87" (98 mm) Inner Diameter: 2.73" (69 mm) Length: 3.12" (79 mm)</p>
	<p>Part Number: P530628 Description: AIR PRIMARY Primary App: BRIGGS & STRATTON 394018 Dimensions: Outer Diameter: 6.90" (175 mm) Inner Diameter: 5.50" (140 mm) Length: 2.20" (56 mm)</p>		<p>Part Number: P530645 Description: AIR PRIMARY Primary App: STIHL 4201-1410300 Dimensions: Outer Diameter: 3.82" (97 mm) Inner Diameter: 2.37" (60 mm) Length: 2.76" (70 mm)</p>
	<p>Part Number: P530633 Description: AIR PRIMARY Primary App: IHC 385163R1,R2,R91, KOHLER 23048, TECUMSEH 30804 Dimensions: Outer Diameter: 4.39" (112 mm) Inner Diameter: 3.00" (76 mm) Length: 1.56" (40 mm)</p>		<p>Part Number: P530866 Description: AIR PRIMARY, KONEPAC™ Primary App: JEFFREY DRESSER 4110 RAMCAR EXH FILTER 516372 Dimensions: Outer Diameter: 12.75" (324 mm) Inner Diameter: 8.32" (211 mm) Length: 23.99" (609 mm) Gasket OD: 9.81" (249 mm) Gasket ID: 5.38" (137 mm)</p>

	<p>Part Number: P531017 Description: AIR PANEL, ENGINE Primary App: TENNANT 04600, 81363 Dimensions: Width: 20.00" (508 mm) Depth: 3.19" (81 mm) Height: 30.00" (762 mm)</p>		<p>Part Number: P532503 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON FRG13 A/C, CAT 6I2503 Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 5.80" (147 mm) Length: 15.95" (405 mm)</p>
	<p>Part Number: P531751 Description: AIR SAFETY, RADIALSEAL Primary App: GM 12544543, FORD Dimensions: Outer Diameter: 5.30" (135 mm) Inner Diameter: 4.43" (113 mm) Length: 11.82" (300 mm)</p>		<p>Part Number: P532504 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSON FRG13 A/C, CAT 6I-2504 Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 4.40" (112 mm) Length: 15.51" (394 mm)</p>
	<p>Part Number: P532410 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON FPG06, CLARK LIFTRUCK, 4G64 MITSUBISHI Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 3.20" (81 mm) Length: 11.97" (304 mm)</p>		<p>Part Number: P532505 Description: AIR PRIMARY, RADIALSEAL Primary App: CATERPILLAR 6I-2505, 1P-8482 Dimensions: Outer Diameter: 12.50" (318 mm) Inner Diameter: 8.21" (209 mm) Length: 15.02" (382 mm)</p>
	<p>Part Number: P532473 Description: AIR PRIMARY, RADIALSEAL Primary App: CATERPILLAR 6I-0273 Dimensions: Outer Diameter: 11.50" (292 mm) Inner Diameter: 7.19" (183 mm) Length: 13.00" (330 mm)</p>		<p>Part Number: P532506 Description: AIR SAFETY, RADIALSEAL Primary App: CATERPILLAR 6I-2506 Dimensions: Outer Diameter: 8.32" (211 mm) Inner Diameter: 6.20" (158 mm) Length: 15.18" (386 mm)</p>
	<p>Part Number: P532474 Description: AIR SAFETY, RADIALSEAL Primary App: CATERPILLAR 6I-0274 Dimensions: Outer Diameter: 7.31" (186 mm) Inner Diameter: 5.23" (133 mm) Length: 13.16" (334 mm)</p>		<p>Part Number: P532507 Description: AIR PRIMARY, RADIALSEAL Primary App: CATERPILLAR 6I-2507, 6N-6444 Dimensions: Outer Diameter: 12.50" (318 mm) Inner Diameter: 8.20" (208 mm) Length: 15.02" (382 mm)</p>
	<p>Part Number: P532499 Description: AIR PRIMARY, RADIALSEAL Primary App: CATERPILLAR 6I-2499 Dimensions: Outer Diameter: 9.22" (234 mm) Inner Diameter: 4.61" (117 mm) Length: 12.00" (305 mm)</p>		<p>Part Number: P532508 Description: AIR SAFETY, RADIALSEAL Primary App: CATERPILLAR 6I-2508 Dimensions: Outer Diameter: 8.32" (211 mm) Inner Diameter: 6.20" (158 mm) Length: 11.72" (298 mm)</p>
	<p>Part Number: P532500 Description: AIR SAFETY, RADIALSEAL Primary App: CATERPILLAR 6I-2500 Dimensions: Outer Diameter: 4.76" (121 mm) Inner Diameter: 3.25" (83 mm) Length: 11.56" (294 mm)</p>		<p>Part Number: P532509 Description: AIR PRIMARY, RADIALSEAL Primary App: CATERPILLAR 6I2509 Dimensions: Outer Diameter: 12.50" (318 mm) Inner Diameter: 8.21" (209 mm) Length: 18.52" (470 mm)</p>
	<p>Part Number: P532501 Description: AIR PRIMARY, RADIALSEAL Primary App: CATERPILLAR 6I-2501 Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 5.80" (147 mm) Length: 12.88" (327 mm)</p>		<p>Part Number: P532510 Description: AIR SAFETY, RADIALSEAL Primary App: CATERPILLAR 6I-2510 Dimensions: Outer Diameter: 8.33" (212 mm) Inner Diameter: 6.12" (155 mm) Length: 15.18" (386 mm)</p>
	<p>Part Number: P532502 Description: AIR SAFETY, RADIALSEAL Primary App: CATERPILLAR 6I-2502 Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 4.40" (112 mm) Length: 12.44" (316 mm)</p>		<p>Part Number: P532703 Description: AIR PRIMARY, RADIALSEAL Primary App: CHRYSLER 3242-4713953 Dimensions: Outer Diameter: 8.02" (204 mm) Inner Diameter: 4.20" (107 mm) Length: 9.47" (241 mm)</p>

	<p>Part Number: P532931 Description: AIR PRIMARY Primary App: JOHN DEERE AH115833 Dimensions: Outer Diameter: 10.87" (276 mm) Inner Diameter: 6.50" (165 mm) Length: 7.00" (178 mm) Gasket ID: 9.00" (229 mm)</p>		<p>Part Number: P533256 Description: AIR PRIMARY Primary App: HYSTER 3007274 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 2.48" (63 mm) Length: 10.00" (254 mm)</p>
	<p>Part Number: P532966 Description: AIR PRIMARY Primary App: FREIGHTLINER FLN, DONALDSON EPG11 or FRG11 HOUSING Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.15" (131 mm) Length: 18.50" (470 mm)</p>		<p>Part Number: P533308 Description: AIR PRIMARY Primary App: FREIGHTLINER Dimensions: Outer Diameter: 8.84" (225 mm) Inner Diameter: 5.48" (139 mm) Length: 22.00" (559 mm) Gasket ID: 7.00" (178 mm)</p>
	<p>Part Number: P533109 Description: AIR PRIMARY, RADIALSEAL Primary App: CATERPILLAR LIFTTRUCKS V50E, T50E Dimensions: Outer Diameter: 8.18" (208 mm) Inner Diameter: 4.17" (106 mm) Length: 6.07" (154 mm)</p>		<p>Part Number: P533445 Description: AIR PRIMARY Primary App: KOBELCO 2446R35353 Dimensions: Outer Diameter: 10.86" (276 mm) Inner Diameter: 6.50" (165 mm) Length: 15.00" (381 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 7.29" (185 mm)</p>
	<p>Part Number: P533110 Description: AIR SAFETY, RADIALSEAL Primary App: CATERPILLAR 6I-1451, LIFTTRUCKS V50E, T50E Dimensions: Outer Diameter: 4.27" (108 mm) Inner Diameter: 2.79" (71 mm) Length: 5.61" (142 mm)</p>		<p>Part Number: P533559 Description: AIR PANEL, VENTILATION Primary App: KOMATSU 421-07-12312 Dimensions: Width: 6.00" (152 mm) Depth: 2.19" (56 mm) Height: 10.00" (254 mm)</p>
	<p>Part Number: P533230 Description: AIR PRIMARY Primary App: ISUZU 2-90646-900-0 Dimensions: Outer Diameter: 7.93" (201 mm) Inner Diameter: 5.31" (135 mm) Length: 10.00" (254 mm) Bolt Hole Diameter: 0.90" (23 mm)</p>		<p>Part Number: P533597 Description: AIR PRIMARY, FINNED Primary App: JOHN DEERE AM108184 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 2.48" (63 mm) Length: 8.00" (203 mm) Gasket ID: 2.58" (66 mm) Minor OD: 0.66" (17 mm)</p>
	<p>Part Number: P533232 Description: AIR PRIMARY Primary App: MITSUBISHI MB120298 Dimensions: Outer Diameter: 7.95" (202 mm) Inner Diameter: 4.96" (126 mm) Length: 7.09" (180 mm) Bolt Hole Diameter: 0.51" (13 mm)</p>		<p>Part Number: P533599 Description: AIR SAFETY Primary App: CATERPILLAR 7C1062 Dimensions: Outer Diameter: 3.78" (96 mm) Inner Diameter: 2.62" (67 mm) Length: 10.08" (256 mm) Flange Diameter: 6.69" (170 mm)</p>
	<p>Part Number: P533233 Description: AIR PRIMARY, FINNED Primary App: KOBELCO 2446R255S5 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 4.23" (107 mm) Length: 20.00" (508 mm) Gasket ID: 5.42" (138 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P533651 Description: AIR PRIMARY, RADIALSEAL Primary App: CATERPILLAR 102-9388 Dimensions: Outer Diameter: 8.18" (208 mm) Inner Diameter: 4.17" (106 mm) Length: 6.95" (177 mm)</p>
	<p>Part Number: P533234 Description: AIR SAFETY Primary App: KOBELCO 2446R255S6 Dimensions: Outer Diameter: 4.84" (123 mm) Inner Diameter: 3.65" (93 mm) Length: 19.25" (489 mm)</p>		<p>Part Number: P533652 Description: AIR SAFETY, RADIALSEAL Primary App: CATERPILLAR 102-9387 Dimensions: Outer Diameter: 4.27" (108 mm) Inner Diameter: 2.72" (69 mm) Length: 6.49" (165 mm)</p>
	<p>Part Number: P533235 Description: AIR PRIMARY, RADIALSEAL Primary App: NAVISTAR 2005895C1 Dimensions: Outer Diameter: 13.09" (332 mm) Inner Diameter: 6.78" (172 mm) Length: 18.15" (461 mm)</p>		<p>Part Number: P533653 Description: AIR SAFETY, RADIALSEAL Primary App: JOHN DEERE RE34967 Dimensions: Outer Diameter: 5.30" (135 mm) Inner Diameter: 3.78" (96 mm) Length: 14.73" (374 mm)</p>

	<p>Part Number: P533654 Description: AIR PRIMARY, RADIALSEAL Primary App: JOHN DEERE RE34966 Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.15" (131 mm) Length: 15.15" (385 mm)</p>		<p>Part Number: P533930 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON EPG13 RADIALSEAL AIR CLEANERS Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 5.80" (147 mm) Length: 15.15" (385 mm)</p>
	<p>Part Number: P533655 Description: AIR PRIMARY, RADIALSEAL Primary App: JOHN DEERE RE51629 Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 5.82" (148 mm)</p>		<p>Part Number: P533938 Description: AIR PRIMARY, RADIALSEAL Primary App: FORD F6HZ9601CA, MOTORCRAFT FA1637 Dimensions: Outer Diameter: 13.47" (342 mm) Inner Diameter: 8.20" (208 mm) Length: 17.24" (438 mm)</p>
	<p>Part Number: P533723 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSON EPG15 AIR CLEANERS Dimensions: Outer Diameter: 6.89" (175 mm) Inner Diameter: 5.97" (152 mm) Length: 17.52" (445 mm)</p>		<p>Part Number: P533946 Description: AIR SAFETY, RADIALSEAL Primary App: FORD F6HZ9602AA Dimensions: Outer Diameter: 8.33" (212 mm) Inner Diameter: 6.12" (155 mm) Length: 16.60" (422 mm)</p>
	<p>Part Number: P533781 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSON EPG11 AIR CLEANERS Dimensions: Outer Diameter: 5.30" (135 mm) Inner Diameter: 3.78" (96 mm) Length: 18.04" (458 mm)</p>		<p>Part Number: P534096 Description: AIR PRIMARY, RADIALSEAL Primary App: PETERBILT TRUCK, MODEL 385 Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.80" (147 mm) Length: 23.03" (585 mm)</p>
	<p>Part Number: P533788 Description: AIR PANEL, VENTILATION Primary App: HITACHI 4206637, JOHN DEERE AT116077 Dimensions: Width: 17.12" (435 mm) Depth: 2.19" (56 mm) Height: 8.46" (215 mm)</p>		<p>Part Number: P534104 Description: AIR PANEL, ENGINE Primary App: FORD E6AZ9601B Dimensions: Width: 6.18" (157 mm) Depth: 11.24" (285 mm) Height: 1.15" (29 mm)</p>
	<p>Part Number: P533814 Description: AIR PRIMARY, RADIALSEAL Primary App: FORD F6HZ9601BA, MOTORCRAFT FA1636 Dimensions: Outer Diameter: 13.09" (332 mm) Inner Diameter: 6.78" (172 mm) Length: 16.85" (428 mm)</p>		<p>Part Number: P534105 Description: AIR PANEL, ENGINE Primary App: AMC 8953004383 Dimensions: Width: 6.68" (170 mm) Depth: 13.48" (342 mm) Height: 1.59" (40 mm)</p>
	<p>Part Number: P533882 Description: AIR PRIMARY, RADIALSEAL Primary App: CATERPILLAR 777 ORE TRUCK, 106-3969 Dimensions: Outer Diameter: 14.28" (363 mm) Inner Diameter: 8.98" (228 mm) Length: 17.62" (448 mm)</p>		<p>Part Number: P534435 Description: AIR PRIMARY Primary App: MITSUBISHI ME121023, ME294850 Dimensions: Outer Diameter: 11.06" (281 mm) Inner Diameter: 5.78" (15 mm) Length: 14.21" (361 mm)</p>
	<p>Part Number: P533884 Description: AIR SAFETY, RADIALSEAL Primary App: CATERPILLAR 777 ORE TRUCK, 106-3973 Dimensions: Outer Diameter: 9.09" (231 mm) Inner Diameter: 7.02" (178 mm) Length: 17.76" (451 mm)</p>		<p>Part Number: P534436 Description: AIR PRIMARY, RADIALSEAL Primary App: Isuzu 1142152030 Dimensions: Outer Diameter: 11.10" (282 mm) Inner Diameter: 6.77" (172 mm) Length: 17.80" (452 mm)</p>
	<p>Part Number: P533890 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSON EPG13 RADIALSEAL AIR CLEANERS Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 5.05" (128 mm) Length: 14.84" (377 mm)</p>		<p>Part Number: P534438 Description: AIR PRIMARY, RADIALSEAL Primary App: EXMAN A6115A6114 Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.72" (171 mm) Length: 16.20" (416 mm)</p>
			<p>Part Number: P534544 Description: AIR SAFETY, RADIALSEAL Primary App: ISUZU 1142152200 Dimensions: Outer Diameter: 6.89" (175 mm) Inner Diameter: 5.24" (133 mm) Length: 15.98" (406 mm)</p>

	<p>Part Number: P534816 Description: AIR PRIMARY, RADIALSEAL Primary App: KENWORTH & PETERBILT CONVENTIONALS Dimensions: Outer Diameter: 11.42" (290 mm) Inner Diameter: 6.78" (172 mm) Length: 23.44" (595 mm)</p>		<p>Part Number: P535361 Description: AIR PRIMARY Primary App: KUBOTA 1557111210 Dimensions: Outer Diameter: 6.09" (155 mm) Inner Diameter: 3.47" (88 mm) Length: 9.25" (235 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 4.15" (105 mm)</p>
	<p>Part Number: P534885 Description: AIR SAFETY, RADIALSEAL Primary App: TOYOTA 17744U210071 FLAME RETARDENT Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 2.55" (65 mm) Length: 11.74" (298 mm)</p>		<p>Part Number: P535362 Description: AIR PRIMARY Primary App: KUBOTA 1574111080 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 2.48" (63 mm) Length: 10.00" (254 mm) Bolt Hole Diameter: 0.27" (7 mm)</p>
	<p>Part Number: P534925 Description: AIR PRIMARY, RADIALSEAL Primary App: KENWORTH & PETERBILT CONVENTIONALS Dimensions: Outer Diameter: 13.07" (332 mm) Inner Diameter: 7.44" (189 mm) Length: 25.44" (646 mm)</p>		<p>Part Number: P535364 Description: AIR PRIMARY Primary App: KUBOTA 1572411080 Dimensions: Outer Diameter: 6.09" (155 mm) Inner Diameter: 4.09" (104 mm) Length: 9.25" (235 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 4.50" (114 mm)</p>
	<p>Part Number: P535089 Description: AIR PANEL, VENTILATION Primary App: VOLVO 4771477, 15845753 Dimensions: Width: 7.40" (188 mm) Depth: 10.51" (267 mm) Height: 1.61" (41 mm)</p>		<p>Part Number: P535365 Description: AIR PRIMARY Primary App: KOMATSU 6001816540 Dimensions: Outer Diameter: 7.36" (187 mm) Inner Diameter: 4.78" (121 mm) Length: 15.00" (381 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 6.38" (162 mm)</p>
	<p>Part Number: P535114 Description: AIR PRIMARY Primary App: CATERPILLAR 4P-0710 Dimensions: Outer Diameter: 19.29" (490 mm) Inner Diameter: 12.93" (328 mm) Length: 13.84" (352 mm) Gasket ID: 16.85" (428 mm)</p>		<p>Part Number: P535366 Description: AIR SAFETY Primary App: JOHN DEERE AM108185 Dimensions: Outer Diameter: 2.38" (60 mm) Inner Diameter: 1.91" (49 mm) Length: 7.00" (178 mm)</p>
	<p>Part Number: P535115 Description: AIR SAFETY Primary App: CATERPILLAR 4P-0711 Dimensions: Outer Diameter: 12.78" (325 mm) Inner Diameter: 10.14" (258 mm) Length: 13.81" (351 mm)</p>		<p>Part Number: P535396 Description: AIR SAFETY, RADIALSEAL Primary App: JOHN DEERE M123378 Dimensions: Outer Diameter: 1.82" (46 mm) Inner Diameter: 1.22" (31 mm) Length: 6.59" (167 mm)</p>
	<p>Part Number: P535337 Description: AIR PRIMARY, FINNED Primary App: HYSTER 1377093 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 2.48" (63 mm) Length: 14.00" (356 mm) Gasket ID: 2.58" (66 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P535398 Description: AIR PRIMARY Primary App: EXMAN AE54090 Dimensions: Outer Diameter: 6.37" (162 mm) Inner Diameter: 5.43" (138 mm) Length: 11.96" (304 mm) Gasket ID: 5.39" (137 mm)</p>
	<p>Part Number: P535338 Description: AIR SAFETY Primary App: HYSTER 1377096 Dimensions: Outer Diameter: 2.38" (60 mm) Inner Diameter: 1.87" (47 mm) Length: 13.00" (330 mm)</p>		<p>Part Number: P535596 Description: AIR PRIMARY Primary App: HINO 178012810 Dimensions: Outer Diameter: 9.22" (234 mm) Inner Diameter: 4.84" (123 mm) Length: 18.00" (457 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 6.25" (159 mm)</p>
	<p>Part Number: P535360 Description: AIR PRIMARY Primary App: KUBOTA 1730111080 Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 4.02" (102 mm) Length: 7.50" (190 mm) Bolt Hole Diameter: 0.62" (16 mm)</p>		<p>Part Number: P535597 Description: AIR PRIMARY Primary App: KOBELCO 2446R254S5 Dimensions: Outer Diameter: 8.12" (206 mm) Inner Diameter: 4.84" (123 mm) Length: 21.00" (533 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 6.38" (162 mm)</p>

	<p>Part Number: P535769 Description: AIR PRIMARY Primary App: NISSAN D654601D20 Dimensions: Outer Diameter: 7.93" (201 mm) Inner Diameter: 5.32" (135 mm) Length: 10.00" (254 mm)</p>		<p>Part Number: P536434 Description: AIR PRIMARY, OVAL Primary App: FORD LIGHT TRUCK, F5TZ9601A Dimensions: Width: 6.04" (153 mm) Height: 2.82" (72 mm) Length: 7.15" (182 mm)</p>
	<p>Part Number: P535770 Description: AIR PRIMARY, RADIALSEAL Primary App: UL APPROVED VERSION OF P827653 Dimensions: Outer Diameter: 5.44" (138 mm) Inner Diameter: 3.20" (81 mm) Length: 12.67" (322 mm)</p>		<p>Part Number: P536442 Description: AIR SAFETY, RADIALSEAL Primary App: CHRYSLER RAM 6500 Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 5.05" (128 mm) Length: 9.76" (248 mm)</p>
	<p>Part Number: P536036 Description: AIR PRIMARY, RADIALSEAL Primary App: MITSUBISHI ME073821 Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.15" (131 mm) Length: 15.80" (401 mm)</p>		<p>Part Number: P536448 Description: AIR PRIMARY, RADIALSEAL Primary App: CHRYSLER RAM 6500 Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 5.80" (147 mm) Length: 10.15" (258 mm)</p>
	<p>Part Number: P536425 Description: AIR PANEL, ENGINE Primary App: CHEVROLET LIGHT TRUCK, GMC 25096463 Dimensions: Width: 6.05" (154 mm) Depth: 11.56" (294 mm) Height: 1.66" (42 mm)</p>		<p>Part Number: P536457 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON FRG11 AIR CLEANERS, CONSTRUCTION EQUIPMENT Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.15" (131 mm) Length: 13.00" (330 mm)</p>
	<p>Part Number: P536427 Description: AIR PANEL, ENGINE Primary App: GM LIGHT TRUCK Dimensions: Width: 7.91" (201 mm) Depth: 1.67" (42 mm) Height: 16.00" (406 mm)</p>		<p>Part Number: P536492 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSON FRG11 AIR CLEANER, CAT EXCAVATORS Dimensions: Outer Diameter: 5.30" (135 mm) Inner Diameter: 3.78" (96 mm) Length: 12.74" (324 mm)</p>
	<p>Part Number: P536429 Description: AIR PANEL, ENGINE Primary App: DODGE LIGHT TRUCK, CHRYSLER 4728406 Dimensions: Width: 10.75" (273 mm) Depth: 2.25" (57 mm) Height: 11.82" (300 mm)</p>		<p>Part Number: P536527 Description: AIR PRIMARY, RADIALSEAL Primary App: CASE IH 908300T1 Dimensions: Outer Diameter: 12.50" (318 mm) Inner Diameter: 8.20" (208 mm) Length: 21.10" (536 mm)</p>
	<p>Part Number: P536431 Description: BREATHER, SPECIAL Primary App: FORD LIGHT TRUCK, F4TZ9D695A Dimensions: Height: 2.78" (71 mm) Length: 1.28" (33 mm) Depth: 4.42" (112 mm)</p>		<p>Part Number: P536529 Description: AIR SAFETY, RADIALSEAL Primary App: CASE IH 908301T1 Dimensions: Outer Diameter: 8.32" (211 mm) Inner Diameter: 6.20" (157 mm) Length: 20.81" (529 mm)</p>
	<p>Part Number: P536433 Description: AIR PANEL, ENGINE Primary App: FORD LIGHT TRUCK, F5UZ9601A Dimensions: Width: 6.52" (166 mm) Depth: 1.54" (39 mm) Height: 11.25" (286 mm)</p>		<p>Part Number: P536577 Description: AIR PRIMARY, RADIALSEAL Primary App: NISSAN D6546Z9100 Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.78" (172 mm) Length: 14.19" (360 mm)</p>

	<p>Part Number: P536732 Description: AIR PRIMARY, RADIALSEAL Primary App: GM CK SERIES PICKUPS/VANS Dimensions: Outer Diameter: 7.24" (184 mm) Inner Diameter: 3.58" (91 mm) Length: 10.65" (271 mm)</p>		<p>Part Number: P537405 Description: AIR PRIMARY Primary App: JOHN DEERE AT175344 Dimensions: Outer Diameter: 8.18" (208 mm) Inner Diameter: 4.17" (106 mm) Length: 11.10" (282 mm)</p>
	<p>Part Number: P536733 Description: AIR PRIMARY, RADIALSEAL Primary App: GM CK SERIES PICKUPS/VANS Dimensions: Outer Diameter: 6.49" (165 mm) Inner Diameter: 3.58" (91 mm) Length: 10.65" (271 mm)</p>		<p>Part Number: P537447 Description: AIR CLEANER, DISPOSABLE Primary App: FARR ECOLITE 9.75 X 24 Dimensions: Body Diameter: 9.75" (248 mm) Outlet ID: 6.00" (152 mm) Length: 24.00" (610 mm) Inlet Location: 5.50" (140 mm) Inlet Diameter: 6.00" (152 mm) Inlet Length: 6.75" (171 mm) Rated Flow MR: 1000.00 CFM (28.32 CMM) Restriction HR: 5.00 In H2O (127 mm H2O)</p>
	<p>Part Number: P536940 Description: AIR PRIMARY, RADIALSEAL Primary App: CASE/IH 128781A1 Dimensions: Outer Diameter: 5.44" (138 mm) Inner Diameter: 3.20" (81 mm) Length: 15.15" (385 mm)</p>		<p>Part Number: P537448 Description: AIR CLEANER, DISPOSABLE Primary App: FARR ECOLITE 11 X 24 Dimensions: Body Diameter: 11.00" (279 mm) Outlet ID: 7.00" (178 mm) Length: 24.00" (610 mm) Inlet Location: 5.50" (140 mm) Inlet Diameter: 7.00" (178 mm) Inlet Length: 7.38" (187 mm) Rated Flow HR: 1200.00 CFM (33.98 CMM) Restriction HR: 5.00 In H2O (127 mm H2O)</p>
	<p>Part Number: P536941 Description: AIR SAFETY, RADIALSEAL Primary App: CASE/IH 128782A1 Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 2.55" (65 mm) Length: 14.65" (372 mm)</p>		<p>Part Number: P537449 Description: AIR CLEANER, DISPOSABLE Primary App: FARR ECOLITE 13.5 X 24 Dimensions: Body Diameter: 13.50" (343 mm) Outlet ID: 7.00" (178 mm) Length: 24.00" (610 mm) Inlet Location: 5.50" (140 mm) Inlet Diameter: 7.00" (178 mm) Inlet Length: 8.62" (219 mm) Rated Flow HR: 1500.00 CFM (42.48 CMM) Restriction HR: 5.00 In H2O (127 mm H2O)</p>
	<p>Part Number: P537286 Description: AIR SAFETY, RADIALSEAL Primary App: NAVISTAR 3520401C1 Dimensions: Outer Diameter: 6.52" (166 mm) Inlet Diameter: 5.89" (150 mm) Length: 14.23" (361 mm)</p>		<p>Part Number: P537450 Description: AIR CLEANER, DISPOSABLE Primary App: FARR ECO CM 13.5 X 24 Dimensions: Body Diameter: 13.50" (343 mm) Outlet ID: 8.00" (203 mm) Length: 24.00" (610 mm) Inlet Location: 5.50" (140 mm) Inlet Diameter: 7.00" (178 mm) Inlet Length: 11.12" (282 mm) Rated Flow HR: 1100.00 CFM (31.15 CMM) Restriction HR: 8.00 In H2O (203 mm H2O)</p>
	<p>Part Number: P537355 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON ERA11 AIR CLNR, FRTLNR CLASSIC Dimensions: Outer Diameter: 9.64" (245 mm) Inner Diameter: 5.15" (131 mm) Length: 24.61" (625 mm)</p>		<p>Part Number: P537451 Description: AIR CLEANER, DISPOSABLE Primary App: FARR ECO SE 6.75 X 14 Dimensions: Body Diameter: 6.75" (171 mm) Outlet ID: 2.88" (73 mm) Length: 14.20" (361 mm) Rated Flow HR: 350.00 CFM (9.91 CMM) Restriction HR: 8.00 In H2O (203 mm H2O)</p>
	<p>Part Number: P537369 Description: BREATHER, SPECIAL Primary App: FORD LIGHT TRUCK Dimensions: Height: 1.30" (33 mm) Length: 2.40" (61 mm) Depth: 4.40" (112 mm)</p>		<p>Part Number: P537452 Description: AIR CLEANER, DISPOSABLE Primary App: FARR ECO SE 7.75 X 17 Dimensions: Body Diameter: 7.75" (197 mm) Outlet Diameter: 3.88" (99 mm) Length: 17.20" (437 mm) Rated Flow LR: 355.00 CFM (10.05 CMM) Rated Flow MR: 430.00 CFM (12.17 CMM) Rated Flow HR: 510.00 CFM (14.44 CMM) Restriction LR: 4.00 In H2O (102 mm H2O) Restriction MR: 6.00 In H2O (152 mm H2O) Restriction HR: 8.00 In H2O (203 mm H2O)</p>
	<p>Part Number: P537375 Description: AIR PRIMARY Primary App: GM LIGHT TRUCK Dimensions: Outer Diameter: 5.75" (146 mm) Inner Diameter: 3.58" (91 mm) Length: 5.96" (151 mm)</p>		<p>Part Number: P537452 Description: AIR CLEANER, DISPOSABLE Primary App: FARR ECO SE 7.75 X 17 Dimensions: Body Diameter: 7.75" (197 mm) Outlet Diameter: 3.88" (99 mm) Length: 17.20" (437 mm) Rated Flow LR: 355.00 CFM (10.05 CMM) Rated Flow MR: 430.00 CFM (12.17 CMM) Rated Flow HR: 510.00 CFM (14.44 CMM) Restriction LR: 4.00 In H2O (102 mm H2O) Restriction MR: 6.00 In H2O (152 mm H2O) Restriction HR: 8.00 In H2O (203 mm H2O)</p>
	<p>Part Number: P537377 Description: AIR PANEL, ENGINE Primary App: CLARK, TOWMOTOR Dimensions: Width: 8.38" (213 mm) Depth: 1.63" (41 mm) Height: 8.38" (213 mm)</p>		<p>Part Number: P537452 Description: AIR CLEANER, DISPOSABLE Primary App: FARR ECO SE 7.75 X 17 Dimensions: Body Diameter: 7.75" (197 mm) Outlet Diameter: 3.88" (99 mm) Length: 17.20" (437 mm) Rated Flow LR: 355.00 CFM (10.05 CMM) Rated Flow MR: 430.00 CFM (12.17 CMM) Rated Flow HR: 510.00 CFM (14.44 CMM) Restriction LR: 4.00 In H2O (102 mm H2O) Restriction MR: 6.00 In H2O (152 mm H2O) Restriction HR: 8.00 In H2O (203 mm H2O)</p>



Part Number: P537453
Description: AIR CLEANER, DISPOSABLE
Primary App: FARR ECO SE 9.75 X 20
Dimensions:
 Body Diameter: 9.67" (246 mm)
 Outlet ID: 5.00" (127 mm)
 Length: 20.20" (513 mm)
 Rated Flow HR: 840.00 CFM (23.79 CMM)
 Restriction HR: 8.00 In H2O (203 mm H2O)



Part Number: P537454
Description: AIR CLEANER, DISPOSABLE
Primary App: FARR ECO SE W/SIDE INLET
Dimensions:
 Body Diameter: 9.70" (246 mm)
 Outlet ID: 5.00" (127 mm)
 Length: 19.40" (493 mm)
 Inlet Location: 4.00" (102 mm)
 Inlet Diameter: 6.00" (152 mm)
 Inlet Length: 6.44" (164 mm)
 Rated Flow HR: 960.00 CFM (27.19 CMM)
 Restriction HR: 8.00 In H2O (203 mm H2O)



Part Number: P537455
Description: AIR CLEANER, DISPOSABLE
Primary App: FARR ECO SM 13.5 X 15
Dimensions:
 Body Diameter: 13.50" (343 mm)
 Outlet ID: 7.00" (178 mm)
 Length: 16.80" (427 mm)
 Inlet Location: 5.50" (140 mm)
 Inlet Diameter: 7.00" (178 mm)
 Inlet Length: 8.62" (219 mm)
 Rated Flow HR: 1550.00 CFM (43.90 CMM)
 Restriction HR: 8.00 In H2O (203 mm H2O)



Part Number: P537456
Description: AIR CLEANER, DISPOSABLE
Primary App: FARR ECO SM 13.5 X 15
Dimensions:
 Body Diameter: 13.50" (343 mm)
 Outlet ID: 7.00" (178 mm)
 Length: 16.80" (427 mm)
 Inlet Location: 9.50" (241 mm)
 Inlet Length: 8.62" (219 mm)
 Rated Flow HR: 1530.00 CFM (43.33 CMM)
 Restriction HR: 8.00 In H2O (203 mm H2O)



Part Number: P537716
Description: AIR SAFETY, RADIALSEAL
Primary App: JOHN DEERE AT175345
Dimensions:
 Outer Diameter: 4.27" (108 mm)
 Inner Diameter: 3.45" (88 mm)
 Length: 10.64" (270 mm)



Part Number: P537729
Description: AIR PRIMARY, RADIALSEAL
Primary App: GM 25173425
Dimensions:
 Outer Diameter: 7.50" (190 mm)
 Inner Diameter: 3.58" (91 mm)
 Length: 10.65" (271 mm)



Part Number: P537778
Description: AIR PRIMARY, RADIALSEAL
Primary App: CASE IH 132151A1
Dimensions:
 Outer Diameter: 11.09" (282 mm)
 Inner Diameter: 5.80" (147 mm)
 Length: 21.15" (537 mm)



Part Number: P537779
Description: AIR SAFETY, RADIALSEAL
Primary App: CASE IH 132149A1
Dimensions:
 Outer Diameter: 5.94" (151 mm)
 Inner Diameter: 4.40" (112 mm)
 Length: 20.88" (530 mm)



Part Number: P537791
Description: AIR PRIMARY, KONEPAC™
Primary App: DONALDSON SHORT ECG11 KONEPAC-STANDARD
Dimensions:
 Outer Diameter: 10.62" (270 mm)
 Inner Diameter: 6.69" (170 mm)
 Length: 22.02" (559 mm)
 Gasket OD: 9.21" (234 mm)
 Gasket ID: 5.22" (133 mm)



Part Number: P537876
Description: AIR PRIMARY, RADIALSEAL
Primary App: CASE IH 275809A1, LINK BELT E3H0146
Dimensions:
 Outer Diameter: 11.09" (282 mm)
 Inner Diameter: 5.82" (148 mm)
 Length: 20.08" (510 mm)



Part Number: P537877
Description: AIR SAFETY, RADIALSEAL
Primary App: CASE IH 275810A1, LINK BELT E3H0147
Dimensions:
 Outer Diameter: 5.94" (151 mm)
 Inner Diameter: 4.39" (112 mm)
 Length: 19.02" (483 mm)



Part Number: P538007
Description: AIR PRIMARY, RADIALSEAL
Primary App: CATERPILLAR D11N, 1236855
Dimensions:
 Outer Diameter: 14.28" (363 mm)
 Inner Diameter: 8.98" (228 mm)
 Length: 15.03" (382 mm)



Part Number: P538008
Description: AIR SAFETY, RADIALSEAL
Primary App: CATERPILLAR D11N
Dimensions:
 Outer Diameter: 9.09" (231 mm)
 Inner Diameter: 7.02" (178 mm)
 Length: 15.17" (385 mm)



Part Number: P538359
Description: AIR PRIMARY
Primary App: JOHN DEERE AL65051
Dimensions:
 Outer Diameter: 5.25" (133 mm)
 Inner Diameter: 3.26" (83 mm)
 Length: 12.00" (305 mm)





















Part Number: P538392
Description: AIR PRIMARY, RADIALSEAL
Primary App: JOHN DEERE AT178583
Dimensions:
 Outer Diameter: 9.33" (237 mm)
 Inner Diameter: 5.15" (131 mm)
 Length: 21.50" (546 mm)






Part Number: P538393
Description: AIR SAFETY, RADIALSEAL
Primary App: JOHN DEERE AT178584
Dimensions:
 Outer Diameter: 5.30" (135 mm)
 Inner Diameter: 3.70" (94 mm)
 Length: 21.21" (539 mm)




































Part Number: P538453
Description: AIR PRIMARY
Primary App: AIR MAZE CD1219610826
Dimensions:
 Outer Diameter: 10.00" (254 mm)
 Inner Diameter: 5.88" (149 mm)
 Length: 17.06" (433 mm)
 Bolt Hole Diameter: 0.39" (10 mm)

















	<p>Part Number: P538454 Description: AIR SAFETY Primary App: AIR MAZE CD1219610830 Dimensions: Outer Diameter: 5.68" (144 mm) Inner Diameter: 4.94" (125 mm) Length: 15.56" (395 mm)</p>		<p>Part Number: P539468 Description: BREATHER, SPIN ON Primary App: FIAT-ALLIS 74835378 Dimensions: Outer Diameter: 3.73" (95 mm) Thread Size: 3/4-14 Length: 3.75" (95 mm)</p>
	<p>Part Number: P538456 Description: AIR SAFETY, RADIALSEAL Primary App: JOHN DEERE RE51630 Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 4.39" (112 mm) Length: 14.84" (377 mm)</p>		<p>Part Number: P539470 Description: AIR PRIMARY Primary App: ISUZU 8941042730 Dimensions: Outer Diameter: 6.06" (154 mm) Inner Diameter: 3.14" (80 mm) Length: 7.81" (198 mm) Bolt Hole Diameter: 0.56" (14 mm)</p>
	<p>Part Number: P538542 Description: AIR SAFETY, RADIALSEAL Primary App: FREIGHTLINER FLN SERIES WITH EPG11 HOUSING Dimensions: Outer Diameter: 5.30" (135 mm) Inner Diameter: 4.43" (113 mm) Length: 18.03" (458 mm)</p>		<p>Part Number: P539471 Description: AIR PRIMARY Primary App: METROPLEX M00709102 Dimensions: Outer Diameter: 12.08" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 21.07" (535 mm)</p>
	<p>Part Number: P539242 Description: AIR SAFETY Primary App: JOHN DEERE AL67195 Dimensions: Outer Diameter: 3.62" (92 mm) Inner Diameter: 2.99" (76 mm) Length: 9.25" (235 mm)</p>		<p>Part Number: P539473 Description: AIR PRIMARY Primary App: STEIGER 906443T1 Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 5.87" (149 mm) Length: 17.54" (446 mm) Bolt Hole Diameter: 0.66" (17 mm)</p>
	<p>Part Number: P539458 Description: AIR PRIMARY Primary App: LEROI H43651 Dimensions: Outer Diameter: 4.42" (112 mm) Inner Diameter: 2.98" (76 mm) Length: 4.74" (120 mm)</p>		<p>Part Number: P539474 Description: AIR SAFETY Primary App: STEIGER 906444T1 Dimensions: Outer Diameter: 5.56" (141 mm) Inner Diameter: 4.42" (112 mm) Length: 15.61" (397 mm)</p>
	<p>Part Number: P539460 Description: AIR PRIMARY Primary App: RENAULT/R.V.I. 8983500079 Dimensions: Outer Diameter: 9.70" (246 mm) Inner Diameter: 7.39" (188 mm) Length: 2.48" (63 mm)</p>		<p>Part Number: P539476 Description: AIR PRIMARY Primary App: SULLAIR 250022888 Dimensions: Outer Diameter: 6.70" (170 mm) Inner Diameter: 3.68" (93 mm) Length: 11.04" (280 mm) Bolt Hole Diameter: 0.48" (12 mm)</p>
	<p>Part Number: P539462 Description: AIR PRIMARY Primary App: VOLVO 6888848 Dimensions: Outer Diameter: 14.38" (365 mm) Inner Diameter: 8.26" (210 mm) Length: 16.69" (424 mm) Bolt Hole Diameter: 0.40" (10 mm)</p>		<p>Part Number: P539477 Description: AIR PRIMARY Primary App: TOYOTA 1780124010 Dimensions: Outer Diameter: 7.38" (187 mm) Inner Diameter: 4.34" (110 mm) Length: 2.70" (69 mm)</p>
	<p>Part Number: P539463 Description: AIR PRIMARY Primary App: TOWMOTOR 333660 Dimensions: Outer Diameter: 6.69" (170 mm) Inner Diameter: 5.04" (128 mm) Length: 3.00" (76 mm)</p>		<p>Part Number: P539478 Description: AIR SAFETY Primary App: TEREX 9054912 Dimensions: Outer Diameter: 10.88" (276 mm) Inner Diameter: 8.16" (207 mm) Length: 18.09" (459 mm)</p>
	<p>Part Number: P539466 Description: AIR PRIMARY Primary App: DEUTZ 2339813 Dimensions: Outer Diameter: 6.46" (164 mm) Inner Diameter: 3.38" (86 mm) Length: 7.95" (202 mm)</p>		<p>Part Number: P539479 Description: AIR SAFETY Primary App: ISUZU 1142151570 Dimensions: Outer Diameter: 5.80" (147 mm) Inner Diameter: 3.51" (89 mm) Length: 10.06" (256 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 4.62" (117 mm)</p>

















	<p>Part Number: P539482 Description: AIR SAFETY Primary App: MITSUBISHI MEO33773 Dimensions: Outer Diameter: 5.21" (132 mm) Inner Diameter: 4.16" (106 mm) Length: 11.88" (302 mm)</p>		<p>Part Number: P542033 Description: AIR SAFETY Primary App: KOBELCO 2446R277S6 Dimensions: Outer Diameter: 4.84" (123 mm) Inner Diameter: 3.65" (93 mm) Length: 15.25" (387 mm)</p>
	<p>Part Number: P539484 Description: AIR PRIMARY Primary App: CASE IH A17741 Dimensions: Outer Diameter: 12.00" (305 mm) Inner Diameter: 7.32" (186 mm) Length: 10.76" (273 mm)</p>		<p>Part Number: P542711 Description: AIR SAFETY, RADIALSEAL Primary App: UL APPROVED VERSION OF P829332 Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 2.55" (65 mm) Length: 12.38" (314 mm)</p>
	<p>Part Number: P539486 Description: AIR SAFETY Primary App: CASE IH 530560C1 Dimensions: Outer Diameter: 7.21" (183 mm) Inner Diameter: 5.66" (144 mm) Length: 14.49" (368 mm)</p>		<p>Part Number: P542753 Description: AIR PRIMARY, RADIALSEAL Primary App: PETERBILT, DONALDSON ERA13 Dimensions: Outer Diameter: 11.40" (290 mm) Inner Diameter: 6.78" (172 mm) Length: 21.19" (538 mm)</p>
	<p>Part Number: P539487 Description: AIR PRIMARY Primary App: GM 25096001 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.05" (154 mm) Length: 7.91" (201 mm)</p>		<p>Part Number: P543107 Description: AIR PANEL, VENTILATION Primary App: CATERPILLAR 8C-9657 Dimensions: Width: 6.00" (152 mm) Depth: 2.31" (59 mm) Height: 17.53" (445 mm)</p>
	<p>Part Number: P539765 Description: AIR PRIMARY, RADIALSEAL Primary App: NAVISTAR 3507421C1 Dimensions: Outer Diameter: 9.64" (245 mm) Inner Diameter: 5.15" (131 mm) Length: 23.26" (591 mm)</p>		<p>Part Number: P543614 Description: AIR PRIMARY, RADIALSEAL Primary App: ISUZU 8970622940 Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.15" (131 mm) Length: 10.91" (277 mm)</p>
	<p>Part Number: P540388 Description: AIR PRIMARY, RADIALSEAL Primary App: VOLVO 8076195 Dimensions: Outer Diameter: 13.09" (332 mm) Inner Diameter: 7.69" (195 mm) Length: 15.94" (405 mm)</p>		<p>Part Number: P543661 Description: AIR SAFETY Primary App: HITACHI 4247974 Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 4.13" (105 mm) Length: 9.33" (237 mm)</p>
	<p>Part Number: P540845 Description: AIR PANEL, VENTILATION Primary App: General 10.82 X 10.82 X 2.19 Vent Panel Dimensions: Width: 10.82" (275 mm) Depth: 2.19" (56 mm) Height: 10.82" (275 mm)</p>		<p>Part Number: P543662 Description: AIR PRIMARY Primary App: HITACHI 4285623 Dimensions: Outer Diameter: 6.10" (155 mm) Inner Diameter: 4.09" (104 mm) Length: 12.50" (318 mm) Bolt Hole Diameter: 0.67" (17 mm) Gasket ID: 7.87" (200 mm)</p>
	<p>Part Number: P541575 Description: AIR PRIMARY Primary App: G150144 Dimensions: Outer Diameter: 13.09" (332 mm) Inner Diameter: 6.78" (172 mm) Length: 14.76" (375 mm)</p>		<p>Part Number: P544243 Description: AIR PRIMARY, RADIALSEAL Primary App: PETERBILT, MACK, DONALDSON ERA15 Dimensions: Outer Diameter: 13.06" (332 mm) Inner Diameter: 7.44" (189 mm) Length: 21.38" (543 mm)</p>
	<p>Part Number: P541582 Description: AIR SAFETY Primary App: JOHN DEERE AL27160 Dimensions: Outer Diameter: 3.36" (85 mm) Inner Diameter: 2.90" (74 mm) Length: 9.00" (229 mm)</p>		<p>Part Number: P544301 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON ERA15 RADIAL SEAL AIRCLEANER Dimensions: Outer Diameter: 12.76" (324 mm) Inner Diameter: 7.40" (188 mm) Length: 25.51" (648 mm)</p>









	<p>Part Number: P544432 Description: AIR SAFETY Primary App: FREIGHTLINER M2 SERIES Dimensions: Outer Diameter: 9.03" (229 mm) Length: 1.00" (25 mm)</p>		<p>Part Number: P546598 Description: AIR PRIMARY Primary App: FORD LIGHT TRUCK 1995 - 1998 Dimensions: Outer Diameter: 6.87" (174 mm) Inner Diameter: 3.15" (80 mm) Length: 7.90" (201 mm)</p>
	<p>Part Number: P544741 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON ERA11 RADIAL SEAL AIRCLEANER Dimensions: Outer Diameter: 9.64" (245 mm) Inner Diameter: 5.15" (131 mm) Length: 21.42" (544 mm)</p>		<p>Part Number: P546613 Description: AIR SAFETY Primary App: AIR MAZE CD1628610827 Dimensions: Outer Diameter: 7.38" (187 mm) Inner Diameter: 6.12" (155 mm) Length: 25.38" (645 mm)</p>
	<p>Part Number: P544765 Description: AIR PRIMARY Primary App: ECG 11" AIR CLEANER ASSEMBLY Dimensions: Outer Diameter: 10.62" (270 mm) Inner Diameter: 6.61" (168 mm) Length: 20.04" (509 mm)</p>		<p>Part Number: P546614 Description: AIR PRIMARY Primary App: AIR MAZE CD1628610826 Dimensions: Outer Diameter: 12.56" (319 mm) Inner Diameter: 7.51" (191 mm) Length: 26.81" (681 mm) Bolt Hole Diameter: 0.39" (10 mm)</p>
	<p>Part Number: P544950 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON ERA13 RADIAL SEAL AIRCLEANER Dimensions: Outer Diameter: 11.40" (290 mm) Inner Diameter: 5.82" (148 mm) Length: 22.96" (583 mm)</p>		<p>Part Number: P546641 Description: AIR PRIMARY Primary App: CATERPILLAR 1085330, MITSUBISHI 9136113300 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 2.27" (58 mm) Length: 8.97" (228 mm) D: 6.16" (156 mm)</p>
	<p>Part Number: P545613 Description: AIR PRIMARY Primary App: MITSUBISHI ME073252 Dimensions: Outer Diameter: 9.14" (232 mm) Inner Diameter: 5.78" (147 mm) Length: 17.16" (436 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 6.25" (159 mm)</p>		<p>Part Number: P546755 Description: AIR PRIMARY Primary App: GENERAC GENERATORS Dimensions: Outer Diameter: 11.68" (297 mm) Inner Diameter: 8.13" (207 mm) Length: 10.00" (254 mm)</p>
	<p>Part Number: P546566 Description: AIR PRIMARY, FINNED Primary App: JOHN DEERE RE45827, NEW HOLLAND 86529587 Dimensions: Outer Diameter: 6.08" (154 mm) Inner Diameter: 3.47" (88 mm) Length: 13.00" (330 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P546761 Description: AIR PRIMARY Primary App: AIR MAZE CD1830610826 Dimensions: Outer Diameter: 13.88" (353 mm) Inner Diameter: 9.95" (253 mm) Length: 29.00" (737 mm) Bolt Hole Diameter: 0.52" (13 mm)</p>
	<p>Part Number: P546567 Description: AIR PRIMARY Primary App: GARDNER DENVER EQUIPMENT Dimensions: Outer Diameter: 8.51" (216 mm) Inner Diameter: 5.37" (136 mm) Length: 15.00" (381 mm) Bolt Hole Diameter: 0.44" (11 mm)</p>		<p>Part Number: P546762 Description: AIR SAFETY Primary App: AIR MAZE CD1830610827 Dimensions: Outer Diameter: 9.88" (251 mm) Inner Diameter: 8.06" (205 mm) Length: 27.75" (705 mm)</p>
	<p>Part Number: P546596 Description: AIR PANEL, ENGINE Primary App: MOTORCRAFT FA1680 Dimensions: Width: 7.22" (183 mm) Depth: 13.35" (339 mm) Height: 2.30" (58 mm)</p>		<p>Part Number: P547331 Description: AIR PRIMARY, RADIALSEAL Primary App: CASE IH 187471A1 Dimensions: Outer Diameter: 8.18" (208 mm) Inner Diameter: 4.17" (106 mm) Length: 15.09" (383 mm)</p>
	<p>Part Number: P546597 Description: AIR PRIMARY Primary App: FORD LIGHT TRUCK Dimensions: Outer Diameter: 8.13" (207 mm) Inner Diameter: 4.26" (108 mm) Length: 7.81" (198 mm)</p>		<p>Part Number: P547332 Description: AIR SAFETY, RADIALSEAL Primary App: CASE IH 187472A1 Dimensions: Outer Diameter: 4.27" (108 mm) Inner Diameter: 3.45" (88 mm) Length: 15.08" (383 mm)</p>

















	<p>Part Number: P547520 Description: AIR SAFETY Primary App: FREIGHTLINER M2 HIGH HP Dimensions: Outer Diameter: 9.37" (238 mm) Length: 1.50" (38 mm)</p>		<p>Part Number: P549644 Description: AIR PRIMARY, RADIALSEAL Primary App: KENWORTH T2000 FROM 11/98 Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.78" (172 mm) Length: 15.15" (385 mm)</p>
	<p>Part Number: P548900 Description: AIR PRIMARY, RADIALSEAL Primary App: CASE IH 243968A1 Dimensions: Outer Diameter: 13.09" (332 mm) Inner Diameter: 6.78" (172 mm) Length: 21.86" (555 mm)</p>		<p>Part Number: P550004 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: Renault Dimensions: Outer Diameter: 3.78" (96 mm) Thread Size: M18 x 1.5 Length: 5.59" (142 mm) Gasket OD: 2.80" (71 mm) Gasket ID: 2.44" (62 mm)</p>
	<p>Part Number: P548901 Description: AIR SAFETY, RADIALSEAL Primary App: CASE 243969A1 Dimensions: Outer Diameter: 6.89" (175 mm) Inner Diameter: 5.24" (133 mm) Length: 21.33" (542 mm)</p>		<p>Part Number: P550006 Description: LUBE SPIN-ON FULL FLOW Primary App: MERCEDES, RVI Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 3/4-16 Length: 5.87" (149 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.44" (62 mm)</p>
	<p>Part Number: P548963 Description: AIR PANEL, ENGINE Primary App: CHEVROLET SILVERADO 98-99-00, AF1518 Dimensions: Width: 9.75" (248 mm) Depth: 12.21" (310 mm) Height: 2.31" (59 mm)</p>		<p>Part Number: P550007 Description: FUEL CARTRIDGE Primary App: IHC, DODGE, FORD, JEEP, MELROE Dimensions: Outer Diameter: 1.39" (35 mm) Inner Diameter: 0.50" (13 mm) Length: 1.88" (48 mm) Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P548964 Description: AIR PANEL, ENGINE Primary App: FORD LIGHT TRUCK, AF1658 Dimensions: Width: 7.52" (191 mm) Depth: 8.75" (222 mm) Height: 2.26" (57 mm)</p>		<p>Part Number: P550008 Description: LUBE SPIN-ON FULL FLOW Primary App: FORD, MOTORCRAFT FL1A Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 3/4-16 Length: 5.35" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Relief Valve Setting: 7-10 PSI (0.50 -0.70 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P549271 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON FRG06 AIR CLEANER Dimensions: Outer Diameter: 5.28" (134 mm) Inner Diameter: 3.42" (87 mm) Length: 15.00" (381 mm)</p>		<p>Part Number: P550010 Description: LUBE CARTRIDGE FULL FLOW Primary App: HINO 15607-1090 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 1.92" (49 mm) Length: 6.30" (160 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P549277 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSON FRG06 AIR CLEANER Dimensions: Outer Diameter: 3.57" (91 mm) Inner Diameter: 2.80" (71 mm) Length: 14.65" (372 mm)</p>		<p>Part Number: P550012 Description: FUEL IN-LINE Primary App: PICKUPS AND CARS -- UNIVERSAL 5/16" 2 HOSES 4 CLAMPS Dimensions: Outer Diameter: 1.94" (49 mm) Inlet Size: 5/16" Overall Length: 4.17" (106 mm) Length: 2.36" (60 mm) Outlet Size: 5/16" Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P549523 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON FRG16 AIR CLEANER Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 6.78" (172 mm) Length: 17.99" (457 mm)</p>		<p>Part Number: P550015 Description: LUBE CARTRIDGE FULL FLOW Primary App: ISUZU 9885111940 Dimensions: Outer Diameter: 3.31" (84 mm) Inner Diameter: 0.65" (17 mm) Length: 5.63" (143 mm) Efficiency 50% @ 16 Micron</p>
	<p>Part Number: P549530 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSON FRG16 AIR CLEANER Dimensions: Outer Diameter: 6.89" (175 mm) Inner Diameter: 5.24" (133 mm) Length: 17.83" (453 mm)</p>		

	<p>Part Number: P550016 Description: FUEL IN-LINE Primary App: FORD D7TE9155A, MOTORCRAFT FG778 (1 HOSE 2 CLAMPS INCLUDED) Dimensions: Outer Diameter: 1.33" (34 mm) Inlet Size: 5/16" Body Length: 0.94" (24 mm) Overall Length: 2.71" (69 mm) Outlet Size: 1/8-27 Efficiency 99% @ 100 Micron</p>		<p>Part Number: P550026 Description: FUEL CARTRIDGE Primary App: ISUZU 9-9885111940 Dimensions: Outer Diameter: 2.91" (74 mm) Inner Diameter: 0.63" (16 mm) Length: 4.15" (106 mm) Efficiency 99% @ 30 Micron</p>
	<p>Part Number: P550017 Description: LUBE CARTRIDGE FULL FLOW Primary App: ISUZU 9885132630 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 0.59" (15 mm) Length: 4.17" (106 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P550028 Description: FUEL CARTRIDGE Primary App: NISSAN 16444-99028 Dimensions: Outer Diameter: 4.37" (111 mm) Inner Diameter: 0.59" (15 mm) Length: 5.51" (140 mm) Efficiency 99% @ 30 Micron</p>
	<p>Part Number: P550018 Description: LUBE CARTRIDGE FULL FLOW Primary App: ISUZU 9885132641 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 0.59" (15 mm) Length: 7.30" (185 mm) Efficiency 50% @ 16 Micron</p>		<p>Part Number: P550032 Description: FUEL CARTRIDGE SOCK Primary App: DETROIT DIESEL Dimensions: Outer Diameter: 5.50" (140 mm) Inner Diameter: 2.46" (62 mm) Length: 10.00" (254 mm) Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P550020 Description: LUBE SPIN-ON FULL FLOW Primary App: JOHN DEERE AR58956, T19044 Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 13/16-16 Length: 5.53" (140 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Relief Valve Setting: 18-23 PSI (1.30-1.60 Bar) Efficiency 99% @ 40 Micron</p>		<p>Part Number: P550034 Description: LUBE CARTRIDGE FULL FLOW Primary App: NISSAN 15274-99227 Dimensions: Outer Diameter: 5.12" (130 mm) Inner Diameter: 0.59" (15 mm) Length: 9.17" (233 mm) Efficiency 50% @ 5 Micron</p>
	<p>Part Number: P550021 Description: LUBE CARTRIDGE FULL FLOW Primary App: NISSAN 15274-99329 Dimensions: Outer Diameter: 5.04" (128 mm) Inner Diameter: 0.61" (15 mm) Length: 6.30" (160 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P550035 Description: LUBE SPIN-ON FULL FLOW Primary App: GM, ACPF35 Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 13/16-16 Length: 5.12" (130 mm) Gasket OD: 3.38" (86 mm) Gasket ID: 3.04" (77 mm) Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P550023 Description: FUEL CARTRIDGE Primary App: NISSAN 16444-90127 Dimensions: Outer Diameter: 3.62" (92 mm) Inner Diameter: 0.59" (15 mm) Length: 5.31" (135 mm) Efficiency 99% @ 30 Micron</p>		<p>Part Number: P550037 Description: HYDRAULIC CARTRIDGE Primary App: MITSUBISHI 68937001001 Dimensions: Outer Diameter: 4.47" (114 mm) Inner Diameter: 2.87" (73 mm) Length: 14.72" (374 mm) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P550024 Description: LUBE SPIN-ON FULL FLOW Primary App: ALLIS CHALMERS, CASE, IHC Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 13/16-16 Length: 5.18" (132 mm) Gasket OD: 2.82" (72 mm) Gasket ID: 2.42" (61 mm) Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>		<p>Part Number: P550038 Description: FUEL CARTRIDGE Primary App: HINO 23401-1060 Dimensions: Outer Diameter: 2.44" (62 mm) Inner Diameter: 0.43" (11 mm) Length: 2.36" (60 mm) Efficiency 99% @ 30 Micron</p>
	<p>Part Number: P550025 Description: LUBE SPIN-ON FULL FLOW Primary App: GMC 6CYL. & V8 GAS Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 13/16-16 Length: 4.22" (107 mm) Gasket OD: 3.38" (86 mm) Gasket ID: 3.04" (77 mm) Efficiency 99% @ 40 Micron</p>		<p>Part Number: P550040 Description: FUEL CARTRIDGE Primary App: HITACHI 4514801, ISUZU 1878100270 Dimensions: Outer Diameter: 3.53" (90 mm) Inner Diameter: 0.57" (14 mm) Length: 5.31" (135 mm) Efficiency 50% @ 5 Micron</p>
			<p>Part Number: P550041 Description: LUBE CARTRIDGE FULL FLOW Primary App: MERCEDES BENZ 001 1843825, M.A.N. Dimensions: Outer Diameter: 4.76" (121 mm) Inner Diameter: 2.20" (56 mm) Length: 9.60" (244 mm) Overall Length: 10.44" (265 mm) Efficiency 50% @ 20 Micron</p>

	<p>Part Number: P550042 Description: FUEL CARTRIDGE Primary App: ISUZU 1878102070 Dimensions: Outer Diameter: 4.00" (102 mm) Inner Diameter: 0.57" (14 mm) Length: 6.32" (161 mm) Efficiency 99% @ 30 Micron</p>		<p>Part Number: P550051 Description: LUBE SPIN-ON FULL FLOW Primary App: GMC 25010908 Dimensions: Outer Diameter: 3.00" (76 mm) Thread Size: M18 x 1.5 Length: 5.09" (129 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.39" (61 mm) Anti Drain Valve: Yes Y/N Efficiency 99% @ 45 Micron</p>
	<p>Part Number: P550043 Description: FUEL CARTRIDGE Primary App: CUMMINS, HOUGH, MICH 139097, 256834 Dimensions: Outer Diameter: 5.81" (148 mm) Inner Diameter: 1.00" (25 mm) Length: 9.37" (238 mm) ID Width: 1.77" (45 mm) Efficiency 99% @ 20 Micron</p>		<p>Part Number: P550052 Description: LUBE CARTRIDGE FULL FLOW Primary App: MASSEY FERGUSON 101811M91, 1881840M1, 894976M91 Dimensions: Outer Diameter: 2.85" (72 mm) Inner Diameter: 1.30" (33 mm) Length: 5.39" (137 mm)</p>
	<p>Part Number: P550044 Description: FUEL CARTRIDGE Primary App: MITSUBISHI 30062-65011 Dimensions: Outer Diameter: 3.54" (90 mm) Inner Diameter: 0.57" (14 mm) Length: 5.52" (140 mm) Efficiency 99% @ 30 Micron</p>		<p>Part Number: P550054 Description: FUEL CARTRIDGE Primary App: MITSUBISHI ME036478 Dimensions: Outer Diameter: 3.62" (92 mm) Inner Diameter: 0.59" (15 mm) Length: 4.33" (110 mm) Efficiency 99% @ 30 Micron</p>
	<p>Part Number: P550045 Description: LUBE SPIN-ON FULL FLOW Primary App: GMC 25010324 Dimensions: Outer Diameter: 3.00" (76 mm) Thread Size: 13/16-16 Length: 4.74" (120 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.36" (60 mm)</p>		<p>Part Number: P550055 Description: FUEL CARTRIDGE Primary App: NISSAN 16444-99128 Dimensions: Outer Diameter: 3.61" (92 mm) Inner Diameter: 0.59" (15 mm) Length: 5.28" (134 mm) Efficiency 99% @ 30 Micron</p>
	<p>Part Number: P550047 Description: LUBE SPIN-ON FULL FLOW Primary App: AMC, GMC 25010792 Dimensions: Outer Diameter: 3.00" (76 mm) Thread Size: M18 x 1.5 Length: 3.40" (86 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.39" (61 mm) Relief Valve Setting: 7-9 PSI (0.50-0.60 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 45 Micron</p>		<p>Part Number: P550056 Description: FUEL CARTRIDGE Primary App: NISSAN 16444-29000 Dimensions: Outer Diameter: 2.83" (72 mm) Inner Diameter: 0.43" (11 mm) Length: 3.54" (90 mm) Efficiency 99% @ 30 Micron</p>
	<p>Part Number: P550048 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: MITSUBISHI ME006066 Dimensions: Outer Diameter: 3.74" (95 mm) Thread Size: M20 x 1.5 Length: 3.15" (80 mm) Gasket OD: 2.52" (64 mm) Gasket ID: 2.28" (58 mm) Efficiency 99% @ 30 Micron</p>		<p>Part Number: P550057 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: TOYOTA 23303-56301 Dimensions: Outer Diameter: 3.30" (84 mm) Thread Size: 3/4-16 Length: 3.39" (86 mm) Gasket OD: 2.50" (64 mm) Gasket ID: 2.11" (54 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P550049 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: MITSUBISHI ME016823 Dimensions: Outer Diameter: 3.68" (93 mm) Thread Size: M20 x 1.5 Length: 3.94" (100 mm) Gasket OD: 2.54" (65 mm) Gasket ID: 2.28" (58 mm) Efficiency 99% @ 30 Micron</p>		<p>Part Number: P550058 Description: LUBE CARTRIDGE Primary App: HINO 156071010 Dimensions: Outer Diameter: 4.81" (122 mm) Inner Diameter: 0.66" (17 mm) Length: 8.86" (225 mm)</p>
	<p>Part Number: P550050 Description: LUBE SPIN-ON BYPASS Primary App: CAT, AMC, MF, ALLIS 74512207 Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 5/8-18 Length: 5.22" (133 mm) Gasket OD: 2.82" (72 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 45 Micron</p>		<p>Part Number: P550059 Description: LUBE CARTRIDGE FULL FLOW Primary App: HITACHI 4505384 Dimensions: Outer Diameter: 4.10" (104 mm) Inner Diameter: 0.59" (15 mm) Length: 9.13" (232 mm) Efficiency 50% @ 16 Micron</p>

	<p>Part Number: P550060 Description: FUEL CARTRIDGE Primary App: DEUTZ, ATLAS COPCO (Pleated Paper) Dimensions: Outer Diameter: 2.60" (66 mm) Inner Diameter: 0.55" (14 mm) Length: 4.30" (109 mm) Efficiency 99% @ 9 Micron</p>		<p>Part Number: P550070 Description: LUBE CARTRIDGE FULL FLOW Primary App: MITSUBISHI ME034481 Dimensions: Outer Diameter: 3.98" (101 mm) Inner Diameter: 0.65" (17 mm) Length: 7.68" (195 mm) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P550061 Description: FUEL CARTRIDGE Primary App: DEUTZ 1168469 Dimensions: Outer Diameter: 3.30" (84 mm) Inner Diameter: 0.53" (13 mm) Length: 5.30" (135 mm)</p>		<p>Part Number: P550071 Description: LUBE CARTRIDGE FULL FLOW Primary App: MITSUBISHI ME064289 Dimensions: Outer Diameter: 4.57" (116 mm) Inner Diameter: 2.12" (54 mm) Length: 12.68" (322 mm) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P550062 Description: LUBE CARTRIDGE FULL FLOW Primary App: HITACHI 4507886 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 0.59" (15 mm) Length: 5.67" (144 mm) Efficiency 50% @ 16 Micron</p>		<p>Part Number: P550073 Description: LUBE SPIN-ON FULL FLOW Primary App: NISSAN 15208-Z9001 Dimensions: Outer Diameter: 4.50" (114 mm) Thread Size: 1 1/8-16 Length: 8.50" (216 mm) Gasket OD: 3.34" (85 mm) Gasket ID: 2.95" (75 mm) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P550065 Description: LUBE CARTRIDGE KIT Primary App: MITSUBISHI ME064356 Dimensions: Outer Diameter: 5.12" (130 mm) Inner Diameter: 0.59" (15 mm) Length: 11.79" (299 mm) Efficiency 99% @ 48 Micron</p>		<p>Part Number: P550074 Description: LUBE CARTRIDGE Primary App: NISSAN 15274-Z9029 Dimensions: Outer Diameter: 3.89" (99 mm) Inner Diameter: 0.66" (17 mm) Length: 5.67" (144 mm)</p>
	<p>Part Number: P550066 Description: LUBE CARTRIDGE FULL FLOW Primary App: MITSUBISHI 31240-53054 Dimensions: Outer Diameter: 5.02" (128 mm) Inner Diameter: 2.26" (57 mm) Length: 5.59" (142 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P550075 Description: LUBE CARTRIDGE Primary App: NISSAN 15274-99428 Dimensions: Outer Diameter: 3.82" (97 mm) Inner Diameter: 1.73" (44 mm) Length: 5.74" (146 mm)</p>
	<p>Part Number: P550067 Description: LUBE SPIN-ON FULL FLOW Primary App: MITSUBISHI ME014833, ME004099 Dimensions: Outer Diameter: 4.20" (107 mm) Thread Size: M20 x 1.5 Length: 4.98" (126 mm) Gasket OD: 3.90" (99 mm) Gasket ID: 3.46" (88 mm) Efficiency 50% @ 16 Micron</p>		<p>Part Number: P550077 Description: LUBE CARTRIDGE FULL FLOW Primary App: NISSAN 15274-90225 Dimensions: Outer Diameter: 3.94" (100 mm) Inner Diameter: 1.73" (44 mm) Length: 7.24" (184 mm) Efficiency 50% @ 16 Micron</p>
	<p>Part Number: P550068 Description: LUBE CARTRIDGE FULL FLOW Primary App: MITSUBISHI ME021254 Dimensions: Outer Diameter: 3.98" (101 mm) Inner Diameter: 1.10" (28 mm) Length: 9.25" (235 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P550078 Description: LUBE SPIN-ON FULL FLOW Primary App: TOYOTA 15601-33010 Dimensions: Outer Diameter: 3.31" (84 mm) Thread Size: 3/4-16 Length: 4.92" (125 mm) Gasket OD: 2.47" (63 mm) Gasket ID: 2.25" (57 mm) Anti Drain Valve: Yes Y/N Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P550069 Description: LUBE CARTRIDGE FULL FLOW Primary App: MITSUBISHI ME034161 Dimensions: Outer Diameter: 3.98" (101 mm) Inner Diameter: 1.22" (31 mm) Length: 7.64" (194 mm)</p>		<p>Part Number: P550079 Description: HYDRAULIC CARTRIDGE Primary App: IHC 1140079-C1 Dimensions: Outer Diameter: 4.51" (115 mm) Inner Diameter: 2.30" (58 mm) Length: 9.02" (229 mm) Efficiency 50% @ 3 Micron</p>

	<p>Part Number: P550080 Description: LUBE CARTRIDGE FULL FLOW Primary App: HINO 6071-2104-40 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 1.26" (32 mm) Length: 6.69" (170 mm) Efficiency 50% @ 16 Micron</p>		<p>Part Number: P550088 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: FORD 6.6L & 7.8L ENG #E7HZ4N184A, RACOR R26P Dimensions: Outer Diameter: 3.75" (95 mm) Thread Size: 1-14 Length: 4.12" (105 mm) Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P550081 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: BEDFORD 90166585 Dimensions: Outer Diameter: 3.31" (84 mm) Thread Size: M16 x 1.5 Length: 3.89" (99 mm) Gasket OD: 2.75" (70 mm) Gasket ID: 2.47" (63 mm)</p>		<p>Part Number: P550089 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: DETROIT DIESEL 8.2L ENG, FORD TRK & BUS Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 1-12 Length: 4.25" (108 mm) Gasket OD: 3.55" (90 mm) Gasket ID: 3.18" (81 mm) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P550082 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU DOZERS D50A, 53A, 58-1, P-17 Dimensions: Outer Diameter: 2.56" (65 mm) Inner Diameter: 1.00" (25 mm) Length: 10.94" (278 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P550090 Description: FUEL IN-LINE Primary App: FORD, GMC -- 2 HOSES 4 CLAMPS INCLUDED Dimensions: Outer Diameter: 1.94" (49 mm) Inlet Size: 3/8" Overall Length: 3.88" (99 mm) Outlet Size: 3/8" Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P550083 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 198-49-11440 Dimensions: Outer Diameter: 4.41" (112 mm) Inner Diameter: 2.76" (70 mm) Length: 11.50" (292 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P550091 Description: FUEL IN-LINE Primary App: FORD, MOTORCRAFT FG14 -- 1 HOSE 2 CLAMPS INCLUDED Dimensions: Outer Diameter: 1.06" (27 mm) Inlet Size: 5/16" Overall Length: 2.86" (73 mm) Outlet Size: 1/8-27 Efficiency 99% @ 100 Micron</p>
	<p>Part Number: P550084 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 4241611140, WHEEL LOADERS Dimensions: Outer Diameter: 4.22" (107 mm) Inner Diameter: 1.78" (45 mm) Length: 9.00" (229 mm) Efficiency 50% @ 14 Micron Efficiency 99% @ 30 Micron</p>		<p>Part Number: P550092 Description: LUBE CARTRIDGE FULL FLOW Primary App: AC, CASE, CAT, CLARK, FTGD LF503 Dimensions: Outer Diameter: 3.75" (95 mm) Inner Diameter: 1.04" (26 mm) Length: 5.94" (151 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P550085 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 101-60-15171 Dimensions: Outer Diameter: 2.56" (65 mm) Inner Diameter: 1.07" (27 mm) Length: 5.62" (143 mm) Efficiency 50% @ 12 Micron</p>		<p>Part Number: P550094 Description: FUEL IN-LINE Primary App: UNIVERSAL 1/4" O.D. LINES, Dimensions: Outer Diameter: 1.94" (49 mm) Inlet Size: 1/4" Overall Length: 4.06" (103 mm) Outlet Size: 1/4" Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P550086 Description: LUBE SPIN-ON FULL FLOW Primary App: KOMATSU 6136-51-5120 Dimensions: Outer Diameter: 4.26" (108 mm) Thread Size: 1 1/8-16 Length: 6.57" (167 mm) Gasket OD: 3.89" (99 mm) Gasket ID: 3.55" (90 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P550095 Description: LUBE SPIN-ON FULL FLOW Primary App: FORD, ONAN Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 3/4-16 Length: 3.72" (95 mm) Gasket OD: 2.82" (72 mm) Gasket ID: 2.42" (61 mm) Relief Valve Setting: 8-11 PSI (0.60-0.80 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 36 Micron</p>
	<p>Part Number: P550087 Description: LUBE CARTRIDGE FULL FLOW Primary App: KOMATSU 6610-50-5100 Dimensions: Outer Diameter: 5.04" (128 mm) Inner Diameter: 2.22" (56 mm) Length: 9.10" (231 mm)</p>		<p>Part Number: P550104 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CUMMINS 138627 Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 1-14 Length: 4.22" (107 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 25 Micron</p>

	<p>Part Number: P550105 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CUMMINS 154709 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-14 Length: 5.35" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 25 Micron</p>		<p>Part Number: P550125 Description: FUEL CARTRIDGE Primary App: CUMMINS 130909,299125 Dimensions: Outer Diameter: 4.64" (118 mm) Inner Diameter: 0.87" (22 mm) Length: 8.39" (213 mm) Efficiency 99% @ 20 Micron</p>
	<p>Part Number: P550106 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CUMMINS D156172, 202893, FURN GSKT-P169192 Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 1-14 Length: 7.40" (188 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 25 Micron</p>		<p>Part Number: P550126 Description: FUEL IN-LINE Primary App: FORD E3FZ9155C Dimensions: Outer Diameter: 2.97" (75 mm) Inlet Size: 5/16" Overall Length: 5.82" (148 mm) Outlet Size: 5/16" Efficiency 50% @ 23 Micron</p>
	<p>Part Number: P550108 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: JOHN DEERE AR45098, AR45097 Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 1-14 Length: 5.68" (144 mm) Gasket OD: 2.84" (72 mm) Gasket ID: 2.47" (63 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P550127 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: KUBOTA 70000-43081 Dimensions: Outer Diameter: 3.00" (76 mm) Thread Size: M20 x 1.5 Length: 3.40" (86 mm) Gasket OD: 2.70" (69 mm) Gasket ID: 2.33" (59 mm) Efficiency 99% @ 17 Micron</p>
	<p>Part Number: P550109 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: FORD D3HE9176AA Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 1-14 Length: 5.70" (145 mm)</p>		<p>Part Number: P550128 Description: HYDRAULIC CARTRIDGE Primary App: IHC 401073R2, 530144R92 Dimensions: Outer Diameter: 5.00" (127 mm) Inner Diameter: 3.00" (76 mm) Length: 3.00" (76 mm)</p>
	<p>Part Number: P550110 Description: FUEL SPIN-ON SECONDARY Primary App: CASE A39867 Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 15/16-16 Length: 4.75" (121 mm) Gasket OD: 2.82" (72 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 8 Micron</p>		<p>Part Number: P550132 Description: LUBE CARTRIDGE FULL FLOW Primary App: DET. DIESEL ENG W/CARTRIDGE LUBE Dimensions: Outer Diameter: 4.30" (109 mm) Inner Diameter: 1.45" (37 mm) Length: 8.90" (226 mm) Efficiency 99% @ 30 Micron</p>
	<p>Part Number: P550115 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: FUEL DISPENSING PUMPS Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 1-12 Length: 5.37" (136 mm) Gasket OD: 2.84" (72 mm) Gasket ID: 2.47" (63 mm) Efficiency 99% @ 45 Micron</p>		<p>Part Number: P550133 Description: HYDRAULIC CARTRIDGE Primary App: CASE D43800, D43801 Dimensions: Outer Diameter: 2.63" (67 mm) Inner Diameter: 1.25" (32 mm) Length: 7.25" (184 mm)</p>
	<p>Part Number: P550117 Description: LUBE CARTRIDGE Primary App: CLARK EUCLID GMC 5572425 (MILITARY SEN.) Dimensions: Outer Diameter: 4.02" (102 mm) Inner Diameter: 0.55" (14 mm) Length: 8.00" (203 mm) Efficiency 99% @ 20 Micron</p>		<p>Part Number: P550138 Description: HYDRAULIC CARTRIDGE Primary App: GRESEN 3294 Dimensions: Outer Diameter: 4.50" (114 mm) Inner Diameter: 1.78" (45 mm) Length: 7.00" (178 mm) Efficiency 50% @ 26 Micron</p>
	<p>Part Number: P550120 Description: FUEL CARTRIDGE Primary App: MANN BF700X Dimensions: Outer Diameter: 2.59" (66 mm) Inner Diameter: 0.62" (16 mm) Length: 4.47" (114 mm) Efficiency 99% @ 20 Micron</p>		<p>Part Number: P550140 Description: HYDRAULIC CARTRIDGE Primary App: IHC 612713C91 Dimensions: Outer Diameter: 4.51" (115 mm) Inner Diameter: 2.30" (58 mm) Length: 7.04" (179 mm) Efficiency 50% @ 20 Micron</p>
			<p>Part Number: P550141 Description: LUBE CARTRIDGE FULL FLOW Primary App: JOY, GMC 5576054, 5574540 Dimensions: Outer Diameter: 3.56" (90 mm) Inner Diameter: 1.28" (33 mm) Length: 5.69" (145 mm) Efficiency 50% @ 20 Micron</p>



Part Number: P550147
Description: LUBE CARTRIDGE SOCK
Primary App: GMC 5574978
Dimensions:
 Outer Diameter: 4.38" (111 mm)
 Inner Diameter: 1.44" (37 mm)
 Length: 5.75" (146 mm)
 Efficiency 99% @ 40 Micron



Part Number: P550148
Description: HYDRAULIC SPIN-ON
Primary App: UCC MX1591-4-10
Dimensions:
 Outer Diameter: 5.04" (128 mm)
 Thread Size: 1 1/4 BSP
 Length: 7.00" (178 mm)
 Gasket OD: 4.27" (108 mm)
 Gasket ID: 3.91" (99 mm)
 Efficiency 50% @ 10 Micron



Part Number: P550152
Description: LUBE SPIN-ON FULL FLOW
Primary App: FIAT ALLIS, A.CHALMERS 4023548-3
Dimensions:
 Outer Diameter: 4.28" (109 mm)
 Thread Size: 1-16
 Length: 5.78" (147 mm)
 Gasket OD: 2.83" (72 mm)
 Gasket ID: 2.45" (62 mm)
 Efficiency 99% @ 40 Micron



Part Number: P550154
Description: LUBE SPIN-ON BYPASS
Primary App: IHC 538836R1
Dimensions:
 Outer Diameter: 3.73" (95 mm)
 Thread Size: 5/8-18
 Length: 4.31" (109 mm)
 Gasket OD: 2.83" (72 mm)
 Gasket ID: 2.46" (62 mm)
 Efficiency 99% @ 45 Micron



Part Number: P550157
Description: LUBE SPIN-ON FULL FLOW
Primary App: FORD EDNN6714AA
Dimensions:
 Outer Diameter: 5.56" (141 mm)
 Thread Size: 1 1/8-16
 Length: 6.00" (152 mm)
 Gasket OD: 4.37" (111 mm)
 Gasket ID: 3.97" (101 mm)
 Relief Valve Setting: 18 - 22 PSI (1.24 - 1.52 Bar)



Part Number: P550158
Description: LUBE SPIN-ON FULL FLOW
Primary App: FORD E3TZ6731C
Dimensions:
 Outer Diameter: 3.69" (94 mm)
 Thread Size: M20 x 1.5
 Length: 5.37" (136 mm)
 Gasket OD: 2.81" (71 mm)
 Gasket ID: 2.46" (62 mm)
 Relief Valve Setting: 8-11 PSI (0.60-0.80 Bar)
 Anti Drain Valve: Yes Y/N
 Efficiency 50% @ 27 Micron



Part Number: P550159
Description: HYDRAULIC/LUBE SPIN-ON
Primary App: IHC 995285C1
Dimensions:
 Outer Diameter: 3.81" (97 mm)
 Thread Size: 13/16-16
 Length: 4.22" (107 mm)
 Relief Valve Setting: 8-11 PSI (0.60-0.80 Bar)



Part Number: P550162
Description: LUBE SPIN-ON FULL FLOW
Primary App: ISUZU, HONDA
Dimensions:
 Outer Diameter: 3.18" (81 mm)
 Thread Size: M20 x 1.5
 Length: 3.39" (86 mm)
 Gasket OD: 2.50" (64 mm)
 Gasket ID: 2.11" (54 mm)
 Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar)
 Anti Drain Valve: Yes Y/N
 Efficiency 99% @ 39 Micron



Part Number: P550165
Description: LUBE CARTRIDGE FULL FLOW
Primary App: CAT, LINK BELT 9F6742, LEROI
Dimensions:
 Outer Diameter: 3.11" (79 mm)
 Inner Diameter: 1.38" (35 mm)
 Length: 9.04" (230 mm)



Part Number: P550166
Description: LUBE SPIN-ON FULL FLOW
Primary App: ONAN 122-0550
Dimensions:
 Outer Diameter: 3.67" (93 mm)
 Thread Size: M22 x 1.5
 Length: 5.42" (138 mm)
 Gasket OD: 2.83" (72 mm)
 Gasket ID: 2.46" (62 mm)
 Relief Valve Setting: 17-22 PSI (1.20-1.50 Bar)
 Efficiency 99% @ 45 Micron



Part Number: P550170
Description: LUBE CARTRIDGE FULL FLOW
Primary App: FRAM F4
Dimensions:
 Outer Diameter: 4.09" (102 mm)
 Inner Diameter: 0.55" (14 mm)
 Length: 5.00" (127 mm)



Part Number: P550171
Description: LUBE CARTRIDGE
Primary App: FRAM F21
Dimensions:
 Outer Diameter: 4.09" (104 mm)
 Inner Diameter: 0.55" (14 mm)
 Length: 5.00" (127 mm)






Part Number: P550173
Description: LUBE SPIN-ON FULL FLOW
Primary App: CHRYSLER
Dimensions:
 Outer Diameter: 3.67" (93 mm)
 Thread Size: M20 x 1.5
 Length: 3.16" (80 mm)
 Gasket OD: 2.63" (67 mm)
 Relief Valve Setting: 8-10 PSI (0.60-0.70 Bar)
 Anti Drain Valve: Yes Y/N



Part Number: P550174
Description: LUBE CARTRIDGE FULL FLOW
Primary App: IHC 213445R91
Dimensions:
 Outer Diameter: 4.59" (117 mm)
 Inner Diameter: 2.25" (57 mm)
 Length: 7.00" (178 mm)
 Efficiency 99% @ 18 Micron



Part Number: P550179
Description: LUBE CARTRIDGE
Primary App: CASE 08152AB
Dimensions:
 Outer Diameter: 3.52" (89 mm)
 Inner Diameter: 0.69" (18 mm)
 Length: 4.16" (106 mm)
 Efficiency 50% @ 10 Micron

	<p>Part Number: P550181 Description: LUBE CARTRIDGE Primary App: IHC 376375R91 Dimensions: Outer Diameter: 3.26" (83 mm) Inner Diameter: 0.48" (12 mm) Length: 7.58" (193 mm) Efficiency 99% @ 20 Micron</p>		<p>Part Number: P550201 Description: FUEL CARTRIDGE SECONDARY Primary App: MACK 237-GB-28 Dimensions: Outer Diameter: 3.19" (81 mm) Inner Diameter: 1.06" (27 mm) Length: 4.53" (115 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P550183 Description: LUBE CARTRIDGE FULL FLOW Primary App: FORD E1ADKN18662A Dimensions: Outer Diameter: 2.75" (70 mm) Inner Diameter: 1.31" (33 mm) Length: 6.00" (152 mm) Efficiency 99% @ 36 Micron</p>		<p>Part Number: P550202 Description: FUEL SPIN ON Primary App: CUMMINS 299202 Dimensions: Outer Diameter: 4.66" (118 mm) Thread Size: 1 1/4-12 Length: 10.24" (260 mm) Gasket OD: 4.32" (110 mm) Gasket ID: 3.85" (98 mm) Efficiency 99% @ 9 Micron</p>
	<p>Part Number: P550184 Description: LUBE CARTRIDGE FULL FLOW Primary App: FORD A730X6731TA Dimensions: Outer Diameter: 2.83" (72 mm) Inner Diameter: 0.83" (21 mm) Length: 4.47" (114 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P550203 Description: LUBE CARTRIDGE FULL FLOW Primary App: FIAT ALLIS, CASE, CLARK, MF, HYSTER, GALION Dimensions: Outer Diameter: 3.91" (99 mm) Inner Diameter: 0.57" (15 mm) Length: 4.37" (111 mm) Efficiency 99% @ 20 Micron</p>
	<p>Part Number: P550185 Description: LUBE CARTRIDGE FULL FLOW Primary App: MASSEY FERGUSON 1852331M1 Dimensions: Outer Diameter: 3.82" (97 mm) Inner Diameter: 1.35" (34 mm) Length: 4.41" (112 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P550209 Description: FUEL IN-LINE Primary App: GM Light Truck Dimensions: Outer Diameter: 2.17" (55 mm) Inlet Size: M16 x 1.5 Overall Length: 4.29" (109 mm) Length: 3.09" (78 mm) Outlet Size: M16 x 1.5 Efficiency 50% @ 23 Micron</p>
	<p>Part Number: P550186 Description: LUBE CARTRIDGE Primary App: IHC 355009R91 Dimensions: Outer Diameter: 3.47" (89 mm) Inner Diameter: 0.94" (24 mm) Length: 5.53" (141 mm) Efficiency 99% @ 20 Micron</p>		<p>Part Number: P550210 Description: HYDRAULIC/LUBE SPIN-ON Primary App: JOHN DEERE AM39653 Dimensions: Outer Diameter: 3.88" (99 mm) Thread Size: 3/4-16 Length: 3.80" (97 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P550188 Description: LUBE SPIN-ON FULL FLOW Primary App: CUMMINS 170200 Dimensions: Outer Diameter: 3.68" (93 mm) Thread Size: 13/16-16 Length: 5.44" (138 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.46" (62 mm) Relief Valve Setting: 8-10 PSI (0.60-0.70 Bar) Efficiency 99% @ 40 Micron</p>		<p>Part Number: P550212 Description: HYDRAULIC CARTRIDGE Primary App: HILCO PL718-5 Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 2.60" (66 mm) Length: 18.00" (457 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 17 Micron</p>
	<p>Part Number: P550190 Description: LUBE CARTRIDGE FULL FLOW Primary App: GMC 6437562, AC PF166 Dimensions: Outer Diameter: 3.56" (90 mm) Inner Diameter: 1.28" (33 mm) Length: 8.44" (214 mm) Efficiency 99% @ 36 Micron</p>		<p>Part Number: P550213 Description: HYDRAULIC CARTRIDGE Primary App: HILCO PL-718-10 Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 2.60" (66 mm) Length: 18.00" (457 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P550194 Description: LUBE SPIN-ON FULL FLOW Primary App: WISCONSIN RV38 Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 5/8-18 Length: 5.68" (144 mm) Relief Valve Setting: 12-15 PSI (0.80-1.00 Bar)</p>		<p>Part Number: P550214 Description: FUEL CARTRIDGE Primary App: CLARK, GMC, IHC, AUTO, PICKUP Dimensions: Outer Diameter: 2.14" (54 mm) Inner Diameter: 0.44" (11 mm) Length: 3.47" (88 mm) Efficiency 99% @ 20 Micron</p>



Part Number: P550215
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: WATER ABSORBING, FUEL DISPENSING PUMPS
Dimensions:
 Outer Diameter: 3.69" (94 mm)
 Thread Size: 1-12
 Length: 5.37" (136 mm)
 Gasket OD: 2.84" (72 mm)
 Gasket ID: 2.46" (62 mm)
 Efficiency 99% @ 22 Micron



Part Number: P550216
Description: HYDRAULIC CARTRIDGE
Primary App: HILCO PL-718
Dimensions:
 Outer Diameter: 6.00" (152 mm)
 Inner Diameter: 2.60" (66 mm)
 Length: 18.00" (457 mm)
 Efficiency 50% @ 25 Micron



Part Number: P550218
Description: FUEL SPIN-ON SECONDARY
Primary App: MACK 483-GB-218B
Dimensions:
 Outer Diameter: 4.28" (109 mm)
 Thread Size: 7/8-16
 Length: 7.89" (200 mm)
 Gasket OD: 2.82" (72 mm)
 Gasket ID: 2.42" (61 mm)
 Efficiency 99% @ 17 Micron



Part Number: P550219
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: MACK 483-GB-219A
Dimensions:
 Outer Diameter: 4.28" (109 mm)
 Thread Size: 13/16-18
 Length: 7.89" (200 mm)
 Gasket OD: 2.82" (72 mm)
 Gasket ID: 2.42" (61 mm)
 Efficiency 50% @ 14 Micron



Part Number: P550220
Description: LUBE CARTRIDGE FULL FLOW
Primary App: SCANIA 1329876, 1381235
Dimensions:
 Outer Diameter: 3.31" (84 mm)
 Inner Diameter: 0.75" (19 mm)
 Length: 4.21" (107 mm)



Part Number: P550222
Description: HYDRAULIC SPIN-ON
Primary App: GMC 25010543
Dimensions:
 Outer Diameter: 3.66" (93 mm)
 Thread Size: 3/4-16
 Length: 5.37" (136 mm)
 Gasket OD: 2.81" (71 mm)
 Gasket ID: 2.42" (61 mm)
 Relief Valve Setting: 7-10 PSI (0.50-0.70 Bar)
 Anti Drain Valve: Yes Y/N
 Efficiency 50% @ 20 Micron



Part Number: P550223
Description: HYDRAULIC SPIN-ON
Primary App: GMC 25010643, AC #HD223, ALLISON TRANS.
Dimensions:
 Outer Diameter: 4.87" (124 mm)
 Thread Size: 1 5/16-12
 Length: 10.23" (260 mm)
 Gasket OD: 4.04" (103 mm)
 Gasket ID: 3.64" (92 mm)
 Efficiency 50% @ 15 Micron



Part Number: P550225
Description: FUEL SPIN-ON SECONDARY
Primary App: HINO 23401-1332, NISSAN 16403Z9003
Dimensions:
 Outer Diameter: 3.31" (84 mm)
 Thread Size: 3/4-16
 Length: 3.94" (100 mm)
 Gasket OD: 2.48" (63 mm)
 Gasket ID: 2.08" (53 mm)
 Efficiency 50% @ 10 Micron



Part Number: P550226
Description: LUBE SPIN-ON FULL FLOW
Primary App: IVECO 1902047
Dimensions:
 Outer Diameter: 4.40" (112 mm)
 Thread Size: 3/4-16
 Length: 5.70" (145 mm)
 Gasket OD: 2.83" (72 mm)
 Gasket ID: 2.44" (62 mm)
 Relief Valve Setting: 20-23 PSI (1.30-1.80 Bar)
 Anti Drain Valve: Yes Y/N
 Efficiency 50% @ 4 Micron



Part Number: P550227
Description: LUBE SPIN-ON FULL FLOW
Primary App: SUBARU, PINTO, DATSUN
Dimensions:
 Outer Diameter: 3.31" (84 mm)
 Thread Size: 3/4-16
 Length: 3.93" (100 mm)
 Gasket OD: 2.47" (63 mm)
 Gasket ID: 2.25" (57 mm)
 Anti Drain Valve: Yes Y/N
 Efficiency 99% @ 45 Micron



Part Number: P550229
Description: HYDRAULIC SPIN-ON
Primary App: LINDE 009830615
Dimensions:
 Outer Diameter: 3.82" (97 mm)
 Thread Size: 1-12
 Length: 7.01" (178 mm)
 Gasket OD: 2.80" (71 mm)
 Gasket ID: 2.40" (61 mm)
 Relief Valve Setting: 30-42 PSI (2.10-2.80 Bar)
 Efficiency 50% @ 20 Micron



Part Number: P550230
Description: HYDRAULIC SPIN-ON
Primary App: ZF 0750131007
Dimensions:
 Outer Diameter: 3.82" (97 mm)
 Thread Size: 1-12
 Length: 8.23" (209 mm)
 Gasket OD: 2.80" (71 mm)
 Gasket ID: 2.40" (61 mm)
 Relief Valve Setting: 32-38 PSI (2.20-2.70 Bar)
 Efficiency 50% @ 15 Micron



















Part Number: P550232
Description: HYDRAULIC CARTRIDGE
Primary App: MARVEL 529206-5125, PUROLATOR PM6035
Dimensions:
 Outer Diameter: 2.61" (66 mm)
 Inner Diameter: 1.25" (32 mm)
 Length: 4.80" (122 mm)
 Efficiency 50% @ 5 Micron


















Part Number: P550242
Description: LUBE SPIN-ON BYPASS
Primary App: MITSUBISHI ME014838
Dimensions:
 Outer Diameter: 3.70" (94 mm)
 Thread Size: M18 x 1.5
 Length: 3.72" (95 mm)
 Gasket OD: 2.46" (62 mm)
 Gasket ID: 2.20" (56 mm)
 Relief Valve Setting: 8-11 PSI (0.60-0.80 Bar)
 Anti Drain Valve: Yes Y/N
 Efficiency 50% @ 25 Micron



Part Number: P550248
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: CUMMINS 3903202
Dimensions:
 Outer Diameter: 2.99" (76 mm)
 Thread Size: M16 x 1.5
 Length: 5.71" (145 mm)
 Gasket OD: 2.82" (72 mm)
 Gasket ID: 2.46" (62 mm)
 Stand Pipe: Yes Y/N
 Efficiency 99% @ 25 Micron

	<p>Part Number: P550249 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CUMMINS 3912104 Dimensions: Outer Diameter: 3.03" (77 mm) Thread Size: M16 x 1.5 Length: 4.51" (115 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.48" (63 mm) Stand Pipe: No Y/N Efficiency 99% @ 25 Micron</p>		<p>Part Number: P550268 Description: HYDRAULIC SPIN-ON Primary App: UCC MX1518-4-10, PTI F4E-35-CCB Dimensions: Outer Diameter: 3.86" (98 mm) Thread Size: 3/4-14 Length: 5.80" (147 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P550250 Description: HYDRAULIC SPIN-ON Primary App: GRESEN, DONALDSON LPS05 ASSY Dimensions: Outer Diameter: 5.00" (127 mm) Thread Size: 1 1/2-16 Length: 10.66" (271 mm) Gasket OD: 5.05" (128 mm) Gasket ID: 4.71" (120 mm) Efficiency 50% @ 4 Micron</p>		<p>Part Number: P550274 Description: HYDRAULIC SPIN-ON Primary App: ZINGA AE-100, DONALDSON LPS04 Dimensions: Outer Diameter: 3.73" (95 mm) Thread Size: 1-12 Length: 5.76" (146 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (62 mm) Efficiency 99% @ 149 Micron</p>
	<p>Part Number: P550251 Description: HYDRAULIC SPIN-ON Primary App: GRESEN, DONALDSON LPS05 ASSY Dimensions: Outer Diameter: 5.00" (127 mm) Thread Size: 1 1/2-16 Length: 10.66" (271 mm) Gasket OD: 5.05" (128 mm) Gasket ID: 4.71" (120 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P550275 Description: HYDRAULIC SPIN-ON Primary App: ZINGA SE-100, DONALDSON LPS05 Dimensions: Outer Diameter: 5.06" (129 mm) Thread Size: 1 1/2-16 Length: 6.63" (169 mm) Gasket OD: 5.05" (128 mm) Gasket ID: 4.71" (120 mm) Efficiency 99% @ 149 Micron</p>
	<p>Part Number: P550252 Description: HYDRAULIC SPIN-ON Primary App: GRESEN, DONALDSON LPS05 ASSY Dimensions: Outer Diameter: 5.00" (127 mm) Thread Size: 1 1/2-16 Length: 10.66" (271 mm) Gasket OD: 5.05" (128 mm) Gasket ID: 4.71" (120 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P550276 Description: HYDRAULIC SPIN-ON Primary App: ZINGA LE-100, DONALDSON LPS05 Dimensions: Outer Diameter: 5.06" (129 mm) Thread Size: 1 1/2-16 Length: 10.63" (270 mm) Gasket OD: 5.05" (128 mm) Gasket ID: 4.71" (120 mm) Efficiency 99% @ 149 Micron</p>
	<p>Part Number: P550255 Description: HYDRAULIC SPIN-ON Primary App: GRESEN, MFP, CROSS, DONALDSON LPS04 ASSY Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 8.60" (218 mm) Gasket OD: 2.82" (72 mm) Gasket ID: 2.42" (61 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P550284 Description: HYDRAULIC CARTRIDGE Primary App: VICKERS 404210 Dimensions: Outer Diameter: 4.00" (102 mm) Inner Diameter: 2.23" (57 mm) Length: 9.00" (229 mm) Efficiency 50% @ 16 Micron Efficiency 99% @ 47 Micron</p>
	<p>Part Number: P550256 Description: HYDRAULIC SPIN-ON Primary App: GRESEN, MFP, CROSS, DONALDSON LPS04 ASSY Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 8.60" (218 mm) Gasket OD: 2.82" (72 mm) Gasket ID: 2.42" (61 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P550286 Description: LUBE CARTRIDGE Primary App: MACK 57GC2134 Dimensions: Outer Diameter: 3.87" (98 mm) Inner Diameter: 0.64" (16 mm) Length: 4.58" (116 mm) Gasket OD: 0.56" (14 mm)</p>
	<p>Part Number: P550264 Description: HYDRAULIC CARTRIDGE Primary App: VICKERS 398856 Dimensions: Outer Diameter: 3.12" (79 mm) Inner Diameter: 1.86" (47 mm) Length: 8.00" (203 mm) Efficiency 50% @ 16 Micron Efficiency 99% @ 47 Micron</p>		<p>Part Number: P550287 Description: LUBE CARTRIDGE Primary App: MACK 57GC2187 Dimensions: Outer Diameter: 3.87" (98 mm) Inner Diameter: 0.49" (13 mm) Length: 4.58" (116 mm) Gasket OD: 0.40" (10 mm)</p>
	<p>Part Number: P550267 Description: HYDRAULIC CARTRIDGE Primary App: VICKERS 404211 Dimensions: Outer Diameter: 4.00" (102 mm) Inner Diameter: 2.23" (57 mm) Length: 18.00" (457 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 21 Micron</p>		<p>Part Number: P550299 Description: LUBE SPIN-ON FULL FLOW Primary App: FORD D3HZ6731B, MOTORCRAFT FL788 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 3/4-16 Length: 6.85" (174 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Relief Valve Setting: 7-10 PSI (0.50 -0.70 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>

	<p>Part Number: P550308 Description: HYDRAULIC CARTRIDGE Primary App: HANOMAG 373952178 Dimensions: Outer Diameter: 4.65" (118 mm) Inner Diameter: 2.40" (61 mm) Length: 6.50" (165 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P550319 Description: LUBE SPIN-ON FULL FLOW Primary App: IHC 1811953C1 FOR DT/DTA360 & 466 DIESEL ENG Dimensions: Outer Diameter: 4.27" (108 mm) Thread Size: 1-12 Length: 8.00" (203 mm) Gasket OD: 2.82" (72 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P550309 Description: HYDRAULIC CARTRIDGE Primary App: ZF 7632141102 Dimensions: Outer Diameter: 2.36" (60 mm) Inner Diameter: 0.71" (18 mm) Length: 3.94" (100 mm) Efficiency 50% @ 15 Micron</p>		<p>Part Number: P550320 Description: HYDRAULIC SPIN-ON Primary App: DRESSER 1214275H1, 1214275H2 Dimensions: Outer Diameter: 5.00" (127 mm) Thread Size: 1 1/2-16 Length: 11.71" (298 mm) Gasket OD: 4.17" (106 mm) Gasket ID: 3.58" (91 mm) Efficiency 50% @ 2 Micron</p>
	<p>Part Number: P550310 Description: HYDRAULIC CARTRIDGE Primary App: ZF 7633141101 Dimensions: Outer Diameter: 3.23" (82 mm) Inner Diameter: 0.75" (19 mm) Length: 4.33" (110 mm)</p>		<p>Part Number: P550325 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: ONAN 122B325 Dimensions: Outer Diameter: 3.03" (77 mm) Thread Size: 7/16-20 Length: 4.87" (124 mm) Gasket OD: 3.02" (77 mm) Gasket ID: 1.75" (44 mm)</p>
	<p>Part Number: P550311 Description: LUBE CARTRIDGE FULL FLOW Primary App: LEYLAND 602426 Dimensions: Outer Diameter: 3.11" (79 mm) Inner Diameter: 0.75" (19 mm) Length: 9.37" (238 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P550335 Description: LUBE SPIN-ON FULL FLOW Primary App: MOPAR L335, CHYRSLER, CLARK, INTERCEPTOR MARINE Dimensions: Outer Diameter: 3.00" (76 mm) Thread Size: 3/4-16 Length: 3.40" (86 mm) Gasket OD: 2.75" (70 mm) Gasket ID: 2.37" (60 mm) Relief Valve Setting: 7-10 PSI (0.50-0.70 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P550315 Description: LUBE CARTRIDGE FULL FLOW Primary App: MERCEDES 3661800009 Dimensions: Outer Diameter: 3.30" (84 mm) Inner Diameter: 0.93" (24 mm) Length: 7.50" (190 mm)</p>		<p>Part Number: P550341 Description: LUBE SPIN-ON FULL FLOW Primary App: DAF 267714 Dimensions: Outer Diameter: 5.55" (141 mm) Thread Size: 1 1/2-16 Length: 12.20" (310 mm) Gasket OD: 4.37" (111 mm) Gasket ID: 3.94" (100 mm) Relief Valve Setting: 32-40 PSI (2.20-2.80 Bar) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P550316 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: CAT, CUMMINS, GROVE Dimensions: Outer Diameter: 5.83" (148 mm) Inner Diameter: 0.98" (25 mm) Length: 8.07" (205 mm) Efficiency 99% @ 20 Micron</p>		<p>Part Number: P550342 Description: LUBE SPIN-ON FULL FLOW Primary App: IVECO 1902102 Dimensions: Outer Diameter: 4.29" (109 mm) Thread Size: M30 x 2 Length: 9.06" (230 mm) Gasket OD: 4.06" (103 mm) Gasket ID: 3.62" (92 mm) Relief Valve Setting: 36 PSI (2.48 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 12 Micron</p>
	<p>Part Number: P550317 Description: LUBE SPIN-ON FULL FLOW Primary App: RENAULT RVI 5000670671 Dimensions: Outer Diameter: 3.74" (95 mm) Thread Size: 1-12 Length: 8.31" (211 mm) Gasket OD: 2.80" (71 mm) Gasket ID: 2.40" (61 mm) Relief Valve Setting: 34-37 PSI (2.40-2.60 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>		<p>Part Number: P550345 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: DEUTZ 1174424, MANN WK712/2 Dimensions: Outer Diameter: 3.03" (77 mm) Thread Size: M16 x 1.5 Length: 3.15" (80 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.40" (61 mm) Efficiency 50% @ 7 Micron</p>
	<p>Part Number: P550318 Description: LUBE SPIN-ON FULL FLOW Primary App: SCANIA 173171 Dimensions: Outer Diameter: 3.74" (95 mm) Thread Size: 3/4-16 Length: 3.62" (92 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Relief Valve Setting: 14-20 PSI (1.00-1.40 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 25 Micron</p>		

<p>Part Number: P550347 Description: FUEL CARTRIDGE Primary App: FIAT GEOTECH 1909107 Dimensions: Outer Diameter: 3.70" (94 mm) Inner Diameter: 0.98" (25 mm) Length: 7.19" (183 mm) Efficiency 99% @ 28 Micron</p>	 <p>Part Number: P550359 Description: LUBE CARTRIDGE FULL FLOW Primary App: ROLLS ROYCE OE12448 Dimensions: Outer Diameter: 3.62" (92 mm) Inner Diameter: 0.51" (13 mm) Length: 5.83" (148 mm)</p>
 <p>Part Number: P550348 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: DETROIT DIESEL 23512631 Dimensions: Outer Diameter: 5.38" (137 mm) Thread Size: 1 3/8-16 Length: 11.77" (299 mm) Gasket OD: 4.29" (109 mm) Gasket ID: 3.92" (100 mm) Efficiency 99% @ 7 Micron</p>	 <p>Part Number: P550361 Description: LUBE CARTRIDGE COMBINATION Primary App: MERCEDES 6011800009 Dimensions: Outer Diameter: 3.58" (91 mm) Inner Diameter: 0.47" (12 mm) Length: 6.42" (163 mm)</p>
 <p>Part Number: P550349 Description: FUEL CARTRIDGE Primary App: MERCEDES, MANN BF900X (FELT) Dimensions: Outer Diameter: 3.30" (84 mm) Inner Diameter: 0.47" (12 mm) Length: 5.53" (140 mm)</p>	 <p>Part Number: P550362 Description: LUBE SPIN-ON FULL FLOW Primary App: DEUTZ 1174419 Dimensions: Outer Diameter: 3.75" (95 mm) Thread Size: 1-12 Length: 6.99" (178 mm) Relief Valve Setting: 30 PSI (2.07 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>
 <p>Part Number: P550351 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: JOHN DEERE RE50455 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.73" (69 mm) Length: 4.03" (102 mm) Gasket OD: 5.05" (128 mm) Efficiency 50% @ 5 Micron</p>	 <p>Part Number: P550364 Description: FUEL CARTRIDGE Primary App: LISTER PETTER 20113112 Dimensions: Outer Diameter: 2.19" (56 mm) Inner Diameter: 0.26" (7 mm) Length: 1.47" (37 mm)</p>
 <p>Part Number: P550352 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: GM 10154635, 6.2L DIESEL Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.73" (69 mm) Length: 5.23" (133 mm) Efficiency 50% @ 5 Micron</p>	 <p>Part Number: P550365 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: ROLLS ROYCE OE42873 Dimensions: Outer Diameter: 3.78" (96 mm) Thread Size: M24 x 1.5 Length: 7.00" (178 mm) Efficiency 99% @ 20 Micron</p>
 <p>Part Number: P550354 Description: LUBE CARTRIDGE FULL FLOW Primary App: MERCEDES 3661840225 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 0.94" (24 mm) Length: 5.12" (130 mm)</p>	 <p>Part Number: P550366 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: FORD 844F9176CAB Dimensions: Outer Diameter: 3.50" (89 mm) Inner Diameter: 0.63" (16 mm) Length: 6.42" (163 mm)</p>
 <p>Part Number: P550356 Description: LUBE SPIN-ON COMBINATION Primary App: FORD 826F6714 Dimensions: Outer Diameter: 5.48" (139 mm) Thread Size: M60 x 3 Length: 6.62" (168 mm) Relief Valve Setting: 10-15 PSI (0.70-1.00 Bar)</p>	 <p>Part Number: P550367 Description: LUBE SPIN-ON FULL FLOW Primary App: NAVISTAR 1819452C1 Dimensions: Outer Diameter: 5.32" (136 mm) Thread Size: M36 x 1.5 Length: 12.10" (307 mm) Gasket OD: 4.35" (110 mm) Gasket ID: 3.95" (100 mm) Relief Valve Setting: 26-30 PSI (1.80-2.10 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 21 Micron</p>
 <p>Part Number: P550357 Description: LUBE SPIN-ON FULL FLOW Primary App: FORD 844F6716AA Dimensions: Outer Diameter: 3.78" (96 mm) Thread Size: M22 x 1.5 Length: 3.78" (96 mm) Gasket OD: 3.54" (90 mm) Gasket ID: 3.03" (77 mm) Relief Valve Setting: 10-15 PSI (0.70-1.00 Bar) Anti Drain Valve: Yes Y/N</p>	 <p>Part Number: P550368 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: NAVISTAR 1820749C1 Dimensions: Outer Diameter: 3.05" (77 mm) Thread Size: 7/8-14 Length: 5.83" (148 mm) Gasket OD: 5.05" (128 mm) Gasket ID: 4.71" (120 mm) Efficiency 50% @ 5 Micron</p>



Part Number: P550371
Description: LUBE SPIN-ON FULL FLOW
Primary App: NAVISTAR 1822731C1, 1814562C1 Ford F4TZ6731-A
Dimensions:
 Outer Diameter: 4.27" (108 mm)
 Thread Size: 1 1/2-16
 Length: 8.02" (204 mm)
 Gasket OD: 3.89" (99 mm)
 Gasket ID: 3.55" (90 mm)
 Efficiency 99% @ 17 Micron



Part Number: P550372
Description: FUEL SPIN ON
Primary App: VOLVO 420799
Dimensions:
 Outer Diameter: 3.71" (94 mm)
 Thread Size: M18 x 1.5
 Length: 8.13" (207 mm)
 Gasket OD: 2.81" (71 mm)
 Gasket ID: 2.46" (62 mm)
 Efficiency 99% @ 5 Micron



Part Number: P550378
Description: LUBE CARTRIDGE FULL FLOW
Primary App: MITSUBISHI ME034605
Dimensions:
 Outer Diameter: 4.33" (110 mm)
 Inner Diameter: 0.75" (19 mm)
 Length: 7.56" (192 mm)
 Efficiency 50% @ 25 Micron



Part Number: P550379
Description: LUBE CARTRIDGE FULL FLOW
Primary App: HINO 156071560
Dimensions:
 Outer Diameter: 4.09" (104 mm)
 Inner Diameter: 1.26" (32 mm)
 Length: 7.09" (180 mm)
 Efficiency 50% @ 25 Micron

Part Number: P550380
Description: LUBE CARTRIDGE FULL FLOW
Primary App: ISUZU 1878103141
Dimensions:
 Outer Diameter: 5.04" (128 mm)
 Inner Diameter: 0.79" (20 mm)
 Length: 7.91" (201 mm)
 Efficiency 50% @ 25 Micron



Part Number: P550381
Description: LUBE CARTRIDGE
Primary App: ISUZU 1878100501
Dimensions:
 Outer Diameter: 6.50" (165 mm)
 Inner Diameter: 6.50" (165 mm)
 Length: 13.00" (330 mm)



Part Number: P550382
Description: LUBE CARTRIDGE
Primary App: ISUZU 1878102390
Dimensions:
 Outer Diameter: 6.50" (165 mm)
 Length: 11.02" (280 mm)



Part Number: P550383
Description: LUBE SPIN-ON FULL FLOW
Primary App: ISUZU 8941145850
Dimensions:
 Outer Diameter: 4.13" (105 mm)
 Thread Size: M20 x 1.5
 Length: 3.15" (80 mm)
 Gasket OD: 3.92" (100 mm)
 Gasket ID: 3.52" (89 mm)



Part Number: P550384
Description: LUBE CARTRIDGE
Primary App: ISUZU 1132400560
Dimensions:
 Outer Diameter: 6.50" (165 mm)
 Inner Diameter: 11.02" (280 mm)
 Length: 12.95" (329 mm)
 Efficiency 50% @ 5 Micron



Part Number: P550385
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: TOYOTA 2330364010
Dimensions:
 Outer Diameter: 3.70" (94 mm)
 Thread Size: 3/4-16
 Length: 5.43" (138 mm)
 Gasket OD: 2.48" (63 mm)
 Gasket ID: 2.20" (56 mm)
 Efficiency 50% @ 10 Micron



Part Number: P550386
Description: HYDRAULIC SPIN-ON
Primary App: GRESEN, DONALDSON LPS05
Dimensions:
 Outer Diameter: 5.00" (127 mm)
 Thread Size: 1 1/2-16
 Length: 6.85" (174 mm)
 Gasket OD: 5.05" (128 mm)
 Gasket ID: 4.71" (120 mm)
 Efficiency 50% @ 4 Micron



Part Number: P550387
Description: HYDRAULIC SPIN-ON
Primary App: GRESEN, VICKERS, DONALDSON LPS05
Dimensions:
 Outer Diameter: 4.91" (125 mm)
 Thread Size: 1 1/2-16
 Length: 7.06" (179 mm)
 Gasket OD: 5.05" (128 mm)
 Gasket ID: 4.71" (120 mm)
 Efficiency 50% @ 25 Micron



Part Number: P550388
Description: HYDRAULIC SPIN-ON
Primary App: GRESEN, VICKERS, DONALDSON LPS05
Dimensions:
 Outer Diameter: 4.91" (125 mm)
 Thread Size: 1 1/2-16
 Length: 6.66" (169 mm)
 Gasket OD: 5.04" (128 mm)
 Gasket ID: 4.76" (121 mm)
 Efficiency 50% @ 10 Micron



Part Number: P550389
Description: LUBE SPIN-ON FULL FLOW
Primary App: ISUZU 8941145840
Dimensions:
 Outer Diameter: 3.15" (80 mm)
 Thread Size: M22 x 1.5
 Length: 3.94" (100 mm)
 Gasket OD: 2.48" (63 mm)
 Gasket ID: 1.99" (51 mm)
 Relief Valve Setting: 8-11 PSI (0.60-0.80 Bar)
 Anti Drain Valve: Yes Y/N
 Efficiency 50% @ 25 Micron



Part Number: P550390
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: MITSUBISHI MB220900
Dimensions:
 Outer Diameter: 3.90" (99 mm)
 Thread Size: M20 x 1.5
 Length: 5.43" (138 mm)
 Gasket OD: 2.87" (73 mm)
 Gasket ID: 2.20" (56 mm)
 Efficiency 50% @ 10 Micron



Part Number: P550391
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: MITSUBISHI ME056280
Dimensions:
 Outer Diameter: 3.66" (93 mm)
 Thread Size: M24 x 1.5
 Length: 6.77" (172 mm)
 Gasket OD: 3.54" (90 mm)
 Gasket ID: 2.66" (68 mm)
 Efficiency 99% @ 30 Micron















Part Number: P550392
Description: FUEL CARTRIDGE
Primary App: HINO 234011090
Dimensions:
 Outer Diameter: 4.09" (104 mm)
 Inner Diameter: 0.59" (15 mm)
 Length: 4.09" (104 mm)
 Efficiency 99% @ 30 Micron



















	<p>Part Number: P550393 Description: LUBE SPIN-ON FULL FLOW Primary App: MERCEDES TRUCK 0031841701 Dimensions: Outer Diameter: 4.27" (108 mm) Thread Size: 1-12 Length: 9.09" (231 mm) Gasket OD: 2.82" (72 mm) Gasket ID: 2.44" (62 mm) Efficiency 99% @ 40 Micron</p>		<p>Part Number: P550404 Description: FUEL IN-LINE Primary App: TOYOTA 2330034100 Dimensions: Height: 2.40" (61 mm) Outer Diameter: 2.22" (56 mm) Length: 1.97" (50 mm) Efficiency 99% @ 30 Micron</p>
	<p>Part Number: P550394 Description: FUEL CARTRIDGE Primary App: MASSEY FERGUSON, PERKINS Dimensions: Outer Diameter: 3.50" (89 mm) Inner Diameter: 0.74" (19 mm) Length: 5.28" (134 mm)</p>		<p>Part Number: P550405 Description: LUBE SPIN-ON FULL FLOW Primary App: HINO 23304-78020 Dimensions: Outer Diameter: 3.15" (80 mm) Thread Size: M20 x 1.5 Length: 3.98" (101 mm) Gasket OD: 2.48" (63 mm) Gasket ID: 1.81" (46 mm) Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P550396 Description: LUBE CARTRIDGE FULL FLOW Primary App: Mercedes 001844901, 00184425 Dimensions: Outer Diameter: 2.35" (60 mm) Inner Diameter: 0.70" (18 mm) Length: 3.90" (99 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P550406 Description: LUBE SPIN-ON FULL FLOW Primary App: HINO 156071480 Dimensions: Outer Diameter: 4.02" (102 mm) Thread Size: M26 x 1.5 Length: 6.02" (153 mm) Gasket OD: 2.87" (73 mm) Gasket ID: 2.20" (56 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 16 Micron</p>
	<p>Part Number: P550397 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: JOHN DEERE RE62419, STANADYNE 31733 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.73" (69 mm) Length: 5.02" (128 mm) Overall Length: 6.04" (153 mm) Efficiency 95% @ 5 Micron</p>		<p>Part Number: P550409 Description: LUBE SPIN-ON FULL FLOW Primary App: MAZDA SL0223802 Dimensions: Outer Diameter: 4.02" (102 mm) Thread Size: 1-12 Length: 5.91" (150 mm) Gasket OD: 3.92" (100 mm) Gasket ID: 3.46" (88 mm) Efficiency 50% @ 16 Micron</p>
	<p>Part Number: P550398 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: JOHN DEERE RE62421, STANADYNE 31734DN Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.73" (69 mm) Length: 5.02" (128 mm) Overall Length: 6.04" (153 mm) Efficiency 95% @ 30 Micron</p>		<p>Part Number: P550410 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: KOMATSU 600-311-8220 Dimensions: Outer Diameter: 3.01" (76 mm) Thread Size: 3/4-16 Length: 5.75" (146 mm) Gasket OD: 2.75" (70 mm) Gasket ID: 2.37" (60 mm) Efficiency 99% @ 17 Micron</p>
	<p>Part Number: P550399 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: CATERPILLAR 1383100, STANADYNE 32919 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.73" (69 mm) Length: 4.00" (102 mm) Overall Length: 5.02" (128 mm) Efficiency 50% @ 150 Micron</p>		<p>Part Number: P550411 Description: LUBE SPIN-ON FULL FLOW Primary App: MAZDA 130523802 Dimensions: Outer Diameter: 3.96" (101 mm) Thread Size: 1-12 Length: 4.92" (125 mm) Gasket OD: 3.92" (100 mm) Gasket ID: 3.48" (88 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Anti Drain Valve: Yes Y/N</p>
	<p>Part Number: P550400 Description: LUBE SPIN-ON FULL FLOW Primary App: FORD E1FZ6731A, MOTORCRAFT FL400 Dimensions: Outer Diameter: 3.00" (76 mm) Thread Size: 3/4-16 Length: 4.74" (120 mm) Gasket OD: 2.75" (70 mm) Gasket ID: 2.37" (60 mm) Relief Valve Setting: 7-10 PSI (0.50 -0.70 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>		<p>Part Number: P550412 Description: LUBE SPIN-ON BYPASS Primary App: MAZDA SL5014V61 Dimensions: Outer Diameter: 3.64" (92 mm) Thread Size: M20 x 1.5 Length: 4.92" (125 mm) Gasket OD: 3.43" (87 mm) Gasket ID: 2.08" (53 mm) Efficiency 50% @ 5 Micron</p>
	<p>Part Number: P550401 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: CATERPILLAR 100-5593, 1383098 STANADYNE 30729 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.73" (69 mm) Length: 4.75" (121 mm) Overall Length: 5.77" (147 mm) Efficiency 95% @ 5 Micron</p>		<p>Part Number: P550413 Description: LUBE SPIN-ON FULL FLOW Primary App: TOYOTA 9091503006 Dimensions: Outer Diameter: 3.94" (100 mm) Thread Size: M24 x 1.5 Length: 4.74" (120 mm) Gasket OD: 3.15" (80 mm) Gasket ID: 2.64" (67 mm)</p>

<p>Part Number: P550415 Description: HYDRAULIC SPIN-ON Primary App: JOHN DEERE AT140315 Dimensions: Outer Diameter: 4.84" (123 mm) Thread Size: 1 1/2-16 Length: 11.41" (290 mm) Efficiency 50% @ 7 Micron</p>	 <p>Part Number: P550426 Description: HYDRAULIC SPIN-ON Primary App: ZINGA BE10-18 Dimensions: Outer Diameter: 2.99" (76 mm) Thread Size: 3/4-16 Length: 3.39" (86 mm) Gasket OD: 2.75" (70 mm) Gasket ID: 2.37" (60 mm)</p>
 <p>Part Number: P550416 Description: HYDRAULIC SPIN-ON Primary App: JOHN DEERE AT140030, HITACHI 4230376 Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: M24 x 1.5 Male Length: 8.88" (226 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (62 mm) Relief Valve Setting: 30 PSI (2 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 25 Micron</p>	 <p>Part Number: P550427 Description: HYDRAULIC CARTRIDGE Primary App: EUCLID, TEREX, PUROLATOR EP114 Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 3.52" (89 mm) Length: 8.50" (216 mm) Efficiency 50% @ 20 Micron</p>
<p>Part Number: P550417 Description: HYDRAULIC SPIN-ON Primary App: JOHN DEERE 1T172912 Dimensions: Outer Diameter: 4.84" (123 mm) Thread Size: 1 1/2-16 Length: 11.41" (290 mm) Efficiency 50% @ 10 Micron</p>	 <p>Part Number: P550428 Description: LUBE SPIN-ON FULL FLOW Primary App: CUMMINS "98" B SERIES Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1 1/8-16 Length: 6.85" (174 mm) Gasket OD: 2.84" (72 mm) Gasket ID: 2.44" (62 mm) Efficiency 50% @ 20 Micron</p>
 <p>Part Number: P550420 Description: LUBE SPIN-ON FULL FLOW Primary App: HITACHI 4296675 Dimensions: Outer Diameter: 4.33" (110 mm) Thread Size: 1 1/8-16 Length: 6.38" (162 mm) Gasket OD: 4.13" (105 mm) Gasket ID: 3.74" (95 mm) Efficiency 50% @ 20 Micron</p>	 <p>Part Number: P550429 Description: LUBE CARTRIDGE FULL FLOW Primary App: CATERPILLAR 9T9054 Dimensions: Outer Diameter: 3.03" (77 mm) Inner Diameter: 1.02" (26 mm) Length: 8.19" (208 mm) Efficiency 99% @ 45 Micron</p>
 <p>Part Number: P550421 Description: LUBE SPIN-ON FULL FLOW Primary App: HITACHI 4266385, ISUZU 11324010521 Dimensions: Outer Diameter: 4.66" (118 mm) Thread Size: 1 3/8-16 Length: 9.91" (252 mm) Gasket OD: 4.33" (110 mm) Gasket ID: 3.85" (98 mm) Efficiency 99% @ 50 Micron</p>	 <p>Part Number: P550430 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: CUMMINS ISB SERIES ENGINES Dimensions: Outer Diameter: 3.38" (86 mm) Inner Diameter: 0.81" (21 mm) Length: 4.94" (125 mm)</p>
 <p>Part Number: P550422 Description: LUBE SPIN-ON FULL FLOW Primary App: HITACHI 4183853, ISUZU 8943212191 Dimensions: Outer Diameter: 4.00" (102 mm) Thread Size: 1-12 Length: 5.92" (150 mm) Gasket OD: 3.92" (100 mm) Gasket ID: 3.48" (88 mm) Relief Valve Setting: 17 PSI (1.20 Bar) Anti Drain Valve: Yes Y/N</p>	 <p>Part Number: P550431 Description: FUEL SPIN-ON SECONDARY Primary App: MACK 483-GB-431 Dimensions: Outer Diameter: 4.28" (109 mm) Thread Size: 1 1/16-16 Length: 10.31" (262 mm) Gasket OD: 3.89" (99 mm) Gasket ID: 3.55" (90 mm) Efficiency 99% @ 9 Micron</p>
 <p>Part Number: P550423 Description: LUBE CARTRIDGE Primary App: HITACHI 4225367 Dimensions: Outer Diameter: 6.30" (160 mm) Inner Diameter: 0.67" (17 mm) Length: 10.51" (267 mm)</p>	 <p>Part Number: P550433 Description: FUEL IN-LINE Primary App: CASE IH D145357 Dimensions: Outer Diameter: 1.94" (49 mm) Inlet Size: 3/8" Overall Length: 3.88" (99 mm) Outlet Size: 3/8" Efficiency 99% @ 150 Micron</p>
 <p>Part Number: P550425 Description: LUBE SPIN-ON BYPASS Primary App: VOLVO 4775665 Dimensions: Outer Diameter: 4.29" (109 mm) Thread Size: 1 3/8-16 Length: 10.36" (263 mm) Gasket OD: 3.99" (101 mm) Gasket ID: 3.63" (92 mm) Efficiency 99% @ 21 Micron</p>	 <p>Part Number: P550434 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: NEW HOLLAND 87840591 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.73" (69 mm) Length: 4.75" (121 mm) Overall Length: 5.77" (147 mm) Efficiency 99% @ 150 Micron</p>
















	<p>Part Number: P550435 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: NEW HOLLAND 87840590 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.73" (69 mm) Length: 6.41" (163 mm) Overall Length: 7.43" (189 mm) Efficiency 50% @ 5 Micron</p>		<p>Part Number: P550451 Description: LUBE CARTRIDGE Primary App: M.A.N. 51055040096 Dimensions: Outer Diameter: 3.22" (82 mm) Inner Diameter: 1.50" (38 mm) Length: 7.89" (200 mm)</p>
	<p>Part Number: P550436 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: RACOR S3225P Dimensions: Outer Diameter: 4.36" (111 mm) Thread Size: 1-14 Length: 5.04" (128 mm) Efficiency 50% @ 30 Micron</p>		<p>Part Number: P550452 Description: LUBE SPIN-ON FULL FLOW Primary App: DAF 1310901, FLEETGUARD LF3737 & LF3773 Dimensions: Outer Diameter: 5.51" (140 mm) Thread Size: M42 x 2 Length: 11.89" (302 mm) Gasket OD: 4.37" (111 mm) Gasket ID: 3.97" (101 mm) Relief Valve Setting: 36 PSI (2.48 Bar)</p>
	<p>Part Number: P550437 Description: FUEL CARTRIDGE Primary App: MOTORCRAFT FD4596, Ford F81Z-9N184-AA Dimensions: Outer Diameter: 3.81" (97 mm) Inner Diameter: 0.50" (13 mm) Length: 2.85" (72 mm) Efficiency 95% @ 5 Micron</p>		<p>Part Number: P550453 Description: LUBE CARTRIDGE Primary App: MERCEDES A5411840225 Dimensions: Outer Diameter: 4.64" (118 mm) Inner Diameter: 1.78" (45 mm) Length: 11.77" (299 mm)</p>
	<p>Part Number: P550440 Description: FUEL SPIN-ON SECONDARY Primary App: CUMMINS 6C, 6CT SERIES Dimensions: Outer Diameter: 2.99" (76 mm) Thread Size: M16 x 1.5 Length: 5.12" (130 mm) Gasket OD: 2.75" (70 mm) Gasket ID: 2.37" (60 mm) Stand Pipe: Yes Y/N Efficiency 99% @ 16 Micron</p>		<p>Part Number: P550454 Description: FUEL IN-LINE Primary App: FORD D3FZ9155A, D2RY9155A -- 2 HOSES 4 CLAMPS INCLUDED Dimensions: Outer Diameter: 0.94" (24 mm) Inlet Size: 5/16" Overall Length: 2.87" (73 mm) Outlet Size: 5/16" Efficiency 99% @ 100 Micron</p>
	<p>Part Number: P550445 Description: HYDRAULIC SPIN-ON Primary App: Clark Hurth 247052, Hyster 1315621 Dimensions: Outer Diameter: 3.68" (93 mm) Thread Size: 2-16 Length: 6.89" (175 mm) Gasket OD: 2.75" (70 mm) Gasket ID: 2.44" (62 mm) Relief Valve Setting: 37 PSI (2.55 Bar) Efficiency 50% @ 6 Micron</p>		<p>Part Number: P550455 Description: FUEL SPIN ON Primary App: CARRIER 300109000 Dimensions: Outer Diameter: 4.26" (108 mm) Thread Size: 1-14 Length: 5.90" (150 mm) Gasket OD: 4.00" (102 mm) Gasket ID: 3.56" (90 mm) Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P550446 Description: FUEL IN-LINE Primary App: JOHN DEERE AR103220, CUMMINS 3318919 Dimensions: Outer Diameter: 2.00" (51 mm) Inlet Size: 5/8-24 Overall Length: 3.54" (90 mm) Length: 2.41" (61 mm) Outlet Size: 5/8-24 Efficiency 99% @ 150 Micron</p>		<p>Part Number: P550457 Description: FUEL IN-LINE Primary App: JOHN DEERE T19743 Dimensions: Outer Diameter: 2.00" (51 mm) Inlet Size: 1/8-27 Overall Length: 3.38" (86 mm) Outlet Size: 1/2-20 Efficiency 50% @ 23 Micron</p>
	<p>Part Number: P550447 Description: FUEL IN-LINE Primary App: JOHN DEERE AR103220, CUMMINS 3318919 Dimensions: Outer Diameter: 2.00" (51 mm) Inlet Size: 5/8-24 Overall Length: 3.54" (90 mm) Length: 2.41" (61 mm) Outlet Size: 5/8-24 Efficiency 99% @ 150 Micron</p>		<p>Part Number: P550460 Description: FUEL CARTRIDGE Primary App: DAVCO 230/232 SERIES DETROIT DIESEL Dimensions: Outer Diameter: 3.45" (88 mm) Inner Diameter: 0.66" (17 mm) Length: 4.44" (113 mm)</p>
	<p>Part Number: P550447 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: FLEETGUARD FS1011 FOR OPTIGUARD SYSTEM Dimensions: Outer Diameter: 4.31" (109 mm) Inner Diameter: 0.65" (17 mm) Length: 6.47" (164 mm) Efficiency 99% @ 20 Micron</p>		<p>Part Number: P550463 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: DAVCO 380 AND 382 7 MICRON Dimensions: Outer Diameter: 3.82" (97 mm) Inner Diameter: 0.66" (17 mm) Length: 6.74" (171 mm) Efficiency 98% @ 7 Micron Efficiency 99% @ 8 Micron</p>
	<p>Part Number: P550448 Description: FUEL SPIN ON Primary App: CARRIER 300109001 Dimensions: Outer Diameter: 4.26" (108 mm) Thread Size: 1-14 Length: 5.93" (151 mm) Gasket OD: 3.54" (90 mm) Gasket ID: 3.16" (80 mm) Efficiency 99% @ 10 Micron</p>		<p>Part Number: P550464 Description: HYDRAULIC SPIN-ON Primary App: ZINGA BE10-0, GALBREATH 1674 Dimensions: Outer Diameter: 2.99" (76 mm) Thread Size: 3/4-16 Length: 3.39" (86 mm) Gasket OD: 2.75" (70 mm) Gasket ID: 2.37" (60 mm)</p>



















	<p>Part Number: P550467 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: DAVCO 380 AND 382 ELEMEX 7 MICRON Dimensions: Outer Diameter: 3.82" (97 mm) Inner Diameter: 0.66" (17 mm) Length: 6.74" (171 mm) Efficiency 98% @ 7 Micron Efficiency 99% @ 8 Micron</p>		<p>Part Number: P550484 Description: LUBE CARTRIDGE FULL FLOW Primary App: CAT 1R-0659, 4W-4840, KOMATSU 6610-53-5120 Dimensions: Outer Diameter: 3.98" (101 mm) Inner Diameter: 1.63" (41 mm) Length: 9.29" (236 mm) Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P550472 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: DAF 1328177 Dimensions: Outer Diameter: 3.77" (96 mm) Thread Size: M16 x 1.5 Length: 8.34" (211 mm) Gasket OD: 2.80" (71 mm) Gasket ID: 2.44" (62 mm) Efficiency 50% @ 3 Micron</p>		<p>Part Number: P550485 Description: LUBE CARTRIDGE FULL FLOW Primary App: CAT 1R-0721, 5S-0485, HYSTER 75669 Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 3.37" (86 mm) Length: 8.94" (227 mm) Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P550473 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: Mercedes-Benz 10922201, 10922301 Dimensions: Outer Diameter: 3.50" (89 mm) Thread Size: M12 x 1.5 Length: 8.16" (207 mm) Gasket OD: 2.80" (71 mm) Gasket ID: 2.44" (62 mm)</p>		<p>Part Number: P550486 Description: HYDRAULIC SPIN-ON Primary App: CATERPILLAR 1194740 Dimensions: Outer Diameter: 3.05" (77 mm) Thread Size: 13/16-16 Length: 5.50" (140 mm)</p>
	<p>Part Number: P550476 Description: HYDRAULIC INLINE Primary App: TOYOTA 675022300071 Dimensions: Outer Diameter: 3.95" (100 mm) Inlet Size: 1.06 Overall Length: 4.72" (120 mm) Outlet Size: 3/4 PT E: 4.25" (108 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P550487 Description: HYDRAULIC CARTRIDGE Primary App: IHC 279294C92, MACK 485GB3160 Dimensions: Outer Diameter: 3.47" (88 mm) Inner Diameter: 1.39" (35 mm) Length: 2.72" (69 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P550477 Description: HYDRAULIC INLINE Primary App: TOYOTA 675022054071 Dimensions: Outer Diameter: 3.95" (100 mm) Inlet Size: 1.08 Overall Length: 4.72" (120 mm) Outlet Size: 1.08 (27) E: 4.25" (108 mm) F: 2.21" (56 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P550488 Description: HYDRAULIC INLINE Primary App: TOYOTA 675021330071 Dimensions: Outer Diameter: 3.95" (100 mm) Inlet Size: 1.08 Overall Length: 4.72" (120 mm) Outlet Size: 3/4 PT E: 4.25" (108 mm)</p>
	<p>Part Number: P550478 Description: HYDRAULIC INLINE Primary App: TOYOTA 329013163071 Dimensions: Outer Diameter: 3.95" (100 mm) Inlet Size: 0.09 Overall Length: 4.72" (120 mm) Outlet Size: 0.09 (22) E: 4.25" (108 mm) F: 2.21" (56 mm)</p>		<p>Part Number: P550489 Description: FUEL CARTRIDGE Primary App: CLAAS, DEMAG, LIEBHERR, MERCEDES Dimensions: Outer Diameter: 3.36" (85 mm) Inner Diameter: 0.52" (13 mm) Length: 5.70" (145 mm)</p>
	<p>Part Number: P550479 Description: HYDRAULIC INLINE Primary App: TOYOTA 675023288171 Dimensions: Outer Diameter: 3.95" (100 mm) Inlet Size: 1.62 Overall Length: 6.89" (175 mm) Outlet Size: 1 PT E: 4.25" (108 mm) F: 3.94" (100 mm)</p>		<p>Part Number: P550490 Description: LUBE SPIN-ON FULL FLOW Primary App: SCANIA 1117285 Dimensions: Outer Diameter: 4.33" (110 mm) Thread Size: 1 1/8-16 Length: 10.20" (260 mm) Gasket OD: 4.09" (104 mm) Gasket ID: 3.66" (93 mm)</p>
	<p>Part Number: P550481 Description: FUEL CARTRIDGE Primary App: CLAAS, HANOMAG, LIEBHERR, MERCEDES, VOLVO Dimensions: Outer Diameter: 2.75" (70 mm) Inner Diameter: 0.52" (13 mm) Length: 4.52" (115 mm)</p>		<p>Part Number: P550491 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: RVI, M&H WK727 Dimensions: Outer Diameter: 3.14" (80 mm) Thread Size: M16 x 1.5 Length: 4.88" (124 mm) Gasket OD: 2.80" (71 mm) Gasket ID: 2.44" (62 mm)</p>
			<p>Part Number: P550492 Description: LUBE CARTRIDGE Primary App: BOSCH 1457429630 Dimensions: Outer Diameter: 5.00" (127 mm) Inner Diameter: 2.51" (64 mm) Length: 8.29" (211 mm)</p>



















<p>Part Number: P550493 Description: LUBE CARTRIDGE Primary App: CUMMINS 106621 Dimensions: Outer Diameter: 7.87" (200 mm) Inner Diameter: 0.86" (22 mm) Length: 10.03" (255 mm)</p>	 <p>Part Number: P550504 Description: FUEL IN-LINE Primary App: GM LIGHT TRUCK, AC GF624, G580 Dimensions: Outer Diameter: 2.28" (58 mm) Inlet Size: 3/8" Overall Length: 6.38" (162 mm) Outlet Size: 3/8" Efficiency 50% @ 23 Micron</p>
<p>Part Number: P550494 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: DAF 1318695 Dimensions: Outer Diameter: 3.77" (96 mm) Thread Size: M16 x 1.5 Length: 5.66" (144 mm) Gasket OD: 2.80" (71 mm) Gasket ID: 2.44" (62 mm)</p>	 <p>Part Number: P550505 Description: LUBE SPIN-ON FULL FLOW Primary App: GM LIGHT TRUCK, AC PF59, PH59 Dimensions: Outer Diameter: 2.96" (75 mm) Thread Size: 13/16-16 Length: 4.45" (113 mm) Gasket OD: 2.77" (70 mm) Gasket ID: 2.36" (60 mm) Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>
<p>Part Number: P550495 Description: FUEL SPIN ON Primary App: Saab-Scania 1361685, 1372444 Dimensions: Outer Diameter: 3.77" (96 mm) Thread Size: M24 x 1.5 Length: 5.66" (144 mm) Gasket OD: 2.80" (71 mm) Gasket ID: 2.44" (62 mm) Efficiency 50% @ 3 Micron</p>	 <p>Part Number: P550506 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: GM 12554082 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.73" (69 mm) Length: 5.50" (140 mm) Overall Length: 6.52" (166 mm)</p>
<p>Part Number: P550496 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: RENAULT V.1. 5010359706 Dimensions: Outer Diameter: 3.78" (96 mm) Thread Size: M16 x 1.5 Length: 5.66" (144 mm) Gasket OD: 2.80" (71 mm) Gasket ID: 2.44" (62 mm)</p>	 <p>Part Number: P550507 Description: LUBE SPIN-ON FULL FLOW Primary App: GM LIGHT TRUCK, AC PF454, PH454 Dimensions: Outer Diameter: 3.77" (96 mm) Thread Size: 13/16-16 Length: 3.08" (78 mm) Gasket OD: 3.57" (91 mm) Gasket ID: 3.16" (80 mm) Anti Drain Valve: Yes Y/N Efficiency 99% @ 22 Micron</p>
<p>Part Number: P550498 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: M & H WDK724 Dimensions: Outer Diameter: 3.15" (80 mm) Outlet Diameter: 3.14" (80 mm) Thread Size: M16 x 1.5 Thread Size: M16 x 1.5 Length: 5.74" (146 mm) Length: 5.74" (152 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.46" (62 mm)</p>	 <p>Part Number: P550508 Description: FUEL IN-LINE Primary App: AC LIGHT DUTY, GF645, G645 Dimensions: Outer Diameter: 2.28" (58 mm) Inlet Size: M16 x 1.5 Overall Length: 5.35" (136 mm) Outlet Size: 3/8" Anti Drain Valve: Yes Y/N Efficiency 50% @ 23 Micron Efficiency 99% @ 70 Micron</p>
 <p>Part Number: P550500 Description: LUBE CARTRIDGE Primary App: 500 SERIES BYPASS Dimensions: Outer Diameter: 7.72" (196 mm) Inner Diameter: 0.86" (22 mm) Length: 10.06" (256 mm) Efficiency 50% @ 5 Micron</p>	 <p>Part Number: P550510 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: DAVCO 102011, 102012 Dimensions: Outer Diameter: 4.21" (107 mm) Inner Diameter: 0.66" (17 mm) Length: 6.74" (171 mm) Gasket OD: 2.72" (69 mm) Gasket ID: 2.46" (62 mm) Efficiency 99% @ 8 Micron</p>
 <p>Part Number: P550501 Description: FUEL CARTRIDGE Primary App: PUROLATOR F70100 HOUSING Dimensions: Outer Diameter: 3.48" (88 mm) Inner Diameter: 1.32" (34 mm) Length: 4.80" (122 mm) Efficiency 99% @ 9 Micron</p>	 <p>Part Number: P550512 Description: LUBE SPIN-ON FULL FLOW Primary App: DETROIT DIESEL 5241840301 Dimensions: Outer Diameter: 5.33" (135 mm) Thread Size: M36 x 1.5 Length: 12.10" (308 mm) Gasket OD: 4.31" (109 mm) Gasket ID: 3.92" (100 mm) Relief Valve Setting: 31-38 PSI (2.14-2.62 Bar) Efficiency 99% @ 21 Micron</p>
 <p>Part Number: P550502 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: CATERPILLAR 1174089 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.73" (69 mm) Length: 4.75" (121 mm) Gasket OD: 5.77" (147 mm) Efficiency 99% @ 150 Micron</p>	 <p>Part Number: P550515 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: MANN & HUMMEL WK940/2 Dimensions: Outer Diameter: 3.70" (94 mm) Thread Size: M24 x 1.5 Length: 5.59" (142 mm)</p>
 <p>Part Number: P550503 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: CATERPILLAR 1311812 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.73" (69 mm) Length: 4.75" (121 mm) Overall Length: 5.77" (147 mm) Efficiency 95% @ 30 Micron</p>	
















	<p>Part Number: P550516 Description: LUBE CARTRIDGE FULL FLOW Primary App: CUMMINS 158139 Dimensions: Outer Diameter: 5.00" (127 mm) Inner Diameter: 1.50" (38 mm) Length: 9.62" (244 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P550527 Description: FUEL CARTRIDGE Primary App: FORD 3C3Z9N184CA F SERIES PICKUP Dimensions: Outer Diameter: 2.32" (59 mm) Length: 2.60" (66 mm)</p>
	<p>Part Number: P550518 Description: LUBE SPIN-ON FULL FLOW Primary App: AC PF2232 2001 SILVERADO V8 400 6.6L F.I. Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 13/16-16 Length: 5.36" (136 mm) Gasket OD: 3.48" (88 mm) Gasket ID: 3.10" (79 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 20 Micron</p>		<p>Part Number: P550528 Description: LUBE CARTRIDGE FULL FLOW Primary App: FORD 3C3Z6731AA F SERIES PICKUP Dimensions: Outer Diameter: 3.25" (83 mm) Length: 7.13" (181 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P550519 Description: LUBE SPIN-ON FULL FLOW Primary App: M&H W11102/20 Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: 1 1/8-16 Length: 10.24" (260 mm)</p>		<p>Part Number: P550529 Description: FUEL SPIN ON Primary App: VOLVO 20430751 Dimensions: Outer Diameter: 4.43" (113 mm) Thread Size: M32 x 1.5 Length: 10.00" (254 mm) Gasket OD: 4.09" (104 mm) Gasket ID: 3.66" (93 mm) Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P550520 Description: LUBE SPIN-ON FULL FLOW Primary App: DAF 1399494 Dimensions: Outer Diameter: 3.85" (98 mm) Thread Size: M27 x 2 Length: 6.89" (175 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Efficiency @ 83.00 Percent</p>		<p>Part Number: P550532 Description: HYDRAULIC INLINE Primary App: HITACHI 4185299 Dimensions: Outer Diameter: 5.51" (140 mm) Inlet Size: 0.79 x 1.16 Overall Length: 12.01" (305 mm) Outlet Size: 0.79 x 1.16</p>
	<p>Part Number: P550521 Description: LUBE CARTRIDGE FULL FLOW Primary App: MERCEDES 1041800109 Dimensions: Outer Diameter: 2.44" (62 mm) Inner Diameter: 0.86" (21 mm) Length: 6.20" (157 mm)</p>		<p>Part Number: P550534 Description: LUBE SPIN-ON FULL FLOW Primary App: DATSUN, TOYOTA SUZUKI Dimensions: Outer Diameter: 2.56" (65 mm) Thread Size: 3/4-16 Length: 2.80" (71 mm) Gasket OD: 2.46" (62 mm) Gasket ID: 1.94" (49 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Anti Drain Valve: Yes Y/N</p>
	<p>Part Number: P550522 Description: FUEL CARTRIDGE Primary App: GMC 21029 Dimensions: Outer Diameter: 3.00" (76 mm) Inner Diameter: 1.02" (26 mm) Length: 6.00" (152 mm) Efficiency 99% @ 40 Micron</p>		<p>Part Number: P550540 Description: FUEL CARTRIDGE SECONDARY Primary App: CUMMINS, GMC 5573262 Dimensions: Outer Diameter: 2.98" (76 mm) Inner Diameter: 1.03" (26 mm) Length: 7.81" (198 mm) Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P550523 Description: HYDRAULIC CARTRIDGE Primary App: CAT 4T-0522, 4T-0523 Dimensions: Outer Diameter: 5.07" (129 mm) Inner Diameter: 3.34" (85 mm) Length: 7.00" (178 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 35 Micron</p>		<p>Part Number: P550541 Description: FUEL CARTRIDGE SOCK Primary App: GMC 5574980 Dimensions: Outer Diameter: 4.00" (102 mm) Inner Diameter: 1.12" (28 mm) Length: 8.75" (222 mm) Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P550526 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: VOLVO Dimensions: Outer Diameter: 2.99" (76 mm) Thread Size: M14 x 1.5 Length: 4.72" (120 mm)</p>		<p>Part Number: P550542 Description: HYDRAULIC SPIN-ON Primary App: HITACHI 4252563 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 1/8-16 Length: 5.95" (151 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm)</p>
	<p>Part Number: P550547 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: CIMTEK EHS30, 300-07 Dimensions: Outer Diameter: 4.81" (122 mm) Inner Diameter: 1.12" (28 mm) Length: 9.13" (232 mm) Efficiency 50% @ 30 Micron</p>		<p>Part Number: P550547 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: CIMTEK EHS30, 300-07 Dimensions: Outer Diameter: 4.81" (122 mm) Inner Diameter: 1.12" (28 mm) Length: 9.13" (232 mm) Efficiency 50% @ 30 Micron</p>

	<p>Part Number: P550548 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: NAVISTAR 1685159C1 Dimensions: Outer Diameter: 4.26" (108 mm) Thread Size: 1-14 Length: 5.79" (147 mm) Gasket OD: 3.60" (91 mm) Gasket ID: 3.20" (81 mm) Efficiency 50% @ 5 Micron</p>		<p>Part Number: P550559 Description: FUEL CARTRIDGE Primary App: GM 5651921 Dimensions: Outer Diameter: 0.70" (18 mm) Inner Diameter: 0.20" (5 mm) Length: 2.01" (51 mm)</p>
	<p>Part Number: P550549 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CUMMINS 3942533 Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: M20 x 1.5 Length: 5.75" (146 mm) Gasket OD: 2.73" (69 mm) Gasket ID: 2.46" (63 mm) Efficiency 99% @ 10 Micron</p>		<p>Part Number: P550560 Description: FUEL CARTRIDGE SOCK Primary App: CASE A35863, A36557 Dimensions: Outer Diameter: 2.90" (74 mm) Inner Diameter: 1.10" (28 mm) Length: 2.37" (60 mm)</p>
	<p>Part Number: P550550 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: KOMATSU 6003112110 Dimensions: Outer Diameter: 3.11" (79 mm) Thread Size: 3/4-16 Length: 5.59" (142 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm) Efficiency 95% @ 20 Micron</p>		<p>Part Number: P550562 Description: LUBE SPIN-ON FULL FLOW Primary App: LIEBHERR 5700043 Dimensions: Outer Diameter: 3.70" (94 mm) Thread Size: 1-12 Length: 8.30" (211 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.48" (63 mm)</p>
	<p>Part Number: P550551 Description: LUBE SPIN-ON BYPASS Primary App: WISCONSIN RV51 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 13/16-16 Length: 4.34" (110 mm) Gasket OD: 3.44" (87 mm) Gasket ID: 3.10" (79 mm)</p>	<p>Part Number: P550563 Description: LUBE CARTRIDGE FULL FLOW Primary App: MERCEDES 6061840125 Dimensions: Outer Diameter: 3.24" (83 mm) Inner Diameter: 1.41" (36 mm) Length: 6.65" (169 mm)</p>	
	<p>Part Number: P550552 Description: FUEL CARTRIDGE SOCK Primary App: GMC 5575032 Dimensions: Outer Diameter: 2.95" (75 mm) Inner Diameter: 1.24" (31 mm) Length: 8.38" (213 mm)</p>		<p>Part Number: P550564 Description: LUBE CARTRIDGE FULL FLOW Primary App: MERCEDES 6111800009 Dimensions: Outer Diameter: 2.50" (65 mm) Inner Diameter: 1.22" (32 mm) Length: 4.53" (116 mm) Efficiency @ 10/20/40 Micron</p>
	<p>Part Number: P550553 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: 1999 FORD LIGHT TRUCK, MOTORCRAFT FD4597 Dimensions: Outer Diameter: 3.79" (96 mm) Thread Size: 1-14 Length: 6.22" (158 mm) Gasket OD: 3.59" (91 mm) Gasket ID: 3.15" (80 mm) Efficiency 99% @ 40 Micron</p>		<p>Part Number: P550567 Description: FUEL CARTRIDGE Primary App: PETTER 20332470 Dimensions: Outer Diameter: 2.19" (56 mm) Inner Diameter: 0.91" (23 mm) Length: 2.48" (63 mm)</p>
	<p>Part Number: P550554 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: NAVISTAR 1685159C91 Dimensions: Outer Diameter: 4.29" (109 mm) Thread Size: 1-14 Length: 5.75" (146 mm) Gasket OD: 3.97" (101 mm) Gasket ID: 3.59" (91 mm) Efficiency 50% @ 12 Micron</p>		<p>Part Number: P550569 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: FORD D3HE9176AA Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-14 Length: 6.09" (155 mm) Gasket OD: 3.66" (93 mm) Gasket ID: 3.17" (81 mm)</p>
	<p>Part Number: P550556 Description: FUEL IN-LINE Primary App: MOTORCRAFT FG1036 Dimensions: Outer Diameter: 2.22" (56 mm) Inlet Size: 3/8" Overall Length: 7.00" (178 mm) Outlet Size: 3/8" Efficiency 50% @ 23 Micron</p>		<p>Part Number: P550572 Description: LUBE SPIN-ON FULL FLOW Primary App: VOLVO, KUBOTA, NEW HOLLAND Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 3/4-16 Length: 3.57" (91 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (63 mm) Relief Valve Setting: 16 PSI (1.10 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 21 Micron</p>

	<p>Part Number: P550573 Description: HYDRAULIC SPIN-ON Primary App: MASSEY FERGUSON 3435446M1 Dimensions: Outer Diameter: 3.70" (94 mm) Thread Size: 1 1/8-16 Length: 4.38" (111 mm) Gasket OD: 2.73" (69 mm) Gasket ID: 2.42" (61 mm)</p>		<p>Part Number: P550585 Description: COOLANT SPIN-ON Primary App: FLEETGUARD WF2127, CUMMINS SIGNATURE 600 ENGINES Dimensions: Outer Diameter: 3.77" (96 mm) Thread Size: M36 x 2 Length: 5.76" (146 mm) Gasket OD: 3.73" (95 mm) Gasket ID: 3.18" (81 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P550575 Description: HYDRAULIC CARTRIDGE Primary App: CATERPILLAR 1R0774 Dimensions: Outer Diameter: 5.12" (130 mm) Inner Diameter: 3.34" (85 mm) Length: 11.06" (281 mm) Efficiency 99% @ 25 Micron</p>		<p>Part Number: P550587 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: DEUTZ 2133558, 2133943 Dimensions: Outer Diameter: 3.00" (76 mm) Thread Size: M16 x 1.5 Length: 6.50" (165 mm) Gasket OD: 2.75" (70 mm) Gasket ID: 2.37" (60 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P550576 Description: HYDRAULIC CARTRIDGE Primary App: CASE 153233A1, CLARK 6655066 Dimensions: Outer Diameter: 1.67" (42 mm) Inner Diameter: 0.91" (23 mm) Length: 3.45" (88 mm) Efficiency 99% @ 50 Micron</p>		<p>Part Number: P550588 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: BOSCH 1457434056 Dimensions: Outer Diameter: 3.02" (77 mm) Thread Size: M16 x 1.5 Length: 5.55" (141 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.40" (61 mm) Efficiency 99% @ 11 Micron</p>
	<p>Part Number: P550577 Description: HYDRAULIC CARTRIDGE Primary App: CATERPILLAR 1262081 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 3.84" (98 mm) Length: 16.75" (425 mm) Efficiency 99% @ 25 Micron</p>		<p>Part Number: P550589 Description: HYDRAULIC SPIN-ON Primary App: TOYOTA 32670-12620-71, KOMATSU AS150002300 Dimensions: Outer Diameter: 3.00" (76 mm) Thread Size: 3/4-16 Length: 3.53" (90 mm) Gasket OD: 2.74" (70 mm) Gasket ID: 2.37" (60 mm) Relief Valve Setting: 8-11 PSI (0.55 Bar) Anti Drain Valve: Yes</p>
	<p>Part Number: P550578 Description: HYDRAULIC CARTRIDGE Primary App: HITACHI 3501404 Dimensions: Outer Diameter: 3.53" (90 mm) Inner Diameter: 1.91" (49 mm) Length: 11.44" (291 mm)</p>		<p>Part Number: P550590 Description: HYDRAULIC SPIN-ON Primary App: FORD D8NMF914BA, CA, D8NNM903AA,FA Dimensions: Outer Diameter: 5.00" (127 mm) Thread Size: 1 1/2-16 Length: 6.87" (174 mm) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P550580 Description: LUBE SPIN-ON FULL FLOW Primary App: FORD, MASSEY FERGUSON, MPLS MOLINE Dimensions: Outer Diameter: 4.28" (109 mm) Thread Size: 3/4-16 Length: 3.77" (96 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Relief Valve Setting: 8-11 PSI (0.60-0.80 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 45 Micron</p>		<p>Part Number: P550591 Description: HYDRAULIC SPIN-ON Primary App: VOITH 90610310, DYNAPAC 499519 Dimensions: Outer Diameter: 3.68" (93 mm) Thread Size: 1-12 Length: 8.29" (211 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm)</p>
	<p>Part Number: P550581 Description: HYDRAULIC CARTRIDGE Primary App: CLARK 733289, 883687, 1810143 Dimensions: Outer Diameter: 5.98" (152 mm) Inner Diameter: 3.52" (89 mm) Length: 3.97" (101 mm)</p>		<p>Part Number: P550592 Description: HYDRAULIC SPIN-ON Primary App: JOHN DEERE AT180249 Dimensions: Outer Diameter: 4.80" (122 mm) Thread Size: 1 1/2-16 Length: 11.75" (298 mm) Gasket OD: 4.18" (106 mm) Gasket ID: 3.78" (96 mm)</p>
	<p>Part Number: P550582 Description: HYDRAULIC CARTRIDGE Primary App: ZINGA WE51810 Dimensions: Outer Diameter: 5.22" (133 mm) Inner Diameter: 3.24" (82 mm) Length: 18.13" (461 mm)</p>		<p>Part Number: P550593 Description: FUEL IN-LINE Primary App: FORD MOTORCRAFT FG19B Dimensions: Outer Diameter: 0.78" (20 mm) Inlet Size: 5/16" Overall Length: 2.17" (55 mm) Outlet Size: 7/8-20 E: 0.94" (24 mm) Efficiency 99% @ 100 Micron</p>
	<p>Part Number: P550584 Description: HYDRAULIC SPIN-ON Primary App: ALLIS CHALMERS 71367794 Dimensions: Outer Diameter: 5.04" (128 mm) Thread Size: 1 1/2-16 Length: 6.87" (174 mm) Efficiency 95% @ 8 Micron</p>		

	<p>Part Number: P550595 Description: LUBE SPIN-ON COMBINATION Primary App: JOHN DEERE VENTURI COMBO Dimensions: Outer Diameter: 4.66" (118 mm) Thread Size: M52 x 1.5 Length: 11.70" (297 mm) Gasket OD: 4.68" (119 mm) Gasket ID: 4.01" (102 mm) Efficiency 99% @ 22 Micron</p>		<p>Part Number: P550606 Description: HYDRAULIC SPIN-ON Primary App: GM 29537628, 29539579 Dimensions: Outer Diameter: 3.07" (73 mm) Thread Size: 3/4-20 Length: 3.00" (76 mm) Gasket OD: 2.75" (70 mm) Relief Valve Setting: 9 PSI (0.62 Bar)</p>
	<p>Part Number: P550596 Description: LUBE SPIN-ON FULL FLOW Primary App: HITACHI 4448336, 4658521 Dimensions: Outer Diameter: 4.65" (118 mm) Thread Size: 1 1/2-12 Length: 8.09" (205 mm) Gasket OD: 4.33" (110 mm) Gasket ID: 3.85" (98 mm) Relief Valve Setting: 20 PSI (1.40 Bar) Efficiency 99% @ 25 Micron</p>		<p>Part Number: P550607 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: FUEL DISPENSING PUMPS Dimensions: Outer Diameter: 4.81" (122 mm) Inner Diameter: 1.12" (28 mm) Length: 9.13" (232 mm) Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P550597 Description: LUBE SPIN-ON COMBINATION Primary App: TOYOTA 9091503006, 9091530002 Dimensions: Outer Diameter: 4.13" (105 mm) Thread Size: M24 x 1.5 Length: 4.81" (122 mm) Gasket OD: 3.15" (80 mm) Gasket ID: 2.80" (71 mm)</p>		<p>Part Number: P550613 Description: LUBE CARTRIDGE FULL FLOW Primary App: CUMMINS 173174 Dimensions: Outer Diameter: 4.76" (121 mm) Inner Diameter: 1.50" (38 mm) Length: 7.44" (189 mm) Efficiency 99% @ 48 Micron</p>
	<p>Part Number: P550598 Description: LUBE SPIN-ON FULL FLOW Primary App: GM 25010324 Dimensions: Outer Diameter: 2.92" (74 mm) Thread Size: 13/16-16 Length: 4.83" (123 mm) Gasket OD: 2.73" (69 mm) Gasket ID: 2.43" (62 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P550614 Description: LUBE CARTRIDGE Primary App: WAUKESHA 168660 Dimensions: Outer Diameter: 4.25" (108 mm) Inner Diameter: 1.67" (42 mm) Length: 32.00" (813 mm) Efficiency 95% @ 15 Micron</p>
	<p>Part Number: P550599 Description: LUBE SPIN-ON FULL FLOW Primary App: GM 6437462 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 13/16-16 Length: 4.34" (110 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (63 mm)</p>		<p>Part Number: P550615 Description: HYDRAULIC SPIN-ON Primary App: KOMATSU 21N6012210 Dimensions: Outer Diameter: 5.00" (127 mm) Length: 11.50" (292 mm)</p>
	<p>Part Number: P550600 Description: LUBE SPIN-ON FULL FLOW Primary App: HONDA 15400PL2004, 005, 305 Dimensions: Outer Diameter: 3.15" (80 mm) Thread Size: M22 x 1.5 Length: 3.17" (81 mm) Gasket OD: 2.94" (75 mm) Gasket ID: 2.43" (62 mm)</p>		<p>Part Number: P550616 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 2093812470 Dimensions: Outer Diameter: 1.65" (42 mm) Inner Diameter: 0.91" (23 mm) Length: 3.46" (88 mm)</p>
	<p>Part Number: P550601 Description: HYDRAULIC CARTRIDGE Primary App: FORD FOHZ3C602A, NAVISTAR 1684202C91 Dimensions: Outer Diameter: 4.00" (102 mm) Inner Diameter: 2.42" (61 mm) Length: 4.21" (107 mm)</p>		<p>Part Number: P550625 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CATERPILLAR 1R0762 Dimensions: Outer Diameter: 3.70" (94 mm) Thread Size: 1-14 Length: 10.75" (273 mm) Gasket OD: 3.60" (91 mm) Gasket ID: 3.03" (77 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P550605 Description: HYDRAULIC SPIN-ON Primary App: VOITH 6770859226, 90439911 Dimensions: Outer Diameter: 5.50" (140 mm) Thread Size: 1 1/2-16 Length: 7.00" (178 mm) Gasket OD: 4.36" (111 mm) Gasket ID: 3.96" (101 mm) Relief Valve Setting: 22 PSI (1.52 Bar)</p>		<p>Part Number: P550626 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CATERPILLAR 1R0770 Dimensions: Outer Diameter: 4.27" (108 mm) Thread Size: 1-14 Length: 9.17" (233 mm) Gasket OD: 4.27" (108 mm) Gasket ID: 3.68" (93 mm) Efficiency 99% @ 20 Micron</p>
	<p>Part Number: P550627 Description: FUEL CARTRIDGE Primary App: MAN TGA Dimensions: Outer Diameter: 2.99" (76 mm) Inner Diameter: 1.08" (27 mm) Length: 7.95" (202 mm)</p>		<p>Part Number: P550627 Description: FUEL CARTRIDGE Primary App: MAN TGA Dimensions: Outer Diameter: 2.99" (76 mm) Inner Diameter: 1.08" (27 mm) Length: 7.95" (202 mm)</p>

	<p>Part Number: P550628 Description: FUEL CARTRIDGE Primary App: Scania 164 series and Scania marine engines DI series Dimensions: Outer Diameter: 3.35" (85 mm) Inner Diameter: 1.50" (38 mm) Length: 7.11" (180 mm)</p>		<p>Part Number: P550642 Description: LUBE SPIN-ON FULL FLOW Primary App: Yanmar excavator VIO20-3; VIO35-3; VIO45-5; VIO40-2A; VIO50-2A; VIO50-3; VIO55-5 Dimensions: Thread Size: M20 x 1.5 Length: 3.05" (77 mm)</p>
	<p>Part Number: P550629 Description: LUBE CARTRIDGE Primary App: Scania 164 serie, scania marine engines DI series Dimensions: Outer Diameter: 4.02" (102 mm) Inner Diameter: 1.76" (45 mm) Length: 9.92" (252 mm)</p>		<p>Part Number: P550643 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: Yanmar SV serie; Volvo EC/EW serie; Volvo EC55B; Volvo ECR and ECR88 Dimensions: Outer Diameter: 3.68" (93 mm) Thread Size: M20 x 1.5 Length: 6.30" (93 mm)</p>
	<p>Part Number: P550630 Description: LUBE CARTRIDGE FULL FLOW Primary App: Daf 75CF, Daf 85CF, Daf 95 XF Dimensions: Outer Diameter: 4.41" (112 mm) Inner Diameter: 2.22" (56 mm) Length: 5.91" (150 mm)</p>		<p>Part Number: P550645 Description: FUEL CARTRIDGE Primary App: Yanmar 11974055600 Dimensions: Outer Diameter: 1.42" (36 mm) Inner Diameter: 0.49" (12 mm) Length: 3.54" (90 mm)</p>
	<p>Part Number: P550631 Description: FUEL CARTRIDGE Primary App: CUMMINS 299631 Dimensions: Outer Diameter: 4.13" (105 mm) Inner Diameter: 1.81" (46 mm) Length: 8.06" (205 mm)</p>		<p>Part Number: P550648 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU WHEEL LOADERS 4241611140 Dimensions: Outer Diameter: 4.02" (102 mm) Inner Diameter: 1.78" (45 mm) Length: 8.98" (228 mm)</p>
	<p>Part Number: P550632 Description: FUEL CARTRIDGE Primary App: MERCEDES 0000901551 Dimensions: Outer Diameter: 3.62" (92 mm) Inner Diameter: 1.06" (27 mm) Length: 3.98" (101 mm) Efficiency 99% @ 8 Micron</p>		<p>Part Number: P550653 Description: FUEL CARTRIDGE Primary App: Scania Serie P,R,T, 4; Scania bus Irizar K and N Dimensions: Outer Diameter: 2.56" (65 mm) Inner Diameter: 1.50" (38 mm) Length: 6.38" (162 mm)</p>
	<p>Part Number: P550633 Description: LUBE CARTRIDGE Primary App: Volvo 1521527 / M&H HU721 Dimensions: Outer Diameter: 2.50" (64 mm) Inner Diameter: 1.22" (31 mm) Length: 5.91" (150 mm)</p>		<p>Part Number: P550654 Description: HYDRAULIC CARTRIDGE Primary App: IHC 930654-C1 Dimensions: Outer Diameter: 4.52" (115 mm) Inner Diameter: 1.75" (44 mm) Length: 9.10" (231 mm) Efficiency 50% @ 4 Micron</p>
	<p>Part Number: P550636 Description: LUBE CARTRIDGE Primary App: P22 RR & MARINE Dimensions: Outer Diameter: 6.50" (165 mm) Inner Diameter: 1.47" (37 mm) Length: 29.38" (746 mm) Efficiency 99% @ 35 Micron</p>		<p>Part Number: P550656 Description: LUBE SPIN-ON COMBINATION Primary App: IH DT466 2004 ON Dimensions: Outer Diameter: 4.65" (118 mm) Thread Size: M95 X 2 Length: 13.67" (347 mm) Gasket OD: 4.68" (119 mm) Gasket ID: 4.00" (102 mm) Efficiency 99% @ 30 Micron</p>
	<p>Part Number: P550637 Description: HYDRAULIC CARTRIDGE Primary App: MACK POWER STEERING Dimensions: Outer Diameter: 5.00" (127 mm) Inner Diameter: 1.50" (38 mm) Length: 4.12" (105 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P550657 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: IH DT466 2004 ON Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 0.82" (21 mm) Length: 5.59" (142 mm) Efficiency 99% @ 7 Micron</p>
	<p>Part Number: P550639 Description: LUBE SPIN-ON FULL FLOW Primary App: IVECO 2992544, CNH 1931099 Dimensions: Outer Diameter: 4.45" (113 mm) Thread Size: M30 x 2 Length: 8.92" (227 mm) Efficiency 50% @ 14 Micron</p>		<p>Part Number: P550659 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CATERPILLAR 1466695 P553205 Std T&D, P553215 T&D WIF Sensor Dimensions: Outer Diameter: 3.68" (93 mm) Thread Size: 1-14 Length: 8.63" (219 mm) Efficiency 99% @ 30 Micron</p>

	<p>Part Number: P550660 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CUMMINS 3991498 TIER 2 QSB & 2VE ENGINES Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: M20 x 1.5 Length: 7.58" (193 mm) Gasket OD: 2.84" (72 mm) Gasket ID: 2.46" (63 mm) Efficiency 99% @ 5 Micron</p>		<p>Part Number: P550671 Description: LUBE SPIN-ON FULL FLOW Primary App: CUMMINS Dimensions: Outer Diameter: 4.67" (119 mm) Thread Size: 1 1/2-12 Length: 8.94" (227 mm) Gasket OD: 4.32" (110 mm) Gasket ID: 3.85" (98 mm) Efficiency 50% @ 14 Micron</p>
	<p>Part Number: P550661 Description: LUBE CARTRIDGE Primary App: Daf 85CF and XF95 Dimensions: Outer Diameter: 4.41" (112 mm) Inlet Diameter: 2.67" (68 mm) Length: 8.66" (220 mm)</p>		<p>Part Number: P550672 Description: FUEL CARTRIDGE Primary App: KOMATSU 600-311-8210 Dimensions: Outer Diameter: 2.93" (74 mm) Inner Diameter: 0.62" (16 mm) Length: 4.11" (104 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P550662 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: VOLVO 11708555 Dimensions: Outer Diameter: 3.68" (94 mm) Thread Size: M16 x 1.5 Length: 4.25" (108 mm)</p>		<p>Part Number: P550673 Description: FUEL CARTRIDGE Primary App: IHC 478037C1 Dimensions: Outer Diameter: 2.93" (74 mm) Inner Diameter: 0.62" (16 mm) Length: 2.20" (56 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P550663 Description: LUBE CARTRIDGE Primary App: DAF 1376481 Dimensions: Outer Diameter: 3.82" (97 mm) Inner Diameter: 0.55" (14 mm) Length: 4.57" (116 mm)</p>		<p>Part Number: P550674 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: BULK FUEL TANK FILTER Dimensions: Outer Diameter: 2.96" (75 mm) Thread Size: 1 1/8-12 Length: 5.23" (133 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P550665 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: Iveco 1907539 / New Holland 1931061 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: M14 x 1.5 Length: 7.60" (193 mm)</p>		<p>Part Number: P550677 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: FRAM PS3808, PUROLATOR GP23 Dimensions: Outer Diameter: 3.80" (97 mm) Thread Size: 1 1/16-16 Length: 4.16" (106 mm) Gasket OD: 3.60" (91 mm) Gasket ID: 3.17" (81 mm) Efficiency @ 10 Micron</p>
	<p>Part Number: P550666 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: JOHN DEERE RE60021 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.73" (69 mm) Length: 3.48" (88 mm) Overall Length: 4.50" (114 mm) Efficiency 50% @ 5 Micron</p>		<p>Part Number: P550678 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: FORD E6HZ9365B Dimensions: Outer Diameter: 3.03" (77 mm) Thread Size: M16 x 1.5 Length: 2.49" (63 mm) Gasket ID: 2.45" (62 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P550667 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: JOHN DEERE RE509032 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.73" (69 mm) Length: 6.65" (169 mm) Overall Length: 7.67" (195 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P550683 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: HINO 23501-1010 Dimensions: Outer Diameter: 3.73" (95 mm) Thread Size: 1-14 Length: 5.69" (145 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.45" (62 mm) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P550668 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: JOHN DEERE RE522687 Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: 1-14 Length: 11.88" (302 mm) Overall Length: 19.64" (499 mm) Efficiency 99% @ 10 Micron</p>		<p>Part Number: P550685 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: FRAM CC1133PL COALESCER Dimensions: Outer Diameter: 3.01" (76 mm) Inner Diameter: 1.04" (26 mm) Length: 7.34" (186 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P550669 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: JOHN DEERE RE522688 Dimensions: Outer Diameter: 4.24" (108 mm) Thread Size: 7/8-14 Length: 6.74" (171 mm) Gasket OD: 3.93" (100 mm) Gasket ID: 3.55" (90 mm) Efficiency 99% @ 5 Micron</p>		<p>Part Number: P550685 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: FRAM CC1133PL COALESCER Dimensions: Outer Diameter: 3.01" (76 mm) Inner Diameter: 1.04" (26 mm) Length: 7.34" (186 mm) Efficiency 99% @ 25 Micron</p>



Part Number: **P550686**
 Description: **FUEL/WATER SEPARATOR CARTRIDGE**
 Primary App: FRAM CS1133PL SEPARATOR
 Dimensions: Outer Diameter: 3.01" (76 mm)
 Inner Diameter: 1.04" (26 mm)
 Length: 4.41" (112 mm)
 Efficiency 99% @ 25 Micron



Part Number: **P550698**
 Description: **HYDRAULIC CARTRIDGE**
 Primary App: GMC 15513845
 Dimensions: Outer Diameter: 3.98" (101 mm)
 Inner Diameter: 1.42" (36 mm)
 Length: 5.00" (127 mm)
 Efficiency 50% @ 22 Micron



Part Number: **P550687**
 Description: **FUEL/WATER SEPARATOR SPIN-ON**
 Primary App: CUMMINS 3309437
 Dimensions: Outer Diameter: 4.65" (118 mm)
 Thread Size: 1 1/4-12
 Length: 11.80" (300 mm)
 Gasket OD: 4.39" (112 mm)
 Gasket ID: 3.87" (98 mm)
 Efficiency 99% @ 25 Micron



Part Number: **P550699**
 Description: **HYDRAULIC CARTRIDGE**
 Primary App: CLARK 244530
 Dimensions: Outer Diameter: 3.45" (88 mm)
 Inner Diameter: 1.13" (29 mm)
 Length: 5.51" (139 mm)
 Efficiency 50% @ 13 Micron
 Efficiency 99% @ 36 Micron



Part Number: **P550688**
 Description: **FUEL/WATER SEPARATOR SPIN-ON**
 Primary App: DEUTZ
 Dimensions: Outer Diameter: 3.06" (78 mm)
 Thread Size: M16 x 1.5
 Length: 6.74" (171 mm)
 Gasket OD: 2.46" (62 mm)
 Efficiency 99% @ 25 Micron



Part Number: **P550700**
 Description: **HYDRAULIC CARTRIDGE**
 Primary App: CAT 2P-5834
 Dimensions: Outer Diameter: 2.97" (75 mm)
 Inner Diameter: 1.02" (26 mm)
 Length: 5.67" (143 mm)
 Efficiency 50% @ 18 Micron
 Efficiency 99% @ 54 Micron



Part Number: **P550690**
 Description: **FUEL/WATER SEPARATOR SPIN-ON**
 Primary App: CASE J911213
 Dimensions: Outer Diameter: 3.03" (77 mm)
 Thread Size: M16 x 1.5
 Length: 4.40" (112 mm)
 Gasket OD: 2.83" (72 mm)
 Gasket ID: 2.46" (62 mm)
 Efficiency 99% @ 25 Micron



Part Number: **P550701**
 Description: **HYDRAULIC SPIN-ON**
 Primary App: CLARK 2366807
 Dimensions: Outer Diameter: 3.72" (95 mm)
 Thread Size: 2-16
 Length: 6.81" (173 mm)
 Gasket OD: 2.83" (72 mm)
 Gasket ID: 2.46" (62 mm)
 Efficiency 50% @ 6 Micron



Part Number: **P550691**
 Description: **FUEL/WATER SEPARATOR SPIN-ON**
 Primary App: CUMMINS 3843447
 Dimensions: Outer Diameter: 3.69" (94 mm)
 Thread Size: 1-14
 Length: 5.85" (149 mm)
 Gasket OD: 2.83" (72 mm)
 Gasket ID: 2.46" (62 mm)
 Efficiency 99% @ 25 Micron



Part Number: **P550702**
 Description: **HYDRAULIC CARTRIDGE**
 Primary App: JOHN DEERE AT127608, AT147343
 Dimensions: Outer Diameter: 5.91" (150 mm)
 Inner Diameter: 4.33" (110 mm)
 Length: 17.72" (450 mm)
 Efficiency 50% @ 10 Micron
 Efficiency 99% @ 22 Micron



Part Number: **P550694**
 Description: **HYDRAULIC CARTRIDGE**
 Primary App: MICHIGAN 230962, JOHN DEERE AT49249
 Dimensions: Outer Diameter: 3.48" (88 mm)
 Inner Diameter: 1.14" (29 mm)
 Length: 5.50" (140 mm)
 Efficiency 50% @ 22 Micron



Part Number: **P550705**
 Description: **HYDRAULIC SPIN-ON**
 Primary App: IHC 1272942C1
 Dimensions: Outer Diameter: 3.75" (95 mm)
 Thread Size: 1 1/2-16
 Length: 8.00" (203 mm)
 Gasket OD: 3.45" (88 mm)
 Gasket ID: 2.97" (75 mm)
 Efficiency 50% @ 10 Micron



Part Number: **P550695**
 Description: **HYDRAULIC SPIN-ON**
 Primary App: PETERBILT 10-960
 Dimensions: Outer Diameter: 3.73" (95 mm)
 Thread Size: 1-12
 Length: 6.83" (173 mm)
 Gasket OD: 2.83" (72 mm)
 Gasket ID: 2.45" (62 mm)
 Relief Valve Setting: 20-24 PSI (1.40-1.70 Bar)
 Efficiency 50% @ 26 Micron



Part Number: **P550707**
 Description: **LUBE SPIN-ON FULL FLOW**
 Primary App: TOYOTA 15601-68010
 Dimensions: Outer Diameter: 4.25" (108 mm)
 Thread Size: M30 x 1.5
 Length: 5.51" (140 mm)
 Gasket OD: 3.37" (86 mm)
 Gasket ID: 2.95" (75 mm)
 Relief Valve Setting: 18-21 PSI (1.30-1.50 Bar)
 Anti Drain Valve: Yes Y/N
 Efficiency 99% @ 48 Micron



Part Number: **P550696**
 Description: **HYDRAULIC CARTRIDGE**
 Primary App: VERSATILE 36169
 Dimensions: Outer Diameter: 3.48" (88 mm)
 Inner Diameter: 1.36" (35 mm)
 Length: 9.27" (235 mm)
 Relief Valve Setting: 16-19 PSI (1.00-1.30 Bar)
 Efficiency 50% @ 22 Micron



Part Number: **P550708**
 Description: **LUBE SPIN-ON FULL FLOW**
 Primary App: KOMATSU 6134-51-5120
 Dimensions: Outer Diameter: 4.24" (108 mm)
 Thread Size: 1 1/8-16
 Length: 6.56" (167 mm)
 Gasket OD: 3.94" (100 mm)
 Gasket ID: 3.58" (91 mm)
 Relief Valve Setting: 27 PSI (1.86 Bar)
 Anti Drain Valve: Yes Y/N
 Efficiency 99% @ 45 Micron



Part Number: P550710
Description: LUBE SPIN-ON FULL FLOW
Primary App: KOMATSU 600-211-6140
Dimensions:
 Outer Diameter: 3.70" (94 mm)
 Thread Size: 1-12
 Length: 3.75" (95 mm)
 Gasket OD: 2.85" (72 mm)
 Gasket ID: 2.45" (62 mm)
 Relief Valve Setting: 34-37 PSI (2.40-2.60 Bar)
 Anti Drain Valve: Yes Y/N
 Efficiency 99% @ 40 Micron



Part Number: P550719
Description: LUBE SPIN-ON FULL FLOW
Primary App: IHC 3136046R93
Dimensions:
 Outer Diameter: 3.73" (95 mm)
 Thread Size: 1-12
 Length: 4.22" (107 mm)
 Gasket OD: 2.78" (71 mm)
 Gasket ID: 2.43" (62 mm)
 Relief Valve Setting: 20-24 PSI (1.40-1.70 Bar)
 Efficiency 99% @ 40 Micron



Part Number: P550711
Description: LUBE SPIN-ON FULL FLOW
Primary App: NISSAN 15208-H8911
Dimensions:
 Outer Diameter: 3.24" (82 mm)
 Thread Size: 3/4-16
 Length: 3.90" (99 mm)
 Gasket OD: 2.26" (57 mm)
 Anti Drain Valve: Yes Y/N
 Efficiency 99% @ 45 Micron



Part Number: P550726
Description: LUBE SPIN-ON FULL FLOW
Primary App: KUBOTA 15841-32430, 15841-32431
Dimensions:
 Outer Diameter: 3.28" (83 mm)
 Thread Size: M20 x 1.5
 Length: 2.78" (71 mm)
 Gasket OD: 2.52" (64 mm)
 Gasket ID: 2.26" (57 mm)
 Relief Valve Setting: 11-15 PSI (0.80-1.00 Bar)
 Efficiency 99% @ 40 Micron



Part Number: P550712
Description: LUBE SPIN-ON FULL FLOW
Primary App: FIAT ALLIS 74744707
Dimensions:
 Outer Diameter: 4.27" (108 mm)
 Thread Size: M30 x 2
 Length: 9.00" (229 mm)
 Gasket OD: 3.96" (101 mm)
 Gasket ID: 3.59" (91 mm)
 Relief Valve Setting: 18-21 PSI (1.30-1.50 Bar)
 Anti Drain Valve: Yes Y/N
 Efficiency 99% @ 35 Micron



Part Number: P550729
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: NAVISTAR 1677004C91
Dimensions:
 Outer Diameter: 4.36" (111 mm)
 Thread Size: 1-14
 Length: 5.05" (128 mm)
 Efficiency 50% @ 5 Micron

Part Number: P550713
Description: LUBE SPIN-ON FULL FLOW
Primary App: LEYLAND HAJ8423
Dimensions:
 Outer Diameter: 5.38" (137 mm)
 Thread Size: 1 1/2-16
 Length: 8.16" (207 mm)
 Gasket OD: 4.28" (109 mm)
 Gasket ID: 3.90" (99 mm)



Part Number: P550730
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: FORD F1HZ9365A, CARRIER 30-01079
Dimensions:
 Outer Diameter: 4.36" (111 mm)
 Thread Size: 1-14
 Length: 5.10" (130 mm)
 Efficiency 50% @ 10 Micron



Part Number: P550714
Description: LUBE SPIN-ON FULL FLOW
Primary App: WHITE 303068145
Dimensions:
 Outer Diameter: 4.27" (108 mm)
 Thread Size: 7/8-16
 Length: 8.06" (205 mm)
 Gasket OD: 2.82" (72 mm)
 Relief Valve Setting: 13-19 PSI
 Anti Drain Valve: Yes Y/N
 Efficiency 99% @ 40 Micron



Part Number: P550731
Description: LUBE SPIN-ON FULL FLOW
Primary App: FORD E7HZ6731A (BRAZILIAN CAB FORWARD)
Dimensions:
 Outer Diameter: 4.25" (108 mm)
 Thread Size: 1-12
 Length: 6.00" (152 mm)
 Gasket OD: 2.82" (72 mm)
 Gasket ID: 2.42" (61 mm)
 Relief Valve Setting: 18-23 PSI (1.30-1.60 Bar)
 Efficiency 50% @ 25 Micron



Part Number: P550715
Description: LUBE SPIN-ON FULL FLOW
Primary App: KUBOTA 15426-32430
Dimensions:
 Outer Diameter: 3.24" (82 mm)
 Thread Size: 3/4-16
 Length: 4.40" (112 mm)
 Gasket OD: 2.58" (66 mm)
 Gasket ID: 2.26" (57 mm)
 Relief Valve Setting: 16-19 PSI (1.00-1.30 Bar)
 Anti Drain Valve: Yes Y/N
 Efficiency 99% @ 40 Micron



Part Number: P550733
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: THERMO KING 118047
Dimensions:
 Outer Diameter: 3.69" (94 mm)
 Thread Size: M22 x 1.5
 Length: 6.42" (163 mm)
 Gasket OD: 2.83" (72 mm)
 Gasket ID: 2.46" (62 mm)
 Efficiency 50% @ 10 Micron



Part Number: P550718
Description: LUBE SPIN-ON FULL FLOW
Primary App: ISUZU 8-9421-7272-0
Dimensions:
 Outer Diameter: 3.54" (90 mm)
 Thread Size: M20 x 1.5
 Length: 4.92" (125 mm)
 Gasket OD: 3.42" (87 mm)
 Gasket ID: 3.01" (76 mm)
 Efficiency 50% @ 19 Micron



















Part Number: P550735
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: NATURAL GAS FUELED CUMMINS ENGINES
Dimensions:
 Outer Diameter: 3.78" (96 mm)
 Thread Size: 1 1/2-16
 Length: 7.35" (187 mm)
 Gasket OD: 3.47" (88 mm)
 Gasket ID: 2.99" (76 mm)













Part Number: P550736
Description: FUEL/WATER SEPARATOR CARTRIDGE
Primary App: DAVCO 380 AND 382 ELEMEX 25 MICRON
Dimensions:
 Outer Diameter: 3.82" (97 mm)
 Inner Diameter: 0.66" (17 mm)
 Length: 7.00" (178 mm)
 Efficiency 99% @ 27 Micron








	<p>Part Number: P550737 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: DAVCO 380 AND 382 ELEMEX 50 MICRON Dimensions: Outer Diameter: 3.82" (97 mm) Inner Diameter: 0.66" (17 mm) Length: 7.00" (178 mm) Efficiency 99% @ 40 Micron</p>		<p>Part Number: P550752 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: FLEETGUARD FS19559 Dimensions: Outer Diameter: 4.62" (117 mm) Inner Diameter: 6.47" (164 mm) Length: 0.65" (17 mm)</p>
	<p>Part Number: P550743 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: GMC 97385488, ISUZU 8973854880 Dimensions: Outer Diameter: 4.02" (102 mm) Thread Size: 3 3/8-8 Length: 5.60" (142 mm) Gasket OD: 3.77" (96 mm) Gasket ID: 3.50" (89 mm) Efficiency 99% @ 4 Micron</p>		<p>Part Number: P550753 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: JOHN DEERE RE509596, RE521818 Dimensions: Outer Diameter: 4.24" (108 mm) Thread Size: 1-12 Length: 10.38" (264 mm) Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P550744 Description: LUBE CARTRIDGE Primary App: Mercedes-Benz A0002690321 Dimensions: Outer Diameter: 2.36" (60 mm) Inner Diameter: 0.63" (16 mm) Length: 3.94" (100 mm)</p>		<p>Part Number: P550754 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: CATERPILLAR 1454501 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.73" (69 mm) Length: 6.65" (169 mm) Overall Length: 7.67" (195 mm) Efficiency 50% @ 5 Micron</p>
	<p>Part Number: P550745 Description: FUEL CARTRIDGE Primary App: YANMAR 120324-55760 Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 0.46" (12 mm) Length: 3.14" (80 mm)</p>		<p>Part Number: P550755 Description: HYDRAULIC SPIN-ON Primary App: JOHN DEERE LVA11522 Dimensions: Outer Diameter: 4.65" (118 mm) Thread Size: 1 1/2-16 Length: 6.29" (160 mm) Efficiency 99% @ 15 Micron</p>
	<p>Part Number: P550746 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: RACOR R45 SERIES Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: 1-14 Length: 3.50" (89 mm) Efficiency 50% @ 2 Micron</p>		<p>Part Number: P550756 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: John Deere RE65431 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.73" (69 mm) Length: 6.65" (169 mm) Overall Length: 7.67" (195 mm) Efficiency 99% @ 150 Micron</p>
	<p>Part Number: P550747 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: RACOR R90 SERIES Dimensions: Outer Diameter: 4.36" (111 mm) Thread Size: 1-14 Length: 6.10" (155 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P550757 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: DAVCO 380 AND 382 15 MICRON Dimensions: Outer Diameter: 3.82" (97 mm) Inner Diameter: 0.66" (17 mm) Length: 7.00" (178 mm) Efficiency 99% @ 16 Micron</p>
	<p>Part Number: P550748 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: RACOR R120 SERIES Dimensions: Outer Diameter: 4.38" (111 mm) Thread Size: 1-14 Length: 8.50" (216 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P550758 Description: LUBE SPIN-ON FULL FLOW Primary App: JOHN DEERE RE519626, RE518977 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: M24 x 1.5 Length: 5.35" (136 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Relief Valve Setting: 24 PSI (1.70 Bar) Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P550750 Description: LUBE CARTRIDGE Primary App: 750 SERIES CARTRIDGE BYPASS Dimensions: Outer Diameter: 7.72" (196 mm) Inner Diameter: 0.86" (22 mm) Length: 15.06" (383 mm) Efficiency 50% @ 5 Micron</p>		<p>Part Number: P550759 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: JOHN DEERE RE509031 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.73" (69 mm) Length: 4.98" (126 mm) Overall Length: 6.00" (152 mm) Efficiency 50% @ 2 Micron</p>
	<p>Part Number: P550751 Description: LUBE CARTRIDGE Primary App: 750 SERIES PREMIUM BYPASS Dimensions: Outer Diameter: 7.72" (196 mm) Inner Diameter: 0.86" (22 mm) Length: 15.06" (383 mm) Efficiency 50% @ 5 Micron</p>		<p>Part Number: P550760 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: JOHN DEERE RE517181 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.72" (69 mm) Length: 4.98" (126 mm) Overall Length: 6.00" (152 mm) Efficiency 50% @ 10 Micron</p>

















	<p>Part Number: P550761 Description: LUBE CARTRIDGE FULL FLOW Primary App: MERCEDES 0001801709 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.00" (51 mm) Length: 8.24" (209 mm) Efficiency 50% @ 15 Micron</p>		<p>Part Number: P550772 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: LIEBHERR 7381877 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.73" (69 mm) Length: 4.75" (121 mm) Overall Length: 5.77" (147 mm) Efficiency 95% @ 30 Micron</p>
	<p>Part Number: P550762 Description: FUEL CARTRIDGE Primary App: MERCEDES 5410900151 Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 0.55" (14 mm) Length: 7.97" (202 mm) Efficiency 99% @ 15 Micron</p>		<p>Part Number: P550773 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: LIEBHERR 7382111 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.73" (69 mm) Length: 6.41" (163 mm) Overall Length: 7.43" (189 mm) Efficiency 50% @ 2 Micron</p>
	<p>Part Number: P550763 Description: LUBE CARTRIDGE FULL FLOW Primary App: METAL FREE LUBE Dimensions: Outer Diameter: 3.26" (83 mm) Inner Diameter: 2.20" (56 mm) Length: 7.59" (193 mm)</p>		<p>Part Number: P550774 Description: FUEL SPIN ON Primary App: CUMMINS 3959612, ISC, ISL ISM ENGINES Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 7/8-14 Length: 6.85" (174 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P550764 Description: LUBE CARTRIDGE FULL FLOW Primary App: MERCEDES, M.A.N., CLAAS Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 0.83" (21 mm) Length: 7.60" (193 mm)</p>		<p>Part Number: P550775 Description: LUBE SPIN-ON FULL FLOW Primary App: CUMMINS QSK ENGINES Dimensions: Outer Diameter: 4.79" (122 mm) Thread Size: M90 x 2.0 Length: 11.85" (301 mm) Efficiency 50% @ 7 Micron</p>
	<p>Part Number: P550765 Description: LUBE CARTRIDGE FULL FLOW Primary App: M.A.N. 51.05504.0098 Dimensions: Outer Diameter: 4.76" (121 mm) Inner Diameter: 2.20" (56 mm) Length: 5.67" (144 mm)</p>		<p>Part Number: P550776 Description: LUBE SPIN-ON FULL FLOW Primary App: KUBOTA 7000015241 Dimensions: Outer Diameter: 3.15" (80 mm) Thread Size: M20 x 1.5 Length: 3.15" (80 mm) Gasket OD: 2.48" (63 mm) Relief Valve Setting: 10-15 PSI (.69-1.03 Bar) Anti Drain Valve: Yes</p>
	<p>Part Number: P550766 Description: LUBE CARTRIDGE FULL FLOW Primary App: MERCEDES, DEMAG, LIEBHERR, O&K, RVI, CLAAS Dimensions: Outer Diameter: 3.27" (83 mm) Length: 5.39" (137 mm)</p>		<p>Part Number: P550777 Description: LUBE SPIN-ON BYPASS Primary App: CUMMINS 330432, 3313289 Dimensions: Outer Diameter: 4.65" (118 mm) Thread Size: 1 3/8-16 Length: 10.24" (260 mm) Gasket OD: 4.32" (110 mm) Gasket ID: 3.85" (98 mm) Efficiency 50% @ 14 Micron</p>
	<p>Part Number: P550767 Description: LUBE CARTRIDGE FULL FLOW Primary App: MERCEDES OM SERIES ENGINES Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 0.83" (21 mm) Length: 5.16" (131 mm)</p>		
	<p>Part Number: P550768 Description: LUBE CARTRIDGE FULL FLOW Primary App: MERCEDES 0001801609 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 1.59" (40 mm) Length: 5.80" (147 mm) Efficiency 99% @ 40 Micron</p>		<p>Part Number: P550778 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: DAF 1433649 Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: 1-14 Length: 9.06" (230 mm) Efficiency @ >10% @ 3-5 Micron Percent</p>
	<p>Part Number: P550769 Description: LUBE CARTRIDGE FULL FLOW Primary App: MERCEDES 0001802109 Dimensions: Outer Diameter: 4.76" (121 mm) Inner Diameter: 2.24" (57 mm) Length: 9.76" (248 mm) Efficiency 99% @ 30 Micron</p>		<p>Part Number: P550779 Description: LUBE SPIN-ON FULL FLOW Primary App: JOHN DEERE RE504836 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: M92 x 2.5 Length: 6.10" (155 mm) Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P550771 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: LIEBHERR 7381645 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.72" (69 mm) Length: 4.75" (121 mm) Overall Length: 5.77" (147 mm) Efficiency 50% @ 5 Micron</p>		<p>Part Number: P550780 Description: FUEL IN-LINE Primary App: MERCEDES A6120920001, SPRINTER VAN PRE 2004 Dimensions: Outer Diameter: 3.59" (91 mm) Inlet Diameter: 0.44" (11 mm) Length: 4.78" (121 mm)</p>

	<p>Part Number: P550781 Description: HYDRAULIC CARTRIDGE Primary App: GILLIG 5322412002 Dimensions: Outer Diameter: 3.98" (101 mm) Inner Diameter: 1.10" (28 mm) Length: 5.06" (129 mm) ID Width: 1.31" (33 mm) Efficiency 99% @ 47 Micron</p>		<p>Part Number: P550794 Description: LUBE SPIN-ON FULL FLOW Primary App: GM 2007 LIGHT TRUCK Dimensions: Outer Diameter: 3.00" (76 mm) Thread Size: M22 x 1.5 Length: 3.26" (83 mm) Relief Valve Setting: 20 PSI (1.40 Bar) Anti Drain Valve: Yes Y/N</p>
	<p>Part Number: P550782 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: DAVCO 210 - M16 X 1.5 - 10 MICRON Dimensions: Outer Diameter: 3.18" (81 mm) Thread Size: M16 x 1.5 Length: 6.93" (176 mm) Gasket OD: 2.91" (74 mm) Gasket ID: 2.52" (64 mm) Efficiency 99% @ 10 Micron</p>		<p>Part Number: P550796 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: DAVCO 380 AND 382 ELEMEX 10 MICRON Dimensions: Outer Diameter: 3.81" (97 mm) Length: 7.03" (179 mm) Inner Diameter: 0.66" (17 mm) Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P550783 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: DAVCO 210 - M16 X 1.5 - 25 MICRON Dimensions: Outer Diameter: 3.18" (81 mm) Thread Size: M16 x 1.5 Length: 6.93" (176 mm) Gasket OD: 2.91" (74 mm) Gasket ID: 2.52" (64 mm) Efficiency 99% @ 25 Micron</p>		<p>Part Number: P550797 Description: LUBE CARTRIDGE Primary App: MERCEDES 6421800009 Dimensions: Outer Diameter: 2.79" (71 mm) Inner Diameter: 1.22" (31 mm) Length: 3.74" (95 mm) Efficiency 99% @ 38 Micron</p>
	<p>Part Number: P550784 Description: LUBE SPIN-ON FULL FLOW Primary App: FORD E3TZ6731A, IHC 6.9L 1804442C1 Dimensions: Outer Diameter: 4.24" (108 mm) Thread Size: 1 1/2-16 Length: 5.63" (143 mm) Gasket OD: 3.89" (99 mm) Gasket ID: 3.55" (90 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P550798 Description: LUBE CARTRIDGE Primary App: MERCEDES 0001802609 Dimensions: Outer Diameter: 2.59" (66 mm) Inner Diameter: 1.22" (31 mm) Length: 4.52" (115 mm) Efficiency 99% @ 39 Micron</p>
	<p>Part Number: P550785 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: CHRYSLER 5015581AD Dimensions: Outer Diameter: 3.39" (86 mm) Inner Diameter: 0.83" (21 mm) Length: 4.09" (104 mm) Efficiency 99% @ 10 Micron</p>		<p>Part Number: P550800 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: DODGE LIGHT TRUCK, CHRYSLER 68001914AA Dimensions: Outer Diameter: 3.41" (87 mm) Inner Diameter: 0.82" (21 mm) Length: 4.10" (104 mm)</p>
	<p>Part Number: P550786 Description: HYDRAULIC SPIN-ON Primary App: LINDE 0009830633 Dimensions: Outer Diameter: 3.71" (94 mm) Thread Size: 1-12 Length: 5.97" (152 mm)</p>		<p>Part Number: P550807 Description: LUBE CARTRIDGE Primary App: WAUKESHA 168660H Dimensions: Outer Diameter: 4.50" (114 mm) Inner Diameter: 1.56" (39 mm) Length: 31.00" (787 mm)</p>
	<p>Part Number: P550787 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 2076071181 Dimensions: Outer Diameter: 5.91" (150 mm) Inner Diameter: 3.62" (92 mm) Length: 7.87" (200 mm)</p>		<p>Part Number: P550808 Description: FUEL CARTRIDGE Primary App: MERCEDES 6460920501 Dimensions: Outer Diameter: 3.58" (91 mm) Length: 3.94" (100 mm) Efficiency @ >85% @ 3-5 Micron</p>
	<p>Part Number: P550788 Description: LUBE SPIN-ON FULL FLOW Primary App: CATERPILLAR ENGINES Dimensions: Outer Diameter: 5.32" (135 mm) Thread Size: 1 1/2-16 Length: 9.61" (244 mm) Gasket OD: 4.31" (109 mm) Gasket ID: 3.92" (99 mm) Efficiency 99% @ 21 Micron</p>		<p>Part Number: P550811 Description: FUEL SPIN-ON SECONDARY Primary App: FORD, IHC 6.9L 1804459C1 Dimensions: Outer Diameter: 4.28" (109 mm) Thread Size: 7/8-14 Length: 4.60" (117 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.45" (62 mm) Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P550793 Description: LUBE CARTRIDGE Primary App: MERCEDES A9061810086 Dimensions: Outer Diameter: 4.06" (103 mm) Length: 5.80" (146 mm)</p>		<p>Part Number: P550812 Description: LUBE CARTRIDGE FULL FLOW Primary App: DAF 1643070 Dimensions: Outer Diameter: 4.44" (113 mm) Inner Diameter: 2.31" (59 mm) Length: 8.66" (220 mm)</p>

	<p>Part Number: P550816 Description: LUBE CARTRIDGE FULL FLOW Primary App: CAT 4J-0816 Dimensions: Outer Diameter: 3.12" (79 mm) Inner Diameter: 1.83" (46 mm) Length: 9.00" (229 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P550830 Description: HYDRAULIC CARTRIDGE Primary App: POWER STEERING FILTER Dimensions: Outer Diameter: 3.38" (86 mm) Inner Diameter: 2.00" (51 mm) Length: 2.73" (69 mm)</p>
	<p>Part Number: P550820 Description: LUBE CARTRIDGE Primary App: MAN 51055040107 / 51055040108, INTERNATIONAL MAXX FORCE 11, 13 ENGINES Dimensions: Outer Diameter: 4.72" (120 mm) Inner Diameter: 2.24" (57 mm) Length: 7.95" (202 mm) Efficiency 50% @ 17 Micron</p>		<p>Part Number: P550832 Description: LUBE SPIN-ON FULL FLOW Primary App: GMC 6439034 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 13/16-16 Length: 7.87" (200 mm) Gasket OD: 3.38" (86 mm) Gasket ID: 3.04" (77 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P550821 Description: FUEL CARTRIDGE Primary App: NAVISTAR 3004473C91, NTERNATIONAL MAXX FORCE 11, 13 ENGINES Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.77" (45 mm) Length: 5.67" (144 mm) F: 1.06" (27 mm) E: 0.55" (14 mm) Efficiency 50% @ 2 Micron</p>		<p>Part Number: P550833 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: GM 6.6L DIESEL Dimensions: Outer Diameter: 4.02" (102 mm) Thread Size: 3 3/8-8 Length: 6.39" (162 mm)</p>
	<p>Part Number: P550822 Description: TRANSMISSION FILTER KIT Primary App: MERCEDES 1402770095 WITH 722.6 TRANSMISSION Dimensions: B: 4.90" (125 mm) C: 1.99" (51 mm)</p>		<p>Part Number: P550834 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: THERMOKING 119342 Dimensions: Outer Diameter: 3.69" (93 mm) Thread Size: M22 X 1.5 Length: 4.98" (126 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P550824 Description: FUEL CARTRIDGE Primary App: NAVISTAR 1878042C91 Dimensions: Outer Diameter: 3.28" (83 mm) Length: 5.54" (141 mm)</p>		<p>Part Number: P550835 Description: LUBE SPIN-ON FULL FLOW Primary App: THERMOKING 119182 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1 1/8-12 Length: 6.85" (174 mm)</p>
	<p>Part Number: P550825 Description: HYDRAULIC STRAINER Primary App: SENNEBOGEN 027376 Dimensions: Outer Diameter: 3.40" (86 mm) Thread Size: 1 1/2-11 BSP Length: 12.20" (310 mm) Efficiency 99% @ 74 Micron</p>		<p>Part Number: P550837 Description: FUEL CARTRIDGE Primary App: VOLVO 11988962, 11708554 Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 0.55" (14 mm) Length: 3.39" (86 mm)</p>
	<p>Part Number: P550826 Description: HYDRAULIC CARTRIDGE Primary App: SENNEBOGEN 027417 Dimensions: Outer Diameter: 3.72" (95 mm) Inner Diameter: 1.81" (46 mm) Length: 24.72" (628 mm) Relief Valve Setting: 87 PSI (6 Bar) Efficiency 99% @ 10 Micron</p>		<p>Part Number: P550847 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CAT 1752949 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-14 Length: 7.37" (187 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P550827 Description: HYDRAULIC CARTRIDGE Primary App: SENNEBOGEN 054523 Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.57" (40 mm) Length: 16.14" (410 mm) Relief Valve Setting: 87 PSI (6 Bar) Efficiency 99% @ 5 Micron</p>		<p>Part Number: P550848 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CUMMINS QSC, QSL TIER 3 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-14 Length: 8.40" (213 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P550828 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CUMMINS ENGINES Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-14 Length: 6.11" (155 mm) Gasket OD: 2.83" (72 mm)</p>		<p>Part Number: P550849 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: DAVCO PLUS SIZE ELEMEX 7 MICRON Dimensions: Outer Diameter: 4.21" (107 mm) Inner Diameter: .66" (17 mm) Length: 7.00" (178 mm) Efficiency 99% @ 8 Micron</p>

<p>Part Number: P550851 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: DAVCO PLUS SIZE ELEMEX 25 MICRON Dimensions: Outer Diameter: 4.21" (107 mm) Inner Diameter: .66" (17 mm) Length: 7.00" (178 mm) Efficiency 99% @ 25 Micron</p>	<p>Part Number: P550879 Description: FUEL SPIN ON Primary App: CUMMINS 4940647 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 7/8-14 Length: 6.89" (175 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Efficiency 99% @ 5 Micron</p>
 <p>Part Number: P550852 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: DAVCO PLUS SIZE ELEMEX 2 MICRON Dimensions: Outer Diameter: 4.21" (107 mm) Inner Diameter: 0.66" (17 mm) Length: 7.00" (178 mm) Efficiency 98% @ 2 Micron Efficiency 99% @ 2 Micron</p>	 <p>Part Number: P550880 Description: FUEL SPIN ON Primary App: CASE 87803200, CUMMINS 4897897 Dimensions: Outer Diameter: 3.66" (93 mm) Inner Diameter: M20 X 1.5 Length: 6.85" (174 mm) Efficiency 99% @ 5 Micron</p>
<p>Part Number: P550853 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: DAVCO PLUS SIZE ELEMEX 50 MICRON Dimensions: Outer Diameter: 4.21" (107 mm) Inner Diameter: .66" (17 mm) Length: 7.00" (178 mm) Efficiency 99% @ 40 Micron</p>	<p>Part Number: P550881 Description: FUEL SPIN ON Primary App: CUMMINS 4897833, IVECO 2992241, DAF 1399760 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: M20 X 1.5 Length: 6.85" (174 mm) Gasket OD: 2.83" (72 mm) Efficiency 99% @ 5 Micron</p>
 <p>Part Number: P550854 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: DAVCO 482 SERIES 7 MICRON Dimensions: Outer Diameter: 5.83" (148 mm) Inner Diameter: 1.02" (26 mm) Length: 8.00" (203 mm) Efficiency 98% @ 7 Micron Efficiency 99% @ 7 Micron</p>	 <p>Part Number: P550882 Description: LUBE SPIN-ON FULL FLOW Primary App: ATLAS COPCO 10300882, FORD, MACK Dimensions: Outer Diameter: 3.66" (97 mm) Thread Size: 3/4-16 Length: 3.58" (91 mm) Gasket OD: 2.82" (72 mm) Gasket ID: 2.42" (61 mm) Relief Valve Setting: 10 - 20 PSI (0.80-1.20 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>
 <p>Part Number: P550860 Description: FUEL CARTRIDGE Primary App: DEUTZ 1160033 (FELT) Dimensions: Outer Diameter: 2.22" (56 mm) Inner Diameter: 0.53" (13 mm) Length: 4.49" (114 mm)</p>	<p>Part Number: P550889 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CUMMINS 3991350 Dimensions: Outer Diameter: 3.69" (93 mm) Thread Size: M20 X 1.5 Length: 7.56" (192 mm) Efficiency 99% @ 5 Micron</p>
 <p>Part Number: P550861 Description: FUEL CARTRIDGE Primary App: DEUTZ, MERCEDES, ATLAS-COPCO, IHC Dimensions: Outer Diameter: 3.30" (84 mm) Inner Diameter: 0.47" (12 mm) Length: 5.50" (140 mm) Efficiency 99% @ 9 Micron</p>	<p>Part Number: P550901 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CUMMINS ENGINES Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-14 Length: 9.71" (247 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.46" (63 mm) Efficiency 99% @ 7 Micron</p>
 <p>Part Number: P550866 Description: COOLANT SPIN-ON Primary App: CUMMINS EXTENDED LIFE COOLANT Dimensions: Outer Diameter: 3.68" (94 mm) Thread Size: M36 X 2 Length: 5.79" (147 mm) Gasket OD: 3.75" (95 mm) Gasket ID: 3.17" (81 mm)</p>	<p>Part Number: P550908 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: SERVICE CARTRIDGE FOR P550907 Dimensions: Outer Diameter: 3.54" (90 mm) Length: 6.22" (158 mm) Efficiency 99% @ 5 Micron</p>
<p>Part Number: P550867 Description: COOLANT SPIN-ON Primary App: CUMMINS EXTENDED SERVICE NON CHEMICAL Dimensions: Outer Diameter: 3.68" (93 mm) Thread Size: M36 X 2 Length: 5.79" (147 mm) Gasket OD: 3.75" (95 mm) Gasket ID: 3.17" (81 mm)</p>	 <p>Part Number: P550909 Description: LUBE SPIN-ON FULL FLOW Primary App: KOMATSU 6736515142 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-16 Length: 6.94" (176 mm) Anti Drain Valve: Yes</p>
 <p>Part Number: P550868 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CASE A39868, DAVID BROWN Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 13/16-18 Length: 4.50" (114 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.46" (62 mm) Efficiency 99% @ 28 Micron</p>	<p>Part Number: P550910 Description: LUBE CARTRIDGE Primary App: Clark C52; GE 2X4223, 41C615890 Dimensions: Outer Diameter: 6.42" (163 mm) Inner Diameter: 1.47" (37 mm) Length: 30.08" (764 mm) Efficiency 99% @ 35 Micron</p>

<p>Part Number: P550920 Description: LUBE SPIN-ON FULL FLOW Primary App: CAT 2698325 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 15/16-16 Overall Length: 7.87" (200 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Efficiency 99% @ 26 Micron (N/A)</p>	<p>Part Number: P550940 Description: HYDRAULIC/LUBE SPIN-ON Primary App: JOHN DEERE AM39653 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 3/4-16 Overall Length: 3.66" (93 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Efficiency 99% @ 40 Micron (N/A)</p>
<p>Part Number: P550927 Description: HYDRAULIC CARTRIDGE Primary App: CATERPILLAR 9T9054 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 3/4-16 Overall Length: 4.21" (107 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Efficiency 99% @ 40 Micron (N/A)</p>	<p>Part Number: P550941 Description: LUBE SPIN-ON FULL FLOW Primary App: CASE, DAVID BROWN, TOYOTA Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 3/4-16 Overall Length: 4.21" (107 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Efficiency 99% @ 40 Micron (N/A)</p>
 <p>Part Number: P550928 Description: FUEL SPIN-ON SECONDARY Primary App: GMC 25010959 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 13/16-12 Length: 4.21" (107 mm) Gasket OD: 3.38" (86 mm) Gasket ID: 3.04" (77 mm) Efficiency 99% @ 16 Micron</p>	<p>Part Number: P550942 Description: LUBE SPIN-ON FULL FLOW Primary App: KUBOTA 1540232090 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 3/4-16 Overall Length: 4.21" (107 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Efficiency 99% @ 40 Micron (N/A)</p>
<p>Part Number: P550929 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CUMMINS 3991498 TIER 2 QSB & 2VE ENGINES Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: M20 X 1.5 Overall Length: 7.96" (202 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Efficiency 99% @ 5 Micron</p>	 <p>Part Number: P550943 Description: FUEL SPIN-ON SECONDARY Primary App: GMC 6.2L 25011214 Dimensions: Outer Diameter: 3.03" (77 mm) Thread Size: M16 x 1.5 Length: 4.87" (124 mm) Gasket OD: 2.75" (70 mm) Gasket ID: 2.37" (60 mm) Efficiency 99% @ 9 Micron</p>
<p>Part Number: P550934 Description: LUBE SPIN-ON FULL FLOW Primary App: FORD E3TZ6731C Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: M20 X 1.5 Overall Length: 5.35" (136 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Efficiency 99% @ 40 Micron (N/A)</p>	 <p>Part Number: P550944 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: GMC 6.2L 25011285 Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 1-12 Length: 6.08" (154 mm) Gasket OD: 3.55" (90 mm) Gasket ID: 3.18" (81 mm) Efficiency 99% @ 38 Micron</p>
 <p>Part Number: P550936 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: GMC 25011011, 8.2L Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 5.35" (136 mm) Gasket OD: 3.38" (86 mm) Gasket ID: 3.04" (77 mm) Efficiency 99% @ 25 Micron</p>	<p>Part Number: P550945 Description: LUBE SPIN-ON FULL FLOW Primary App: M.A.N. Dimensions: Outer Diameter: 4.23" (107 mm) Thread Size: M30 x 2 Length: 6.95" (177 mm) Gasket OD: 4.02" (102 mm) Gasket ID: 3.50" (89 mm)</p>
 <p>Part Number: P550937 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: KOMATSU 6003114510 Dimensions: Outer Diameter: 4.66" (118 mm) Thread Size: 1 1/4-12 Length: 12.25" (311 mm)</p>	 <p>Part Number: P550947 Description: LUBE SPIN-ON FULL FLOW Primary App: GMC 25011106, Detroit Diesel Engines Dimensions: Outer Diameter: 4.67" (119 mm) Thread Size: 1 1/2-12 Length: 6.28" (159 mm) Gasket OD: 4.32" (110 mm) Gasket ID: 3.85" (98 mm) Efficiency 99% @ 21 Micron</p>
<p>Part Number: P550939 Description: LUBE SPIN-ON FULL FLOW Primary App: VOLVO, KUBOTA, NEW HOLLAND, ATLAS COPCO Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 3/4-16 Overall Length: 3.39" (86 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Relief Valve Setting: 10 PSI (0.69 Bar) Efficiency 99% @ 40 Micron (N/A)</p>	 <p>Part Number: P550951 Description: TRANSMISSION CARTRIDGE Primary App: DDA AC PF951 Dimensions: Inlet Diameter: 1.44" (37 mm) Length: 9.06" (230 mm) Efficiency 50% @ 10 Micron</p>

	<p>Part Number: P550955 Description: FUEL BOX PRIMARY Primary App: GMC 6.2 DIESEL, STANADYNE 23775 Dimensions: Width: 2.83" (72 mm) Height: 2.43" (62 mm) Length: 4.61" (117 mm) Efficiency 99% @ 22 Micron</p>		<p>Part Number: P550967 Description: FUEL IN-LINE Primary App: FORD LIGHT TRUCK Dimensions: Outer Diameter: 3.08" (78 mm) Inlet Size: 5/16" Overall Length: 6.77" (172 mm) Outlet Size: 5/16" Efficiency 50% @ 23 Micron</p>
	<p>Part Number: P550958 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: DETROIT DIESEL 25011024 Dimensions: Outer Diameter: 4.67" (119 mm) Thread Size: 1 1/4-12 Length: 8.94" (227 mm) Gasket OD: 4.32" (110 mm) Gasket ID: 3.85" (98 mm) Efficiency 99% @ 30 Micron</p>		<p>Part Number: P550968 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: DODGE LIGHT TRUCK WITH CUMMINS DIESEL Dimensions: Outer Diameter: 3.78" (96 mm) Thread Size: M20 x 1.5 Length: 4.65" (118 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (62 mm) Efficiency 95% @ 20 Micron</p>
	<p>Part Number: P550959 Description: FUEL SPIN-ON SECONDARY Primary App: FORD, GMC 25011026 Dimensions: Outer Diameter: 4.67" (119 mm) Thread Size: 1 1/16-16 Length: 8.94" (227 mm) Gasket OD: 4.32" (110 mm) Gasket ID: 3.85" (98 mm) Efficiency 99% @ 16 Micron</p>		<p>Part Number: P550971 Description: LUBE SPIN-ON FULL FLOW Primary App: ISUZU 8944637150 Dimensions: Outer Diameter: 3.14" (80 mm) Thread Size: 3/4-16 Length: 3.87" (98 mm) Gasket OD: 2.45" (62 mm) Gasket ID: 2.15" (55 mm)</p>
	<p>Part Number: P550960 Description: TRANSMISSION FILTER KIT Primary App: GM LIGHT TRUCK Dimensions: Width: 7.00" (178 mm) Height: 8.53" (217 mm) C: 6.58" (167 mm) Length: 5.00" (127 mm)</p>		<p>Part Number: P550973 Description: LUBE SPIN-ON COMBINATION Primary App: ISUZU 8970492820, FULL FLOW BYPASS COMBO Dimensions: Outer Diameter: 4.86" (123 mm) Thread Size: 1 1/2-12 Length: 5.87" (149 mm) Gasket OD: 4.32" (110 mm) Gasket ID: 3.85" (98 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P550963 Description: LUBE SPIN-ON FULL FLOW Primary App: DODGE LIGHT TRUCK Dimensions: Outer Diameter: 3.72" (95 mm) Thread Size: 3/4-16 Length: 3.95" (100 mm) Gasket OD: 2.84" (72 mm) Gasket ID: 2.48" (63 mm) Relief Valve Setting: 8-16 PSI (0.60-1.10 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 20 Micron</p>		<p>Part Number: P550974 Description: FUEL IN-LINE Primary App: CUMMINS 3826094, CASE IH STX Dimensions: Outer Diameter: 1.94" (49 mm) Inlet Size: 3/8" Overall Length: 3.93" (100 mm) Outlet Size: 3/8" Efficiency 99% @ 150 Micron</p>
	<p>Part Number: P550964 Description: LUBE SPIN-ON FULL FLOW Primary App: GM LIGHT TRUCK Dimensions: Outer Diameter: 3.78" (96 mm) Thread Size: 13/16-16 Length: 5.14" (131 mm) Gasket OD: 3.38" (86 mm) Gasket ID: 3.04" (77 mm) Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>		<p>Part Number: P550975 Description: LUBE SPIN-ON FULL FLOW Primary App: VALMET 836136342 Dimensions: Outer Diameter: 3.75" (95 mm) Thread Size: M24 x 1.5 Length: 6.88" (175 mm) Relief Valve Setting: 34-37 PSI (2.40-2.60 Bar) Anti Drain Valve: Yes Y/N</p>
	<p>Part Number: P550965 Description: LUBE SPIN-ON FULL FLOW Primary App: FORD LIGHT TRUCK Dimensions: Outer Diameter: 3.67" (93 mm) Thread Size: M22 x 1.5 Length: 3.58" (91 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Relief Valve Setting: 15 PSI (1.03 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>		<p>Part Number: P551000 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CUMMINS CELECT & QUANTUM ENGINE APPLICATIONS Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-14 Length: 9.70" (246 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Stand Pipe: Yes Y/N Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P550966 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: FORD NAVISTAR LIGHT TRUCK Dimensions: Outer Diameter: 3.56" (90 mm) Inner Diameter: 0.56" (14 mm) Length: 3.99" (101 mm) Efficiency 50% @ 7 Micron</p>		<p>Part Number: P551001 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CUMMINS CELECT & QUANTUM ENGINE APPLICATIONS Dimensions: Outer Diameter: 3.68" (93 mm) Thread Size: 1-14 Length: 7.98" (203 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (62 mm) Stand Pipe: Yes Y/N Efficiency 99% @ 10 Micron</p>



Part Number: P551003
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: CUMMINS 3406889 ISM SERIES ENGINES
Dimensions: Outer Diameter: 3.69" (94 mm)
Thread Size: 1-14
Length: 9.71" (247 mm)
Gasket OD: 3.69" (94 mm)
Gasket ID: 2.83" (72 mm)
Stand Pipe: Yes Y/N
Efficiency 99% @ 10 Micron



Part Number: P551006
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: CUMMINS 3089916
Dimensions: Outer Diameter: 4.65" (118 mm)
Thread Size: 1 1/4-12
Length: 12.32" (313 mm)
Gasket OD: 4.39" (112 mm)
Gasket ID: 3.87" (98 mm)
Efficiency 99% @ 10 Micron



Part Number: P551014
Description: LUBE CARTRIDGE FULL FLOW
Primary App: FORD C5TE6744A
Dimensions: Outer Diameter: 4.59" (117 mm)
Inner Diameter: 0.75" (19 mm)
Length: 4.87" (124 mm)



Part Number: P551022
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: CUMMINS ISC ENGINES
Dimensions: Outer Diameter: 3.69" (94 mm)
Thread Size: 1-14
Length: 9.38" (238 mm)
Gasket OD: 2.83" (72 mm)
Gasket ID: 2.46" (62 mm)
Stand Pipe: Yes Y/N
Efficiency 99% @ 10 Micron



Part Number: P551039
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: BOBCAT 6667352, CNH 86504140
Dimensions: Outer Diameter: 3.02" (77 mm)
Thread Size: M16 x 1.5
Length: 3.79" (96 mm)
Efficiency 99% @ 20 Micron



Part Number: P551040
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: CUMMINS 4010651
Dimensions: Outer Diameter: 4.65" (118 mm)
Thread Size: M85 x 2
Length: 11.57" (294 mm)
Gasket OD: 4.68" (119 mm)
Gasket ID: 4.00" (102 mm)
Efficiency 99% @ 25 Micron



Part Number: P551042
Description: LUBE SPIN-ON FULL FLOW
Primary App: BOBCAT 6678233
Dimensions: Outer Diameter: 3.66" (93 mm)
Thread Size: 3/4-16
Length: 3.30" (84 mm)
Gasket OD: 2.83" (72 mm)
Gasket ID: 2.44" (62 mm)



Part Number: P551049
Description: FUEL BOX PRIMARY
Primary App: GMC V8-379, STANADYNE 27611
Dimensions: Width: 3.28" (83 mm)
Height: 2.64" (67 mm)
Length: 6.31" (160 mm)
Efficiency 99% @ 22 Micron



Part Number: P551054
Description: HYDRAULIC CARTRIDGE
Primary App: KOMATSU 0706301054, 154-6012170
Dimensions: Outer Diameter: 3.94" (100 mm)
Inner Diameter: 2.34" (59 mm)
Length: 8.27" (210 mm)
Efficiency 50% @ 14 Micron
Efficiency 99% @ 30 Micron



Part Number: P551102
Description: LUBE SPIN-ON FULL FLOW
Primary App: DEUTZ 1174420
Dimensions: Outer Diameter: 4.33" (110 mm)
Thread Size: 1 1/8-16
Length: 10.08" (256 mm)
Gasket OD: 4.02" (102 mm)
Gasket ID: 3.62" (92 mm)
Relief Valve Setting: 30-42 PSI (2.10-2.80 Bar)
Anti Drain Valve: Yes Y/N
Efficiency 50% @ 20 Micron



Part Number: P551103
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: CUMMINS 3406889 ISM SERIES ENGINES
Dimensions: Outer Diameter: 3.66" (93 mm)
Thread Size: 1-14
Length: 9.40" (239 mm)
Gasket OD: 2.60" (67 mm)
Gasket ID: 2.40" (62 mm)
Stand Pipe: Yes
Efficiency 99% @ 10 Micron



Part Number: P551122
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: CUMMINS ISC ENGINES
Dimensions: Outer Diameter: 3.66" (93 mm)
Thread Size: 1-14
Length: 9.01" (229 mm)
Gasket OD: 2.60" (67 mm)
Gasket ID: 2.40" (62 mm)
Stand Pipe: Yes
Efficiency 99% @ 10 Micron



Part Number: P551127
Description: FUEL SPIN-ON SECONDARY
Primary App: CASE A58713
Dimensions: Outer Diameter: 3.81" (97 mm)
Thread Size: 15/16-16
Length: 5.61" (142 mm)
Gasket OD: 2.85" (72 mm)
Gasket ID: 2.46" (62 mm)
Efficiency 99% @ 12 Micron



Part Number: P551130
Description: FUEL BOX PRIMARY
Primary App: JOHN DEERE AR50041, STANADYNE 20014
Dimensions: Width: 3.71" (94 mm)
Height: 3.15" (80 mm)
Length: 4.95" (126 mm)
Efficiency 99% @ 22 Micron



Part Number: P551142
Description: HYDRAULIC CARTRIDGE
Primary App: KOMATSU 07063-01142, 195-60-16320
Dimensions: Outer Diameter: 5.90" (150 mm)
Inner Diameter: 4.34" (110 mm)
Length: 11.81" (300 mm)
Efficiency 50% @ 14 Micron
Efficiency 99% @ 30 Micron



Part Number: P551158
Description: HYDRAULIC CARTRIDGE
Primary App: KOMATSU 175-49-11580
Dimensions: Outer Diameter: 3.94" (100 mm)
Inner Diameter: 1.65" (42 mm)
Length: 9.12" (232 mm)
Efficiency 50% @ 14 Micron
Efficiency 99% @ 30 Micron

	<p>Part Number: P551160 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 144-60-11160 Dimensions: Outer Diameter: 3.94" (100 mm) Inner Diameter: 2.32" (59 mm) Length: 10.94" (278 mm) Efficiency 50% @ 9 Micron</p>		<p>Part Number: P551193 Description: HYDRAULIC CARTRIDGE Primary App: CASE IH A46403 Dimensions: Outer Diameter: 4.52" (115 mm) Inner Diameter: 2.27" (58 mm) Length: 7.12" (181 mm)</p>
	<p>Part Number: P551162 Description: FUEL CARTRIDGE Primary App: CONTINENTAL 12395HE Dimensions: Outer Diameter: 3.01" (76 mm) Inner Diameter: 1.04" (26 mm) Length: 9.70" (246 mm)</p>		<p>Part Number: P551196 Description: HYDRAULIC CARTRIDGE Primary App: CASE IH 388080R93 Dimensions: Outer Diameter: 7.24" (184 mm) Inner Diameter: 1.49" (38 mm) Length: 2.48" (63 mm)</p>
	<p>Part Number: P551164 Description: FUEL CARTRIDGE Primary App: MASSEY FERGUSON 1006543M91 Dimensions: Outer Diameter: 3.97" (101 mm) Inner Diameter: 0.54" (14 mm) Length: 5.00" (127 mm)</p>		<p>Part Number: P551197 Description: HYDRAULIC CARTRIDGE Primary App: ALLIS CHALMERS 70269310 Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 2.81" (71 mm) Length: 8.97" (228 mm)</p>
	<p>Part Number: P551167 Description: FUEL CARTRIDGE Primary App: CHRYSLER 5037896 Dimensions: Outer Diameter: 2.75" (70 mm) Inner Diameter: 0.81" (21 mm) Length: 3.37" (86 mm)</p>		<p>Part Number: P551200 Description: HYDRAULIC CARTRIDGE Primary App: GM 7194968 Dimensions: Outer Diameter: 2.75" (70 mm) Inner Diameter: 0.31" (8 mm) Length: 3.36" (85 mm)</p>
	<p>Part Number: P551168 Description: FUEL CARTRIDGE Primary App: PERKINS 31938 Dimensions: Outer Diameter: 3.50" (89 mm) Inner Diameter: 0.75" (19 mm) Length: 2.76" (70 mm)</p>		<p>Part Number: P551201 Description: LUBE SPIN-ON FULL FLOW Primary App: ZETTELMEYER 2138220 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 3/4-16 Length: 3.98" (101 mm) Gasket OD: 2.80" (71 mm) Gasket ID: 2.40" (61 mm) Relief Valve Setting: 36 PSI (2.48 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P551178 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: NISSAN FL40399008 Dimensions: Outer Diameter: 3.68" (93 mm) Thread Size: 1-14 Length: 6.85" (174 mm) Gasket OD: 2.85" (72 mm) Gasket ID: 2.47" (63 mm)</p>		<p>Part Number: P551204 Description: HYDRAULIC SPIN-ON Primary App: REXNORD 493308 Dimensions: Outer Diameter: 3.67" (93 mm) Thread Size: 1-12 Length: 3.75" (95 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (62 mm) Relief Valve Setting: 12-15 PSI (0.80-1.00 Bar) Efficiency 99% @ 47 Micron</p>
	<p>Part Number: P551183 Description: HYDRAULIC CARTRIDGE Primary App: CASE IH A44012 Dimensions: Outer Diameter: 4.51" (115 mm) Inner Diameter: 0.66" (17 mm) Length: 7.06" (179 mm)</p>		<p>Part Number: P551205 Description: HYDRAULIC SPIN-ON Primary App: CLARK 6559458 Dimensions: Outer Diameter: 3.68" (93 mm) Thread Size: 1-12 Length: 8.00" (203 mm) Gasket OD: 2.84" (72 mm)</p>
	<p>Part Number: P551187 Description: HYDRAULIC CARTRIDGE Primary App: JOHN DEERE Dimensions: Outer Diameter: 4.52" (115 mm) Inner Diameter: 2.27" (58 mm) Length: 7.97" (202 mm)</p>		<p>Part Number: P551210 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 07063-01210, 205-60-51430 Dimensions: Outer Diameter: 5.90" (150 mm) Inner Diameter: 4.34" (110 mm) Length: 17.72" (450 mm) Efficiency 50% @ 14 Micron Efficiency 99% @ 30 Micron</p>

<p>Part Number: P551211 Description: HYDRAULIC SPIN-ON Primary App: CASE IH A161845 Dimensions: Thread Size: 1 1/2-16 Length: 10.71" (272 mm)</p>	 <p>Part Number: P551244 Description: HYDRAULIC SPIN-ON Primary App: JOHN DEERE AT144879 Dimensions: Outer Diameter: 4.99" (127 mm) Thread Size: 1 1/2-16 Length: 8.22" (209 mm) Gasket OD: 4.17" (106 mm) Efficiency 50% @ 5 Micron</p>
 <p>Part Number: P551213 Description: HYDRAULIC CARTRIDGE Primary App: JOHN DEERE AT62042 Dimensions: Outer Diameter: 4.52" (115 mm) Inner Diameter: 1.75" (44 mm) Length: 7.18" (182 mm)</p>	 <p>Part Number: P551245 Description: HYDRAULIC CARTRIDGE Primary App: HITACHI 3021593 Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 1.38" (35 mm) Length: 8.27" (210 mm)</p>
 <p>Part Number: P551215 Description: HYDRAULIC CARTRIDGE Primary App: CATERPILLAR 349804 Dimensions: Outer Diameter: 4.52" (115 mm) Inner Diameter: 2.27" (58 mm) Length: 9.00" (229 mm) Efficiency 50% @ 16 Micron Efficiency 99% @ 47 Micron</p>	 <p>Part Number: P551251 Description: LUBE SPIN-ON FULL FLOW Primary App: OPEL 2866477 Dimensions: Outer Diameter: 3.00" (76 mm) Thread Size: 3/4-16 Length: 3.42" (87 mm)</p>
 <p>Part Number: P551216 Description: HYDRAULIC CARTRIDGE Primary App: CASE IH L52029 Dimensions: Outer Diameter: 4.52" (115 mm) Inner Diameter: 0.54" (14 mm) Length: 9.00" (229 mm) Efficiency 50% @ 16 Micron Efficiency 99% @ 47 Micron</p>	 <p>Part Number: P551253 Description: LUBE SPIN-ON FULL FLOW Primary App: ROLLS ROYCE CV2473 Dimensions: Outer Diameter: 4.24" (108 mm) Thread Size: M30 x 1.5 Length: 7.48" (190 mm) Gasket OD: 4.05" (103 mm) Gasket ID: 3.42" (87 mm) Relief Valve Setting: 18-21 PSI (1.30-1.50 Bar) Efficiency 50% @ 15 Micron</p>
 <p>Part Number: P551222 Description: HYDRAULIC CARTRIDGE Primary App: JOHN DEERE AT45811 Dimensions: Outer Diameter: 4.52" (115 mm) Inner Diameter: 2.22" (56 mm) Length: 7.44" (189 mm)</p>	 <p>Part Number: P551257 Description: LUBE SPIN-ON FULL FLOW Primary App: ISUZU X13201012 Dimensions: Outer Diameter: 4.33" (110 mm) Thread Size: M20 x 1.5 Length: 6.38" (162 mm) Gasket OD: 4.13" (105 mm) Gasket ID: 3.74" (95 mm) Efficiency 99% @ 5 Micron</p>
 <p>Part Number: P551227 Description: HYDRAULIC SPIN-ON Primary App: GM 25010643 Dimensions: Outer Diameter: 4.67" (119 mm) Thread Size: 1 5/16-12 Length: 10.30" (262 mm) Gasket OD: 4.19" (106 mm) Gasket ID: 3.66" (93 mm) Efficiency 50% @ 6 Micron</p>	 <p>Part Number: P551262 Description: LUBE SPIN-ON FULL FLOW Primary App: NAVISTAR 1808896C1 Dimensions: Outer Diameter: 3.67" (93 mm) Thread Size: 1-12 Length: 8.00" (203 mm) Gasket OD: 2.85" (72 mm) Gasket ID: 2.47" (63 mm)</p>
 <p>Part Number: P551234 Description: HYDRAULIC SPIN-ON Primary App: JOHN DEERE RE17380 Dimensions: Outer Diameter: 3.67" (93 mm) Thread Size: 1-12 Length: 5.66" (144 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (62 mm) Efficiency 50% @ 10 Micron</p>	 <p>Part Number: P551263 Description: LUBE SPIN-ON FULL FLOW Primary App: VOLVO 8477416 Dimensions: Outer Diameter: 4.24" (108 mm) Thread Size: 1 1/8-16 Length: 7.02" (178 mm) Gasket OD: 3.94" (100 mm) Gasket ID: 3.56" (90 mm)</p>
 <p>Part Number: P551235 Description: HYDRAULIC SPIN-ON Primary App: JOHN DEERE AT147496 Dimensions: Outer Diameter: 3.86" (98 mm) Thread Size: 1 1/2-16 Length: 9.50" (241 mm) Efficiency 50% @ 4 Micron</p>	 <p>Part Number: P551264 Description: LUBE SPIN-ON FULL FLOW Primary App: KOMATSU/KOMATSU DRESSER Z1402OF105 Dimensions: Outer Diameter: 4.24" (108 mm) Thread Size: M20 x 1.5 Length: 5.62" (143 mm) Gasket OD: 3.94" (100 mm) Gasket ID: 3.56" (90 mm) Relief Valve Setting: 20 PSI (1.38 Bar) Anti Drain Valve: Yes Y/N</p>
 <p>Part Number: P551242 Description: HYDRAULIC SPIN-ON Primary App: JOHN DEERE AT103193 Dimensions: Outer Diameter: 4.89" (124 mm) Thread Size: 1 1/2-16 Length: 8.22" (209 mm) Gasket OD: 4.17" (106 mm) Efficiency 50% @ 8 Micron</p>	



Part Number: P551265
Description: LUBE SPIN-ON FULL FLOW
Primary App: DAEWOO 65055105009
Dimensions:
 Outer Diameter: 3.67" (93 mm)
 Thread Size: 1-16
 Length: 6.87" (174 mm)
 Gasket OD: 2.83" (72 mm)
 Gasket ID: 2.46" (62 mm)



Part Number: P551290
Description: HYDRAULIC CARTRIDGE
Primary App: KOMATSU 281-16-11290
Dimensions:
 Outer Diameter: 3.94" (100 mm)
 Inner Diameter: 1.62" (41 mm)
 Length: 9.12" (232 mm)
 Efficiency 50% @ 14 Micron
 Efficiency 99% @ 30 Micron



Part Number: P551266
Description: LUBE SPIN-ON FULL FLOW
Primary App: NISSAN FL20129010
Dimensions:
 Outer Diameter: 4.24" (108 mm)
 Thread Size: 1 1/8-16
 Length: 6.73" (171 mm)
 Gasket OD: 4.01" (102 mm)
 Gasket ID: 3.60" (91 mm)
 Efficiency 99% @ 37 Micron



Part Number: P551291
Description: LUBE CARTRIDGE FULL FLOW
Primary App: LEYLAND 134311
Dimensions:
 Outer Diameter: 2.75" (70 mm)
 Inner Diameter: 1.31" (33 mm)
 Length: 3.33" (85 mm)



Part Number: P551267
Description: LUBE SPIN-ON FULL FLOW
Primary App: NISSAN 1520129008
Dimensions:
 Outer Diameter: 4.24" (108 mm)
 Thread Size: 3/4-16
 Length: 6.59" (167 mm)
 Gasket OD: 2.82" (72 mm)
 Gasket ID: 2.46" (62 mm)
 Efficiency 99% @ 30 Micron



Part Number: P551294
Description: LUBE CARTRIDGE FULL FLOW
Primary App: CASE IH 376373R91
Dimensions:
 Outer Diameter: 2.30" (58 mm)
 Inner Diameter: 0.44" (11 mm)
 Length: 4.63" (118 mm)



Part Number: P551268
Description: LUBE SPIN-ON FULL FLOW
Primary App: KUBOTA 1732132430
Dimensions:
 Outer Diameter: 3.67" (93 mm)
 Thread Size: 3/4-16
 Length: 3.39" (86 mm)
 Gasket OD: 2.83" (72 mm)
 Gasket ID: 2.46" (62 mm)



Part Number: P551296
Description: LUBE CARTRIDGE FULL FLOW
Primary App: CASE IH A40902
Dimensions:
 Outer Diameter: 2.97" (75 mm)
 Inner Diameter: 1.07" (27 mm)
 Length: 5.64" (143 mm)
 Efficiency 99% @ 30 Micron

Part Number: P551277
Description: LUBE CARTRIDGE
Primary App: DELUXE WD30
Dimensions:
 Outer Diameter: 4.03" (102 mm)
 Inner Diameter: 0.66" (17 mm)
 Length: 4.67" (119 mm)



Part Number: P551297
Description: LUBE SPIN-ON FULL FLOW
Primary App: KOMATSU/KOMATSU DRESSER 6002115213
Dimensions:
 Outer Diameter: 3.67" (93 mm)
 Thread Size: 1-12
 Length: 6.88" (175 mm)
 Gasket OD: 2.85" (72 mm)
 Gasket ID: 2.47" (63 mm)
 Relief Valve Setting: 18-21 PSI (1.30-1.50 Bar)
 Anti Drain Valve: Yes Y/N
 Efficiency 99% @ 45 Micron



Part Number: P551279
Description: LUBE CARTRIDGE FULL FLOW
Primary App: CHRYSLER 1634447
Dimensions:
 Outer Diameter: 2.98" (76 mm)
 Inner Diameter: 0.78" (20 mm)
 Length: 4.07" (103 mm)



Part Number: P551300
Description: LUBE SPIN-ON FULL FLOW
Primary App: KUBOTA 1540232090
Dimensions:
 Outer Diameter: 3.70" (94 mm)
 Thread Size: 3/4-16
 Length: 4.33" (110 mm)
 Gasket OD: 2.80" (71 mm)
 Gasket ID: 2.48" (63 mm)
 Relief Valve Setting: 34-37 PSI (2.40-2.60 Bar)
 Anti Drain Valve: Yes Y/N



Part Number: P551285
Description: LUBE CARTRIDGE FULL FLOW
Primary App: PERKINS 101606
Dimensions:
 Outer Diameter: 3.50" (89 mm)
 Inner Diameter: 1.34" (34 mm)
 Length: 3.78" (96 mm)



















Part Number: P551304
Description: LUBE SPIN-ON FULL FLOW
Primary App: CASE IH A62423
Dimensions:
 Outer Diameter: 4.24" (108 mm)
 Thread Size: 7/8-16
 Length: 8.05" (204 mm)
 Gasket OD: 2.82" (72 mm)
 Gasket ID: 2.46" (62 mm)
 Anti Drain Valve: Yes Y/N
 Efficiency 99% @ 40 Micron









Part Number: P551287
Description: LUBE SPIN-ON FULL FLOW
Primary App: CATERPILLAR 9M8755
Dimensions:
 Outer Diameter: 3.67" (93 mm)
 Thread Size: 7/8-14
 Length: 3.75" (95 mm)
 Gasket OD: 2.85" (72 mm)
 Gasket ID: 2.45" (62 mm)
 Relief Valve Setting: 17-19 PSI (1.20-1.30 Bar)
 Anti Drain Valve: Yes Y/N
 Efficiency 50% @ 25 Micron

































Part Number: P551306
Description: LUBE SPIN-ON FULL FLOW
Primary App: HONDA, ISUZU, MAZDA
Dimensions:
 Outer Diameter: 3.67" (93 mm)
 Thread Size: M20 x 1.5
 Length: 3.16" (80 mm)
 Gasket OD: 3.59" (91 mm)
 Relief Valve Setting: 13.50 PSI (0.93 Bar)



















	<p>Part Number: P551307 Description: LUBE SPIN-ON FULL FLOW Primary App: GM 6439857,25010325 Dimensions: Outer Diameter: 2.99" (76 mm) Thread Size: 13/16-16 Length: 3.41" (87 mm) Gasket OD: 2.84" (72 mm) Gasket ID: 2.47" (63 mm) Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>		<p>Part Number: P551317 Description: FUEL CARTRIDGE Primary App: Caterpillar 1R-0756 Dimensions: Outer Diameter: 3.90" (99 mm) Inner Diameter: 1.61" (41 mm) Length: 9.23" (234 mm) Efficiency 99% @ 2 Micron</p>
	<p>Part Number: P551309 Description: COOLANT SPIN-ON Primary App: MACK Without Chemical Dimensions: Outer Diameter: 3.67" (93 mm) Thread Size: 3/4-20 Length: 5.32" (135 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P551318 Description: FUEL SPIN ON Primary App: NAVISTAR 1822588C1 Dimensions: Outer Diameter: 4.24" (108 mm) Thread Size: 7/8-14 Length: 7.14" (181 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.45" (62 mm) Efficiency 99% @ 9 Micron</p>
	<p>Part Number: P551310 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: CHRYSLER 0488396AA Dimensions: Outer Diameter: 4.23" (107 mm) Inner Diameter: 0.75" (19 mm) Length: 4.34" (110 mm) Gasket OD: 2.01" (51 mm) Efficiency 99% @ 10 Micron</p>		<p>Part Number: P551323 Description: HYDRAULIC SPIN-ON Primary App: FORD Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 1 1/8-16 Length: 5.26" (134 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Relief Valve Setting: 7-9 PSI (0.50-0.60 Bar) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P551311 Description: FUEL SPIN ON Primary App: Caterpillar 1R0749 Dimensions: Outer Diameter: 3.68" (93 mm) Thread Size: 1-14 Length: 9.43" (240 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (62 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P551324 Description: HYDRAULIC SPIN-ON Primary App: CATERPILLAR Dimensions: Outer Diameter: 3.75" (95 mm) Thread Size: 13/16-16 Length: 4.57" (116 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (62 mm) Relief Valve Setting: 20 PSI (1.38 Bar) Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P551312 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: Caterpillar 1R-0753 Dimensions: Outer Diameter: 3.68" (93 mm) Thread Size: 7/8-14 Length: 9.43" (240 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (62 mm) Efficiency 99% @ 2 Micron</p>		<p>Part Number: P551327 Description: HYDRAULIC SPIN-ON Primary App: HYSTER Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 3/4-16 Length: 5.56" (141 mm) Gasket OD: 2.42" (61 mm) Gasket ID: 2.82" (72 mm) Relief Valve Setting: 23 PSI (1.59 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P551313 Description: FUEL SPIN-ON SECONDARY Primary App: Caterpillar 1R-0750 Dimensions: Outer Diameter: 3.68" (93 mm) Thread Size: 1-14 Length: 6.95" (177 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (62 mm) Efficiency 99% @ 2 Micron</p>		<p>Part Number: P551329 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CASE, CUMMINS Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 13/16-18 Length: 5.85" (149 mm) Efficiency 99% @ 13 Micron</p>
	<p>Part Number: P551315 Description: FUEL SPIN ON Primary App: CATERPILLAR 1R0759 Dimensions: Outer Diameter: 3.15" (80 mm) Thread Size: 7/8-14 Length: 6.93" (176 mm) Gasket OD: 2.89" (74 mm) Gasket ID: 2.50" (64 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P551331 Description: HYDRAULIC CARTRIDGE Primary App: ALLISON TRANS Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 1.18" (30 mm) Length: 8.44" (214 mm) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P551316 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CATERPILLAR 1R0755 Dimensions: Outer Diameter: 5.34" (136 mm) Thread Size: 1 3/8-16 Length: 12.19" (310 mm) Gasket OD: 4.28" (109 mm) Gasket ID: 3.90" (99 mm) Efficiency 99% @ 2 Micron</p>		<p>Part Number: P551333 Description: HYDRAULIC CARTRIDGE Primary App: HITACHI 4206705, KOBELCO 24046273 Dimensions: Outer Diameter: 5.90" (150 mm) Inner Diameter: 4.34" (110 mm) Length: 17.72" (450 mm) Efficiency 50% @ 14 Micron Efficiency 99% @ 30 Micron</p>

	<p>Part Number: P551334 Description: HYDRAULIC CARTRIDGE Primary App: HITACHI 4219713 Dimensions: Outer Diameter: 5.90" (150 mm) Inner Diameter: 4.34" (110 mm) Length: 17.72" (450 mm) Efficiency 50% @ 14 Micron Efficiency 99% @ 30 Micron</p>		<p>Part Number: P551345 Description: LUBE CARTRIDGE Primary App: HITACHI 4231195 Dimensions: Outer Diameter: 6.30" (160 mm) Inner Diameter: 0.28" (7 mm) Length: 5.20" (132 mm) Efficiency 50% @ 5 Micron</p>
	<p>Part Number: P551335 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: DAVCO 320120 Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: 1-14 Length: 7.91" (201 mm) Gasket OD: 3.98" (101 mm) Gasket ID: 3.58" (91 mm) Efficiency 99% @ 20 Micron</p>		<p>Part Number: P551347 Description: HYDRAULIC CARTRIDGE Primary App: CATERPILLAR 997352 Dimensions: Outer Diameter: 2.01" (51 mm) Inner Diameter: 0.91" (23 mm) Length: 2.95" (75 mm)</p>
	<p>Part Number: P551336 Description: LUBE CARTRIDGE FULL FLOW Primary App: FLEETLIFE FP614-40 Dimensions: Outer Diameter: 6.01" (153 mm) Inner Diameter: 3.50" (89 mm) Length: 14.50" (368 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P551348 Description: HYDRAULIC SPIN-ON Primary App: MITSUBISHI C45702411, WP110 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1 1/8-16 Length: 6.81" (173 mm) Gasket OD: 2.80" (71 mm) Gasket ID: 2.01" (51 mm) Efficiency 50% @ 16 Micron</p>
	<p>Part Number: P551337 Description: FUEL CARTRIDGE Primary App: NISSAN 1644497001 Dimensions: Outer Diameter: 4.33" (110 mm) Inner Diameter: 1.02" (26 mm) Length: 7.91" (201 mm) Efficiency 99% @ 30 Micron</p>		<p>Part Number: P551351 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: NISSAN 1640505E01 Dimensions: Outer Diameter: 3.85" (98 mm) Thread Size: 3/4-16 Length: 5.47" (139 mm) Gasket OD: 2.89" (74 mm) Gasket ID: 2.00" (51 mm) Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P551338 Description: FUEL CARTRIDGE Primary App: NISSAN 16444Z9027 Dimensions: Outer Diameter: 3.60" (91 mm) Inner Diameter: 0.59" (15 mm) Length: 6.38" (162 mm) Efficiency 99% @ 30 Micron</p>		<p>Part Number: P551352 Description: LUBE SPIN-ON FULL FLOW Primary App: JOHN DEERE RE59754 Dimensions: Outer Diameter: 3.70" (94 mm) Thread Size: 1 1/2-16 Length: 5.51" (140 mm) Gasket OD: 3.76" (96 mm) Gasket ID: 3.22" (82 mm) Efficiency 99% @ 48 Micron</p>
	<p>Part Number: P551339 Description: FUEL CARTRIDGE Primary App: TOYOTA 0423468010 Dimensions: Outer Diameter: 2.93" (74 mm) Inner Diameter: 0.58" (15 mm) Length: 2.91" (74 mm) Efficiency 99% @ 30 Micron</p>		<p>Part Number: P551360 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: M&H WK1060 Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: 1-12 Length: 10.85" (276 mm) Gasket OD: 4.10" (104 mm) Gasket ID: 3.50" (91 mm)</p>
	<p>Part Number: P551343 Description: LUBE SPIN-ON BYPASS Primary App: MITSUBISHI MD069782 Dimensions: Outer Diameter: 4.02" (102 mm) Thread Size: M26 x 1.5 Length: 5.31" (135 mm) Gasket OD: 2.87" (73 mm) Gasket ID: 1.77" (45 mm) Relief Valve Setting: 12-16 PSI (0.80-1.00 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 16 Micron</p>		<p>Part Number: P551369 Description: HYDRAULIC CARTRIDGE Primary App: VME 4786819 Dimensions: Outer Diameter: 3.78" (96 mm) Inner Diameter: 1.92" (49 mm) Length: 10.00" (254 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P551344 Description: LUBE CARTRIDGE Primary App: HITACHI 4208241 Dimensions: Outer Diameter: 6.50" (165 mm) Inner Diameter: 1.69" (43 mm) Length: 7.56" (192 mm)</p>		<p>Part Number: P551381 Description: LUBE SPIN-ON FULL FLOW Primary App: HINO 15607-1381 Dimensions: Outer Diameter: 4.67" (119 mm) Thread Size: 1 1/2-12 Length: 7.85" (199 mm) Gasket OD: 4.32" (110 mm) Gasket ID: 3.85" (98 mm) Efficiency 50% @ 20 Micron</p>

	<p>Part Number: P551400 Description: LUBE SPIN-ON FULL FLOW Primary App: DETROIT DIESEL 4000 SERIES ENGINE Dimensions: Outer Diameter: 5.33" (135 mm) Thread Size: M45 x 1.5 Length: 12.13" (308 mm) Gasket OD: 4.31" (109 mm) Gasket ID: 3.92" (100 mm) Efficiency 99% @ 21 Micron</p>	<p>Part Number: P551428 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: JOHN DEERE Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: .90" (23 mm) Length: 7.71" (196 mm) Efficiency 99% @ 20 Micron</p>
	<p>Part Number: P551402 Description: LUBE SPIN-ON FULL FLOW Primary App: DD 2000 SERIES AND MARINE VERSION 4000 SERIES Dimensions: Outer Diameter: 5.33" (135 mm) Thread Size: 1 1/2-16 Length: 12.13" (308 mm) Gasket OD: 4.31" (109 mm) Gasket ID: 3.92" (100 mm) Relief Valve Setting: 31-38 PSI (2.20-2.70 Bar) Efficiency 99% @ 21 Micron</p>	<p>Part Number: P551429 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: AGCO, CAT, PERKINS Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: .90" (23 mm) Length: 5.31" (135 mm) Efficiency 99% @ 50 Micron</p>
	<p>Part Number: P551421 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: IR, JOHN DEERE, LIEBHERR Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: .90" (23 mm) Length: 6.05" (154 mm) Efficiency 99% @ 3 Micron</p>	<p>Part Number: P551430 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: JOHN DEERE, LIEBHERR, NEW HOLLAND Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: .90" (23 mm) Length: 6.05" (154 mm) Efficiency 99% @ 50 Micron</p>
	<p>Part Number: P551422 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: JOHN DEERE, LIEBHERR Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: .90" (23 mm) Length: 7.71" (196 mm) Efficiency 99% @ 3 Micron</p>	<p>Part Number: P551431 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: JOHN DEERE, MACK, RVI Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: .90" (23 mm) Length: 7.71" (196 mm) Efficiency 99% @ 50 Micron</p>
	<p>Part Number: P551423 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: CAT, JOHN DEERE Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: .90" (23 mm) Length: 5.31" (135 mm) Efficiency 99% @ 5 Micron</p>	<p>Part Number: P551432 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: CNH, PERKINS, FORD Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: .90" (23 mm) Length: 6.05" (154 mm) Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P551424 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: JOHN DEERE, PERKINS, CAT Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: .90" (23 mm) Length: 6.05" (154 mm) Efficiency 99% @ 5 Micron</p>	<p>Part Number: P551433 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: CNH, FORD, CAT Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: .90" (23 mm) Length: 7.71" (196 mm) Efficiency 99% @ 5 Micron</p>
	<p>Part Number: P551425 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: CAT, CNH, JCB Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: .90" (23 mm) Length: 7.71" (196 mm) Efficiency 99% @ 5 Micron</p>	<p>Part Number: P551434 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: JOHN DEERE, LIEBHERR, CASE, JCB Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: .90" (23 mm) Length: 6.05" (154 mm) Efficiency 99% @ 20 Micron</p>
	<p>Part Number: P551426 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: AGCO, CAT, JCB Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: .90" (23 mm) Length: 5.31" (135 mm) Efficiency 99% @ 20 Micron</p>	<p>Part Number: P551435 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: JOHN DEERE, MCCORMICK Dimensions: Outlet Diameter: 3.15" (80 mm) Inner Diameter: .90" (23 mm) Length: 7.71" (196 mm) Efficiency 99% @ 20 Micron</p>
	<p>Part Number: P551427 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: CAT, JOHN DEERE, JCB Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: .90" (23 mm) Length: 6.05" (154 mm) Efficiency 99% @ 20 Micron</p>	<p>Part Number: P551436 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: CAT Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: .90" (23 mm) Length: 5.31" (135 mm) Efficiency 99% @ 50 Micron</p>
	<p>Part Number: P551427 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: CAT, JOHN DEERE, JCB Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: .90" (23 mm) Length: 6.05" (154 mm) Efficiency 99% @ 20 Micron</p>	<p>Part Number: P551437 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: JOHN DEERE, NEW HOLLAND Dimensions: Inner Diameter: 3.15" (80 mm) Outer Diameter: .90" (23 mm) Length: 6.05" (154 mm) Efficiency 99% @ 50 Micron</p>

	<p>Part Number: P551475 Description: LUBE CARTRIDGE FULL FLOW Primary App: CASE A21475, ALLIS CHALMERS Dimensions: Outer Diameter: 3.93" (100 mm) Inner Diameter: 0.87" (22 mm) Length: 4.81" (122 mm) Efficiency 99% @ 40 Micron</p>		<p>Part Number: P551624 Description: FUEL CARTRIDGE SECONDARY Primary App: AC TP624 w/Pleated Paper Dimensions: Outer Diameter: 4.52" (115 mm) Inner Diameter: 0.69" (18 mm) Length: 8.10" (206 mm) Efficiency 99% @ 30 Micron</p>
	<p>Part Number: P551550 Description: HYDRAULIC SPIN-ON Primary App: GRESEN, MFP, CROSS, DONALDSON LPS04 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 5.35" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 50% @ 4 Micron</p>		<p>Part Number: P551670 Description: LUBE SPIN-ON FULL FLOW Primary App: CUMMINS 3313279, DET DIESEL ENG Dimensions: Outer Diameter: 4.65" (118 mm) Thread Size: 1 1/2-12 Length: 10.24" (260 mm) Gasket OD: 4.32" (110 mm) Gasket ID: 3.85" (98 mm) Efficiency 99% @ 21 Micron</p>
	<p>Part Number: P551551 Description: HYDRAULIC SPIN-ON Primary App: GRESEN, CROSS, DONALDSON LPS04 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 5.35" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P551712 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CATERPILLAR 1R-0712 Dimensions: Outer Diameter: 3.72" (95 mm) Thread Size: 1-14 Length: 9.43" (240 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 9 Micron</p>
	<p>Part Number: P551553 Description: HYDRAULIC SPIN-ON Primary App: GRESEN, CROSS, DONALDSON LPS04 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 5.35" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P551723 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: JOHN DEERE RE61723, RE62424 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 2.73" (69 mm) Length: 6.04" (153 mm) Overall Length: 6.04" (153 mm) Efficiency 95% @ 150 Micron</p>
	<p>Part Number: P551603 Description: LUBE SPIN-ON FULL FLOW Primary App: FIAT 71909101, IVECO 01901603, HESSTON Dimensions: Outer Diameter: 4.26" (108 mm) Thread Size: 3/4-16 Length: 7.25" (184 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Relief Valve Setting: 30 PSI (2.07 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 23 Micron</p>		<p>Part Number: P551740 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CATERPILLAR 1R-0740 Dimensions: Outer Diameter: 3.34" (85 mm) Thread Size: 1-14 Length: 7.09" (180 mm) Gasket OD: 2.50" (64 mm) Gasket ID: 2.11" (54 mm) Efficiency 99% @ 9 Micron</p>
	<p>Part Number: P551604 Description: LUBE SPIN-ON FULL FLOW Primary App: FIAT 71909137, IVECO 01901604 Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: 1-12 Length: 9.13" (232 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.46" (62 mm) Relief Valve Setting: 18-20 PSI (1.30-1.40 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 14 Micron</p>		<p>Part Number: P551744 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: RACOR R24S Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 1-14 Length: 5.52" (140 mm) Gasket OD: 3.43" (87 mm) Gasket ID: 3.11" (79 mm)</p>
	<p>Part Number: P551605 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: IVECO 1901605 Dimensions: Outer Diameter: 4.29" (109 mm) Thread Size: 3/4-16 Length: 7.20" (183 mm) Gasket OD: 2.80" (71 mm) Gasket ID: 2.40" (61 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P551745 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CATERPILLAR 1290373 Dimensions: Outer Diameter: 4.38" (111 mm) Thread Size: 1-14 Length: 11.31" (287 mm) Gasket OD: 3.50" (89 mm) Gasket ID: 3.18" (81 mm)</p>
			<p>Part Number: P551746 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CATERPILLAR 1335673 Dimensions: Outer Diameter: 4.38" (111 mm) Thread Size: 1-14 Length: 11.30" (287 mm) Gasket OD: 3.50" (89 mm) Gasket ID: 3.18" (81 mm) Efficiency 99% @ 5 Micron</p>
			<p>Part Number: P551748 Description: FUEL CARTRIDGE Primary App: JOHN DEERE AR45678 Dimensions: Outer Diameter: 3.37" (86 mm) Inner Diameter: 0.75" (19 mm) Length: 4.12" (105 mm)</p>









	<p>Part Number: P551751 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: REPLACES WIX 24104 Dimensions: Outer Diameter: 2.62" (67 mm) Thread Size: 1-14 Length: 4.34" (110 mm) Gasket OD: 1.00" (25 mm) Gasket ID: 0.80" (20 mm)</p>		<p>Part Number: P551759 Description: FUEL IN-LINE Primary App: CHRYSLER 4554040 Dimensions: Outer Diameter: 2.16" (55 mm) Inlet Size: 3/8" Overall Length: 6.37" (162 mm) Outlet Size: 5/16" Efficiency 50% @ 23 Micron</p>
	<p>Part Number: P551752 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: AMACO A08 Dimensions: Outer Diameter: 3.67" (93 mm) Thread Size: 1 3/8-12 Length: 7.50" (190 mm) Gasket OD: 2.73" (69 mm) Gasket ID: 2.42" (61 mm) Efficiency 50% @ 30 Micron</p>		<p>Part Number: P551760 Description: FUEL IN-LINE Primary App: ISUZU 825053640, 8251217780 Dimensions: Outer Diameter: 2.32" (59 mm) Inlet Size: 5/16" Overall Length: 5.47" (139 mm) Outlet Size: 5/16" Efficiency 50% @ 23 Micron</p>
	<p>Part Number: P551753 Description: HYDRAULIC CARTRIDGE Primary App: CATERPILLAR 1R0746 Dimensions: Outer Diameter: 2.91" (74 mm) Inner Diameter: 1.06" (27 mm) Length: 5.68" (144 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P551761 Description: LUBE CARTRIDGE FULL FLOW Primary App: CASE 902125 Dimensions: Outer Diameter: 3.98" (101 mm) Inner Diameter: 1.27" (32 mm) Length: 2.78" (71 mm)</p>
	<p>Part Number: P551754 Description: HYDRAULIC CARTRIDGE Primary App: CATERPILLAR 955481 Dimensions: Outer Diameter: 4.50" (114 mm) Inner Diameter: 2.28" (58 mm) Length: 7.18" (182 mm)</p>		<p>Part Number: P551763 Description: LUBE SPIN-ON FULL FLOW Primary App: KOHLER 1205001, CUB CADET Dimensions: Outer Diameter: 2.92" (74 mm) Thread Size: 3/4-16 Length: 4.53" (115 mm) Gasket OD: 2.73" (69 mm) Gasket ID: 2.43" (62 mm) Relief Valve Setting: 8 PSI (0.55 Bar) Anti Drain Valve: Yes Y/N</p>
	<p>Part Number: P551755 Description: HYDRAULIC CARTRIDGE Primary App: TOWMOTOR 941053 Dimensions: Outer Diameter: 1.63" (41 mm) Inner Diameter: 0.87" (22 mm) Length: 3.44" (87 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P551764 Description: LUBE SPIN-ON FULL FLOW Primary App: GM 6438868 Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 13/16-16 Length: 5.20" (132 mm) Gasket OD: 3.44" (87 mm) Gasket ID: 3.10" (79 mm)</p>
	<p>Part Number: P551756 Description: HYDRAULIC SPIN-ON Primary App: IHC 404886R1 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 3.79" (96 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (62 mm) Relief Valve Setting: 7-9 PSI (0.48-0.62 Bar)</p>		<p>Part Number: P551766 Description: TRANSMISSION FILTER KIT Primary App: FORD TRUCKS, VANS WITH E40D 2WD TRANSMISSION Dimensions: Width: 6.90" (175 mm) Height: 10.72" (272 mm)</p>
	<p>Part Number: P551757 Description: HYDRAULIC SPIN-ON Primary App: ZF 750131012, JOHN DEERE AT179323 Dimensions: Outer Diameter: 3.70" (94 mm) Thread Size: M24 x 1.5 Length: 5.96" (151 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.46" (62 mm)</p>		<p>Part Number: P551767 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: GM 23514654, JOHN DEERE 500186 Dimensions: Outer Diameter: 4.38" (111 mm) Thread Size: 1-14 Length: 8.21" (209 mm) Efficiency 99% @ 40 Micron</p>
<p>Part Number: P551758 Description: HYDRAULIC SPIN-ON Primary App: HYSTER 309112 Hyster Lift Trucks Dimensions: Outer Diameter: 3.70" (94 mm) Thread Size: 3/4-16 Length: 4.35" (110 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (62 mm) Relief Valve Setting: 16 PSI (1.10 Bar)</p>			<p>Part Number: P551768 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: RACOR R12P Dimensions: Outer Diameter: 3.00" (76 mm) Thread Size: M18 x 1.5 Length: 2.40" (62 mm) Efficiency 50% @ 15 Micron</p>
			<p>Part Number: P551769 Description: FUEL CARTRIDGE Primary App: ISUZU 5878101970 Dimensions: Outer Diameter: 1.87" (47 mm) Inner Diameter: 0.51" (13 mm) Length: 1.77" (45 mm)</p>

	<p>Part Number: P551770 Description: FUEL IN-LINE Primary App: KOMATSU 20704A1100 Dimensions: Outer Diameter: 1.88" (48 mm) Inlet Size: 1/2" Overall Length: 4.34" (110 mm) Outlet Size: 1/2" Efficiency 99% @ 150 Micron</p>		<p>Part Number: P551780 Description: HYDRAULIC SPIN-ON Primary App: KUBOTA 3586182630 Dimensions: Outer Diameter: 3.67" (93 mm) Thread Size: 1-12 Length: 7.35" (187 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (63 mm)</p>
	<p>Part Number: P551771 Description: FUEL IN-LINE Primary App: GM 25055347 Dimensions: Outer Diameter: 2.00" (51 mm) Inlet Size: 1/2" Overall Length: 4.35" (110 mm) Outlet Size: 1/2" Efficiency 50% @ 23 Micron</p>		<p>Part Number: P551781 Description: LUBE CARTRIDGE Primary App: WAUKESHA 73759B Dimensions: Outer Diameter: 5.00" (127 mm) Inner Diameter: 0.69" (18 mm) Length: 7.88" (200 mm)</p>
	<p>Part Number: P551772 Description: FUEL IN-LINE Primary App: FORD F89Z9155A Dimensions: Outer Diameter: 2.30" (58 mm) Inlet Size: 5/16" Overall Length: 7.00" (178 mm) Outlet Size: 5/16"</p>		<p>Part Number: P551783 Description: LUBE SPIN-ON FULL FLOW Primary App: HONDA 15410MM90003 Dimensions: Outer Diameter: 2.69" (68 mm) Thread Size: M20 x 1.5 Length: 2.78" (71 mm) Gasket OD: 2.42" (61 mm) Gasket ID: 2.23" (57 mm) Relief Valve Setting: 8 PSI (0.55 Bar)</p>
	<p>Part Number: P551773 Description: FUEL SPIN-ON SECONDARY Primary App: JOHN DEERE RE506428 Dimensions: Outer Diameter: 4.22" (107 mm) Thread Size: 7/8-14 Length: 5.84" (148 mm) Gasket OD: 3.56" (90 mm) Gasket ID: 3.16" (80 mm)</p>		<p>Part Number: P551784 Description: LUBE SPIN-ON FULL FLOW Primary App: LISTER PETTER 75110620 Dimensions: Outer Diameter: 3.67" (93 mm) Thread Size: 3/4-16 Length: 2.22" (56 mm) Gasket OD: 2.75" (70 mm) Gasket ID: 2.43" (62 mm) Efficiency 50% @ 13 Micron</p>
	<p>Part Number: P551774 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: JOHN DEERE RE519608 Dimensions: Outer Diameter: 4.24" (108 mm) Thread Size: 1-12 Length: 8.90" (226 mm) Gasket OD: 3.57" (91 mm) Gasket ID: 3.15" (80 mm)</p>		<p>Part Number: P551807 Description: LUBE SPIN-ON FULL FLOW Primary App: CATERPILLAR 1R1807, MACK 485GB3236 Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: 1 1/8-16 Length: 10.32" (262 mm) Gasket OD: 3.89" (99 mm) Gasket ID: 3.55" (90 mm) Efficiency 99% @ 21 Micron</p>
	<p>Part Number: P551775 Description: HYDRAULIC CARTRIDGE Primary App: GM 2354770 Dimensions: Outer Diameter: 2.88" (73 mm) Inner Diameter: 1.06" (27 mm) Length: 3.00" (76 mm)</p>		<p>Part Number: P551808 Description: LUBE SPIN-ON FULL FLOW Primary App: CATERPILLAR 1R1808 Dimensions: Outer Diameter: 5.32" (135 mm) Thread Size: 1 1/2-16 Length: 12.13" (308 mm) Gasket OD: 4.31" (109 mm) Gasket ID: 3.92" (100 mm) Efficiency 99% @ 21 Micron</p>
	<p>Part Number: P551777 Description: HYDRAULIC CARTRIDGE Primary App: SAMSUNG 103061460 Dimensions: Inlet Diameter: 0.84" (21 mm) Length: 3.44" (87 mm)</p>		<p>Part Number: P551915 Description: FUEL SPIN ON Primary App: BULK FUEL TANKS WITH SEDIMENT DRAIN Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 1-12 Length: 7.44" (189 mm) Gasket OD: 2.84" (72 mm) Gasket ID: 2.47" (63 mm) Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P551778 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 706351054 Dimensions: Outer Diameter: 3.94" (100 mm) Inner Diameter: 2.34" (59 mm) Length: 8.31" (211 mm)</p>		<p>Part Number: P552000 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: RACOR 2000SM Dimensions: Outer Diameter: 1.78" (45 mm) Inner Diameter: 0.50" (13 mm) Length: 2.68" (68 mm) Efficiency 99% @ 30 Micron</p>
	<p>Part Number: P551779 Description: HYDRAULIC SPIN-ON Primary App: KUBOTA 3396082631 Dimensions: Outer Diameter: 3.73" (95 mm) Thread Size: 1 1/8-16 Length: 7.02" (178 mm) Gasket OD: 3.44" (87 mm) Gasket ID: 2.97" (75 mm)</p>		<p>Part Number: P551779 Description: HYDRAULIC SPIN-ON Primary App: KUBOTA 3396082631 Dimensions: Outer Diameter: 3.73" (95 mm) Thread Size: 1 1/8-16 Length: 7.02" (178 mm) Gasket OD: 3.44" (87 mm) Gasket ID: 2.97" (75 mm)</p>


















	<p>Part Number: P552006 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CUMMINS 3089916 Dimensions: Outer Diameter: 4.66" (118 mm) Thread Size: 1 1/4"-12 Length: 12.24" (311 mm) Gasket OD: 4.33" (110 mm) Gasket ID: 3.86" (98 mm) Stand Pipe: Yes Y/N Efficiency 99% @ 9 Micron</p>		<p>Part Number: P552070 Description: COOLANT SPIN-ON Primary App: CUMMINS 3318157 Dimensions: Outer Diameter: 3.70" (94 mm) Thread Size: 11/16-16 Length: 4.20" (107 mm) Gasket OD: 2.85" (72 mm) Gasket ID: 2.45" (62 mm) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P552010 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: JOHN DEERE Dimensions: Outer Diameter: 3.25" (83 mm) Inner Diameter: 0.63" (16 mm) Length: 2.44" (62 mm) Efficiency 99% @ 30 Micron</p>		<p>Part Number: P552071 Description: COOLANT SPIN-ON Primary App: CUMMINS 3315116 Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 11/16-16 Length: 4.20" (107 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (62 mm) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P552020 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: RACOR 2020 SERIES Dimensions: Outer Diameter: 4.28" (109 mm) Inner Diameter: 0.81" (21 mm) Length: 9.63" (245 mm) Efficiency 99% @ 30 Micron</p>		<p>Part Number: P552072 Description: COOLANT SPIN-ON Primary App: CUMMINS 3318201 Dimensions: Outer Diameter: 3.70" (94 mm) Thread Size: 11/16-16 Length: 4.20" (107 mm) Gasket OD: 2.85" (72 mm) Gasket ID: 2.45" (62 mm) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P552025 Description: LUBE SPIN-ON FULL FLOW Primary App: IH DT466 2004 ON Dimensions: Outer Diameter: 4.64" (118 mm) Thread Size: M95 X 2 Length: 11.53" (293 mm) Efficiency 99% @ 16 Micron</p>		<p>Part Number: P552073 Description: COOLANT SPIN-ON Primary App: CUMMINS 3315115 Dimensions: Outer Diameter: 3.70" (94 mm) Thread Size: 11/16-16 Length: 5.35" (136 mm) Gasket OD: 2.85" (72 mm) Gasket ID: 2.45" (62 mm) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P552032 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CUMMINS ISC, ISM ENGINES - CONTAINS DRAIN AND SENSOR PORT Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-14 Length: 9.22" (234 mm) Efficiency 99% @ 10 Micron</p>		<p>Part Number: P552074 Description: COOLANT SPIN-ON Primary App: CUMMINS 3316053 Dimensions: Outer Diameter: 3.70" (94 mm) Thread Size: 11/16-16 Length: 5.35" (136 mm) Gasket OD: 2.85" (72 mm) Gasket ID: 2.45" (62 mm) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P552040 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: RACOR 2040SM Dimensions: Outer Diameter: 4.28" (109 mm) Inner Diameter: 0.81" (21 mm) Length: 4.63" (118 mm) Efficiency 99% @ 30 Micron</p>		<p>Part Number: P552075 Description: COOLANT SPIN-ON Primary App: CUMMINS 3318318 Dimensions: Outer Diameter: 3.70" (94 mm) Thread Size: 11/16-16 Length: 5.35" (136 mm) Gasket OD: 2.85" (72 mm) Gasket ID: 2.45" (62 mm) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P552041 Description: LUBE CARTRIDGE Primary App: ISUZU/GMC CAB FORWARD HOUSING Dimensions: Outer Diameter: 6.50" (165 mm) Thread Size: 3/8-24 Length: 8.75" (222 mm)</p>		<p>Part Number: P552076 Description: COOLANT SPIN-ON Primary App: CUMMINS 3318319 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 11/16-16 Length: 7.87" (200 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P552050 Description: LUBE SPIN-ON FULL FLOW Primary App: HINO 156072050 Dimensions: Outer Diameter: 4.65" (118 mm) Thread Size: 1 1/2-16 Length: 7.83" (199 mm) Gasket OD: 4.32" (110 mm) Gasket ID: 3.85" (98 mm) Efficiency 99% @ 39 Micron</p>		<p>Part Number: P552088 Description: COOLANT SPIN-ON Primary App: NALCO NF2008, PENRAY NR2088, FLEETGUARD WF2131 Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 11/16-16 Length: 5.44" (138 mm) Gasket OD: 2.85" (72 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P552055 Description: COOLANT SPIN-ON Primary App: CUMMINS 3305371 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 11/16-16 Length: 7.87" (200 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P552088 Description: COOLANT SPIN-ON Primary App: NALCO NF2008, PENRAY NR2088, FLEETGUARD WF2131 Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 11/16-16 Length: 5.44" (138 mm) Gasket OD: 2.85" (72 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 25 Micron</p>
















	<p>Part Number: P552096 Description: COOLANT SPIN-ON Primary App: VOLVO 1661964, 1699830 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: M16 x 1.5 Length: 5.35" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm)</p>		<p>Part Number: P552251 Description: FUEL SPIN-ON Primary App: IHC 702250C1 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-14 Length: 5.35" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 17 Micron</p>
	<p>Part Number: P552100 Description: LUBE SPIN-ON FULL FLOW Primary App: DET. DIESEL 50 & 60 SERIES ENGINES, 23518480 Dimensions: Outer Diameter: 4.65" (118 mm) Thread Size: 1 5/8-12 Length: 10.24" (260 mm) Gasket OD: 4.32" (110 mm) Gasket ID: 3.85" (98 mm) Efficiency 99% @ 21 Micron</p>		<p>Part Number: P552253 Description: FUEL SPIN-ON SECONDARY Primary App: IHC 702253C1 Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 1-14 Length: 8.69" (221 mm) Gasket OD: 2.84" (72 mm) Gasket ID: 2.47" (63 mm) Efficiency 99% @ 15 Micron</p>
	<p>Part Number: P552106 Description: COOLANT SPIN-ON Primary App: NAVISTAR Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 11/16-16 Length: 5.35" (136 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (62 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P552290 Description: LUBE SPIN-ON FULL FLOW Primary App: CASE, DAVID BROWN, TOYOTA Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 3/4-16 Length: 4.36" (111 mm) Gasket OD: 2.84" (72 mm) Gasket ID: 2.47" (63 mm) Relief Valve Setting: 18-20 PSI (1.30-1.40 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P552126 Description: COOLANT SPIN-ON Primary App: CUMMINS SIGNATURE 600 ENGINE 8 UNITS DCA4 Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: M36 x 2 Length: 5.76" (146 mm) Efficiency 99% @ 25 Micron</p>		<p>Part Number: P552341 Description: FUEL CARTRIDGE Primary App: CAT 9M2341, FOR 9M2342 USE 2 P552341 Dimensions: Outer Diameter: 2.24" (57 mm) Inner Diameter: 0.38" (10 mm) Length: 2.99" (76 mm) Efficiency 99% @ 45 Micron</p>
	<p>Part Number: P552200 Description: FUEL SPIN-ON SECONDARY Primary App: CUMMINS 4088272, FLEETGUARD FF2200 Dimensions: Outer Diameter: 3.58" (91 mm) Thread Size: M72 x 2 Length: 9.00" (228 mm) Gasket OD: 3.74" (95 mm) Gasket ID: 3.10" (79 mm) Efficiency 99% @ 8 Micron</p>		<p>Part Number: P552361 Description: LUBE CARTRIDGE FULL FLOW Primary App: GMC 25177917 Dimensions: Outer Diameter: 2.09" (53 mm) Inner Diameter: 0.77" (20 mm) Length: 3.86" (98 mm)</p>
	<p>Part Number: P552203 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CUMMINS 4010476, FLEETGUARD FF2203 Dimensions: Outer Diameter: 3.72" (95 mm) Thread Size: 1-14 Length: 5.78" (147 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (62 mm)</p>		<p>Part Number: P552363 Description: LUBE SPIN-ON BYPASS Primary App: Thermo King 116228 Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 3/4-20 Length: 5.43" (138 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (63 mm) Efficiency 50% @ 21 Micron</p>
	<p>Part Number: P552206 Description: LUBE CARTRIDGE Primary App: MACK ASET Dimensions: Outer Diameter: 3.84" (98 mm) Length: 7.00" (178 mm)</p>		<p>Part Number: P552366 Description: FUEL IN-LINE Primary App: GM 5651944 Dimensions: Outer Diameter: 2.28" (58 mm) Inlet Size: 5/8-18 Overall Length: 4.75" (121 mm) Outlet Size: 3/8" Efficiency 50% @ 23 Micron</p>
	<p>Part Number: P552231 Description: LUBE CARTRIDGE Primary App: MACK E7 Dimensions: Outer Diameter: 4.29" (109 mm) Length: 7.44" (189 mm)</p>		<p>Part Number: P552370 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: FORD E7HZ-9N184-B, E8HT-9J288-AA Dimensions: Outer Diameter: 4.28" (109 mm) Thread Size: 15/16-16 Length: 10.31" (262 mm) Gasket OD: 2.85" (72 mm) Gasket ID: 2.48" (63 mm)</p>

	<p>Part Number: P552371 Description: FUEL IN-LINE Primary App: GMC 25121293 Dimensions: Outer Diameter: 2.17" (55 mm) Inlet Size: 3/8" Overall Length: 5.47" (137 mm) Outlet Size: M16 x 1.5 Efficiency 50% @ 23 Micron</p>		<p>Part Number: P552383 Description: FUEL CARTRIDGE Primary App: MURPHYMD13924A Dimensions: Outer Diameter: 2.38" (60 mm) Thread Size: 1/4-18 Length: 37.25" (946 mm)</p>
	<p>Part Number: P552373 Description: FUEL CARTRIDGE SECONDARY Primary App: Ford D9PZ-9155-A; GMC 5651924 Dimensions: Outer Diameter: 0.64" (16 mm) Length: 0.79" (20 mm) Efficiency 50% @ 40 Micron</p>		<p>Part Number: P552387 Description: FUEL BOX PRIMARY Primary App: GMC 25010487 Dimensions: Height: 2.59" (66 mm) Width: 2.64" (67 mm) Length: 4.38" (111 mm) Inlet Size: 3/8" Outlet Size: 1/4" Inlet Location: Both Inverted Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P552374 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: Onan 149-2106; Toro 63-8300 Dimensions: Outer Diameter: 3.02" (77 mm) Thread Size: M16 x 1.5 Length: 3.37" (86 mm) Gasket OD: 2.74" (70 mm) Gasket ID: 2.37" (60 mm) Efficiency 50% @ 14 Micron</p>		<p>Part Number: P552391 Description: FUEL IN-LINE Primary App: GMC 250055481 Dimensions: Outer Diameter: 2.17" (55 mm) Thread Size: M16 x 1.5 Overall Length: 4.75" (121 mm) Efficiency 50% @ 12 Micron</p>
	<p>Part Number: P552375 Description: LUBE CARTRIDGE SOCK Primary App: Oliver 156149AS; Waukesha 493009; White 872946 Dimensions: Outer Diameter: 3.63" (92 mm) Inner Diameter: 1.31" (33 mm) Length: 7.88" (200 mm)</p>		<p>Part Number: P552392 Description: FUEL IN-LINE Primary App: BMW 13321270038 13329063165 Dimensions: Outer Diameter: 3.19" (81 mm) Inlet Size: 5/16" Overall Length: 6.26" (159 mm) Outlet Size: 5/16" Efficiency 50% @ 23 Micron</p>
	<p>Part Number: P552376 Description: FUEL IN-LINE Primary App: AMC 8933000076 Dimensions: Outer Diameter: 3.07" (78 mm) Inlet Size: 3/8" Overall Length: 6.06" (154 mm) Outlet Size: 5/16" Efficiency 50% @ 23 Micron</p>		<p>Part Number: P552394 Description: FUEL IN-LINE Primary App: GMC 25175542; Nissan 16400-D0100; Toyota Dimensions: Outer Diameter: 4.05" (103 mm) Inlet Size: 9/32" Overall Length: 2.31" (59 mm) Outlet Size: 9/32" Efficiency 50% @ 23 Micron</p>
	<p>Part Number: P552377 Description: LUBE CARTRIDGE FULL FLOW Primary App: NUGENT LUBE BAG REPLACEMENT CARTRIDGE Dimensions: Outer Diameter: 5.06" (127 mm) Inner Diameter: 0.07" (2 mm) Length: 12.13" (305 mm)</p>		<p>Part Number: P552395 Description: FUEL CARTRIDGE Primary App: WHITE 163956AS Dimensions: Outer Diameter: 1.45" (37 mm) Inner Diameter: 0.70" (18 mm) Length: 3.82" (97 mm)</p>
	<p>Part Number: P552378 Description: FUEL CARTRIDGE Primary App: FORD SBA360720020 Dimensions: Outer Diameter: 1.14" (29 mm) Inner Diameter: 0.52" (13 mm) Length: 2.27" (58 mm)</p>		<p>Part Number: P552397 Description: FUEL IN-LINE Primary App: GMC 25121472 Dimensions: Outer Diameter: 2.28" (58 mm) Inlet Size: 3/8" Overall Length: 6.47" (164 mm) Outlet Size: 3/8" Efficiency 50% @ 23 Micron</p>
	<p>Part Number: P552380 Description: LUBE CARTRIDGE FULL FLOW Primary App: INTERNATIONAL 623017-C1 Dimensions: Outer Diameter: 5.06" (129 mm) Inner Diameter: 2.94" (75 mm) Length: 9.00" (229 mm)</p>		<p>Part Number: P552398 Description: FUEL IN-LINE Primary App: Mitsubishi MB504753, MB658689; Toyota 23030-74020, 23300-19045 Dimensions: Outer Diameter: 2.80" (71 mm) Inlet Size: M14 x 1.5 Overall Length: 4.37" (111 mm) Outlet Size: M12 x 1.25 Efficiency 50% @ 23 Micron</p>
	<p>Part Number: P552382 Description: LUBE CARTRIDGE FULL FLOW Primary App: INTERNATIONAL 406669-R1 406705-R91 Dimensions: Outer Diameter: 2.90" (74 mm) Inner Diameter: 1.12" (28 mm) Length: 5.53" (140 mm)</p>		<p>Part Number: P552399 Description: FUEL IN-LINE Primary App: GMC 25010487 Dimensions: Outer Diameter: 2.05" (52 mm) Inlet Size: 5/16" Overall Length: 2.11" (53 mm) Outlet Size: 5/16"</p>

	<p>Part Number: P552400 Description: FUEL IN-LINE Primary App: Chrysler MB504732, MB504750; Suzuki 15410-61A00 Dimensions: Outer Diameter: 2.80" (71 mm) Inlet Size: M12 x 1.25 Length: 5.04" (128 mm) Outlet Size: M12 x 1.25 Efficiency 50% @ 12 Micron</p>		<p>Part Number: P552409 Description: HYDRAULIC SPIN-ON Primary App: Ford F0NN-B486-AA Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1 1/8-16 Length: 6.48" (164 mm) Gasket OD: 2.73" (69 mm) Gasket ID: 2.42.00" (61 mm) Relief Valve Setting: 11-13 PSI (0.80-0.90 Bar)</p>
	<p>Part Number: P552401 Description: FUEL IN-LINE Primary App: Mitsubishi MB433774 Dimensions: Outer Diameter: 2.07" (53 mm) Inlet Size: 5/16" Overall Length: 2.82" (72 mm) Outlet Size: 5/16"</p>		<p>Part Number: P552410 Description: HYDRAULIC SPIN-ON Primary App: Deutz 4305722 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 8.23" (209 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (63 mm)</p>
	<p>Part Number: P552402 Description: LUBE CARTRIDGE FULL FLOW Primary App: Case A22279; International 133205-R91 Dimensions: Outer Diameter: 3.09" (79 mm) Inner Diameter: 1.03" (26 mm) Length: 1.56" (40 mm)</p>		<p>Part Number: P552412 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 922785 Dimensions: Outer Diameter: 4.25" (108 mm) Inner Diameter: 3.12" (79 mm) Length: 9.56" (243 mm) Gasket OD: 4.00" (102 mm) Gasket ID: 3.44" (87 mm)</p>
	<p>Part Number: P552403 Description: FUEL IN-LINE Primary App: Chrysler 4443452, 4443454, 4549712 Dimensions: Outer Diameter: 2.18" (55 mm) Inlet Size: 5/16" Length: 4.74" (120 mm) Outlet Size: 5/16"</p>		<p>Part Number: P552414 Description: LUBE CARTRIDGE SOCK Primary App: WHITE 673374 Dimensions: Outer Diameter: 6.75" (171 mm) Inner Diameter: 2.47" (63 mm) Length: 17.75" (451 mm)</p>
	<p>Part Number: P552404 Description: LUBE SPIN-ON BYPASS Primary App: Oliver 100126ASA; White 1LA5507 Dimensions: Outer Diameter: 3.79" (96 mm) Thread Size: 2 3/4-4 Length: 6.02" (153 mm) Gasket OD: 3.05" (77 mm) Gasket ID: 2.68" (68 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P552415 Description: LUBE CARTRIDGE FULL FLOW Primary App: GMC 5573976 Dimensions: Outer Diameter: 3.59" (91 mm) Inner Diameter: 1.28" (33 mm) Length: 6.37" (162 mm)</p>
	<p>Part Number: P552405 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: NISSAN 1640305D00, FL40305D00 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 3/4-16 Length: 5.19" (132 mm) Gasket OD: 2.83" (72 mm)</p>		<p>Part Number: P552419 Description: LUBE CARTRIDGE FULL FLOW Primary App: Ford D0HZ-3C602-B; International 507809-C91 Dimensions: Outer Diameter: 2.48" (63 mm) Inner Diameter: 1.08" (27 mm) Length: 3.53" (90 mm)</p>
	<p>Part Number: P552406 Description: HYDRAULIC CARTRIDGE Primary App: Ford C5NN-F882-B, C7NN-F882-A Dimensions: Inlet Diameter: 6.00" (152 mm) Length: 6.03" (153 mm)</p>		<p>Part Number: P552421 Description: LUBE CARTRIDGE FULL FLOW Primary App: Honda 15410-KF0-315, 15412-KF0-000 Dimensions: Outer Diameter: 1.97" (50 mm) Inner Diameter: 0.46" (12 mm) Length: 1.48" (38 mm)</p>
	<p>Part Number: P552407 Description: HYDRAULIC CARTRIDGE Primary App: International 26328-M1, 878015-C3 Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 2.63" (67 mm) Length: 9.00" (229 mm)</p>		<p>Part Number: P552422 Description: LUBE CARTRIDGE FULL FLOW Primary App: BMW 11421745390 11421745391 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 1.49" (38 mm) Length: 6.36" (161 mm)</p>
	<p>Part Number: P552408 Description: HYDRAULIC CARTRIDGE Primary App: Oliver 165442-A Dimensions: Outer Diameter: 2.03" (52 mm) Inner Diameter: 0.89" (22 mm) Length: 5.56" (141 mm)</p>		<p>Part Number: P552423 Description: FUEL CARTRIDGE Primary App: Service Element for Gravity Flow Service Tanks Dimensions: Outer Diameter: 3.13" (80 mm) Inner Diameter: 0.72" (18 mm) Length: 5.44" (138 mm)</p>

	<p>Part Number: P552427 Description: LUBE CARTRIDGE SOCK Primary App: Winslow W1645T Dimensions: Outer Diameter: 4.25" (108 mm) Inner Diameter: 1.25" (32 mm) Length: 16.38" (416 mm)</p>		<p>Part Number: P552448 Description: FUEL IN-LINE Primary App: GMC 25121978 Dimensions: Outer Diameter: 2.28" (58 mm) Inlet Size: 3/8" Overall Length: 6.37" (162 mm) Outlet Size: 3/8" Efficiency 50% @ 23 Micron</p>
	<p>Part Number: P552428 Description: LUBE CARTRIDGE SOCK Primary App: Waukesha 167602B Dimensions: Outer Diameter: 4.50" (114 mm) Inner Diameter: 1.45" (37 mm) Length: 16.00" (406 mm)</p>		<p>Part Number: P552451 Description: LUBE SPIN-ON BYPASS Primary App: Wisconsin RV40 Dimensions: Outer Diameter: 3.33" (85 mm) Thread Size: 2 3/4-5 Length: 4.84" (123 mm)</p>
	<p>Part Number: P552430 Description: LUBE SPIN-ON FULL FLOW Primary App: Harley-Davidson 63805-80A Dimensions: Outer Diameter: 2.92" (74 mm) Thread Size: 3/4-16 Length: 3.40" (86 mm) Gasket OD: 2.73" (69 mm) Gasket ID: 2.42" (61 mm) Relief Valve Setting: 8-11 PSI (N/A) Efficiency 50% @ 24 Micron</p>		<p>Part Number: P552452 Description: HYDRAULIC SPIN-ON Primary App: Komatsu 113-60-23160 Dimensions: Outer Diameter: 4.28" (109 mm) Thread Size: 1 1/8-16 Length: 8.09" (206 mm) Gasket OD: 3.97" (101 mm) Gasket ID: 3.59" (91 mm)</p>
	<p>Part Number: P552432 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: Allis Chalmers 4321716, 4321716-5 Dimensions: Outer Diameter: 3.70" (94 mm) Thread Size: 15/16-16 Length: 8.42" (214 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (63 mm)</p>		<p>Part Number: P552454 Description: LUBE SPIN-ON FULL FLOW Primary App: Allis Chalmers 2100723; Massey Ferguson 3283341-M1 Dimensions: Outer Diameter: 3.23" (82 mm) Thread Size: 3/4-16 Length: 3.19" (81 mm) Gasket OD: 2.49" (63 mm) Gasket ID: 2.01" (51 mm)</p>
	<p>Part Number: P552437 Description: FUEL IN-LINE Primary App: Nissan 16400-72L00 Dimensions: Outer Diameter: 2.50" (64 mm) Inlet Size: 5/16" Overall Length: 5.00" (127 mm) Outlet Size: 5/16" Efficiency 50% @ 23 Micron</p>		<p>Part Number: P552455 Description: LUBE CARTRIDGE FULL FLOW Primary App: Case D45378, G33058, A60524, A61234 Dimensions: Outer Diameter: 3.78" (96 mm) Inner Diameter: 1.10" (28 mm) Length: 6.09" (155 mm)</p>
	<p>Part Number: P552439 Description: FUEL IN-LINE Primary App: Chrysler 4708317, 52019023, 52020016 Dimensions: Outer Diameter: 2.15" (55 mm) Inlet Size: 5/16" Overall Length: 6.22" (158 mm) Outlet Size: 5/16" Efficiency 50% @ 23 Micron</p>		<p>Part Number: P552458 Description: LUBE CARTRIDGE FULL FLOW Primary App: Case D45378, G33058, A60524, A61234 Dimensions: Outer Diameter: 3.78" (96 mm) Inner Diameter: 1.10" (28 mm) Length: 5.96" (151 mm)</p>
	<p>Part Number: P552440 Description: FUEL IN-LINE Primary App: Volkswagen 191127401A Dimensions: Outer Diameter: 3.41" (87 mm) Inlet Size: 5/16" Overall Length: 6.61" (168 mm) Outlet Size: 5/16" Efficiency 50% @ 23 Micron</p>		<p>Part Number: P552459 Description: HYDRAULIC CARTRIDGE Primary App: Allis Chalmers 631828, 4995265 Dimensions: Outer Diameter: 2.72" (69 mm) Inner Diameter: 1.06" (27 mm) Length: 7.78" (198 mm)</p>
	<p>Part Number: P552442 Description: FUEL IN-LINE Primary App: Audi 893133511; Ferrari 117792; Volkswagen 447133511; Volvo 13895628 Dimensions: Outer Diameter: 3.46" (88 mm) Inlet Size: M14 x 1.5 Overall Length: 5.86" (149 mm) Outlet Size: M12 x 1.5 Efficiency 50% @ 23 Micron</p>		<p>Part Number: P552461 Description: HYDRAULIC SPIN-ON Primary App: JOHN DEERE AT184206; KOMATSU 1233914-H1, 1233914-H2, 1233914-H4 Dimensions: Outer Diameter: 5.00" (127 mm) Thread Size: 1 1/2-16 Length: 8.22" (209 mm) Gasket OD: 4.11" (104 mm) Gasket ID: 3.58" (91 mm)</p>
	<p>Part Number: P552444 Description: HYDRAULIC SPIN-ON Primary App: Hesston 8040461 Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 13/16-16 Length: 5.27" (134 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (63 mm)</p>		<p>Part Number: P552462 Description: LUBE CARTRIDGE FULL FLOW Primary App: Ford B8C-6731-A Dimensions: Gasket OD: 4.11" (104 mm) Outer Diameter: 5.00" (127 mm) Inner Diameter: 0.77" (19 mm) Length: 8.22" (209 mm) Gasket ID: 3.58" (91 mm)</p>

	<p>Part Number: P552464 Description: LUBE SPIN-ON FULL FLOW Primary App: Oliver 250046, 100125ASA; Waukesha 119390A, K5507 Dimensions: Outer Diameter: 3.79" (96 mm) Thread Size: 2 3/4-4 Length: 8.13" (206 mm) Gasket OD: 3.05" (77 mm) Gasket ID: 2.68" (68 mm)</p>		<p>Part Number: P552476 Description: HYDRAULIC SPIN-ON Primary App: MASSEY-FERGUSON TRACTORS Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: M24 x 2 Length: 5.50" (140 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (63 mm)</p>
	<p>Part Number: P552465 Description: LUBE CARTRIDGE Primary App: JOHN DEERE AH1081R Dimensions: Outer Diameter: 3.37" (86 mm) Inner Diameter: 1.13" (29 mm) Length: 4.25" (108 mm)</p>		<p>Part Number: P552482 Description: FUEL IN-LINE Primary App: JOHN DEERE RE38818 Dimensions: Outer Diameter: 1.94" (49 mm) Inlet Size: 9/16-18 Overall Length: 3.65" (93 mm) Outlet Size: 9/16-18 Efficiency 99% @ 150 Micron</p>
	<p>Part Number: P552469 Description: LUBE CARTRIDGE FULL FLOW Primary App: John Deere AT45422 Dimensions: Outer Diameter: 4.37" (111 mm) Inner Diameter: 3.62" (92 mm) Length: 9.56" (243 mm)</p>		<p>Part Number: P552483 Description: HYDRAULIC SPIN-ON Primary App: NEW HOLLAND 81869132, FORD F0NN3N976AA Dimensions: Outer Diameter: 3.87" (98 mm) Thread Size: 1 1/8-16 Length: 8.15" (207 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (63 mm)</p>
	<p>Part Number: P552470 Description: FUEL CARTRIDGE Primary App: ALLIS CHALMERS 4512207-3; CHRYSLER J0936407; MASSEY FERGUSON 1069954-M91 Dimensions: Outer Diameter: 3.33" (84 mm) Inner Diameter: 0.58" (15 mm) Length: 2.88" (73 mm)</p>		<p>Part Number: P552504 Description: LUBE SPIN-ON FULL FLOW Primary App: MACK ASET; VOLVO VED12 Dimensions: Outer Diameter: 4.25" (108 mm) Length: 10.31" (262 mm)</p>
	<p>Part Number: P552471 Description: LUBE CARTRIDGE FULL FLOW Primary App: Mercedes-Benz 6171840025, 6171840125 Dimensions: Outer Diameter: 3.47" (88 mm) Inner Diameter: 0.43" (11 mm) Length: 7.61" (193 mm)</p>		<p>Part Number: P552518 Description: LUBE SPIN-ON FULL FLOW Primary App: DODGE 6CYL-225,V8-318, CHYRYS, FORD & OTHERS Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 3/4-16 Length: 4.21" (107 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Relief Valve Setting: 7-10 PSI (0.50 -0.70 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P552472 Description: HYDRAULIC SPIN-ON Primary App: Ford SBA340500610; New Holland 9846407 Dimensions: Outer Diameter: 3.71" (94 mm) Thread Size: 1 1/8-16 Length: 5.59" (142 mm) Gasket OD: 2.73" (69 mm) Gasket ID: 2.42" (61 mm)</p>		<p>Part Number: P552561 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: MITSUBISHI ME035393, ME035829 Dimensions: Outer Diameter: 3.70" (94 mm) Thread Size: M20 x 1.5 Length: 4.72" (120 mm) Gasket OD: 3.43" (87 mm) Gasket ID: 2.52" (64 mm) Efficiency 99% @ 30 Micron</p>
	<p>Part Number: P552473 Description: FUEL CARTRIDGE Primary App: Allis Chalmers BM33761; Cummins BM33761; Ford EDL-9176-A; International 3054750-R91 Dimensions: Outer Diameter: 3.98" (101 mm) Inner Diameter: 0.77" (19 mm) Length: 4.78" (121 mm) Gasket OD: 4.74" (120 mm) Gasket ID: 4.34" (110 mm)</p>		<p>Part Number: P552562 Description: LUBE SPIN-ON COMBINATION Primary App: MITSUBISHI ME074013 Dimensions: Outer Diameter: 5.04" (128 mm) Thread Size: M36 x 1.5 Length: 8.67" (220 mm) Gasket OD: 4.21" (107 mm) Gasket ID: 3.68" (93 mm) Efficiency 99% @ 45 Micron</p>
	<p>Part Number: P552474 Description: LUBE SPIN-ON FULL FLOW Primary App: Allis Chalmers 4037047 Dimensions: Outer Diameter: 4.28" (109 mm) Thread Size: 1-16 Length: 7.33" (186 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (63 mm)</p>		<p>Part Number: P552563 Description: FUEL CARTRIDGE Primary App: ISUZU 5-878100500 Dimensions: Outer Diameter: 2.83" (72 mm) Inner Diameter: 0.57" (14 mm) Length: 3.35" (85 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P552475 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: LUBER-FINER LFP2100C Dimensions: Outer Diameter: 4.26" (108 mm) Thread Size: 15/16-16 Length: 8.96" (228 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.46" (62 mm)</p>		

	<p>Part Number: P552564 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: ISUZU 1-13240-074-0, HITACHI 4206080 Dimensions: Outer Diameter: 3.71" (94 mm) Thread Size: 3/4-16 Length: 4.92" (125 mm) Gasket OD: 2.48" (63 mm) Gasket ID: 1.74" (44 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P553004 Description: FUEL SPIN ON Primary App: VOLVO 243004 Dimensions: Outer Diameter: 2.99" (76 mm) Thread Size: M16 x 1.5 Length: 4.72" (120 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.38" (60 mm) Stand Pipe: Yes Y/N Efficiency 99% @ 16 Micron</p>
	<p>Part Number: P552565 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: DETROIT DIESEL 23530772 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-14 Length: 8.40" (213 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 25 Micron</p>		<p>Part Number: P553080 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CAT 8N-3080, 3500 SERIES ENGINE Dimensions: Outer Diameter: 5.38" (137 mm) Thread Size: 1 3/8-16 Length: 12.13" (308 mm) Gasket OD: 4.31" (109 mm) Gasket ID: 3.92" (100 mm) Efficiency 99% @ 9 Micron</p>
	<p>Part Number: P552603 Description: FUEL SPIN-ON SECONDARY Primary App: IHC 672603C1 Dimensions: Outer Diameter: 4.28" (109 mm) Thread Size: 7/8-14 Length: 7.98" (203 mm) Gasket OD: 2.82" (72 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 9 Micron</p>		<p>Part Number: P553191 Description: LUBE SPIN-ON FULL FLOW Primary App: MACK 485-GB-3191, RENAULT, VOLVO & ON HWY TRUCKS Dimensions: Outer Diameter: 4.24" (108 mm) Thread Size: 1 1/8-16 Length: 10.32" (262 mm) Gasket OD: 3.89" (99 mm) Gasket ID: 3.55" (90 mm) Efficiency 99% @ 219 Micron</p>
	<p>Part Number: P552819 Description: LUBE SPIN-ON FULL FLOW Primary App: DEUTZ, CLARK, HYSTER Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 5.35" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Relief Valve Setting: 18-23 PSI (1.30-1.60 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 20 Micron</p>		<p>Part Number: P553200 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: KOMATSU 6003114510, 6003194540 Dimensions: Outer Diameter: 4.65" (118 mm) Thread Size: 1 1/4-12 Length: 10.04" (255 mm)</p>
	<p>Part Number: P552849 Description: LUBE SPIN-ON FULL FLOW Primary App: FORD, MAZDA Dimensions: Outer Diameter: 2.96" (75 mm) Thread Size: M20 x 1.5 Length: 3.40" (86 mm) Gasket OD: 2.70" (69 mm) Gasket ID: 2.33" (59 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 36 Micron</p>		<p>Part Number: P553201 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: RACOR S3201 Can Replace P555001, P555010, Use P553211 for Twist & Drain Integral Thd Sensor Port Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-14 Length: 8.64" (219 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm)</p>
	<p>Part Number: P552850 Description: HYDRAULIC SPIN-ON Primary App: CLARK 234099-MODEL 35C & 45C, MB GCS20-30 Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 2-16 Length: 5.56" (141 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.45" (62 mm) Relief Valve Setting: 23 PSI (1.59 Bar) Efficiency 50% @ 12 Micron</p>		<p>Part Number: P553202 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: RACOR S3202 Can Replace P555002, P555020, Use P553212 for Twist & Drain Integral Thd Sensor Port Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 8.64" (219 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.05" (77 mm)</p>
	<p>Part Number: P553000 Description: LUBE SPIN-ON COMBINATION Primary App: CUMMINS ENGINES Dimensions: Outer Diameter: 4.65" (118 mm) Thread Size: 2 1/4-12 Length: 11.70" (297 mm) Gasket OD: 4.68" (119 mm) Gasket ID: 4.00" (102 mm) Efficiency 99% @ 16 Micron</p>		<p>Part Number: P553203 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: RACOR S3203 Can Replace P555003, Use P553213 for Twist and Drain Integral Threaded Sensor Port Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-14 Length: 7.61" (193 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm)</p>
			<p>Part Number: P553204 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: ALLIANCE ABPN12232FRT04 Use P553214 for Twist and Drain Integral Threaded Sensor Port Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-14 Length: 8.64" (219 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Efficiency 99% @ 35 Micron</p>



Part Number: P553205
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: CATERPILLAR ENGINES Replaces P550659, Use P553215 for Twist and Drain Integral Threaded Sensor Port
Dimensions: Outer Diameter: 3.66" (93 mm)
Thread Size: 1-14
Length: 7.62" (194 mm)
Gasket OD: 3.39" (86 mm)
Gasket ID: 3.05" (77 mm)
Efficiency 99% @ 15 Micron



Part Number: P553217
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: ALLIANCE ABPN12232FRT03 Use P553207 for Standard Twist and Drain
Dimensions: Outer Diameter: 3.66" (93 mm)
Thread Size: 1-14
Length: 8.64" (219 mm)
Gasket OD: 2.83" (72 mm)
Gasket ID: 2.44" (62 mm)
Efficiency 99% @ 3 Micron



Part Number: P553207
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: ALLIANCE ABPN12232FRT03 Use P553217 for Twist and Drain Integral Threaded Sensor Port
Dimensions: Outer Diameter: 3.66" (93 mm)
Thread Size: 1-14
Length: 8.64" (219 mm)
Gasket OD: 2.83" (72 mm)
Gasket ID: 2.43" (62 mm)
Efficiency 99% @ 3 Micron



Part Number: P553240
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: ISUZU 8-94414-796
Dimensions: Outer Diameter: 3.01" (76 mm)
Thread Size: 3/4-16
Length: 3.46" (88 mm)
Gasket OD: 2.50" (64 mm)
Gasket ID: 2.16" (55 mm)
Efficiency 99% @ 22 Micron



Part Number: P553211
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: RACOR S3201 Can Replace P555001, P555010, Use P553211 for Twist & Drain Integral Thd Sensor Port
Dimensions: Outer Diameter: 3.66" (93 mm)
Thread Size: 1-14
Length: 8.64" (219 mm)
Gasket OD: 2.83" (72 mm)
Gasket ID: 2.44" (62 mm)



Part Number: P553261
Description: FUEL CARTRIDGE SECONDARY
Primary App: GMC 5573261
Dimensions: Outer Diameter: 3.40" (86 mm)
Inner Diameter: 1.10" (28 mm)
Length: 3.27" (83 mm)
Efficiency 99% @ 20 Micron



Part Number: P553212
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: RACOR S3202 Can Replace P555002, P555020, Use P553212 for Twist & Drain Integral Thd Sensor Port
Dimensions: Outer Diameter: 3.66" (93 mm)
Thread Size: 1-12
Length: 8.64" (219 mm)
Gasket OD: 3.39" (86 mm)
Gasket ID: 3.05" (77 mm)



Part Number: P553287
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: DEUTZ 3363287
Dimensions: Outer Diameter: 3.07" (78 mm)
Thread Size: M14 x 1.5
Length: 5.03" (128 mm)



Part Number: P553213
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: RACOR S3203 Can Replace P555003, Use P553213 for Twist and Drain Integral Threaded Sensor Port
Dimensions: Outer Diameter: 3.66" (93 mm)
Thread Size: 1-14
Length: 7.61" (193 mm)
Gasket OD: 2.83" (72 mm)
Gasket ID: 2.44" (62 mm)
Efficiency 99% @ 3 Micron



Part Number: P553293
Description: HYDRAULIC CARTRIDGE
Primary App: GRESEN 3293, A.CHALMERS, CASE
Dimensions: Outer Diameter: 4.52" (115 mm)
Inner Diameter: 1.80" (46 mm)
Length: 7.05" (179 mm)
Efficiency 50% @ 10 Micron
Efficiency 99% @ 25 Micron



Part Number: P553214
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: ALLIANCE ABPN12232FRT04 Use P553204 for Standard Twist and Drain
Dimensions: Outer Diameter: 3.66" (93 mm)
Thread Size: 1-14
Length: 8.64" (219 mm)
Gasket OD: 2.83" (72 mm)
Gasket ID: 2.44" (62 mm)
Efficiency 99% @ 35 Micron



Part Number: P553315
Description: LUBE SPIN-ON FULL FLOW
Primary App: FORD 785F-6714-AA3A
Dimensions: Outer Diameter: 3.82" (97 mm)
Thread Size: M22 x 1.5
Length: 5.51" (140 mm)
Gasket OD: 2.82" (72 mm)
Gasket ID: 2.45" (62 mm)



















Part Number: P553215
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: CATERPILLAR ENGINES Replaces P550659, Use P553215 for Twist and Drain Integral Threaded Sensor Port
Dimensions: Outer Diameter: 3.66" (93 mm)
Thread Size: 1-14
Overall Length: 7.61" (193 mm)
Gasket OD: 3.39" (86 mm)
Gasket ID: 3.05" (77 mm)





































Part Number: P553335
Description: LUBE CARTRIDGE FULL FLOW
Primary App: IHC, GALLON, HOUGH, TOWMOTOR
Dimensions: Outer Diameter: 4.06" (103 mm)
Inner Diameter: 1.62" (41 mm)
Length: 5.50" (140 mm)
Efficiency 99% @ 40 Micron



















Part Number: P553375
Description: FUEL/WATER SEPARATOR SPIN-ON
Primary App: FORD E8TZ-9N184-A
Dimensions: Outer Diameter: 4.39" (112 mm)
Thread Size: 1-14
Length: 4.02" (102 mm)
Efficiency 50% @ 10 Micron
















	<p>Part Number: P553404 Description: LUBE SPIN-ON BYPASS Primary App: CARRIER TRANSICOLD 30.00304.00 Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 5/8-18 Length: 7.91" (201 mm) Gasket OD: 2.82" (72 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 45 Micron</p>		<p>Part Number: P553771 Description: LUBE SPIN-ON FULL FLOW Primary App: DEUTZ 1174421, CASE IH Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 7.87" (200 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Relief Valve Setting: 35 PSI (2.41 Bar) Anti Drain Valve: Yes Y/N Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P553411 Description: LUBE SPIN-ON FULL FLOW Primary App: ALLIS CHALMERS, WORTHINGTON, FORD Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 3/4-16 Length: 5.54" (141 mm) Gasket OD: 3.50" (89 mm) Gasket ID: 2.79" (71 mm) Relief Valve Setting: 18-20 PSI (1.30-1.40 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>		<p>Part Number: P553854 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CARRIER, IHC, THERMOKING 11.3854 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-14 Length: 6.85" (174 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P553500 Description: FUEL SPIN-ON SECONDARY Primary App: KOMATSU 6003193550 Dimensions: Outer Diameter: 4.65" (118 mm) Thread Size: 1 5/8-12 Length: 11.00" (279 mm)</p>		<p>Part Number: P553855 Description: FUEL SPIN-ON SECONDARY Primary App: IHC, THERMOKING 11.3855 Dimensions: Outer Diameter: 3.78" (96 mm) Thread Size: 7/8-14 Length: 8.70" (221 mm) Gasket OD: 2.84" (72 mm) Gasket ID: 2.46" (62 mm) Efficiency 99% @ 20 Micron</p>
	<p>Part Number: P553548 Description: LUBE SPIN-ON COMBINATION Primary App: CASE IH J919562 Dimensions: Outer Diameter: 4.65" (118 mm) Thread Size: 2 1/4-12 Length: 8.94" (227 mm) Gasket OD: 4.68" (119 mm) Gasket ID: 4.00" (102 mm) Efficiency 99% @ 15 Micron</p>		<p>Part Number: P553871 Description: LUBE SPIN-ON FULL FLOW Primary App: THERMOKING 11.3871 Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: 1-12 Length: 6.61" (168 mm) Gasket OD: 2.82" (72 mm) Gasket ID: 2.42" (61 mm) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P553634 Description: LUBE SPIN-ON FULL FLOW Primary App: MICH FP, JOHN DEERE AR43634 Dimensions: Outer Diameter: 5.00" (127 mm) Thread Size: 1 1/2-16 Length: 6.85" (174 mm) Gasket OD: 5.05" (128 mm) Gasket ID: 4.71" (120 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P553925 Description: LUBE CARTRIDGE FULL FLOW Primary App: MERCEDES BENZ 0011843925 Dimensions: Outer Diameter: 4.84" (123 mm) Inner Diameter: 2.25" (57 mm) Length: 8.86" (225 mm) Efficiency 99% @ 36 Micron</p>
	<p>Part Number: P553693 Description: FUEL SPIN-ON SECONDARY Primary App: CARRIER, THERMOKING 11.3693 Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 7/8-14 Length: 5.22" (133 mm) Gasket OD: 2.82" (72 mm) Gasket ID: 2.42" (61 mm)</p>		<p>Part Number: P554004 Description: LUBE SPIN-ON FULL FLOW Primary App: CATERPILLAR 1R-0658, 2P-4004 Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: 1 1/8-16 Length: 10.31" (262 mm) Gasket OD: 3.89" (99 mm) Gasket ID: 3.55" (90 mm) Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P553712 Description: LUBE SPIN-ON FULL FLOW Primary App: CARRIER, ATLS COPCO, THERMOKING 11.3712 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 6.85" (174 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P554005 Description: LUBE SPIN-ON FULL FLOW Primary App: CAT 1R-0716, 2P-4005, STGR, SULLAIR Dimensions: Outer Diameter: 5.33" (135 mm) Thread Size: 1 1/2-16 Length: 12.13" (308 mm) Gasket OD: 4.31" (109 mm) Gasket ID: 3.92" (100 mm) Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P553746 Description: LUBE SPIN-ON BYPASS Primary App: THERMO KING 11.3746 Dimensions: Outer Diameter: 4.28" (109 mm) Thread Size: 3/4-20 Length: 7.89" (200 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.45" (62 mm) Efficiency 99% @ 12 Micron</p>		<p>Part Number: P554019 Description: COOLANT SPIN-ON Primary App: VOLVO 3945411 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: M16 x 1.5 Length: 5.35" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm)</p>







	<p>Part Number: P554056 Description: HYDRAULIC CARTRIDGE Primary App: CAT ENGINES Dimensions: Outer Diameter: 5.07" (129 mm) Inner Diameter: 2.28" (58 mm) Length: 10.29" (261 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 9 Micron</p>		<p>Part Number: P554206 Description: LUBE SPIN-ON FULL FLOW Primary App: IHC 684206C1 Dimensions: Outer Diameter: 5.35" (136 mm) Thread Size: 1 1/2-16 Length: 9.68" (246 mm) Gasket OD: 4.29" (109 mm) Gasket ID: 3.89" (99 mm) Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P554071 Description: COOLANT SPIN-ON Primary App: CUMMINS 3315116 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 11/16-16 Length: 4.21" (107 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P554347 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: BULK FUEL W/O DRAIN Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 6.85" (174 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P554072 Description: COOLANT SPIN-ON Primary App: CUMMINS 3318201 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 11/16-16 Length: 4.21" (107 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P554403 Description: LUBE SPIN-ON FULL FLOW Primary App: PERKINS 2654403, MF Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 3/4-16 Length: 5.35" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.41" (61 mm) Relief Valve Setting: 7-10 PSI (0.50-0.70 Bar) Stand Pipe: Yes Y/N Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P554073 Description: COOLANT SPIN-ON Primary App: CUMMINS 3315115 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 11/16-16 Length: 5.35" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P554407 Description: LUBE SPIN-ON FULL FLOW Primary App: PERKINS 2654407 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 3/4-16 Length: 6.86" (174 mm) Gasket OD: 2.82" (72 mm) Gasket ID: 2.48" (63 mm) Relief Valve Setting: 8-11 PSI (0.60-0.80 Bar) Stand Pipe: Yes Y/N Anti Drain Valve: Yes Y/N Efficiency 99% @ 48 Micron</p>
	<p>Part Number: P554074 Description: COOLANT SPIN-ON Primary App: CUMMINS 3316053 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 11/16-16 Length: 5.35" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P554408 Description: LUBE SPIN-ON FULL FLOW Primary App: PERKINS 2654408, MF Dimensions: Outer Diameter: 3.00" (76 mm) Thread Size: 3/4-16 Length: 5.53" (140 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Relief Valve Setting: 8-11 PSI (0.60-0.80 Bar) Stand Pipe: Yes Y/N Anti Drain Valve: Yes Y/N Efficiency 99% @ 48 Micron</p>
	<p>Part Number: P554075 Description: COOLANT SPIN-ON Primary App: CUMMINS 3318318 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 11/16-16 Length: 5.35" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 50% @ 25 Micron</p>		<p>Part Number: P554409 Description: LUBE SPIN-ON FULL FLOW Primary App: PERKINS 2654409, MF Dimensions: Outer Diameter: 3.00" (76 mm) Thread Size: 3/4-16 Length: 5.53" (140 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Relief Valve Setting: 8-11 PSI (0.60-0.80 Bar) Stand Pipe: Yes Y/N Anti Drain Valve: Yes Y/N Efficiency 99% @ 48 Micron</p>
	<p>Part Number: P554105 Description: LUBE SPIN-ON FULL FLOW Primary App: 4-5/8" DIA. VERSION OF CATERPILLAR #2P4005 Dimensions: Outer Diameter: 4.67" (119 mm) Thread Size: 1 1/2-16 Length: 11.75" (298 mm) Gasket OD: 4.32" (110 mm) Gasket ID: 3.85" (98 mm) Efficiency 99% @ 40 Micron</p>		<p>Part Number: P554422 Description: COOLANT SPIN-ON Primary App: MACK 25MF422 Dimensions: Outer Diameter: 4.25" (109 mm) Thread Size: 1-16 Length: 5.78" (147 mm) Gasket OD: 3.89" (99 mm) Gasket ID: 3.55" (90 mm)</p>
	<p>Part Number: P554136 Description: LUBE CARTRIDGE FULL FLOW Primary App: CAT 1W-4136 Dimensions: Outer Diameter: 7.42" (188 mm) Inner Diameter: 3.43" (87 mm) Length: 13.38" (340 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P554470 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: MACK 483-GB-470M Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: M22 x 1.5 Length: 7.95" (202 mm) Gasket OD: 3.88" (99 mm) Gasket ID: 3.54" (90 mm) Efficiency 99% @ 25 Micron</p>

	<p>Part Number: P554471 Description: FUEL SPIN-ON SECONDARY Primary App: MACK 483GB471M Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: M30 x 1.5 Length: 10.30" (262 mm) Gasket OD: 3.88" (99 mm) Gasket ID: 3.54" (90 mm) Efficiency 99% @ 9 Micron</p>		<p>Part Number: P554860 Description: COOLANT SPIN-ON Primary App: MACK 25-MF-314A Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 3/4-20 Length: 5.35" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm)</p>
	<p>Part Number: P554472 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: MACK 483GB472M Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: M22 x 1.5 Length: 10.40" (264 mm) Efficiency 99% @ 25 Micron</p>		<p>Part Number: P554925 Description: LUBE CARTRIDGE FULL FLOW M.A.N. 81.05504.0025 Dimensions: Outer Diameter: 4.53" (115 mm) Inner Diameter: 2.24" (57 mm) Length: 7.68" (195 mm)</p>
	<p>Part Number: P554476 Description: FUEL SPIN-ON SECONDARY Primary App: MACK 483GB476M Dimensions: Outer Diameter: 4.23" (107 mm) Thread Size: M30 x 1.5 Length: 7.95" (202 mm) Gasket OD: 3.90" (99 mm) Gasket ID: 3.54" (90 mm)</p>		<p>Part Number: P555001 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: RACOR B32001, INCLUDES BOWL P553201 Std T&D, P553211 T&D WIF Sensor, P505961 WITHOUT BOWL Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 1-14 Length: 9.94" (252 mm) Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P554477 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: MACK ASET Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: M30 x 1.5 Length: 8.34" (212 mm) Gasket OD: 3.98" (101 mm) Gasket ID: 3.58" (91 mm) Efficiency 99% @ 5 Micron</p>		<p>Part Number: P555002 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: RACOR B32002, INCLUDES BOWL Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 1-12 Length: 9.94" (252 mm) Efficiency 50% @ 30 Micron</p>
	<p>Part Number: P554620 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: DEUTZ 1174422 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: M16 x 1.5 Length: 5.47" (139 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 9 Micron</p>		<p>Part Number: P555003 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: RACOR B32003, INCLUDES BOWL Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 1-14 Length: 8.06" (205 mm) Efficiency 50% @ 2 Micron</p>
	<p>Part Number: P554636 Description: HYDRAULIC CARTRIDGE Primary App: INT'L 390560-R91, 527507-R91, AND -R92 Dimensions: Outer Diameter: 5.00" (127 mm) Inner Diameter: 2.81" (71 mm) Length: 6.12" (155 mm)</p>		<p>Part Number: P555006 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: RACOR B32006, INCLUDES BOWL Dimensions: Outer Diameter: 4.38" (111 mm) Thread Size: 1-14 Length: 11.38" (289 mm) Efficiency 50% @ 2 Micron</p>
	<p>Part Number: P554685 Description: COOLANT SPIN-ON Primary App: CUMMINS without chemicals Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 11/16-16 Length: 5.35" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P555010 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: RACOR S3201 P553201 Std T&D, P553211 T&D WIF Sensor Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 1-14 Length: 7.40" (188 mm) Efficiency 99% @ 30 Micron</p>
	<p>Part Number: P554770 Description: LUBE SPIN-ON FULL FLOW Primary App: JOHN DEERE AM34770 Dimensions: Outer Diameter: 2.99" (76 mm) Thread Size: 3/4-16 Length: 4.72" (120 mm) Gasket OD: 2.75" (70 mm) Gasket ID: 2.37" (60 mm) Relief Valve Setting: 26-30 PSI (1.80-2.10 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>		<p>Part Number: P555020 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: RACOR S3202 P553202 Std T&D, P553212T&D WIF Sensor, Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 1-12 Length: 7.40" (188 mm) Efficiency 50% @ 30 Micron</p>
			<p>Part Number: P555060 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: RACOR S3206 Dimensions: Outer Diameter: 4.38" (111 mm) Thread Size: 1-14 Length: 8.56" (217 mm) Efficiency 50% @ 2 Micron</p>

	<p>Part Number: P555088 Description: LUBE CARTRIDGE FULL FLOW Primary App: JOHN DEERE AT15088T, PURO R14 Dimensions: Outer Diameter: 3.34" (85 mm) Inner Diameter: 1.62" (41 mm) Length: 6.50" (165 mm) Efficiency 99% @ 38 Micron</p>		<p>Part Number: P555616 Description: LUBE SPIN-ON FULL FLOW Primary App: IHC 675616C91, CASE Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 6.85" (174 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Stand Pipe: Yes Y/N Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P555095 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: FORD #E67HZ9365A (BRAZILIAN CAB FORWARD) Dimensions: Outer Diameter: 3.01" (76 mm) Thread Size: M16 x 1.5 Length: 3.46" (88 mm) Gasket OD: 2.75" (70 mm) Gasket ID: 2.37" (60 mm) Efficiency 99% @ 9 Micron</p>		<p>Part Number: P555627 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: IHC 625627C1 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-14 Length: 7.87" (200 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 9 Micron</p>
	<p>Part Number: P555150 Description: HYDRAULIC CARTRIDGE Primary App: AC, CLARK, JD, FORD, ALLIS 70679513-2 Dimensions: Outer Diameter: 4.50" (114 mm) Inner Diameter: 2.22" (56 mm) Length: 7.25" (184 mm) Efficiency 50% @ 10 Micron Efficiency 99% @ 25 Micron</p>		<p>Part Number: P555680 Description: LUBE SPIN-ON FULL FLOW Primary App: CAT 9N-5680 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 5.35" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Relief Valve Setting: 18-23 PSI (1.30-1.60 Bar) Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P555400 Description: LUBE CARTRIDGE FULL FLOW Primary App: LISTER, PETTER Dimensions: Outer Diameter: 2.00" (51 mm) Inner Diameter: 0.81" (21 mm) Length: 2.12" (54 mm)</p>		<p>Part Number: P555823 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CAT 4N-5823 Dimensions: Outer Diameter: 4.31" (109 mm) Thread Size: 1-14 Length: 10.60" (269 mm) Gasket OD: 2.82" (72 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 9 Micron</p>
	<p>Part Number: P555461 Description: HYDRAULIC CARTRIDGE Primary App: CAT 9J5461 Dimensions: Outer Diameter: 5.07" (129 mm) Inner Diameter: 3.58" (91 mm) Length: 11.00" (279 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P555935 Description: HYDRAULIC CARTRIDGE Primary App: CAT 8B-5935 Dimensions: Outer Diameter: 3.66" (93 mm) Inner Diameter: 1.60" (36 mm) Length: 5.94" (151 mm)</p>
	<p>Part Number: P555522 Description: LUBE SPIN-ON FULL FLOW Primary App: THERMOKING 11.5522, J.DEERE, YANMAR Dimensions: Outer Diameter: 3.12" (79 mm) Thread Size: M20 x 1.5 Length: 3.87" (98 mm) Gasket OD: 2.45" (62 mm) Gasket ID: 2.15" (55 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 50 Micron</p>		<p>Part Number: P556001 Description: HYDRAULIC CARTRIDGE Primary App: IHC, EATON, RACINE Dimensions: Outer Diameter: 4.50" (114 mm) Inner Diameter: 0.53" (13 mm) Length: 9.06" (230 mm) Efficiency 50% @ 16 Micron Efficiency 99% @ 47 Micron</p>
	<p>Part Number: P555570 Description: LUBE SPIN-ON FULL FLOW Primary App: CAT 8N9586, 9N5570 Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 1 1/8-16 Length: 5.22" (133 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 40 Micron</p>		<p>Part Number: P556004 Description: HYDRAULIC CARTRIDGE Primary App: IHC, TOWMOTOR, CHRYSLER, FORD, REXNORD 4931343 Dimensions: Outer Diameter: 4.50" (114 mm) Inner Diameter: 0.53" (13 mm) Length: 5.00" (127 mm) Efficiency 50% @ 20 Micron Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P555603 Description: HYDRAULIC CARTRIDGE Primary App: JOHN DEERE AR75603, AR75601 Dimensions: Outer Diameter: 4.61" (118 mm) Inner Diameter: 2.20" (56 mm) Length: 5.29" (134 mm) Efficiency 50% @ 20 Micron</p>		<p>Part Number: P556005 Description: HYDRAULIC SPIN-ON Primary App: CESSNA 62200-A, VCKRS 350577, 573082, 573083, Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 1 1/8-16 Length: 5.37" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 50% @ 10 Micron</p>

	<p>Part Number: P556007 Description: LUBE SPIN-ON FULL FLOW Primary App: CAT 9N6007 Dimensions: Outer Diameter: 4.28" (109 mm) Thread Size: 1 1/8-16 Length: 5.78" (147 mm) Gasket OD: 3.94" (100 mm) Gasket ID: 3.55" (90 mm) Efficiency 99% @ 40 Micron</p>		<p>Part Number: P556915 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: DET. DIESEL 23517471, AC T915D Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 1-12 Length: 7.97" (202 mm) Gasket OD: 3.38" (86 mm) Gasket ID: 3.04" (77 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P556064 Description: HYDRAULIC CARTRIDGE Primary App: CAT 4J-6064, 4J-0806 Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 3.35" (85 mm) Length: 9.02" (229 mm) Efficiency 50% @ 20 Micron Efficiency 99% @ 35 Micron</p>		<p>Part Number: P556916 Description: FUEL SPIN-ON SECONDARY Primary App: DET. DIESEL 23518530, AC TP916D Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 13/16-12 Length: 6.85" (174 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.05" (77 mm) Efficiency 99% @ 9 Micron</p>
	<p>Part Number: P556219 Description: HYDRAULIC CARTRIDGE Primary App: IHC 666219-C1 Dimensions: Outer Diameter: 6.50" (165 mm) Inner Diameter: 5.50" (140 mm) Length: 12.16" (309 mm)</p>		<p>Part Number: P556917 Description: FUEL SPIN-ON SECONDARY Primary App: DETROIT DIESEL 23533726 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 13/16-12 Length: 6.85" (174 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.05" (77 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P556245 Description: FUEL CARTRIDGE Primary App: CASE, JOHN DEERE, IHC, MF, ROOSAMASTER Dimensions: Outer Diameter: 3.41" (87 mm) Inner Diameter: 0.74" (19 mm) Length: 2.80" (71 mm) Efficiency 99% @ 14 Micron</p>		<p>Part Number: P557111 Description: FUEL CARTRIDGE Primary App: CAV FUEL SYSTEM APPLICATIONS Dimensions: Outer Diameter: 3.50" (89 mm) Inner Diameter: 0.75" (19 mm) Length: 2.80" (71 mm)</p>
	<p>Part Number: P556285 Description: FUEL BOX PRIMARY Primary App: THERMOKING 116285 Dimensions: Width: 2.83" (72 mm) Height: 2.46" (62 mm) Length: 4.62" (117 mm) Efficiency 99% @ 10 Micron</p>		<p>Part Number: P557207 Description: LUBE SPIN-ON FULL FLOW Primary App: IHC 427207C2 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 6.85" (174 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Relief Valve Setting: 7-10 PSI (0.50 -0.70 Bar) Efficiency 50% @ 20 Micron</p>
	<p>Part Number: P556286 Description: FUEL/WATER SEPARATOR BOX Primary App: THERMOKING 116286 Dimensions: Width: 2.83" (72 mm) Height: 2.46" (62 mm) Length: 4.62" (117 mm)</p>		<p>Part Number: P557222 Description: HYDRAULIC SPIN-ON Primary App: TORO 69-1720 Dimensions: Outer Diameter: 4.78" (121 mm) Thread Size: 1 1/2-16 Length: 10.93" (278 mm)</p>
	<p>Part Number: P556287 Description: FUEL CARTRIDGE Primary App: C.A.V. 7111/792 Dimensions: Outer Diameter: 3.46" (88 mm) Inner Diameter: 1.53" (39 mm) Length: 4.45" (113 mm)</p>		<p>Part Number: P557264 Description: FUEL/WATER SEPARATOR BOX Primary App: THERMOKING 117264 Dimensions: Width: 2.83" (72 mm) Height: 2.46" (62 mm) Length: 4.62" (117 mm) Efficiency 99% @ 30 Micron</p>
	<p>Part Number: P556700 Description: HYDRAULIC CARTRIDGE Primary App: CAT 7J-0670, KOMATSU Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 3.94" (100 mm) Length: 9.00" (229 mm) Efficiency 50% @ 15 Micron Efficiency 99% @ 35 Micron</p>		<p>Part Number: P557373 Description: HYDRAULIC CARTRIDGE Primary App: GALION B67373, B67373A Dimensions: Outer Diameter: 5.00" (127 mm) Inner Diameter: 2.50" (64 mm) Length: 11.87" (301 mm)</p>
	<p>Part Number: P556745 Description: FUEL BOX PRIMARY Primary App: JOHN DEERE AR86745, STANADYNE 26667 Dimensions: Width: 3.71" (94 mm) Height: 3.28" (83 mm) Length: 5.04" (128 mm) Efficiency 99% @ 22 Micron</p>		

	<p>Part Number: P557380 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 175-60-27380 Dimensions: Outer Diameter: 5.12" (130 mm) Inner Diameter: 3.40" (86 mm) Length: 11.50" (292 mm) Efficiency 50% @ 14 Micron Efficiency 99% @ 30 Micron</p>		<p>Part Number: P558010 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: DETROIT DIESEL 23512317 Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 1-12 Length: 7.36" (187 mm) Gasket OD: 3.55" (90 mm) Gasket ID: 3.18" (81 mm) Efficiency 99% @ 20 Micron</p>
	<p>Part Number: P557382 Description: LUBE SPIN-ON COMBINATION Primary App: THERMO KING 117382 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: M26 x 1.5 Length: 6.92" (176 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 25 Micron</p>		<p>Part Number: P558250 Description: LUBE SPIN-ON FULL FLOW Primary App: IHC 528250R91, Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 1-12 Length: 6.78" (172 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Relief Valve Setting: 11-17 PSI (0.80-1.00 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P557440 Description: FUEL SPIN ON Primary App: CAT 1R-0711, 1P-2299, 6L-7440, KTSU 600-311-8290 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-14 Length: 6.85" (174 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 9 Micron</p>		<p>Part Number: P558329 Description: LUBE SPIN-ON FULL FLOW Primary App: JOHN DEERE AR98329 Dimensions: Outer Diameter: 5.06" (129 mm) Thread Size: 1 1/2-12 Length: 6.72" (171 mm) Efficiency 50% @ 25 Micron</p>
	<p>Part Number: P557500 Description: LUBE CARTRIDGE FULL FLOW Primary App: CAT 7N-7500 Dimensions: Outer Diameter: 7.42" (188 mm) Inner Diameter: 2.63" (67 mm) Length: 10.00" (254 mm) Efficiency 99% @ 40 Micron</p>		<p>Part Number: P558425 Description: LUBE CARTRIDGE FULL FLOW Primary App: MERCEDES 4011840025 Dimensions: Outer Diameter: 4.70" (119 mm) Inner Diameter: 2.16" (55 mm) Length: 7.60" (193 mm)</p>
	<p>Part Number: P557780 Description: LUBE SPIN-ON FULL FLOW Primary App: ISUZU, NISSAN Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 3/4-16 Length: 5.35" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Relief Valve Setting: 18-23 PSI (1.30-1.60 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>		<p>Part Number: P558462 Description: LUBE CARTRIDGE FULL FLOW Primary App: IHC 268462R91, CUMMINS 104428 Dimensions: Outer Diameter: 4.47" (114 mm) Inner Diameter: 1.75" (44 mm) Length: 9.06" (230 mm)</p>
	<p>Part Number: P557826 Description: HYDRAULIC CARTRIDGE Primary App: HOUGH, IHC, MICHIGAN Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 2.62" (67 mm) Length: 17.94" (456 mm) Efficiency 50% @ 5 Micron Efficiency 99% @ 17 Micron</p>		<p>Part Number: P558467 Description: HYDRAULIC CARTRIDGE Primary App: VICKERS 228467, 270562, 922788, 923115 IHC, NEW HOL Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 0.47" (12 mm) Length: 4.37" (111 mm) Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P557841 Description: HYDRAULIC CARTRIDGE Primary App: CASE, CAT, FORD, IHC 267841C91, GARRISON 32446 Dimensions: Outer Diameter: 2.52" (64 mm) Inner Diameter: 1.06" (27 mm) Length: 3.70" (94 mm) Efficiency 50% @ 14 Micron Efficiency 99% @ 30 Micron</p>		<p>Part Number: P558600 Description: FUEL CARTRIDGE Primary App: KOMATSU 6610-79-8600 Dimensions: Outer Diameter: 5.00" (127 mm) Inner Diameter: 0.97" (25 mm) Length: 9.75" (248 mm)</p>
	<p>Part Number: P558000 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CUMMINS 3308638 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-14 Length: 7.40" (188 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 20 Micron</p>		<p>Part Number: P558615 Description: LUBE SPIN-ON FULL FLOW Primary App: CUMMINS 3932217, 3908615 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-16 Length: 6.85" (174 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 40 Micron</p>

	<p>Part Number: P558616 Description: LUBE SPIN-ON FULL FLOW Primary App: CUMMINS 3903224, 3908616 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-16 Length: 5.35" (136 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 40 Micron</p>	<p>Part Number: P559127 Description: LUBE SPIN-ON FULL FLOW Primary App: FORD E3TZ6731A, IHC 6.9L 1804442C1 Dimensions: Outer Diameter: 4.23" (107 mm) Thread Size: 1 1/2-16 Overall Length: 5.79" (147 mm) Gasket OD: 3.90" (99 mm) Gasket ID: 3.56" (90 mm) Efficiency 99% @ 40 Micron (N/A)</p>
	<p>Part Number: P558712 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CASE IH A58712 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 13/16-18 Length: 5.67" (144 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 40 Micron</p>	<p>Part Number: P559128 Description: LUBE SPIN-ON FULL FLOW Primary App: CAT 9N6007 Dimensions: Outer Diameter: 4.23" (107 mm) Thread Size: 1 1/8-16 Overall Length: 5.79" (147 mm) Gasket OD: 3.90" (99 mm) Gasket ID: 3.56" (90 mm) Efficiency 99% @ 40 Micron (N/A)</p>
	<p>Part Number: P558717 Description: LUBE SPIN-ON BYPASS Primary App: Case A36136, Hyster 38714, MF 835652M91 Dimensions: Outer Diameter: 3.54" (90 mm) Thread Size: 2 3/4-4 Length: 4.86" (123 mm)</p>	<p>Part Number: P559129 Description: LUBE SPIN-ON FULL FLOW Primary App: ROLLS ROYCE CV2473 Dimensions: Outer Diameter: 4.23" (107 mm) Thread Size: M30 X 1.5 Overall Length: 6.61" (168 mm) Gasket OD: 3.90" (99 mm) Gasket ID: 3.56" (90 mm) Efficiency 99% @ 30 Micron</p>
	<p>Part Number: P558792 Description: FUEL CARTRIDGE Primary App: CAT 4H-8792, 9H-4729, 6H-5932 Dimensions: Outer Diameter: 3.37" (86 mm) Inner Diameter: 1.12" (28 mm) Length: 6.50" (165 mm) Efficiency 99% @ 10 Micron</p>	<p>Part Number: P559130 Description: LUBE SPIN-ON FULL FLOW Primary App: CASE IH A62423 Dimensions: Outer Diameter: 4.23" (107 mm) Thread Size: 7/8-16 UN-2B Overall Length: 7.95" (202 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.44" (62 mm) Efficiency 99% @ 40 Micron (N/A)</p>
	<p>Part Number: P558877 Description: HYDRAULIC CARTRIDGE Primary App: CAT 5J8877 Dimensions: Outer Diameter: 5.12" (130 mm) Inner Diameter: 3.37" (86 mm) Length: 6.00" (152 mm)</p>	<p>Part Number: P559418 Description: LUBE SPIN-ON FULL FLOW Primary App: DEUTZ 1174418 Dimensions: Outer Diameter: 3.74" (95 mm) Thread Size: 1-12 Length: 5.47" (139 mm) Gasket OD: 2.81" (71 mm) Gasket ID: 2.42" (61 mm) Relief Valve Setting: 36 PSI (2.48 Bar) Anti Drain Valve: Yes Y/N Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P559000 Description: LUBE SPIN-ON COMBINATION Primary App: FLEETGUARD LF9000, LF9001 CUMMINS SIGNATURE 600 Dimensions: Outer Diameter: 4.66" (118 mm) Thread Size: M95 x 2.5 Length: 11.70" (297 mm) Gasket OD: 4.68" (119 mm) Gasket ID: 4.00" (102 mm) Efficiency 99% @ 16 Micron</p>	<p>Part Number: P559434 Description: HYDRAULIC CARTRIDGE Primary App: FIAT ALLIS 70669434, A.CHALMERS 676022 Dimensions: Outer Diameter: 4.39" (112 mm) Inner Diameter: 1.75" (44 mm) Length: 12.75" (324 mm)</p>
	<p>Part Number: P559100 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CAT 9L-9100, 9L-8794 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 15/16-16 Length: 5.55" (141 mm) Gasket OD: 2.75" (70 mm) Gasket ID: 2.42" (61 mm) Efficiency 99% @ 23 Micron</p>	<p>Part Number: P559624 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: DAF 247138 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: M16 x 1.5 Length: 8.27" (210 mm) Gasket OD: 2.80" (71 mm) Gasket ID: 2.44" (62 mm) Efficiency 50% @ 5 Micron</p>
<p>Part Number: P559125 Description: FUEL SPIN ON Primary App: CARRIER 300109000 Dimensions: Outer Diameter: 4.25" (108 mm) Thread Size: 1-14 Overall Length: 5.79" (147 mm) Gasket OD: 3.90" (99 mm) Gasket ID: 3.56" (90 mm) Efficiency 99% @ 11 Micron</p>	<p>Part Number: P559740 Description: HYDRAULIC CARTRIDGE Primary App: CAT 9M-9740 Dimensions: Outer Diameter: 4.00" (102 mm) Inner Diameter: 2.27" (58 mm) Length: 9.25" (235 mm) Efficiency 50% @ 20 Micron</p>	

	<p>Part Number: P559803 Description: FUEL BOX PRIMARY Primary App: CAT 8N-9850, STANADYNE 21167 Dimensions: Width: 3.71" (94 mm) Height: 3.34" (85 mm) Length: 4.95" (126 mm) Efficiency 99% @ 22 Micron</p>		<p>Part Number: P560404 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC6300FKN13H, HC6300FDN13H Dimensions: Outer Diameter: 3.07" (78 mm) Inner Diameter: 1.63" (41 mm) Length: 12.87" (327 mm) Efficiency 99% @ 6 Micron</p>
	<p>Part Number: P559850 Description: FUEL CARTRIDGE Primary App: CATERPILLAR 8N9850, 1R0718 Dimensions: Outer Diameter: 3.93" (100 mm) Inner Diameter: 1.62" (41 mm) Length: 9.25" (235 mm) Efficiency 99% @ 22 Micron</p>		<p>Part Number: P560405 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC6500FKS16H, HC6500FDS16H Dimensions: Outer Diameter: 3.80" (97 mm) Inner Diameter: 2.20" (56 mm) Length: 16.80" (427 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>
	<p>Part Number: P560141 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0280D010BNHC Dimensions: Outer Diameter: 2.75" (70 mm) Inner Diameter: 1.35" (34 mm) Length: 13.98" (355 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P560406 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC6500FDN26H, HC6500FKN26H Dimensions: Outer Diameter: 3.80" (97 mm) Inner Diameter: 2.20" (56 mm) Length: 25.71" (653 mm) Efficiency 99% @ 6 Micron</p>
	<p>Part Number: P560398 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER KSX7V, KSX7, KZX10 Dimensions: Outer Diameter: 3.19" (81 mm) Inner Diameter: 1.63" (41 mm) Length: 9.19" (233 mm)</p>		<p>Part Number: P560438 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 2600R005BNHC Dimensions: Outer Diameter: 5.65" (144 mm) Inner Diameter: 3.80" (97 mm) Length: 36.26" (921 mm) ID Width: 3.76" (96 mm) Relief Valve Setting: 44 PSI (3.03 Bar) Efficiency 99% @ 6 Micron</p>
	<p>Part Number: P560399 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER KSX3V, KXS3, KZX3 Dimensions: Outer Diameter: 3.19" (81 mm) Inner Diameter: 1.63" (41 mm) Length: 9.19" (233 mm)</p>		<p>Part Number: P560514 Description: HYDRAULIC SPIN-ON Primary App: GARDNER DENVER 2116110 Dimensions: Outer Diameter: 4.76" (121 mm) Thread Size: 1 1/2-16 Length: 10.66" (271 mm) Efficiency 50% @ 10 Micron</p>
	<p>Part Number: P560400 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER BBS7, BBZ10 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 3.31" (84 mm) Length: 18.31" (465 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P560524 Description: HYDRAULIC CARTRIDGE Primary App: HAK05 FILTER ASSY'S Dimensions: Outer Diameter: 4.39" (112 mm) Inner Diameter: 2.45" (62 mm) Length: 5.00" (127 mm) Efficiency 50% @ 7 Micron Efficiency 99% @ 22 Micron</p>
	<p>Part Number: P560401 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER 18LS7, 18LZ10 Dimensions: Outer Diameter: 3.90" (99 mm) Inner Diameter: 2.26" (57 mm) Length: 18.50" (470 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P560525 Description: HYDRAULIC CARTRIDGE Primary App: HAK05 FILTER ASSY'S Dimensions: Outer Diameter: 4.39" (112 mm) Inner Diameter: 2.45" (62 mm) Length: 5.00" (127 mm)</p>
	<p>Part Number: P560402 Description: HYDRAULIC CARTRIDGE Primary App: BLOUNT PRENTICE # 31001609 Dimensions: Outer Diameter: 3.90" (99 mm) Inner Diameter: 1.61" (41 mm) Length: 18.31" (465 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>		<p>Part Number: P560526 Description: HYDRAULIC CARTRIDGE Primary App: HAK05 FILTER ASSY'S Dimensions: Outer Diameter: 4.39" (112 mm) Inner Diameter: 2.44" (62 mm) Length: 5.00" (127 mm) Efficiency 50% @ 20 Micron Efficiency 99% @ 40 Micron</p>
	<p>Part Number: P560403 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC6300FDN16H, HC6300FKN16H Dimensions: Outer Diameter: 3.07" (78 mm) Inner Diameter: 1.63" (41 mm) Length: 18.81" (478 mm) Efficiency 99% @ 6 Micron</p>		<p>Part Number: P560527 Description: HYDRAULIC CARTRIDGE Primary App: HAK05 ASSY'S Dimensions: Outer Diameter: 4.39" (112 mm) Inner Diameter: 2.45" (62 mm) Length: 8.00" (203 mm) Efficiency 50% @ 20 Micron Efficiency 99% @ 40 Micron</p>




	<p>Part Number: P560528 Description: HYDRAULIC CARTRIDGE Primary App: HAK05 ASSY'S Dimensions: Outer Diameter: 4.39" (112 mm) Inner Diameter: 2.45" (62 mm) Length: 13.00" (330 mm) Efficiency 50% @ 20 Micron Efficiency 99% @ 40 Micron</p>		<p>Part Number: P560707 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 170L205A, 170Z205A, 170Z222A Dimensions: Outer Diameter: 2.18" (55 mm) Inner Diameter: 0.77" (20 mm) Length: 4.82" (123 mm)</p>
	<p>Part Number: P560584 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: HMK04/HMK24 ASSY'S, WATER REMOVAL ELEMENT Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 9.44" (240 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm)</p>		<p>Part Number: P560708 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 170L210A, 170Z210A, 170Z223A Dimensions: Outer Diameter: 2.18" (55 mm) Inner Diameter: 0.77" (20 mm) Length: 4.82" (123 mm) Efficiency 99% @ 26 Micron</p>
	<p>Part Number: P560653 Description: HYDRAULIC SPIN-ON Primary App: CASE IH 1976934C5 Dimensions: Outer Diameter: 4.86" (123 mm) Thread Size: 1 1/2-16 Length: 7.85" (199 mm) Efficiency 50% @ 4 Micron</p>		<p>Part Number: P560709 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG050-GU-B Dimensions: Outer Diameter: 3.29" (84 mm) Inner Diameter: 1.87" (48 mm) Length: 5.59" (142 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P560693 Description: HYDRAULIC SPIN-ON Primary App: SP15/25 Series, 10 micron abs Synteq., 5.35" long Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 5.35" (136 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (62 mm)</p>		<p>Part Number: P560710 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG050-HU-B Dimensions: Outer Diameter: 3.29" (84 mm) Inner Diameter: 1.87" (47 mm) Length: 5.59" (142 mm) Efficiency 99% @ 6 Micron</p>
	<p>Part Number: P560694 Description: HYDRAULIC SPIN-ON Primary App: SP15/25 SERIES, 22 micron abs. Synteq, 5.35" long Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 5.35" (136 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (62 mm)</p>		<p>Part Number: P560711 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG050-JUB Dimensions: Outer Diameter: 3.29" (84 mm) Inner Diameter: 1.87" (48 mm) Length: 5.59" (142 mm) Efficiency 99% @ 25 Micron</p>
	<p>Part Number: P560703 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 2600R003BNHC Dimensions: Outer Diameter: 5.65" (144 mm) Inner Diameter: 3.80" (97 mm) Length: 36.26" (921 mm) Efficiency 99% @ 3 Micron</p>		<p>Part Number: P560712 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG080-GU-B Dimensions: Outer Diameter: 3.29" (84 mm) Inner Diameter: 1.87" (47 mm) Length: 10.04" (255 mm) Efficiency 99% @ 3 Micron</p>
	<p>Part Number: P560704 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 2600R010BNHC Dimensions: Outer Diameter: 5.65" (144 mm) Inner Diameter: 3.80" (97 mm) Length: 36.26" (921 mm) Efficiency 99% @ 10 Micron</p>		<p>Part Number: P560713 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG080-GU-B Dimensions: Outer Diameter: 3.29" (84 mm) Inner Diameter: 1.87" (47 mm) Length: 10.04" (255 mm) Efficiency 99% @ 6 Micron</p>
	<p>Part Number: P560705 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 170L105A, 170Z105A, 170Z122A Dimensions: Outer Diameter: 2.18" (55 mm) Inner Diameter: 0.77" (20 mm) Length: 2.62" (67 mm) Efficiency 99% @ 12 Micron</p>		<p>Part Number: P560714 Description: HYDRAULIC CARTRIDGE Primary App: PTI # PG080-HU-B Dimensions: Outer Diameter: 3.29" (84 mm) Inner Diameter: 1.87" (47 mm) Length: 10.04" (255 mm) Efficiency 99% @ 6 Micron</p>
	<p>Part Number: P560706 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON 170L123A, 170Z123A, 170Z110A Dimensions: Outer Diameter: 2.18" (55 mm) Inner Diameter: 0.77" (20 mm) Length: 2.62" (67 mm)</p>		<p>Part Number: P560715 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG080-JUB Dimensions: Outer Diameter: 3.29" (84 mm) Inner Diameter: 1.87" (48 mm) Length: 10.04" (255 mm) Efficiency 99% @ 25 Micron</p>
			<p>Part Number: P560716 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG120-GU-B Dimensions: Outer Diameter: 3.29" (84 mm) Inner Diameter: 1.87" (47 mm) Length: 14.69" (373 mm) Efficiency 99% @ 3 Micron</p>







	<p>Part Number: P560717 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG120-HU-B Dimensions: Outer Diameter: 3.29" (84 mm) Inner Diameter: 1.87" (48 mm) Length: 14.69" (373 mm) Efficiency 99% @ 6 Micron</p>		<p>Part Number: P561183 Description: HYDRAULIC SPIN-ON Primary App: SP50/60 WATER ABSORBING SPIN-ON FILTER Dimensions: Outer Diameter: 5.04" (128 mm) Thread Size: 1 1/2-16 Length: 10.66" (271 mm)</p>
	<p>Part Number: P560718 Description: HYDRAULIC CARTRIDGE Primary App: PTI PG120-JUB Dimensions: Outer Diameter: 3.29" (84 mm) Inner Diameter: 1.87" (48 mm) Length: 14.69" (373 mm) Efficiency 99% @ 25 Micron</p>		<p>Part Number: P561201 Description: HYDRAULIC CARTRIDGE Primary App: EPE 10005G25A000P Dimensions: Inner Diameter: 1.35" (34 mm) Outer Diameter: 2.36" (60 mm) Length: 3.94" (100 mm) Efficiency @ 25 Micron</p>
	<p>Part Number: P560719 Description: HYDRAULIC CARTRIDGE Primary App: MP FILTRI, CU250-A10N Dimensions: Outer Diameter: 3.90" (99 mm) Inner Diameter: 2.03" (52 mm) Length: 8.27" (210 mm) Efficiency 99% @ 25 Micron</p>		<p>Part Number: P561208 Description: HYDRAULIC CARTRIDGE Primary App: EPE 10018H6SLA0009 Dimensions: Inner Diameter: 1.66" (42 mm) Outer Diameter: 3.15" (80 mm) Length: 9.84" (250 mm)</p>
	<p>Part Number: P560720 Description: HYDRAULIC CARTRIDGE Primary App: MP FILTRI, CU630-A25N Dimensions: Outer Diameter: 5.12" (130 mm) Inner Diameter: 2.99" (76 mm) Length: 9.84" (250 mm) Efficiency 99% @ 25 Micron</p>		<p>Part Number: P561229 Description: HYDRAULIC CARTRIDGE Primary App: EPE 1.0270H10SLA000P Dimensions: Inner Diameter: 3.71" (94 mm) Outer Diameter: 6.30" (160 mm) Length: 38.98" (990 mm)</p>
	<p>Part Number: P560725 Description: HYDRAULIC SPIN-ON Primary App: HBK04 ELEMENT, 5" LG., 22 MICRON ABS. SYNTEQ Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 1/4-12 Length: 5.97" (152 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm)</p>		<p>Part Number: P561230 Description: HYDRAULIC CARTRIDGE Primary App: EPE 1.0270H20SLA0009 Dimensions: Inner Diameter: 3.71" (94 mm) Outer Diameter: 6.30" (160 mm) Length: 38.98" (990 mm)</p>
	<p>Part Number: P560837 Description: HYDRAULIC CARTRIDGE Primary App: HEK11 FUEL/WATER SEPARATOR ELEMENT Dimensions: Outer Diameter: 7.44" (189 mm) Inner Diameter: 4.86" (123 mm) Length: 22.00" (559 mm) Efficiency 50% @ 3 Micron Efficiency 99% @ 20 Micron</p>		<p>Part Number: P561243 Description: HYDRAULIC CARTRIDGE Primary App: EPE 1.18H10SLA000 ELEMENT Dimensions: Outer Diameter: 1.73" (44 mm) Inner Diameter: 1.02" (26 mm) Length: 1.97" (50 mm)</p>
	<p>Part Number: P560971 Description: TRANSMISSION FILTER KIT Primary App: ALLISON 29540494 Dimensions: Outer Diameter: 3.21" (82 mm) Length: 5.98" (152 mm) Inner Diameter: 1.57" (40 mm) Efficiency 99% @ 35 Micron</p>		<p>Part Number: P561253 Description: HYDRAULIC CARTRIDGE Primary App: EPE 1.360H20SLA000P ELEMENT Dimensions: Outer Diameter: 4.02" (102 mm) Inner Diameter: 2.48" (63 mm) Length: 9.09" (231 mm)</p>
	<p>Part Number: P560972 Description: TRANSMISSION FILTER KIT Primary App: ALLISON 29540493 Dimensions: Outer Diameter: 3.21" (82 mm) Length: 4.21" (107 mm) Inner Diameter: 1.57" (40 mm) Efficiency 99% @ 35 Micron</p>		<p>Part Number: P561260 Description: HYDRAULIC CARTRIDGE Primary App: EPE 1.361H10SLA000P Dimensions: Outer Diameter: 4.02" (102 mm) Inner Diameter: 2.38" (60 mm) Length: 9.21" (234 mm)</p>
	<p>Part Number: P561013 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: HMK05/25 ELEMENT, HEAVY DUTY, 11.6" LONG, # 3 SYNTHETIC MEDIA Dimensions: Outer Diameter: 4.77" (121 mm) Thread Size: 1 3/4-12 Length: 11.63" (295 mm) Gasket OD: 3.39" (86 mm) Gasket ID: 3.11" (79 mm)</p>		<p>Part Number: P561269 Description: HYDRAULIC CARTRIDGE Primary App: EPE 1.561H1SLA000P ELEMENT Dimensions: Outer Diameter: 5.59" (142 mm) Inner Diameter: 3.70" (94 mm) Length: 10.35" (263 mm)</p>
			<p>Part Number: P561271 Description: HYDRAULIC CARTRIDGE Primary App: EPE 1.56H10SLA0000 Dimensions: Outer Diameter: 2.09" (53 mm) Inner Diameter: 1.30" (33 mm) Length: 3.62" (92 mm)</p>
			<p>Part Number: P561276 Description: HYDRAULIC CARTRIDGE Primary App: EPE 1.901H10SLA000P Dimensions: Outer Diameter: 5.59" (142 mm) Inner Diameter: 3.70" (94 mm) Length: 15.20" (386 mm)</p>
















<p>Part Number: P561323 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0004G60A000P Dimensions: Outer Diameter: 1.77" (45 mm) Inner Diameter: 0.95" (24 mm) Length: 3.27" (83 mm) Efficiency @ 60 Micron</p>	<p>Part Number: P561351 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0015H20SLA000P Dimensions: Outer Diameter: 2.36" (60 mm) Inner Diameter: 1.35" (34 mm) Length: 6.89" (175 mm)</p>
<p>Part Number: P561324 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0004H10SLA000P Dimensions: Outer Diameter: 1.77" (45 mm) Inner Diameter: 0.96" (25 mm) Length: 3.27" (83 mm)</p>	<p>Part Number: P561354 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0020J10SLA000P Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: 1.66" (42 mm) Length: 6.22" (158 mm)</p>
<p>Part Number: P561326 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0004P10A000P ELEMENT Dimensions: Outer Diameter: 1.77" (45 mm) Inner Diameter: 0.95" (24 mm) Length: 3.27" (83 mm) Efficiency @ 10 Micron</p>	<p>Part Number: P561363 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0030H10SLA000P Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: 1.66" (42 mm) Length: 9.76" (248 mm)</p>
<p>Part Number: P561327 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0005G10A000P Dimensions: Outer Diameter: 1.77" (45 mm) Inner Diameter: 0.95" (24 mm) Length: 3.86" (98 mm)</p>	<p>Part Number: P561368 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0045H10SLA000P Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: 1.66" (42 mm) Length: 15.67" (398 mm)</p>
<p>Part Number: P561328 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0005G25A000P Dimensions: Outer Diameter: 1.77" (45 mm) Inner Diameter: 0.95" (24 mm) Length: 3.86" (98 mm) Efficiency @ 25 Micron</p>	<p>Part Number: P561370 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0045H3SLA000P ELEMENT Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: 1.66" (42 mm) Length: 15.63" (397 mm)</p>
<p>Part Number: P561330 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0005G60A000P Dimensions: Outer Diameter: 1.77" (45 mm) Inner Diameter: 0.95" (24 mm) Length: 3.86" (98 mm) Efficiency @ 60 Micron</p>	<p>Part Number: P561375 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.10G25A000P ELEMENT Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.72" (18 mm) Length: 1.30" (33 mm) Efficiency @ 25 Micron</p>
<p>Part Number: P561336 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0008G25A000P Dimensions: Outer Diameter: 1.77" (45 mm) Inner Diameter: 0.95" (24 mm) Length: 6.22" (158 mm)</p>	<p>Part Number: P561376 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.10H10SLA000P Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.72" (18 mm) Length: 1.30" (33 mm)</p>
<p>Part Number: P561337 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0008G60A000P ELEMENT Dimensions: Outer Diameter: 1.77" (45 mm) Inner Diameter: 0.95" (24 mm) Length: 6.18" (157 mm) Efficiency @ 60 Micron</p>	<p>Part Number: P561379 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.140G100A000P Dimensions: Outer Diameter: 2.91" (74 mm) Inner Diameter: 1.59" (40 mm) Length: 5.98" (152 mm) Efficiency @ 100 Micron</p>
<p>Part Number: P561338 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0008G80A000P Dimensions: Outer Diameter: 1.77" (45 mm) Inner Diameter: 0.95" (24 mm) Length: 6.18" (157 mm) Efficiency @ 80 Micron</p>	<p>Part Number: P561380 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.140G130A000P Dimensions: Outer Diameter: 2.91" (74 mm) Inner Diameter: 1.59" (40 mm) Length: 5.98" (152 mm) Efficiency @ 130 Micron</p>
<p>Part Number: P561339 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0008H20SLA000P ELEMENT Dimensions: Outer Diameter: 1.77" (45 mm) Inner Diameter: 0.95" (24 mm) Length: 6.18" (157 mm)</p>	<p>Part Number: P561383 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.140G25A000P Dimensions: Outer Diameter: 2.91" (74 mm) Inner Diameter: 1.59" (40 mm) Length: 5.98" (152 mm) Efficiency @ 25 Micron</p>
<p>Part Number: P561347 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0015G25A000P Dimensions: Outer Diameter: 2.36" (60 mm) Inner Diameter: 1.35" (34 mm) Length: 6.89" (175 mm) Efficiency @ 25 Micron</p>	<p>Part Number: P561386 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.140G350A000P Dimensions: Outer Diameter: 2.91" (74 mm) Inner Diameter: 1.60" (41 mm) Length: 5.98" (152 mm) Efficiency @ 300 Micron</p>

<p>Part Number: P561388 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.140G60A000P ELEMENT Dimensions: Outer Diameter: 2.91" (74 mm) Inner Diameter: 1.59" (40 mm) Length: 5.98" (152 mm) Efficiency @ 60 Micron</p>	<p>Part Number: P561403 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.18G60A000P Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.72" (18 mm) Length: 2.09" (53 mm) Efficiency @ 60 Micron</p>
<p>Part Number: P561389 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.140H10SLA000P ELEMENT Dimensions: Outer Diameter: 2.91" (74 mm) Inner Diameter: 1.59" (40 mm) Length: 5.98" (152 mm)</p>	<p>Part Number: P561407 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.225G25A000P Dimensions: Outer Diameter: 2.91" (74 mm) Inner Diameter: 1.59" (40 mm) Length: 8.86" (225 mm) Efficiency @ 25 Micron</p>
<p>Part Number: P561391 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.140H10SLC000P ELEMENT Dimensions: Outer Diameter: 3.07" (78 mm) Inner Diameter: 1.58" (40 mm) Length: 6.14" (156 mm)</p>	<p>Part Number: P561410 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.225G25C000P Dimensions: Outer Diameter: 3.07" (78 mm) Inner Diameter: 1.58" (40 mm) Length: 9.09" (231 mm) Efficiency @ 25 Micron</p>
<p>Part Number: P561392 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.140H20SLA000P Dimensions: Outer Diameter: 2.91" (74 mm) Inner Diameter: 1.59" (40 mm) Length: 5.98" (152 mm)</p>	<p>Part Number: P561417 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.225P10A000P Dimensions: Outer Diameter: 2.91" (74 mm) Inner Diameter: 1.59" (40 mm) Length: 8.86" (225 mm)</p>
<p>Part Number: P561393 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.140H3SLA000P ELEMENT Dimensions: Outer Diameter: 2.91" (74 mm) Inner Diameter: 1.59" (40 mm) Length: 5.98" (152 mm)</p>	<p>Part Number: P561418 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.18G250C000P ELEMENT Dimensions: Outer Diameter: 1.81" (46 mm) Inner Diameter: 0.72" (18 mm) Length: 2.05" (52 mm) Efficiency @ 250 Micron</p>
<p>Part Number: P561394 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.140H6SLA000P ELEMENT Dimensions: Outer Diameter: 2.91" (74 mm) Inner Diameter: 1.59" (40 mm) Length: 5.98" (152 mm)</p>	<p>Part Number: P561419 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.32G100A000P ELEMENT Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.72" (18 mm) Length: 3.27" (83 mm) Efficiency @ 100 Micron</p>
<p>Part Number: P561395 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.140H6SLC000P Dimensions: Outer Diameter: 3.07" (78 mm) Inner Diameter: 1.58" (40 mm) Length: 6.14" (156 mm)</p>	<p>Part Number: P561421 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.32G25A000P Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.72" (18 mm) Length: 3.27" (83 mm) Efficiency @ 25 Micron</p>
<p>Part Number: P561397 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.140P25A000P Dimensions: Outer Diameter: 2.91" (74 mm) Inner Diameter: 1.59" (40 mm) Length: 5.98" (152 mm) Efficiency @ 25 Micron</p>	<p>Part Number: P561427 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.32G40A000P Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.72" (18 mm) Length: 3.27" (83 mm)</p>
<p>Part Number: P561400 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.18G10A000P Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.72" (18 mm) Length: 2.09" (53 mm) Efficiency @ 10 Micron</p>	<p>Part Number: P561428 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.32G60A000P ELEMENT Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.72" (18 mm) Length: 3.27" (83 mm) Efficiency @ 60 Micron</p>
<p>Part Number: P561401 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.18G25A000P ELEMENT Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.72" (18 mm) Length: 2.09" (53 mm) Efficiency @ 25 Micron</p>	<p>Part Number: P561430 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.32H10SLA000P Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.72" (18 mm) Length: 3.27" (83 mm)</p>
<p>Part Number: P561402 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.18G40A000P Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.72" (18 mm) Length: 2.09" (53 mm) Efficiency @ 40 Micron</p>	<p>Part Number: P561435 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.32H6SLA000P Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.72" (18 mm) Length: 3.27" (83 mm)</p>

<p>Part Number: P561436 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.32P10A000P ELEMENT Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.72" (18 mm) Length: 3.27" (83 mm)</p>	<p>Part Number: P561464 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.56H10SLA000V Dimensions: Outer Diameter: 2.09" (53 mm) Inner Diameter: 0.96" (24 mm) Length: 3.70" (94 mm)</p>
<p>Part Number: P561437 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.32P25A000P ELEMENT Dimensions: Outer Diameter: 1.69" (43 mm) Inner Diameter: 0.72" (18 mm) Length: 3.27" (83 mm)</p>	<p>Part Number: P561466 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.56H20SLA000P Dimensions: Outer Diameter: 2.09" (53 mm) Inner Diameter: 0.96" (24 mm) Length: 3.70" (94 mm)</p>
<p>Part Number: P561439 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.360G25C000P ELEMENT Dimensions: Outer Diameter: 3.07" (78 mm) Inner Diameter: 1.58" (40 mm) Length: 11.06" (280 mm)</p>	<p>Part Number: P561468 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.56H6SLA000P Dimensions: Outer Diameter: 2.09" (53 mm) Inner Diameter: 0.96" (24 mm) Length: 3.70" (94 mm)</p>
<p>Part Number: P561441 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.360H10SLA000P ELEMENT Dimensions: Outer Diameter: 2.91" (74 mm) Inner Diameter: 1.59" (40 mm) Length: 10.83" (275 mm)</p>	<p>Part Number: P561470 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.56P25A000P Dimensions: Outer Diameter: 2.09" (53 mm) Inner Diameter: 0.96" (24 mm) Length: 3.70" (94 mm)</p>
<p>Part Number: P561442 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.360H10SLC000P Dimensions: Outer Diameter: 3.07" (78 mm) Inner Diameter: 1.58" (40 mm) Length: 11.06" (281 mm)</p>	<p>Part Number: P561475 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.90G25A000P Dimensions: Outer Diameter: 2.09" (53 mm) Inner Diameter: 0.96" (24 mm) Length: 5.87" (149 mm) Efficiency @ 25 Micron</p>
<p>Part Number: P561444 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.360H3SLA000P ELEMENT Dimensions: Outer Diameter: 2.91" (74 mm) Inner Diameter: 1.59" (40 mm) Length: 10.83" (275 mm)</p>	<p>Part Number: P561476 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.90G25C000P Dimensions: Outer Diameter: 2.13" (54 mm) Inner Diameter: 0.95" (24 mm) Length: 6.06" (154 mm) Efficiency @ 25 Micron</p>
<p>Part Number: P561445 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.360H6SLA000P ELEMENT Dimensions: Outer Diameter: 2.91" (74 mm) Inner Diameter: 1.59" (40 mm) Length: 10.83" (275 mm)</p>	<p>Part Number: P561480 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.90H10SLA000P Dimensions: Outer Diameter: 2.09" (53 mm) Inner Diameter: 0.96" (24 mm) Length: 5.87" (149 mm)</p>
<p>Part Number: P561459 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.56G25A000P ELEMENT Dimensions: Outer Diameter: 2.09" (53 mm) Inner Diameter: 0.96" (24 mm) Length: 3.70" (94 mm) Efficiency @ 25 Micron</p>	<p>Part Number: P561482 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.90H20SLA000P Dimensions: Outer Diameter: 2.09" (53 mm) Inner Diameter: 0.96" (24 mm) Length: 5.87" (149 mm)</p>
<p>Part Number: P561461 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.56G40A000P Dimensions: Outer Diameter: 2.09" (53 mm) Inner Diameter: 0.96" (24 mm) Length: 3.70" (94 mm) Efficiency @ 40 Micron</p>	<p>Part Number: P561534 Description: HYDRAULIC CARTRIDGE Primary App: EPE 4.06G100A000P Dimensions: Outer Diameter: 1.63" (41 mm) Thread Size: M16 X 1.5 Length: 2.48" (63 mm) Efficiency @ 100 Micron</p>
<p>Part Number: P561462 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.56G60A000P Dimensions: Outer Diameter: 2.09" (53 mm) Inner Diameter: 0.96" (24 mm) Length: 3.70" (94 mm) Efficiency @ 60 Nominal Micron</p>	<p>Part Number: P561541 Description: HYDRAULIC CARTRIDGE Primary App: EPE 4.10G200A000P Dimensions: Outer Diameter: 1.63" (41 mm) Thread Size: M16 X 1.5 Length: 2.99" (76 mm) Efficiency @ 200 Micron</p>
<p>Part Number: P561463 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.56H10SLA000P Dimensions: Outer Diameter: 2.09" (53 mm) Inner Diameter: 0.96" (24 mm) Length: 3.70" (94 mm)</p>	<p>Part Number: P561542 Description: HYDRAULIC CARTRIDGE Primary App: EPE 4.10G25A000P Dimensions: Outer Diameter: 1.63" (41 mm) Thread Size: M16 X 1.5 Length: 2.99 In Hg (76 MM Hg) Efficiency @ 25 Micron</p>













<p>Part Number: P562005 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0020G25A00OP Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: 1.66" (42 mm) Length: 6.18" (157 mm) Efficiency @ 25 Micron</p>	 <p>Part Number: P562202 Description: HYDRAULIC SPIN-ON Primary App: SPE-50-25 Dimensions: Outer Diameter: 4.86" (123 mm) Thread Size: 1 1/2-16 Length: 6.66" (169 mm) Gasket OD: 5.04" (128 mm) Gasket ID: 4.76" (121 mm)</p>
<p>Part Number: P562006 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0020G60A000P ELEMENT Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: 1.66" (42 mm) Length: 6.18" (157 mm) Efficiency @ 60 Micron</p>	 <p>Part Number: P562203 Description: HYDRAULIC SPIN-ON Primary App: SPE-50-140W Dimensions: Outer Diameter: 4.86" (123 mm) Thread Size: 1 1/2-16 Length: 6.66" (169 mm) Gasket OD: 5.04" (128 mm) Gasket ID: 4.76" (121 mm)</p>
<p>Part Number: P562007 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0030G25A0VOP ELEMENT Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: 1.66" (42 mm) Length: 9.76" (248 mm) Efficiency @ 25 Micron</p>	<p>Part Number: P562204 Description: HYDRAULIC SPIN-ON Primary App: SPE-60-10 Dimensions: Outer Diameter: 4.76" (121 mm) Thread Size: 1 1/2-16 Length: 10.66" (271 mm)</p>
<p>Part Number: P562011 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.0045H6SLA000P Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: 1.66" (42 mm) Length: 15.67" (398 mm)</p>	<p>Part Number: P562205 Description: HYDRAULIC SPIN-ON Primary App: SPE-60-25 Dimensions: Outer Diameter: 4.76" (121 mm) Thread Size: 1 1/2-16 Length: 10.66" (271 mm)</p>
<p>Part Number: P562024 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.225P25A000P Dimensions: Outer Diameter: 2.91" (74 mm) Inner Diameter: 1.59" (40 mm) Length: 8.86" (225 mm)</p>	<p>Part Number: P562207 Description: HYDRAULIC SPIN-ON Primary App: SPE-50-BTA-10 Dimensions: Outer Diameter: 4.86" (123 mm) Thread Size: 1 1/2-16 Length: 6.66" (169 mm) Gasket OD: 5.04" (128 mm) Gasket ID: 4.76" (121 mm)</p>
<p>Part Number: P562025 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.18G25C000PX ELEMENT Dimensions: Outer Diameter: 1.81" (46 mm) Inner Diameter: 0.72" (18 mm) Length: 2.05" (52 mm) Efficiency @ 25 Micron</p>	<p>Part Number: P562208 Description: HYDRAULIC SPIN-ON Primary App: SPE-60-BTA-10 Dimensions: Outer Diameter: 4.86" (123 mm) Thread Size: 1 1/2-16 Length: 10.66" (271 mm) Gasket OD: 5.04" (128 mm) Gasket ID: 4.76" (121 mm)</p>
<p>Part Number: P562034 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.90G250A000P Dimensions: Outer Diameter: 2.09" (53 mm) Inner Diameter: 0.96" (24 mm) Length: 5.87" (149 mm) Efficiency @ 250 Micron</p>	<p>Part Number: P562211 Description: STRAINER Primary App: SEC-100-3-60 Dimensions: Outer Diameter: 5.12" (130 mm) Inlet Diameter: 4.00" (102 mm) Thread Size: 3 NPT Length: 11.80" (300 mm) Efficiency 50% @ 238 Micron</p>
 <p>Part Number: P562198 Description: HYDRAULIC SPIN-ON Primary App: SPE-15-10 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 5.35" (136 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (63 mm)</p>	<p>Part Number: P562212 Description: STRAINER Primary App: SEC-100-3-60-RV3 Dimensions: Outer Diameter: 5.12" (130 mm) Inlet Diameter: 4.00" (102 mm) Thread Size: 3 NPT Length: 11.80" (300 mm) Relief Valve Setting: 3 PSI (0.21 Bar) Efficiency 50% @ 238 Micron</p>
<p>Part Number: P562199 Description: HYDRAULIC SPIN-ON Primary App: SPE-15-25 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 5.35" (136 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (63 mm)</p>	<p>Part Number: P562213 Description: STRAINER Primary App: SEC-200-3-100 Dimensions: Outer Diameter: 8.10" (206 mm) Inlet Diameter: 4.00" (102 mm) Thread Size: 3 NPT Length: 11.30" (287 mm) Efficiency 50% @ 149 Micron</p>
<p>Part Number: P562200 Description: HYDRAULIC SPIN-ON Primary App: SPE-50-3-N Dimensions: Outer Diameter: 4.86" (123 mm) Thread Size: 1 1/2-16 Length: 6.66" (169 mm) Gasket OD: 5.04" (128 mm) Gasket ID: 4.76" (121 mm)</p>	










<p>Part Number: P562214 Description: STRAINER Primary App: SEC-300-4-100 Dimensions: Outer Diameter: 8.10" (206 mm) Inlet Diameter: 5.00" (127 mm) Thread Size: 4 NPT Length: 15.00" (381 mm) Efficiency 50% @ 149 Micron</p>	<p>Part Number: P562229 Description: STRAINER Primary App: PEC-20-1.1/4-100-RV3 Dimensions: Outer Diameter: 3.40" (86 mm) Inlet Diameter: 2.00" (51 mm) Thread Size: 1 1/4 NPT Length: 5.60" (142 mm) Relief Valve Setting: 3 PSI (0.21 Bar) Efficiency 50% @ 149 Micron</p>
<p>Part Number: P562221 Description: STRAINER Primary App: SEH-3-3/8-100 Dimensions: Outer Diameter: 1.90" (48 mm) Thread Size: 3/8-18 Length: 2.50" (64 mm) Efficiency 50% @ 149 Micron</p>	<p>Part Number: P562231 Description: STRAINER Primary App: PEC-20-1.1/4-200 Dimensions: Outer Diameter: 3.40" (86 mm) Inlet Diameter: 2.00" (51 mm) Thread Size: 1 1/4 NPT Length: 5.60" (142 mm) Efficiency 50% @ 74 Micron</p>
<p>Part Number: P562222 Description: STRAINER Primary App: SEH-50-1.1/2-60 Dimensions: Outer Diameter: 4.00" (102 mm) Thread Size: 1 1/2 NPT Length: 10.00" (254 mm) Efficiency 50% @ 238 Micron</p>	 <p>Part Number: P562232 Description: STRAINER Primary App: PEC-30-1.1/2-100 Dimensions: Outer Diameter: 3.40" (86 mm) Inlet Diameter: 2.30" (58 mm) Thread Size: 1 1/2 NPT Length: 5.60" (142 mm) Efficiency 50% @ 149 Micron</p>
<p>Part Number: P562223 Description: STRAINER Primary App: PEC-100-3-100 Dimensions: Outer Diameter: 5.20" (132 mm) Thread Size: 3-8 Length: 11.50" (292 mm) Efficiency 50% @ 149 Micron</p>	 <p>Part Number: P562233 Description: STRAINER Primary App: PEC-30-1.1/2-100-RV3 Dimensions: Outer Diameter: 3.40" (86 mm) Inlet Diameter: 2.30" (58 mm) Thread Size: 1 1/2 NPT Length: 5.60" (142 mm) Relief Valve Setting: 3 PSI (0.21 Bar) Efficiency 50% @ 149 Micron</p>
<p>Part Number: P562224 Description: STRAINER Primary App: PEC-100-3-100-RV3 Dimensions: Outer Diameter: 5.20" (132 mm) Thread Size: 3-8 Length: 11.50" (292 mm) Relief Valve Setting: 3 PSI (0.21 Bar) Efficiency 50% @ 149 Micron</p>	 <p>Part Number: P562235 Description: STRAINER Primary App: PEC-3-3/8-100 Dimensions: Outer Diameter: 1.90" (48 mm) Thread Size: 1 3/8 NPT Inner Diameter: 4.2" (107 mm) Length: 4.20" (107 mm) Efficiency 50% @ 149 Micron</p>
<p>Part Number: P562225 Description: STRAINER Primary App: PEC-100-3-100-SST Dimensions: Outer Diameter: 5.20" (132 mm) Thread Size: 3-8 Length: 11.50" (292 mm) Efficiency 50% @ 149 Micron</p>	 <p>Part Number: P562236 Description: STRAINER Primary App: PEC-50-1.1/2-100 Dimensions: Outer Diameter: 4.00" (102 mm) Thread Size: 1 1/2 NPT Length: 8.00" (203 mm) Efficiency 50% @ 149 Micron</p>
<p>Part Number: P562226 Description: STRAINER Primary App: PEC-10-1-100 Dimensions: Outer Diameter: 2.70" (68 mm) Inlet Diameter: 1.60" (41 mm) Thread Size: 1 NPT Length: 5.60" (142 mm) Efficiency 50% @ 149 Micron</p>	 <p>Part Number: P562237 Description: STRAINER Primary App: PEC-50-1.1/2-100-RV3 Dimensions: Outer Diameter: 4.00" (102 mm) Thread Size: 1 1/2 NPT Length: 8.00" (203 mm) Relief Valve Setting: 3 PSI (0.21 Bar) Efficiency 50% @ 149 Micron</p>
<p>Part Number: P562227 Description: STRAINER Primary App: PEC-10-1-100-RV3 Dimensions: Outer Diameter: 2.70" (68 mm) Thread Size: 1 NPT Length: 5.60" (142 mm) Relief Valve Setting: 3 PSI (0.21 Bar) Efficiency 50% @ 149 Micron</p>	<p>Part Number: P562238 Description: STRAINER Primary App: PEC-50-2-100 Dimensions: Outer Diameter: 4.00" (102 mm) Thread Size: 2 NPT Length: 10.40" (264 mm) Efficiency 50% @ 149 Micron</p>
<p>Part Number: P562228 Description: STRAINER Primary App: PEC-20-1.1/4-100 Dimensions: Outer Diameter: 3.40" (86 mm) Inlet Diameter: 2.00" (51 mm) Thread Size: 1 1/4 NPT Length: 5.60" (142 mm) Efficiency 50% @ 149 Micron</p>	 <p>Part Number: P562239 Description: STRAINER Primary App: PEC-50-2-100-RV3 Dimensions: Outer Diameter: 4.00" (102 mm) Thread Size: 2 NPT Length: 10.40" (264 mm) Relief Valve Setting: 3 PSI (0.21 Bar) Efficiency 50% @ 149 Micron</p>















	<p>Part Number: P562240 Description: STRAINER Primary App: PEC-5-1/2-100 Dimensions: Outer Diameter: 1.90" (48 mm) Inlet Diameter: 1.00" (25 mm) Thread Size: 1/2 NPT Length: 4.30" (109 mm) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P562250 Description: STRAINER Primary App: STM-15-100-RV5 Dimensions: Outer Diameter: 1.66" (35 mm) Thread Size: 1 5/16-12 Length: 8.20" (208 mm) Relief Valve Setting: 5 PSI (0.34 Bar) Efficiency 50% @ 149 Micron</p>
	<p>Part Number: P562242 Description: STRAINER Primary App: PEC-75-2.1/2-100 Dimensions: Outer Diameter: 5.20" (132 mm) Inlet Diameter: 3.30" (84 mm) Thread Size: 2 1/2 NPT Length: 8.50" (216 mm) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P562251 Description: STRAINER Primary App: STM-25-100 Dimensions: Outer Diameter: 2.12" (54 mm) Thread Size: 1 5/8-12 Length: 9.04" (230 mm) Efficiency 50% @ 149 Micron</p>
	<p>Part Number: P562243 Description: STRAINER Primary App: PEC-75-2.1/2-100-RV3 Dimensions: Outer Diameter: 5.20" (132 mm) Inlet Diameter: 3.30" (84 mm) Thread Size: 2 1/2 NPT Length: 8.50" (216 mm) Relief Valve Setting: 3 PSI (0.21 Bar) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P562252 Description: STRAINER Primary App: STM-25-100-RV5 Dimensions: Outer Diameter: 2.12" (54 mm) Thread Size: 1 5/8-12 Length: 9.04" (230 mm) Relief Valve Setting: 5 PSI (0.34 Bar) Efficiency 50% @ 149 Micron</p>
	<p>Part Number: P562244 Description: STRAINER Primary App: PEC-8-1-100 Dimensions: Outer Diameter: 2.70" (68 mm) Inlet Diameter: 1.60" (41 mm) Thread Size: 1 NPT Length: 4.30" (109 mm) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P562253 Description: STRAINER Primary App: STM-5-100 Dimensions: Outer Diameter: 1.17" (30 mm) Thread Size: 3/4-16 Length: 5.34" (136 mm) Efficiency 50% @ 149 Micron</p>
	<p>Part Number: P562245 Description: STRAINER Primary App: PEC-8-3/4-100 Dimensions: Outer Diameter: 2.70" (68 mm) Thread Size: 3/4-14 NPT Length: 4.30" (109 mm) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P562254 Description: STRAINER Primary App: STM-5-100-RV5 Dimensions: Outer Diameter: 1.17" (30 mm) Thread Size: 3/4-16 Length: 5.34" (136 mm) Relief Valve Setting: 5 PSI (0.34 Bar) Efficiency 50% @ 149 Micron</p>
	<p>Part Number: P562246 Description: STRAINER Primary App: PEC-8-3/4-100-RV3 Dimensions: Outer Diameter: 2.70" (68 mm) Thread Size: 3/4-14 NPT Length: 4.30" (109 mm) Relief Valve Setting: 3 PSI (0.21 Bar) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P562255 Description: STRAINER Primary App: TM-100-100-RV5 Dimensions: Outer Diameter: 4.00" (102 mm) Thread Size: Outer 4 NPTM Inner 3 NPT Length: 11.30" (287 mm) Relief Valve Setting: 5 PSI (0.34 Bar) Efficiency 50% @ 149 Micron</p>
	<p>Part Number: P562247 Description: STRAINER Primary App: STM-10-100 Dimensions: Outer Diameter: 1.36" (35 mm) Thread Size: 1 1/16-12 Length: 8.17" (208 mm) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P562256 Description: STRAINER Primary App: TM-10-100 Dimensions: Outer Diameter: 1.36" (35 mm) Thread Size: Outer 1 1/4NPTM Inner 3/4 NPT Length: 8.17" (208 mm) Efficiency 50% @ 149 Micron</p>
	<p>Part Number: P562248 Description: STRAINER Primary App: STM-10-100-RV5 Dimensions: Outer Diameter: 1.36" (35 mm) Thread Size: 1 1/16-12 Length: 8.17" (208 mm) Relief Valve Setting: 5 PSI (0.34 Bar) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P562257 Description: STRAINER Primary App: TM-10-100-RV5 Dimensions: Outer Diameter: 1.36" (35 mm) Thread Size: Outer 1 1/4 NPTM Inner 3 NPT Length: 8.17" (208 mm) Relief Valve Setting: 5 PSI (0.34 Bar) Efficiency 50% @ 149 Micron</p>
	<p>Part Number: P562249 Description: STRAINER Primary App: STM-15-100 Dimensions: Outer Diameter: 1.66" (35 mm) Thread Size: 1 5/16-12 Length: 8.20" (208 mm) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P562259 Description: STRAINER Primary App: TM-10-60-RV5 Dimensions: Outer Diameter: 1.36" (35 mm) Thread Size: Outer 1 1/4 NPTM Inner 3 NPT Length: 8.17" (208 mm) Relief Valve Setting: 5 PSI (0.34 Bar) Efficiency 50% @ 238 Micron</p>






	<p>Part Number: P562260 Description: STRAINER Primary App: TM-15-100 Dimensions: Outer Diameter: 1.66" (42 mm) Thread Size: Outer 1 1/2 NPTM Inner 1 NPT Length: 8.20" (208 mm) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P562273 Description: STRAINER Primary App: TM-50-100-RV5 Dimensions: Outer Diameter: 3.00" (76 mm) Thread Size: Outer 3 NPTM Inner: 2 NPT Length: 9.70" (246 mm) Relief Valve Setting: 5 PSI (0.34 Bar) Efficiency 50% @ 149 Micron</p>
	<p>Part Number: P562264 Description: STRAINER Primary App: TM-15-100-RV5 Dimensions: Outer Diameter: 1.66" (42 mm) Thread Size: Outer 1 1/2 NPTM Inner 1 NPT Length: 8.20" (208 mm) Relief Valve Setting: 5 PSI (0.34 Bar) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P562274 Description: STRAINER Primary App: TM-5-100 Dimensions: Outer Diameter: 1.17" (30 mm) Thread Size: Outer 1 NPTM Inner 1/2 NPT Length: 5.34" (136 mm) Efficiency 50% @ 149 Micron</p>
	<p>Part Number: P562265 Description: STRAINER Primary App: TM-15-200-RV5 Dimensions: Outer Diameter: 1.66" (42 mm) Thread Size: Outer 1 1/2 NPTM Inner 1 NPT Length: 8.20" (208 mm) Relief Valve Setting: 5 PSI (0.34 Bar) Efficiency 50% @ 74 Micron</p>		<p>Part Number: P562275 Description: STRAINER Primary App: TM-5-100-RV5 Dimensions: Outer Diameter: 1.17" (30 mm) Thread Size: Outer 1 NPTM Inner 1/2 NPT Length: 5.34" (136 mm) Relief Valve Setting: 5 PSI (0.34 Bar) Efficiency 50% @ 149 Micron</p>
	<p>Part Number: P562266 Description: STRAINER Primary App: TM-25-100 Dimensions: Outer Diameter: 2.12" (54 mm) Thread Size: Outer 2 NPTM Inner 1 1/4 NPT Length: 9.04" (230 mm) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P563030 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.460H10SLC000V Dimensions: Outer Diameter: 3.07" (78 mm) Inner Diameter: 1.58" (40 mm) Length: 15.00" (381 mm)</p>
	<p>Part Number: P562267 Description: STRAINER Primary App: TM-25-100-RV5 Dimensions: Outer Diameter: 2.12" (54 mm) Thread Size: Outer 2 NPTM Inner 1 1/4 NPT Length: 9.04" (230 mm) Relief Valve Setting: 5 PSI (0.34 Bar) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P563762 Description: HYDRAULIC SPIN-ON Primary App: SPE-15-10 BLANK Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 5.35" (136 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (63 mm)</p>
	<p>Part Number: P562269 Description: STRAINER Primary App: TM-25-200-RV5 Dimensions: Outer Diameter: 2.12" (54 mm) Thread Size: Outer 2 NPTM Inner 1 1/4 NPT Length: 9.04" (230 mm) Relief Valve Setting: 5 PSI (0.34 Bar) Efficiency 50% @ 74 Micron</p>		<p>Part Number: P563767 Description: HYDRAULIC SPIN-ON Primary App: SPE-60-10 BLANK Dimensions: Outer Diameter: 4.78" (121 mm) Thread Size: 1 1/2-16 Length: 10.66" (271 mm) Gasket OD: 5.04" (128 mm) Gasket ID: 4.76" (121 mm)</p>
	<p>Part Number: P562270 Description: STRAINER Primary App: TM-3-100 Dimensions: Outer Diameter: 0.87" (22 mm) Thread Size: Outer 3/4 NPTM Inner 3/8 NPT Length: 4.00" (102 mm) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P564041 Description: HYDRAULIC SPIN-ON Primary App: CASE 177356A1 Dimensions: Outer Diameter: 4.78" (121 mm) Thread Size: 1 1/2-16 Length: 10.66" (271 mm) Gasket OD: 5.04" (128 mm) Gasket ID: 4.76" (121 mm)</p>
	<p>Part Number: P562271 Description: STRAINER Primary App: TM-50-100 Dimensions: Outer Diameter: 3.00" (76 mm) Thread Size: Outer 3 NPTM Inner: 2 NPT Length: 9.70" (246 mm) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P564042 Description: HYDRAULIC SPIN-ON Primary App: JOHN DEERE RE161181 Dimensions: Outer Diameter: 3.71" (94 mm) Thread Size: 1 1/4-12 Length: 9.67" (246 mm) Gasket OD: 2.84" (72 mm) Gasket ID: 2.47" (63 mm)</p>
	<p>Part Number: P562272 Description: STRAINER Primary App: TM-50-100-RV3 Dimensions: Outer Diameter: 3.00" (76 mm) Thread Size: Outer 3 NPTM Inner: 2 NPT Length: 9.70" (246 mm) Relief Valve Setting: 3 PSI (0.21 Bar) Efficiency 50% @ 149 Micron</p>		<p>Part Number: P564085 Description: HYDRAULIC CARTRIDGE Primary App: EPE 1.0095G25A000P Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.87" (73 mm) Length: 15.75" (400 mm) Efficiency @ 25 Micron</p>

	<p>Part Number: P564278 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: SERVICE FILTER FOR DONALDSON K031005, K031008 FUEL MANAGER Dimensions: Outer Diameter: 4.37" (111 mm) Inner Diameter: 3.75" (95 mm) Length: 9.25" (235 mm) Efficiency 50% @ 5 Micron</p>		<p>Part Number: P564557 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU AK3572, PALL HC8604FKS16H, Pall HC9604FKS16H Dimensions: Outer Diameter: 3.12" (79 mm) Inner Diameter: 2.01" (51 mm) Length: 16.56" (421 mm)</p>
	<p>Part Number: P564357 Description: HYDRAULIC SPIN-ON Primary App: DONALDSON SP15/25 SPIN-ON Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 7.87" (200 mm)</p>		<p>Part Number: P564563 Description: HYDRAULIC CARTRIDGE Primary App: Pall HC8914FKS16H Dimensions: Outer Diameter: 3.86" (98 mm) Inlet Diameter: 2.53" (64 mm) Length: 16.03" (407 mm)</p>
	<p>Part Number: P564392 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: SERVICE FILTER FOR DONALDSON K031010 FUEL MANAGER Dimensions: Outer Diameter: 4.37" (111 mm) Inner Diameter: 3.75" (95 mm) Length: 9.25" (235 mm) Efficiency 50% @ 2 Micron</p>		<p>Part Number: P564669 Description: BREATHER Primary App: BULK FLUID STORAGE TANKS Dimensions: Outer Diameter: 4.52" (115 mm) Thread Size: 1 NPT Length: 4.50" (114 mm)</p>
	<p>Part Number: P564393 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: SERVICE FILTER FOR DONALDSON K031011 FUEL MANAGER Dimensions: Outer Diameter: 4.37" (111 mm) Inner Diameter: 3.75" (95 mm) Length: 5.25" (133 mm) Efficiency 50% @ 2 Micron</p>		<p>Part Number: P564849 Description: HYDRAULIC CARTRIDGE Primary App: PALL HC9404FKS12H Dimensions: Outer Diameter: 3.88" (99 mm) Inner Diameter: 2.53" (64 mm) Length: 12.31" (313 mm)</p>
	<p>Part Number: P564424 Description: BREATHER, SPIN ON Primary App: SCHROEDER ABF3/10 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1 1/8-16 Length: 3.66" (93 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P564859 Description: HYDRAULIC CARTRIDGE Primary App: JCB Dimensions: Outer Diameter: 2.36" (60 mm) Inner Diameter: 1.35" (34 mm) Length: 8.46" (215 mm) Relief Valve Setting: 43.5 PSI (3.00 Bar)</p>
	<p>Part Number: P564425 Description: BREATHER, SPIN ON Primary App: GBS-10-03-N12 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 3/4 NPT Length: 3.65" (93 mm) Efficiency 50% @ 10 Micron</p>		<p>Part Number: P564860 Description: HYDRAULIC CARTRIDGE Primary App: GENIE Dimensions: Outer Diameter: 2.20" (56 mm) Inner Diameter: 1.00" (25 mm) Length: 6.69" (170 mm)</p>
	<p>Part Number: P564430 Description: FUEL/WATER SEPARATOR CARTRIDGE Primary App: SERVICE FILTER FOR DONALDSON K031012 FUEL MANAGER Dimensions: Outer Diameter: 4.37" (111 mm) Inner Diameter: 3.75" (95 mm) Length: 9.25" (235 mm) Efficiency Beta 2 @ 30 Micron (30 Micron) Efficiency 50% @ 30 Micron</p>		<p>Part Number: P564967 Description: HYDRAULIC SPIN-ON Primary App: SPE-15-BTA-3 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 5.35" (136 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (63 mm)</p>
	<p>Part Number: P564468 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: DONALDSON HMK05/25 # 1/2 MEDIA Dimensions: Outer Diameter: 4.60" (117 mm) Thread Size: 1 3/4-12 Length: 14.24" (362 mm)</p>		<p>Part Number: P565059 Description: HYDRAULIC SPIN-ON Primary App: DONALDSON SP15/25 SERIES HYDRAULIC FILTER ASSEMBLIES Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 7.87" (200 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (63 mm)</p>
	<p>Part Number: P564556 Description: HYDRAULIC CARTRIDGE Primary App: Pall HC9604FKN16H -- TRIBOGUARD HYDRAULIC ELEMENT Dimensions: Outer Diameter: 3.12" (79 mm) Inner Diameter: 2.01" (51 mm) Length: 16.56" (421 mm)</p>		<p>Part Number: P565060 Description: HYDRAULIC SPIN-ON Primary App: DONALDSON SP15/25 SERIES HYDRAULIC FILTER ASSEMBLIES Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 7.87" (200 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (63 mm)</p>

<p>Part Number: P565061 Description: HYDRAULIC SPIN-ON Primary App: DONALDSON SP15/25 SERIES HYDRAULIC FILTER ASSEMBLIES Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 5.35" (136 mm)</p>	 <p>Part Number: P565309 Description: HYDRAULIC CARTRIDGE Primary App: Pall HC8300FKN29H or Z Dimensions: Outer Diameter: 5.97" (152 mm) Inlet Diameter: 4.14" (105 mm) Length: 38.62" (981 mm)</p>
 <p>Part Number: P565062 Description: HYDRAULIC SPIN-ON Primary App: DONALDSON SP15/25 SERIES HYDRAULIC FILTER ASSEMBLIES Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 5.35" (136 mm)</p>	 <p>Part Number: P565310 Description: HYDRAULIC CARTRIDGE Primary App: Pall HC8300FKS39H or Z Dimensions: Outer Diameter: 5.97" (152 mm) Inner Diameter: 4.14" (105 mm) Length: 38.62" (981 mm)</p>
<p>Part Number: P565105 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON CXW4115V Dimensions: Outer Diameter: 2.17" (55 mm) Inner Diameter: 1.07" (27 mm) Length: 12.31" (313 mm) Efficiency @ 14 @ Beta 1000 Micron</p>	 <p>Part Number: P565311 Description: HYDRAULIC CARTRIDGE Primary App: Pall HC8300FKT39H or Z Dimensions: Outer Diameter: 5.97" (152 mm) Inlet Diameter: 4.14" (105 mm) Length: 38.62" (981 mm)</p>
 <p>Part Number: P565149 Description: HYDRAULIC SPIN-ON Primary App: SULLAIR 250026-982 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 31/32-20 Length: 5.35" (136 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (63 mm)</p>	 <p>Part Number: P565312 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER 39QM60V Dimensions: Outer Diameter: 5.97" (152 mm) Inner Diameter: 4.14" (106 mm) Length: 38.62" (981 mm)</p>
 <p>Part Number: P565150 Description: HYDRAULIC CARTRIDGE Primary App: FILTREC R472G06 Dimensions: Outer Diameter: 3.80" (97 mm) Inner Diameter: 2.20" (56 mm) Length: 16.81" (427 mm) Efficiency 99% @ 6 Micron</p>	 <p>Part Number: P565313 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER 39QM150V Dimensions: Outer Diameter: 5.97" (152 mm) Inner Diameter: 4.14" (105 mm) Length: 38.62" (981 mm)</p>
 <p>Part Number: P565242 Description: HYDRAULIC SPIN-ON Primary App: LHA TTE-15-10 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 3/4-BSP Length: 5.36" (136 mm)</p>	<p>Part Number: P565930 Description: HYDRAULIC CARTRIDGE Primary App: EPE 2.32G60C000V Dimensions: Outer Diameter: 1.81" (46 mm) Inner Diameter: 0.72" (18 mm) Length: 3.23" (82 mm) Efficiency @ 60 Nominal Micron</p>
 <p>Part Number: P565243 Description: HYDRAULIC SPIN-ON Primary App: UCC MX1518-4-10, PTI F4E-35-CCB Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 3/4-BSP Length: 5.36" (136 mm) Gasket OD: 2.83" (72 mm) Gasket ID: 2.46" (63 mm) Efficiency 99% @ 23 Micron</p>	<p>Part Number: P566040 Description: HYDRAULIC SPIN-ON Primary App: SP15/25 PLURASAFE ENBIO TCS COMPATIBLE Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 5.35" (136 mm)</p>
 <p>Part Number: P565245 Description: HYDRAULIC SPIN-ON Primary App: UCC MX1591-4-10 Dimensions: Outer Diameter: 4.66" (118 mm) Thread Size: 1 1/4-11 BSP Length: 6.22" (158 mm)</p>	<p>Part Number: P566041 Description: HYDRAULIC SPIN-ON Primary App: LPS04 Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 5.35" (136 mm)</p>
 <p>Part Number: P565308 Description: HYDRAULIC CARTRIDGE Primary App: Pall HC8300FKP39H or Z Dimensions: Outer Diameter: 5.97" (152 mm) Inlet Diameter: 4.14" (105 mm) Length: 38.62" (981 mm)</p>	<p>Part Number: P566042 Description: HYDRAULIC SPIN-ON Primary App: SP15/25 PLURASAFE ENBIO TCS COMPATIBLE Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1-12 Length: 7.87" (200 mm)</p>
	<p>Part Number: P566043 Description: HYDRAULIC SPIN-ON Primary App: LPS05/HBK05 Dimensions: Outer Diameter: 4.87" (124 mm) Thread Size: 1 1/2-16 Length: 5.00" (127 mm)</p>


<p>Part Number: P566044 Description: HYDRAULIC SPIN-ON Primary App: LPS05/HBK05 Dimensions: Outer Diameter: 4.78" (121 mm) Thread Size: 1 1/2-16 Length: 10.66" (271 mm) Gasket OD: 5.04" (128 mm) Gasket ID: 4.76" (121 mm)</p>	 <p>Part Number: P566312 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: DONALDSON 93 MM FUEL FAMILY FILTER WATER SEPARATOR 20 MICRON Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: M92 x 2.5 Length: 6.88" (174 mm) Efficiency 50% @ 7 Micron Efficiency 99% @ 20 Micron</p>
<p>Part Number: P566045 Description: HYDRAULIC SPIN-ON Primary App: LPS05/HBK05 Dimensions: Outer Diameter: 4.87" (124 mm) Thread Size: 1 1/2-16 Length: 6.66" (169 mm) Gasket OD: 5.04" (128 mm) Gasket ID: 4.76" (121 mm)</p>	<p>Part Number: P566619 Description: HYDRAULIC CARTRIDGE Primary App: Parker 932692Q Dimensions: Outer Diameter: 3.68" (93 mm) Inner Diameter: 1.75" (44 mm) Length: 18.78" (477 mm)</p>
<p>Part Number: P566046 Description: HYDRAULIC SPIN-ON Primary App: LPS05/HBK05 Dimensions: Outer Diameter: 4.78" (121 mm) Thread Size: 1 1/2-16 Length: 10.66" (271 mm) Gasket OD: 5.04" (128 mm) Gasket ID: 4.76" (121 mm)</p>	 <p>Part Number: P566903 Description: HYDRAULIC CARTRIDGE Primary App: AN-6236-1 Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 2.60" (66 mm) Length: 1.88" (48 mm) Efficiency 99% @ 9 Micron</p>
 <p>Part Number: P566047 Description: HYDRAULIC SPIN-ON Primary App: HMK04 Dimensions: Outer Diameter: 3.71" (94 mm) Thread Size: 1-3/8-12 Length: 5.97" (152 mm)</p>	 <p>Part Number: P566904 Description: HYDRAULIC CARTRIDGE Primary App: AN-6236-3 Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 2.60" (66 mm) Length: 8.00" (203 mm) Efficiency 99% @ 9 Micron</p>
<p>Part Number: P566048 Description: HYDRAULIC SPIN-ON Primary App: HMK04 Dimensions: Outer Diameter: 3.71" (94 mm) Thread Size: 1-3/8-12 Length: 9.44" (240 mm)</p>	 <p>Part Number: P566919 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7400SKP4H Dimensions: Outer Diameter: 3.66" (923 mm) Thread Size: 1 1/2-16 Length: 5.78" (147 mm) Gasket OD: 3.37" (86 mm)</p>
<p>Part Number: P566049 Description: HYDRAULIC SPIN-ON Primary App: HMK05 Dimensions: Outer Diameter: 4.60" (117 mm) Thread Size: 1-3/4-12 Length: 11.65" (296 mm)</p>	 <p>Part Number: P566920 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7400SKN4H Dimensions: Outer Diameter: 3.66" (93 mm) Thread Size: 1 1/2-16 Length: 5.78" (147 mm) Gasket OD: 3.37" (86 mm) Efficiency 99% @ 5 Micron</p>
<p>Part Number: P566050 Description: HYDRAULIC SPIN-ON Primary App: HBK04 Dimensions: Outer Diameter: 3.71" (94 mm) Thread Size: 1 1/4-12 Length: 5.97" (152 mm)</p>	<p>Part Number: P566921 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7400SKS4H Dimensions: Outer Diameter: 3.66" (923 mm) Thread Size: 1 1/2-16 Length: 5.78" (147 mm) Gasket OD: 3.37" (86 mm)</p>
 <p>Part Number: P566310 Description: FUEL SPIN ON Primary App: DONALDSON 93 MM FUEL FAMILY FILTER 5 MICRON Dimensions: Outer Diameter: 3.62" (91 mm) Thread Size: M92 x 2.5 Length: 6.10" (155 mm)</p>	 <p>Part Number: P566922 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7400SKT4H Dimensions: Outer Diameter: 3.66" (923 mm) Thread Size: 1 1/2-16 Length: 5.78" (147 mm) Gasket OD: 3.37" (86 mm)</p>
 <p>Part Number: P566311 Description: FUEL SPIN ON Primary App: DONALDSON 93 MM FUEL FAMILY FILTER 10 MICRON Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: M92 x 2.5 Length: 6.10" (155 mm) Gasket OD: 3.92" (100 mm) Gasket ID: 3.45" (88 mm) Efficiency 99% @ 8 Micron</p>	<p>Part Number: P567460 Description: HYDRAULIC CARTRIDGE Primary App: AN6236-2 Dimensions: Outer Diameter: 6.02" (152 mm) Inner Diameter: 3.50" (88 mm) Length: 3.94" (100 mm)</p>
	<p>Part Number: P567551 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC/GE BRAKE FILTER 1.5 MM Dimensions: Outer Diameter: 1.37" (35 mm) Inner Diameter: 0.49" (12 mm) Length: 1.65" (41 mm)</p>














	<p>Part Number: P567580 Description: HYDRAULIC SPIN-ON Primary App: CAT APPLICATIONS Dimensions: Outer Diameter: 4.59" (117 mm) Thread Size: 1 3/4-12 Length: 11.63" (295 mm)</p>	<p>Part Number: P569382 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7400SKS8H Dimensions: Outer Diameter: 3.66" (923 mm) Thread Size: 1 1/2-16 Length: 8.06" (205 mm) Gasket OD: 3.37" (86 mm)</p>
	<p>Part Number: P567882 Description: HYDRAULIC CARTRIDGE Primary App: Neg Micon 1650 and 82 wind turbines Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: 1.59" (40 mm) Length: 6.29" (160 mm)</p>	 <p>Part Number: P569383 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7400SKT8H Dimensions: Outer Diameter: 3.66" (923 mm) Thread Size: 1 1/2-16 Length: 8.06" (205 mm) Gasket OD: 3.37" (86 mm)</p>
	<p>Part Number: P568081 Description: HYDRAULIC CARTRIDGE Primary App: ZINGA, ZRE-409-03 Dimensions: Outer Diameter: 3.83" (97 mm) Inner Diameter: 1.90" (48 mm) Length: 9.19" (233 mm) Efficiency Beta 1000 @ 5 Micron</p>	 <p>Part Number: P569401 Description: HYDRAULIC SPIN-ON Primary App: JOHN DEERE RE205726 Dimensions: Outer Diameter: 3.71" (94 mm) Thread Size: 1-3/8-12 Length: 9.65" (245 mm) Gasket OD: 3.82" (97 mm) Efficiency 99% @ 6 Micron</p>
	<p>Part Number: P568091 Description: HYDRAULIC CARTRIDGE Primary App: ZINGA, ZRE-409-10 Dimensions: Outer Diameter: 3.83" (97 mm) Inner Diameter: 1.90" (48 mm) Length: 9.19" (233 mm) Efficiency Beta 1000 @ 14 Micron</p>	 <p>Part Number: P569402 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7400SKZ8H Dimensions: Outer Diameter: 3.66" (923 mm) Thread Size: 1 1/2-16 Length: 8.06" (205 mm) Gasket OD: 3.37" (86 mm)</p>
	<p>Part Number: P568093 Description: HYDRAULIC CARTRIDGE Primary App: ZINGA, ZRE-418-10 Dimensions: Outer Diameter: 3.83" (97 mm) Length: 18.19" (462 mm) Efficiency Beta 1000 @ 14 Micron</p>	 <p>Part Number: P569527 Description: HYDRAULIC CARTRIDGE Primary App: SCHROEDER K SERIES WATER REMOVAL Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 1.62" (41 mm) Length: 9.22" (234 mm)</p>
	<p>Part Number: P568094 Description: HYDRAULIC CARTRIDGE Primary App: ZINGA, ZRE-418-03 Dimensions: Outer Diameter: 3.83" (97 mm) Inner Diameter: 1.90" (48 mm) Length: 18.19" (462 mm) Efficiency Beta 1000 @ 5 Micron</p>	 <p>Part Number: P569528 Description: HYDRAULIC CARTRIDGE Primary App: PALL 9600 8" WATER REMOVAL Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 8.16" (207 mm)</p>
	<p>Part Number: P568449 Description: HYDRAULIC CARTRIDGE Primary App: EPE FLE 0145 - 1.0145G40A0 Dimensions: Outer Diameter: 6.28" (160 mm) Inner Diameter: 3.76" (96 mm) Length: 15.69" (398 mm) Efficiency @ 40 wire screen Micron</p>	 <p>Part Number: P569529 Description: HYDRAULIC CARTRIDGE Primary App: PALL 9600 13" WATER REMOVAL Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 12.89" (327 mm)</p>
	<p>Part Number: P568532 Description: HYDRAULIC CARTRIDGE Primary App: NORDBERG 3894081 Dimensions: Outer Diameter: 6.08" (154 mm) Inner Diameter: 1.75" (44 mm) Length: 31.00" (787 mm)</p>	 <p>Part Number: P569530 Description: HYDRAULIC CARTRIDGE Primary App: PALL 9600 16" WATER REMOVAL Dimensions: Outer Diameter: 3.10" (79 mm) Inner Diameter: 1.71" (43 mm) Length: 16.80" (427 mm)</p>
	<p>Part Number: P569380 Description: HYDRAULIC SPIN-ON Primary App: Pall HC7400SKP8H Dimensions: Outer Diameter: 3.66" (923 mm) Thread Size: 1 1/2-16 Length: 8.06" (205 mm) Gasket OD: 3.37" (86 mm)</p>	<p>Part Number: P569531 Description: HYDRAULIC CARTRIDGE Primary App: HRK 10 WATER REMOVAL Dimensions: Outer Diameter: 7.44" (189 mm) Inner Diameter: 4.76" (121 mm) Length: 22.00" (559 mm)</p>
	<p>Part Number: P569381 Description: HYDRAULIC SPIN-ON Primary App: PALL HC7400SKN8H Dimensions: Outer Diameter: 3.66" (923 mm) Thread Size: 1 1/2-16 Length: 8.06" (205 mm) Gasket OD: 3.37" (86 mm)</p>	 <p>Part Number: P569532 Description: HYDRAULIC CARTRIDGE Primary App: 6X18 WATER REMOVAL ELEMENT Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 2.60" (66 mm) Length: 18.00" (457 mm)</p>

	<p>Part Number: P569533 Description: HYDRAULIC CARTRIDGE Primary App: PALL 8310 16" WATER REMOVAL Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 4.12" (105 mm) Length: 15.95" (405 mm)</p>		<p>Part Number: P601437 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON FRG08 AIR CLEANER Dimensions: Outer Diameter: 6.12" (155 mm) Inner Diameter: 3.08" (78 mm) Length: 15.04" (382 mm)</p>
	<p>Part Number: P569534 Description: HYDRAULIC CARTRIDGE Primary App: PALL 8310 39" WATER REMOVAL Dimensions: Outer Diameter: 6.00" (152 mm) Inner Diameter: 4.12" (105 mm) Length: 37.80" (960 mm)</p>		<p>Part Number: P601476 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSON FRG08 AIR CLEANER Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 2.55" (65 mm) Length: 14.60" (371 mm)</p>
	<p>Part Number: P569553 Description: HYDRAULIC CARTRIDGE Primary App: EPE 20400H20SLA000V Dimensions: Outer Diameter: 3.07" (78 mm) Inner Diameter: 1.59" (40 mm) Length: 15.63" (397 mm)</p>		<p>Part Number: P601560 Description: AIR SAFETY, OVAL Primary App: DONALDSON PSD10 SERIES POWERCORE Dimensions: Width: 7.46" (189 mm) Height: 1.57" (40 mm) Length: 12.46" (316 mm)</p>
	<p>Part Number: P600043 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON FRG05 AIR CLEANER Dimensions: Outer Diameter: 4.16" (106 mm) Inner Diameter: 2.36" (60 mm) Length: 14.31" (363 mm)</p>		<p>Part Number: P601767 Description: AIR PRIMARY, RADIALSEAL Primary App: Donaldson FRG12 Air Cleaner Dimensions: Outer Diameter: 9.22" (234 mm) Inner Diameter: 4.61" (117 mm) Length: 13.03" (331 mm)</p>
	<p>Part Number: P600047 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSON FRG05 AIR CLEANER Dimensions: Outer Diameter: 2.44" (62 mm) Inner Diameter: 1.77" (45 mm) Length: 13.50" (343 mm)</p>		<p>Part Number: P601774 Description: AIR SAFETY, RADIALSEAL Primary App: Donaldson FRG12 Air Cleaner Dimensions: Outer Diameter: 4.76" (121 mm) Inner Diameter: 3.17" (81 mm) Length: 12.71" (323 mm)</p>
	<p>Part Number: P600501 Description: AIR PRIMARY, RADIALSEAL Primary App: AC A1621C 2001 CHEVROLET EXPRESS VAN Dimensions: Outer Diameter: 5.44" (138 mm) Inner Diameter: 3.20" (81 mm) Length: 12.87" (327 mm)</p>		<p>Part Number: P601790 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON FRG10 AIR CLEANER Dimensions: Outer Diameter: 8.18" (208 mm) Inner Diameter: 4.17" (106 mm) Length: 16.12" (409 mm)</p>
	<p>Part Number: P600676 Description: AIR PRIMARY, RADIALSEAL Primary App: MACK 57MD46M, 57MD48M, 81SF28 Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.80" (147 mm) Length: 25.04" (636 mm)</p>		<p>Part Number: P602344 Description: AIR PRIMARY, KONEPAC™ Primary App: ENDURANCE EON VERSION OF P530866 Dimensions: Outer Diameter: 12.74" (324 mm) Inner Diameter: 8.32" (211 mm) Length: 23.99" (609 mm)</p>
	<p>Part Number: P600975 Description: AIR SAFETY, OVAL Primary App: DONALDSON PSD08 SERIES POWERCORE Dimensions: Width: 4.24" (108 mm) Height: 1.86" (47 mm) Length: 8.24" (209 mm)</p>		<p>Part Number: P602427 Description: AIR SAFETY Primary App: DONALDSON FKB05 SERIES Dimensions: Outer Diameter: 3.07" (78 mm) Inner Diameter: 2.04" (52 mm) Length: 12.64" (321 mm)</p>
	<p>Part Number: P601280 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON FRG09 AIR CLEANER Dimensions: Outer Diameter: 6.89" (175 mm) Inner Diameter: 4.00" (102 mm) Length: 16.00" (406 mm)</p>		<p>Part Number: P602657 Description: AIR PANEL, ENGINE Primary App: AC A1618C SILVERADO & SERRIA PICKUPS Dimensions: Width: 9.73" (247 mm) Depth: 2.39" (61 mm) Length: 12.29" (312 mm)</p>
	<p>Part Number: P601286 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSON FRG09 AIR CLEANER Dimensions: Outer Diameter: 4.14" (105 mm) Inner Diameter: 3.33" (85 mm) Length: 15.41" (391 mm)</p>		

	<p>Part Number: P602658 Description: AIR PANEL, ENGINE Primary App: FORD LIGHT TRUCK, MOTORCRAFT FA1710, FA1750 Dimensions: Width: 7.23" (184 mm) Depth: 3.30" (84 mm) Length: 13.35" (339 mm)</p>		<p>Part Number: P604430 Description: AIR PRIMARY Primary App: G092037 Dimensions: Outer Diameter: 8.66" (220 mm) Inner Diameter: 5.21" (132 mm) Length: 28.00" (711 mm) D: 5.74" (146 mm) Gasket ID: 7.29" (185 mm)</p>
	<p>Part Number: P603568 Description: BREATHER, CYLINDRICAL Primary App: DONALDSON SPIRACLE BREATHER ELEMENT Dimensions: Outer Diameter: 6.24" (158 mm) Inner Diameter: 3.27" (83 mm) Length: 12.30" (312 mm)</p>		<p>Part Number: P604457 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON FKB04 SERIES Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 3.41" (87 mm) Length: 10.48" (266 mm)</p>
	<p>Part Number: P603577 Description: AIR PRIMARY, PowerCore® Primary App: FORD F-SERIES SUPER DUTY 6.0L DIESEL Dimensions: Outlet Diameter: 7.95" (202 mm) Length: 10.66" (271 mm)</p>		<p>Part Number: P604996 Description: AIR PRIMARY, RADIALSEAL Primary App: KOMATSU 3EC02A541E Dimensions: Outer Diameter: 6.47" (164 mm) Inner Diameter: 3.58" (91 mm) Length: 13.66" (347 mm)</p>
	<p>Part Number: P603729 Description: AIR SAFETY Primary App: DONALDSON FKB04 SERIES Dimensions: Outer Diameter: 2.62" (67 mm) Length: 10.24" (260 mm)</p>		<p>Part Number: P604997 Description: AIR SAFETY, RADIALSEAL Primary App: Komatsu 3EC02A5240, 8775087, Toyota 17744-U3330-71 Dimensions: Outer Diameter: 3.72" (95 mm) Inner Diameter: 2.92" (74 mm) Length: 13.37" (340 mm)</p>
	<p>Part Number: P603746 Description: BREATHER, CYLINDRICAL Primary App: DONALDSON SPIRACLE BREATHER ELEMENT Dimensions: Outer Diameter: 5.09" (129 mm) Inner Diameter: 2.13" (54 mm) Length: 8.08" (205 mm)</p>		<p>Part Number: P605022 Description: AIR PRIMARY, RADIALSEAL Primary App: ISUZU 1142152130 Dimensions: Outer Diameter: 13.08" (332 mm) Inner Diameter: 6.78" (172 mm) Length: 16.69" (424 mm)</p>
	<p>Part Number: P603755 Description: AIR PRIMARY, RADIALSEAL Primary App: JOHN DEERE RE164839 800 SERIES TRACTOR Dimensions: Outer Diameter: 13.09" (332 mm) Inner Diameter: 6.78" (172 mm) Length: 11.10" (282 mm)</p>		<p>Part Number: P605552 Description: AIR SAFETY Primary App: VOLVO 20411816 VN SERIES Dimensions: Outer Diameter: 8.44" (214 mm) Length: 18.56" (471 mm)</p>
	<p>Part Number: P603757 Description: AIR SAFETY, RADIALSEAL Primary App: JOHN DEERE RE172447 800 SERIES TRACTOR Dimensions: Outer Diameter: 6.89" (175 mm) Inner Diameter: 5.24" (133 mm) Length: 10.62" (270 mm)</p>		<p>Part Number: P605960 Description: AIR PRIMARY, PowerCore® Primary App: FREIGHTLINER M2 SERIES HIGH HP FLAME RETARDANT Dimensions: Outer Diameter: 14.84" (377 mm) Length: 8.03" (204 mm)</p>
	<p>Part Number: P603857 Description: AIR PRIMARY Primary App: CATERPILLAR 1131578 Dimensions: Outer Diameter: 19.29" (490 mm) Inner Diameter: 12.93" (328 mm) Length: 17.84" (453 mm) Gasket ID: 16.85" (428 mm)</p>		<p>Part Number: P606059 Description: BREATHER, CYLINDRICAL Primary App: MIDLAND 100696E Dimensions: Outer Diameter: 4.00" (102 mm) Inner Diameter: 1.33" (34 mm) Length: 1.39" (35 mm)</p>
	<p>Part Number: P604273 Description: AIR PRIMARY, PowerCore® Primary App: H2 HUMMER Dimensions: Width: 6.00" (152 mm) Height: 7.20" (183 mm) Length: 11.10" (282 mm)</p>		<p>Part Number: P606060 Description: AIR PANEL Primary App: ISUZU 8943763530 Dimensions: Width: 9.81" (249 mm) Depth: 6.66" (169 mm) Height: 1.99" (51 mm)</p>
	<p>Part Number: P606061 Description: AIR PANEL Primary App: TOYOTA 1780146060 Dimensions: Width: 8.16" (207 mm) Depth: 9.65" (245 mm) Height: 2.03" (52 mm)</p>		<p>Part Number: P606061 Description: AIR PANEL Primary App: TOYOTA 1780146060 Dimensions: Width: 8.16" (207 mm) Depth: 9.65" (245 mm) Height: 2.03" (52 mm)</p>


	<p>Part Number: P606062 Description: AIR PANEL Primary App: MOPAR 53007386 Dimensions: Width: 9.61" (244 mm) Depth: 11.36" (288 mm) Height: 1.46" (37 mm)</p>		<p>Part Number: P606075 Description: AIR PRIMARY, OVAL Primary App: GENERAL MOTORS 25095707 Dimensions: Width: 5.75" (146 mm) Height: 3.98" (101 mm) Length: 5.75" (146 mm)</p>
	<p>Part Number: P606063 Description: AIR PANEL, VENTILATION Primary App: KOMATSU 4270722120 Dimensions: Width: 10.03" (255 mm) Depth: 12.32" (313 mm) Height: 1.84" (47 mm)</p>		<p>Part Number: P606076 Description: AIR PRIMARY Primary App: GENERAL MOTORS 8994941 Dimensions: Outer Diameter: 5.13" (130 mm) Inner Diameter: 3.41" (87 mm) Length: 5.28" (134 mm)</p>
	<p>Part Number: P606067 Description: AIR PRIMARY, FINNED Primary App: Case D73225; John Deere AR44774 Dimensions: Outer Diameter: 6.38" (162 mm) Inner Diameter: 5.25" (133 mm) Length: 13.25" (337 mm)</p>		<p>Part Number: P606077 Description: AIR PANEL, VENTILATION Primary App: FORD F3T29601Z Dimensions: Width: 8.35" (212 mm) Depth: 10.55" (268 mm) Height: 1.65" (42 mm)</p>
	<p>Part Number: P606068 Description: AIR PRIMARY Primary App: DURAQIP 90603 DUST COLLECTOR ELEMENT Dimensions: Outer Diameter: 9.25" (216 mm) Inner Diameter: 6.34" (443 mm) Length: 24.50" (622 mm)</p>		<p>Part Number: P606078 Description: AIR PRIMARY Primary App: FORD F67Z9601AA Dimensions: Outer Diameter: 6.87" (174 mm) Inner Diameter: 3.26" (83 mm) Length: 5.91" (150 mm)</p>
	<p>Part Number: P606070 Description: AIR PRIMARY, OVAL Primary App: FORD D2AZ9601A Dimensions: Width: 11.25" (285 mm) Height: 2.62" (66 mm) Length: 11.25" (285 mm)</p>		<p>Part Number: P606079 Description: AIR PRIMARY, OVAL Primary App: INGERSOLL RAND 32012957 Dimensions: Width: 4.35" (110 mm) Height: 3.00" (76 mm) Length: 4.71" (120 mm)</p>
	<p>Part Number: P606071 Description: AIR PRIMARY, OVAL Primary App: ALLIS CHALMERS 49931583 Dimensions: Width: 6.64" (169 mm) Height: 3.05" (77 mm) Length: 6.64" (169 mm)</p>		<p>Part Number: P606081 Description: AIR SAFETY Primary App: MASSEY FERGUSON 1688093M1 Dimensions: Outer Diameter: 2.94" (75 mm) Inner Diameter: 2.47" (63 mm) Length: 8.06" (205 mm)</p>
	<p>Part Number: P606072 Description: AIR PRIMARY Primary App: LISTER PETTER ACF4996 Dimensions: Outer Diameter: 1.97" (50 mm) Inner Diameter: 3.63" (92 mm) Length: 2.84" (72 mm)</p>		<p>Part Number: P606082 Description: AIR PANEL, VENTILATION Primary App: CATERPILLAR 6P1319 Dimensions: Width: 4.70" (119 mm) Depth: 10.70" (272 mm) Height: 4.20" (107 mm)</p>
	<p>Part Number: P606073 Description: AIR PRIMARY, OVAL Primary App: GMC 25040929; Isuzu 8-25040-929-0 Dimensions: Width: 9.72" (247 mm) Height: 2.83" (72 mm) Length: 9.72" (247 mm)</p>		<p>Part Number: P606083 Description: AIR PANEL, VENTILATION Primary App: CATERPILLAR 7T3519 Dimensions: Width: 3.94" (100 mm) Depth: 19.69" (500 mm) Height: 3.95" (100 mm)</p>
	<p>Part Number: P606074 Description: AIR PRIMARY Primary App: PETTER DIESEL ZPF356, VOLVO 66392036 Dimensions: Outer Diameter: 5.43" (138 mm) Inner Diameter: 3.13" (80 mm) Length: 2.52" (64 mm)</p>		<p>Part Number: P606084 Description: AIR PANEL, VENTILATION Primary App: CATERPILLAR 7T1889 Dimensions: Width: 6.00" (152 mm) Depth: 23.50" (597 mm) Height: 2.50" (64 mm)</p>

	<p>Part Number: P606085 Description: AIR PANEL, VENTILATION Primary App: JOHN DEERE AH92463 Dimensions: Width: 5.00" (127 mm) Depth: 16.50" (419 mm) Height: 1.19" (30 mm)</p>		<p>Part Number: P606220 Description: AIR PRIMARY, RADIALSEAL Primary App: CATERPILLAR 1651689 Dimensions: Outer Diameter: 13.47" (342 mm) Inner Diameter: 8.20" (208 mm) Length: 15.02" (382 mm)</p>
	<p>Part Number: P606086 Description: AIR PANEL, VENTILATION Primary App: CATERPILLAR 1130305 Dimensions: Width: 5.56" (141 mm) Depth: 16.41" (417 mm) Height: 2.59" (66 mm)</p>		<p>Part Number: P606271 Description: AIR PRIMARY Primary App: WISCONSIN LO173B Dimensions: Outer Diameter: 3.56" (90 mm) Inner Diameter: 2.06" (52 mm) Length: 4.17" (106 mm)</p>
	<p>Part Number: P606087 Description: AIR PANEL, VENTILATION Primary App: CATERPILLAR 777358 Dimensions: Width: 12.00" (305 mm) Depth: 12.88" (327 mm) Height: 2.19" (56 mm)</p>		<p>Part Number: P606272 Description: AIR PANEL Primary App: DAIHATSU 17801-87104-000; TOYOTA 17801-01020, 17801-74010 Dimensions: Width: 6.58" (167 mm) Depth: 8.99" (228 mm) Height: 2.17" (55 mm)</p>
	<p>Part Number: P606089 Description: AIR PANEL, VENTILATION Primary App: CATERPILLAR 9P5174, 2G1946 Dimensions: Width: 11.94" (303 mm) Depth: 13.25" (337 mm) Height: 0.81" (21 mm)</p>		<p>Part Number: P606275 Description: AIR PANEL Primary App: FORD F5RZ-9601-C Dimensions: Width: 5.83" (148 mm) Depth: 15.53" (395 mm) Height: 1.62" (41 mm)</p>
	<p>Part Number: P606090 Description: AIR PANEL, VENTILATION Primary App: CATERPILLAR 9X4986 Dimensions: Width: 4.06" (103 mm) Depth: 14.90" (378 mm) Height: 2.88" (73 mm)</p>		<p>Part Number: P606276 Description: AIR PANEL, ENGINE Primary App: BRIGGS & STRATTON 491588 Dimensions: Width: 4.45" (113 mm) Depth: 5.20" (132 mm) Length: .86" (22 mm)</p>
	<p>Part Number: P606119 Description: AIR PRIMARY, PowerCore® Primary App: JOHN DEERE AL119839 Dimensions: Width: 5.12" (130 mm) Height: 7.22" (183 mm) Length: 12.87" (327 mm)</p>		<p>Part Number: P606277 Description: BREATHER, SPIN ON Primary App: MACK 2MD3131 Dimensions: Outer Diameter: 3.69" (94 mm) Thread Size: 3/4-20 Length: 4.34" (110 mm)</p>
	<p>Part Number: P606120 Description: AIR PRIMARY, PowerCore® Primary App: JOHN DEERE AL150285 Dimensions: Width: 5.12" (130 mm) Height: 11.15" (283 mm) Length: 12.87" (327 mm)</p>		<p>Part Number: P606278 Description: AIR PRIMARY Primary App: JOHN DEERE AM3100 Dimensions: Outer Diameter: 4.93" (125 mm) Inner Diameter: 3.00" (76 mm) Length: 5.00" (127 mm)</p>
	<p>Part Number: P606121 Description: AIR SAFETY, OVAL Primary App: DONALDSON PSD09 SERIES POWERCORE, JOHN DEERE AL150288 Dimensions: Width: 4.24" (108 mm) Height: 0.74" (19 mm) Length: 11.73" (298 mm)</p>		<p>Part Number: P606279 Description: AIR PRIMARY Primary App: CASE K922630, Lister 194010 Dimensions: Outer Diameter: 8.25" (210 mm) Inner Diameter: 5.90" (150 mm) Length: 3.95" (100 mm)</p>
	<p>Part Number: P606122 Description: AIR PRIMARY, PowerCore® Primary App: FORD 2U2J9601BA, MOTORCRAFT FA1757 Dimensions: Width: 8.43" (214 mm) Height: 6.20" (157 mm) Length: 14.38" (365 mm)</p>		<p>Part Number: P606280 Description: AIR PRIMARY Primary App: CUMMINS 3903876, 3903879; KOHLER 253108 Dimensions: Outer Diameter: 8.00" (203 mm) Inner Diameter: 5.38" (137 mm) Length: 10.90" (277 mm)</p>
	<p>Part Number: P606219 Description: AIR PANEL Primary App: GM 25095333 Dimensions: Width: 6.06" (154 mm) Depth: 7.63" (194 mm) Height: 1.62" (41 mm)</p>		

	<p>Part Number: P606281 Description: AIR PANEL Primary App: GMC 25099149 Dimensions: Width: 7.13" (181 mm) Depth: 9.37" (238 mm) Height: 1.70" (43 mm)</p>		<p>Part Number: P606483 Description: AIR ROUND, VENTILATION Primary App: JOHN DEERE T168220 Dimensions: Outer Diameter: 6.44" (163 mm) Inner Diameter: 3.63" (92 mm) Length: 11.50" (292 mm)</p>
	<p>Part Number: P606282 Description: AIR PANEL Primary App: MOTORCRAFT FA1630 Dimensions: Width: 7.11" (181 mm) Depth: 10.02" (255 mm) Height: 1.58" (40 mm)</p>		<p>Part Number: P606488 Description: AIR PRIMARY Primary App: EUCLID 9029495 Dimensions: Outer Diameter: 4.25" (108 mm) Inner Diameter: 1.56" (40 mm) Length: 4.81" (122 mm)</p>
	<p>Part Number: P606284 Description: AIR PANEL Primary App: FORD YF1Z-9601AA Dimensions: Width: 7.10" (180 mm) Depth: 10.02" (255 mm) Height: 2.33" (59 mm)</p>		<p>Part Number: P606502 Description: AIR PRIMARY, OVAL Primary App: CHRYSLER 1739549, 1739649 Dimensions: Width: 8.00" (203 mm) Height: 3.54" (90 mm) Length: 5.75" (146 mm)</p>
	<p>Part Number: P606288 Description: AIR PRIMARY Primary App: INGERSOLL RAND Dimensions: Outer Diameter: 10.93" (278 mm) Inner Diameter: 6.50" (165 mm) Length: 5.03" (128 mm)</p>		<p>Part Number: P606503 Description: AIR PRIMARY Primary App: INTERNATIONAL 3532799C1 Dimensions: Outer Diameter: 10.22" (260 mm) Inner Diameter: 7.97" (202 mm) Length: 16.00" (406 mm)</p>
	<p>Part Number: P606290 Description: AIR PRIMARY Primary App: BRIGGS & STRATTON 393957 Dimensions: Outer Diameter: 4.25" (108 mm) Inner Diameter: 2.00" (51 mm) Length: 3.81" (97 mm)</p>		<p>Part Number: P606555 Description: AIR PANEL, VENTILATION Primary App: VOLVO 20435801 Dimensions: Width: 12.25" (311 mm) Depth: 1.13" (29 mm) Height: 9.18" (233 mm)</p>
	<p>Part Number: P606295 Description: AIR PRIMARY, OVAL Primary App: GMC 6484294 Dimensions: Width: 10.75" (273 mm) Height: 8.61" (219 mm) Length: 2.55" (65 mm)</p>		<p>Part Number: P606712 Description: AIR PRIMARY Primary App: Freightliner M2 Series Emergency Vehicles, Flame Retardant Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.15" (131 mm) Length: 12.28" (312 mm)</p>
	<p>Part Number: P606296 Description: AIR PRIMARY Primary App: AIR REFINER ARM10131S Dimensions: Outer Diameter: 10.00" (254 mm) Inner Diameter: 5.00" (127 mm) Length: 12.88" (327 mm)</p>		<p>Part Number: P606715 Description: AIR SAFETY Primary App: Freightliner M2 Series Emergency Vehicles, Flame Retardant Dimensions: Outer Diameter: 5.30" (135 mm) Inner Diameter: 4.35" (110 mm) Length: 11.82" (300 mm)</p>
	<p>Part Number: P606481 Description: AIR PRIMARY Primary App: IH 494730C91 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.72" (196 mm) Length: 17.75" (451 mm)</p>		<p>Part Number: P606720 Description: AIR PRIMARY Primary App: VOLVO 20411815 VN SERIES Dimensions: Outer Diameter: 12.98" (330 mm) Inner Diameter: 9.13" (232 mm) Length: 18.91" (480 mm)</p>
	<p>Part Number: P606482 Description: AIR PRIMARY Primary App: MASSEY FERGUSON 1670260-M1 Dimensions: Outer Diameter: 5.88" (149 mm) Inner Diameter: 3.00" (76 mm) Length: 9.25" (235 mm)</p>		<p>Part Number: P606735 Description: AIR PRIMARY Primary App: Freightliner M2 Series Emergency Vehicles, Flame Retardant Dimensions: Outer Diameter: 13.09" (332 mm) Inner Diameter: 6.78" (172 mm) Length: 14.76" (375 mm)</p>

	<p>Part Number: P606761 Description: BREATHER, SPECIAL Primary App: Bendix 239262; Cummins 299365; GMC 9028042 Dimensions: Outer Diameter: 2.50" (64 mm) Depth: 1.32" (34 mm) Overall Length: 1.75" (45 mm)</p>		<p>Part Number: P606953 Description: AIR PRIMARY Primary App: KUBOTA T007016323 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 2.50" (64 mm) Length: 9.94" (252 mm)</p>
	<p>Part Number: P606762 Description: AIR PANEL, VENTILATION Primary App: CATERPILLAR 1807487 Dimensions: Width: 11.73" (298 mm) Depth: 2.19" (56 mm) Height: 16.84" (428 mm)</p>		<p>Part Number: P606954 Description: AIR PRIMARY Primary App: FARR 119861003 Dimensions: Outer Diameter: 11.03" (280 mm) Inner Diameter: 6.00" (152 mm) Length: 19.59" (498 mm) Rated Flow LR: 825.00 CFM (23.36 CMM) Rated Flow MR: 1030.00 CFM (29.17 CMM) Rated Flow HR: 1210.00 CFM (34.26 CMM) Restriction LR: 4.00 In H2O (102 mm H2O) Restriction MR: 6.00 In H2O (152 mm H2O) Restriction HR: 8.00 In H2O (203 mm H2O)</p>
	<p>Part Number: P606803 Description: AIR PRIMARY, RADIALSEAL Primary App: JOHN DEERE R119168 Dimensions: Outer Diameter: 6.47" (164 mm) Inner Diameter: 3.58" (91 mm) Length: 12.15" (309 mm)</p>		
	<p>Part Number: P606804 Description: AIR PRIMARY, RADIALSEAL Primary App: CATERPILLAR 1805474 Dimensions: Outer Diameter: 6.47" (164 mm) Inner Diameter: 3.58" (91 mm) Length: 12.17" (309 mm)</p>		<p>Part Number: P606956 Description: AIR PANEL, ENGINE Primary App: BRIGGS & STRATTON 491384 Dimensions: Width: 7.00" (178 mm) Depth: 3.50" (89 mm) Height: 1.50" (38 mm)</p>
	<p>Part Number: P606944 Description: BREATHER, CYLINDRICAL Primary App: CATERPILLAR EQUIPMENT Dimensions: Outer Diameter: 3.03" (77 mm) Inner Diameter: 1.47" (37 mm) Length: 2.28" (58 mm)</p>		<p>Part Number: P606957 Description: AIR PANEL Primary App: GMC 25097453 Dimensions: Width: 11.50" (292 mm) Depth: 7.03" (179 mm) Height: 1.66" (42 mm)</p>
	<p>Part Number: P606946 Description: AIR PRIMARY Primary App: NEW HOLLAND 82001819, 82008606 Dimensions: Outer Diameter: 8.50" (216 mm) Inner Diameter: 4.84" (123 mm) Length: 15.56" (395 mm)</p>		<p>Part Number: P606958 Description: AIR PRIMARY Primary App: Saab-Scania 4023420; Volkswagen 25129620, 25129620A Dimensions: Outer Diameter: 7.06" (179 mm) Inner Diameter: 3.88" (99 mm) Length: 4.06" (103 mm)</p>
	<p>Part Number: P606948 Description: AIR PRIMARY, FINNED Primary App: NISSAN 1654651H10B Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 2.84" (72 mm) Length: 9.50" (241 mm)</p>		<p>Part Number: P606960 Description: AIR PANEL, VENTILATION Primary App: VOLVO 8089705 Dimensions: Width: 4.70" (119 mm) Depth: 11.50" (292 mm) Height: 1.74" (44 mm)</p>
	<p>Part Number: P606949 Description: AIR PRIMARY Primary App: Caterpillar 35-8896, GMC 25041709 Dimensions: Outer Diameter: 2.94" (75 mm) Inner Diameter: 2.00" (51 mm) Length: 3.94" (100 mm) D: 3.25" (83 mm)</p>		<p>Part Number: P606962 Description: AIR PRIMARY Primary App: NELSON 870448A Dimensions: Outer Diameter: 9.22" (234 mm) Inner Diameter: 5.84" (148 mm) Length: 14.75" (375 mm)</p>
	<p>Part Number: P606951 Description: AIR PRIMARY Primary App: ATLAS COPCO 1503-0189 Dimensions: Outer Diameter: 5.16" (131 mm) Inner Diameter: 3.34" (85 mm) Length: 1.94" (49 mm)</p>		<p>Part Number: P607096 Description: AIR PRIMARY Primary App: FRANKLIN 1504917 Dimensions: Outer Diameter: 9.00" (229 mm) Inner Diameter: 5.69" (145 mm) Length: 13.56" (344 mm)</p>
	<p>Part Number: P606952 Description: AIR PRIMARY Primary App: VOLVO 7820580 Dimensions: Outer Diameter: 5.98" (152 mm) Inner Diameter: 3.46" (88 mm) Length: 8.72" (221 mm)</p>		













	<p>Part Number: P607097 Description: AIR PANEL, ENGINE Primary App: Motorcraft FA1675 Dimensions: Width: 7.03" (179 mm) Depth: 13.88" (353 mm) Height: 2.38" (60 mm)</p>		<p>Part Number: P607235 Description: AIR PRIMARY Primary App: GMC 6422260 Dimensions: Outer Diameter: 11.50" (292 mm) Inner Diameter: 8.63" (219 mm) Length: 3.03" (77 mm)</p>
	<p>Part Number: P607098 Description: AIR SECONDARY Primary App: FRANKLIN 1504918 Dimensions: Outer Diameter: 5.56" (141 mm) Inner Diameter: 4.50" (114 mm) Length: 12.50" (318 mm)</p>		<p>Part Number: P607236 Description: AIR PRIMARY Primary App: GMC 6424140 Dimensions: Outer Diameter: 13.88" (353 mm) Inner Diameter: 11.63" (295 mm) Length: 3.04" (77 mm)</p>
	<p>Part Number: P607221 Description: AIR PANEL, VENTILATION Primary App: Ford F6DZ-19N619-BA, F6DZ-19N619-C, F7DZ-19N619-A Dimensions: Width: 10.39" (264 mm) Depth: 1.14" (29 mm) Height: 6.69" (170 mm)</p>		<p>Part Number: P607237 Description: AIR PRIMARY Primary App: GMC 6484963 Dimensions: Outer Diameter: 12.00" (305 mm) Inner Diameter: 9.83" (250 mm) Length: 2.49" (63 mm)</p>
	<p>Part Number: P607223 Description: AIR PRIMARY Primary App: Case D46062 Dimensions: Outer Diameter: 7.55" (192 mm) Inner Diameter: 4.69" (119 mm) Length: 12.59" (320 mm)</p>		<p>Part Number: P607238 Description: AIR PRIMARY Primary App: GMC 8996587 Dimensions: Outer Diameter: 9.97" (253 mm) Inner Diameter: 8.63" (219 mm) Length: 2.31" (59 mm)</p>
	<p>Part Number: P607224 Description: AIR SAFETY Primary App: SULLAIR 2250051239 Dimensions: Outer Diameter: 9.91" (252 mm) Inner Diameter: 8.06" (205 mm) Length: 23.50" (597 mm)</p>		<p>Part Number: P607240 Description: AIR PRIMARY Primary App: Lister-Petter 366-07188 Dimensions: Outer Diameter: 5.91" (150 mm) Inner Diameter: 3.50" (89 mm) Length: 2.87" (73 mm)</p>
	<p>Part Number: P607228 Description: AIR PRIMARY Primary App: AMC 3190562; Ford 3CAZ-9601-A; International 332623-C91; Jeep J3190562 Dimensions: Outer Diameter: 9.72" (247 mm) Inner Diameter: 8.19" (208 mm) Length: 2.26" (57 mm)</p>		<p>Part Number: P607243 Description: AIR PANEL, VENTILATION Primary App: VOLKSWAGEN 34133837 Dimensions: Width: 13.18" (335 mm) Depth: 5.25" (133 mm) Height: 1.65" (42 mm)</p>
	<p>Part Number: P607231 Description: AIR PRIMARY Primary App: Massey Ferguson 1029945-M92 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 2.48" (63 mm) Length: 9.38" (238 mm)</p>		<p>Part Number: P607246 Description: AIR PRIMARY Primary App: INTERNATIONAL 401270-R1 Dimensions: Outer Diameter: 6.94" (176 mm) Inner Diameter: 4.22" (107 mm) Length: 15.37" (390 mm)</p>
	<p>Part Number: P607232 Description: AIR PRIMARY Primary App: Ford E4TE-9601-AA Dimensions: Outer Diameter: 11.75" (298 mm) Inner Diameter: 9.56" (243 mm) Length: 2.12" (54 mm)</p>		<p>Part Number: P607247 Description: AIR SECONDARY Primary App: INTERNATIONAL 398519-R91 Dimensions: Outer Diameter: 4.12" (105 mm) Inner Diameter: 3.00" (76 mm) Length: 14.56" (370 mm)</p>
	<p>Part Number: P607234 Description: AIR PRIMARY Primary App: Cushman 111316; GMC 6420249; Outboard Marine Corporation 111949 Dimensions: Outer Diameter: 5.50" (140 mm) Inner Diameter: 3.82" (97 mm) Length: 3.11" (79 mm)</p>		<p>Part Number: P607248 Description: AIR PRIMARY Primary App: CASE K963803; HOUGH 87924C1; WAYNE 6049133 Dimensions: Outer Diameter: 7.13" (181 mm) Inner Diameter: 4.94" (125 mm) Length: 4.44" (113 mm)</p>


















	<p>Part Number: P607250 Description: AIR PRIMARY Primary App: TOYOTA 17801-70020 Dimensions: Outer Diameter: 8.70" (221 mm) Inner Diameter: 7.76" (197 mm) Length: 2.80" (71 mm)</p>		<p>Part Number: P607262 Description: AIR SECONDARY Primary App: Versatile 22935 Dimensions: Outer Diameter: 7.40" (188 mm) Inner Diameter: 5.90" (150 mm) Length: 18.62" (473 mm)</p>
	<p>Part Number: P607253 Description: AIR PANEL, VENTILATION Primary App: CHRYSLER 4861480AA Dimensions: Width: 7.63" (194 mm) Depth: 8.50" (216 mm) Height: 1.65" (42 mm)</p>		<p>Part Number: P607263 Description: AIR PRIMARY Primary App: Versatile 24574 Dimensions: Outer Diameter: 14.00" (356 mm) Inner Diameter: 7.72" (196 mm) Length: 20.63" (524 mm)</p>
	<p>Part Number: P607254 Description: AIR PRIMARY Primary App: HONDA 17210-ZE3-010, 17210-ZE3-505 Dimensions: Outer Diameter: 4.41" (112 mm) Inner Diameter: 1.63" (41 mm) Length: 3.62" (92 mm)</p>		<p>Part Number: P607265 Description: AIR SAFETY Primary App: Massey Ferguson 1039045-M91 Dimensions: Outer Diameter: 3.35" (85 mm) Inner Diameter: 2.29" (58 mm) Length: 13.44" (341 mm)</p>
	<p>Part Number: P607255 Description: AIR PRIMARY Primary App: KOHLER 2408303 Dimensions: Outer Diameter: 6.96" (177 mm) Inner Diameter: 5.60" (142 mm) Length: 3.00" (76 mm)</p>		<p>Part Number: P607266 Description: AIR PRIMARY Primary App: Sullair 225005-1136 Dimensions: Outer Diameter: 9.22" (234 mm) Inner Diameter: 5.32" (135 mm) Length: 12.00" (305 mm)</p>
	<p>Part Number: P607256 Description: AIR PANEL, VENTILATION Primary App: Toyota 17801-50040 Dimensions: Width: 9.04" (230 mm) Depth: 12.21" (310 mm) Height: 2.05" (52 mm)</p>		<p>Part Number: P607267 Description: AIR PRIMARY Primary App: Ford D2NN-9601-A; Versatile 24575 Dimensions: Outer Diameter: 9.81" (249 mm) Inner Diameter: 4.61" (117 mm) Length: 14.41" (366 mm)</p>
	<p>Part Number: P607257 Description: AIR PANEL, VENTILATION Primary App: Toyota 17801-07010 Dimensions: Width: 9.31" (236 mm) Depth: 12.24" (311 mm) Height: 2.05" (52 mm)</p>		<p>Part Number: P607268 Description: AIR SECONDARY Primary App: Ford D2NN-9R500-B; Versatile 24574 Dimensions: Outer Diameter: 4.53" (115 mm) Inner Diameter: 3.50" (89 mm) Length: 13.53" (344 mm)</p>
	<p>Part Number: P607258 Description: AIR PANEL, VENTILATION Primary App: Ford 1L2Z-9601-AA Dimensions: Width: 11.50" (292 mm) Depth: 7.13" (181 mm) Height: 2.33" (59 mm)</p>		<p>Part Number: P607272 Description: AIR PRIMARY Primary App: JOHN DEERE AR51431 Dimensions: Outer Diameter: 7.40" (188 mm) Inner Diameter: 5.83" (148 mm) Length: 18.62" (473 mm)</p>
	<p>Part Number: P607259 Description: AIR SECONDARY Primary App: Allis Chalmers 279245; Case A45695; Ford SFD07-1010 Dimensions: Outer Diameter: 5.96" (151 mm) Inner Diameter: 4.83" (123 mm) Length: 16.38" (416 mm)</p>		<p>Part Number: P607273 Description: AIR PRIMARY, OVAL Primary App: HONDA 17210ZE2505, 17210ZE2822 Dimensions: Width: 3.50" (89 mm) Height: 3.07" (78 mm) Length: 4.01" (102 mm)</p>
	<p>Part Number: P607260 Description: AIR PRIMARY Primary App: International 424181-C91 Dimensions: Outer Diameter: 13.85" (352 mm) Inner Diameter: 7.45" (189 mm) Length: 7.50" (191 mm)</p>		<p>Part Number: P607274 Description: AIR PRIMARY Primary App: CASE A44694 Dimensions: Outer Diameter: 12.08" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 7.50" (191 mm)</p>
	<p>Part Number: P607275 Description: AIR SAFETY Primary App: CASE A44695 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 4.22" (107 mm) Length: 5.12" (130 mm)</p>		<p>Part Number: P607275 Description: AIR SAFETY Primary App: CASE A44695 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 4.22" (107 mm) Length: 5.12" (130 mm)</p>

	<p>Part Number: P607276 Description: BREATHER, CYLINDRICAL Primary App: CUMMINS 255180 Dimensions: Outer Diameter: 5.00" (127 mm) Inner Diameter: 2.62" (67 mm) Length: 1.25" (32 mm)</p>		<p>Part Number: P607290 Description: AIR PRIMARY Primary App: NISSAN; SUBARU 421454110; TCM 16546L3200 Dimensions: Outer Diameter: 9.17" (233 mm) Inner Diameter: 6.80" (173 mm) Length: 1.94" (49 mm)</p>
	<p>Part Number: P607277 Description: AIR PANEL, VENTILATION Primary App: CHRYSLER 53032404AA Dimensions: Width: 9.40" (239 mm) Depth: 13.78" (350 mm) Height: 2.05" (52 mm)</p>		<p>Part Number: P607291 Description: AIR PRIMARY Primary App: Ingersoll-Rand 35104793; Joy 1224813; Sullair 40899 Dimensions: Outer Diameter: 9.75" (248 mm) Inner Diameter: 6.13" (156 mm) Length: 5.24" (133 mm)</p>
	<p>Part Number: P607278 Description: AIR PRIMARY Primary App: MASSEY FERFUSON 1038946-M91 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 4.22" (107 mm) Length: 14.28" (363 mm)</p>		<p>Part Number: P607293 Description: AIR SECONDARY Primary App: International 622041-C91 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 2.48" (63 mm) Length: 13.38" (340 mm)</p>
	<p>Part Number: P607279 Description: AIR PRIMARY Primary App: FORD B4HF9601DA Dimensions: Outer Diameter: 12.06" (306 mm) Inner Diameter: 4.91" (125 mm) Length: 9.32" (237 mm)</p>		<p>Part Number: P607295 Description: AIR PRIMARY Primary App: BMW 13720043524 Dimensions: Outer Diameter: 3.89" (99 mm) Inner Diameter: 2.36" (60 mm) Length: 2.76" (70 mm)</p>
	<p>Part Number: P607281 Description: AIR PANEL, VENTILATION Primary App: GMC 8469003 Dimensions: Width: 14.00" (356 mm) Depth: 22.50" (572 mm) Height: 6.19" (157 mm)</p>		<p>Part Number: P607298 Description: BREATHER, SPECIAL Primary App: GM 6484966 Dimensions: Width: 3.95" (100 mm) Length: 1.88" (48 mm)</p>
	<p>Part Number: P607283 Description: AIR PRIMARY Primary App: MASSEY FERGUSON 1041845-M91 Dimensions: Outer Diameter: 9.06" (230 mm) Inner Diameter: 5.29" (134 mm) Length: 13.50" (343 mm)</p>		<p>Part Number: P607299 Description: AIR PANEL, VENTILATION Primary App: ISUZU, TOYOTA Dimensions: Width: 12.22" (310 mm) Depth: 7.88" (200 mm) Height: 2.05" (52 mm)</p>
	<p>Part Number: P607284 Description: AIR SECONDARY Primary App: MASSEY FERGUSON 104186-M91 Dimensions: Outer Diameter: 5.20" (132 mm) Inner Diameter: 4.08" (104 mm) Length: 12.25" (311 mm)</p>		<p>Part Number: P607300 Description: AIR PANEL, VENTILATION Primary App: Toyota 17801-74060 Dimensions: Width: 12.30" (312 mm) Depth: 7.35" (187 mm) Height: 1.64" (42 mm)</p>
	<p>Part Number: P607286 Description: AIR SECONDARY Primary App: International 606861C91 Dimensions: Outer Diameter: 7.00" (178 mm) Inner Diameter: 3.42" (87 mm) Length: 17.02" (432 mm)</p>		<p>Part Number: P607301 Description: AIR PRIMARY Primary App: Nissan 16546-89G00; GMC 25147122 Dimensions: Outer Diameter: 12.87" (327 mm) Inner Diameter: 0.48" (12 mm) Length: 2.30" (58 mm)</p>
	<p>Part Number: P607288 Description: AIR PRIMARY Primary App: Atlas Copco 1030-1070 Dimensions: Outer Diameter: 11.94" (303 mm) Inner Diameter: 7.50" (191 mm) Length: 4.25" (108 mm)</p>		<p>Part Number: P607306 Description: AIR PANEL, VENTILATION Primary App: Mitsubishi MD620472 Dimensions: Width: 8.88" (226 mm) Depth: 8.88" (226 mm) Height: 1.54" (39 mm)</p>



















	<p>Part Number: P607308 Description: AIR PRIMARY Primary App: GMC 6422214, 25177939 Dimensions: Outer Diameter: 8.60" (218 mm) Inner Diameter: 7.60" (193 mm) Length: 7.00" (178 mm)</p>		<p>Part Number: P607331 Description: AIR PRIMARY Primary App: Ford E1VZ-9601-A, F1UZ-9601-A Dimensions: Outer Diameter: 11.63" (295 mm) Inner Diameter: 8.38" (213 mm) Length: 4.42" (112 mm)</p>
	<p>Part Number: P607314 Description: AIR PRIMARY, SPECIAL Foam Blanket for PA1765 Dimensions: Width: 24.00" (610 mm) Depth: 26.00" (660 mm) Height: 0.50" (13 mm)</p>		<p>Part Number: P607332 Description: AIR PANEL, VENTILATION Primary App: GMC 25098522; Toyota 17801-74020 Dimensions: Width: 12.20" (310 mm) Depth: 6.10" (155 mm) Height: 1.55" (39 mm)</p>
	<p>Part Number: P607317 Description: AIR PANEL, VENTILATION Primary App: Chrysler 53006317; Volkswagen 34133837 Dimensions: Width: 13.18" (335 mm) Depth: 5.25" (133 mm) Height: 1.65" (42 mm)</p>		<p>Part Number: P607333 Description: AIR PANEL, VENTILATION Primary App: GMC 25097917 Dimensions: Width: 13.77" (350 mm) Depth: 4.16" (106 mm) Height: 1.65" (42 mm)</p>
	<p>Part Number: P607323 Description: AIR PANEL Primary App: GMC 24508572; ACDelco A1614C; GMC 25096932 Dimensions: Width: 10.68" (271 mm) Depth: 7.95" (202 mm) Height: 1.62" (41 mm)</p>		<p>Part Number: P607334 Description: AIR PRIMARY Primary App: GMC 8994224 Dimensions: Outer Diameter: 20.73" (527 mm) Inner Diameter: 10.58" (269 mm) Length: 7.53" (191 mm)</p>
	<p>Part Number: P607324 Description: AIR PRIMARY Primary App: GMC 94213709; Isuzu 8-94206-007-0 Dimensions: Outer Diameter: 10.31" (262 mm) Inner Diameter: 7.94" (202 mm) Length: 0.41" (10 mm)</p>		<p>Part Number: P607336 Description: AIR PRIMARY Primary App: Mitsubishi MD620047 Dimensions: Outer Diameter: 9.16" (233 mm) Inner Diameter: 6.80" (173 mm) Length: 7.53" (191 mm)</p>
	<p>Part Number: P607325 Description: AIR PRIMARY Primary App: Atlas Copco 1503-0190 Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 3.56" (90 mm) Length: 2.78" (71 mm)</p>		<p>Part Number: P607338 Description: AIR PANEL, VENTILATION Primary App: Honda 17220-P0A-A00; Isuzu 5-86202-255-0 Dimensions: Width: 7.24" (184 mm) Depth: 11.91" (303 mm) Height: 2.01" (51 mm)</p>
	<p>Part Number: P607326 Description: AIR PRIMARY Primary App: GMC 25043119 Dimensions: Outer Diameter: 5.75" (146 mm) Inner Diameter: 3.64" (92 mm) Length: 4.94" (125 mm)</p>		<p>Part Number: P607340 Description: AIR SECONDARY Primary App: Case K200380 Dimensions: Outer Diameter: 2.97" (75 mm) Inner Diameter: 1.86" (47 mm) Length: 9.94" (252 mm)</p>
	<p>Part Number: P607328 Description: AIR PRIMARY Primary App: Atlas Copco 16191269; Petter CF4223LT Dimensions: Outer Diameter: 5.44" (138 mm) Inner Diameter: 3.25" (83 mm) Length: 4.75" (121 mm)</p>		<p>Part Number: P607342 Description: AIR PRIMARY Primary App: Ford F7CZ-9601-A Dimensions: Outer Diameter: 6.87" (174 mm) Inner Diameter: 3.41" (87 mm) Length: 7.90" (201 mm)</p>
	<p>Part Number: P607329 Description: AIR PRIMARY Primary App: Nissan 16546-48200 Dimensions: Outer Diameter: 6.38" (162 mm) Inner Diameter: 3.69" (94 mm) Length: 5.00" (127 mm)</p>		<p>Part Number: P607343 Description: AIR SECONDARY Primary App: Ford E9NN-9R500-AB; New Holland 82008601 Dimensions: Outer Diameter: 4.34" (110 mm) Inner Diameter: 3.00" (76 mm) Length: 11.57" (294 mm)</p>

	<p>Part Number: P607345 Description: AIR PRIMARY, FINNED Primary App: John Deere AM108243 Dimensions: Outer Diameter: 4.25" (108 mm) Inner Diameter: 2.22" (56 mm) Length: 7.13" (181 mm)</p>		<p>Part Number: P607360 Description: AIR PRIMARY Primary App: Endustra 51049; Torit 8PP18803-00 Dimensions: Outer Diameter: 7.94" (202 mm) Inner Diameter: 3.59" (91 mm) Length: 16.50" (419 mm)</p>
	<p>Part Number: P607346 Description: AIR PANEL, VENTILATION Primary App: Honda 17220-PAA-000, 17220-PAA-A00 Dimensions: Width: 10.77" (274 mm) Depth: 6.61" (168 mm) Height: 1.74" (44 mm)</p>		<p>Part Number: P607361 Description: AIR PRIMARY Primary App: Chrysler 5011836AA Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 3.33" (85 mm) Length: 6.25" (159 mm)</p>
	<p>Part Number: P607348 Description: AIR PANEL, VENTILATION Primary App: Chrysler 459110AB, 4591100AC Dimensions: Width: 9.52" (242 mm) Depth: 7.03" (179 mm) Length: 1.44" (37 mm)</p>		<p>Part Number: P607362 Description: AIR PRIMARY Primary App: Endustra 51055S Dimensions: Outer Diameter: 12.78" (325 mm) Inner Diameter: 0.50" (13 mm) Length: 26.50" (673 mm)</p>
	<p>Part Number: P607350 Description: AIR PRIMARY Primary App: John Deere AL65051 Dimensions: Outer Diameter: 5.24" (133 mm) Inner Diameter: 3.25" (83 mm) Length: 12.50" (318 mm)</p>		<p>Part Number: P607365 Description: AIR PRIMARY Primary App: John Deere RE46310 Dimensions: Outer Diameter: 9.04" (230 mm) Inner Diameter: 5.80" (147 mm) Length: 17.17" (436 mm)</p>
	<p>Part Number: P607351 Description: AIR PRIMARY Primary App: Ford E9NN-9B618-BA; New Holland 82003726 Dimensions: Outer Diameter: 8.04" (204 mm) Inner Diameter: 3.75" (95 mm) Length: 13.12" (333 mm)</p>		<p>Part Number: P607366 Description: AIR PRIMARY Primary App: International 627114-C1 Dimensions: Outer Diameter: 6.59" (167 mm) Inner Diameter: 3.81" (97 mm) Length: 17.33" (440 mm)</p>
	<p>Part Number: P607352 Description: AIR PRIMARY Primary App: John Deere AT76215 Dimensions: Outer Diameter: 7.31" (186 mm) Inner Diameter: 4.00" (102 mm) Length: 13.38" (340 mm)</p>		<p>Part Number: P607367 Description: AIR PRIMARY Primary App: Torit 8PP18583-01 Dimensions: Outer Diameter: 12.69" (322 mm) Inner Diameter: 8.38" (213 mm) Length: 22.50" (572 mm)</p>
	<p>Part Number: P607353 Description: AIR PRIMARY Primary App: Ford D5NN-9B618-B Dimensions: Outer Diameter: 10.06" (256 mm) Inner Diameter: 5.68" (144 mm) Length: 16.38" (416 mm)</p>		<p>Part Number: P607369 Description: AIR PRIMARY Primary App: Ingersoll-Rand 36864361 Dimensions: Outer Diameter: 13.75" (349 mm) Inner Diameter: 9.50" (241 mm) Length: 27.50" (699 mm)</p>
	<p>Part Number: P607355 Description: AIR PANEL, VENTILATION Primary App: Waukesha 169180A, 169180C Dimensions: Width: 19.50" (495 mm) Depth: 25.50" (648 mm) Height: 6.13" (156 mm)</p>		<p>Part Number: P607370 Description: AIR SECONDARY Primary App: Ingersoll-Rand 36864379 Dimensions: Outer Diameter: 9.25" (235 mm) Inner Diameter: 8.00" (203 mm) Length: 25.20" (640 mm)</p>
	<p>Part Number: P607359 Description: AIR PRIMARY Primary App: New Holland 9846494 Dimensions: Outer Diameter: 9.88" (251 mm) Inner Diameter: 6.00" (152 mm) Length: 16.00" (406 mm)</p>		<p>Part Number: P607371 Description: AIR PRIMARY Primary App: Quincy 234583; Worthington ELM64 Dimensions: Outer Diameter: 12.56" (319 mm) Inner Diameter: 7.50" (191 mm) Length: 21.00" (533 mm)</p>

	<p>Part Number: P607373 Description: AIR CLEANER, DISPOSABLE Primary App: FARR 400292-000, 400292-000-A Dimensions: Body Diameter: 11.50" (292 mm) Outlet ID: 7.00" (178 mm) Length: 16.88" (429 mm)</p>		<p>Part Number: P608300 Description: AIR SAFETY Primary App: Freightliner M2 Series Emergency Vehicles, Flame Retardant Dimensions: Outer Diameter: 6.89" (175 mm) Inner Diameter: 5.89" (150 mm) Length: 14.23" (361 mm)</p>
	<p>Part Number: P607374 Description: AIR PRIMARY Primary App: FARR 117122-000 Dimensions: Outer Diameter: 10.92" (277 mm) Inner Diameter: 6.75" (171 mm) Length: 25.56" (649 mm)</p>		<p>Part Number: P608305 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSON SSG SERIES RADIAL SEAL AIR CLEANERS Dimensions: Outer Diameter: 11.61" (295 mm) Inner Diameter: 9.29" (236 mm) Length: 22.31" (567 mm)</p>
	<p>Part Number: P607377 Description: AIR PRIMARY Primary App: Farr 119862-001, 119862-001G; Thomas 61100179 Dimensions: Outer Diameter: 9.67" (246 mm) Inner Diameter: 6.00" (152 mm) Length: 19.80" (503 mm)</p>		<p>Part Number: P608306 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON SSG SERIES RADIAL SEAL AIR CLEANERS Dimensions: Outer Diameter: 17.76" (451 mm) Inner Diameter: 11.46" (291 mm) Length: 24.06" (611 mm)</p>
	<p>Part Number: P607557 Description: AIR SAFETY, OVAL Primary App: DONALDSON PSD12 SERIES POWERCORE Dimensions: Width: 9.47" (241 mm) Height: 1.57" (40 mm) Length: 14.47" (368 mm)</p>		<p>Part Number: P608391 Description: AIR SAFETY, KONEPAC™ Primary App: DONALDSON XRB12 SERIES Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 4.31" (110 mm) Length: 19.65" (499 mm)</p>
<p>Part Number: P607673 Description: BREATHER, CYLINDRICAL Primary App: DONALDSON SPIRACLE BREATHER ELEMENT Dimensions: Outer Diameter: 5.09" (129 mm) Inner Diameter: 2.13" (54 mm) Length: 7.59" (193 mm)</p>		<p>Part Number: P608533 Description: AIR PRIMARY, PowerCore® Primary App: DONALDSON PSD08 SERIES POWERCORE Dimensions: Width: 5.82" (148 mm) Height: 7.13" (181 mm) Length: 9.83" (250 mm)</p>	
	<p>Part Number: P607955 Description: AIR PRIMARY, PowerCore® Primary App: FREIGHTLINER M2 SERIES Dimensions: Outer Diameter: 12.85" (326 mm) Length: 7.99" (203 mm)</p>		<p>Part Number: P608599 Description: AIR SAFETY, KONEPAC™ Primary App: DONALDSON FKB06 SERIES Dimensions: Outer Diameter: 3.56" (90 mm) Inner Diameter: 2.44" (62 mm) Length: 12.80" (325 mm)</p>
	<p>Part Number: P607960 Description: AIR PRIMARY, PowerCore® Primary App: FREIGHTLINER M2 SERIES FLAME RETARDANT Dimensions: Outer Diameter: 12.84" (326 mm) Length: 7.99" (203 mm)</p>		<p>Part Number: P608653 Description: AIR PRIMARY Primary App: BULK TANKS Dimensions: Outer Diameter: 11.03" (280 mm) Inner Diameter: 5.84" (148 mm) Length: 19.38" (492 mm)</p>
	<p>Part Number: P607965 Description: AIR PRIMARY, PowerCore® Primary App: FREIGHTLINER M2 SERIES HIGH HP Dimensions: Outer Diameter: 14.84" (377 mm) Length: 7.99" (203 mm)</p>		<p>Part Number: P608654 Description: AIR PRIMARY Primary App: FARR T520D Dimensions: Outer Diameter: 7.16" (182 mm) Inner Diameter: 6.01" (153 mm) Length: 3.00" (76 mm)</p>
	<p>Part Number: P608116 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON XRB12 SERIES Dimensions: Outer Diameter: 12.20" (310 mm) Inner Diameter: 4.45" (113 mm) Length: 20.41" (519 mm)</p>		<p>Part Number: P608665 Description: AIR PRIMARY, PowerCore® Primary App: DONALDSON PSD09 SERIES POWERCORE Dimensions: Width: 4.75" (121 mm) Height: 7.26" (184 mm) Length: 12.54" (319 mm)</p>

	<p>Part Number: P608666 Description: AIR PRIMARY, PowerCore® Primary App: DONALDSON PSD10 SERIES POWERCORE Dimensions: Width: 8.05" (204 mm) Height: 7.35" (187 mm) Length: 13.41" (341 mm)</p>		<p>Part Number: P609221 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON FKB06 SERIES Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 5.12" (130 mm) Length: 13.03" (331 mm)</p>
	<p>Part Number: P608667 Description: AIR PRIMARY, PowerCore® Primary App: DONALDSON PSD12 SERIES POWERCORE Dimensions: Width: 10.00" (254 mm) Height: 9.31" (236 mm) Length: 15.06" (383 mm)</p>		<p>Part Number: P609239 Description: AIR SAFETY Primary App: INTERNATIONAL TRUCKS 3532800C1 Dimensions: Outer Diameter: 8.09" (206 mm) Inner Diameter: 5.28" (134 mm) Length: 15.25" (387 mm)</p>
	<p>Part Number: P608675 Description: AIR PRIMARY, PowerCore® Primary App: DONALDSON PSD09 SERIES POWERCORE Dimensions: Width: 7.39" (188 mm) Height: 11.20" (285 mm) Length: 12.56" (319 mm)</p>	<p>Part Number: P609421 Description: AIR PANEL Primary App: FARR 55445011, RC250 Dimensions: Width: 14.00" (356 mm) Depth: 5.31" (135 mm) Height: 36.44" (926 mm)</p>	
	<p>Part Number: P608676 Description: AIR PRIMARY, PowerCore® Primary App: DONALDSON PSD10 SERIES POWERCORE Dimensions: Width: 7.86" (200 mm) Height: 11.07" (281 mm) Length: 13.05" (331 mm)</p>		<p>Part Number: P609422 Description: AIR PANEL, VENTILATION Primary App: FREIGHTLINER 91559, BOA91559 Dimensions: Width: 10.63" (270 mm) Depth: 10.63" (270 mm) Height: 0.98" (25 mm) Efficiency 95% @ 5 Micron</p>
	<p>Part Number: P608677 Description: AIR PRIMARY, PowerCore® Primary App: DONALDSON PSD12 SERIES POWERCORE Dimensions: Width: 10.06" (256 mm) Height: 13.25" (337 mm) Length: 15.06" (383 mm)</p>		<p>Part Number: P609444 Description: AIR PANEL, VENTILATION Primary App: Caterpillar 1707272 Dimensions: Width: 9.75" (248 mm) Depth: 1.03" (26 mm) Height: 15.30" (389 mm)</p>
	<p>Part Number: P608766 Description: AIR PRIMARY, PowerCore® Primary App: CATERPILLAR BACKHOE LOADER Dimensions: Width: 6.42" (163 mm) Height: 6.89" (175 mm) Length: 9.06" (230 mm)</p>		<p>Part Number: P609445 Description: AIR PANEL, VENTILATION Primary App: Caterpillar 1167376 Dimensions: Width: 7.07" (180 mm) Depth: 1.44" (37 mm) Height: 12.50" (318 mm)</p>
	<p>Part Number: P608885 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON FRG15, KOMATSU 6001856110 Dimensions: Outer Diameter: 12.34" (314 mm) Inner Diameter: 6.99" (178 mm) Length: 20.08" (510 mm)</p>		<p>Part Number: P609446 Description: AIR PANEL, VENTILATION Primary App: Caterpillar 9X8216 Dimensions: Width: 5.98" (152 mm) Depth: 2.19" (56 mm) Height: 26.96" (685 mm)</p>
	<p>Part Number: P609086 Description: AIR PRIMARY, PowerCore® Primary App: FORD F-SERIES F650, F750 6.0L DIESEL Dimensions: Height: 9.11" (232 mm) Width: 7.09" (180 mm) Length: 11.57" (295 mm)</p>		<p>Part Number: P609447 Description: AIR PRIMARY, RADIALSEAL Primary App: Caterpillar 1491912 Dimensions: Outer Diameter: 6.47" (164 mm) Inner Diameter: 3.58" (91 mm) Length: 11.42" (290 mm)</p>
	<p>Part Number: P609218 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON FKB05 SERIES Dimensions: Outer Diameter: 4.79" (122 mm) Inner Diameter: 4.03" (102 mm) Length: 12.92" (328 mm)</p>		<p>Part Number: P609518 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSON SSG SERIES RADIAL SEAL AIR CLEANERS Dimensions: Outer Diameter: 11.61" (295 mm) Inner Diameter: 9.29" (236 mm) Length: 27.40" (696 mm)</p>













	<p>Part Number: P609519 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON SSG SERIES RADIAL SEAL AIR CLEANERS Dimensions: Outer Diameter: 17.76" (451 mm) Inner Diameter: 11.46" (291 mm) Length: 29.25" (743 mm)</p>		<p>Part Number: P611189 Description: AIR SAFETY Primary App: DONALDSON XRB08 SERIES Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 4.13" (104 mm) Length: 14.40" (366 mm)</p>
	<p>Part Number: P610485 Description: AIR SAFETY Primary App: MISC INDUSTRIAL APPLICATIONS Dimensions: Outer Diameter: 7.88" (200 mm) Inner Diameter: 4.13" (105 mm) Length: 11.15" (283 mm)</p>		<p>Part Number: P611190 Description: AIR PRIMARY Primary App: DONALDSON XRB08 SERIES Dimensions: Outer Diameter: 7.66" (195 mm) Inner Diameter: 4.61" (117 mm) Length: 14.13" (359 mm)</p>
	<p>Part Number: P610489 Description: AIR SAFETY, RADIALSEAL Primary App: CATERPILLAR 1805475 Dimensions: Outer Diameter: 3.46" (88 mm) Inner Diameter: 2.92" (74 mm) Length: 12.02" (305 mm)</p>		<p>Part Number: P611440 Description: AIR PRIMARY Primary App: JOHN DEERE RE24619, RE67829 Dimensions: Outer Diameter: 6.84" (174 mm) Inner Diameter: 3.48" (88 mm) Length: 12.00" (305 mm) D: 4.91" (125 mm) Gasket ID: 3.95" (100 mm)</p>
	<p>Part Number: P610561 Description: AIR PANEL Primary App: Chrysler 53032700A Dimensions: Width: 10.00" (254 mm) Depth: 10.75" (273 mm) Height: 1.99" (51 mm)</p>		<p>Part Number: P611539 Description: AIR PRIMARY, KONEPAC™ Primary App: DONALDSON XRB10 SERIES Dimensions: Outer Diameter: 9.96" (253 mm) Inner Diameter: 5.69" (145 mm) Length: 18.85" (479 mm)</p>
	<p>Part Number: P610696 Description: AIR SAFETY Primary App: John Deere RE46311 Dimensions: Outer Diameter: 5.69" (145 mm) Inner Diameter: 4.50" (114 mm) Length: 14.88" (378 mm)</p>		<p>Part Number: P611540 Description: AIR SAFETY, KONEPAC™ Primary App: DONALDSON XRB10 SERIES Dimensions: Outer Diameter: 5.30" (135 mm) Inner Diameter: 3.70" (94 mm) Length: 17.44" (443 mm)</p>
	<p>Part Number: P610875 Description: AIR PRIMARY, PowerCore® Primary App: GM SILVERADO, SIERRA 6.6L DURAMAX DIESEL Dimensions: Outer Diameter: 9.26" (235 mm) Length: 6.28" (160 mm)</p>		<p>Part Number: P611720 Description: AIR PRIMARY, PowerCore® Primary App: CHEVROLET EXPRESS VAN Dimensions: Width: 6.00" (152 mm) Height: 6.31" (160 mm) Length: 11.16" (283 mm)</p>
	<p>Part Number: P610903 Description: AIR PRIMARY, RADIALSEAL Primary App: TOYOTA 177432360071, 177412360071 Dimensions: Outer Diameter: 5.44" (138 mm) Inner Diameter: 3.20" (81 mm) Length: 10.71" (272 mm)</p>		<p>Part Number: P611856 Description: AIR PRIMARY, RADIALSEAL Primary App: John Deere AT225338 Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.15" (131 mm) Length: 16.49" (419 mm)</p>
	<p>Part Number: P610904 Description: AIR SAFETY, RADIALSEAL Primary App: TOYOTA 177442360071 Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 2.55" (65 mm) Length: 10.42" (265 mm)</p>		<p>Part Number: P611857 Description: AIR SAFETY Primary App: John Deere AT225339 Dimensions: Outer Diameter: 5.30" (135 mm) Inner Diameter: 3.70" (94 mm) Length: 16.21" (412 mm)</p>
	<p>Part Number: P610905 Description: AIR PRIMARY, RADIALSEAL Primary App: TOYOTA 17743U110071 Dimensions: Outer Diameter: 5.44" (138 mm) Inner Diameter: 3.20" (81 mm) Length: 10.71" (272 mm)</p>		<p>Part Number: P611858 Description: AIR PRIMARY, KONEPAC™ Primary App: Hyster 1559418, Yale 580048838 Dimensions: Outer Diameter: 4.09" (104 mm) Length: 10.52" (267 mm)</p>

	<p>Part Number: P611859 Description: AIR PRIMARY, KONEPAC™ Primary App: Hyster 1574111, Yale 580053908 Dimensions: Outer Diameter: 4.81" (122 mm) Length: 12.86" (327 mm)</p>		<p>Part Number: P613336 Description: AIR PRIMARY Primary App: INTERNATIONAL 3551814C1 Dimensions: Outer Diameter: 12.01" (305 mm) Inner Diameter: 9.90" (251 mm) Length: 16.10" (409 mm)</p>
	<p>Part Number: P612469 Description: AIR PRIMARY, RADIALSEAL Primary App: JOHN DEERE AH164062 Dimensions: Outer Diameter: 13.09" (332 mm) Inner Diameter: 6.78" (172 mm) Length: 22.86" (581 mm)</p>		<p>Part Number: P613337 Description: AIR SAFETY Primary App: International 3551815C1 Dimensions: Outer Diameter: 9.94" (252 mm) Inner Diameter: 5.37" (136 mm) Length: 15.44" (392 mm)</p>
	<p>Part Number: P612470 Description: AIR SAFETY, RADIALSEAL Primary App: JOHN DEERE AH164063 Dimensions: Outer Diameter: 6.89" (175 mm) Inner Diameter: 5.24" (133 mm) Length: 22.32" (567 mm)</p>		<p>Part Number: P613439 Description: AIR PRIMARY Primary App: LETOURNEAU 4219820 Dimensions: Outer Diameter: 13.85" (352 mm) Inner Diameter: 10.12" (257 mm) Length: 22.00" (559 mm)</p>
	<p>Part Number: P612815 Description: AIR PANEL, VENTILATION Primary App: VOLVO 3948712 Dimensions: Width: 8.43" (214 mm) Length: 12.36" (314 mm) Height: 0.80" (20 mm)</p>		<p>Part Number: P613522 Description: AIR PRIMARY, PowerCore® Primary App: FORD F SERIES 6.4L DIESEL Dimensions: Width: 6.04" (153 mm) Height: 8.78" (223 mm) Length: 12.21" (310 mm)</p>
	<p>Part Number: P612826 Description: AIR PANEL, ENGINE Primary App: Mercedes 0040942604 Dimensions: Width: 10.87" (276 mm) Depth: 2.36" (60 mm) Height: 12.40" (315 mm)</p>		<p>Part Number: P613679 Description: AIR CLEANER, DISPOSABLE Primary App: FARR ECO SE 114880005 Dimensions: Body Diameter: 7.75" (197 mm) Length: 17.20" (437 mm) Outlet ID: 4.00" (102 mm) Inlet Location: 5.54" (141 mm) F: 1.56" (40 mm) G: 4.50" (114 mm) H: 8.12" (206 mm) J: 1.25" (32 mm)</p>
	<p>Part Number: P612827 Description: AIR PANEL, VENTILATION Primary App: Mercedes 008303318 Dimensions: Width: 6.34" (162 mm) Depth: 14.41" (366 mm) Height: 1.12" (28 mm)</p>		<p>Part Number: P613926 Description: AIR SAFETY, RADIALSEAL Primary App: Volvo 8079756 Dimensions: Outer Diameter: 7.90" (201 mm) Inner Diameter: 6.24" (158 mm) Length: 15.47" (393 mm)</p>
	<p>Part Number: P613333 Description: AIR PRIMARY Primary App: Cummins/Fleetguard AF25708M Dimensions: Outer Diameter: 11.00" (279 mm) Inner Diameter: 7.93" (201 mm) Length: 20.44" (519 mm)</p>		<p>Part Number: P614220 Description: AIR PANEL, VENTILATION Primary App: FREIGHTLINER CENTURY Dimensions: Width: 10.07" (256 mm) Depth: 10.67" (271 mm) Height: 0.68" (17 mm)</p>
	<p>Part Number: P613334 Description: AIR PRIMARY Primary App: JOHN DEERE AT300487 Dimensions: Outer Diameter: 8.84" (225 mm) Inner Diameter: 7.14" (182 mm) Length: 16.74" (425 mm)</p>		<p>Part Number: P614221 Description: AIR PANEL, VENTILATION Primary App: INTERNATIONAL 4200, 4300, 4400, 7600, 8600 Dimensions: Width: 7.21" (183 mm) Depth: 12.49" (317 mm) Height: 0.99" (25 mm)</p>
	<p>Part Number: P613335 Description: AIR SAFETY Primary App: JOHN DEERE AT300488, AT314583 Dimensions: Outer Diameter: 4.81" (122 mm) Inner Diameter: 3.63" (92 mm) Length: 15.96" (405 mm)</p>		<p>Part Number: P614222 Description: AIR PANEL, VENTILATION Primary App: KENWORTH T2000 Dimensions: Width: 10.07" (256 mm) Depth: 13.97" (355 mm) Height: 0.68" (17 mm)</p>










	<p>Part Number: P614223 Description: AIR PANEL, VENTILATION Primary App: PETERBILT 379 Dimensions: Width: 8.12" (206 mm) Depth: 11.94" (303 mm) Height: 0.79" (20 mm)</p>		<p>Part Number: P614544 Description: AIR PANEL, VENTILATION Primary App: JOHN DEERE RE48882 Dimensions: Width: 7.18" (182 mm) Depth: 9.03" (229 mm) Height: 1.63" (41 mm)</p>
	<p>Part Number: P614224 Description: AIR PANEL, VENTILATION Primary App: PETERBILT 379 Dimensions: Width: 6.81" (173 mm) Depth: 10.94" (278 mm) Height: 0.68" (17 mm)</p>		<p>Part Number: P614545 Description: AIR PANEL Primary App: CHRYSLER 5019002AA, 5037615AA Dimensions: Height: 8.28" (210 mm) Depth: 1.51" (38 mm) Width: 11.50" (292 mm)</p>
	<p>Part Number: P614225 Description: AIR PANEL, VENTILATION Primary App: FREIGHTLINER COLUMBIA & CORONADO Dimensions: Width: 7.68" (195 mm) Depth: 8.59" (218 mm) Height: 0.71" (18 mm)</p>		<p>Part Number: P614546 Description: AIR PANEL, VENTILATION Primary App: FREIGHTLINER 803190013701 Dimensions: Height: 7.62" (194 mm) Width: 8.66" (220 mm) Depth: 0.98" (25 mm)</p>
	<p>Part Number: P614226 Description: AIR PANEL, VENTILATION Primary App: FREIGHTLINER CENTURY Dimensions: Width: 12.61" (320 mm) Depth: 13.40" (340 mm) Height: 0.32" (8 mm)</p>		<p>Part Number: P614547 Description: AIR PANEL, VENTILATION Primary App: FREIGHTLINER VCC36000006 Dimensions: Height: 8.62" (219 mm) Width: 8.39" (213 mm) Depth: 0.98" (25 mm)</p>
	<p>Part Number: P614227 Description: AIR PANEL, VENTILATION Primary App: INTERNATIONAL 9670 & 4300 Dimensions: Width: 12.61" (320 mm) Depth: 13.40" (340 mm) Height: 0.79" (20 mm)</p>		<p>Part Number: P614563 Description: AIR PRIMARY, RADIALSEAL Primary App: CHEVROLET KODIAK, GMC TOPKICK, C4500 & C5500 SERIES Dimensions: Outer Diameter: 7.80" (198 mm) Inner Diameter: 4.40" (111 mm) Length: 17.40" (442 mm)</p>
	<p>Part Number: P614228 Description: AIR PANEL, VENTILATION Primary App: VOLVO VN Dimensions: Width: 6.46" (164 mm) Depth: 6.46" (164 mm) Height: 0.32" (8 mm)</p>		<p>Part Number: P614876 Description: AIR PRIMARY, RADIALSEAL Primary App: CHEVROLET KODIAK, GMC TOPKICK Dimensions: Outer Diameter: 7.62" (194 mm) Inner Diameter: 4.56" (116 mm) Length: 18.35" (466 mm)</p>
	<p>Part Number: P614476 Description: AIR PANEL, VENTILATION Primary App: CATERPILLAR EQUIPMENT Dimensions: Width: 8.91" (227 mm) Depth: 1.82" (46 mm) Height: 11.27" (287 mm)</p>		<p>Part Number: P615748 Description: AIR PANEL Primary App: VW 7H0129620A Dimensions: Width: 7.48" (190 mm) Height: 2.28" (58 mm) Length: 12.28" (312 mm)</p>
	<p>Part Number: P614541 Description: AIR PANEL, ENGINE Primary App: MERCEDES 0000902651 Dimensions: Width: 10.40" (265 mm) Depth: 14.00" (355 mm) Height: 2.29" (58 mm)</p>		<p>Part Number: P616056 Description: AIR PRIMARY, PowerCore® Primary App: KENWORTH T660/T800 Dimensions: Width: 9.96" (253 mm) Height: 9.84" (250 mm) Length: 17.35" (440.8 mm)</p>
	<p>Part Number: P614542 Description: AIR PANEL Primary App: FORD E-SERIES VAN 4C2U9601AB Dimensions: Width: 6.79" (172 mm) Depth: 12.29" (312 mm) Height: 3.30" (84 mm)</p>		<p>Part Number: P616081 Description: AIR PRIMARY, RADIALSEAL Primary App: Reytor IT2000 Dimensions: Outer Diameter: 9.97" (253 mm) Inner Diameter: 4.85" (123 mm) Length: 15.50" (394 mm) Efficiency @ 99% Percent</p>
	<p>Part Number: P614543 Description: AIR PANEL Primary App: FORD/LINCOLN LIGHT DUTY TRUCK 4L3Z9601BA Dimensions: Height: 8.50" (216 mm) Width: 11.30" (287 mm) Depth: 1.41" (36 mm)</p>		<p>Part Number: P616082 Description: AIR SAFETY, RADIALSEAL Primary App: Reytor IT2000S Dimensions: Outer Diameter: 5.06" (128 mm) Inner Diameter: 4.00" (102 mm) Length: 14.62" (371 mm) Efficiency @ 96.50 Percent</p>



	<p>Part Number: P616400 Description: AIR SAFETY Primary App: FREIGHTLINER M2 SERIES Dimensions: Outer Diameter: 9.31" (237 mm) Length: 1.39" (35 mm)</p>		<p>Part Number: P617644 Description: AIR SAFETY Primary App: FLEETGUARD 1300 SERIES OPTIAIR Dimensions: Outer Diameter: 8.04" (204 mm) Inner Diameter: 5.00" (127 mm) Length: 19.52" (496 mm)</p>
	<p>Part Number: P616641 Description: AIR PRIMARY Primary App: CARRIER 300042624, 300042627 Dimensions: Outer Diameter: 4.16" (106 mm) Inner Diameter: 3.00" (76 mm) Length: 10.70" (272 mm) Efficiency @ 99% Percent</p>		<p>Part Number: P617645 Description: AIR SAFETY Primary App: JOHN DEERE RE210103 Dimensions: Outer Diameter: 7.17" (182 mm) Inner Diameter: 5.79" (147 mm) Length: 11.73" (298 mm)</p>
	<p>Part Number: P616648 Description: AIR PRIMARY Primary App: CUMMINS ENGINES Dimensions: Outer Diameter: 10.41" (264 mm) Inner Diameter: 7.78" (198 mm) Length: 12.00" (305 mm)</p>		<p>Part Number: P617646 Description: AIR PRIMARY Primary App: JOHN DEERE RE210102 Dimensions: Outer Diameter: 12.13" (308 mm) Inner Diameter: 7.83" (199 mm) Length: 12.68" (322 mm)</p>
	<p>Part Number: P616742 Description: AIR PRIMARY, KONEPAC™ Primary App: HYSTER 1620142, YALE 580069337 Dimensions: Outer Diameter: 5.94" (151 mm) Length: 13.03" (331 mm)</p>		<p>Part Number: P618642 Description: AIR PANEL Primary App: Cat Industrial Trucks - Cabin Air Dimensions: Width: 7.87" (200 mm) Depth: 15.95" (405 mm) Height: 2.57" (65 mm)</p>
	<p>Part Number: P616743 Description: AIR PANEL, ENGINE Primary App: DODGE RAM PICKUP, 6.7L CUMMINS DIESEL Dimensions: Width: 10.93" (278 mm) Depth: 9.91" (252 mm) Height: 4.38" (111 mm)</p>		<p>Part Number: P618643 Description: AIR PANEL, VENTILATION Primary App: JOHN DEERE T156471 Dimensions: Width: 8.58" (218 mm) Length: 16.36" (416 mm) Depth: 1.05" (27 mm)</p>
	<p>Part Number: P616850 Description: AIR PANEL Primary App: CAT EXCAVATORS Dimensions: Width: 5.30" (135 mm) Depth: 9.65" (245 mm) Height: 0.77" (20 mm)</p>		<p>Part Number: P618644 Description: AIR PANEL, VENTILATION Primary App: JOHN DEERE RE70742 Dimensions: Width: 6.60" (168 mm) Depth: 12.60" (320 mm) Height: 1.88" (48 mm)</p>
	<p>Part Number: P616898 Description: AIR PANEL, VENTILATION Primary App: MERCEDES 9068300318 Dimensions: Width: 13.84" (352 mm) Depth: 1.38" (35 mm) Height: 9.21" (234 mm)</p>		<p>Part Number: P618921 Description: AIR PRIMARY Primary App: CLARK EG1; EMD 8470903; GE 41A218313P1 Dimensions: Width: 29.37" (746 mm) Height: 27.38" (695 mm) Depth: 6.37" (162 mm)</p>
	<p>Part Number: P617005 Description: AIR PANEL, VENTILATION Primary App: NAVISTAR 1699956C1 Dimensions: Width: 9.97" (253 mm) Depth: 13.61" (346 mm) Height: 0.60" (15 mm)</p>		<p>Part Number: P618922 Description: AIR PRIMARY Primary App: CLARK EG2, EMD9522063 Dimensions: Length: 18.75" (476 mm) Width: 5.00" (127 mm) Height: 22.00" (559 mm)</p>
	<p>Part Number: P617283 Description: AIR SAFETY, RADIALSEAL Primary App: CHEVROLET KODIAK, GMC TOPKICK Dimensions: Outer Diameter: 4.45" (113 mm) Inner Diameter: 3.31" (84 mm) Length: 17.72" (450 mm)</p>		<p>Part Number: P619334 Description: AIR PRIMARY, PowerCore® Primary App: JOHN DEERE RE196945 Dimensions: Outer Diameter: 10.33" (262 mm) Length: 9.16" (233 mm)</p>
	<p>Part Number: P617643 Description: AIR PRIMARY Primary App: FLEETGUARD 1300 SERIES OPTIAIR Dimensions: Outer Diameter: 10.31" (262 mm) Inner Diameter: 8.03" (204 mm) Length: 20.47" (520 mm)</p>		<p>Part Number: P760155 Description: HYDRAULIC CARTRIDGE Primary App: MANITOU 21967 NOREMAT 121706 SOFRALUB 50715 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.65" (42 mm) Length: 7.64" (194 mm)</p>


<p>Part Number: P760173 Description: HYDRAULIC CARTRIDGE Primary App: FIOA 220/6 Dimensions: Outer Diameter: 3.90" (99 mm) Thread Size: G2 Length: 8.62" (219 mm)</p>	<p>Part Number: P761189 Description: HYDRAULIC CARTRIDGE Primary App: NEW HOLLAND 322736650 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.65" (42 mm) Length: 8.27" (210 mm)</p>
<p>Part Number: P760175 Description: STRAINER Primary App: FIOA 220/3 Dimensions: Outer Diameter: 3.98" (101 mm) Thread Size: G2 Length: 8.62" (219 mm)</p>	 <p>Part Number: P761207 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXX1110 Dimensions: Outer Diameter: 7.95" (202 mm) Inner Diameter: 0.06" (2 mm) Length: 17.32" (440 mm)</p>
 <p>Part Number: P760327 Description: HYDRAULIC CARTRIDGE Primary App: O & K 1425534 Dimensions: Outer Diameter: 1.81" (46 mm) Inner Diameter: 0.70" (18 mm) Length: 5.98" (152 mm) Efficiency 50% @ 44 Micron</p>	<p>Part Number: P761354 Description: HYDRAULIC CARTRIDGE Primary App: ATLAS 385673 Dimensions: Outer Diameter: 7.95" (202 mm) Inner Diameter: 0.06" (2 mm) Length: 12.99" (330 mm)</p>
<p>Part Number: P760796 Description: HYDRAULIC CARTRIDGE Primary App: AGCO 3818364M1 Dimensions: Outer Diameter: 0.43" (11 mm) Length: 1.73" (44 mm)</p>	<p>Part Number: P761387 Description: HYDRAULIC CARTRIDGE Primary App: NEW HOLLAND 5194879 Dimensions: Outer Diameter: 1.97" (50 mm) Inner Diameter: 0.94" (24 mm) Length: 4.45" (113 mm)</p>
 <p>Part Number: P760943 Description: HYDRAULIC CARTRIDGE Primary App: HYDAC 0140D010BNHC Dimensions: Outer Diameter: 1.81" (46 mm) Inner Diameter: 0.87" (22 mm) Length: 7.60" (193 mm) Efficiency 50% @ 2 Micron Efficiency 99% @ 10 Micron</p>	 <p>Part Number: P761424 Description: HYDRAULIC CARTRIDGE Primary App: NEW HOLLAND 45482320 Dimensions: Outer Diameter: 3.66" (93 mm) Inner Diameter: 1.89" (48 mm) Length: 12.60" (320 mm)</p>
<p>Part Number: P761040 Description: STRAINER Primary App: FAL Dimensions: Outer Diameter: 2.68" (68 mm) Inner Diameter: 1.50" (38 mm) Length: 8.19" (208 mm)</p>	<p>Part Number: P761490 Description: HYDRAULIC CARTRIDGE Primary App: ARGO K3102652 Dimensions: Outer Diameter: 3.89" (99 mm) Inner Diameter: 1.96" (50 mm) Length: 10.84" (275 mm) Efficiency 95% @ 2 Micron</p>
<p>Part Number: P761045 Description: HYDRAULIC CARTRIDGE Primary App: MAHLE Dimensions: Outer Diameter: 3.39" (86 mm) Inner Diameter: 1.73" (44 mm) Length: 2.36" (60 mm)</p>	<p>Part Number: P761995 Description: HYDRAULIC CARTRIDGE Primary App: CR800/6 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 15.75" (400 mm)</p>
<p>Part Number: P761051 Description: BREATHER Primary App: FS 7/1 Dimensions: Outer Diameter: 2.83" (72 mm) Thread Size: G 1/2 Inner Diameter: 2.52" (64 mm) Radius: 2.91" (74 mm)</p>	<p>Part Number: P761996 Description: HYDRAULIC CARTRIDGE Primary App: CR150/6 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.65" (42 mm) Length: 8.27" (210 mm)</p>
<p>Part Number: P761054 Description: HYDRAULIC CARTRIDGE Primary App: Hydraulic Assemblies, FBO CS4/1 Dimensions: Outer Diameter: 4.33" (110 mm) Inner Diameter: 2.95" (75 mm) Length: 3.23" (82 mm)</p>	<p>Part Number: P761997 Description: HYDRAULIC CARTRIDGE Primary App: CR220/6 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 5.35" (136 mm)</p>
<p>Part Number: P761093 Description: HYDRAULIC CARTRIDGE Primary App: FIAT 1930870 Dimensions: Outer Diameter: 5.91" (150 mm) Length: 12.99" (330 mm)</p>	<p>Part Number: P762091 Description: HYDRAULIC CARTRIDGE Dimensions: Outer Diameter: 4.45" (113 mm) Inner Diameter: 1.89" (48 mm) Length: 5.79" (147 mm)</p>
 <p>Part Number: P761108 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: SCANIA 1301696 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: M23 x 1.5 Length: 4.45" (113 mm)</p>	<p>Part Number: P762563 Description: HYDRAULIC CARTRIDGE Primary App: CASE 1930731 Dimensions: Outer Diameter: 5.91" (150 mm) Inner Diameter: 3.35" (85 mm) Length: 9.45" (240 mm)</p>

	<p>Part Number: P762756 Description: HYDRAULIC CARTRIDGE Primary App: MANN AND HUMMEL H7101 Dimensions: Outer Diameter: 2.72" (69 mm) Inner Diameter: 1.34" (34 mm) Length: 4.09" (104 mm)</p>		<p>Part Number: P763010 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXW5-GDL6 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 2.52" (64 mm) Length: 10.20" (259 mm)</p>
<p>Part Number: P762806 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 848100037 Dimensions: Outer Diameter: 5.51" (140 mm) Length: 13.58" (345 mm)</p>		<p>Part Number: P763014 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXW5A-GDL6 Dimensions: Outer Diameter: 4.17" (106 mm) Inner Diameter: 2.52" (64 mm) Length: 18.31" (465 mm)</p>	<p>Part Number: P762808 Description: STRAINER Dimensions: Outer Diameter: 3.74" (95 mm) Thread Size: G 1-1/4 Length: 7.24" (184 mm)</p>
<p>Part Number: P762810 Description: HYDRAULIC CARTRIDGE Primary App: CR600/03 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 9.88" (251 mm)</p>		<p>Part Number: P763016 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXW8C-GDL6 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 3.62" (92 mm) Length: 18.90" (480 mm) Efficiency 99% @ 5 Micron</p>	<p>Part Number: P762810 Description: HYDRAULIC CARTRIDGE Primary App: CR600/03 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 9.88" (251 mm)</p>
<p>Part Number: P762811 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 848101182 Dimensions: Outer Diameter: 5.51" (140 mm) Length: 9.72" (247 mm)</p>		<p>Part Number: P763018 Description: HYDRAULIC CARTRIDGE Primary App: FAIREY ARLON TXW8A-GDL6 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 3.62" (92 mm) Length: 11.42" (290 mm)</p>	<p>Part Number: P762811 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 848101182 Dimensions: Outer Diameter: 5.51" (140 mm) Length: 9.72" (247 mm)</p>
	<p>Part Number: P762860 Description: HYDRAULIC CARTRIDGE Primary App: MANN & HUMMEL H7101 Dimensions: Outer Diameter: 1.97" (50 mm) Inner Diameter: 0.94" (24 mm) Length: 6.22" (158 mm) Efficiency 99% @ 25 Micron</p>		<p>Part Number: P763034 Description: HYDRAULIC CARTRIDGE Primary App: PARKER 170L123 Dimensions: Outer Diameter: 2.20" (56 mm) Inner Diameter: 0.74" (19 mm) Length: 2.63" (67 mm) Efficiency 99% @ 25 Micron</p>
<p>Part Number: P762865 Description: HYDRAULIC CARTRIDGE Primary App: LUGLI, 39500017 Dimensions: Outer Diameter: 4.84" (123 mm) Inner Diameter: 3.94" (100 mm) Length: 11.14" (283 mm)</p>		<p>Part Number: P763081 Description: STRAINER Primary App: KOMATSU 848001062 Dimensions: Outer Diameter: 2.95" (75 mm) Thread Size: GAS 1 Length: 7.09" (180 mm)</p>	<p>Part Number: P762865 Description: HYDRAULIC CARTRIDGE Primary App: LUGLI, 39500017 Dimensions: Outer Diameter: 4.84" (123 mm) Inner Diameter: 3.94" (100 mm) Length: 11.14" (283 mm)</p>
	<p>Part Number: P762877 Description: HYDRAULIC CARTRIDGE Primary App: SCANIA 274108 Dimensions: Outer Diameter: 3.35" (85 mm) Inner Diameter: 3.30" (84 mm) Length: 3.34" (85 mm) Efficiency 99% @ 22 Micron</p>	<p>Part Number: P763182 Description: HYDRAULIC CARTRIDGE Primary App: HYDRAULIC FILTER Dimensions: Outer Diameter: 5.07" (129 mm) Inner Diameter: 3.35" (85 mm) Length: 9.45" (240 mm)</p>	<p>Part Number: P762877 Description: HYDRAULIC CARTRIDGE Primary App: SCANIA 274108 Dimensions: Outer Diameter: 3.35" (85 mm) Inner Diameter: 3.30" (84 mm) Length: 3.34" (85 mm) Efficiency 99% @ 22 Micron</p>
<p>Part Number: P762880 Description: HYDRAULIC CARTRIDGE Primary App: CR500/6 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 7.99" (203 mm)</p>	<p>Part Number: P763184 Description: HYDRAULIC CARTRIDGE Primary App: HYDRAULIC FILTER Dimensions: Outer Diameter: 5.07" (129 mm) Inner Diameter: 3.35" (85 mm) Length: 9.84" (250 mm)</p>	<p>Part Number: P763184 Description: HYDRAULIC CARTRIDGE Primary App: HYDRAULIC FILTER Dimensions: Outer Diameter: 5.07" (129 mm) Inner Diameter: 3.35" (85 mm) Length: 9.84" (250 mm)</p>	<p>Part Number: P762880 Description: HYDRAULIC CARTRIDGE Primary App: CR500/6 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.56" (65 mm) Length: 7.99" (203 mm)</p>
	<p>Part Number: P762904 Description: HYDRAULIC CARTRIDGE Primary App: VOLVO 62135819 Dimensions: Outer Diameter: 2.20" (56 mm) Inner Diameter: 1.12" (28 mm) Length: 2.66" (68 mm) Efficiency 99% @ 22 Micron</p>		<p>Part Number: P763185 Description: HYDRAULIC CARTRIDGE Primary App: Tamrock 04004080 Dimensions: Outer Diameter: 2.83" (72 mm) Inner Diameter: 1.77" (45 mm) Length: 13.78" (350 mm)</p>
	<p>Part Number: P762921 Description: HYDRAULIC CARTRIDGE Primary App: HITACHI 4333469 Dimensions: Outer Diameter: 6.89" (175 mm) Inner Diameter: 4.33" (110 mm) Length: 17.71" (450 mm) Efficiency 50% @ 10 Micron</p>	<p>Part Number: P763186 Description: HYDRAULIC CARTRIDGE Primary App: HYDRAULIC FILTER Dimensions: Outer Diameter: 4.41" (112 mm) Inner Diameter: 1.42" (36 mm) Length: 7.32" (186 mm)</p>	<p>Part Number: P762921 Description: HYDRAULIC CARTRIDGE Primary App: HITACHI 4333469 Dimensions: Outer Diameter: 6.89" (175 mm) Inner Diameter: 4.33" (110 mm) Length: 17.71" (450 mm) Efficiency 50% @ 10 Micron</p>

<p>Part Number: P763187 Description: HYDRAULIC CARTRIDGE Primary App: HYDRAULIC FILTER Dimensions: Outer Diameter: 1.97" (50 mm) Inner Diameter: 1.97" (50 mm) Length: 11.02" (280 mm)</p>	 <p>Part Number: P763266 Description: HYDRAULIC CARTRIDGE Primary App: P171577 WITH DIFFERENT COVERS Dimensions: Outer Diameter: 5.12" (130 mm) Inner Diameter: 2.56" (65 mm) Length: 9.84" (250 mm)</p>
 <p>Part Number: P763190 Description: HYDRAULIC CARTRIDGE Primary App: HYDRAULIC FILTER Dimensions: Outer Diameter: 5.07" (129 mm) Inner Diameter: 3.35" (85 mm) Length: 9.45" (240 mm)</p>	 <p>Part Number: P763267 Description: HYDRAULIC CARTRIDGE Primary App: P171576 WITH DIFFERENT COVERS Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 2.56" (65 mm) Length: 9.84" (250 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 30 Micron</p>
 <p>Part Number: P763191 Description: HYDRAULIC CARTRIDGE Primary App: HYDRAULIC FILTER Dimensions: Outer Diameter: 4.61" (117 mm) Inner Diameter: 2.32" (59 mm) Length: 19.49" (495 mm)</p>	 <p>Part Number: P763268 Description: HYDRAULIC CARTRIDGE Primary App: MP Filtri MP4003P10HB & MF4003P10HB Dimensions: Outer Diameter: 5.12" (130 mm) Inner Diameter: 2.56" (65 mm) Length: 9.84" (250 mm)</p>
<p>Part Number: P763257 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 07063-01210, 205-60-51430 Dimensions: Outer Diameter: 5.91" (150 mm) Inner Diameter: 3.80" (97 mm) Length: 17.76" (451 mm)</p>	 <p>Part Number: P763269 Description: HYDRAULIC CARTRIDGE Primary App: P171572 WITH DIFFERENT COVERS Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 2.56" (65 mm) Length: 9.84" (250 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 90 Micron</p>
 <p>Part Number: P763258 Description: HYDRAULIC CARTRIDGE Primary App: P171580 WITH DIFFERENT COVERS Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 2.56" (65 mm) Length: 15.75" (400 mm) Relief Valve Setting: 22 PSI (1.52 Bar)</p>	 <p>Part Number: P763270 Description: HYDRAULIC CARTRIDGE Primary App: P171562 WITH DIFFERENT COVERS Dimensions: Outer Diameter: 5.12" (130 mm) Inner Diameter: 2.56" (65 mm) Length: 9.84" (250 mm) Relief Valve Setting: 22 PSI (1.52 Bar)</p>
 <p>Part Number: P763259 Description: HYDRAULIC CARTRIDGE Primary App: P171579 WITH DIFFERENT COVERS Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 2.56" (65 mm) Length: 15.75" (400 mm) Relief Valve Setting: 22 PSI (1.52 Bar)</p>	 <p>Part Number: P763271 Description: HYDRAULIC CARTRIDGE Primary App: P171561 WITH DIFFERENT COVERS Dimensions: Outer Diameter: 5.12" (130 mm) Inner Diameter: 2.56" (65 mm) Length: 9.84" (250 mm) Relief Valve Setting: 22 PSI (1.52 Bar)</p>
<p>Part Number: P763260 Description: HYDRAULIC CARTRIDGE Primary App: P171583 WITH DIFFERENT COVERS Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 2.56" (65 mm) Length: 15.74" (400 mm) Relief Valve Setting: 22 PSI (1.52 Bar)</p>	 <p>Part Number: P763272 Description: HYDRAULIC CARTRIDGE Primary App: P173065 WITH DIFFERENT MEDIA + SPIRAL LINER Ø76 Dimensions: Outer Diameter: 5.00" (127 mm) Inner Diameter: 2.56" (65 mm) Length: 9.84" (250 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 50% @ 10 Micron</p>
 <p>Part Number: P763263 Description: HYDRAULIC CARTRIDGE Primary App: P171578 WITH DIFFERENT COVERS Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 2.56" (65 mm) Length: 15.75" (400 mm) Relief Valve Setting: 22 PSI (1.52 Bar)</p>	 <p>Part Number: P763273 Description: HYDRAULIC CARTRIDGE Primary App: P171560 WITH DIFFERENT COVERS Dimensions: Outer Diameter: 5.12" (130 mm) Inner Diameter: 2.56" (65 mm) Length: 9.84" (250 mm) Relief Valve Setting: 22 PSI (1.52 Bar)</p>
 <p>Part Number: P763264 Description: HYDRAULIC CARTRIDGE Primary App: P171574 WITH DIFFERENT COVERS Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 2.56" (65 mm) Length: 9.84" (250 mm) Relief Valve Setting: 22 PSI (1.52 Bar)</p>	 <p>Part Number: P763274 Description: HYDRAULIC CARTRIDGE Primary App: P171549 WITH SIMILAR COVERS + SPIRAL LINER Ø76 Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 2.05" (52 mm) Length: 5.35" (136 mm) Relief Valve Setting: 22 PSI (1.52 Bar)</p>
 <p>Part Number: P763265 Description: HYDRAULIC CARTRIDGE Primary App: P171573 WITH DIFFERENT COVERS Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 2.56" (65 mm) Length: 9.84" (250 mm) Relief Valve Setting: 22 PSI (1.52 Bar)</p>	

<p>Part Number: P763275 Description: HYDRAULIC CARTRIDGE Primary App: P171553 WITH DIFFERENT COVERS + SPIRAL LINER Ø76 Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 2.05" (52 mm) Length: 5.35" (126 mm) Relief Valve Setting: 22 PSI (1.52 Bar)</p>	 <p>Part Number: P763668 Description: HYDRAULIC SPIN-ON Primary App: MAHLE HC35 Dimensions: Outer Diameter: 5.35" (136 mm) Thread Size: 1 1/2-16 Length: 12.04" (306 mm) Efficiency 50% @ 2 Micron</p>
 <p>Part Number: P763276 Description: HYDRAULIC CARTRIDGE Primary App: P171551 WITH DIFFERENT COVERS Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 2.05" (52 mm) Length: 5.35" (136 mm) Relief Valve Setting: 22 PSI (1.52 Bar)</p>	 <p>Part Number: P763756 Description: HYDRAULIC CARTRIDGE Primary App: Valtra 20626500 Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 1.26" (32 mm) Length: 3.50" (89 mm)</p>
<p>Part Number: P763277 Description: HYDRAULIC CARTRIDGE Primary App: P171551 WITH DIFFERENT COVERS + SPIRAL LINER Ø76 Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 2.05" (52 mm) Length: 5.35" (136 mm) Relief Valve Setting: 22 PSI (1.52 Bar) Efficiency 95% @ 10 Micron</p>	<p>Part Number: P763757 Description: HYDRAULIC CARTRIDGE Primary App: Valmet 355; 365; 455; 465; 555; 565; 665 Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 1.26" (32 mm) Length: 7.09" (180 mm)</p>
<p>Part Number: P763278 Description: HYDRAULIC CARTRIDGE Primary App: CR250 Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 2.05" (52 mm) Length: 5.35" (136 mm) Relief Valve Setting: 22 PSI (1.52 Bar)</p>	<p>Part Number: P763758 Description: HYDRAULIC SPIN-ON Primary App: Valtra 20606000 Dimensions: Outer Diameter: 3.78" (96 mm) Thread Size: M24 x 1.5 Length: 6.93" (176 mm)</p>
<p>Part Number: P763415 Description: HYDRAULIC CARTRIDGE Primary App: New Holland 5198414 Dimensions: Outer Diameter: 3.66" (93 mm) Inner Diameter: 1.89" (48 mm) Length: 10.16" (258 mm)</p>	 <p>Part Number: P763761 Description: HYDRAULIC SPIN-ON Primary App: Donaldson branded version of HMK04 spin on P763723 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 13/16-16 Length: 5.95" (151 mm)</p>
<p>Part Number: P763529 Description: HYDRAULIC SPIN-ON Primary App: Case tractor M and U serie Dimensions: Outer Diameter: 4.57" (116 mm) Thread Size: 1 3/8-12 Length: 11.57" (294 mm)</p>	 <p>Part Number: P763835 Description: HYDRAULIC SPIN-ON Primary App: Cartridge CA160/1R hexagonal housing Dimensions: Outer Diameter: 5.08" (129 mm) Thread Size: G 1 1/4 Length: 7.05" (179 mm)</p>
<p>Part Number: P763535 Description: HYDRAULIC SPIN-ON Primary App: CNH 47131180 AND 47131182 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 9.41" (239 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm)</p>	<p>Part Number: P763866 Description: HYDRAULIC CARTRIDGE Primary App: Fiat Kobelco W190 Cummins Engine 6CT8,3 / W270 Cummins Engine M11 Dimensions: Outer Diameter: 2.20" (56 mm) Inner Diameter: 0.93" (24 mm) Length: 6.69" (170 mm)</p>
 <p>Part Number: P763558 Description: HYDRAULIC SPIN-ON Primary App: HP 539047001 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 3.98" (101 mm)</p>	 <p>Part Number: P763873 Description: HYDRAULIC CARTRIDGE Primary App: TAMROCK 86727289 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 3.31" (84 mm) Length: 22.83" (580 mm)</p>
 <p>Part Number: P763577 Description: HYDRAULIC SPIN-ON Primary App: ATLAS COPCO COMPRESSORS Dimensions: Outer Diameter: 3.81" (97 mm) Thread Size: 1-12 Length: 8.15" (207 mm)</p>	 <p>Part Number: P763874 Description: HYDRAULIC CARTRIDGE Primary App: TAMROCK 04004079 Dimensions: Outer Diameter: 7.95" (202 mm) Inner Diameter: 6.18" (157 mm) Length: 25.98" (660 mm)</p>
<p>Part Number: P763592 Description: HYDRAULIC CARTRIDGE Primary App: FL K041510 (Venieri MF04124). Dimensions: Outer Diameter: 3.07" (78 mm) Inner Diameter: 1.59" (40 mm) Length: 10.12" (257 mm)</p>	<p>Part Number: P763889 Description: HYDRAULIC CARTRIDGE Primary App: KUBOTA ENGINE D850 (Diesel) All Dimensions: Outer Diameter: 1.92" (49 mm) Thread Size: 3/4 NPT Length: 5.87" (149 mm)</p>

<p>Part Number: P763950 Description: HYDRAULIC CARTRIDGE Primary App: Komatsu 42Y60H5080 Dimensions: Outer Diameter: 5.82" (148 mm) Inner Diameter: 1.97" (50 mm) Length: 13.85" (352 mm)</p>	<p>Part Number: P764371 Description: STRAINER Primary App: FIOA 160/3 Dimensions: Outer Diameter: 3.31" (84 mm) Thread Size: G1-1/2 Length: 5.12" (130 mm)</p>
<p>Part Number: P763954 Description: HYDRAULIC CARTRIDGE Primary App: Manitou 224726 Dimensions: Outer Diameter: 3.36" (86 mm) Thread Size: G 2 Length: 10.15" (258 mm)</p>	<p>Part Number: P764409 Description: HYDRAULIC SPIN-ON Primary App: CA250/3 --> 230L/MIN Dimensions: Outer Diameter: 5.35" (136 mm) Thread Size: 1 1/2-16 Length: 12.04" (306 mm)</p>
<p>Part Number: P763956 Description: HYDRAULIC SPIN-ON Primary App: DEMAG SC-serie / BOMAG BW-serie / Losenhausen W1000-serie Dimensions: Outer Diameter: 3.78" (96 mm) Thread Size: 1-12 Length: 6.69" (170 mm)</p>	<p>Part Number: P764554 Description: HYDRAULIC CARTRIDGE Primary App: Fendt F916100600010 Dimensions: Outer Diameter: 2.75" (70 mm) Inner Diameter: 0.98" (25 mm) Length: 7.87" (200 mm)</p>
 <p>Part Number: P763960 Description: HYDRAULIC CARTRIDGE Primary App: Volvo Bus Olympian 3114655-8, NH (CNH) FX/TX series 84004451, Daewoo CE Mega serie 44749047S Dimensions: Outer Diameter: 2.20" (56 mm) Inner Diameter: 1.00" (25 mm) Length: 4.02" (102 mm)</p>	<p>Part Number: P764618 Description: HYDRAULIC CARTRIDGE Primary App: Palfinger EA610A Dimensions: Outer Diameter: 2.36" (60 mm) Inner Diameter: 1.14" (29 mm) Length: 7.91" (201 mm)</p>
<p>Part Number: P763987 Description: HYDRAULIC SPIN-ON Primary App: SAME 244192800 Dimensions: Outer Diameter: 4.25" (108 mm) Length: 9.06" (230 mm) Thread Size: M40 X 2</p>	<p>Part Number: P764626 Description: HYDRAULIC CARTRIDGE Primary App: KOMATSU 2076071180 Dimensions: Outer Diameter: 5.91" (150 mm) Length: 7.87" (200 mm) Inner Diameter: 3.62" (92 mm)</p>
<p>Part Number: P764126 Description: HYDRAULIC CARTRIDGE Primary App: Vogele S serie 1800 9606671002 Dimensions: Outer Diameter: 4.01" (102 mm) Inner Diameter: 2.48" (63 mm) Length: 12.99" (330 mm)</p>	<p>Part Number: P764638 Description: HYDRAULIC SPIN-ON Primary App: FIAT AGRI 1930986 Dimensions: Outer Diameter: 4.25" (108 mm) Length: 7.20" (183 mm)</p>
 <p>Part Number: P764183 Description: HYDRAULIC CARTRIDGE Primary App: SP1156 Combo 200 l/min (short version) Dimensions: Outer Diameter: 3.89" (99 mm) Inner Diameter: 2.59" (66 mm) Length: 1.96" (50 mm)</p>	<p>Part Number: P764660 Description: HYDRAULIC CARTRIDGE Primary App: CARR. ELEVATORI 9847217 Dimensions: Outer Diameter: 1.73" (44 mm) Inner Diameter: 0.91" (23 mm) Length: 7.99" (203 mm)</p>
<p>Part Number: P764259 Description: HYDRAULIC SPIN-ON Primary App: GIMA 4300400H1 Dimensions: Outer Diameter: 5.04" (128 mm) Thread Size: M45 x 2 Length: 7.09" (180 mm)</p>	<p>Part Number: P764665 Description: HYDRAULIC CARTRIDGE Primary App: Bobcat/Ingersoll Rand /Sambron 821397 Dimensions: Outer Diameter: 0.20" (56 mm) Inner Diameter: 0.98" (25 mm) Length: 4.65" (118 mm)</p>
<p>Part Number: P764260 Description: HYDRAULIC SPIN-ON Primary App: Gima 4303303H1, Massey Ferguson 3616579M2 Dimensions: Outer Diameter: 5.04" (128 mm) Thread Size: M42x 2 Length: 3.94" (100 mm)</p>	<p>Part Number: P764668 Description: HYDRAULIC SPIN-ON Primary App: John deere tractors AL156625 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 6.22" (158 mm)</p>
<p>Part Number: P764367 Description: HYDRAULIC SPIN-ON Primary App: Sauer Danfoss 11004918 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 1 3/8-12 Length: 7.08" (180 mm)</p>	<p>Part Number: P764679 Description: HYDRAULIC CARTRIDGE Primary App: NH 71418763 Dimensions: Outer Diameter: 5.91" (150 mm) Thread Size: M10 Length: 26.57" (675 mm)</p>
<p>Part Number: P764370 Description: STRAINER Primary App: FIOA 160/6 Dimensions: Outer Diameter: 3.31" (84 mm) Thread Size: G1-1/2 Length: 5.12" (130 mm)</p>	<p>Part Number: P764724 Description: BREATHER Primary App: TCO 500/2 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 2.50" (64 mm) Length: 7.09" (180 mm)</p>

	<p>Part Number: P764729 Description: HYDRAULIC SPIN-ON, DURAMAX® Primary App: JCB 32925197 -- ZF transmission filter Dimensions: Outer Diameter: 3.70" (94 mm) Thread Size: M24x1.5 Length: 7.12" (181 mm) Gasket OD: 2.76" (70 mm) Gasket ID: 2.48" (63 mm)</p>	<p>Part Number: P765543 Description: HYDRAULIC SPIN-ON Primary App: Komatsu 21T6071180 Dimensions: Length: 5.67" (144 mm) Outer Diameter: 3.78" (96 mm)</p>
	<p>Part Number: P764737 Description: HYDRAULIC SPIN-ON Primary App: CASE 254353A1 Dimensions: Outer Diameter: 4.76" (121 mm) Thread Size: 1 3/8-12 Length: 11.61" (295 mm)</p>	<p>Part Number: P765634 Description: HYDRAULIC CARTRIDGE Primary App: FINN FILTER FC1260Q020XS Dimensions: Inner Diameter: 1.77" (45 mm) Length: 10.24" (260 mm) Outer Diameter: 2.83" (72 mm)</p>
	<p>Part Number: P764831 Description: HYDRAULIC SPIN-ON Primary App: JCB 32925197 Dimensions: Outer Diameter: 3.70" (94 mm) Thread Size: 1-3/8-12 Length: 7.13" (181 mm) Gasket OD: 3.82" (97 mm)</p>	<p>Part Number: P765662 Description: HYDRAULIC SPIN-ON Primary App: CNH 84123428 Dimensions: Length: 6.89" (175 mm) Outer Diameter: 5.35" (136 mm) Thread Size: 1 3/4-12</p>
	<p>Part Number: P765075 Description: HYDRAULIC SPIN-ON Primary App: Dana-Spicer 4209440 Dimensions: Outer Diameter: 3.82" (97 mm) Thread Size: 2-16 Height: 7.09" (180 mm) Relief Valve Setting: 40 +/- 10 PSI (2.76 +/- 70KPa Bar)</p>	<p>Part Number: P765663 Description: HYDRAULIC SPIN-ON Primary App: Dana-spicer D4210289 Dimensions: Length: 5.94" (151 mm) Outer Diameter: 3.82" (97 mm) Thread Size: M22 X 1.5</p>
	<p>Part Number: P765199 Description: FUEL SPIN ON Primary App: AM VERSION OF MTU 0020922101 Dimensions: Outer Diameter: 5.35" (136 mm) Thread Size: M39 x 1.5 Length: 12.05" (306 mm) Gasket OD: 4.33" (110 mm) Gasket ID: 3.94" (100 mm)</p>	
	<p>Part Number: P765281 Description: HYDRAULIC CARTRIDGE Primary App: TIMBERJACK F058437 Dimensions: Length: 47.00" (127 mm) Outer Diameter: 2.72" (69 mm) Inner Diameter: 1.34" (34 mm)</p>	
	<p>Part Number: P765308 Description: HYDRAULIC CARTRIDGE Primary App: Argo V3093308, V03093308 Dimensions: Outer Diameter: 3.54" (90 mm) Inner Diameter: 1.58" (40 mm) Length: 12.91" (328 mm)</p>	
	<p>Part Number: P765325 Description: FUEL IN-LINE Primary App: JCB 32007057 & 32007155 Dimensions: Outer Diameter: 3.14" (80 mm) Outlet Size: SAE 5/16 Inlet Size: SAE 3/8 Efficiency @ 5 @ 99% Micron</p>	<p>Part Number: P770397 Description: AIR SAFETY Primary App: FIAT GEOTECH 1930537, RENAULT 5010140506 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 2.40" (61 mm) Length: 12.13" (308 mm)</p>
	<p>Part Number: P765352 Description: HYDRAULIC SPIN-ON Primary App: John Deere AL156624 Dimensions: Outer Diameter: 3.71" (94 mm) Thread Size: 1-3/8-12 Length: 4.68" (119 mm) Efficiency 99% @ 40 Micron</p>	<p>Part Number: P770399 Description: AIR SAFETY Primary App: DONALDSON EUROPE AIR CLEANERS Dimensions: Outer Diameter: 3.64" (92 mm) Inner Diameter: 2.40" (61 mm) Length: 11.14" (283 mm)</p>
	<p>Part Number: P765457 Description: HYDRAULIC CARTRIDGE Primary App: DONALDSON SRK04 Dimensions: Outer Diameter: 3.46" (88 mm) Inner Diameter: 2.44" (62 mm) Length: 16.96" (431 mm)</p>	

	<p>Part Number: P770735 Description: AIR SAFETY Primary App: MASSEY FERGUSON 3595501M1 Dimensions: Outer Diameter: 3.36" (85 mm) Inner Diameter: 2.93" (74 mm) Length: 9.00" (229 mm)</p>		<p>Part Number: P771502 Description: AIR PRIMARY Primary App: DRONNINGBORG 46422200 Dimensions: Outer Diameter: 7.93" (201 mm) Inner Diameter: 4.45" (113 mm) Length: 12.99" (330 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 4.50" (114 mm)</p>
	<p>Part Number: P770828 Description: AIR PRIMARY Primary App: DEUTZ 4353103 Dimensions: Outer Diameter: 6.10" (155 mm) Inner Diameter: 3.46" (88 mm) Length: 13.46" (342 mm) Bolt Hole Diameter: 0.75" (19 mm) Gasket ID: 4.72" (120 mm)</p>		<p>Part Number: P771504 Description: AIR PRIMARY Primary App: FORD 83DB-9601-AA, IVECO 7980508, IHC 3372006R1 Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.86" (123 mm) Length: 16.57" (421 mm)</p>
	<p>Part Number: P770829 Description: AIR PRIMARY Primary App: DEUTZ 4353065 Dimensions: Outer Diameter: 6.10" (155 mm) Inner Diameter: 3.46" (88 mm) Length: 10" (254 mm) Gasket OD: 4.82" (123 mm) Gasket ID: 4.45" (113 mm)</p>		<p>Part Number: P771505 Description: AIR PRIMARY Primary App: LEYLAND-DAF 10906067 Dimensions: Outer Diameter: 7.95" (202 mm) Inner Diameter: 3.54" (90 mm) Length: 13.54" (344 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 4.72" (120 mm)</p>
	<p>Part Number: P770908 Description: AIR SAFETY Primary App: BEPCO GROUP LTD 1629 Dimensions: Outer Diameter: 3.38" (86 mm) Inner Diameter: 2.89" (74 mm) Length: 8.99" (228 mm)</p>		<p>Part Number: P771508 Description: AIR PRIMARY Primary App: MERCEDES-BENZ 0010944704, KHD 42216-5054 Dimensions: Outer Diameter: 8.94" (227 mm) Inner Diameter: 4.58" (116 mm) Length: 14.61" (371 mm) Bolt Hole Diameter: 0.44" (11 mm) Gasket ID: 5.42" (138 mm)</p>
	<p>Part Number: P770960 Description: AIR PRIMARY Primary App: JOHN DEERE AL30395 Dimensions: Outer Diameter: 3.38" (86 mm) Inner Diameter: 2.93" (74 mm) Length: 13.07" (332 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket OD: 3.74" (95 mm) Gasket ID: 3.47" (88 mm)</p>		<p>Part Number: P771509 Description: AIR PRIMARY Primary App: M.A.N. 81.05504.0033 Dimensions: Outer Diameter: 9.55" (243 mm) Inner Diameter: 5.18" (132 mm) Length: 19.13" (486 mm) Gasket OD: 6.63" (169 mm) Gasket ID: 6.26" (159 mm)</p>
	<p>Part Number: P770991 Description: AIR PRIMARY Primary App: COOPERS AEK2234 Dimensions: Outer Diameter: 7.93" (201 mm) Inner Diameter: 7.49" (190 mm) Length: 16.00" (406 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 6.38" (162 mm)</p>		<p>Part Number: P771510 Description: AIR PRIMARY Primary App: MERCEDES-BENZ 0010949304 Dimensions: Outer Diameter: 10.91" (277 mm) Inner Diameter: 6.30" (160 mm) Length: 10.12" (257 mm) Bolt Hole Diameter: 0.41" (10 mm) Gasket ID: 5.82" (148 mm)</p>
	<p>Part Number: P771003 Description: AIR PRIMARY, KONEPAC™ Primary App: RENAULT RVI 5010039162, MACK Dimensions: Outer Diameter: 8.66" (220 mm) Inner Diameter: 5.20" (132 mm) Length: 15.00" (381 mm) Gasket OD: 7.05" (179 mm) Gasket ID: 3.03" (77 mm)</p>		<p>Part Number: P771511 Description: AIR PRIMARY, FINNED Primary App: FIAT 920007502 Dimensions: Outer Diameter: 7.95" (202 mm) Inner Diameter: 3.54" (90 mm) Length: 14.09" (358 mm) Gasket ID: 6.36" (162 mm) Minor OD: 0.66" (17 mm)</p>
	<p>Part Number: P771073 Description: AIR SAFETY Primary App: FIAT GEOTECH 1930901 Dimensions: Outer Diameter: 7.28" (185 mm) Inner Diameter: 6.18" (157 mm) Length: 19.29" (490 mm)</p>		<p>Part Number: P771514 Description: AIR PRIMARY Primary App: LEYLAND-DAF BBU7280 Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.86" (123 mm) Length: 16.57" (421 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 7.28" (185 mm)</p>
	<p>Part Number: P771501 Description: AIR PRIMARY Primary App: WALGAHN-MOTORENTECHN 00811518 Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 7.59" (193 mm) Length: 9.99" (254 mm) Bolt Hole Diameter: 0.56" (14 mm) Gasket ID: 7.64" (194 mm)</p>		<p>Part Number: P771515 Description: AIR PRIMARY Primary App: LEYLAND-DAF ACU2889 Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.84" (123 mm) Length: 10.98" (279 mm) Gasket OD: 7.68" (195 mm) Gasket ID: 7.30" (186 mm)</p>



	<p>Part Number: P771516 Description: AIR PRIMARY Primary App: IVECO-FIAT 1902128, KHD 422168629 Dimensions: Outer Diameter: 8.90" (226 mm) Inner Diameter: 4.57" (116 mm) Length: 11.69" (297 mm) Bolt Hole Diameter: 0.41" (10 mm) Gasket ID: 5.82" (148 mm)</p>		<p>Part Number: P771529 Description: AIR PRIMARY Primary App: VOLVO 475230, ATLAS 3216708001, LISTER 38207906 Dimensions: Outer Diameter: 6.97" (177 mm) Inner Diameter: 3.46" (88 mm) Length: 15.51" (394 mm) Gasket ID: 4.72" (120 mm)</p>
	<p>Part Number: P771519 Description: AIR PRIMARY Primary App: Clean MA521 Dimensions: Outer Diameter: 12.75" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 19.99" (508 mm) Gasket ID: 10.12" (257 mm)</p>		<p>Part Number: P771530 Description: AIR PRIMARY Primary App: FIAT GEOTECH 1930786 Dimensions: Outer Diameter: 8.35" (212 mm) Inner Diameter: 4.86" (123 mm) Length: 16.54" (420 mm)</p>
	<p>Part Number: P771520 Description: AIR PRIMARY Primary App: DONALDSON FLB12 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 15.98" (406 mm) Gasket ID: 6.38" (162 mm)</p>		<p>Part Number: P771531 Description: AIR PRIMARY, FINNED Primary App: BENFRA 40199 Dimensions: Outer Diameter: 3.72" (95 mm) Inner Diameter: 2.92" (74 mm) Length: 13.50" (343 mm) Gasket ID: 6.26" (159 mm)</p>
	<p>Part Number: P771522 Description: AIR PRIMARY Primary App: FIAT GEOTECH 1930784, ATLAS COPCO 3216708201 Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.86" (123 mm) Length: 15.98" (406 mm) Gasket ID: 6.38" (162 mm)</p>		<p>Part Number: P771532 Description: AIR PRIMARY Primary App: MASSEY FERGUSON 3385733M1 Dimensions: Outer Diameter: 8.34" (212 mm) Inner Diameter: 4.84" (123 mm) Length: 12.99" (330 mm)</p>
	<p>Part Number: P771523 Description: AIR PRIMARY Primary App: MACK/RVI FRI COACH Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.71" (196 mm) Length: 16.22" (412 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 9.56" (243 mm)</p>		<p>Part Number: P771533 Description: AIR PRIMARY Primary App: OLSSONS I ELLOS AB AR79941 Dimensions: Outer Diameter: 7.32" (186 mm) Length: 14.88" (378 mm) Bolt Hole Diameter: 0.39" (10 mm) Gasket ID: 4.72" (120 mm)</p>
	<p>Part Number: P771524 Description: AIR PRIMARY Primary App: ATLAS COPCO 3216707901 Dimensions: Outer Diameter: 10.39" (264 mm) Inner Diameter: 6.06" (154 mm) Length: 15.98" (406 mm)</p>		<p>Part Number: P771534 Description: AIR PRIMARY Primary App: AC A1005C Dimensions: Outer Diameter: 6.83" (173 mm) Inner Diameter: 3.48" (88 mm) Length: 13.97" (355 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 4.72" (120 mm)</p>
	<p>Part Number: P771526 Description: AIR PRIMARY Primary App: Agco 1495490M91 Dimensions: Outer Diameter: 13.81" (351 mm) Inner Diameter: 9.44" (240 mm) Length: 13.99" (355 mm) Bolt Hole Diameter: 0.56" (14 mm) Gasket OD: 13.82" (351 mm) Gasket ID: 12.83" (326 mm)</p>		<p>Part Number: P771538 Description: AIR PRIMARY Primary App: MASSEY FERGUSON 2871928M1 Dimensions: Outer Diameter: 6.10" (155 mm) Inner Diameter: 3.46" (88 mm) Length: 12.01" (305 mm) Gasket OD: 4.82" (123 mm) Gasket ID: 4.45" (113 mm)</p>
	<p>Part Number: P771527 Description: AIR PRIMARY Primary App: FIAT GEOTECH 1930174 Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.86" (123 mm) Length: 13.54" (344 mm) Gasket ID: 6.38" (162 mm)</p>		<p>Part Number: P771541 Description: AIR PRIMARY Primary App: John Deere AH69798 Dimensions: Outer Diameter: 6.08" (154 mm) Inner Diameter: 3.48" (88 mm) Length: 9.99" (254 mm) Bolt Hole Diameter: 0.75" (19 mm) Gasket ID: 4.50" (114 mm)</p>
	<p>Part Number: P771528 Description: AIR PRIMARY Primary App: VOLVO 475230, 475618 Dimensions: Outer Diameter: 12.05" (306 mm) Inner Diameter: 8.03" (204 mm) Length: 8.43" (214 mm) Gasket OD: 12.42" (316 mm) Gasket ID: 12.05" (306 mm)</p>		<p>Part Number: P771542 Description: AIR PRIMARY Primary App: IHC 3073012R1 Dimensions: Outer Diameter: 6.85" (174 mm) Inner Diameter: 4.24" (108 mm) Length: 9.06" (230 mm)</p>

	Part Number: P771546 Description: AIR PRIMARY Primary App: AGCO 3621291M1 Dimensions: Outer Diameter: 6.61" (168 mm) Inner Diameter: 3.74" (95 mm) Length: 14.72" (374 mm) Gasket ID: 4.72" (120 mm)		Part Number: P771558 Description: AIR PRIMARY Primary App: M.A.N. 81.08304.0044 Dimensions: Outer Diameter: 11.89" (302 mm) Inner Diameter: 7.52" (191 mm) Length: 18.66" (474 mm) Bolt Hole Diameter: 0.43" (11 mm) Gasket ID: 8.70" (221 mm)
	Part Number: P771547 Description: AIR PRIMARY, FINNED Primary App: FIAT GEOTECH 1909139 Dimensions: Outer Diameter: 5.24" (133 mm) Inner Diameter: 2.64" (67 mm) Length: 11.54" (293 mm) Gasket OD: 4.06" (103 mm) Gasket ID: 3.68" (93 mm)		Part Number: P771559 Description: AIR PRIMARY Primary App: LEYLAND-DAF 37H6186 Dimensions: Outer Diameter: 6.61" (168 mm) Inner Diameter: 7.85" (200 mm) Length: 10.98" (279 mm) Gasket ID: 3.70" (94 mm)
	Part Number: P771548 Description: AIR PRIMARY, FINNED Primary App: JOHN DEERE AL30394 Dimensions: Outer Diameter: 6.09" (155 mm) Inner Diameter: 3.48" (88 mm) Length: 14.11" (358 mm) Gasket ID: 4.72" (120 mm)		Part Number: P771560 Description: AIR PRIMARY Primary App: LEYLAND-DAF 37H6581 Dimensions: Outer Diameter: 5.43" (138 mm) Inner Diameter: 2.83" (72 mm) Length: 19.13" (486 mm)
	Part Number: P771549 Description: AIR PRIMARY Primary App: BOMAG, PERKINS Dimensions: Outer Diameter: 5.44" (138 mm) Inner Diameter: 2.86" (73 mm) Length: 11.46" (291 mm) Gasket ID: 4.13" (105 mm)		Part Number: P771561 Description: AIR PRIMARY Primary App: DAF, SCANIA, DEUTZ, KHD 42216-5049 Dimensions: Outer Diameter: 7.80" (198 mm) Inner Diameter: 4.44" (113 mm) Length: 14.40" (366 mm) Bolt Hole Diameter: 0.34" (9 mm) Gasket ID: 5.00" (127 mm)
	Part Number: P771550 Description: AIR PRIMARY, FINNED Primary App: CASE T1950555, LANDROVER NTC3535, MF 3310355M91 Dimensions: Outer Diameter: 6.10" (155 mm) Inner Diameter: 3.47" (88 mm) Length: 14.96" (380 mm) Gasket OD: 5.10" (130 mm) Gasket ID: 4.72" (120 mm)		Part Number: P771562 Description: AIR PRIMARY Primary App: BEPCO GROUP LTD 1619 Dimensions: Outer Diameter: 6.83" (173 mm) Inner Diameter: 4.23" (107 mm) Length: 9.99" (254 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 4.72" (120 mm)
	Part Number: P771551 Description: AIR PRIMARY Primary App: VOLVO 475339 Dimensions: Outer Diameter: 10.55" (268 mm) Inner Diameter: 7.68" (195 mm) Length: 11.18" (284 mm) Gasket ID: 8.46" (215 mm)		Part Number: P771563 Description: AIR PRIMARY Primary App: CNH 3125199R2 Dimensions: Outer Diameter: 5.43" (138 mm) Inner Diameter: 2.85" (72 mm) Length: 11.56" (294 mm) Gasket OD: 4.51" (115 mm) Gasket ID: 4.13" (105 mm)
	Part Number: P771552 Description: AIR PRIMARY Primary App: SAME 2.4229.200.1, LISTER 38207898 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.83" (72 mm) Length: 12.01" (305 mm) Gasket ID: 4.15" (105 mm)		Part Number: P771572 Description: AIR PRIMARY Primary App: LISTER 38207903 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.83" (72 mm) Length: 13.98" (355 mm) Gasket ID: 4.15" (105 mm)
	Part Number: P771555 Description: AIR PRIMARY, FINNED Primary App: FIAT GEOTECH 1930603 Dimensions: Outer Diameter: 7.91" (201 mm) Inner Diameter: 5.32" (135 mm) Length: 16.54" (420 mm) Gasket ID: 6.36" (162 mm)		Part Number: P771573 Description: AIR PRIMARY Primary App: SCANIA #261185, MANN & H C30880/1 Dimensions: Outer Diameter: 11.89" (302 mm) Inner Diameter: 7.52" (191 mm) Length: 19.06" (484 mm)
	Part Number: P771557 Description: AIR PRIMARY Primary App: DEUTZ 2323855, KHD 422339823 Dimensions: Outer Diameter: 6.46" (164 mm) Inner Diameter: 3.41" (87 mm) Length: 13.07" (332 mm) Gasket ID: 4.15" (105 mm)		Part Number: P771574 Description: AIR PRIMARY Primary App: R.V.I. DODGE SPAIN Dimensions: Outer Diameter: 11.88" (302 mm) Inner Diameter: 7.51" (191 mm) Length: 17.71" (450 mm)

	<p>Part Number: P771575 Description: AIR PRIMARY Primary App: DAF 667078 Dimensions: Outer Diameter: 11.89" (302 mm) Inner Diameter: 7.52" (191 mm) Length: 14.98" (380 mm) Bolt Hole Diameter: 0.41" (10 mm) Gasket ID: 8.46" (215 mm)</p>		<p>Part Number: P771592 Description: AIR PRIMARY Primary App: KOBELCO VV12961212550 Dimensions: Outer Diameter: 5.24" (133 mm) Inner Diameter: 2.63" (67 mm) Length: 10.98" (279 mm) Gasket ID: 4.15" (105 mm)</p>
	<p>Part Number: P771576 Description: AIR PRIMARY Primary App: MERCEDES-BENZ 0020947304 Dimensions: Outer Diameter: 7.80" (198 mm) Inner Diameter: 4.11" (104 mm) Length: 10.12" (257 mm) Bolt Hole Diameter: 0.33" (8 mm) Gasket ID: 4.96" (126 mm)</p>		<p>Part Number: P771593 Description: AIR PRIMARY Primary App: FENDT F178201090020 Dimensions: Outer Diameter: 6.46" (164 mm) Inner Diameter: 3.41" (87 mm) Length: 9.37" (238 mm) Gasket ID: 4.15" (105 mm)</p>
	<p>Part Number: P771582 Description: AIR PRIMARY Primary App: MERCEDES-BENZ 0020942404 Dimensions: Outer Diameter: 12.83" (326 mm) Inner Diameter: 6.57" (167 mm) Length: 13.94" (354 mm) Bolt Hole Diameter: 0.43" (11 mm) Gasket ID: 7.32" (186 mm)</p>		<p>Part Number: P771594 Description: AIR PRIMARY Primary App: DEUTZ 2319813 Dimensions: Outer Diameter: 6.46" (164 mm) Inner Diameter: 3.41" (87 mm) Length: 8.35" (212 mm) Gasket ID: 4.15" (105 mm)</p>
	<p>Part Number: P771583 Description: AIR PRIMARY Primary App: MERCEDES-BENZ 0010948304 Dimensions: Outer Diameter: 12.83" (326 mm) Inner Diameter: 7.60" (193 mm) Length: 9.57" (243 mm)</p>		<p>Part Number: P771595 Description: AIR PRIMARY Primary App: MERCEDES-BENZ 0030944204 Dimensions: Outer Diameter: 12.87" (327 mm) Inner Diameter: 6.33" (161 mm) Length: 10.16" (258 mm) Bolt Hole Diameter: 0.41" (10 mm) Gasket ID: 7.28" (185 mm)</p>
	<p>Part Number: P771584 Description: AIR PRIMARY Primary App: CLARK 3339355, HYSTER 3049299 Dimensions: Outer Diameter: 6.10" (155 mm) Inner Diameter: 3.46" (88 mm) Length: 11.57" (294 mm) Bolt Hole Diameter: 0.75" (19 mm) Gasket ID: 4.50" (114 mm)</p>		<p>Part Number: P772504 Description: AIR PRIMARY Primary App: LEYLAND-DAF ABU9896 Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.84" (123 mm) Length: 16.00" (406 mm) Gasket ID: 7.63" (194 mm)</p>
	<p>Part Number: P771588 Description: AIR PRIMARY Primary App: TOYOTA 17752-20540-71A Dimensions: Outer Diameter: 5.24" (133 mm) Inner Diameter: 2.64" (67 mm) Length: 18.11" (460 mm) Gasket OD: 4.35" (110 mm) Gasket ID: 3.98" (101 mm)</p>		<p>Part Number: P772506 Description: AIR PRIMARY Primary App: O&K HR120C EXCAVATOR Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.72" (196 mm) Length: 23.00" (584 mm) Bolt Hole Diameter: 0.90" (23 mm) Gasket ID: 8.12" (206 mm)</p>
	<p>Part Number: P771589 Description: AIR PRIMARY Primary App: MASSEY FERGUSON 3515586-M1 Dimensions: Outer Diameter: 6.10" (155 mm) Inner Diameter: 3.46" (88 mm) Length: 11.10" (282 mm) Gasket ID: 4.72" (120 mm)</p>		<p>Part Number: P772507 Description: AIR PRIMARY Primary App: Mercedes 0010948004 Dimensions: Outer Diameter: 9.53" (242 mm) Inner Diameter: 5.18" (132 mm) Length: 19.13" (486 mm) Bolt Hole Diameter: 0.41" (10 mm) Gasket ID: 6.25" (159 mm)</p>
	<p>Part Number: P771590 Description: AIR PRIMARY Primary App: MASSEY FERGUSON 3595500M1 Dimensions: Outer Diameter: 6.97" (177 mm) Inner Diameter: 3.46" (88 mm) Length: 11.10" (282 mm) Gasket ID: 4.72" (120 mm)</p>		<p>Part Number: P772512 Description: AIR PRIMARY Primary App: LEYLAND-DAF ABU9145 Dimensions: Outer Diameter: 8.43" (214 mm) Inner Diameter: 4.00" (102 mm) Length: 22.91" (582 mm)</p>
	<p>Part Number: P771591 Description: AIR PRIMARY Primary App: MASSEY FERGUSON 3595518-M1 Dimensions: Outer Diameter: 5.43" (138 mm) Inner Diameter: 2.83" (72 mm) Length: 12.01" (305 mm) Gasket ID: 4.15" (105 mm)</p>		<p>Part Number: P772519 Description: AIR PRIMARY Primary App: RENAULT 0003564135 Dimensions: Outer Diameter: 12.76" (324 mm) Inner Diameter: 8.38" (213 mm) Length: 21.10" (536 mm) Gasket ID: 10.12" (257 mm)</p>

	<p>Part Number: P772520 Description: AIR PRIMARY Primary App: FIAT 1930783, MF 3580723M1 Dimensions: Outer Diameter: 10.39" (264 mm) Inner Diameter: 6.06" (154 mm) Length: 16.54" (420 mm) Gasket ID: 6.38" (162 mm)</p>		<p>Part Number: P772536 Description: AIR PRIMARY Primary App: FIAT GEOTECH 1930900, PEGASO Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 20.55" (522 mm) Bolt Hole Diameter: 0.67" (17 mm) Gasket ID: 9.00" (229 mm)</p>
	<p>Part Number: P772521 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P771521 Dimensions: Outer Diameter: 7.72" (196 mm) Inner Diameter: 12.09" (307 mm) Length: 18.54" (471 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 9.56" (243 mm)</p>		<p>Part Number: P772545 Description: AIR PRIMARY Primary App: FIAT 1930794 Dimensions: Outer Diameter: 7.91" (201 mm) Inner Diameter: 5.32" (135 mm) Length: 16.54" (420 mm) Bolt Hole Diameter: 0.67" (17 mm) Gasket ID: 7.17" (182 mm)</p>
	<p>Part Number: P772522 Description: AIR PRIMARY Primary App: JOHN DEERE DOX18913, FIAT 300138019 Dimensions: Outer Diameter: 9.22" (234 mm) Inner Diameter: 4.84" (123 mm) Length: 15.98" (406 mm) Gasket ID: 6.38" (162 mm)</p>		<p>Part Number: P772549 Description: AIR PRIMARY Primary App: CAT 100-6844, FIAT 1930764, PERKINS 26510313 Dimensions: Outer Diameter: 5.43" (138 mm) Inner Diameter: 2.83" (72 mm) Length: 12.01" (305 mm) Gasket ID: 4.15" (105 mm)</p>
	<p>Part Number: P772523 Description: AIR PRIMARY Primary App: IHC-DRESSER 1201733H1, FIAT 321549350 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.72" (196 mm) Length: 16.20" (411 mm) Bolt Hole Diameter: 0.67" (17 mm) Gasket ID: 9.56" (243 mm)</p>		<p>Part Number: P772550 Description: AIR PRIMARY, FINNED Primary App: FIAT 79072797, VOLVO 3576571 Dimensions: Outer Diameter: 6.09" (155 mm) Inner Diameter: 3.48" (88 mm) Length: 14.98" (380 mm) Gasket ID: 4.75" (121 mm)</p>
	<p>Part Number: P772524 Description: AIR PRIMARY Primary App: FIAT AGRI 700056048, OREN & KOPPEL 8300375 Dimensions: Outer Diameter: 10.40" (264 mm) Inner Diameter: 6.04" (153 mm) Length: 15.98" (406 mm) Gasket ID: 6.26" (159 mm)</p>		<p>Part Number: P772552 Description: AIR PRIMARY Primary App: MACOSULLAIR 529054, OK 1499157 Dimensions: Outer Diameter: 5.51" (140 mm) Inner Diameter: 2.83" (72 mm) Length: 12.01" (305 mm) Gasket ID: 4.15" (105 mm)</p>
	<p>Part Number: P772529 Description: AIR PRIMARY Primary App: LONG LIFE VERSION OF P771529 Dimensions: Outer Diameter: 6.97" (177 mm) Inner Diameter: 3.46" (88 mm) Length: 15.51" (394 mm) Gasket ID: 4.72" (120 mm)</p>		<p>Part Number: P772553 Description: AIR PRIMARY Primary App: FIAT 1930824 Dimensions: Outer Diameter: 6.10" (155 mm) Inner Diameter: 3.46" (88 mm) Length: 13.94" (354 mm) Gasket ID: 4.72" (120 mm)</p>
	<p>Part Number: P772530 Description: AIR PRIMARY Primary App: FIAT AGRI 22190599 Dimensions: Outer Diameter: 9.22" (234 mm) Inner Diameter: 4.84" (123 mm) Length: 15.98" (406 mm) Gasket ID: 6.38" (162 mm)</p>		<p>Part Number: P772555 Description: AIR PRIMARY, FINNED Primary App: CAT 100-6846, FIAT 1930603, PERKINS 26510317 Dimensions: Outer Diameter: 7.91" (201 mm) Inner Diameter: 5.32" (135 mm) Length: 16.54" (420 mm) Gasket ID: 6.36" (162 mm)</p>
	<p>Part Number: P772531 Description: AIR PRIMARY Primary App: FIAT 1930602 Dimensions: Outer Diameter: 10.39" (264 mm) Inner Diameter: 6.06" (154 mm) Length: 16.54" (420 mm) Gasket ID: 6.26" (159 mm)</p>		<p>Part Number: P772556 Description: AIR PRIMARY Primary App: FIAT AGRI 320498750 Dimensions: Outer Diameter: 6.09" (155 mm) Inner Diameter: 3.48" (88 mm) Length: 15.96" (405 mm) Gasket ID: 4.75" (121 mm)</p>
	<p>Part Number: P772535 Description: AIR PRIMARY Primary App: FIAT GEOTECH 1930138 Dimensions: Outer Diameter: 6.97" (177 mm) Inner Diameter: 3.46" (88 mm) Length: 13.54" (344 mm) Gasket ID: 4.72" (120 mm)</p>		<p>Part Number: P772564 Description: AIR PRIMARY Primary App: FIAT GEOTECH 1909116 Dimensions: Outer Diameter: 6.10" (155 mm) Inner Diameter: 3.46" (88 mm) Length: 13.46" (342 mm) Bolt Hole Diameter: 0.75" (19 mm) Gasket ID: 4.72" (120 mm)</p>

















	<p>Part Number: P772565 Description: AIR PRIMARY Primary App: FIAT GEOTECH 1930536 Dimensions: Outer Diameter: 5.43" (138 mm) Inner Diameter: 2.83" (72 mm) Length: 13.98" (355 mm) Gasket ID: 4.15" (105 mm)</p>		<p>Part Number: P772587 Description: AIR PRIMARY Primary App: FIAT 1930604 Dimensions: Outer Diameter: 9.65" (245 mm) Inner Diameter: 6.04" (153 mm) Length: 16.54" (420 mm) Bolt Hole Diameter: 0.63" (16 mm) Gasket ID: 6.26" (159 mm)</p>
	<p>Part Number: P772567 Description: AIR PRIMARY Primary App: LEYLAND-DAF MKZ2802 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 18.58" (472 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 9.00" (229 mm)</p>		<p>Part Number: P772597 Description: AIR PRIMARY Primary App: KOMATSU 205-01-73570 Dimensions: Outer Diameter: 7.91" (201 mm) Inner Diameter: 5.32" (135 mm) Length: 17.87" (454 mm) Gasket ID: 6.38" (162 mm)</p>
	<p>Part Number: P772577 Description: AIR PRIMARY Primary App: IVECO-PEGASO 171686 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 20.55" (522 mm)</p>		<p>Part Number: P773605 Description: AIR PRIMARY, FINNED Primary App: JCB 32/903601 Dimensions: Outer Diameter: 6.10" (155 mm) Inner Diameter: 3.46" (88 mm) Length: 15.51" (394 mm)</p>
	<p>Part Number: P772578 Description: AIR PRIMARY, RADIALSEAL Primary App: FIAT 1930591, L.PETTER 36608105 Dimensions: Outer Diameter: 4.13" (105 mm) Inner Diameter: 2.68" (68 mm) Length: 11.81" (300 mm)</p>		<p>Part Number: P775026 Description: AIR PRIMARY Primary App: JOHN DEERE AZ45868 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 22.56" (573 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 9.56" (243 mm)</p>
	<p>Part Number: P772579 Description: AIR PRIMARY, RADIALSEAL Primary App: FIAT 1930587, L.PETTER 366-08109 Dimensions: Outer Diameter: 5.52" (140 mm) Inner Diameter: 3.50" (89 mm) Length: 12.93" (328 mm)</p>		<p>Part Number: P775298 Description: AIR SAFETY, RADIALSEAL Primary App: FIAT GEOTECH 1930592, L. PETTER 366-08106 Dimensions: Outer Diameter: 2.40" (61 mm) Inner Diameter: 1.89" (48 mm) Length: 11.42" (290 mm)</p>
	<p>Part Number: P772580 Description: AIR PRIMARY, RADIALSEAL Primary App: FIAT 1930589, CAT 110-6326, IR 92793025 Dimensions: Outer Diameter: 6.50" (165 mm) Inner Diameter: 3.96" (101 mm) Length: 13.90" (353 mm)</p>		<p>Part Number: P775300 Description: AIR SAFETY, RADIALSEAL Primary App: FIAT 1930588, L.PETTER 366-08110, MACOSLR 560938 Dimensions: Outer Diameter: 3.31" (84 mm) Inner Diameter: 2.62" (67 mm) Length: 12.56" (319 mm)</p>
	<p>Part Number: P772581 Description: AIR PRIMARY Primary App: PERLINI 350087A Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 24.57" (624 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 9.00" (229 mm)</p>		<p>Part Number: P775339 Description: AIR SAFETY Primary App: PERLINI 350088A Dimensions: Outer Diameter: 7.28" (185 mm) Inner Diameter: 6.22" (158 mm) Length: 23.82" (605 mm)</p>
	<p>Part Number: P772585 Description: AIR PRIMARY Primary App: RENAULT RVI.5010094146 Dimensions: Outer Diameter: 11.10" (282 mm) Inner Diameter: 6.73" (171 mm) Length: 15.35" (390 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 9.56" (246 mm)</p>		<p>Part Number: P775373 Description: AIR SAFETY Primary App: JCB 321906802 Dimensions: Outer Diameter: 3.39" (86 mm) Inner Diameter: 2.93" (74 mm) Length: 10.16" (258 mm)</p>
	<p>Part Number: P772586 Description: AIR PRIMARY Primary App: RENAULT RVI.5000814797 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 15.35" (390 mm)</p>		<p>Part Number: P775457 Description: AIR SAFETY Primary App: FIAT ALLIS 71406283 Dimensions: Outer Diameter: 3.39" (86 mm) Inner Diameter: 2.93" (74 mm) Length: 12.13" (308 mm)</p>


	<p>Part Number: P775500 Description: AIR SAFETY Primary App: RENAULT RVI 5000814798 Dimensions: Outer Diameter: 7.28" (185 mm) Inner Diameter: 6.22" (158 mm) Length: 14.57" (370 mm)</p>		<p>Part Number: P775756 Description: AIR PRIMARY Primary App: COOPERS AEK2172 Dimensions: Outer Diameter: 3.26" (83 mm) Inner Diameter: 1.65" (42 mm) Length: 7.00" (178 mm) Bolt Hole Diameter: 0.43" (11 mm)</p>
	<p>Part Number: P775510 Description: AIR SAFETY Primary App: FIAT GEOTECH 1930606 Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 4.84" (123 mm) Length: 14.37" (365 mm)</p>		<p>Part Number: P775792 Description: AIR PRIMARY Primary App: IVECO 1904581 Dimensions: Outer Diameter: 5.82" (148 mm) Inner Diameter: 3.09" (78 mm) Length: 12.71" (323 mm)</p>
	<p>Part Number: P775631 Description: AIR PRIMARY, RADIALSEAL Primary App: GEHL 781360775631 Dimensions: Outer Diameter: 4.13" (105 mm) Inner Diameter: 2.68" (68 mm) Length: 11.81" (300 mm)</p>		<p>Part Number: P775803 Description: AIR SAFETY Primary App: AR FILTER AR308 Dimensions: Outer Diameter: 6.37" (162 mm) Inner Diameter: 5.27" (134 mm) Length: 14.80" (376 mm)</p>
	<p>Part Number: P775681 Description: AIR PRIMARY Primary App: TOYOTA 17801-23000-71 Dimensions: Outer Diameter: 5.24" (133 mm) Inner Diameter: 2.64" (67 mm) Length: 11.02" (280 mm)</p>		<p>Part Number: P775804 Description: AIR PRIMARY Primary App: RENAULT RVI 5010094154 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 15.75" (400 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 9.56" (243 mm)</p>
	<p>Part Number: P775687 Description: AIR PRIMARY Primary App: KOMATSU Z76-01-18130, JCB KAP0482 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 2.49" (63 mm) Length: 10.55" (268 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 2.87" (73 mm)</p>		<p>Part Number: P775843 Description: AIR PRIMARY Primary App: IVECO 1905710 Dimensions: Outer Diameter: 12.87" (327 mm) Inner Diameter: 9.56" (243 mm) Length: 18.11" (460 mm)</p>
	<p>Part Number: P775688 Description: AIR PRIMARY Primary App: KOMATSU Z76-01-17130 Dimensions: Outer Diameter: 3.27" (83 mm) Inner Diameter: 1.65" (42 mm) Gasket OD: 2.50" (64 mm) Gasket ID: 2.13" (54 mm)</p>		<p>Part Number: P775896 Description: AIR PRIMARY Primary App: SCANIA 370750 Dimensions: Outer Diameter: 9.53" (242 mm) Inner Diameter: 5.21" (132 mm) Length: 20.87" (530 mm) Bolt Hole Diameter: 0.43" (11 mm) Gasket ID: 6.26" (159 mm)</p>
	<p>Part Number: P775704 Description: AIR SAFETY Primary App: FENDT X810270072 Dimensions: Outer Diameter: 2.87" (73 mm) Inner Diameter: 2.86" (73 mm) Length: 7.48" (190 mm)</p>		<p>Part Number: P775918 Description: AIR PRIMARY Primary App: SCANIA 395776-7087 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.73" (196 mm) Length: 17.24" (438 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 9.56" (243 mm)</p>
	<p>Part Number: P775732 Description: AIR PRIMARY, FINNED Primary App: HINO 17801-1080 Dimensions: Outer Diameter: 7.95" (202 mm) Inner Diameter: 4.57" (116 mm) Length: 11.81" (300 mm) Gasket ID: 4.72" (120 mm) Minor OD: 0.53" (13 mm)</p>		<p>Part Number: P775945 Description: AIR PRIMARY, KONEPAC™ Primary App: VOLVO 6792554 Dimensions: Outer Diameter: 7.36" (187 mm) Inner Diameter: 4.68" (119 mm) Length: 23.31" (592 mm) Gasket OD: 6.10" (155 mm) Gasket ID: 3.39" (86 mm)</p>
	<p>Part Number: P775749 Description: AIR PRIMARY, FINNED Primary App: NISSAN 16546-05H10 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 2.49" (63 mm) Length: 8.03" (204 mm) Gasket OD: 3.74" (95 mm) Gasket ID: 2.52" (64 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P776019 Description: AIR SAFETY Primary App: KOMATSU 205-01-K1480 Dimensions: Outer Diameter: 4.57" (116 mm) Inner Diameter: 3.46" (88 mm) Length: 16.54" (420 mm)</p>

	<p>Part Number: P776102 Description: AIR SAFETY Primary App: JOHN DEERE AZ45867 Dimensions: Outer Diameter: 7.28" (185 mm) Inner Diameter: 6.22" (158 mm) Length: 21.89" (556 mm)</p>		<p>Part Number: P776303 Description: AIR SAFETY Primary App: FIAT ALLIS 1930758 Dimensions: Outer Diameter: 5.35" (136 mm) Inner Diameter: 4.00" (102 mm) Length: 6.93" (176 mm)</p>
	<p>Part Number: P776157 Description: AIR PRIMARY, KONEPAC™ Primary App: LEYLAND-DAF BBU8384 Dimensions: Outer Diameter: 11.50" (292 mm) Inner Diameter: 6.57" (167 mm) Length: 19.72" (501 mm) Gasket OD: 10.35" (263 mm) Gasket ID: 5.41" (137 mm) Minor OD: 0.65" (17 mm)</p>		<p>Part Number: P776341 Description: AIR PRIMARY Primary App: CASE K200379 Dimensions: Outer Diameter: 5.24" (133 mm) Inner Diameter: 3.23" (82 mm) Length: 10.98" (279 mm) Gasket OD: 4.13" (105 mm) Gasket ID: 3.76" (96 mm)</p>
	<p>Part Number: P776158 Description: AIR PRIMARY, KONEPAC™ Primary App: FORD 81DB-9601-TB Dimensions: Outer Diameter: 7.01" (178 mm) Inner Diameter: 3.62" (92 mm) Length: 15.63" (397 mm) Gasket OD: 5.98" (152 mm) Gasket ID: 2.46" (62 mm) Minor OD: 0.65" (17 mm)</p>		<p>Part Number: P776356 Description: AIR PRIMARY, FINNED Primary App: JCB 32/905301 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 2.49" (63 mm) Length: 8.54" (217 mm) Gasket ID: 2.87" (73 mm)</p>
	<p>Part Number: P776159 Description: AIR PRIMARY, KONEPAC™ Primary App: E.R.F. 95708-8, LEYLAND-DAF Dimensions: Outer Diameter: 8.27" (210 mm) Inner Diameter: 4.74" (120 mm) Length: 18.58" (472 mm) Gasket OD: 7.17" (182 mm) Gasket ID: 3.39" (86 mm) Minor OD: 0.65" (17 mm)</p>		<p>Part Number: P776357 Description: AIR SAFETY Primary App: JCB 32/905302 Dimensions: Outer Diameter: 2.28" (58 mm) Inner Diameter: 2.04" (52 mm) Length: 7.13" (181 mm)</p>
	<p>Part Number: P776198 Description: AIR PRIMARY Primary App: IVECO PEGASO 172150 Dimensions: Outer Diameter: 9.55" (243 mm) Inner Diameter: 5.18" (132 mm) Length: 15.98" (406 mm) Gasket OD: 6.63" (169 mm) Gasket ID: 6.26" (159 mm)</p>		<p>Part Number: P776358 Description: AIR PRIMARY, FINNED Primary App: JCB 32/206002 Dimensions: Outer Diameter: 5.24" (133 mm) Inner Diameter: 2.83" (72 mm) Length: 13.98" (355 mm) Gasket ID: 3.89" (99 mm) Minor OD: 0.47" (12 mm)</p>
	<p>Part Number: P776251 Description: AIR PRIMARY Primary App: RENAULT 5000807196 Dimensions: Outer Diameter: 11.73" (298 mm) Inner Diameter: 8.66" (220 mm) Length: 15.78" (401 mm)</p>		<p>Part Number: P776360 Description: AIR PRIMARY, FINNED Primary App: ARRF ARM27-50, FRAM CA4412, FTGD AF1829 Dimensions: Outer Diameter: 5.24" (133 mm) Inner Diameter: 2.83" (72 mm) Length: 8.50" (216 mm) Gasket ID: 3.89" (99 mm) Minor OD: 0.47" (12 mm)</p>
	<p>Part Number: P776252 Description: AIR PRIMARY Primary App: MAN 81.08304.0072 Dimensions: Outer Diameter: 11.89" (302 mm) Inner Diameter: 7.52" (191 mm) Length: 13.31" (338 mm)</p>		<p>Part Number: P776386 Description: AIR PRIMARY Primary App: MERCEDES 0010947304 Dimensions: Outer Diameter: 10.47" (266 mm) Inner Diameter: 5.25" (133 mm) Length: 9.13" (232 mm) Bolt Hole Diameter: 0.41" (10 mm) Gasket ID: 5.86" (149 mm)</p>
	<p>Part Number: P776260 Description: AIR PRIMARY Primary App: IVECO 1905983 Dimensions: Outer Diameter: 9.48" (241 mm) Inner Diameter: 6.22" (158 mm) Length: 11.10" (282 mm)</p>		<p>Part Number: P776490 Description: AIR PANEL, VENTILATION Primary App: FIAT 1930782 Dimensions: Width: 6.00" (152 mm) Depth: 2.20" (56 mm) Height: 17.17" (436 mm)</p>
	<p>Part Number: P776302 Description: AIR PRIMARY Primary App: FIAT ALLIS 1930740 Dimensions: Outer Diameter: 8.74" (222 mm) Inner Diameter: 6.16" (156 mm) Length: 8.19" (208 mm)</p>		<p>Part Number: P776497 Description: AIR PRIMARY Primary App: FIAT 1930600 Dimensions: Outer Diameter: 9.65" (245 mm) Inner Diameter: 6.04" (153 mm) Length: 13.58" (345 mm) Bolt Hole Diameter: 0.65" (17 mm) Gasket ID: 6.26" (159 mm)</p>

















	<p>Part Number: P776498 Description: AIR SAFETY Primary App: FIAT GEOTECH 1930601 Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 4.84" (123 mm) Length: 12.01" (305 mm)</p>		<p>Part Number: P776695 Description: AIR SAFETY Primary App: MANN & HUMMEL CF1000 Dimensions: Outer Diameter: 4.37" (111 mm) Length: 14.65" (372 mm) Inner Diameter: 0.69" (18 mm)</p>
	<p>Part Number: P776565 Description: AIR SAFETY Primary App: CASE E41535 Dimensions: Outer Diameter: 2.60" (66 mm) Inner Diameter: 2.12" (54 mm) Length: 10.39" (264 mm)</p>		<p>Part Number: P776696 Description: AIR SAFETY Primary App: MANN & HUMMEL CF1200 Dimensions: Outer Diameter: 4.76" (121 mm) Inner Diameter: 3.94" (100 mm) Length: 14.93" (379 mm)</p>
	<p>Part Number: P776566 Description: AIR SAFETY Primary App: CASE E43789 Dimensions: Outer Diameter: 2.91" (74 mm) Inner Diameter: 1.89" (48 mm) Length: 10.20" (259 mm)</p>		<p>Part Number: P776697 Description: AIR SAFETY Primary App: MANN & HUMMEL CF1300 Dimensions: Outer Diameter: 5.55" (141 mm) Inner Diameter: 4.65" (118 mm) Length: 18.64" (473 mm)</p>
	<p>Part Number: P776567 Description: AIR PRIMARY Primary App: CASE E43790 Dimensions: Outer Diameter: 5.24" (133 mm) Inner Diameter: 3.23" (82 mm) Length: 10.98" (279 mm) Gasket OD: 4.33" (110 mm) Gasket ID: 3.96" (101 mm)</p>		<p>Part Number: P776730 Description: AIR PRIMARY, FINNED Primary App: TOYOTA 17806-23800-71 Dimensions: Outer Diameter: 5.24" (133 mm) Inner Diameter: 3.22" (82 mm) Length: 11.42" (290 mm) Gasket ID: 3.89" (99 mm) Minor OD: 0.47" (12 mm)</p>
	<p>Part Number: P776568 Description: AIR PRIMARY Primary App: CASE E46373 Dimensions: Outer Diameter: 5.24" (133 mm) Inner Diameter: 3.66" (93 mm) Length: 14.96" (380 mm) Gasket OD: 4.51" (115 mm) Gasket ID: 4.13" (105 mm)</p>		<p>Part Number: P776765 Description: AIR PRIMARY, KONEPAC™ Primary App: E.R.F. 95518-0 Dimensions: Outer Diameter: 9.88" (251 mm) Inner Diameter: 6.22" (158 mm) Length: 19.53" (496 mm) Gasket OD: 8.35" (212 mm) Gasket ID: 4.02" (102 mm) Minor OD: 0.66" (17 mm)</p>
	<p>Part Number: P776615 Description: AIR PRIMARY, FINNED Primary App: TOYOTA 17803-23001-71 Dimensions: Outer Diameter: 5.24" (133 mm) Inner Diameter: 3.30" (84 mm) Length: 11.57" (294 mm) Gasket ID: 3.89" (99 mm) Minor OD: 0.47" (12 mm)</p>		<p>Part Number: P776830 Description: AIR PRIMARY, FINNED Primary App: JCB 32/906801 Dimensions: Outer Diameter: 6.10" (155 mm) Inner Diameter: 3.46" (88 mm) Length: 11.77" (299 mm) Gasket ID: 4.45" (113 mm)</p>
	<p>Part Number: P776623 Description: AIR SAFETY Primary App: TOYOTA 17804-23000-71 Dimensions: Outer Diameter: 3.19" (81 mm) Inner Diameter: 2.50" (64 mm) Length: 10.39" (264 mm)</p>		<p>Part Number: P776895 Description: AIR SAFETY Primary App: JCB 32/905002 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 2.40" (61 mm) Length: 7.24" (184 mm)</p>
	<p>Part Number: P776636 Description: AIR PRIMARY, FINNED Primary App: TOYOTA 17801-23001-71 Dimensions: Outer Diameter: 5.24" (133 mm) Inner Diameter: 2.50" (64 mm) Length: 11.57" (294 mm) Gasket ID: 3.97" (101 mm) Minor OD: 0.47" (12 mm)</p>		<p>Part Number: P776993 Description: AIR PRIMARY Primary App: RANGE ROVER NTC 6660 Dimensions: Outer Diameter: 5.24" (133 mm) Inner Diameter: 2.62" (67 mm) Length: 11.57" (294 mm)</p>
	<p>Part Number: P776694 Description: AIR SAFETY Primary App: MANN & HUMMEL CF800 Dimensions: Outer Diameter: 3.62" (92 mm) Inner Diameter: 2.80" (71 mm) Length: 13.46" (342 mm)</p>		<p>Part Number: P776995 Description: AIR PRIMARY Primary App: COMPAIR 98262/109 Dimensions: Outer Diameter: 6.50" (165 mm) Inner Diameter: 4.06" (103 mm) Length: 9.13" (232 mm) Gasket OD: 4.13" (105 mm) Gasket ID: 3.76" (96 mm)</p>

	<p>Part Number: P777105 Description: AIR PRIMARY Primary App: VOLVO 1544428, 1600375, 475755 Dimensions: Outer Diameter: 10.66" (271 mm) Inner Diameter: 6.22" (158 mm) Length: 22.44" (570 mm) Bolt Hole Diameter: 0.51" (13 mm) Gasket ID: 7.32" (186 mm)</p>		<p>Part Number: P777356 Description: AIR PRIMARY Primary App: O & K 101228 Dimensions: Outer Diameter: 7.73" (196 mm) Inner Diameter: 6.06" (154 mm) Length: 14.05" (357 mm)</p>
	<p>Part Number: P777152 Description: AIR PRIMARY Primary App: VOLVO 1542743, 1660619, 475386 Dimensions: Outer Diameter: 12.24" (311 mm) Inner Diameter: 7.87" (200 mm) Length: 14.13" (359 mm) Bolt Hole Diameter: 0.46" (12 mm) Gasket ID: 8.70" (221 mm)</p>		<p>Part Number: P777357 Description: AIR PRIMARY Primary App: VIRGIS CH12826 Dimensions: Outer Diameter: 8.41" (214 mm) Inner Diameter: 4.80" (122 mm) Length: 10.90" (277 mm)</p>
	<p>Part Number: P777156 Description: AIR PRIMARY Primary App: CATERPILLAR 1149097 Dimensions: Outer Diameter: 10.39" (264 mm) Inner Diameter: 6.02" (153 mm) Length: 17.99" (457 mm) Gasket ID: 6.26" (159 mm)</p>		<p>Part Number: P777409 Description: AIR PRIMARY, RADIALSEAL Primary App: VOLVO 11110022 Dimensions: Outer Diameter: 11.10" (282 mm) Inner Diameter: 5.83" (148 mm) Length: 20.08" (510 mm)</p>
	<p>Part Number: P777179 Description: AIR PRIMARY Primary App: BEDFORD 91107151 Dimensions: Outer Diameter: 6.47" (164 mm) Inner Diameter: 3.86" (98 mm) Length: 14.09" (358 mm)</p>		<p>Part Number: P777414 Description: AIR SAFETY, RADIALSEAL Primary App: VOLVO 11110023 Dimensions: Outer Diameter: 5.94" (151 mm) Inner Diameter: 4.31" (109 mm) Length: 19.53" (496 mm)</p>
	<p>Part Number: P777240 Description: AIR PRIMARY Primary App: KUBOTA 1735111080 Dimensions: Outer Diameter: 5.23" (133 mm) Inner Diameter: 2.87" (73 mm) Length: 11.02" (280 mm) Bolt Hole Diameter: 0.55" (14 mm) Gasket ID: 6.97" (177 mm)</p>		<p>Part Number: P777483 Description: AIR PRIMARY Primary App: LISTER PETER 36606227 Dimensions: Outer Diameter: 5.74" (146 mm) Inner Diameter: 4.09" (104 mm) Length: 2.52" (64 mm)</p>
	<p>Part Number: P777241 Description: AIR PRIMARY Primary App: DAF TRUCK 265045 Dimensions: Outer Diameter: 7.79" (198 mm) Inner Diameter: 4.09" (104 mm) Length: 14.37" (365 mm) Bolt Hole Diameter: 0.33" (8 mm) Gasket ID: 4.96" (126 mm)</p>		<p>Part Number: P777523 Description: AIR SAFETY Primary App: FENDT F345200090010 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 1.97" (50 mm) Length: 11.16" (283 mm)</p>
	<p>Part Number: P777242 Description: AIR PRIMARY Primary App: DAF 667078 Dimensions: Outer Diameter: 11.88" (302 mm) Inner Diameter: 7.51" (191 mm) Length: 14.37" (365 mm)</p>		<p>Part Number: P777524 Description: AIR SAFETY Primary App: MERCEDES 0020943304 Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: 2.25" (57 mm) Length: 12.83" (326 mm)</p>
	<p>Part Number: P777243 Description: AIR PRIMARY Primary App: DAF 0112294 Dimensions: Outer Diameter: 8.89" (226 mm) Inner Diameter: 4.61" (117 mm) Length: 14.61" (371 mm)</p>		<p>Part Number: P777525 Description: AIR SAFETY Primary App: MANN & HUMMEL CF1620 Dimensions: Outer Diameter: 5.98" (152 mm) Inner Diameter: 5.35" (136 mm) Length: 13.18" (335 mm)</p>
	<p>Part Number: P777279 Description: AIR PRIMARY Primary App: DAF 1295090, PERKINS CV20948 Dimensions: Outer Diameter: 11.06" (281 mm) Inner Diameter: 6.77" (172 mm) Length: 20.08" (510 mm)</p>		<p>Part Number: P777526 Description: AIR SAFETY Primary App: MANN & HUMMEL CF1610 Dimensions: Outer Diameter: 5.98" (152 mm) Inner Diameter: 5.47" (139 mm) Length: 13.78" (350 mm)</p>







	<p>Part Number: P777551 Description: AIR SAFETY Primary App: ATLAS COPCO 161956900 Dimensions: Outer Diameter: 6.38" (162 mm) Inner Diameter: 5.47" (139 mm) Length: 18.54" (471 mm)</p>		<p>Part Number: P777759 Description: AIR SAFETY Primary App: DEUTZ 4308634 Dimensions: Outer Diameter: 3.15" (80 mm) Inner Diameter: 2.24" (57 mm) Length: 7.87" (200 mm)</p>
	<p>Part Number: P777576 Description: AIR PANEL, VENTILATION Primary App: CATERPILLAR 6C-9926 Dimensions: Width: 9.84" (250 mm) Depth: 0.95" (24 mm) Height: 11.81" (300 mm)</p>		<p>Part Number: P777767 Description: AIR PRIMARY Primary App: VOLVO 1080918, 10809184 Dimensions: Outer Diameter: 10.67" (271 mm) Inner Diameter: 6.22" (158 mm) Length: 23.19" (589 mm) Gasket ID: 7.32" (186 mm)</p>
	<p>Part Number: P777577 Description: AIR SAFETY, RADIALSEAL Primary App: FENDT Dimensions: Outer Diameter: 3.85" (98 mm) Inner Diameter: 3.11" (79 mm) Length: 13.18" (335 mm)</p>		<p>Part Number: P777776 Description: AIR PRIMARY Primary App: KOMATSU 20701K1190 Dimensions: Outer Diameter: 10.87" (276 mm) Inner Diameter: 6.50" (165 mm) Length: 15.00" (381 mm) Bolt Hole Diameter: 0.89" (23 mm) Gasket ID: 8.38" (213 mm)</p>
	<p>Part Number: P777578 Description: AIR PRIMARY, RADIALSEAL Primary App: FENDT H3112000901 Dimensions: Outer Diameter: 3.93" (100 mm) Inner Diameter: 7.48" (190 mm) Length: 13.28" (337 mm)</p>		<p>Part Number: P777777 Description: AIR SAFETY Primary App: KOMATSU 20701K1210 Dimensions: Outer Diameter: 6.43" (163 mm) Inner Diameter: 5.28" (134 mm) Length: 13.98" (355 mm)</p>
	<p>Part Number: P777579 Description: AIR PRIMARY, RADIALSEAL Primary App: M.A.N. 81083040083 Dimensions: Outer Diameter: 12.01" (305 mm) Inner Diameter: 6.65" (169 mm) Length: 18.58" (472 mm)</p>		<p>Part Number: P777779 Description: AIR SAFETY, RADIALSEAL Primary App: ATLAS WEYHAUSEN 2998145 Dimensions: Outer Diameter: 4.13" (105 mm) Inner Diameter: 3.58" (91 mm) Length: 14.06" (357 mm)</p>
	<p>Part Number: P777588 Description: AIR PRIMARY, RADIALSEAL Primary App: M.A.N. Dimensions: Outer Diameter: 7.95" (202 mm) Inner Diameter: 4.84" (123 mm) Length: 14.57" (370 mm)</p>		<p>Part Number: P777868 Description: AIR PRIMARY, RADIALSEAL Primary App: TEREX 15270188 Dimensions: Outer Diameter: 12.31" (313 mm) Inner Diameter: 6.99" (178 mm) Length: 20.08" (510 mm)</p>
	<p>Part Number: P777592 Description: AIR PRIMARY, RADIALSEAL Primary App: DAF ACHD040 Dimensions: Outer Diameter: 8.17" (208 mm) Inner Diameter: 20.35" (517 mm) Length: 3.14" (80 mm)</p>		<p>Part Number: P777869 Description: AIR SAFETY, RADIALSEAL Primary App: TEREX 15270189 Dimensions: Outer Diameter: 7.08" (180 mm) Inner Diameter: 5.90" (150 mm) Length: 19.72" (501 mm)</p>
	<p>Part Number: P777638 Description: AIR PRIMARY, RADIALSEAL Primary App: FENDT, JCB, LIEBHERR Dimensions: Outer Diameter: 8.19" (208 mm) Inner Diameter: 4.33" (110 mm) Length: 16.14" (410 mm)</p>		<p>Part Number: P777871 Description: AIR PRIMARY, RADIALSEAL Primary App: TEREX 15272252, VOLVO 11033998 Dimensions: Outer Diameter: 12.32" (313 mm) Inner Diameter: 7.01" (178 mm) Length: 22.44" (570 mm)</p>
	<p>Part Number: P777639 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSON FRG10 AIR CLEANER Dimensions: Outer Diameter: 4.27" (108 mm) Inner Diameter: 3.44" (87 mm) Length: 15.75" (400 mm)</p>		<p>Part Number: P777875 Description: AIR SAFETY, RADIALSEAL Primary App: TEREX 15272253, VOLVO 11033999 Dimensions: Outer Diameter: 6.85" (174 mm) Inner Diameter: 5.82" (148 mm) Length: 21.97" (558 mm)</p>













	<p>Part Number: P777938 Description: AIR SAFETY Primary App: RENAULT 5010269967 Dimensions: Outer Diameter: 7.28" (185 mm) Inner Diameter: 6.18" (157 mm) Length: 17.32" (440 mm)</p>		<p>Part Number: P778131 Description: AIR SAFETY Primary App: MANN & HUMMEL CF811 Dimensions: Outer Diameter: 3.62" (92 mm) Inner Diameter: 2.80" (71 mm) Length: 12.76" (324 mm)</p>
	<p>Part Number: P778027 Description: AIR SAFETY Primary App: SURE FILTER SFA1451S Dimensions: Outer Diameter: 4.27" (108 mm) Inner Diameter: 3.44" (87 mm) Length: 5.61" (142 mm)</p>		<p>Part Number: P778174 Description: AIR PRIMARY Primary App: LEYLAND Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 2.52" (64 mm) Length: 10" (254 mm) Gasket OD: 3.46" (88 mm) Gasket ID: 3.09" (79 mm)</p>
	<p>Part Number: P778081 Description: AIR PRIMARY Primary App: FIAT 1907695 Dimensions: Outer Diameter: 14.64" (372 mm) Inner Diameter: 9.44" (240 mm) Length: 19.68" (500 mm)</p>		<p>Part Number: P778320 Description: AIR PRIMARY Primary App: FARYMAN DIESEL 5410612 Dimensions: Outer Diameter: 5.00" (127 mm) Inner Diameter: 2.52" (64 mm) Length: 6.46" (164 mm) Bolt Hole Diameter: 0.33" (8 mm)</p>
	<p>Part Number: P778090 Description: AIR SAFETY Primary App: MASSEY FERGUSON 1678295M1 Dimensions: Outer Diameter: 2.95" (75 mm) Inner Diameter: 1.89" (48 mm) Length: 11.18" (284 mm)</p>		<p>Part Number: P778335 Description: AIR PRIMARY, RADIALSEAL Primary App: SCANIA 1335679 Dimensions: Outer Diameter: 11.96" (304 mm) Inner Diameter: 6.81" (173 mm) Length: 17.09" (434 mm)</p>
	<p>Part Number: P778100 Description: AIR PRIMARY Primary App: DAF 19G101, BAU1475 Dimensions: Outer Diameter: 5.24" (133 mm) Inner Diameter: 2.81" (71 mm) Length: 18" (457 mm) Gasket OD: 4.27" (109 mm) Gasket ID: 3.90" (99 mm)</p>		<p>Part Number: P778336 Description: AIR PRIMARY, RADIALSEAL Primary App: SCANIA 1335678 Dimensions: Outer Diameter: 12.00" (305 mm) Inner Diameter: 6.65" (169 mm) Length: 20.24" (514 mm)</p>
	<p>Part Number: P778108 Description: AIR PRIMARY Primary App: BEDFORD 91138957 Dimensions: Outer Diameter: 6.09" (155 mm) Inner Diameter: 3.47" (88 mm) Length: 7.76" (197 mm) Gasket OD: 4.82" (123 mm) Gasket ID: 4.45" (113 mm)</p>		<p>Part Number: P778337 Description: AIR PRIMARY Primary App: KOMATSU 6001819470 Dimensions: Outer Diameter: 6.11" (155 mm) Inner Diameter: 3.38" (86 mm) Length: 11.85" (301 mm) Bolt Hole Diameter: 0.63" (16 mm) Gasket ID: 7.64" (194 mm)</p>
	<p>Part Number: P778109 Description: AIR PRIMARY Primary App: ROVER NRC9238 Dimensions: Outer Diameter: 5.24" (133 mm) Inner Diameter: 2.81" (71 mm) Length: 12.20" (310 mm) Gasket OD: 4.27" (109 mm) Gasket ID: 3.90" (99 mm)</p>		<p>Part Number: P778339 Description: AIR SAFETY Primary App: KOMATSU 6001819480 Dimensions: Outer Diameter: 3.31" (84 mm) Inner Diameter: 2.60" (66 mm) Length: 11.02" (280 mm)</p>
	<p>Part Number: P778116 Description: AIR PRIMARY Primary App: AWD 91133369 Dimensions: Outer Diameter: 6.10" (155 mm) Inner Diameter: 3.47" (88 mm) Length: 7.76" (197 mm) Gasket OD: 5.37" (137 mm) Gasket ID: 5.00" (127 mm)</p>		<p>Part Number: P778340 Description: AIR PRIMARY Primary App: KOMATSU Z760125830 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 2.48" (63 mm) Length: 10.00" (254 mm) Bolt Hole Diameter: 0.26" (7 mm) Gasket ID: 2.56" (65 mm)</p>
	<p>Part Number: P778124 Description: AIR PRIMARY Primary App: LEYLAND DAF ACU8498 Dimensions: Outer Diameter: 9.21" (234 mm) Inner Diameter: 4.84" (123 mm) Length: 15.00" (381 mm) Gasket OD: 7.99" (203 mm) Gasket ID: 7.62" (194 mm)</p>		<p>Part Number: P778359 Description: AIR PRIMARY Primary App: RENAULT 5001826454 Dimensions: Outer Diameter: 6.59" (167 mm) Inner Diameter: 3.14" (80 mm) Length: 11.96" (304 mm)</p>

	<p>Part Number: P778361 Description: AIR SAFETY Primary App: JCB 32203703 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 2.40" (61 mm) Length: 10.98" (279 mm)</p>		<p>Part Number: P778457 Description: AIR PRIMARY Primary App: RENAULT 5430027451 Dimensions: Outer Diameter: 7.93" (202 mm) Inner Diameter: 4.57" (116 mm) Length: 13.74" (349 mm) Gasket OD: 5.43" (138 mm) Gasket ID: 5.06" (129 mm)</p>
	<p>Part Number: P778375 Description: AIR PRIMARY Primary App: LANCER BOSS P15324 Dimensions: Outer Diameter: 11.54" (293 mm) Inner Diameter: 7.40" (188 mm) Length: 14.88" (378 mm)</p>		<p>Part Number: P778462 Description: AIR PRIMARY Primary App: MERCEDES BENZ 0010949604 Dimensions: Outer Diameter: 6.50" (165 mm) Inner Diameter: 3.43" (87 mm) Length: 13.39" (340 mm) Bolt Hole Diameter: 0.33" (8 mm) Gasket ID: 4.15" (105 mm)</p>
	<p>Part Number: P778399 Description: AIR PRIMARY Primary App: MANITOU 177130 Dimensions: Outer Diameter: 6.10" (155 mm) Inner Diameter: 3.46" (88 mm) Length: 11.73" (298 mm) Bolt Hole Diameter: 0.67" (17 mm) Gasket ID: 4.72" (120 mm)</p>		<p>Part Number: P778472 Description: AIR PRIMARY Primary App: MERCEDES BENZ 0010949404 Dimensions: Outer Diameter: 8.31" (211 mm) Inner Diameter: 4.06" (103 mm) Length: 8.27" (210 mm)</p>
	<p>Part Number: P778403 Description: AIR SAFETY Primary App: VOLVO 1660377, 1661808 Dimensions: Outer Diameter: 6.88" (175 mm) Inner Diameter: 6.10" (155 mm) Length: 21.22" (539 mm)</p>		<p>Part Number: P778485 Description: AIR PRIMARY Primary App: VOLVO 111101754 Dimensions: Outer Diameter: 12.87" (327 mm) Inner Diameter: 7.51" (191 mm) Length: 18.38" (467 mm) Bolt Hole Diameter: 0.43" (11 mm) Gasket ID: 9.49" (241 mm)</p>
	<p>Part Number: P778404 Description: AIR PRIMARY Primary App: DEUTZ Dimensions: Outer Diameter: 4.33" (110 mm) Inner Diameter: 1.99" (51 mm) Length: 8.58" (218 mm) Bolt Hole Diameter: 0.33" (8 mm)</p>		<p>Part Number: P778507 Description: AIR PRIMARY, RADIALSEAL Primary App: IVECO 1908234 Dimensions: Outer Diameter: 6.14" (156 mm) Inner Diameter: 3.14" (80 mm) Length: 9.80" (249 mm)</p>
	<p>Part Number: P778415 Description: AIR PRIMARY Primary App: MASSEY FERGUSON 1678294M1, 1678296M1 Dimensions: Outer Diameter: 5.22" (133 mm) Inner Diameter: 2.95" (75 mm) Length: 12.28" (312 mm) Bolt Hole Diameter: 0.53" (13 mm) Gasket ID: 3.93" (100 mm)</p>		<p>Part Number: P778509 Description: AIR PRIMARY, RADIALSEAL Primary App: IVECO 1908233 Dimensions: Outer Diameter: 6.14" (156 mm) Inner Diameter: 3.15" (80 mm) Length: 13.54" (344 mm)</p>
	<p>Part Number: P778436 Description: AIR PRIMARY Primary App: VOLVO 1660600, 16606606 Dimensions: Outer Diameter: 10.16" (258 mm) Inner Diameter: 6.30" (160 mm) Gasket OD: 7.68" (195 mm) Gasket ID: 7.30" (186 mm)</p>		<p>Part Number: P778605 Description: AIR PRIMARY Primary App: VOLVO 15444490, 1544449 Dimensions: Outer Diameter: 13.82" (351 mm) Inner Diameter: 8.23" (209 mm) Length: 14.09" (358 mm) Bolt Hole Diameter: 0.51" (13 mm) Gasket ID: 8.70" (221 mm)</p>
	<p>Part Number: P778441 Description: AIR PRIMARY Primary App: DAF 393561 Dimensions: Outer Diameter: 9.49" (241 mm) Inner Diameter: 5.19" (132 mm) Length: 14.33" (364 mm) Bolt Hole Diameter: 0.41" (10 mm) Gasket ID: 6.26" (159 mm)</p>		<p>Part Number: P778613 Description: AIR PRIMARY Primary App: MERCEDES BENZ 0030941504 Dimensions: Outer Diameter: 11.89" (302 mm) Inner Diameter: 7.52" (191 mm) Length: 18.15" (461 mm) Bolt Hole Diameter: 0.41" (10 mm) Gasket ID: 8.46" (215 mm)</p>
	<p>Part Number: P778453 Description: AIR SAFETY, RADIALSEAL Primary App: M.A.N. 81083040084 Dimensions: Outer Diameter: 6.75" (172 mm) Inner Diameter: 5.30" (135 mm) Length: 17.80" (452 mm)</p>		<p>Part Number: P778637 Description: AIR SAFETY, RADIALSEAL Primary App: DYNAPAC 908400 Dimensions: Outer Diameter: 4.12" (105 mm) Inner Diameter: 3.58" (91 mm) Length: 14.21" (361 mm)</p>

	<p>Part Number: P778638 Description: AIR PRIMARY, RADIALSEAL Primary App: DYNAPAC 908401 Dimensions: Outer Diameter: 8.18" (208 mm) Inner Diameter: 4.17" (106 mm) Length: 14.53" (369 mm)</p>		<p>Part Number: P778857 Description: AIR SAFETY Primary App: KOMATSU 20801K1220 Dimensions: Outer Diameter: 7.28" (185 mm) Inner Diameter: 6.20" (157 mm) Length: 15.18" (386 mm)</p>
	<p>Part Number: P778674 Description: AIR PRIMARY, RADIALSEAL Primary App: Van Hool Bus 10591354 Dimensions: Outer Diameter: 12.34" (313 mm) Inner Diameter: 7.00" (178 mm) Length: 22.44" (570 mm)</p>		<p>Part Number: P778905 Description: AIR PRIMARY, RADIALSEAL Primary App: LIEBHERR 7623371, VOLVO 11110175 Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.15" (131 mm) Length: 18.15" (461 mm)</p>
	<p>Part Number: P778702 Description: AIR PRIMARY Primary App: CASE IH 1931168 Dimensions: Outer Diameter: 8.36" (212 mm) Inner Diameter: 3.42" (87 mm) Length: 13.85" (352 mm)</p>		<p>Part Number: P778906 Description: AIR SAFETY, RADIALSEAL Primary App: VOLVO 11110176 Dimensions: Outer Diameter: 17.90" (455 mm) Inner Diameter: 5.29" (135 mm) Length: 3.70" (94 mm)</p>
	<p>Part Number: P778778 Description: AIR PRIMARY Primary App: Volvo 1665908 Dimensions: Outer Diameter: 13.97" (355 mm) Inner Diameter: 7.99" (203 mm) Length: 16.45" (418 mm)</p>		<p>Part Number: P778924 Description: AIR PRIMARY, RADIALSEAL Primary App: KAESSBOHRER 83191471870 Dimensions: Outer Diameter: 11.95" (303 mm) Inner Diameter: 6.88" (175 mm) Length: 17.99" (457 mm)</p>
	<p>Part Number: P778779 Description: AIR PRIMARY Primary App: VOLVO 1665898 Dimensions: Outer Diameter: 13.09" (332 mm) Inner Diameter: 7.99" (203 mm) Length: 16.22" (412 mm) Bolt Hole Diameter: 0.39" (10 mm) Gasket ID: 4.00" (102 mm)</p>		<p>Part Number: P778972 Description: AIR PRIMARY Primary App: MANN & HUMMEL Europiclon C16400 Dimensions: Outer Diameter: 6.30" (160 mm) Inner Diameter: 3.82" (97 mm) Length: 14.80" (376 mm)</p>
	<p>Part Number: P778795 Description: AIR PRIMARY Primary App: ZETOR 53011904 Dimensions: Outer Diameter: 6.09" (155 mm) Inner Diameter: 3.47" (88 mm) Length: 10.96" (279 mm) Gasket ID: 4.72" (120 mm)</p>		<p>Part Number: P778979 Description: AIR PRIMARY Primary App: MANN & HUMMEL Europiclon C11100 Dimensions: Outer Diameter: 4.48" (114 mm) Inner Diameter: 2.64" (67 mm) Length: 9.43" (240 mm)</p>
	<p>Part Number: P778832 Description: AIR SAFETY Primary App: JCB 32903202 Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 2.93" (74 mm) Length: 10.08" (256 mm)</p>		<p>Part Number: P778984 Description: AIR PRIMARY Primary App: MANN & HUMMEL Europiclon C14200 Dimensions: Outer Diameter: 4.88" (124 mm) Inner Diameter: 3.03" (77 mm) Length: 12.13" (308 mm)</p>
	<p>Part Number: P778833 Description: AIR SAFETY Primary App: ATLAS COPCO 1613740700 Dimensions: Outer Diameter: 2.76" (70 mm) Inner Diameter: 2.40" (61 mm) Length: 9.06" (230 mm)</p>		<p>Part Number: P778989 Description: AIR PRIMARY Primary App: MANN & HUMMEL Europiclon C15300 Dimensions: Outer Diameter: 5.91" (150 mm) Inner Diameter: 3.44" (87 mm) Length: 13.62" (346 mm)</p>
	<p>Part Number: P778856 Description: AIR PRIMARY Primary App: KOMATSU 20801K1210 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.71" (196 mm) Length: 15.65" (398 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 9.00" (229 mm)</p>		<p>Part Number: P778994 Description: AIR PRIMARY Primary App: MANN & HUMMEL Europiclon C20500 Dimensions: Outer Diameter: 7.44" (189 mm) Inner Diameter: 4.61" (117 mm) Length: 15.23" (387 mm)</p>










	<p>Part Number: P780006 Description: AIR PRIMARY Primary App: LIEBHERR 7368216 Dimensions: Outer Diameter: 12.88" (327 mm) Inner Diameter: 8.50" (216 mm) Length: 23.77" (604 mm) Bolt Hole Diameter: 0.41" (10 mm) Gasket ID: 9.56" (243 mm)</p>		<p>Part Number: P780165 Description: AIR PRIMARY Primary App: DAF 0693076 Dimensions: Outer Diameter: 8.40" (213 mm) Inner Diameter: 4.02" (102 mm) Length: 11.83" (300 mm) Gasket ID: 4.50" (114 mm)</p>
	<p>Part Number: P780012 Description: AIR SAFETY Primary App: MANN & HUMMEL Europiclon CF400 Dimensions: Outer Diameter: 3.35" (85 mm) Inner Diameter: 2.79" (71 mm) Length: 14.15" (359 mm)</p>		<p>Part Number: P780175 Description: AIR PRIMARY Primary App: RENAULT 5010317060 Dimensions: Outer Diameter: 12.09" (307 mm) Inner Diameter: 7.71" (196 mm) Length: 18.23" (463 mm) Gasket OD: 9.93" (252 mm) Gasket ID: 9.56" (243 mm)</p>
	<p>Part Number: P780018 Description: AIR SAFETY Primary App: MANN & HUMMEL EUROPICLON CF100 Dimensions: Outer Diameter: 2.20" (56 mm) Inner Diameter: 1.78" (45 mm) Length: 9.33" (237 mm)</p>		<p>Part Number: P780249 Description: AIR PRIMARY Primary App: DAF 0693075 Dimensions: Outer Diameter: 8.74" (222 mm) Inner Diameter: 4.76" (121 mm) Length: 14.80" (376 mm)</p>
	<p>Part Number: P780024 Description: AIR SAFETY Primary App: MANN & HUMMEL Europiclon CF200 Dimensions: Outer Diameter: 2.56" (65 mm) Inner Diameter: 2.16" (55 mm) Length: 12.02" (305 mm)</p>		<p>Part Number: P780272 Description: AIR PRIMARY Primary App: JCB 32903001 Dimensions: Outer Diameter: 6.26" (159 mm) Inner Diameter: 2.81" (71 mm) Length: 10.91" (277 mm) D: 6.81" (173 mm) Gasket ID: 3.93" (100 mm)</p>
	<p>Part Number: P780030 Description: AIR SAFETY Primary App: MANN & HUMMEL Europiclon Dimensions: Outer Diameter: 2.95" (75 mm) Inner Diameter: 2.55" (65 mm) Length: 13.52" (343 mm)</p>		<p>Part Number: P780298 Description: AIR PANEL, VENTILATION Primary App: CAT 7X-6041 Dimensions: Width: 9.50" (241 mm) Depth: 2.19" (56 mm) Height: 12.25" (311 mm)</p>
	<p>Part Number: P780036 Description: AIR SAFETY Primary App: MANN & HUMMEL Europiclon CF500 Dimensions: Outer Diameter: 4.13" (105 mm) Inner Diameter: 3.73" (95 mm) Length: 15.21" (386 mm)</p>		<p>Part Number: P780310 Description: AIR PRIMARY Primary App: JCB 32903201 Dimensions: Outer Diameter: 7.62" (194 mm) Inner Diameter: 3.64" (92 mm) Length: 10.90" (277 mm) Gasket ID: 4.72" (120 mm)</p>
	<p>Part Number: P780135 Description: AIR PANEL, VENTILATION Primary App: CAT 3E-0410 Dimensions: Width: 7.00" (178 mm) Depth: 1.02" (26 mm) Height: 9.00" (229 mm)</p>		<p>Part Number: P780331 Description: AIR PRIMARY, RADIALSEAL Primary App: KOMATSU 42401HOP03 Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 6.57" (167 mm) Length: 15.94" (405 mm)</p>
	<p>Part Number: P780163 Description: AIR PANEL, VENTILATION Primary App: CAT 9X-3352 Dimensions: Width: 9.06" (230 mm) Depth: 2.19" (56 mm) Height: 9.06" (230 mm)</p>		<p>Part Number: P780332 Description: AIR SAFETY Primary App: HANOMAG 42401HOP02 Dimensions: Outer Diameter: 5.59" (142 mm) Inner Diameter: 3.24" (83 mm) Length: 15.27" (388 mm)</p>
	<p>Part Number: P780164 Description: AIR PRIMARY, SPECIAL Primary App: CATERPILLAR 3E0411 Dimensions: Width: 7.01" (178 mm) Length: 9.02" (229 mm)</p>		<p>Part Number: P780373 Description: AIR PRIMARY Primary App: HINO 178012960D Dimensions: Outer Diameter: 10.86" (276 mm) Inner Diameter: 6.49" (165 mm) Length: 14.17" (360 mm) Bolt Hole Diameter: 0.89" (23 mm) Gasket ID: 7.40" (188 mm)</p>

	<p>Part Number: P780385 Description: AIR PRIMARY Primary App: HITACHI 426098 Dimensions: Outer Diameter: 7.94" (202 mm) Inner Diameter: 6.38" (162 mm) Length: 10.39" (264 mm) Bolt Hole Diameter: 0.87" (22 mm) Gasket ID: 6.00" (152 mm)</p>		<p>Part Number: P780798 Description: AIR PRIMARY, RADIALSEAL Primary App: DAF 1672464 - DAF LF45 / LF55 Dimensions: Outer Diameter: 8.19" (208 mm) Inner Diameter: 4.72" (120 mm) Length: 16.57" (421 mm)</p>
	<p>Part Number: P780519 Description: AIR PRIMARY Primary App: VOLVO 1660376 Dimensions: Outer Diameter: 10.65" (271 mm) Inner Diameter: 6.97" (177 mm) Length: 22.95" (583 mm) Gasket ID: 7.30" (185 mm)</p>		<p>Part Number: P780815 Description: AIR PRIMARY Primary App: VOLVO 1665563 Dimensions: Outer Diameter: 10.15" (258 mm) Inner Diameter: 6.29" (160 mm) Length: 20.78" (528 mm)</p>
	<p>Part Number: P780522 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON FPG09 AIR CLEANERS Dimensions: Outer Diameter: 7.34" (186 mm) Inner Diameter: 4.17" (106 mm) Length: 15.26" (388 mm)</p>		<p>Part Number: P780834 Description: AIR PRIMARY Primary App: Mercedes-Benz A0030949104 Dimensions: Outer Diameter: 16.53" (420 mm) Inner Diameter: 9.96" (253 mm) Length: 12.00" (305 mm) Bolt Hole Diameter: 0.43" (11 mm)</p>
	<p>Part Number: P780523 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSON FPG09 AIR CLEANERS Dimensions: Outer Diameter: 4.27" (108 mm) Inner Diameter: 3.45" (88 mm) Length: 14.83" (377 mm)</p>		<p>Part Number: P780848 Description: AIR PRIMARY Primary App: MERCEDES BENZ 30949204 Dimensions: Outer Diameter: 16.53" (420 mm) Inner Diameter: 9.96" (253 mm) Length: 9.84" (250 mm) Bolt Hole Diameter: 0.43" (11 mm) Gasket ID: 10.55" (268 mm)</p>
	<p>Part Number: P780621 Description: AIR PRIMARY, RADIALSEAL Primary App: RVI 5010230916 Dimensions: Outer Diameter: 12.32" (313 mm) Inner Diameter: 7.71" (196 mm) Length: 21.37" (543 mm)</p>		<p>Part Number: P780910 Description: AIR PRIMARY, RADIALSEAL Primary App: DAF 1295090 Dimensions: Outer Diameter: 11.06" (281 mm) Inner Diameter: 6.57" (167 mm) Length: 20.07" (510 mm)</p>
	<p>Part Number: P780622 Description: AIR PRIMARY Primary App: Renault 5010230841 Dimensions: Outer Diameter: 12.32" (313 mm) Inner Diameter: 7.71" (196 mm) Length: 17.71" (450 mm)</p>		<p>Part Number: P780911 Description: AIR PRIMARY Primary App: DAF 1317409 Dimensions: Outer Diameter: 11.06" (281 mm) Inner Diameter: 6.57" (167 mm) Length: 18.38" (467 mm)</p>
	<p>Part Number: P780623 Description: AIR SAFETY, RADIALSEAL Primary App: RVI 5010269584 Dimensions: Outer Diameter: 6.85" (174 mm) Inner Diameter: 5.51" (140 mm) Length: 20.78" (528 mm)</p>		<p>Part Number: P781039 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON FRG10 AIR CLEANERS Dimensions: Outer Diameter: 8.18" (208 mm) Inner Diameter: 4.17" (106 mm) Length: 16.12" (410 mm)</p>
	<p>Part Number: P780624 Description: AIR SAFETY, RADIALSEAL Primary App: RVI 5010317187 Dimensions: Outer Diameter: 6.85" (174 mm) Inner Diameter: 5.51" (140 mm) Length: 17.48" (444 mm)</p>		<p>Part Number: P781098 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON FRG18 Air Cleaner Dimensions: Outer Diameter: 14.28" (363 mm) Inner Diameter: 8.98" (228 mm) Length: 24.41" (620 mm)</p>
	<p>Part Number: P780731 Description: AIR PRIMARY Primary App: EVOBUS 83191501920 Dimensions: Outer Diameter: 11.92" (303 mm) Inner Diameter: 6.88" (175 mm) Length: 12.55" (319 mm)</p>		<p>Part Number: P781102 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSON FRG18 Air Cleaner Dimensions: Outer Diameter: 9.09" (231 mm) Inner Diameter: 6.94" (176 mm) Length: 24.57" (624 mm)</p>
			<p>Part Number: P781176 Description: AIR PANEL, VENTILATION Primary App: CATEPILLAR VENT CAB AIR APPLICATIONS Dimensions: Width: 4.84" (123 mm) Depth: 23.62" (600 mm) Height: 0.95" (24 mm)</p>


	<p>Part Number: P781187 Description: AIR PRIMARY Primary App: . Dimensions: Outer Diameter: 12.31" (313 mm) Inner Diameter: 6.99" (178 mm) Length: 22.44" (570 mm)</p>		<p>Part Number: P781465 Description: AIR PRIMARY Primary App: MERCEDES-BENZ 30949604 Dimensions: Outer Diameter: 11.08" (282 mm) Inner Diameter: 5.66" (144 mm) Length: 12.24" (311 mm)</p>
	<p>Part Number: P781203 Description: AIR SAFETY Primary App: NEW HOLLAND 84072430 Dimensions: Outer Diameter: 5.59" (142 mm) Inner Diameter: 3.22" (82 mm) Length: 21.88" (556 mm)</p>		<p>Part Number: P781466 Description: AIR DRYER SPIN ON Primary App: Mercedes-Benz : Actros I, Actros II, Atego, Vario Dimensions: Outer Diameter: 5.51" (140 mm) Thread Size: M39 x 1.5 Length: 6.50" (165 mm)</p>
	<p>Part Number: P781228 Description: AIR SAFETY, RADIALSEAL Primary App: SCANIA 1335680Z Dimensions: Outer Diameter: 6.75" (171 mm) Inner Diameter: 5.15" (131 mm) Length: 19.82" (504 mm)</p>		<p>Part Number: P781470 Description: AIR PRIMARY Primary App: DYNAPAC 909270 Dimensions: Outer Diameter: 8.14" (207 mm) Inner Diameter: 4.61" (117 mm) Length: 20.03" (509 mm)</p>
	<p>Part Number: P781349 Description: AIR PANEL, VENTILATION Primary App: M&H 641500 Dimensions: Width: 5.94" (151 mm) Depth: 2.75" (70 mm) Height: 23.85" (606 mm)</p>		<p>Part Number: P781471 Description: AIR SAFETY Primary App: DYNAPAC 909271 Dimensions: Outer Diameter: 4.27" (108 mm) Inner Diameter: 3.47" (88 mm) Length: 19.72" (501 mm)</p>
	<p>Part Number: P781350 Description: AIR PRIMARY Primary App: M&H C291219/1 Dimensions: Outer Diameter: 11.06" (281 mm) Inner Diameter: 4.99" (127 mm) Length: 15.94" (405 mm)</p>		<p>Part Number: P781525 Description: AIR PRIMARY Primary App: DAF 1353115 Dimensions: Outer Diameter: 11.06" (281 mm) Inner Diameter: 6.57" (167 mm) Length: 19.44" (494 mm)</p>
	<p>Part Number: P781351 Description: AIR SAFETY Primary App: M&H CF2100 Dimensions: Outer Diameter: 8.30" (211 mm) Inner Diameter: 7.72" (196 mm) Length: 23.97" (609 mm)</p>		<p>Part Number: P781530 Description: AIR PRIMARY Primary App: MANN AND HUMMEL C21461 Dimensions: Outer Diameter: 6.69" (170 mm) Inner Diameter: 4.05" (103 mm) Length: 10.37" (264 mm) Gasket ID: 6.69" (170 mm)</p>
	<p>Part Number: P781352 Description: AIR SAFETY Primary App: M&H CF830 Dimensions: Outer Diameter: 3.24" (82 mm) Length: 12.24" (311 mm)</p>		<p>Part Number: P781640 Description: AIR PRIMARY, RADIALSEAL Primary App: CATERPILLAR 1421340 Dimensions: Outer Diameter: 12.32" (313 mm) Inner Diameter: 6.99" (178 mm) Length: 20.07" (510 mm)</p>
	<p>Part Number: P781373 Description: AIR PRIMARY Primary App: JOHN DEERE AL78869 Dimensions: Outer Diameter: 8.90" (226 mm) Inner Diameter: 4.65" (118 mm) Length: 12.34" (314 mm)</p>		<p>Part Number: P781678 Description: AIR PRIMARY Primary App: CASE H187471 Dimensions: Outer Diameter: 8.17" (208 mm) Inner Diameter: 6.88" (175 mm) Length: 15.14" (385 mm)</p>
	<p>Part Number: P781398 Description: AIR PRIMARY, RADIALSEAL Primary App: VOLVO 11110217 Dimensions: Outer Diameter: 14.28" (363 mm) Inner Diameter: 8.98" (228 mm) Length: 18.90" (480 mm)</p>		<p>Part Number: P781682 Description: AIR PANEL, VENTILATION Primary App: MAN 81619100011 Dimensions: Width: 7.09" (180 mm) Depth: 1.57" (40 mm) Height: 15.74" (400 mm)</p>
	<p>Part Number: P781399 Description: AIR SAFETY, RADIALSEAL Primary App: VOLVO 11110218 Dimensions: Outer Diameter: 9.09" (231 mm) Inner Diameter: 6.94" (176 mm) Length: 19.06" (484 mm)</p>		

<p>Part Number: P781740 Description: AIR PRIMARY, RADIALSEAL Primary App: SCANIA 1387549 Dimensions: Outer Diameter: 12.12" (308 mm) Inner Diameter: 6.90" (176 mm) Length: 17.09" (434 mm)</p>	 <p>Part Number: P782138 Description: AIR PANEL Primary App: CASE IH 80441838 Dimensions: Width: 7.95" (202 mm) Depth: 2.18" (55 mm) Height: 31.41" (798 mm)</p>
 <p>Part Number: P781741 Description: AIR PRIMARY Primary App: KNECHT LX605 Dimensions: Outer Diameter: 12.12" (308 mm) Inner Diameter: 6.91" (176 mm) Length: 21.44" (544 mm)</p>	 <p>Part Number: P782299 Description: AIR PRIMARY Primary App: DYNAPAC 380295 Dimensions: Outer Diameter: 5.03" (128 mm) Inner Diameter: 3.18" (81 mm) Length: 9.37" (238 mm)</p>
 <p>Part Number: P781746 Description: AIR PRIMARY, OVAL Primary App: HATZ 952900 Dimensions: Width: 6.41" (163 mm) Height: 3.66" (93 mm) Length: 9.56" (243 mm)</p>	 <p>Part Number: P782300 Description: AIR SAFETY, RADIALSEAL Primary App: DYNAPAC 380294 Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 2.54" (65 mm) Length: 8.89" (226 mm)</p>
 <p>Part Number: P782104 Description: AIR PRIMARY, RADIALSEAL Primary App: MANN AND HUMMELL C23610 Dimensions: Outer Diameter: 8.66" (220 mm) Inner Diameter: 5.03" (128 mm) Length: 15.90" (404 mm)</p>	 <p>Part Number: P782328 Description: AIR PRIMARY, RADIALSEAL Primary App: DAF 1385791, 1346885 Dimensions: Outer Diameter: 9.68" (246 mm) Inner Diameter: 4.92" (125 mm) Length: 16.50" (419 mm)</p>
 <p>Part Number: P782105 Description: AIR PRIMARY, RADIALSEAL Primary App: MANN & HUMMEL C25710, MF 3902806M1 Dimensions: Outer Diameter: 9.44" (240 mm) Inner Diameter: 5.78" (147 mm) Length: 21.22" (539 mm)</p>	 <p>Part Number: P782396 Description: AIR PRIMARY, RADIALSEAL Primary App: VOLVO 8149961 Dimensions: Outer Diameter: 13.09" (332 mm) Inner Diameter: 8.66" (220 mm) Length: 15.57" (396 mm)</p>
 <p>Part Number: P782106 Description: AIR PRIMARY, RADIALSEAL Primary App: ATLAS COPCO 2914501700 Dimensions: Outer Diameter: 11.73" (298 mm) Inner Diameter: 8.07" (205 mm) Length: 23.38" (594 mm)</p>	 <p>Part Number: P782596 Description: AIR PRIMARY, RADIALSEAL Primary App: M.A.N. 81083040087 Dimensions: Outer Diameter: 9.68" (246 mm) Inner Diameter: 4.92" (125 mm) Length: 15.07" (383 mm)</p>
 <p>Part Number: P782107 Description: AIR SAFETY, RADIALSEAL Primary App: BOMAG 5821150 Dimensions: Outer Diameter: 4.60" (117 mm) Inner Diameter: 4.48" (114 mm) Length: 15.19" (386 mm)</p>	 <p>Part Number: P782811 Description: AIR PANEL, VENTILATION Primary App: VOLVO 8143691 Dimensions: Width: 8.26" (210 mm) Depth: 1.57" (40 mm) Height: 8.26" (210 mm)</p>
 <p>Part Number: P782108 Description: AIR SAFETY, RADIALSEAL Primary App: ATLAS COPCO 2914502400 Dimensions: Outer Diameter: 5.43" (138 mm) Inner Diameter: 7.59" (193 mm) Length: 20.55" (522 mm)</p>	<p>Part Number: P782857 Description: AIR PRIMARY Primary App: VOLVO Dimensions: Outer Diameter: 11.96" (304 mm) Inner Diameter: 5.83" (148 mm) Length: 15.98" (406 mm)</p>
 <p>Part Number: P782109 Description: AIR SAFETY, RADIALSEAL Primary App: ATLAS COPCO 2914501800 Dimensions: Outer Diameter: 7.75" (197 mm) Inner Diameter: 7.59" (193 mm) Length: 22.51" (572 mm)</p>	<p>Part Number: P782879 Description: AIR PRIMARY Primary App: VALTRA TRACTOR Dimensions: Outer Diameter: 6.50" (165 mm) Inner Diameter: 3.43" (87 mm) Length: 14.61" (371 mm)</p>
 <p>Part Number: P782137 Description: AIR PRIMARY Primary App: RENAULT V.I. 5010315990 Dimensions: Outer Diameter: 9.68" (246 mm) Inner Diameter: 5.09" (129 mm) Length: 14.68" (373 mm)</p>	 <p>Part Number: P782880 Description: AIR PRIMARY Primary App: AM VERSION OF M&H C25860/1 Dimensions: Outer Diameter: 9.72" (247 mm) Inner Diameter: 5.47" (139 mm) Length: 15.43" (392 mm) Overall Length: 16.34" (415 mm)</p>






	<p>Part Number: P782881 Description: AIR PRIMARY Primary App: AM VERSION OF M&H C25660 Dimensions: Outer Diameter: 9.72" (247 mm) Inner Diameter: 5.90" (150 mm) Length: 12.24" (311 mm)</p>	<p>Part Number: P783289 Description: AIR PRIMARY, RADIALSEAL Primary App: DAF 1672463 - DAF LF45/LF55 Dimensions: Outer Diameter: 12.13" (308 mm) Inner Diameter: 6.93" (176 mm) Length: 20.24" (514 mm)</p>
	<p>Part Number: P782936 Description: AIR PRIMARY Primary App: M&H C271250 Dimensions: Outer Diameter: 10.51" (267 mm) Inner Diameter: 6.69" (170 mm) Length: 19.17" (487 mm)</p>	<p>Part Number: P783386 Description: AIR PANEL Primary App: MERCEDES-BENZ 0008354047 Dimensions: Outer Diameter: 7.09" (180 mm) Inner Diameter: 4.72" (120 mm) Height: 3.39" (86 mm)</p>
	<p>Part Number: P782937 Description: AIR SAFETY Primary App: M.A.N. 81084050017 Dimensions: Outer Diameter: 6.12" (156 mm) Inner Diameter: 5.39" (137 mm) Length: 16.37" (416 mm)</p>	<p>Part Number: P783387 Description: AIR PANEL Primary App: MERCEDES-BENZ 0008356247 Dimensions: Outer Diameter: 7.13" (181 mm) Inner Diameter: 4.72" (120 mm) Height: 3.31" (84 mm)</p>
	<p>Part Number: P782998 Description: AIR PRIMARY, RADIALSEAL Primary App: MANN 81.08304.0093 and M&H C25978 Dimensions: Outer Diameter: 9.68" (246 mm) Inner Diameter: 7.91" (201 mm) Length: 19.72" (501 mm)</p>	 <p>Part Number: P783400 Description: AIR PRIMARY Primary App: Fendt H916.201.091.050 Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 5.82" (148 mm) Length: 17.66" (448 mm)</p>
	<p>Part Number: P783024 Description: AIR PANEL Primary App: LIEBHERR 7618809 Dimensions: Width: 6.73" (171 mm) Length: 23.54" (598 mm) Height: 1.97" (50 mm)</p>	 <p>Part Number: P783432 Description: AIR PRIMARY Primary App: Massey Ferguson 1644333M1 Tractor 2640 / 2675 / 2705 / 3505 / 3525 / 3545 Dimensions: Outer Diameter: 8.31" (211 mm) Inner Diameter: 5.30" (135 mm) Length: 12.28" (312 mm)</p>
	<p>Part Number: P783117 Description: AIR PRIMARY, RADIALSEAL Primary App: VAN HOOL BUS Dimensions: Outer Diameter: 7.33" (186 mm) Inner Diameter: 4.16" (106 mm) Length: 13.70" (348 mm)</p>	<p>Part Number: P783462 Description: AIR PANEL Primary App: CASE 134584216 Dimensions: Width: 6.81" (173 mm) Length: 9.61" (244 mm) Height: 1.97" (50 mm)</p>
	<p>Part Number: P783197 Description: AIR PANEL, ENGINE Primary App: aftermarket version of Mercedes Benz 002 094 9204 (or Virgis PF15690); Dimensions: Width: 6.77" (172 mm) Depth: 1.98" (50 mm) Height: 23.50" (597 mm)</p>	 <p>Part Number: P783500 Description: AIR PRIMARY, RADIALSEAL Primary App: John Deere 6000 and 7200 series Dimensions: Outer Diameter: 7.28" (185 mm) Inner Diameter: 3.60" (91 mm) Length: 12.34" (314 mm)</p>
	<p>Part Number: P783198 Description: AIR PANEL, ENGINE Primary App: aftermarket version of Mercedes Benz 002 094 9304 (or Virgis PF15693) Dimensions: Width: 6.77" (172 mm) Depth: 2.76" (70 mm) Height: 23.50" (597 mm)</p>	 <p>Part Number: P783501 Description: AIR SAFETY, RADIALSEAL Primary App: JOHN DEERE 6000 SERIES Dimensions: Outer Diameter: 5.04" (128 mm) Inner Diameter: 3.62" (92 mm) Length: 5.22" (132 mm)</p>
	<p>Part Number: P783280 Description: AIR PRIMARY Primary App: TEREX 15273424 Dimensions: Outer Diameter: 14.28" (363 mm) Inner Diameter: 7.20" (183 mm) Length: 20.24" (514 mm)</p>	 <p>Part Number: P783554 Description: AIR PRIMARY, RADIALSEAL Primary App: FPG10 SERIES FLAME RETARDANT Dimensions: Outer Diameter: 8.18" (208 mm) Inner Diameter: 4.17" (106 mm) Length: 13.74" (349 mm)</p>
	<p>Part Number: P783281 Description: AIR SAFETY Primary App: TEREX 15273424 Dimensions: Outer Diameter: 9.09" (231 mm) Inner Diameter: 6.94" (176 mm) Length: 20.23" (514 mm)</p>	 <p>Part Number: P783611 Description: AIR PRIMARY, RADIALSEAL Primary App: Volvo 11110532 Dimensions: Outer Diameter: 14.28" (363 mm) Inner Diameter: 8.98" (228 mm) Length: 21.89" (556 mm)</p>



















	<p>Part Number: P783612 Description: AIR SAFETY Primary App: Volvo 11110533 Dimensions: Outer Diameter: 9.09" (231 mm) Inner Diameter: 6.94" (176 mm) Length: 22.05" (560 mm)</p>	<p>Part Number: P783871 Description: AIR PRIMARY, RADIALSEAL Primary App: DAF LF45 Dimensions: Outer Diameter: 8.18" (208 mm) Inner Diameter: 4.73" (120 mm) Length: 12.64" (321 mm)</p>
	<p>Part Number: P783642 Description: AIR PANEL Primary App: Evobus 0018356247 Dimensions: Width: 4.61" (117 mm) Length: 10.91" (277 mm) Height: 0.51" (13 mm)</p>	<p>Part Number: P784015 Description: AIR PANEL Primary App: Mercedes Benz Sprinter Series Dimensions: Width: 10.35" (263 mm) Depth: 3.15" (80 mm) Height: 11.93" (303 mm)</p>
	<p>Part Number: P783648 Description: AIR PRIMARY, SPECIAL Primary App: ATLAS COPCO 3214623900 Dimensions: Outer Diameter: 4.72" (120 mm) Thread Size: M76 x 4 Length: 23.62" (600 mm)</p>	<p>Part Number: P784036 Description: HYDRAULIC CARTRIDGE Primary App: A/R 900 (B)Litronic with Deutz BF4m1013E Dimensions: Outer Diameter: 6.14" (156 mm) Inner Diameter: 3.16" (80 mm) Length: 24.84" (631 mm)</p>
	<p>Part Number: P783687 Description: AIR PANEL, VENTILATION Primary App: FENDT GT SERIES Dimensions: Width: 4.29" (109 mm) Depth: 2.16" (55 mm) Height: 23.74" (603 mm)</p>	 <p>Part Number: P784037 Description: HYDRAULIC CARTRIDGE Primary App: R934 LITRONIC Dimensions: Outer Diameter: 6.14" (156 mm) Inner Diameter: 3.16" (80 mm) Length: 24.84" (631 mm)</p>
	<p>Part Number: P783729 Description: AIR PRIMARY Primary App: New Holland tractors 89846494 Dimensions: Outer Diameter: 9.90" (252 mm) Inner Diameter: 6.04" (154 mm) Length: 15.53" (395 mm)</p>	 <p>Part Number: P784198 Description: AIR PRIMARY Primary App: MAN Bus (Neoman) nl, NM, NUE serie Dimensions: Outer Diameter: 9.76" (248 mm) Inner Diameter: 5.90" (150 mm) Length: 15.43" (392 mm)</p>
	<p>Part Number: P783730 Description: AIR PRIMARY, RADIALSEAL Primary App: MANITOU 563416, LIFT TRUCK Dimensions: Outer Diameter: 6.48" (164 mm) Inner Diameter: 3.58" (91 mm) Length: 13.08" (332 mm)</p>	 <p>Part Number: P784269 Description: AIR PRIMARY, FINNED Primary App: Donaldson branded version of a P782344 Dimensions: Outer Diameter: 5.24" (133 mm) Inner Diameter: 3.32" (84 mm) Length: 10.87" (276 mm)</p>
	<p>Part Number: P783731 Description: AIR SAFETY, RADIALSEAL Primary App: MANITOU 563415, LIFT TRUCK Dimensions: Outer Diameter: 3.46" (88 mm) Inner Diameter: 2.92" (74 mm) Length: 12.84" (326 mm)</p>	<p>Part Number: P784456 Description: AIR PRIMARY Primary App: Iveco autobus (IRISBUS) EuroClass & EuroRider 42537392 Dimensions: Outer Diameter: 10.52" (267 mm) Inner Diameter: 6.69" (170 mm) Length: 19.41" (493 mm)</p>
	<p>Part Number: P783753 Description: AIR DRYER SPIN ON Primary App: SCANIA P-R-T SERIES 4 Dimensions: Outer Diameter: 5.51" (140 mm) Thread Size: G 1 1/4 Length: 6.93" (176 mm)</p>	<p>Part Number: P784457 Description: AIR PRIMARY Primary App: Daimler Chrysler Actros II Dimensions: Outer Diameter: 10.51" (267 mm) Inlet Diameter: 6.69" (170 mm) Length: 19.41" (493 mm)</p>
	<p>Part Number: P783756 Description: AIR SAFETY Primary App: VOLVO 1544298, 15442981 Dimensions: Outer Diameter: 7.80" (198 mm) Inner Diameter: 6.54" (166 mm) Length: 12.36" (314 mm) Gasket OD: 7.11" (181 mm) Gasket ID: 6.73" (171 mm)</p>	<p>Part Number: P784467 Description: AIR PRIMARY Primary App: Renault Bus FR1, Renault truck C serie Dimensions: Outer Diameter: 11.89" (302 mm) Inner Diameter: 7.52" (191 mm) Length: 15.91" (404 mm)</p>
	<p>Part Number: P783870 Description: AIR PRIMARY, RADIALSEAL Primary App: DAF LF55 Dimensions: Outer Diameter: 8.18" (208 mm) Inner Diameter: 4.73" (120 mm) Length: 16.02" (407 mm)</p>	<p>Part Number: P784473 Description: AIR PANEL, ENGINE Primary App: Mercedes Benz Actros I & II 0008301118 Dimensions: Width: 5.28" (134 mm) Depth: 1.46" (37 mm) Height: 14.96" (380 mm)</p>
		<p>Part Number: P784479 Description: AIR PANEL, ENGINE Primary App: Donaldson Branded version of M&H CU 2956 Dimensions: Width: 11.34" (288 mm) Depth: 1.18" (30 mm) Height: 6.30" (160 mm)</p>






<p>Part Number: P784525 Description: AIR PRIMARY Primary App: DAF 1363024 MANN C271170/4 SCHUPP SL81236 Dimensions: Outer Diameter: 10.52" (267 mm) Inner Diameter: 6.69" (170 mm) Length: 17.32" (440 mm)</p>	<p>Part Number: P784907 Description: AIR PANEL Primary App: EVOBUS 0018359147 Dimensions: Width: 9.06" (230 mm) Length: 19.68" (500 mm) Height: 1.97" (50 mm)</p>
 <p>Part Number: P784569 Description: AIR SAFETY Primary App: DONALDSON BRANDED VERSION OF R801925 Dimensions: Outer Diameter: 8.64" (219 mm) Inner Diameter: 7.06" (179 mm) Length: 22.16" (563 mm)</p>	<p>Part Number: P784971 Description: AIR PANEL Primary App: MERCEDES BENZ ATEGO I & II Dimensions: Width: 6.65" (169 mm) Depth: 1.18" (30 mm) Height: 22.99" (584 mm)</p>
<p>Part Number: P784574 Description: AIR PANEL, VENTILATION Primary App: New Holland 81868102 Dimensions: Width: 4.09" (104 mm) Depth: 1.93" (49 mm) Height: 20.45" (520 mm)</p>	<p>Part Number: P785001 Description: AIR PRIMARY, RADIALSEAL Primary App: Man TGL Series 81084050023 Dimensions: Outer Diameter: 8.94" (227 mm) Inner Diameter: 5.12" (130 mm) Length: 12.00" (305 mm)</p>
 <p>Part Number: P784578 Description: AIR PRIMARY Primary App: MERCEDES BENZ EVOBUS SETRA S400 0009891311 Dimensions: Outer Diameter: 3.94" (100 mm) Inner Diameter: 2.64" (67 mm) Length: 3.11" (67 mm)</p>	<p>Part Number: P785002 Description: AIR PRIMARY, RADIALSEAL Primary App: Man TGL Series 81084050022 Dimensions: Outer Diameter: 9.13" (232 mm) Inner Diameter: 5.91" (150 mm) Length: 16.34" (415 mm)</p>
 <p>Part Number: P784609 Description: AIR PRIMARY Primary App: Daf Leyland 45 /55 series Dimensions: Outer Diameter: 8.18" (208 mm) Inner Diameter: 4.73" (120 mm) Length: 13.66" (347 mm)</p>	<p>Part Number: P785046 Description: AIR PANEL Primary App: DAF TRUCKS CF65, CF75, 75CF, 85CF 1322259 Dimensions: Length: 17.00" (432 mm) Height: 0.94" (24 mm) Width: 6.65" (169 mm)</p>
 <p>Part Number: P784733 Description: AIR PRIMARY Primary App: Manitou tractor 150/170 ATT; 150 ATS serie 1&2; 165 ATJ; 2000 L Mainreach; BT 420/425; MB21C, MB26C Dimensions: Outer Diameter: 5.24" (133 mm) Inner Diameter: 2.64" (67 mm) Length: 10.59" (269 mm)</p>	<p>Part Number: P785307 Description: AIR PANEL Primary App: IVECO EUROTECH / EUROSTAR / EUROTRAKKER 500387947 Dimensions: Length: 17.31" (440 mm) Height: 1.37" (35 mm) Width: 3.90" (99 mm)</p>
 <p>Part Number: P784784 Description: AIR PRIMARY Primary App: Tatra 815 Buses Dimensions: Outer Diameter: 11.90" (302 mm) Inner Diameter: 7.51" (191 mm) Length: 18.11" (460 mm)</p>	<p>Part Number: P785352 Description: AIR PRIMARY, RADIALSEAL Primary App: Iveco Stralis - Trakker 41270082 Dimensions: Outer Diameter: 12.34" (314 mm) Inner Diameter: 8.52" (217 mm) Length: 18.15" (461 mm)</p>
<p>Part Number: P784850 Description: AIR SAFETY Primary App: MCFE 9186105700 Dimensions: Outer Diameter: 3.38" (86 mm) Inner Diameter: 2.25" (57 mm) Length: 10.00" (254 mm)</p>	<p>Part Number: P785353 Description: AIR PRIMARY, RADIALSEAL Primary App: Daf 136 3023 - 65CF/75CF Dimensions: Outer Diameter: 10.51" (267 mm) Inner Diameter: 6.69" (170 mm) Length: 16.53" (420 mm)</p>
<p>Part Number: P784863 Description: AIR PRIMARY Primary App: AGCO FENDT Dimensions: Outer Diameter: 11.09" (282 mm) Inner Diameter: 5.82" (148 mm) Length: 17.66" (449 mm)</p>	<p>Part Number: P785365 Description: AIR PANEL Primary App: DAF CF65, CF 75, CF 85 1362124 Dimensions: Length: 10.24" (260 mm) Height: 1.50" (38 mm) Width: 6.46" (164 mm)</p>
<p>Part Number: P784906 Description: AIR PANEL Primary App: FENDT H816810140070 Dimensions: Width: 4.72" (120 mm) Length: 15.98" (406 mm) Height: 2.20" (56 mm)</p>	<p>Part Number: P785366 Description: AIR PANEL Primary App: MERCEDES BENZ ACTROS I & II 0008301218 Dimensions: Length: 15.37" (391 mm) Height: 1.53" (39 mm) Width: 5.65" (144 mm)</p>
<p>Part Number: P785373 Description: FUEL CARTRIDGE Primary App: Man TGL Series 51125030061 Dimensions: Outer Diameter: 3.74" (95 mm) Inner Diameter: 1.81" (46 mm) Length: 6.79" (173 mm)</p>	

<p>Part Number: P785394 Description: AIR PRIMARY Primary App: Primary element for B180016 Dimensions: Outer Diameter: 14.29" (363 mm) Inner Diameter: 8.98" (228 mm) Overall Length: 24.49" (622 mm)</p>		<p>Part Number: P785965 Description: AIR SAFETY Primary App: CATERPILLAR BACKHOE LOADER Dimensions: Width: 5.51" (140 mm) Inner Diameter: 8.19" (208 mm) Length: 1.77" (45 mm)</p>
<p>Part Number: P785513 Description: AIR SAFETY Primary App: Hitachi excavators 4247975 Dimensions: Outer Diameter: 3.88" (99 mm) Inner Diameter: 3.15" (80 mm) Length: 11.22" (285 mm)</p>		<p>Part Number: P786092 Description: AIR PANEL Primary App: MAN TGL SERIES AND TGA SERIES 81619100019 Dimensions: Width: 6.97" (177 mm) Length: 18.39" (467 mm) Height: 2.76" (70 mm)</p>
<p>Part Number: P785518 Description: AIR PRIMARY Primary App: Scania 1728667 Dimensions: Outer Diameter: 11.96" (304 mm) Inner Diameter: 6.64" (169 mm)</p>	<p>Part Number: P786114 Description: AIR PANEL Primary App: LIEBHERR 7009621 Dimensions: Width: 5.28" (134 mm) Length: 13.15" (334 mm) Height: 1.61" (41 mm)</p>	
<p>Part Number: P785519 Description: AIR PRIMARY Primary App: Scania 1728817 Dimensions: Outer Diameter: 11.96" (304 mm) Inner Diameter: 6.64" (169 mm) Length: 20.31" (516 mm)</p>	<p>Part Number: P786335 Description: AIR PANEL Primary App: MAN TGA & TGL 81619100018 Dimensions: Width: 18.58" (472 mm) Depth: 7.44" (189 mm) Height: 2.76" (70 mm)</p>	
<p>Part Number: P785520 Description: AIR PRIMARY Primary App: Scania Trucks serie T, R, P and 4 Dimensions: Outer Diameter: 11.92" (303 mm) Inner Diameter: 6.91" (176 mm) Length: 17.04" (433 mm)</p>	<p>Part Number: P786360 Description: AIR SAFETY Primary App: SCANIA 1872154 Dimensions: Outer Diameter: 7.20" (183 mm) Inner Diameter: 5.55" (141 mm) Length: 19.80" (503 mm)</p>	
<p>Part Number: P785522 Description: AIR PRIMARY Primary App: FLAME RETARDANT, UL APPROVED, Renault 5001865723 Dimensions: Outer Diameter: 12.32" (313 mm) Inner Diameter: 7.93" (202 mm) Length: 17.76" (451 mm)</p>	<p>Part Number: P786362 Description: AIR SAFETY Primary App: SCANIA 1872153 Dimensions: Outer Diameter: 7.20" (183 mm) Inner Diameter: 5.55" (141 mm) Length: 16.69" (424 mm)</p>	
<p>Part Number: P785530 Description: AIR PRIMARY Primary App: FLAME RETARDANT, UL APPROVED, Renault 5001865725 Dimensions: Outer Diameter: 12.32" (313 mm) Inner Diameter: 6.99" (178 mm) Length: 21.38" (543 mm)</p>	<p>Part Number: P786385 Description: AIR PANEL Primary App: MERCEDES-BENZ 3568303818 Dimensions: Width: 8.86" (225 mm) Length: 19.57" (497 mm) Height: 1.50" (38 mm)</p>	
<p>Part Number: P785542 Description: AIR PRIMARY Primary App: Mercedes Benz Actros II & Axor I & Axor II Dimensions: Outer Diameter: 20.49" (521 mm) Inner Diameter: 8.66" (220 mm) Length: 13.50" (343 mm)</p>	<p>Part Number: P786386 Description: AIR PANEL Primary App: MERCEDES-BENZ 3568303918 Dimensions: Width: 8.86" (225 mm) Length: 20.71" (526 mm) Height: 1.89" (48 mm)</p>	
<p>Part Number: P785589 Description: AIR PRIMARY Primary App: FRG100240 - Preferred A/C Dimensions: Outer Diameter: 8.19" (208 mm) Inner Diameter: 4.17" (106 mm) Overall Length: 16.22" (412 mm)</p>	<p>Part Number: P786405 Description: AIR PANEL Primary App: NEOPLAN STARLINER 180740300 Dimensions: Width: 10.04" (255 mm) Length: 15.53" (395 mm) Height: 1.18" (30 mm)</p>	
<p>Part Number: P785770 Description: FUEL CARTRIDGE Primary App: DAF 1450184 Dimensions: Outer Diameter: 3.50" (89 mm) Inner Diameter: 1.81" (46 mm) Length: 8.62" (219 mm)</p>	<p>Part Number: P786440 Description: AIR PRIMARY Primary App: DEUTZ 173972 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 2.52" (64 mm) Length: 4.92" (125 mm)</p>	
<p>Part Number: P785830 Description: AIR PRIMARY, RADIALSEAL Primary App: Flame retardant version of P777579 Dimensions: Outer Diameter: 11.96" (304 mm) Inner Diameter: 6.64" (169 mm) Length: 19.05" (484 mm)</p>	<p>Part Number: P786442 Description: AIR PRIMARY Primary App: HITACHI L4206099 Dimensions: Outer Diameter: 6.10" (155 mm) Inner Diameter: 4.09" (104 mm) Length: 12.01" (305 mm)</p>	

Part Number: P786443 Description: AIR PRIMARY Primary App: DAF 1638054 Dimensions: Outer Diameter: 8.61" (219 mm) Inner Diameter: 5.82" (148 mm) Length: 20.10" (511 mm)	Part Number: P787247 Description: AIR SAFETY Primary App: IVECO 41214149 Dimensions: Outer Diameter: 7.91" (201 mm) Inner Diameter: 7.68" (195 mm) Length: 18.15" (461 mm)
Part Number: P786611 Description: AIR PANEL Primary App: SCANIA 1420197 - SCANIA 94/114/124/144/164 SERIES Dimensions: Width: 6.77" (172 mm) Depth: 1.18" (30 mm) Height: 8.74" (222 mm) Efficiency @ 99% Percent	Part Number: P787391 Description: AIR PANEL Primary App: MERCEDES-BENZ 0008301518 Dimensions: Width: 5.79" (147 mm) Length: 16.46" (418 mm) Height: 1.46" (37 mm)
Part Number: P786789 Description: AIR PRIMARY Primary App: Honda 17210ZE0822 Dimensions: Outer Diameter: 2.91" (74 mm) Length: 4.06" (103 mm) Height: 2.05" (52 mm)	Part Number: P787392 Description: AIR PANEL Primary App: EVOBUS 43443230000 Dimensions: Width: 4.80" (122 mm) Length: 19.61" (498 mm) Height: 0.98" (25 mm)
Part Number: P786816 Description: AIR PRIMARY Primary App: EVOBUS (MERCEDES-BENZ / SETRA) CITARO / CONECTO Dimensions: Outer Diameter: 11.89" (302 mm) Inner Diameter: 7.48" (190 mm) Length: 18.58" (472 mm)	Part Number: P787408 Description: AIR PANEL Primary App: MERCEDES-BENZ 0008356947 Dimensions: Width: 6.97" (177 mm) Length: 13.54" (344 mm) Height: 1.10" (28 mm)
Part Number: P786843 Description: AIR SAFETY Primary App: Case 294293A1 Dimensions: Outer Diameter: 8.11" (206 mm) Inner Diameter: 6.50" (165 mm) Length: 10.51" (267 mm)	Part Number: P787436 Description: AIR PANEL Primary App: MERCEDES-BENZ 0018354747 Dimensions: Width: 7.91" (201 mm) Length: 21.38" (543 mm) Height: 0.79" (20 mm)
Part Number: P786889 Description: AIR PRIMARY Primary App: HONDA 17210ZE1505 Dimensions: Width: 2.91" (74 mm) Length: 4.06" (103 mm) Height: 2.80" (71 mm)	Part Number: P787437 Description: AIR PANEL Primary App: MAN 88779100003 Dimensions: Width: 5.87" (149 mm) Length: 8.66" (220 mm) Height: 0.79" (20 mm)
Part Number: P786892 Description: AIR PRIMARY Primary App: RENAULT 5001865724 Dimensions: Outer Diameter: 9.69" (246 mm) Inner Diameter: 4.96" (126 mm) Length: 14.13" (359 mm)	Part Number: P787438 Description: AIR PANEL Primary App: VAN HOOL 8270039293 Dimensions: Width: 7.09" (180 mm) Length: 16.06" (408 mm) Height: 1.18" (30 mm)
Part Number: P787036 Description: AIR PRIMARY, KONEPAC™ Primary App: FLAME RETARDANT VERSION OF P129472 Dimensions: Outer Diameter: 8.66" (220 mm) Inner Diameter: 5.20" (132 mm) Length: 27.99" (711 mm)	Part Number: P787439 Description: AIR PANEL Primary App: EVOBUS 0018355547 Dimensions: Width: 5.75" (146 mm) Length: 19.37" (492 mm) Height: 0.51" (13 mm)
Part Number: P787154 Description: AIR SAFETY Primary App: AM VERSION OF LIEBHERR 10021426 Dimensions: Outer Diameter: 5.35" (136 mm) Inner Diameter: 3.7" (94 mm) Length: 15.748" (400 mm)	Part Number: P787440 Description: AIR PANEL Primary App: MERCEDES-BENZ 0018356147 Dimensions: Width: 4.61" (117 mm) Length: 23.39" (594 mm) Height: 0.51" (13 mm)
Part Number: P787155 Description: AIR PRIMARY Primary App: FLAME RETARDANT VERSION OF P781741 Dimensions: Outer Diameter: 8.19" (208 mm) Inner Diameter: 4.72" (120 mm) Length: 12.64" (321 mm)	Part Number: P787448 Description: AIR PANEL Primary App: EVOBUS 3254621500120 Dimensions: Width: 5.87" (149 mm) Length: 64.53" (1639 mm) Height: 0.12" (3 mm)
Part Number: P787157 Description: AIR PRIMARY Primary App: AM VERSION OF IVECO 2992374 Dimensions: Outer Diameter: 12.87" (327 mm) Inner Diameter: 7.52" (191 mm) Length: 18.39" (467 mm)	Part Number: P787449 Description: AIR PANEL Primary App: EVOBUS 0018357047 Dimensions: Width: 5.79" (147 mm) Length: 17.80" (452 mm) Height: 1.10" (28 mm)
	Part Number: P787450 Description: AIR PANEL Primary App: IVECO 2995964 Dimensions: Width: 8.11" (206 mm) Length: 17.80" (452 mm) Height: 0.98" (25 mm)

<p>Part Number: P787451 Description: AIR PANEL Primary App: EVOBUS 0018355847 Dimensions: Width: 5.43" (138 mm) Length: 12.40" (315 mm) Height: 0.28" (7 mm)</p>	<p>Part Number: P788895 Description: AIR PRIMARY, PowerCore® Primary App: IVECO 42558096 Dimensions: Width: 4.96" (126 mm) Length: 9.96" (253 mm) Height: 9.14" (232 mm)</p>
<p>Part Number: P787452 Description: AIR PANEL Primary App: MERCEDES-BENZ A9068300218 Dimensions: Width: 9.17" (233 mm) Length: 13.94" (354 mm) Height: 1.30" (33 mm)</p>	<p>Part Number: P788896 Description: AIR PRIMARY, PowerCore® Primary App: IVECO 42558097 Dimensions: Width: 10.31" (262 mm) Height: 111.18" (282 mm) Length: 9.96" (253 mm)</p>
<p>Part Number: P787479 Description: AIR PANEL Primary App: EVOBUS 87540008760 Dimensions: Width: 5.87" (149 mm) Length: 58.66" (1490 mm) Height: 0.20" (5 mm)</p>	<p>Part Number: P788897 Description: AIR PANEL Primary App: EVOBUS 0018357147 Dimensions: Width: 5.83" (148 mm) Length: 19.37" (492 mm) Height: 1.18" (30 mm)</p>
<p>Part Number: P787492 Description: AIR PRIMARY Primary App: VOLVO AM OF 1661667 Dimensions: Outer Diameter: 11.02" (280 mm) Inner Diameter: 7.20" (183 mm) Length: 26.10" (663 mm)</p>	 <p>Part Number: P812175 Description: AIR PRIMARY, RADIALSEAL Primary App: NISSAN Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.15" (131 mm) Length: 12.06" (306 mm)</p>
<p>Part Number: P787609 Description: AIR PRIMARY Primary App: SCANIA 1872152 Dimensions: Outer Diameter: 11.97" (304 mm) Inner Diameter: 7.09" (180 mm) Length: 20.98" (533 mm)</p>	 <p>Part Number: P812800 Description: AIR PRIMARY Primary App: KOBELCO 2451U3373 Dimensions: Outer Diameter: 6.12" (156 mm) Inner Diameter: 4.75" (121 mm) Length: 12.00" (305 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 4.72" (120 mm)</p>
<p>Part Number: P787610 Description: AIR SAFETY Primary App: SCANIA 1872151 Dimensions: Outer Diameter: 11.97" (304 mm) Inner Diameter: 7.09" (180 mm) Length: 17.80" (452 mm)</p>	 <p>Part Number: P812901 Description: AIR PRIMARY Primary App: KOMATSU 3EE0221320 Dimensions: Outer Diameter: 7.36" (187 mm) Inner Diameter: 4.78" (121 mm) Length: 10.81" (275 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 6.38" (162 mm)</p>
<p>Part Number: P788716 Description: AIR PRIMARY Primary App: AM VERSION OF MAN 81084050030 Dimensions: Outer Diameter: 11.10" (282 mm) Inner Diameter: 7.87" (200 mm) Length: 21.26" (540 mm)</p>	<p>Part Number: P814456 Description: AIR PRIMARY Primary App: HITACHI Dimensions: Outer Diameter: 7.25" (184 mm) Inner Diameter: 4.22" (107 mm) Length: 5.50" (140 mm)</p>
<p>Part Number: P788729 Description: AIR PANEL Primary App: MERCEDES 0018352747 - CITARO/CITO Dimensions: Width: 5.16" (131 mm) Length: 15.75" (400 mm) Height: 0.70" (18 mm)</p>	 <p>Part Number: P814723 Description: AIR PRIMARY, FINNED Primary App: KOMATSU FORKLIFT 3EA-01-18130 Dimensions: Outer Diameter: 4.09" (104 mm) Inner Diameter: 2.48" (63 mm) Length: 10.00" (254 mm) Gasket ID: 5.91" (150 mm) Minor OD: 0.66" (17 mm)</p>
<p>Part Number: P788751 Description: AIR PRIMARY Primary App: FLAME RETARDANT VERSION OF P772524 Dimensions: Outer Diameter: 10.39" (264 mm) Inner Diameter: 6.02" (153 mm) Length: 15.98" (406 mm)</p>	 <p>Part Number: P814749 Description: AIR PRIMARY, FINNED Primary App: FENDT F278201090020, KOMATSU, Z76-01-11630 Dimensions: Outer Diameter: 5.25" (133 mm) Inner Diameter: 2.62" (67 mm) Length: 11.00" (279 mm) Gasket OD: 0.66" (17 mm) Gasket ID: 4.09" (104 mm) Minor OD: 0.66" (17 mm)</p>
<p>Part Number: P788780 Description: AIR PANEL Primary App: MERCEDES-BENZ 0018354647 Dimensions: Width: 5.91" (150 mm) Length: 61.02" (1550 mm) Height: 0.12" (3 mm)</p>	
<p>Part Number: P788809 Description: AIR PRIMARY, RADIALSEAL Primary App: MAN 81084050018 Dimensions: Length: 17.60" (447 mm) Outer Diameter: 10.00" (254 mm) Inner Diameter: 4.96" (126 mm)</p>	
<p>Part Number: P788881 Description: AIR PANEL Primary App: DAF 1658991 - 95 XF SERIES Dimensions: Height: 1.02" (26 mm) Width: 8.86" (225 mm) Length: 12.04" (306 mm)</p>	

	<p>Part Number: P815034 Description: AIR PRIMARY Primary App: EXMAN 810N Dimensions: Outer Diameter: 6.37" (161 mm) Inner Diameter: 3.54" (90 mm) Length: 9.99" (254 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 6.38" (162 mm)</p>		<p>Part Number: P822768 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON FPG06 A/C Dimensions: Outer Diameter: 5.08" (129 mm) Inner Diameter: 3.20" (81 mm) Length: 11.97" (304 mm)</p>
	<p>Part Number: P815288 Description: AIR PRIMARY, FINNED Primary App: DONALDSON FHG AIR CLEANER G088237 Dimensions: Outer Diameter: 6.09" (155 mm) Inner Diameter: 3.47" (88 mm) Length: 15.00" (381 mm) Gasket ID: 8.66" (220 mm) Minor OD: 0.66" (17 mm)</p>		<p>Part Number: P822769 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSON FPG06 A/C Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 2.55" (65 mm) Length: 11.74" (298 mm)</p>
	<p>Part Number: P820633 Description: AIR SAFETY Primary App: JCB KTH0552 Dimensions: Outer Diameter: 7.28" (185 mm) Inner Diameter: 6.37" (162 mm) Length: 17.99" (457 mm)</p>		<p>Part Number: P822858 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSON FPG05 AIR CLEANERS Dimensions: Outer Diameter: 2.44" (62 mm) Inner Diameter: 1.77" (45 mm) Length: 10.23" (260 mm)</p>
	<p>Part Number: P821575 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON FPG05" AIR CLEANERS Dimensions: Outer Diameter: 4.16" (106 mm) Inner Diameter: 2.36" (60 mm) Length: 10.43" (265 mm)</p>		<p>Part Number: P823295 Description: AIR PRIMARY Primary App: FURUKAWA 8840201020 Dimensions: Outer Diameter: 7.93" (201 mm) Inner Diameter: 3.56" (90 mm) Length: 19.77" (502 mm)</p>
	<p>Part Number: P821883 Description: AIR PRIMARY, RADIALSEAL Primary App: HITACHI 4283861 Dimensions: Outer Diameter: 8.18" (208 mm) Inner Diameter: 4.82" (123 mm) Length: 14.06" (357 mm)</p>		<p>Part Number: P827653 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON FPG07 AIR CLEANERS Dimensions: Outer Diameter: 5.44" (138 mm) Inner Diameter: 3.19" (81 mm) Length: 12.67" (322 mm)</p>
	<p>Part Number: P821908 Description: AIR SAFETY, RADIALSEAL Primary App: HITACHI 4287060 Dimensions: Outer Diameter: 4.95" (126 mm) Inner Diameter: 4.10" (104 mm) Length: 13.78" (350 mm)</p>		<p>Part Number: P827655 Description: AIR PRIMARY, RADIALSEAL Primary App: TOYOTA 177432360071, 177412360071 Dimensions: Outer Diameter: 5.44" (138 mm) Inner Diameter: 3.20" (81 mm) Length: 10.71" (272 mm)</p>
	<p>Part Number: P821938 Description: AIR PRIMARY, RADIALSEAL Primary App: HITACHI 4286128 Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.15" (131 mm) Length: 14.06" (357 mm)</p>		<p>Part Number: P828889 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON FPG08 AIR CLEANERS Dimensions: Outer Diameter: 6.48" (164 mm) Inner Diameter: 3.58" (91 mm) Length: 13.66" (347 mm)</p>
	<p>Part Number: P821963 Description: AIR SAFETY, RADIALSEAL Primary App: HITACHI 4286130 Dimensions: Outer Diameter: 4.77" (121 mm) Inner Diameter: 4.43" (113 mm) Length: 13.65" (347 mm)</p>		<p>Part Number: P829332 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSON FPG07 AIR CLEANERS Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 2.55" (65 mm) Length: 12.38" (314 mm)</p>
	<p>Part Number: P822686 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON FPG04 AIR CLEANERS Dimensions: Outer Diameter: 3.54" (90 mm) Inner Diameter: 1.77" (45 mm) Length: 7.05" (179 mm)</p>		<p>Part Number: P829333 Description: AIR SAFETY, RADIALSEAL Primary App: DONALDSON FPG08 AIR CLEANERS Dimensions: Outer Diameter: 3.72" (95 mm) Inner Diameter: 2.92" (74 mm) Length: 13.37" (340 mm)</p>

<p>Part Number: P829964 Description: AIR PRIMARY, RADIALSEAL Primary App: TOYOTA 17743U110071 Dimensions: Outer Diameter: 5.44" (138 mm) Inner Diameter: 3.20" (81 mm) Length: 10.71" (272 mm)</p>	<p>Part Number: P900247 Description: AIR PRIMARY Primary App: NAVISTAR 808039R1 Dimensions: Inner Diameter: 3.55" (90 mm) Length: 10.88" (276 mm)</p>
<p>Part Number: P830520 Description: AIR PRIMARY Primary App: Hino 17801-2900 Dimensions: Outer Diameter: 6.40" (163 mm) Inner Diameter: 5.39" (137 mm) Length: 12.00" (305 mm)</p>	 <p>Part Number: P900333 Description: AIR PANEL, VENTILATION Primary App: AUSTOFT SUGAR CANE HARVESTORS Dimensions: Width: 6.50" (165 mm) Depth: 2.19" (56 mm) Height: 12.12" (308 mm)</p>
 <p>Part Number: P831079 Description: AIR SAFETY, RADIALSEAL Primary App: TOYOTA, DONALDSON FPG07 A/C Dimensions: Outer Diameter: 3.32" (84 mm) Inner Diameter: 2.55" (65 mm) Length: 10.42" (265 mm)</p>	<p>Part Number: P900763 Description: AIR SAFETY Primary App: FORD D2AF9601AA Dimensions: Inner Diameter: 2.30" (58 mm) Length: 9.50" (241 mm)</p>
 <p>Part Number: P831424 Description: AIR PRIMARY, RADIALSEAL Primary App: DONALDSON FPG05 AIR CLEANER Dimensions: Outer Diameter: 4.16" (106 mm) Inner Diameter: 2.36" (60 mm) Length: 10.43" (265 mm)</p>	<p>Part Number: P901417 Description: AIR PRIMARY Primary App: Daihatsu 17801-87701 Dimensions: Outer Diameter: 9.05" (230 mm) Inner Diameter: 6.85" (174 mm) Length: 1.71" (44 mm) Efficiency @ 99%</p>
 <p>Part Number: P832150 Description: AIR PRIMARY, RADIALSEAL Primary App: HINO 178013000 Dimensions: Outer Diameter: 9.33" (237 mm) Inner Diameter: 5.15" (131 mm) Length: 13.15" (334 mm)</p>	<p>Part Number: P902296 Description: AIR PRIMARY, SPECIAL Primary App: FLAME RETARDANT, UL APPROVED Dimensions: Outer Diameter: 8.62" (219 mm) Inner Diameter: 4.29" (109 mm) Length: 5.67" (144 mm)</p>
<p>Part Number: P832214 Description: AIR SAFETY, RADIALSEAL Primary App: Can Be Used With P536036 & P534434 Dimensions: Outer Diameter: 5.30" (135 mm) Inner Diameter: 4.50" (114 mm) Length: 15.50" (394 mm)</p>	<p>Part Number: P902298 Description: AIR PRIMARY, SPECIAL Primary App: Nissan Patrol 2007 Turbo Diesel 4.2L Dimensions: Outer Diameter: 6.94" (176 mm) Inner Diameter: 3.63" (92 mm) Length: 4.95" (126 mm)</p>
<p>Part Number: P832256 Description: AIR SAFETY, RADIALSEAL Primary App: HINO, DONALDSON FPG11 AIR CLEANERS Dimensions: Outer Diameter: 5.30" (135 mm) Inner Diameter: 4.69" (119 mm) Length: 13.15" (334 mm)</p>	<p>Part Number: P902299 Description: AIR PRIMARY, SPECIAL Primary App: FLAME RETARDANT, UL APPROVED, Mitsubishi ME017242 Dimensions: Outer Diameter: 7.09" (180 mm) Inner Diameter: 3.70" (94 mm) Length: 8.62" (219 mm)</p>
<p>Part Number: P832258 Description: AIR SAFETY, RADIALSEAL Primary App: Hino 17801-3020 Dimensions: Outer Diameter: 4.96" (126 mm) Inner Diameter: 4.10" (104 mm) Length: 12.87" (327 mm)</p>	<p>Part Number: P902309 Description: AIR PRIMARY, FINNED Primary App: HYUNDAI 11EM-21041 Dimensions: Outer Diameter: 7.93" (202 mm) Inner Diameter: 5.27" (134 mm) Length: 19.29" (490 mm) Efficiency @ 99% Percent</p>
 <p>Part Number: P841639 Description: AIR SAFETY, RADIALSEAL Primary App: FPG05 UL Dimensions: Outer Diameter: 2.44" (62 mm) Inner Diameter: 1.77" (45 mm) Length: 10.23" (260 mm)</p>	<p>Part Number: P902310 Description: AIR SAFETY Primary App: Hyundai 11EM-21051 Dimensions: Outer Diameter: 5.23" (133 mm) Inner Diameter: 4.13" (105 mm) Length: 18.70" (475 mm) Efficiency @ 99% Percent</p>
<p>Part Number: P849069 Description: AIR PRIMARY, RADIALSEAL Primary App: Hino 1780178020 Dimensions: Outer Diameter: 9.30" (237 mm) Inner Diameter: 5.15" (131 mm) Length: 9.75" (248 mm)</p>	<p>Part Number: P902311 Description: AIR PRIMARY Primary App: Daewoo 24749051 Dimensions: Outer Diameter: 10.9" (277 mm) Inner Diameter: 6.50" (165 mm) Length: 19.0" (483 mm)</p>
<p>Part Number: P902312 Description: AIR SAFETY Primary App: Daewoo 2474-9057 Dimensions: Outer Diameter: 5.27" (134 mm) Inner Diameter: 2.07" (53 mm) Length: 17.20" (437 mm)</p>	<p>Part Number: P902312 Description: AIR SAFETY Primary App: Daewoo 2474-9057 Dimensions: Outer Diameter: 5.27" (134 mm) Inner Diameter: 2.07" (53 mm) Length: 17.20" (437 mm)</p>

	<p>Part Number: P902384 Description: AIR PRIMARY Primary App: Hino 17801-3380 Dimensions: Outer Diameter: 9.13" (232 mm) Inner Diameter: 5.90" (150 mm) Length: 16.30" (414 mm)</p>
	<p>Part Number: P902385 Description: AIR SAFETY Primary App: Hino 17801-3390 Dimensions: Outer Diameter: 4.33" (110 mm) Inner Diameter: 3.89" (99 mm) Length: 16.50" (419 mm)</p>
	<p>Part Number: P902736 Description: AIR PRIMARY, SPECIAL Primary App: AIR PRIMARY RS F/R M/BISHI ME017246 Dimensions: Outer Diameter: 9.09" (231 mm) Inner Diameter: 4.60" (117 mm) Length: 10.70" (272 mm)</p>
	<p>Part Number: P920683 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: 3 GPM HIGH PERF FF/WS Dimensions: Outer Diameter: 4.38" (111 mm) Thread Size: 1 1/4-12 Length: 11.75" (298 mm) Efficiency 99% @ 15 Micron</p>
	<p>Part Number: P920711 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: 1 GPM HIGH PERF FF/WS Dimensions: Outer Diameter: 4.38" (111 mm) Thread Size: 1 1/4-12 Length: 7.44" (189 mm) Efficiency 99% @ 15 Micron</p>
	<p>Part Number: P925683 Description: FUEL/WATER SEPARATOR SPIN-ON Primary App: CANISTER ASSEMBLY (FF/WS) Dimensions: Outer Diameter: 4.25" (108 mm) Length: 11.34" (288 mm)</p>
	<p>Part Number: R000133 Description: AIR PRIMARY Primary App: New Holland M160 82001819 Dimensions: Outer Diameter: 8.26" (210 mm) Length: 15.15" (385 mm)</p>
	<p>Part Number: R800103 Description: AIR PRIMARY Primary App: HITACHI EXCAVATOR Dimensions: Outer Diameter: 7.36" (187 mm) Inner Diameter: 4.78" (121 mm) Length: 15.00" (381 mm) Bolt Hole Diameter: 0.66" (17 mm) Gasket ID: 6.38" (162 mm)</p>
	<p>Part Number: R804523 Description: AIR SAFETY Primary App: KOMATSU 3EB-02-25550 Dimensions: Outer Diameter: 3.13" (80 mm) Inner Diameter: 2.15" (55 mm) Length: 10.00" (254 mm)</p>
	<p>Part Number: R804759 Description: AIR PRIMARY Primary App: ISUZU 2-90646-910-0 Dimensions: Outer Diameter: 8.71" (221 mm) Inner Diameter: 5.35" (136 mm) Length: 13.02" (331 mm)</p>



Part Number: **S028218**
Description: **BREATHER, SPECIAL**
Primary App: KOMATSU 6150216750
Dimensions: Outer Diameter: 3.18" (81 mm)
Inner Diameter: 1.42" (36 mm)
Length: 1.85" (47 mm)

Products by Filter Type (shape) and Dimension

When the filter in front of you is void of any part numbers or markings, this section of the catalog will help. Find the closed product type from the list on the right.

Each product group is sorted by three key dimensional attributes. When you find the one that best matches what's in front of you, go to the part number section to confirm the filter with additional attributes, primary application or by the picture.

On-line Attribute Search








The "attribute search" on our public web site gives you the ability to search for up to four attributes for more flexible and customized search.



On-line Product Details /Specifications

Type in a Donaldson part number in the search window on our public web site. Your results screen will return choices from various countries and results from *ecatalogs* or literature. The image on the left is an example of details available on *ecatalogs* for a Donaldson Duramax spin-on filter.



	Air Breathers 292
	Air Cone-shaped 292
	Air Disposable 292
	Air DuraLite™ 293
	Air Ovals 293
	Air PowerCore® Filters 297
	Air Rounds..... 298
	Air Dryers 293
	Air Specials..... 310
	Air Vee-Pac™ 311
	Air Panels 293
	Coolant Filters..... 311
	Fuel Box..... 311
	Fuel Cartridge 311
	Fuel In-line..... 313
	Fuel Spin-on 315
	Hydraulic Cartridge..... 316
	Hydraulic In-line 326
	Hydraulic Spin-on 326
	Hydraulic Strainers..... 329
	Lube Cartridge 330
	Lube Spin-on..... 332
	Seals, Gaskets, Washers 335
	Transmission..... 335

Product Guide by Part Number

Air Breathers

Height IN MM	Length IN MM	Depth IN MM	PART NUMBER	PART DESCRIPTION
1.30 33	2.40 61	4.40 112	P537369	Breather, Special
Outer Diameter IN MM	Depth IN MM	Overall Length IN MM	PART NUMBER	PART DESCRIPTION
2.50 64	1.32 34	1.75 45	P606761	Breather, Special
Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
2.76 70	2.50 64	7.09 180	P764724	Breather
Height IN MM	Length IN MM	Depth IN MM	PART NUMBER	PART DESCRIPTION
2.78 71	1.28 33	4.42 112	P536431	Breather, Special
Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
2.80 71	1.30 33	1.01 26	P524388	Breather, Cylindrical
Outer Diameter IN MM	Thread Size	Inner Diameter IN MM	PART NUMBER	PART DESCRIPTION
2.83 72	G 1/2	2.52 64	P172386	Breather
2.83 72	G 1/2	2.52 64	P761051	Breather
Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
2.88 73	1.41 36	2.72 69	P526413	Breather, Cylindrical
3.00 76	1.62 41	1.37 35	P524392	Breather, Cylindrical
3.03 77	1.47 37	2.28 58	P606944	Breather, Cylindrical
3.18 81	1.42 36	1.85 47	S028218	Breather, Special
3.30 84	1.97 50	3.25 83	P528234	Breather, Cylindrical
3.31 84	1.02 26	2.66 68	P528708	Breather
Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
3.66 93	1 1/8-16	3.66 93	P564424	Breather, Spin-on
3.66 93	3/4 NPT	3.65 93	P564425	Breather, Spin-on
3.69 94	3/4-20	4.34 110	P606277	Breather, Spin-on
3.73 95	3/4-14	3.75 95	P539468	Breather, Spin-on
Width IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION	
3.95 100	1.88 48	P607298	Breather, Special	
Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
4.00 102	1.33 34	1.39 35	P606059	Breather, Cylindrical
4.17 106	2.48 63	2.88 73	P500196	Breather
Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
4.52 115	1 NPT	4.50 114	P564669	Breather
Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
5.00 127	2.62 67	1.25 32	P607276	Breather, Cylindrical
5.09 129	2.13 54	7.59 193	P607673	Breather, Cylindrical
5.09 129	2.13 54	8.08 205	P603746	Breather, Cylindrical
6.24 158	3.27 83	12.30 312	P603568	Breather, Cylindrical

Air Cone-shaped

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
3.56 90	2.44 62	12.80 325	P608599	Air Safety, Konepac™
3.69 94	2.52 64	13.07 332	P137285	Air Primary, Konepac™
4.09 104		10.52 267	P611858	Air Primary, Konepac™
4.09 104	3.41 87	10.48 266	P604457	Air Primary, Konepac™
4.79 122	4.03 102	12.92 328	P609218	Air Primary, Konepac™
4.81 122		12.86 327	P611859	Air Primary, Konepac™
5.30 135	3.70 94	17.44 443	P611540	Air Safety, Konepac™
5.83 148	3.21 82	12.42 315	P770397	Air Primary, Konepac™
5.87 149	3.14 80	13.03 331	P137293	Air Primary, Konepac™
5.94 151		13.03 331	P616742	Air Primary, Konepac™
5.94 151	4.31 110	19.65 499	P608391	Air Safety, Konepac™
5.94 151	5.12 130	13.03 331	P609221	Air Primary, Konepac™
7.01 178	3.62 92	15.63 397	P776158	Air Primary, Konepac™
7.36 187	4.68 119	23.31 592	P775945	Air Primary, Konepac™
8.27 210	4.74 120	18.58 472	P776159	Air Primary, Konepac™
8.66 220	5.20 132	15.00 381	P771003	Air Primary, Konepac™
8.66 220	5.20 132	27.99 711	P787036	Air Primary, Konepac™
8.66 220	5.20 132	28.02 712	P150693	Air Primary, Konepac™
8.66 220	5.21 132	15.00 381	P130959	Air Primary, Konepac™
8.66 220	5.21 132	15.00 381	P136646	Air Primary, Konepac™
8.66 220	5.21 132	19.29 490	P138428	Air Primary, Konepac™
8.66 220	5.21 132	22.00 559	P141339	Air Primary, Konepac™
8.66 220	5.21 132	28.00 711	P129472	Air Primary, Konepac™
8.66 220	5.21 132	28.00 711	P140822	Air Primary, Konepac™
8.66 220	5.21 132	28.00 711	P148044	Air Primary, Konepac™
8.66 220	5.21 132	28.00 711	P150692	Air Primary, Konepac™
9.88 251	6.22 158	19.53 496	P776765	Air Primary, Konepac™
9.96 253	5.69 145	18.85 479	P611539	Air Primary, Konepac™
10.40 264	6.95 177	22.00 559	P141317	Air Primary, Konepac™
10.40 264	6.95 177	22.00 559	P154575	Air Primary, Konepac™
10.40 264	6.95 177	28.00 711	P129396	Air Primary, Konepac™
10.40 264	6.95 177	28.00 711	P148043	Air Primary, Konepac™
10.40 264	6.95 177	28.00 711	P150694	Air Primary, Konepac™
10.40 264	6.95 177	28.00 711	P151097	Air Primary, Konepac™
10.40 264	6.95 177	28.00 711	P522293	Air Primary, Konepac™
10.62 270	6.69 170	20.02 509	P155842	Air Primary, Konepac™
10.62 270	6.69 170	22.02 559	P153551	Air Primary, Konepac™
10.62 270	6.69 170	22.02 559	P537791	Air Primary, Konepac™
10.62 270	6.69 170	28.02 712	P150695	Air Primary, Konepac™
11.50 292	6.57 167	19.72 501	P776157	Air Primary, Konepac™
11.83 300	7.37 187	24.00 610	P521598	Air Primary, Konepac™
12.20 310	4.45 113	20.41 519	P608116	Air Primary, Konepac™
12.74 324	8.32 211	23.99 609	P602344	Air Primary, Konepac™
12.74 324	8.32 211	24.00 610	P142100	Air Primary, Konepac™
12.75 324	8.32 211	23.99 609	P530866	Air Primary, Konepac™
12.75 324	8.32 211	28.00 711	P141228	Air Primary, Konepac™

Air Disposable

Body Diameter IN MM	Outlet ID IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
6.75 171	2.88 73	14.20 361	P537451	Air Cleaner, Disposable

Air Disposable - continued

Body Diameter IN MM	Outlet Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
7.75 197	3.88 99	17.20 437	P537452	Air Cleaner, Disposable
Body Diameter IN MM	Outlet ID IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
7.75 197	4.00 102	17.20 437	P613679	Air Cleaner, Disposable
9.67 246	5.00 127	20.20 513	P537453	Air Cleaner, Disposable
9.70 246	5.00 127	19.40 493	P537454	Air Cleaner, Disposable
9.75 248	6.00 152	24.00 610	P537447	Air Cleaner, Disposable
Body Diameter IN MM	Outlet Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
11.00 279	6.00 152	24.00 610	P527586	Air Cleaner, Disposable
Body Diameter IN MM	Outlet ID IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
11.00 279	7.00 178	24.00 610	P537448	Air Cleaner, Disposable
11.50 292	7.00 178	16.88 429	P607373	Air Cleaner, Disposable
13.50 343	7.00 178	16.80 427	P537455	Air Cleaner, Disposable
13.50 343	7.00 178	16.80 427	P537456	Air Cleaner, Disposable
13.50 343	7.00 178	24.00 610	P537449	Air Cleaner, Disposable
13.50 343	8.00 203	24.00 610	P537450	Air Cleaner, Disposable

Air Dryers

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
5.51 140	G 1 1/4	6.93 176	P783753	Air Dryer Spin-on
5.51 140	M39 x 1.5	6.50 165	P781466	Air Dryer Spin-on

Air DuraLites

Outer Diameter IN MM	Outlet Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
1.50 38	1.50 38	4.50 114	C045001	Air Primary, DuraLite™
4.50 114	1.50 38	4.50 114	D045003	Air Primary, DuraLite™
4.50 114	1.50 38	6.00 152	D045004	Air Primary, DuraLite™
4.50 114	1.50 38	8.00 203	C045002	Air Primary, DuraLite™
5.50 140	1.75 44	4.00 102	C055003	Air Primary, DuraLite™
5.50 140	1.75 44	7.00 178	C055002	Air Primary, DuraLite™
5.50 140	1.75 44	7.00 178	D055004	Air Primary, DuraLite™
6.50 165	1.93 49	7.50 190	C065002	Air Primary, DuraLite™
6.50 165	2.00 51	4.00 102	C065001	Air Primary, DuraLite™
6.50 165	2.00 51	4.00 102	D065003	Air Primary, DuraLite™
6.50 165	2.00 51	9.00 229	C065015	Air Primary, DuraLite™
6.50 165	2.00 51	9.00 229	D065008	Air Primary, DuraLite™
6.50 165	2.25 57	5.00 127	C065003	Air Primary, DuraLite™
6.58 167	1.30 33	10.00 254	C065051	Air Primary, DuraLite™
7.72 196	5.98 152	10.23 260	B085056	Air Primary, DuraLite™
8.50 216	2.43 62	5.00 127	C085005	Air Primary, DuraLite™
8.50 216	2.43 62	6.50 165	C085002	Air Primary, DuraLite™
8.50 216	2.43 62	9.50 241	C085006	Air Primary, DuraLite™
8.50 216	2.50 64	4.00 102	C085001	Air Primary, DuraLite™
8.50 216	2.50 64	9.50 241	C085043	Air Primary, DuraLite™
8.50 216	3.00 76	5.00 127	C085003	Air Primary, DuraLite™
8.50 216	3.00 76	9.50 241	C085004	Air Primary, DuraLite™

Air DuraLites - continued

Outer Diameter IN MM	Outlet Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
8.50 216	3.00 76	9.50 241	C085041	Air Primary, DuraLite™
8.50 216	3.00 76	11.00 279	B085001	Air Primary, DuraLite™
8.50 216	3.00 76	11.00 279	B085048	Air Primary, DuraLite™
8.50 216	3.00 76	11.51 292	C085061	Air Primary, DuraLite™
8.50 216	4.00 102	11.00 279	B085011	Air Primary, DuraLite™
8.50 216	4.00 102	11.00 279	B085046	Air Primary, DuraLite™
8.75 222	3.00 76	8.50 216	B085008	Air Primary, DuraLite™
10.50 267	3.93 100	6.00 152	C105003	Air Primary, DuraLite™
10.50 267	4.00 102	6.00 152	C105028	Air Primary, DuraLite™
10.50 267	4.00 102	10.50 267	B105006	Air Primary, DuraLite™
10.50 267	4.00 102	10.50 267	B105020	Air Primary, DuraLite™
10.50 267	4.00 102	10.50 267	C105004	Air Primary, DuraLite™
10.50 267	4.00 102	10.50 267	C105017	Air Primary, DuraLite™
10.50 267	5.00 127	15.00 381	B105002	Air Primary, DuraLite™
12.48 317		15.75 400	B120439	Air Primary, DuraLite™
12.50 318	5.00 127	8.01 204	C125020	Air Primary, DuraLite™
12.50 318	5.00 127	8.97 228	B125011	Air Primary, DuraLite™
12.50 318	5.00 127	11.00 279	C125004	Air Primary, DuraLite™
12.50 318	5.00 127	11.00 279	C125017	Air Primary, DuraLite™
12.50 318	5.00 127	15.00 381	B125003	Air Primary, DuraLite™
12.50 318	5.50 140	9.00 229	B125005	Air Primary, DuraLite™
12.50 318	8.00 203	15.75 400	B120376	Air Primary, DuraLite™

Air Ovals

Width IN MM	Height IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
3.50 89	3.07 78	4.01 102	P607273	Air Primary, Oval
4.24 108	0.74 19	11.73 298	P606121	Air Safety, Oval
4.24 108	1.86 47	8.24 209	P600975	Air Safety, Oval
4.35 110	3.00 76	4.71 120	P606079	Air Primary, Oval
5.75 146	3.98 101	5.75 146	P606075	Air Primary, Oval
6.04 153	2.82 72	7.15 182	P536434	Air Primary, Oval
6.41 163	3.66 93	9.56 243	P781746	Air Primary, Oval
6.64 169	3.05 77	6.64 169	P606071	Air Primary, Oval
7.46 189	1.57 40	12.46 316	P601560	Air Safety, Oval
8.00 203	3.54 90	5.75 146	P606502	Air Primary, Oval
9.47 241	1.57 40	14.47 368	P607557	Air Safety, Oval
9.72 247	2.83 72	9.72 247	P606073	Air Primary, Oval
10.75 273	8.61 219	2.55 65	P606295	Air Primary, Oval
11.25 285	2.62 66	11.25 285	P606070	Air Primary, Oval
13.54 344	8.50 216	1.67 42	P500070	Air Primary, Oval

Air Panels

Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
3.94 100	19.69 500	3.95 100	P606083	Air Panel, Ventilation
4.06 103	14.90 378	2.88 73	P606090	Air Panel, Ventilation
4.09 104	1.93 49	20.45 520	P784574	Air Panel, Ventilation
4.22 107	1.58 40	9.44 240	P528224	Air Panel, Engine
4.29 109	2.16 55	23.74 603	P783687	Air Panel, Ventilation

Width IN MM	Depth IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
4.45 113	5.20 132	.86 22	P606276	Air Panel, Engine

Air Panels - continued

Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
4.61 117	10.91 277	0.51 13	P783642	Air Panel
4.61 117	23.39 594	0.51 13	P787440	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
4.70 119	10.70 272	4.20 107	P606082	Air Panel, Ventilation
4.70 119	11.50 292	1.74 44	P606960	Air Panel, Ventilation
Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
4.72 120	15.98 406	2.20 56	P784906	Air Panel
4.80 122	19.61 498	0.98 25	P787392	Air Panel
Width IN MM	Depth IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
4.84 123	1.73 44	17.13 435	P500194	Air Panel, Ventilation
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
4.84 123	23.62 600	0.95 24	P781176	Air Panel, Ventilation
5.00 127	2.19 56	24.00 610	P113330	Air Panel, Ventilation
5.00 127	2.19 56	26.00 660	P128810	Air Panel, Ventilation
5.00 127	2.19 56	29.50 749	P141320	Air Panel, Ventilation
5.00 127	2.19 56	38.00 965	P112775	Air Panel, Ventilation
5.00 127	16.50 419	1.19 30	P606085	Air Panel, Ventilation
Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
5.16 131	15.75 400	0.70 18	P788729	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
5.25 133	2.19 56	18.50 470	P115051	Air Panel, Ventilation
5.26 134	10.68 271	1.65 42	P528225	Air Panel, Engine
5.28 134	1.46 37	14.96 380	P784473	Air Panel, Engine
Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
5.28 134	13.15 334	1.61 41	P786114	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
5.30 135	1.62 41	8.07 205	P524382	Air Panel, Engine
5.30 135	9.65 245	0.77 20	P616850	Air Panel
5.35 136	2.83 72	26.18 665	P525026	Air Panel, Ventilation
Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
5.43 138	12.40 315	0.28 7	P787451	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
5.56 141	16.41 417	2.59 66	P606086	Air Panel, Ventilation
Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
5.75 146	19.37 492	0.51 13	P787439	Air Panel
5.79 147	16.46 418	1.46 37	P787391	Air Panel
5.79 147	17.80 452	1.10 28	P787449	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
5.83 148	15.53 395	1.62 41	P606275	Air Panel

Air Panels - continued

Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
5.83 148	19.37 492	1.18 30	P788897	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
5.86 149	1.65 42	12.87 327	P525130	Air Panel, Engine
Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
5.87 149	8.66 220	0.79 20	P787437	Air Panel
5.87 149	58.66 1490	0.20 5	P787479	Air Panel
5.87 149	64.53 1639	0.12 3	P787448	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
5.91 150	2.19 56	21.26 540	P527595	Air Panel, Ventilation
Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
5.91 150	61.02 1550	0.12 3	P788780	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
5.94 151	2.75 70	23.85 606	P781349	Air Panel, Ventilation
5.95 151	7.79 198	5.95 151	P142792	Air Panel, Engine
5.95 151	7.79 198	8.25 210	P142793	Air Panel, Engine
5.95 151	7.79 198	15.09 383	P142796	Air Panel, Engine
5.95 151	7.79 198	19.75 502	P142798	Air Panel, Engine
5.98 152	2.19 56	26.96 685	P609446	Air Panel, Ventilation
6.00 152	2.19 56	10.00 254	P533559	Air Panel, Ventilation
6.00 152	2.19 56	23.50 597	P120320	Air Panel, Ventilation
6.00 152	2.19 56	25.50 648	P126227	Air Panel, Ventilation
6.00 152	2.19 56	30.00 762	P158893	Air Panel, Ventilation
6.00 152	2.19 56	38.00 965	P121036	Air Panel, Ventilation
6.00 152	2.19 56	38.00 965	P158333	Air Panel, Ventilation
6.00 152	2.19 56	47.00 1194	P121378	Air Panel, Ventilation
6.00 152	2.20 56	17.17 436	P776490	Air Panel, Ventilation
6.00 152	2.31 59	17.53 445	P543107	Air Panel, Ventilation
6.00 152	23.50 597	2.50 64	P606084	Air Panel, Ventilation
6.05 154	11.56 294	1.66 42	P536425	Air Panel, Engine
6.06 154	7.63 194	1.62 41	P606219	Air Panel
6.12 155	2.19 56	37.00 940	P115690	Air Panel, Ventilation
6.18 157	11.24 285	1.15 29	P534104	Air Panel, Engine
6.34 162	14.41 366	1.12 28	P612827	Air Panel, Ventilation
6.46 164	6.46 164	0.32 8	P614228	Air Panel, Ventilation
6.50 165	2.19 56	12.12 308	P900333	Air Panel, Ventilation
6.50 165	2.19 56	23.50 597	P122115	Air Panel, Ventilation
6.50 165	2.19 56	33.00 838	P117109	Air Panel, Ventilation
6.52 166	1.54 39	11.25 286	P536433	Air Panel, Engine
6.58 167	8.99 228	2.17 55	P606272	Air Panel
6.60 168	12.60 320	1.88 48	P618644	Air Panel, Ventilation
6.63 169	11.10 282	1.34 34	P500063	Air Panel, Engine
6.65 169	1.18 30	22.99 584	P784971	Air Panel
6.68 170	13.48 342	1.59 40	P534105	Air Panel, Engine
Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
6.73 171	23.54 598	1.97 50	P783024	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
6.77 172	1.18 30	8.74 222	P786611	Air Panel

Air Panels - continued

Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
6.77 172	1.98 50	23.50 597	P783197	Air Panel, Engine
6.77 172	2.76 70	23.50 597	P783198	Air Panel, Engine
6.79 172	12.29 312	3.30 84	P614542	Air Panel
Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
6.81 173	9.61 244	1.97 50	P783462	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
6.81 173	10.94 278	0.68 17	P614224	Air Panel, Ventilation
Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
6.97 177	13.54 344	1.10 28	P787408	Air Panel
6.97 177	18.39 467	2.76 70	P786092	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
7.00 178	1.02 26	9.00 229	P780135	Air Panel, Ventilation
7.00 178	2.19 56	15.00 381	P137523	Air Panel, Ventilation
7.00 178	2.19 56	23.50 597	P113247	Air Panel, Ventilation
7.00 178	2.19 56	26.00 660	P129862	Air Panel, Ventilation
7.00 178	2.19 56	38.00 965	P132448	Air Panel, Ventilation
7.00 178	2.19 56	47.00 1194	P117049	Air Panel, Ventilation
7.00 178	3.50 89	1.50 38	P606956	Air Panel, Engine
7.03 179	13.88 353	2.38 60	P607097	Air Panel, Engine
7.07 180	1.44 37	12.50 318	P609445	Air Panel, Ventilation
7.09 180	1.57 40	15.74 400	P781682	Air Panel, Ventilation
Outer Diameter IN MM	Inner Diameter IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
7.09 180	4.72 120	3.39 86	P783386	Air Primary
Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
7.09 180	16.06 408	1.18 30	P787438	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
7.10 180	10.02 255	2.33 59	P606284	Air Panel
7.11 181	10.02 255	1.58 40	P606282	Air Panel
7.13 181	9.37 238	1.70 43	P606281	Air Panel
7.18 182	9.03 229	1.63 41	P614544	Air Panel, Ventilation
7.21 183	12.49 317	0.99 25	P614221	Air Panel, Ventilation
7.22 183	13.35 339	2.30 58	P546596	Air Panel, Engine
Width IN MM	Depth IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
7.23 184	3.30 84	13.35 339	P602658	Air Panel, Engine
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
7.24 184	11.91 303	2.01 51	P607338	Air Panel, Ventilation
7.40 188	10.51 267	1.61 41	P535089	Air Panel, Ventilation
Width IN MM	Height IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
7.48 190	2.28 58	12.28 312	P615748	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
7.50 190	2.19 56	20.00 508	P113407	Air Panel, Ventilation
7.50 190	2.19 56	28.00 711	P106680	Air Panel, Ventilation

Air Panels - continued

Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
7.50 190	2.83 72	28.00 711	P158854	Air Panel, Ventilation
7.52 191	8.75 222	2.26 57	P548964	Air Panel, Engine
7.59 193	1.51 38	11.28 287	P528228	Air Panel, Engine
Height IN MM	Width IN MM	Depth IN MM	PART NUMBER	PART DESCRIPTION
7.62 194	8.66 220	0.98 25	P614546	Air Panel, Ventilation
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
7.63 194	8.50 216	1.65 42	P607253	Air Panel, Ventilation
7.68 195	8.59 218	0.71 18	P614225	Air Panel, Ventilation
Width IN MM	Depth IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
7.83 199	0.76 20	7.97 203	P500204	Air Panel, Ventilation
7.83 199	0.76 20	11.94 304	P500203	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
7.87 200	15.95 405	2.57 65	P618642	Air Panel
7.88 200	1.54 39	7.03 179	P528226	Air Panel, Engine
7.91 201	1.67 42	16.00 406	P536427	Air Panel, Engine
Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
7.91 201	21.38 543	0.79 20	P787436	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
7.95 202	2.18 55	31.41 798	P782138	Air Panel
8.00 203	2.19 56	16.00 406	P520450	Air Panel, Ventilation
8.00 203	2.19 56	17.00 432	P123440	Air Panel, Ventilation
Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
8.11 206	17.80 452	0.98 25	P787450	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
8.12 206	11.94 303	0.79 20	P614223	Air Panel, Ventilation
8.15 207	7.79 198	10.48 266	P142795	Air Panel, Engine
8.16 207	9.65 245	2.03 52	P606061	Air Panel
8.25 210	7.79 198	8.25 210	P142794	Air Panel, Engine
8.25 210	7.79 198	19.78 502	P142802	Air Panel, Engine
8.26 210	1.57 40	8.26 210	P782811	Air Panel, Ventilation
Height IN MM	Depth IN MM	Width IN MM	PART NUMBER	PART DESCRIPTION
8.28 210	1.51 38	11.50 292	P614545	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
8.28 210	7.79 198	15.15 385	P142799	Air Panel, Engine
8.35 212	10.55 268	1.65 42	P606077	Air Panel, Ventilation
8.38 213	1.63 41	8.38 213	P537377	Air Panel, Engine
Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
8.43 214	12.36 314	0.80 20	P612815	Air Panel, Ventilation
Height IN MM	Width IN MM	Depth IN MM	PART NUMBER	PART DESCRIPTION
8.50 216	11.30 287	1.41 36	P614543	Air Panel

Air Panels - continued

Width IN MM	Length IN MM	Depth IN MM	PART NUMBER	PART DESCRIPTION
8.58 218	16.36 416	1.05 27	P618643	Air Panel, Ventilation
Height MM	Width MM	Depth MM	PART NUMBER	PART DESCRIPTION
8.62 219	8.39 213	0.98 25	P614547	Air Panel, Ventilation
Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
8.86 225	12.04 306	1.02 26	P788881	Air Panel
8.86 225	19.57 497	1.50 38	P786385	Air Panel
8.86 225	20.71 526	1.89 48	P786386	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
8.88 226	8.88 226	1.54 39	P607306	Air Panel, Ventilation
8.91 227	1.82 46	11.27 287	P228498	Air Panel
8.91 227	1.82 46	11.27 287	P614476	Air Panel, Ventilation
9.00 229	2.19 56	32.00 813	P131231	Air Panel, Ventilation
Width IN MM	Depth IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
9.02 229	2.05 52	12.17 309	P505979	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
9.04 230	12.21 310	2.05 52	P607256	Air Panel, Ventilation
9.06 230	2.19 56	9.06 230	P780163	Air Panel, Ventilation
Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
9.06 230	19.68 500	1.97 50	P784907	Air Panel
9.17 233	13.94 354	1.30 33	P787452	Air Panel
Width IN MM	Depth IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
9.29 236	2.05 52	14.25 362	P505999	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
9.31 236	12.24 311	2.05 52	P607257	Air Panel, Ventilation
9.40 239	13.78 350	2.05 52	P607277	Air Panel, Ventilation
9.50 241	2.19 56	12.25 311	P780298	Air Panel, Ventilation
Width IN MM	Depth IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
9.52 242	7.03 179	1.44 37	P607348	Air Panel, Ventilation
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
9.61 244	11.36 288	1.46 37	P606062	Air Panel
Width IN MM	Depth IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
9.73 247	2.39 61	12.29 312	P602657	Air Panel, Engine
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
9.75 248	1.03 26	15.30 389	P609444	Air Panel, Ventilation
9.75 248	12.21 310	2.31 59	P548963	Air Panel, Engine
9.81 249	6.66 169	1.99 51	P606060	Air Panel
9.84 250	0.95 24	11.81 300	P777576	Air Panel, Ventilation
9.84 250	6.14 156	1.61 41	P500026	Air Panel, Engine
9.97 253	13.61 346	0.60 15	P617005	Air Panel, Ventilation
10.00 254	2.19 56	10.00 254	P105958	Air Panel, Ventilation
10.00 254	2.19 56	17.00 432	P112671	Air Panel, Ventilation

Air Panels - continued

Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
10.00 254	10.75 273	1.99 51	P610561	Air Panel
10.03 255	12.32 313	1.84 47	P606063	Air Panel, Ventilation
Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
10.04 255	15.53 395	1.18 30	P786405	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
10.07 256	10.67 271	0.68 17	P614220	Air Panel, Ventilation
10.07 256	13.97 355	0.68 17	P614222	Air Panel, Ventilation
Length IN MM	Height IN MM	Width IN MM	PART NUMBER	PART DESCRIPTION
10.24 260	1.50 38	6.46 164	P785365	Air Panel
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
10.35 263	3.15 80	11.93 303	P784015	Air Panel
10.39 264	1.14 29	6.69 170	P607221	Air Panel, Ventilation
10.40 265	14.00 355	2.29 58	P614541	Air Panel, Engine
10.50 267	7.79 198	10.50 267	P142797	Air Panel, Engine
10.50 267	7.79 198	15.09 383	P142801	Air Panel, Engine
10.50 267	7.79 198	19.75 502	P142803	Air Panel, Engine
10.53 267	7.79 198	12.78 325	P142800	Air Panel, Engine
10.63 270	10.63 270	0.98 25	P609422	Air Panel, Ventilation
10.68 271	7.95 202	1.62 41	P607322	Air Panel
10.75 273	2.25 57	11.82 300	P536429	Air Panel, Engine
10.77 274	6.61 168	1.74 44	P607346	Air Panel, Ventilation
10.82 275	2.19 56	10.82 275	P540845	Air Panel, Ventilation
10.87 276	2.36 60	12.40 315	P612826	Air Panel, Engine
10.93 278	9.91 252		P616743	Air Panel, Engine
11.00 279	2.19 56	11.00 279	P106965	Air Panel, Ventilation
11.00 279	2.19 56	23.50 597	P114326	Air Panel, Ventilation
11.00 279	2.19 56	26.00 660	P145709	Air Panel, Ventilation
Width IN MM	Height IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
11.26 286	2.44 62	19.13 486	P500195	Air Panel, Ventilation
Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
11.34 288	1.18 30	6.30 160	P784479	Air Panel, Engine
11.50 292	5.00 127	15.00 381	P524835	Air Panel, Engine
11.50 292	7.03 179	1.66 42	P606957	Air Panel
11.50 292	7.13 181	2.33 59	P607258	Air Panel, Ventilation
11.73 298	2.19 56	16.84 428	P606762	Air Panel, Ventilation
11.94 303	13.25 337	0.81 21	P606089	Air Panel, Ventilation
12.00 305	2.19 56	6.00 152	P041028	Air Panel
12.00 305	2.19 56	16.00 406	P123229	Air Panel, Ventilation
12.00 305	12.88 327	2.19 56	P606087	Air Panel, Ventilation
12.08 307	2.04 52	8.97 228	P505983	Air Panel
12.20 310	6.10 155	1.55 39	P607332	Air Panel, Ventilation
12.22 310	7.88 200	2.05 52	P607299	Air Panel, Ventilation
12.25 311	1.13 29	9.18 233	P606555	Air Panel, Ventilation
12.30 312	7.35 187	1.64 42	P607300	Air Panel, Ventilation
12.61 320	13.40 340	0.32 8	P614226	Air Panel, Ventilation
12.61 320	13.40 340	0.79 20	P614227	Air Panel, Ventilation
12.84 326	7.79 198	19.74 501	P142805	Air Panel, Engine
13.18 335	5.25 133	1.65 42	P607243	Air Panel, Ventilation

Specs By Part Type

Air Panels - continued

Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
13.18 335	5.25 133	1.65 42	P607317	Air Panel, Ventilation
13.77 350	4.16 106	1.65 42	P607333	Air Panel, Ventilation
13.84 352	1.38 35	9.21 234	P616898	Air Panel, Ventilation
14.00 356	5.31 135	36.44 926	P609421	Air Panel
14.00 356	22.50 572	6.19 157	P607281	Air Panel, Ventilation
14.31 363	8.00 203	23.25 591	P142813	Air Panel, Engine
15.00 381	2.19 56	15.00 381	P105919	Air Panel, Ventilation
15.00 381	2.19 56	15.00 381	P113946	Air Panel, Ventilation
15.00 381	2.19 56	20.00 508	P121351	Air Panel, Ventilation
15.00 381	2.19 56	20.00 508	P528464	Air Panel, Engine
15.00 381	5.19 132	15.62 397	P150135	Air Panel, Ventilation
15.14 385	7.79 198	19.74 501	P142806	Air Panel, Engine
15.19 386	7.79 198	15.19 386	P142804	Air Panel, Engine

Length IN MM	Height IN MM	Width IN MM	PART NUMBER	PART DESCRIPTION
15.37 391	1.53 39	5.65 144	P785366	Air Panel

Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
16.00 406	2.19 56	24.00 610	P118951	Air Panel, Ventilation
16.00 406	2.19 56	26.00 660	P132447	Air Panel, Ventilation

Length IN MM	Height IN MM	Width IN MM	PART NUMBER	PART DESCRIPTION
17.00 432	0.94 24	6.65 169	P785046	Air Panel

Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
17.12 435	2.19 56	8.46 215	P533788	Air Panel, Ventilation

Length IN MM	Height IN MM	Width IN MM	PART NUMBER	PART DESCRIPTION
17.31 440	1.37 35	3.90 99	P785307	Air Panel

Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
18.00 457	2.19 56	20.00 508	P528465	Air Panel, Engine
18.58 472	7.44 189	2.76 70	P786335	Air Panel
18.74 476	7.79 198	18.74 476	P142807	Air Panel, Engine

Length IN MM	Width IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
18.75 476	5.00 127	22.00 559	P618922	Air Primary

Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
19.00 483	5.00 127	19.00 483	P142810	Air Panel, Engine
19.00 483	5.00 127	19.00 483	P142811	Air Panel, Engine
19.00 483	5.00 127	28.50 724	P142812	Air Panel, Engine
19.38 492	2.19 56	24.38 619	P114229	Air Panel, Ventilation
19.50 495	2.19 56	19.50 495	P102052	Air Panel, Engine
19.50 495	2.19 56	25.50 648	P140277	Air Panel, Ventilation
19.50 495	5.19 132	19.50 495	P146555	Air Panel, Ventilation
19.50 495	25.50 648	6.13 156	P607358	Air Panel, Ventilation
19.68 500	2.19 56	23.94 608	P148018	Air Panel
20.00 508	3.19 81	30.00 762	P531017	Air Panel, Engine
23.44 595	2.19 56	11.94 303	P150348	Air Panel, Ventilation
23.94 608	2.19 56	25.69 653	P148645	Air Panel
24.00 610	2.19 56	24.00 610	P103688	Air Panel, Ventilation
24.00 610	2.19 56	24.00 610	P111098	Air Panel, Engine

Air Panels - continued

Width IN MM	Height IN MM	Depth IN MM	PART NUMBER	PART DESCRIPTION
29.37 746	27.38 695	6.37 162	P618921	Air Primary

Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
33.00 838	2.19 56	4.00 102	P109761	Air Panel, Ventilation

Air PowerCore® Filters

Width IN MM	Height IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
4.75 121	7.26 184	12.54 319	P608665	Air Primary, PowerCore®
4.96 126	9.14 323	9.96 253	P788895	Air Primary, PowerCore®
5.12 130	7.22 183	12.87 327	P606119	Air Primary, PowerCore®
5.12 130	11.15 283	12.87 327	P606120	Air Primary, PowerCore®
5.82 148	7.13 181	9.83 250	P608533	Air Primary, PowerCore®
6.00 152	6.31 160	11.16 283	P611720	Air Primary, PowerCore®
6.00 152	7.20 183	11.10 282	P604273	Air Primary, PowerCore®
6.04 153	8.78 223	12.21 310	P613522	Air Primary, PowerCore®
6.42 163	6.89 175	9.06 230	P608766	Air Primary, PowerCore®
7.39 188	11.20 285	12.56 319	P608675	Air Primary, PowerCore®
7.86 200	11.07 281	13.05 331	P608676	Air Primary, PowerCore®

Outlet Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
7.95 202	10.66 271	P603577	Air Primary, PowerCore®

Width IN MM	Height IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
8.05 204	7.35 187	13.41 341	P608666	Air Primary, PowerCore®
8.43 214	6.20 157	14.38 365	P606122	Air Primary, PowerCore®

Height IN MM	Width IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
9.11 232	7.09 180	11.57 295	P609086	Air Primary, PowerCore®

Outer Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
9.26 235	6.28 160	P610875	Air Primary, PowerCore®

Width IN MM	Height IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
9.96 253	9.84 250	17.35 440	P616056	Air Primary, PowerCore®
10.00 254	9.31 236	15.06 383	P608667	Air Primary, PowerCore®
10.06 256	13.25 337	15.06 383	P608677	Air Primary, PowerCore®
10.31 262	111 282	9.96 253	P788896	Air Primary, PowerCore®

Outer Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
10.33 262	9.16 233	P619334	Air Primary, PowerCore®

Outer Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
12.84 326	7.99 203	P607960	Air Primary, PowerCore®
12.85 326	7.99 203	P607955	Air Primary, PowerCore®
14.84 377	7.99 203	P607965	Air Primary, PowerCore®
14.84 377	8.03 204	P605960	Air Primary, PowerCore®

Air Rounds

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
	2.30 58	9.50 241	P900763	Air Safety
	3.55 90	10.88 276	P900247	Air Primary
1.39 35	0.50 13	1.86 48	P500007	Air Primary
1.82 46	1.22 31	6.59 167	P535396	Air Safety, RadialSeal
1.97 50	3.63 92	2.84 72	P606072	Air Primary
2.10 53	1.90 48	10.25 260	P520511	Air Safety
2.20 56	1.78 45	9.33 237	P780018	Air Safety
2.28 58	2.04 52	7.13 181	P776357	Air Safety
2.38 60	1.87 47	13.00 330	P535338	Air Safety
2.38 60	1.91 49	7.00 178	P535366	Air Safety
2.40 61	1.89 48	11.42 290	P775298	Air Safety, RadialSeal
2.44 62	1.77 45	10.23 260	P822858	Air Safety, RadialSeal
2.44 62	1.77 45	10.23 260	P841639	Air Safety, RadialSeal
2.44 62	1.77 45	13.50 343	P600047	Air Safety, RadialSeal
2.46 62	1.91 49	8.26 210	P118785	Air Safety
2.46 62	1.91 49	8.26 210	P120949	Air Safety
2.46 62	1.91 49	13.00 330	P120307	Air Safety
2.46 62	1.94 49	9.00 229	P141278	Air Safety
2.56 65	2.16 55	12.02 305	P780024	Air Safety
2.59 66	2.15 55	10.00 254	P123160	Air Safety
2.60 66	2.12 54	10.39 264	P776565	Air Safety
2.62 67		10.24 260	P603729	Air Safety
2.76 70	1.97 50	11.16 283	P777523	Air Safety
2.76 70	2.40 61	7.24 184	P776895	Air Safety
2.76 70	2.40 61	9.06 230	P778833	Air Safety
2.76 70	2.40 61	10.02 255	P770181	Air Safety
2.76 70	2.40 61	10.98 279	P778361	Air Safety
2.76 70	2.40 61	12.13 308	P770207	Air Safety
2.87 73	2.86 73	7.48 190	P775704	Air Safety
2.91 74	1.89 48	10.20 259	P776566	Air Safety

Outer Diameter IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
2.91 74	4.06 103	2.05 52	P786789	Air Primary

Width IN MM	Length IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
2.91 74	4.06 103	2.80 71	P786889	Air Primary

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
2.94 75	1.88 48	9.64 245	P526864	Air Safety
2.94 75	2.00 51	3.94 100	P606949	Air Primary
2.94 75	2.38 60	9.94 252	P526501	Air Safety
2.94 75	2.38 60	13.38 340	P526504	Air Safety
2.94 75	2.47 63	8.06 205	P606081	Air Safety
2.95 75	0.69 18	10.98 279	P126984	Air Safety
2.95 75	1.89 48	11.18 284	P778090	Air Safety
2.95 75	2.40 61	14.00 356	P119539	Air Safety
2.95 75	2.55 65	13.52 343	P780030	Air Safety
2.97 75	1.86 47	9.94 252	P607340	AIR Secondary
3.00 76	2.40 61	11.00 279	P130776	Air Safety
3.07 78	2.04 52	12.64 321	P602427	Air Safety
3.12 79	1.50 38	3.25 83	P113720	Air Primary
3.13 80	2.15 55	10.00 254	R804523	Air Safety

Air Rounds - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
3.15 80	2.24 57	7.87 200	P777759	Air Safety
3.15 80	2.25 57	12.83 326	P777524	Air Safety
3.19 81	2.50 64	10.39 264	P776623	Air Safety
3.24 82		12.24 311	P781352	Air Safety
3.26 83		7.00 178	P102745	Air Primary, Finned
3.26 83	1.65 42	7.00 178	P775756	Air Primary
3.26 83	1.68 43	7.00 178	P121240	Air Primary, Finned
3.26 83	1.68 43	7.00 178	P148970	Air Primary, Finned
3.27 83	1.65 42		P775688	Air Primary
3.27 83	1.67 42	7.00 178	P123065	Air Primary, Finned
3.27 83	1.67 42	7.00 178	P526801	Air Primary, Finned
3.27 83	1.79 45	7.00 178	P148113	Air Primary, Finned
3.27 83	2.12 54	9.33 237	P500096	Air Safety
3.31 84	2.60 66	11.02 280	P778339	Air Safety
3.31 84	2.62 67	12.56 319	P775300	Air Safety, RadialSeal
3.32 84	2.54 65	8.89 226	P782300	Air Safety, RadialSeal
3.32 84	2.55 65	10.42 265	P610904	Air Safety, RadialSeal
3.32 84	2.55 65	10.42 265	P831079	Air Safety, RadialSeal
3.32 84	2.55 65	11.74 298	P534885	Air Safety, RadialSeal
3.32 84	2.55 65	11.74 298	P822769	Air Safety, RadialSeal
3.32 84	2.55 65	12.38 314	P542711	Air Safety, RadialSeal
3.32 84	2.55 65	12.38 314	P829332	Air Safety, RadialSeal
3.32 84	2.55 65	14.60 371	P601476	Air Safety, RadialSeal
3.32 84	2.55 65	14.65 372	P536941	Air Safety, RadialSeal
3.35 85	2.27 58	10.00 254	P158671	Air Safety
3.35 85	2.27 58	13.00 330	P112212	Air Safety
3.35 85	2.29 58	13.44 341	P607265	Air Safety
3.35 85	2.79 71	14.15 359	P780012	Air Safety
3.36 85	2.90 74	9.00 229	P541582	Air Safety
3.36 85	2.90 74	11.00 279	P131394	Air Safety
3.36 85	2.93 74	9.00 229	P770735	Air Safety
3.36 85	2.93 74	11.00 279	P119791	Air Safety
3.37 86	2.90 74	14.00 356	P119410	Air Safety
3.38 86	2.25 57		P784850	Air Safety
3.38 86	2.89 74	8.99 228	P770908	Air Safety
3.38 86	2.93 74	13.07 332	P770960	Air Primary
3.39 86	2.93 74	10.16 258	P775373	Air Safety
3.39 86	2.93 74	12.13 308	P775457	Air Safety
3.41 87	2.90 74	10.00 254	P124767	Air Safety
3.41 87	2.93 74	12.00 305	P127787	Air Safety
3.41 87	2.93 74	14.00 356	P114500	Air Safety
3.46 88	2.92 74	12.02 305	P610489	Air Safety, RadialSeal
3.46 88	2.92 74	12.84 326	P783731	Air Safety, RadialSeal
3.50 89	2.08 53	10.35 263	P133702	Air Primary
3.54 90	1.77 45	7.05 179	P822686	Air Primary, RadialSeal
3.56 90	2.06 52	4.17 106	P606271	Air Primary
3.57 91	2.80 71	14.65 372	P549277	Air Safety, RadialSeal
3.62 92	2.80 71	12.76 324	P778131	Air Safety
3.62 92	2.80 71	13.46 342	P776694	Air Safety
3.62 92	2.94 75	13.69 348	P181208	Air Safety
3.62 92	2.99 76	9.25 235	P539242	Air Safety
3.64 93	1.38 35		P500182	Air Primary
3.64 92	2.40 61	11.14 283	P770398	Air Safety
3.72 95	2.92 74	13.37 340	P604997	Air Safety, RadialSeal
3.72 95	2.92 74	13.37 340	P829333	Air Safety, RadialSeal

Air Rounds - continued

Outer Diameter IN MM		Inner Diameter IN MM		Length IN MM		PART NUMBER	PART DESCRIPTION
3.72	95	2.92	74	13.50	343	P771531	Air Primary, Finned
3.74	95	2.93	74	10.08	256	P778832	Air Safety
3.78	96	2.62	67	10.08	256	P533599	Air Safety
3.80	97	2.64	67	10.08	256	P158664	Air Safety
3.82	97	2.37	60	2.76	70	P530645	Air Primary
3.85	98	3.11	79	13.18	335	P777577	Air Safety, RadialSeal
3.87	98	2.73	69	3.12	79	P530643	Air Primary
3.87	98	3.16	80	13.00	330	P136401	Air Safety
3.88	99	2.50	64	11.75	298	P526498	Air Safety
3.88	99	3.15	80	11.22	285	P785513	Air Safety
3.89	99	2.36	60	2.76	70	P607295	Air Primary
3.93	100	7.48	190	13.28	337	P777578	Air Primary, RadialSeal
3.94	100	2.64	67	3.11	67	P784578	Air Primary
3.98	101	4.37	111	12.99	330	P500168	Air Primary
3.99	101	2.32	59	5.07	129	P158676	Air Safety
3.99	101	2.32	59	5.18	132	P527530	Air Safety
4.08	104	1.50	38	6.02	153	P131321	Air Primary
4.08	104	2.49	63	7.00	178	P130769	Air Primary
4.08	104	2.49	63	9.00	229	P108736	Air Primary, Finned
4.08	104	2.49	63	10.00	254	P122510	Air Primary, Finned
4.08	104	2.49	63	10.00	254	P148969	Air Primary, Finned
4.08	104	2.49	63	10.00	254	P181050	Air Primary, Finned
4.08	104	2.49	63	10.00	254	P182050	Air Primary, Finned
4.08	104	2.49	63	14.00	356	P181072	Air Primary, Finned
4.08	104	2.49	63	14.00	356	P182072	Air Primary, Finned
4.09	104	2.47	63	5.71	145	E500667	Air Primary, Finned
4.09	104	2.48	63	8.00	203	P533597	Air Primary, Finned
4.09	104	2.48	63	9.38	238	P607231	Air Primary
4.09	104	2.48	63	10.00	254	P533256	Air Primary
4.09	104	2.48	63	10.00	254	P535362	Air Primary
4.09	104	2.48	63	10.00	254	P778340	Air Primary
4.09	104	2.48	63	10.00	254	P814723	Air Primary, Finned
4.09	104	2.48	63	13.38	340	P607293	AIR Secondary
4.09	104	2.48	63	14.00	356	P535337	Air Primary, Finned
4.09	104	2.49	63	8.03	204	P775749	Air Primary, Finned
4.09	104	2.49	63	8.54	217	P776356	Air Primary, Finned
4.09	104	2.49	63	10.55	268	P775687	Air Primary
4.09	104	2.50	64	9.94	252	P606953	Air Primary
4.09	104	2.52	64	10	254	P778174	Air Primary
4.09	104	2.91	74	14.00	356	P526839	Air Safety
4.09	104	3.23	82	10.11	257	P505976	Air Primary
4.09	104	3.65	93	15.00	381	P119778	Air Safety
4.12	105	3.00	76	14.56	370	P607247	AIR Secondary
4.12	105	3.58	91	14.21	361	P778637	Air Safety, RadialSeal
4.13	105	2.13	54	1.79	46	P500193	Air Primary
4.13	105	2.68	68	11.81	300	P772578	Air Primary, RadialSeal
4.13	105	2.68	68	11.81	300	P775631	Air Primary, RadialSeal
4.13	105	3.58	91	14.06	357	P777779	Air Safety, RadialSeal
4.13	105	3.73	95	15.21	386	P780036	Air Safety
4.14	105	3.33	85	15.41	391	P601286	Air Safety, RadialSeal
4.16	106	2.36	60	10.43	265	P821575	Air Primary, RadialSeal
4.16	106	2.36	60	10.43	265	P831424	Air Primary, RadialSeal
4.16	106	2.36	60	14.31	363	P600043	Air Primary, RadialSeal
4.16	106	3.00	76	10.70	272	P616641	Air Primary
4.16	106	3.65	93	13.00	330	P132939	Air Safety

Air Rounds - continued

Outer Diameter IN MM		Inner Diameter IN MM		Length IN MM		PART NUMBER	PART DESCRIPTION
4.16	106	3.65	93	14.55	370	P120484	Air Safety
4.17	106	2.27	58	8.97	228	P546641	Air Primary
4.25	108	1.56	40	4.50	114	P181128	Air Primary
4.25	108	1.56	40	4.81	122	P606488	Air Primary
4.25	108	2.00	51	3.81	97	P606290	Air Primary
4.25	108	2.00	51	6.14	156	P530634	Air Primary
4.25	108	2.22	56	7.13	181	P607345	Air Primary, Finned
4.27	108	2.72	69	6.49	165	P533652	Air Safety, RadialSeal
4.27	108	2.79	71	5.61	142	P533110	Air Safety, RadialSeal
4.27	108	3.44	87	5.61	142	P778027	Air Safety
4.27	108	3.44	87	15.75	400	P777639	Air Safety, RadialSeal
4.27	108	3.45	88	10.64	270	P537716	Air Safety, RadialSeal
4.27	108	3.45	88	14.83	377	P780523	Air Safety, RadialSeal
4.27	108	3.45	88	15.08	383	P547332	Air Safety, RadialSeal
4.27	108	3.47	88	19.72	501	P781471	Air Safety
4.33	110	1.99	51	8.58	218	P778404	Air Primary
4.33	110	3.89	99	16.50	419	P902385	Air Safety
4.34	110	3.00	76	11.57	294	P607343	AIR Secondary
4.37	111			12.75	324	P503370	Air Safety
4.37	111			14.65	372	P776695	Air Safety
4.38	111	3.00	76	7.00	178	P526873	Air Primary
4.39	112	3.00	76	1.56	40	P530633	Air Primary
4.39	112	3.00	76	2.34	59	P528206	Air Primary
4.41	112	1.63	41	3.62	92	P607254	Air Primary
4.41	112	1.69	43	4.76	121	P500183	Air Primary
4.42	112	2.21	56	10.35	263	P136390	Air Primary
4.42	112	2.21	56	12.25	311	P133706	Air Primary
4.42	112	2.98	76	4.74	120	P539458	Air Primary
4.45	113	3.31	84	17.72	450	P617283	Air Safety, RadialSeal
4.47	114	3.43	87	14.00	356	P526408	Air Safety
4.48	114	2.64	67	9.43	240	P778979	Air Primary
4.50	114	3.00	76	3.34	85	P528220	Air Primary
4.51	115	2.54	65	14.00	355	P114637	Air Primary
4.53	115	2.50	64	13.11	333	P119492	Air Primary
4.53	115	3.50	89	13.53	344	P607268	AIR Secondary
4.57	116	3.46	88	15.00	381	P133138	Air Safety
4.57	116	3.46	88	16.54	420	P776019	Air Safety
4.57	116	3.49	89	15.00	381	P113343	Air Safety
4.58	116	3.48	88	11.00	279	P124837	Air Safety
4.58	116	3.48	88	13.00	330	P119374	Air Safety
4.58	116	3.48	88	14.72	374	P145703	Air Safety
4.58	116	3.48	88	15.65	398	P119375	Air Safety
4.60	117	3.48	88	12.28	312	P123828	Air Safety
4.60	117	3.59	91	12.00	305	P158678	Air Safety
4.60	117	4.48	114	15.19	386	P782107	Air Safety, RadialSeal
4.66	118	3.97	101	14.00	356	P141319	Air Safety
4.66	118	3.97	101	16.50	419	P136406	Air Safety
4.72	120	2.08	53	1.82	46	P505997	Air Primary
4.74	120	2.08	53	4.76	121	P500184	Air Primary
4.74	120	2.60	66	5.20	132	P500048	Air Primary
4.76	121	3.17	81	12.71	323	P601774	Air Safety, RadialSeal
4.76	121	3.25	83	11.56	294	P532500	Air Safety, RadialSeal
4.76	121	3.94	100	14.93	379	P776696	Air Safety
4.77	121	4.43	113	13.65	347	P821963	Air Safety, RadialSeal
4.78	121	3.62	92	12.08	307	P158661	Air Safety

Air Rounds - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
5.50 140	3.25 83	4.50 114	P528221	Air Primary
5.50 140	3.82 97	3.11 79	P607234	Air Primary
5.51 140	2.83 72	12.01 305	P771552	Air Primary
5.51 140	2.83 72	12.01 305	P772552	Air Primary
5.51 140	2.83 72	13.98 355	P771572	Air Primary
5.51 140	3.11 79	4.84 123	P506000	Air Primary

Width MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
5.51 140	8.19 208	1.77 45	P785965	Air Safety

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
5.52 140	3.50 89	12.93 328	P772579	Air Primary, RadialSeal
5.55 141	4.65 118	18.64 473	P776697	Air Safety
5.56 141	4.20 107	10.57 268	P522450	Air Safety
5.56 141	4.42 112	15.61 397	P539474	Air Safety
5.56 141	4.42 112	15.63 397	P526407	Air Safety
5.56 141	4.50 114	12.50 318	P607098	AIR Secondary
5.59 142	3.22 82	21.88 556	P781203	Air Safety
5.59 142	3.24 83	15.27 388	P780332	Air Safety
5.68 144	4.94 125	15.56 395	P538454	Air Safety
5.69 145	4.50 114	14.88 378	P610696	Air Safety
5.70 145	4.58 116	12.00 305	P127315	Air Safety
5.70 145	4.58 116	16.00 406	P131335	Air Safety
5.70 145	4.58 116	17.00 432	P124046	Air Safety
5.74 146	4.09 104	2.52 64	P777483	Air Primary
5.75 146	3.58 91	5.96 151	P537375	Air Primary
5.75 146	3.64 92	4.94 125	P607326	Air Primary
5.77 148	2.42 62	8.74 224	P505998	Air Primary, RadialSeal
5.80 147	3.51 89	10.06 256	P539479	Air Safety
5.82 148	3.09 78	12.71 323	P775792	Air Primary
5.83 148	2.83 72	12.80 325	P181086	Air Primary
5.83 148	2.83 72	12.80 325	P181089	Air Primary
5.88 149	3.00 76	9.25 235	P606482	Air Primary
5.91 150	3.44 87	13.62 346	P778989	Air Primary
5.91 150	3.50 89	2.87 73	P607240	Air Primary
5.94 151	3.25 83	4.00 102	P528235	Air Primary
5.94 151	3.56 90	2.78 71	P607325	Air Primary
5.94 151	4.31 109	19.53 496	P777414	Air Safety, RadialSeal
5.94 151	4.39 112	14.84 377	P538456	Air Safety, RadialSeal
5.94 151	4.39 112	19.02 483	P537877	Air Safety, RadialSeal
5.94 151	4.40 112	12.44 316	P532502	Air Safety, RadialSeal
5.94 151	4.40 112	15.51 394	P532504	Air Safety, RadialSeal
5.94 151	4.40 112	20.88 530	P537779	Air Safety, RadialSeal
5.94 151	4.84 123	12.01 305	P776498	Air Safety
5.94 151	4.84 123	14.37 365	P775510	Air Safety
5.94 151	4.86 123	10.00 254	P131336	Air Safety
5.94 151	4.86 123	11.00 279	P526416	Air Primary
5.94 151	4.86 123	12.00 305	P119371	Air Safety
5.94 151	4.86 123	13.50 343	P137640	Air Safety
5.94 151	4.86 123	14.00 356	P131337	Air Safety
5.94 151	4.86 123	18.00 457	P130772	Air Safety
5.94 151	5.05 128	9.76 248	P536442	Air Safety, RadialSeal
5.94 151	5.05 128	14.84 377	P533890	Air Safety, RadialSeal
5.95 151	4.85 123	14.00 356	P525944	Air Safety

Air Rounds - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
5.95 151	4.85 123	15.00 381	P770678	Air Safety
5.95 151	4.85 123	16.00 406	P126321	Air Safety
5.96 151	4.83 123	16.38 416	P607259	AIR Secondary
5.98 152	3.46 88	8.72 221	P606952	Air Primary
5.98 152	5.35 136	13.18 335	P777525	Air Safety
5.98 152	5.47 139	13.78 350	P777526	Air Safety
6.00 152	4.02 102	7.50 190	P535360	Air Primary
6.00 152	4.62 117	8.56 217	P524348	Air Primary
6.00 152	4.75 121	1.88 48	P528231	Air Primary
6.00 152	4.75 121	3.00 76	P528215	Air Primary
6.02 153	4.61 117	4.06 103	P530641	Air Primary
6.02 153	4.76 121	11.61 295	P500171	Air Safety
6.06 154	3.13 80	5.94 151	P500064	Air Primary
6.06 154	3.14 80	7.81 198	P539470	Air Primary
6.08 154	3.47 88	13.00 330	P546566	Air Primary, Finned
6.08 154	3.48 88	9.99 254	P771541	Air Primary
6.08 154	3.49 89	7.00 178	P181131	Air Primary
6.08 154	3.49 89	11.00 279	P181093	Air Primary, Finned
6.08 154	3.49 89	12.00 305	P130766	Air Primary
6.08 154	3.49 89	12.00 305	P148968	Air Primary, Finned
6.08 154	3.49 89	12.00 305	P181054	Air Primary, Finned
6.08 154	3.49 89	12.00 305	P182054	Air Primary, Finned
6.08 154	3.49 89	14.00 356	P113703	Air Primary
6.08 154	3.49 89	15.00 381	P131283	Air Primary
6.08 154	3.49 89	15.00 381	P148573	Air Primary, Finned
6.08 154	3.49 89	15.00 381	P181059	Air Primary, Finned
6.08 154	3.49 89	15.00 381	P182059	Air Primary, Finned
6.08 154	4.11 104	10.45 265	P526749	Air Primary
6.09 155	3.38 86	7.76 197	P500021	Air Primary
6.09 155	3.47 88	7.76 197	P778108	Air Primary
6.09 155	3.47 88	9.25 235	P535361	Air Primary
6.09 155	3.47 88	10.96 279	P778795	Air Primary
6.09 155	3.47 88	15.00 381	P119136	Air Primary
6.09 155	3.47 88	15.00 381	P815288	Air Primary, Finned
6.09 155	3.48 88	12.00 305	P122492	Air Primary, Finned
6.09 155	3.48 88	13.00 330	P127784	Air Primary, Finned
6.09 155	3.48 88	14.11 358	P771548	Air Primary, Finned
6.09 155	3.48 88	14.98 380	P772550	Air Primary, Finned
6.09 155	3.48 88	15.00 381	P525423	Air Primary
6.09 155	3.48 88	15.96 405	P772556	Air Primary
6.09 155	4.09 104	9.25 235	P535364	Air Primary
6.10 155	3.10 79	10.43 265	P500110	Air Primary
6.10 155	3.11 79	5.90 150	P500078	Air Primary
6.10 155	3.39 86	7.48 190	P500120	Air Primary
6.10 155	3.46 88	10 254	P770829	Air Primary
6.10 155	3.46 88	11.10 282	P771589	Air Primary
6.10 155	3.46 88	11.57 294	P771584	Air Primary
6.10 155	3.46 88	11.73 298	P778399	Air Primary
6.10 155	3.46 88	11.77 299	P776830	Air Primary, Finned
6.10 155	3.46 88	12.01 305	P771538	Air Primary
6.10 155	3.46 88	13.46 342	P770828	Air Primary
6.10 155	3.46 88	13.46 342	P772564	Air Primary
6.10 155	3.46 88	13.94 354	P772553	Air Primary
6.10 155	3.46 88	15.51 394	P773605	Air Primary, Finned
6.10 155	3.47 88	7.76 197	P778116	Air Primary

Air Rounds - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
6.10 155	3.47 88	14.96 380	P771550	Air Primary, Finned
6.10 155	4.09 104	12.01 305	P786442	Air Primary
6.10 155	4.09 104	12.50 318	P543662	Air Primary
6.11 155	3.38 86	11.85 301	P778337	Air Primary
6.12 155	3.08 78	15.04 382	P601437	Air Primary, RadialSeal
6.12 156	4.75 121	12.00 305	P812800	Air Primary
6.12 156	5.39 137	16.37 416	P782937	Air Safety
6.14 156	3.14 80	9.80 249	P778507	Air Primary, RadialSeal
6.14 156	3.15 80	13.54 344	P778509	Air Primary, RadialSeal
6.26 159	2.81 71	10.91 277	P780272	Air Primary
6.27 159	3.00 76	5.67 144	P500027	Air Primary
6.28 160	4.59 117	12.96 329	P158669	Air Safety
6.30 160	3.82 97	14.80 376	P778972	Air Primary
6.31 160	4.63 118	13.08 332	P158662	Air Safety
6.31 160	4.63 118	16.15 410	P158663	Air Safety
6.31 160	4.63 118	16.15 410	P521847	Air Safety
6.37 161	3.54 90	9.99 254	P815034	Air Primary
6.37 162	5.27 134	14.80 376	P775803	Air Safety
6.37 162	5.43 138	11.96 304	P535398	Air Primary
6.38 162	3.69 94	5.00 127	P607329	Air Primary
6.38 162	5.25 133	13.25 337	P606067	Air Primary, Finned
6.38 162	5.47 139	18.54 471	P777551	Air Safety
6.39 162	5.29 134	14.00 356	P134354	Air Safety
6.39 162	5.29 134	15.00 381	P123007	Air Safety
6.39 162	5.29 134	16.00 406	P119373	Air Safety
6.39 162	5.29 134	17.00 432	P529240	Air Safety
6.39 162	5.29 134	19.00 483	P124047	Air Safety
6.39 162	5.29 134	20.00 508	P118216	Air Safety
6.40 163	5.28 134	13.75 349	P526432	Air Safety
6.40 163	5.29 134	18.50 470	P138722	Air Safety
6.40 163	5.39 137	12.00 305	P830520	Air Primary
6.41 163	3.00 76	4.17 106	P500015	Air Primary
6.43 163	5.28 134	13.98 355	P777777	Air Safety
6.44 163	3.63 92	11.50 292	P606483	Air Round, Ventilation
6.46 164	3.38 86	7.95 202	P539466	Air Primary
6.46 164	3.41 87	8.35 212	P771594	Air Primary
6.46 164	3.41 87	9.37 238	P771593	Air Primary
6.46 164	3.41 87	13.07 332	P771557	Air Primary
6.47 164	3.41 87	13.38 340	P181088	Air Primary
6.47 164	3.58 91	11.42 290	P609447	Air Primary, RadialSeal
6.47 164	3.58 91	12.15 309	P606803	Air Primary, RadialSeal
6.47 164	3.58 91	12.17 309	P606804	Air Primary, RadialSeal
6.47 164	3.58 91	13.66 347	P604996	Air Primary, RadialSeal
6.47 164	3.86 98	14.09 358	P777179	Air Primary
6.48 164	3.58 91	13.08 332	P783730	Air Primary, RadialSeal
6.48 164	3.58 91	13.66 347	P828889	Air Primary, RadialSeal
6.49 165	3.58 91	10.65 271	P536733	Air Primary, RadialSeal
6.50 165	3.43 87	13.39 340	P778462	Air Primary
6.50 165	3.43 87	14.61 371	P782879	Air Primary
6.50 165	3.96 101	13.90 353	P772580	Air Primary, RadialSeal
6.50 165	4.06 103	9.13 232	P776995	Air Primary
6.52 166	5.89 150	14.23 361	P537286	Air Safety, RadialSeal
6.59 167	3.14 80	11.96 304	P778359	Air Primary
6.59 167	3.81 97	17.33 440	P607366	Air Primary
6.61 168	3.74 95	14.72 374	P771546	Air Primary

Air Rounds - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
6.61 168	5.23 133	17.32 440	P500174	Air Safety
6.61 168	7.85 200	10.98 279	P771559	Air Primary
6.68 170	3.75 95	14.75 375	P181204	Air Primary
6.69 170	4.05 103	10.37 264	P781530	Air Primary
6.69 170	5.04 128	3.00 76	P539463	Air Primary
6.70 170	3.68 93	11.04 280	P539476	Air Primary
6.75 171	5.15 131	19.82 504	P781228	Air Safety, RadialSeal
6.75 172	5.30 135	17.80 452	P778453	Air Safety, RadialSeal
6.75 171	5.56 141	6.00 152	P526497	Air Primary
6.80 173	4.24 108	15.00 381	P526840	Air Primary, Finned
6.81 173	5.03 128	13.97 355	P500198	Air Safety, RadialSeal
6.83 173	3.48 88	13.97 355	P771534	Air Primary
6.83 173	4.23 107	9.99 254	P771562	Air Primary
6.84 174	3.48 88	12.00 305	P181119	Air Primary
6.84 174	3.48 88	12.00 305	P611440	Air Primary
6.84 174	3.48 88	13.00 330	P123990	Air Primary
6.84 174	3.49 89	12.00 305	P136254	Air Primary
6.84 174	3.49 89	12.00 305	P181163	Air Primary
6.84 174	3.49 89	14.00 356	P150706	Air Primary
6.84 174	3.49 89	15.00 381	P131331	Air Primary, Finned
6.84 174	4.22 107	5.12 130	P607275	Air Safety
6.84 174	4.22 107	14.28 363	P607278	Air Primary
6.84 174	4.22 107	16.00 406	P182063	Air Primary, Finned
6.84 174	4.23 107	20.00 508	P533233	Air Primary, Finned
6.84 174	4.24 108	4.65 118	P526411	Air Primary
6.84 174	4.24 108	5.82 148	P123230	Air Safety
6.84 174	4.24 108	8.00 203	P015835	Air Primary
6.84 174	4.24 108	8.00 203	P124548	Air Safety
6.84 174	4.24 108	9.00 229	P181068	Air Primary
6.84 174	4.24 108	9.00 229	P181130	Air Primary
6.84 174	4.24 108	9.00 229	P181132	Air Primary
6.84 174	4.24 108	9.00 229	P182068	Air Primary
6.84 174	4.24 108	10.00 254	P130763	Air Primary, Finned
6.84 174	4.24 108	12.00 305	P181129	Air Primary
6.84 174	4.24 108	14.00 356	P132935	Air Primary, Finned
6.84 174	4.24 108	16.00 406	P181063	Air Primary, Finned
6.85 174	4.24 108	9.06 230	P771542	Air Primary
6.85 174	5.51 140	17.48 444	P780624	Air Safety, RadialSeal
6.85 174	5.51 140	20.78 528	P780623	Air Safety, RadialSeal
6.85 174	5.82 148	21.97 558	P777875	Air Safety, RadialSeal
6.87 174	3.15 80	7.90 201	P546598	Air Primary
6.87 174	3.26 83	5.91 150	P606078	Air Primary
6.87 174	3.41 87	7.90 201	P607342	Air Primary
6.88 175	5.42 138	13.94 354	P526510	Air Safety
6.88 175	6.10 155	21.22 539	P778403	Air Safety
6.89 175	4.00 102	16.00 406	P601280	Air Primary, RadialSeal
6.89 175	5.24 133	10.62 270	P603757	Air Safety, RadialSeal
6.89 175	5.24 133	15.98 406	P534544	Air Safety, RadialSeal
6.89 175	5.24 133	17.83 453	P549530	Air Safety, RadialSeal
6.89 175	5.24 133	21.33 542	P548901	Air Safety, RadialSeal
6.89 175	5.24 133	22.32 567	P612470	Air Safety, RadialSeal
6.89 175	5.32 135	14.23 361	P527683	Air Safety, RadialSeal
6.89 175	5.89 150	14.23 361	P608300	Air Safety
6.89 175	5.97 152	17.52 445	P533723	Air Safety, RadialSeal
6.90 175	5.50 140	2.20 56	P530628	Air Primary

Specs By Part Type

Air Rounds - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
6.92	176	4.44 113	9.00 229	P136828 Air Primary
6.92	176	5.50 140	2.55 65	P530639 Air Primary
6.94	176	4.22 107	15.37 390	P607246 Air Primary
6.96	177	5.60 142	3.00 76	P607255 Air Primary
6.97	177	3.46 88	11.10 282	P771590 Air Primary
6.97	177	3.46 88	13.54 344	P772535 Air Primary
6.97	177	3.46 88	15.51 394	P771529 Air Primary
6.97	177	3.46 88	15.51 394	P772529 Air Primary
6.98	177	5.58 142	1.84 47	P530635 Air Primary
7.00	178	3.42 87	17.02 432	P607286 AIR Secondary
7.02	178	4.39 112	19.76 502	P108158 Air Primary
7.06	179	3.88 99	4.06 103	P606958 Air Primary
7.07	180	3.98 101	11.77 299	P500094 Air Primary
7.08	180	3.66 93	8.70 221	P500200 Air Primary, RadialSeal
7.08	180	5.90 150	19.72 501	P777869 Air Safety, RadialSeal
7.09	180	3.70 94	8.62 219	P500014 Air Primary

Outer Diameter IN MM	Inner Diameter IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
7.13	181	4.72 120	3.31 84	P783387 Air Primary

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
7.13	181	4.94 125	4.44 113	P607248 Air Primary
7.16	182	6.01 153	3.00 76	P608654 Air Primary
7.17	182	5.79 147	11.73 298	P617645 Air Safety
7.20	183	5.55 141	16.69 424	P786362 Air Safety
7.20	183	5.55 141	19.80 503	P786360 Air Safety
7.21	183	5.66 144	14.49 368	P539486 Air Safety
7.24	184	3.58 91	10.65 271	P536732 Air Primary, RadialSeal
7.24	184	4.64 118	3.98 101	P500056 Air Primary
7.25	184	4.22 107	5.50 140	P814456 Air Primary
7.28	185	3.60 91	12.34 314	P783500 Air Primary, RadialSeal
7.28	185	6.18 157	17.32 440	P777938 Air Safety
7.28	185	6.18 157	19.29 490	P771073 Air Safety
7.28	185	6.19 157	12.86 326	P500177 Air Safety
7.28	185	6.20 157	15.18 386	P778857 Air Safety
7.28	185	6.20 157	15.65 398	P132349 Air Safety
7.28	185	6.20 157	17.70 450	P119372 Air Safety
7.28	185	6.20 157	17.70 450	P145701 Air Safety
7.28	185	6.20 157	18.00 457	P127313 Air Safety
7.28	185	6.20 157	23.00 584	P127309 Air Safety
7.28	185	6.22 158	14.57 370	P775500 Air Safety
7.28	185	6.22 158	21.89 556	P776102 Air Safety
7.28	185	6.22 158	23.82 605	P775339 Air Safety
7.28	185	6.37 162	17.99 457	P820633 Air Safety
7.31	186	4.00 102	13.38 340	P607352 Air Primary
7.31	186	5.23 133	13.16 334	P532474 Air Safety, RadialSeal
7.32	186		14.88 378	P771533 Air Primary
7.32	186	3.07 78	4.92 125	P500020 Air Primary
7.32	186	3.54 90	10.00 254	P136836 Air Primary
7.32	186	3.96 101	14.88 378	P133765 Air Primary
7.32	186	4.29 109	2.19 56	P500016 Air Primary
7.32	186	5.40 137	13.38 340	P526966 Air Primary
7.32	186	5.40 137	23.00 584	P520925 Air Primary

Air Rounds - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
7.33	186	4.00 102	14.25 362	P526499 Air Primary
7.33	186	4.16 106	13.70 348	P783117 Air Primary, RadialSeal
7.33	186	6.12 155	20.87 530	P526511 Air Safety
7.34	186	4.17 106	15.26 388	P780522 Air Primary, RadialSeal
7.36	187	4.78 121	10.81 275	P812901 Air Primary
7.36	187	4.78 121	15.00 381	P535365 Air Primary
7.36	187	4.78 121	15.00 381	R800103 Air Primary
7.36	187	4.78 121	15.00 381	P539477 Air Primary
7.38	187	4.34 110	2.70 69	P539477 Air Primary
7.38	187	6.12 155	25.38 645	P042345 Air Safety
7.38	187	6.12 155	25.38 645	P546613 Air Safety
7.40	188	5.83 148	18.62 473	P607272 Air Primary
7.40	188	5.90 150	18.62 473	P607262 AIR Secondary
7.44	189	4.61 117	15.23 387	P778994 Air Primary
7.46	189	5.99 152	13.38 340	P158670 Air Safety
7.50	190	3.58 91	10.65 271	P537729 Air Primary, RadialSeal
7.55	192	4.69 119	12.59 320	P607223 Air Primary
7.62	194	3.64 92	10.90 277	P780310 Air Primary
7.62	194	4.56 116	18.35 466	P614876 Air Primary, RadialSeal
7.63	194	4.29 109	16.00 406	P114241 Air Primary
7.63	194	4.29 109	16.00 406	P181092 Air Primary
7.63	194	4.29 109	16.00 406	P182092 Air Primary
7.64	194	3.35 85	5.71 145	P500017 Air Primary
7.64	194	3.35 85	5.71 145	P500024 Air Primary
7.64	194	6.04 153	12.00 305	P131338 Air Safety
7.64	194	6.04 153	15.00 381	P119370 Air Safety
7.64	194	6.04 153	15.00 381	P158050 Air Safety
7.64	194	6.04 153	15.50 394	P137641 Air Safety
7.64	194	6.04 153	17.00 432	P122425 Air Safety
7.64	194	6.04 153	18.00 457	P124860 Air Safety
7.64	194	6.04 153	18.00 457	P133179 Air Safety
7.64	194	6.04 153	20.00 508	P520582 Air Safety
7.64	194	6.04 153	21.00 533	P124862 Air Safety
7.64	194	6.04 153	21.65 550	P139293 Air Safety
7.66	195	4.61 117	14.13 359	P611190 Air Primary
7.70	196	6.00 152	8.78 223	P158666 Air Safety
7.70	196	6.00 152	13.38 340	P158668 Air Safety
7.72	196	12.09 307	18.54 471	P772521 Air Primary
7.73	196	6.06 154	14.05 357	P777356 Air Primary
7.75	197		8.09 205	P505061 Air Primary
7.75	197	7.59 193	22.51 572	P782109 Air Safety, RadialSeal
7.79	198	4.09 104	14.37 365	P777241 Air Primary
7.80	198	4.08 104	14.39 366	P140132 Air Primary
7.80	198	4.11 104	10.12 257	P771576 Air Primary
7.80	198	4.40 111	17.40 442	P614563 Air Primary, RadialSeal
7.80	198	4.44 113	14.40 366	P771561 Air Primary
7.80	198	4.44 113	20.00 508	P181165 Air Primary
7.80	198	6.54 166	12.36 314	P783756 Air Safety
7.88	200	4.13 105	11.15 283	P610485 Air Safety
7.90	201	6.24 158	15.47 393	P613926 Air Safety, RadialSeal
7.91	201	5.32 135	16.54 420	P771555 Air Primary, Finned
7.91	201	5.32 135	16.54 420	P772545 Air Primary
7.91	201	5.32 135	16.54 420	P772555 Air Primary, Finned
7.91	201	5.32 135	17.87 454	P772597 Air Primary
7.91	201	7.68 195	18.15 461	P787247 Air Safety
7.92	201	3.56 90	19.68 500	P500202 Air Primary

Air Rounds - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
7.92 201	5.31 135	13.00 330	P117624	Air Primary, Finned
7.93 201	3.56 90	19.77 502	P823295	Air Primary
7.93 201	3.57 91	10.00 254	P182045	Air Primary, Finned
7.93 201	3.57 91	12.00 305	P101038	Air Primary, Finned
7.93 201	3.57 91	13.00 330	P104445	Air Primary, Finned
7.93 201	3.57 91	16.00 406	P130747	Air Primary
7.93 201	3.57 91	16.00 406	P150464	Air Primary
7.93 201	4.45 113	12.99 330	P771502	Air Primary
7.93 201	4.57 116	10.00 254	P181045	Air Primary, Finned
7.93 202	4.57 116	13.74 349	P778457	Air Primary
7.93 202	5.27 134	19.29 490	P902309	Air Primary, Finned
7.93 201	5.31 135	10.00 254	P533230	Air Primary
7.93 201	5.32 135	10.00 254	P535769	Air Primary
7.93 201	5.32 135	12.00 305	P130764	Air Primary
7.93 201	5.32 135	13.00 330	P121557	Air Primary
7.93 201	5.32 135	16.00 406	P158852	Air Primary
7.93 201	5.32 135	16.00 406	P181064	Air Primary, Finned
7.93 201	5.32 135	16.00 406	P182064	Air Primary, Finned
7.93 201	7.49 190	16.00 406	P770991	Air Primary
7.94 202	3.59 91	16.50 419	P607360	Air Primary
7.94 202	6.38 162	10.39 264	P780385	Air Primary
7.95 202	3.54 90	13.54 344	P771505	Air Primary
7.95 202	3.54 90	14.09 358	P771511	Air Primary, Finned
7.95 202	4.37 111	16.85 428	P500169	Air Primary
7.95 202	4.57 116	11.81 300	P775732	Air Primary, Finned
7.95 202	4.84 123	14.57 370	P777588	Air Primary, RadialSeal
7.95 202	4.96 126	7.09 180	P533232	Air Primary
7.98 203	4.64 118	9.28 236	P530355	Air Primary
8.00 203	5.38 137	10.90 277	P606280	Air Primary
8.00 203	6.50 165	2.17 55	P530642	Air Primary
8.02 204	4.20 107	9.47 241	P532703	Air Primary, RadialSeal
8.03 204		6.93 176	P500008	Air Primary
8.04 204	3.75 95	13.12 333	P607351	Air Primary
8.04 204	5.00 127	19.52 496	P617644	Air Safety
8.04 204	6.06 154	11.00 279	P123347	Air Primary
8.06 205	5.78 147	4.00 102	P133705	Air Primary
8.09 206	5.28 134	15.25 387	P609239	Air Safety
8.11 206	6.50 165	10.51 267	P786843	Air Safety
8.12 206	4.84 123	21.00 533	P535597	Air Primary
8.12 206	6.62 168	3.25 83	P524350	Air Primary
8.13 207	4.26 108	7.81 198	P546597	Air Primary
8.14 207	4.61 117	20.03 509	P781470	Air Primary
8.17 208	6.88 175	15.14 385	P781678	Air Primary
8.17 208	20.35 517	3.14 80	P777592	Air Primary, RadialSeal
8.18 208	4.17 106	6.07 154	P533109	Air Primary, RadialSeal
8.18 208	4.17 106	6.95 177	P533651	Air Primary, RadialSeal
8.18 208	4.17 106	11.10 282	P537405	Air Primary
8.18 208	4.17 106	13.74 349	P783554	Air Primary, RadialSeal
8.18 208	4.17 106	14.53 369	P778638	Air Primary, RadialSeal
8.18 208	4.17 106	15.09 383	P547331	Air Primary, RadialSeal
8.18 208	4.17 106	16.12 409	P601790	Air Primary, RadialSeal
8.18 208	4.17 106	16.12 410	P781039	Air Primary, RadialSeal
8.18 208	4.73 120	12.64 321	P783871	Air Primary, RadialSeal
8.18 208	4.73 120	13.66 347	P784609	Air Primary
8.18 208	4.73 120	16.02 407	P783870	Air Primary, RadialSeal

Air Rounds - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
8.18 208	4.82 123	14.06 357	P821883	Air Primary, RadialSeal
8.19 208	4.17 106	16.22 412	P785589	Air Primary
8.19 208	4.33 110	16.14 410	P777638	Air Primary, RadialSeal
8.19 208	4.72 120	16.57 421	P780798	Air Primary, RadialSeal
8.19 208	4.72 120	12.64 321	P787155	Air Primary
8.24 209	4.20 107	12.58 320	P181141	Air Primary
8.24 209	7.12 181	9.00 229	P527957	Air Safety
8.24 209	7.12 181	13.00 330	P521692	Air Safety
8.24 209	7.12 181	22.00 559	P116446	Air Safety
8.25 209	5.75 146	10.50 267	P128487	Air Primary
8.25 210	5.90 150	3.95 100	P606279	Air Primary
8.25 210	6.50 165	3.00 76	P524390	Air Primary
8.26 210		15.15 385	R000133	Air Primary
8.30 211	7.72 196	23.97 609	P781351	Air Safety
8.31 211	4.06 103	8.27 210	P778472	Air Primary
8.31 211	5.30 135	12.28 312	P783432	Air Primary
8.32 211	6.20 158	11.72 298	P532508	Air Safety, RadialSeal
8.32 211	6.20 158	15.18 386	P532506	Air Safety, RadialSeal
8.32 211	6.20 157	20.81 529	P536529	Air Safety, RadialSeal
8.33 212	6.12 155	15.18 386	P532510	Air Safety, RadialSeal
8.33 212	6.12 155	16.60 422	P533946	Air Safety, RadialSeal
8.34 212	4.84 123	12.99 330	P771532	Air Primary
8.35 212	4.86 123	16.54 420	P771530	Air Primary
8.36 212	3.42 87	13.85 352	P778702	Air Primary
8.38 213	4.56 116	15.00 381	P181205	Air Primary
8.39 213		13.22 336	P503360	Air Primary
8.40 213	4.02 102	11.83 300	P780165	Air Primary
8.40 213	4.04 103	5.35 136	P181125	Air Primary
8.40 213	4.04 103	10.00 254	P181105	Air Primary
8.40 213	5.78 147	9.00 229	P017665	Air Primary
8.40 213	5.79 147	9.00 229	P270332	Air Primary
8.40 213	5.79 147	11.00 279	P181071	Air Primary
8.40 213	5.79 147	11.00 279	P182071	Air Primary
8.41 214	4.80 122	10.90 277	P777357	Air Primary
8.42 214	4.21 107	16.25 413	P181142	Air Primary
8.43 214	4.00 102	22.91 582	P772512	Air Primary
8.44 214		18.56 471	P605552	Air Safety
8.46 215	6.99 178	11.97 304	P158677	Air Safety
8.46 215	6.99 178	15.28 388	P158675	Air Safety
8.48 215	6.20 157	9.65 245	P524815	Air Safety
8.50 216	4.84 123	15.56 395	P606946	Air Primary
8.50 216	5.39 137	12.40 315	P500042	Air Primary
8.50 216	6.97 177	2.46 62	P524386	Air Primary
8.51 216	5.37 136	15.00 381	P546567	Air Primary
8.60 219	5.82 148	20.10 510	P786443	Air Primary
8.60 218	7.60 193	7.00 178	P607308	Air Primary
8.62 219	4.25 108	5.67 144	P500125	Air Primary
8.62 219	4.27 108	4.70 119	P500124	Air Primary
8.62 219	4.29 109	5.67 144	P526756	Air Primary
8.64 219	7.06 179	14.00 356	P124366	Air Safety
8.64 219	7.06 179	16.66 423	P114931	Air Safety
8.64 219	7.06 179	18.00 457	P124866	Air Safety
8.64 219	7.06 179	20.66 525	P124868	Air Safety
8.64 219	7.06 179	20.66 525	P133045	Air Primary
8.64 219	7.06 179	22.16 563	P784569	Air Safety

Air Rounds - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
9.33	237	5.15 131	13.15 334	P832150 Air Primary, RadialSeal
9.33	237	5.15 131	14.06 357	P821938 Air Primary, RadialSeal
9.33	237	5.15 131	14.49 368	EA5066 Air Primary, Ultra-Web®
9.33	237	5.15 131	14.49 368	P526678 Air Primary, RadialSeal
9.33	237	5.15 131	15.15 385	P533654 Air Primary, RadialSeal
9.33	237	5.15 131	15.80 401	P536036 Air Primary, RadialSeal
9.33	237	5.15 131	16.49 419	P611856 Air Primary, RadialSeal
9.33	237	5.15 131	18.15 461	P778905 Air Primary, RadialSeal
9.33	237	5.15 131	18.50 470	EA5105 Air Primary, Ultra-Web®
9.33	237	5.15 131	18.50 470	P532966 Air Primary
9.33	237	5.15 131	21.50 546	P538392 Air Primary, RadialSeal
9.33	237	5.16 131	24.61 625	EA5147 Air Primary, Ultra-Web® RS
9.33	237	5.80 147	23.03 585	EA5106 Air Primary, Ultra-Web® RS
9.33	237	5.80 147	23.03 585	P534096 Air Primary, RadialSeal
9.33	237	5.80 147	25.04 636	EA5108 Air Primary, Ultra-Web® RS
9.33	237	5.80 147	25.04 636	EA5114 Air Primary, Ultra-Web® RS
9.33	237	5.80 147	25.04 636	P600676 Air Primary, RadialSeal
9.37	238		1.50 38	P547520 Air Safety
9.40	239	5.78 147	5.18 132	P526753 Air Primary
9.43	240	6.87 174	3.62 92	P528216 Air Primary
9.44	240	5.78 147	21.22 539	P782105 Air Primary, RadialSeal
9.48	241	6.22 158	11.10 282	P776260 Air Primary
9.49	241	5.19 132	14.33 364	P778441 Air Primary
9.49	241	5.19 132	19.00 483	P181137 Air Primary
9.50	241	6.89 175	27.44 697	EA5048 Air Primary, Ultra-Web®
9.50	241	6.89 175	27.44 697	P151028 Air Primary
9.50	241	6.89 175	27.44 697	P524831 Air Primary
9.53	242	5.18 132	19.13 486	P772507 Air Primary
9.53	242	5.21 132	20.87 530	P775896 Air Primary
9.55	243	5.18 132	15.98 406	P776198 Air Primary
9.55	243	5.18 132	19.13 486	P771509 Air Primary
9.56	243	4.07 103	14.75 375	P526489 Air Primary
9.60	244	5.04 128	7.29 185	P136398 Air Primary
9.62	244	5.00 127	6.38 162	P526488 Air Primary
9.62	244	5.26 134	15.00 381	P181139 Air Primary
9.63	245	5.11 130	11.60 295	P133712 Air Primary
9.64	245	5.11 130	8.82 224	P500100 Air Primary
9.64	245	5.15 131	21.42 544	EA5148 Air Primary, Ultra-Web® RS
9.64	245	5.15 131	21.42 544	P544741 Air Primary, RadialSeal
9.64	245	5.15 131	23.26 591	P539765 Air Primary, RadialSeal
9.64	245	5.15 131	24.61 625	P537355 Air Primary, RadialSeal
9.64	245	5.20 132	8.82 224	P500099 Air Primary
9.65	245	3.81 97	18.14 461	P500102 Air Primary
9.65	245	6.04 153	13.58 345	P776497 Air Primary
9.65	245	6.04 153	16.54 420	P772587 Air Primary
9.67	246	6.00 152	19.80 503	P607377 Air Primary
9.68	246	4.92 125	15.07 383	P782596 Air Primary, RadialSeal
9.68	246	4.92 125	16.50 419	P782328 Air Primary, RadialSeal
9.68	246	5.09 129	14.68 373	P782137 Air Primary
9.68	246	7.91 201	19.72 501	P782998 Air Primary, RadialSeal
9.69	246	4.96 126	14.13 359	P786892 Air Primary
9.69	246	8.19 208	3.53 90	P524351 Air Primary
9.70	246	7.39 188	2.48 63	P539460 Air Primary
9.72	247	5.47 139	15.43 392	P782880 Air Primary
9.72	247	5.90 150	12.24 311	P782881 Air Primary

Air Rounds - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
9.72	247	8.19 208	2.26 57	P607228 Air Primary
9.73	247	5.66 144	12.56 319	P522451 Air Primary
9.73	247	5.67 144	12.56 319	EA5112 Air Primary, Ultra-Web®
9.75	248	6.13 156	5.24 133	P607291 Air Primary
9.76	248	5.90 150	15.43 392	P784198 Air Primary
9.81	249	4.61 117	14.41 366	P607267 Air Primary
9.84	250	7.56 192	2.40 61	P500004 Air Primary
9.88	251	6.00 152	16.00 406	P607359 Air Primary
9.88	251	8.06 205	27.75 705	P546762 Air Safety
9.90	252	6.04 154	15.53 395	P783729 Air Primary
9.91	252	6.05 154	16.00 406	P525943 Air Primary
9.91	252	8.06 205	23.50 597	P607224 Air Safety
9.94	252	5.37 136	15.44 392	P613337 Air Safety
9.97	253	4.85 123	15.50 394	P616081 Air Primary, RadialSeal
9.97	253	8.63 219	2.31 59	P607238 Air Primary
9.98	253	5.48 139	20.28 515	P526491 Air Safety
9.98	253	5.48 139	20.28 515	P526492 Air Primary
10.00	254	4.96 126	17.60 447	P788809 Air Primary, RadialSeal
10.00	254	5.00 127	12.88 327	P606296 Air Primary
10.00	254	5.88 149	17.06 433	P538453 Air Primary
10.03	255	6.26 159	16.46 418	P500111 Air Primary
10.03	255	8.14 207	18.03 458	P525129 Air Safety
10.04	255	7.20 183	2.24 57	P500006 Air Primary
10.06	256	5.68 144	16.38 416	P607357 Air Primary
10.15	258	6.29 160	20.78 528	P780815 Air Primary
10.16	258	6.30 160		P778436 Air Primary
10.16	258	7.91 201	2.36 60	P524374 Air Primary
10.22	260	7.97 202	16.00 406	P606503 Air Primary
10.24	260	9.12 232	22.00 559	P128408 Air Safety
10.25	260	5.51 140	12.00 305	P181133 Air Primary
10.25	260	7.62 194	2.75 70	P524391 Air Primary
10.31	262	7.94 202	0.41 10	P607324 Air Primary
10.31	262	8.03 204	20.47 520	P617643 Air Primary
10.37	263	5.63 143	10.00 254	P133701 Air Primary
10.39	264	6.02 153	15.98 406	P788751 Air Primary
10.39	264	6.02 153	17.99 457	P777156 Air Primary
10.39	264	6.06 154	15.98 406	P771524 Air Primary
10.39	264	6.06 154	16.54 420	P772520 Air Primary
10.39	264	6.06 154	16.54 420	P772531 Air Primary
10.40	264	6.03 153	12.00 305	P131348 Air Primary
10.40	264	6.03 153	12.00 305	P136847 Air Primary
10.40	264	6.03 153	13.00 330	P137957 Air Primary
10.40	264	6.04 153	7.75 197	P181107 Air Primary
10.40	264	6.04 153	9.00 229	P181123 Air Primary
10.40	264	6.04 153	10.00 254	P181021 Air Primary
10.40	264	6.04 153	10.00 254	P181200 Air Primary
10.40	264	6.04 153	11.75 298	P181106 Air Primary
10.40	264	6.04 153	11.90 302	P181019 Air Primary
10.40	264	6.04 153	13.76 350	EA5044 Air Primary, Ultra-Web®
10.40	264	6.04 153	14.00 356	P128252 Air Primary
10.40	264	6.04 153	14.00 356	P181044 Air Primary
10.40	264	6.04 153	14.00 356	P182044 Air Primary
10.40	264	6.04 153	15.00 381	EA5014 Air Primary, Ultra-Web®
10.40	264	6.04 153	15.00 381	P181014 Air Primary
10.40	264	6.04 153	15.00 381	P182014 Air Primary

Air Rounds - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
10.40 264	6.04 153	15.98 406	P771520	Air Primary
10.40 264	6.04 153	15.98 406	P772524	Air Primary
10.40 264	6.04 153	16.00 406	EAFF5028	Air Primary, Ultra-Web®
10.40 264	6.04 153	16.00 406	P115889	Air Primary
10.40 264	6.04 153	16.00 406	P131397	Air Primary
10.40 264	6.04 153	16.00 406	P181028	Air Primary
10.40 264	6.04 153	16.00 406	P182028	Air Primary
10.40 264	6.04 153	16.00 406	P524738	Air Primary
10.40 264	6.04 153	18.00 457	P126318	Air Primary
10.40 264	6.04 153	20.00 508	P181091	Air Primary
10.40 264	6.04 153	21.82 554	EAFF5007	Air Primary, Ultra-Web®
10.40 264	6.04 153	21.82 554	P181007	Air Primary
10.40 264	6.04 153	21.82 554	P182007	Air Primary
10.40 264	6.04 153	26.00 660	EAFF5016	Air Primary, Ultra-Web®
10.40 264	6.04 153	26.00 660	P181016	Air Primary
10.40 264	6.04 153	26.00 660	P182016	Air Primary
10.40 264	6.05 154	7.91 201	P539487	Air Primary
10.40 264	6.95 177	28.00 711	EAFF5024	Air Primary, Ultra-Web®
10.40 264	6.95 177	28.00 711	EAFF5061	Air Primary, Ultra-Web®
10.40 264	6.96 177	9.00 229	P181033	Air Primary
10.40 264	6.96 177	9.00 229	P182033	Air Primary
10.40 264	6.96 177	11.00 279	P181074	Air Primary
10.40 264	7.79 198	10.00 254	P119596	Air Primary
10.40 264	7.79 198	12.00 305	P015838	Air Primary
10.41 264	6.03 153	26.00 660	P520620	Air Primary
10.41 264	7.78 198	12.00 305	P616648	Air Primary
10.43 265	6.02 153	20.00 508	P182091	Air Primary
10.47 266	5.25 133	9.13 232	P776386	Air Primary
10.47 266	6.14 156	19.49 494	P500185	Air Primary
10.51 267	6.69 170	16.53 420	P785353	Air Primary, RadialSeal
10.51 267	6.69 170	19.17 487	P782936	Air Primary
10.51 267	6.69 170	19.41 493	P784457	Air Primary
10.52 267	6.69 170	17.32 440	P784525	Air Primary
10.52 267	6.69 170	19.41 493	P784456	Air Primary
10.55 268	7.68 195	11.18 284	P771551	Air Primary
10.62 270	6.61 168	20.04 509	P544765	Air Primary
10.62 270	7.95 202	1.65 42	P500071	Air Primary
10.64 270	7.95 202	2.13 54	P500005	Air Primary
10.65 271	6.97 177	22.95 583	P780519	Air Primary
10.66 271	6.22 158	22.44 570	P777105	Air Primary
10.67 271	6.22 158	23.19 589	P777767	Air Primary
10.75 273	6.38 162	13.91 353	P500046	Air Primary
10.86 276	6.49 165	14.17 360	P780373	Air Primary
10.86 276	6.50 165	15.00 381	P134353	Air Primary
10.86 276	6.50 165	15.00 381	P533445	Air Primary
10.86 276	6.50 165	20.00 508	EAFF5127	Air Primary, Ultra-Web®
10.86 276	6.50 165	20.00 508	P181082	Air Primary
10.86 276	6.50 165	20.00 508	P182082	Air Primary
10.86 276	8.18 208	21.68 551	P115070	Air Safety
10.87 276	6.50 165	7.00 178	P532931	Air Primary
10.87 276	6.50 165	15.00 381	P526428	Air Primary
10.87 276	6.50 165	15.00 381	P526433	Air Primary
10.87 276	6.50 165	15.00 381	P777776	Air Primary
10.87 276	6.50 165	18.00 457	P529241	Air Primary
10.87 276	9.00 229	2.21 56	P524358	Air Primary

Air Rounds - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
10.88 276	8.16 207	18.09 459	P539478	Air Safety
10.9 277	6.50 165	19.0 483	P902311	Air Primary
10.90 277	6.85 174	14.21 361	P500197	Air Primary, RadialSeal
10.91 277	6.30 160	10.12 257	P771510	Air Primary
10.92 277	6.75 171	25.56 649	P607374	Air Primary
10.93 278	6.50 165	5.03 128	P606288	Air Primary
11.00 279	7.93 201	20.44 519	P613333	Air Primary
11.02 280	7.20 183	26.10 663	P787492	Air Primary
11.03 280	5.84 148	19.38 492	P608653	Air Primary
11.03 280	6.00 152	19.59 498	P606954	Air Primary
11.06 281	4.99 127	15.94 405	P781350	Air Primary
11.06 281	5.78 15	14.21 361	P534435	Air Primary
11.06 281	6.57 167	18.38 467	P780911	Air Primary
11.06 281	6.57 167	19.44 494	P781525	Air Primary
11.06 281	6.57 167	20.07 510	P780910	Air Primary, RadialSeal
11.06 281	6.77 172	20.08 510	P777279	Air Primary
11.08 282	5.66 144	12.24 311	P781465	Air Primary
11.09 282	5.80 147	10.15 258	P536448	Air Primary, RadialSeal
11.09 282	5.80 147	12.88 327	P532501	Air Primary, RadialSeal
11.09 282	5.80 147	15.15 385	P533930	Air Primary, RadialSeal
11.09 282	5.80 147	15.95 405	P532503	Air Primary, RadialSeal
11.09 282	5.80 147	21.15 537	P537778	Air Primary, RadialSeal
11.09 282	5.82 148		P533655	Air Primary, RadialSeal
11.09 282	5.82 148	17.66 448	P783400	Air Primary
11.09 282	5.82 148	17.66 449	P784863	Air Primary
11.09 282	5.82 148	20.08 510	P537876	Air Primary, RadialSeal
11.09 282	6.57 167	15.94 405	P780331	Air Primary, RadialSeal
11.09 282	6.72 171	12.00 305	EAFF5000	Air Primary, Ultra-Web®
11.09 282	6.72 171	16.20 416	P534438	Air Primary, RadialSeal
11.09 282	6.72 171	20.00 508	P131280	Air Primary
11.09 282	6.73 171	10.00 254	P127915	Air Primary, Finned
11.09 282	6.73 171	12.00 305	P117383	Air Primary
11.09 282	6.73 171	12.00 305	P140681	Air Primary
11.09 282	6.73 171	12.00 305	P181000	Air Primary, Finned
11.09 282	6.73 171	12.00 305	P182000	Air Primary, Finned
11.09 282	6.73 171	13.00 330	P119720	Air Primary
11.09 282	6.73 171	13.00 330	P181104	Air Primary
11.09 282	6.73 171	15.00 381	P181077	Air Primary, Finned
11.09 282	6.73 171	16.00 406	EAFF5046	Air Primary, Ultra-Web®
11.09 282	6.73 171	16.00 406	P145700	Air Primary
11.09 282	6.73 171	16.00 406	P181023	Air Primary, Finned
11.09 282	6.73 171	16.00 406	P181046	Air Primary
11.09 282	6.73 171	16.00 406	P182046	Air Primary
11.09 282	6.73 171	16.06 408	P181102	Air Primary
11.09 282	6.78 172	14.19 360	P536577	Air Primary, RadialSeal
11.09 282	6.78 172	15.15 385	P549644	Air Primary, RadialSeal
11.09 282	6.78 172	23.44 595	EAFF5100	Air Primary, Ultra-Web®
11.10 282	5.82 148	21.19 538	EAFF5149	Air Primary, Ultra-Web® RS
11.10 282	5.83 148	20.08 510	P777409	Air Primary, RadialSeal
11.10 282	6.73 171	15.35 390	P772585	Air Primary
11.10 282	6.77 172	15.15 385	EAFF5107	Air Primary, Ultra-Web® RS
11.10 282	6.77 172	17.80 452	P534436	Air Primary, RadialSeal
11.10 282	7.87 200	21.26 540	P788716	Air Primary
11.31 287	8.56 217	5.56 141	P524360	Air Primary
11.40 290	5.82 148	22.96 583	P544950	Air Primary, RadialSeal

Air Rounds - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
11.40	290	6.78 172	21.19 538	P542753 Air Primary, RadialSeal
11.42	290	6.78 172	23.44 595	P534816 Air Primary, RadialSeal
11.48	292	5.80 147	15.15 385	EA5109 Air Primary, Ultra-Web® RS
11.49	292	8.12 206	13.00 330	P181118 Air Primary
11.50	292	7.19 183	13.00 330	P532473 Air Primary, RadialSeal
11.50	292	7.25 184	15.68 398	P526509 Air Primary
11.50	292	8.63 219	3.03 77	P607235 Air Primary
11.54	293	7.40 188	14.88 378	P778375 Air Primary
11.59	294	8.98 228	10.00 254	P119595 Air Primary
11.61	295	9.29 236	22.31 567	P608305 Air Safety, RadialSeal
11.61	295	9.29 236	27.40 696	P609518 Air Safety, RadialSeal
11.62	295	7.19 183	7.25 184	P526496 Air Primary
11.63	295	8.38 213	4.42 112	P607331 Air Primary
11.65	296	8.31 211	5.00 127	P524368 Air Primary
11.68	297	8.11 206	5.00 127	EA5187 Air Primary, Ultra-Web®
11.68	297	8.11 206	7.00 178	EA5188 Air Primary, Ultra-Web®
11.68	297	8.12 206	5.00 127	P181187 Air Primary
11.68	297	8.12 206	7.00 178	P181188 Air Primary
11.68	297	8.13 207	10.00 254	P546755 Air Primary
11.73	298	8.07 205	23.38 594	P782106 Air Primary, RadialSeal
11.73	298	8.66 220	15.78 401	P776251 Air Primary
11.75	298	9.56 243	2.12 54	P607232 Air Primary
11.83	300	7.15 182	12.80 325	P136837 Air Primary
11.87	301	10.25 260	17.66 449	P145859 Air Primary
11.87	301	10.25 260	22.02 559	P117781 Air Safety
11.88	302	7.51 191	14.37 365	P777242 Air Primary
11.88	302	7.51 191	17.71 450	P771574 Air Primary
11.89	302	7.48 190	18.58 472	P786816 Air Primary
11.89	302	7.52 191	13.31 338	P776252 Air Primary
11.89	302	7.52 191	14.98 380	P771575 Air Primary
11.89	302	7.52 191	15.91 404	P784467 Air Primary
11.89	302	7.52 191	18.15 461	P778613 Air Primary
11.89	302	7.52 191	18.66 474	P771558 Air Primary
11.89	302	7.52 191	19.06 484	P771573 Air Primary
11.90	302	7.51 191	18.11 460	P784784 Air Primary
11.92	303	6.88 175	12.55 319	P780731 Air Primary
11.92	303	6.91 176	17.04 433	P785520 Air Primary
11.94	303	7.50 191	4.25 108	P607288 Air Primary
11.95	303	6.88 175	17.99 457	P778924 Air Primary, RadialSeal
11.96	304	5.83 148	15.98 406	P782857 Air Primary
11.96	304	6.64 169		P785518 Air Primary
11.96	304	6.64 169	19.05 484	P785830 Air Primary, RadialSeal
11.96	304	6.64 169	20.31 516	P785519 Air Primary
11.96	304	6.81 173	17.09 434	P778335 Air Primary, RadialSeal
11.97	304	7.09 180	17.80 452	P787610 Air Safety
11.97	304	7.09 180	20.98 533	P787609 Air Primary
12.00	305	6.65 169	20.24 514	P778336 Air Primary, RadialSeal
12.00	305	7.29 185	15.00 381	P181134 Air Primary
12.00	305	7.32 186	10.76 273	P539484 Air Primary
12.00	305	9.83 250	2.49 63	P607237 Air Primary
12.00	305	9.88 251	3.46 88	P524355 Air Primary
12.00	305	9.88 251	5.47 139	P524369 Air Primary
12.01	305	6.65 169	18.58 472	P777579 Air Primary, RadialSeal
12.01	305	9.90 251	16.10 409	P613336 Air Primary
12.05	306	8.03 204	8.43 214	P771528 Air Primary

Air Rounds - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
12.06	306	4.91 125	9.32 237	P607279 Air Primary
12.08	307	7.73 196	7.50 191	P607274 Air Primary
12.08	307	7.73 196	21.07 535	P539471 Air Primary
12.09	307	5.73 146	12.00 305	P122605 Air Primary, Finned
12.09	307	6.78 172	17.99 457	P549523 Air Primary, RadialSeal
12.09	307	7.71 196	15.65 398	P778856 Air Primary
12.09	307	7.71 196	16.22 412	P771523 Air Primary
12.09	307	7.71 196	18.23 463	P780175 Air Primary
12.09	307	7.72 196	10.00 254	P181013 Air Primary, Finned
12.09	307	7.72 196	14.00 356	EA55001 Air Primary, Ultra-Web®
12.09	307	7.72 196	15.00 381	EA55096 Air Primary, Ultra-Web®
12.09	307	7.72 196	15.19 386	EA55056 Air Primary, Ultra-Web®
12.09	307	7.72 196	15.19 386	P181056 Air Primary
12.09	307	7.72 196	16.20 411	P772523 Air Primary
12.09	307	7.72 196	17.75 451	P606481 Air Primary
12.09	307	7.72 196	18.00 457	EA55015 Air Primary, Ultra-Web®
12.09	307	7.72 196	18.00 457	P145702 Air Primary
12.09	307	7.72 196	18.00 457	P185002 Air Primary, Ultra-Web®
12.09	307	7.72 196	19.47 495	P136835 Air Primary
12.09	307	7.72 196	20.00 508	P182043 Air Primary
12.09	307	7.72 196	23.00 584	P182078 Air Primary
12.09	307	7.72 196	23.00 584	P772506 Air Primary
12.09	307	7.73 196	7.00 178	P181030 Air Primary
12.09	307	7.73 196	10.00 254	P181032 Air Primary
12.09	307	7.73 196	10.00 254	P182032 Air Primary
12.09	307	7.73 196	12.00 305	P121922 Air Primary
12.09	307	7.73 196	13.00 330	P117327 Air Primary
12.09	307	7.73 196	13.00 330	P181037 Air Primary
12.09	307	7.73 196	13.00 330	P182037 Air Primary
12.09	307	7.73 196	14.00 356	P181001 Air Primary, Finned
12.09	307	7.73 196	14.00 356	P181010 Air Primary
12.09	307	7.73 196	14.00 356	P182001 Air Primary, Finned
12.09	307	7.73 196	15.00 381	P181096 Air Primary
12.09	307	7.73 196	15.00 381	P182096 Air Primary
12.09	307	7.73 196	15.35 390	P772586 Air Primary
12.09	307	7.73 196	15.75 400	P775804 Air Primary
12.09	307	7.73 196	16.00 406	EA55041 Air Primary, Ultra-Web®
12.09	307	7.73 196	16.00 406	P181018 Air Primary
12.09	307	7.73 196	16.00 406	P181041 Air Primary
12.09	307	7.73 196	16.00 406	P181076 Air Primary
12.09	307	7.73 196	16.00 406	P181100 Air Primary
12.09	307	7.73 196	16.00 406	P182041 Air Primary
12.09	307	7.73 196	16.00 406	P521055 Air Primary
12.09	307	7.73 196	17.24 438	P775918 Air Primary
12.09	307	7.73 196	17.25 438	P181136 Air Primary
12.09	307	7.73 196	18.00 457	EA55002 Air Primary, Ultra-Web®
12.09	307	7.73 196	18.00 457	P131343 Air Primary
12.09	307	7.73 196	18.00 457	P181002 Air Primary
12.09	307	7.73 196	18.00 457	P181015 Air Primary
12.09	307	7.73 196	18.00 457	P181079 Air Primary, Finned
12.09	307	7.73 196	18.00 457	P182002 Air Primary
12.09	307	7.73 196	18.00 457	P182015 Air Primary
12.09	307	7.73 196	18.58 472	P772567 Air Primary
12.09	307	7.73 196	19.00 483	P181073 Air Primary
12.09	307	7.73 196	19.88 505	EA55043 Air Primary, Ultra-Web®

Air Rounds - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
12.09 307	7.73 196	20.00 508	P181043	Air Primary
12.09 307	7.73 196	20.00 508	P270336	Air Primary
12.09 307	7.73 196	20.55 522	P772536	Air Primary
12.09 307	7.73 196	20.55 522	P772577	Air Primary
12.09 307	7.73 196	21.00 533	P181183	Air Primary
12.09 307	7.73 196	22.56 573	P775026	Air Primary
12.09 307	7.73 196	23.00 584	P181078	Air Primary
12.09 307	7.73 196	24.00 610	P127308	Air Primary
12.09 307	7.73 196	24.57 624	P772581	Air Primary
12.12 308	6.90 176	17.09 434	P781740	Air Primary, RadialSeal
12.12 308	6.91 176	21.44 544	P781741	Air Primary
12.12 308	7.71 196	14.21 361	P500178	Air Primary
12.13 308	6.93 176	20.24 514	P783289	Air Primary, RadialSeal
12.13 308	7.83 199	12.68 322	P617646	Air Primary
12.24 311	7.87 200	14.13 359	P777152	Air Primary
12.31 313	6.99 178	20.08 510	EAFF5116	Air Primary, Ultra-Web®
12.31 313	6.99 178	20.08 510	P777868	Air Primary, RadialSeal
12.31 313	6.99 178	22.44 570	P781187	Air Primary
12.32 313	6.99 178	20.07 510	P781640	Air Primary, RadialSeal
12.32 313	6.99 178	21.38 543	P785530	Air Primary
12.32 313	7.01 178	22.44 570	P777871	Air Primary, RadialSeal
12.32 313	7.71 196	17.71 450	P780622	Air Primary
12.32 313	7.71 196	21.37 543	P780621	Air Primary, RadialSeal
12.32 313	7.93 202	17.76 451	P785522	Air Primary
12.34 314	6.99 178	20.08 510	P608885	Air Primary, RadialSeal
12.34 313	7.00 178	22.44 570	P778674	Air Primary, RadialSeal
12.34 314	8.52 217	18.15 461	P785352	Air Primary, RadialSeal
12.49 317	7.72 196	15.00 381	P181120	Air Primary
12.49 317	9.13 232	18.50 470	P181124	Air Primary
12.50 318	7.50 190	22.25 565	P526512	Air Primary
12.50 318	8.20 208	15.02 382	P532507	Air Primary, RadialSeal
12.50 318	8.20 208	21.10 536	P536527	Air Primary, RadialSeal
12.50 318	8.21 209	15.02 382	P532505	Air Primary, RadialSeal
12.50 318	8.21 209	18.52 470	P532509	Air Primary, RadialSeal
12.56 319	7.50 191	21.00 533	P607371	Air Primary
12.56 319	7.51 191	26.81 681	P546614	Air Primary
12.56 319	7.51 191	26.88 683	P042343	Air Primary
12.60 320	8.35 212	5.50 140	P524367	Air Primary
12.62 321	9.75 248	5.00 127	P524362	Air Primary
12.62 321	9.75 248	5.51 140	P524366	Air Primary
12.69 322	8.38 213	22.50 572	P607367	Air Primary
12.74 324	7.44 189	21.38 543	EAFF5151	Air Primary, Ultra-Web® RS
12.74 324	7.44 189	25.38 645	EAFF5150	Air Primary, Ultra-Web® RS
12.74 324	7.44 189	25.44 646	EAFF5101	Air Primary, Ultra-Web®
12.74 324	8.38 213	8.00 203	P181005	Air Primary
12.74 324	8.38 213	9.31 236	P181113	Air Primary
12.74 324	8.38 213	11.00 279	P119417	Air Primary
12.74 324	8.38 213	14.00 356	P181004	Air Primary
12.74 324	8.38 213	14.00 356	P181025	Air Primary
12.74 324	8.38 213	14.04 357	P181114	Air Primary
12.74 324	8.38 213	15.75 400	P524344	Air Primary
12.74 324	8.38 213	16.00 406	P151098	Air Primary
12.74 324	8.38 213	17.03 433	EAFF5057	Air Primary, Ultra-Web®
12.74 324	8.38 213	17.03 433	P181057	Air Primary
12.74 324	8.38 213	19.06 484	P181055	Air Primary

Air Rounds - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
12.74 324	8.38 213	19.06 484	P182055	Air Primary
12.74 324	8.38 213	22.00 559	EAFF5008	Air Primary, Ultra-Web®
12.74 324	8.38 213	22.00 559	P181008	Air Primary
12.74 324	8.38 213	22.00 559	P182008	Air Primary
12.74 324	8.38 213	24.03 610	P181049	Air Primary
12.74 324	8.38 213	24.03 610	P182049	Air Primary
12.74 324	8.38 213	24.28 617	EAFF5049	Air Primary, Ultra-Web®
12.74 324	8.38 213	26.00 660	EAFF5102	Air Primary, Ultra-Web®
12.74 324	8.38 213	26.00 660	P145891	Air Primary
12.74 324	8.38 213	26.00 660	P181009	Air Primary
12.74 324	8.38 213	26.00 660	P181166	Air Primary
12.74 324	8.38 213	26.00 660	P181186	Air Primary
12.75 324	8.32 211	23.99 609	EAFF5027	Air Primary, Ultra-Web®
12.75 324	8.32 211	28.00 711	EAFF5026	Air Primary, Ultra-Web®
12.75 324	8.38 213	19.99 508	P771519	Air Primary
12.75 324	8.42 214	23.00 584	P128781	Air Primary
12.76 324	7.40 188	25.51 648	P544301	Air Primary, RadialSeal
12.76 324	8.38 213	21.10 536	P772519	Air Primary
12.78 325	0.50 13	26.50 673	P607362	Air Primary
12.78 325	10.14 258	13.81 351	P535115	Air Safety
12.82 326	10.14 258	9.81 249	P523048	Air Safety
12.83 326	6.57 167	13.94 354	P771582	Air Primary
12.83 326	7.60 193	9.57 243	P771583	Air Primary
12.87 327	0.48 12	2.30 58	P607301	Air Primary
12.87 327	6.33 161	10.16 258	P771595	Air Primary
12.87 327	7.51 191	18.38 467	P778485	Air Primary
12.87 327	7.52 191	18.39 467	P787157	Air Primary
12.87 327	9.56 243	18.11 460	P775843	Air Primary
12.88 327	8.50 216	23.77 604	P780006	Air Primary
12.98 330	9.13 232	18.91 480	P606720	Air Primary
13.06 332	6.78 172	18.15 461	EAFF5104	Air Primary, Ultra-Web®
13.06 332	7.44 189	21.38 543	P544243	Air Primary, RadialSeal
13.07 332	7.44 189	25.44 646	P534925	Air Primary, RadialSeal
13.08 332	6.78 172	14.76 375	P527682	Air Primary, RadialSeal
13.08 332	6.78 172	16.69 424	P605022	Air Primary, RadialSeal
13.09 332	6.78 172	11.10 282	P603755	Air Primary, RadialSeal
13.09 332	6.78 172	14.76 375	EAFF5069	Air Primary, Ultra-Web®
13.09 332	6.78 172	14.76 375	P541575	Air Primary
13.09 332	6.78 172	14.76 375	P606735	Air Primary
13.09 332	6.78 172	16.85 428	P533814	Air Primary, RadialSeal
13.09 332	6.78 172	18.15 461	P533235	Air Primary, RadialSeal
13.09 332	6.78 172	21.86 555	P548900	Air Primary, RadialSeal
13.09 332	6.78 172	22.86 581	P612469	Air Primary, RadialSeal
13.09 332	7.69 195	15.94 405	EAFF5098	Air Primary, Ultra-Web® RS
13.09 332	7.69 195	15.94 405	P540388	Air Primary, RadialSeal
13.09 332	7.99 203	16.22 412	P778779	Air Primary
13.09 332	8.66 220	15.57 396	P782396	Air Primary, RadialSeal
13.28 337	11.28 287	2.78 71	P524357	Air Primary
13.47 342	8.20 208	15.02 382	P606220	Air Primary, RadialSeal
13.47 342	8.20 208	17.24 438	P533938	Air Primary, RadialSeal
13.50 343	7.00 178	18.00 457	P528722	Air Primary
13.75 349	9.50 241	27.50 699	P607369	Air Primary
13.81 351	9.44 240	13.99 355	P771526	Air Primary
13.82 351	8.23 209	14.09 358	P778605	Air Primary
13.83 351	9.49 241	11.75 298	P181108	Air Primary

Air Rounds - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
13.83 351	9.49 241	14.00 356	P131404	Air Primary
13.83 351	9.49 241	14.00 356	P181031	Air Primary
13.83 351	9.49 241	14.00 356	P181066	Air Primary, Finned
13.83 351	9.49 241	14.00 356	P182031	Air Primary
13.83 351	9.49 241	15.00 381	P124370	Air Primary
13.83 351	9.49 241	15.50 394	P181095	Air Primary
13.83 351	9.49 241	15.50 394	P182095	Air Primary
13.83 351	9.49 241	15.68 398	P181115	Air Primary
13.83 351	9.49 241	16.00 406	P181036	Air Primary
13.83 351	9.49 241	16.00 406	P182036	Air Primary
13.83 351	9.49 241	17.75 451	P181109	Air Primary
13.83 351	9.49 241	17.88 454	EAFF5039	Air Primary, Ultra-Web®
13.83 351	9.49 241	18.00 457	P181039	Air Primary
13.83 351	9.49 241	18.00 457	P181193	Air Primary
13.83 351	9.49 241	18.06 459	P181099	Air Primary
13.83 351	9.49 241	19.00 483	P181012	Air Primary
13.83 351	9.49 241	21.02 534	P181185	Air Primary
13.83 351	9.49 241	22.00 559	P133044	Air Safety
13.83 351	9.49 241	22.03 560	P181047	Air Primary
13.83 351	9.49 241	23.00 584	P181058	Air Primary
13.83 351	9.49 241	25.00 635	P181061	Air Primary
13.84 352	6.69 170	10.00 254	EAFF5189	Air Primary, Ultra-Web®
13.84 352	7.47 190	18.06 459	EAFF5099	Air Primary, Ultra-Web®
13.84 352	7.48 190	7.00 178	P522926	Air Primary
13.84 352	7.48 190	10.00 254	P181189	Air Primary
13.84 352	7.48 190	12.00 305	P181060	Air Primary, Finned
13.84 352	7.48 190	18.02 458	P181065	Air Primary
13.84 352	7.48 190	18.06 459	P182099	Air Primary
13.84 352	7.48 190	22.06 560	P181147	Air Primary
13.84 352	9.47 241	13.03 331	P527566	Air Primary
13.84 352	9.47 241	15.50 394	EAFF5095	Air Primary, Ultra-Web®
13.84 352	9.47 241	16.00 406	P153962	Air Primary
13.84 352	9.47 241	16.00 406	P153972	Air Primary
13.84 352	9.47 241	18.00 457	P181053	Air Primary, Finned
13.84 352	9.47 241	18.00 457	P182039	Air Primary
13.84 352	9.47 241	20.00 508	P124867	Air Primary
13.84 352	9.48 241	26.00 660	P181011	Air Primary
13.84 352	11.23 285	7.00 178	P119184	Air Primary
13.84 352	11.23 285	14.00 356	P118157	Air Primary
13.85 352	7.45 189	7.50 191	P607260	Air Primary
13.85 352	10.12 257	22.00 559	P613439	Air Primary
13.88 353	9.95 253	29.00 737	P546761	Air Primary
13.88 353	11.61 295	4.05 103	P524373	Air Primary
13.88 353	11.63 295	3.04 77	P607236	Air Primary
13.97 355	7.99 203	16.45 418	P778778	Air Primary
14.00 356	7.72 196	20.63 524	P607263	Air Primary
14.28 363	7.20 183	20.24 514	P783280	Air Primary
14.28 363	8.98 228	15.03 382	P538007	Air Primary, RadialSeal
14.28 363	8.98 228	17.62 448	P533882	Air Primary, RadialSeal
14.28 363	8.98 228	18.90 480	P781398	Air Primary, RadialSeal
14.28 363	8.98 228	21.89 556	P783611	Air Primary, RadialSeal
14.28 363	8.98 228	24.41 620	P781098	Air Primary, RadialSeal
14.28 363	9.92 252	18.00 457	P181210	Air Primary
14.29 363	8.98 228	24.41 620	EAFF5156	Air Primary, Ultra-Web®
14.29 363	8.98 228	24.49 622	P785394	Air Primary

Air Rounds - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
14.38 365	8.26 210	16.69 424	P539462	Air Primary
14.64 372	9.44 240	19.68 500	P778081	Air Primary
14.68 373	10.34 263	23.88 607	EAFF5042	Air Primary, Ultra-Web®
14.68 373	10.34 263	23.88 607	P182042	Air Primary
14.68 373	10.34 263	24.00 610	P526415	Air Primary
14.68 373	10.34 263	24.02 610	P181042	Air Primary
15.09 383	8.70 221	15.34 390	EAFF5065	Air Primary, Ultra-Web®
15.09 383	8.70 221	15.34 390	P522874	Air Primary
16.53 420	9.96 253	9.84 250	P780848	Air Primary
16.53 420	9.96 253	12.00 305	P780834	Air Primary
16.62 422	12.03 306	16.00 406	P133709	Air Primary
16.62 422	12.03 306	24.00 610	P133714	Air Primary
17.58 447	11.07 281	23.06 586	P181038	Air Primary
17.58 447	12.22 310	19.03 483	P181048	Air Primary
17.58 447	12.22 310	19.03 483	P182048	Air Primary
17.58 447	12.22 310	23.03 585	EAFF5040	Air Primary, Ultra-Web®
17.58 447	12.22 310	23.03 585	P181040	Air Primary
17.58 447	12.22 310	23.03 585	P182040	Air Primary
17.62 448	11.07 281	23.06 586	EAFF5038	Air Primary, Ultra-Web®
17.62 448	11.07 281	23.06 586	P182038	Air Primary
17.76 451	11.46 291	24.06 611	EAFF5152	Air Primary, Ultra-Web® RS
17.76 451	11.46 291	24.06 611	P608306	Air Primary, RadialSeal
17.76 451	11.46 291	29.25 743	EAFF5153	Air Primary, Ultra-Web® RS
17.76 451	11.46 291	29.25 743	P609519	Air Primary, RadialSeal
17.90 455	5.29 135	3.70 94	P778906	Air Safety, RadialSeal
19.29 490	12.93 328	9.84 250	P181126	Air Primary
19.29 490	12.93 328	13.84 352	P535114	Air Primary
19.29 490	12.93 328	17.84 453	P603857	Air Primary
20.49 521	8.66 220	13.50 343	P785542	Air Primary
20.73 527	10.58 269	7.53 191	P607334	Air Primary
22.00 559	15.64 397	24.00 610	P529552	Air Primary

Air Specials

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
4.51 115	2.28 58	23.70 602	P500149	Air Primary, Special
4.51 115	2.81 72	23.70 602	P500146	Air Primary, Special

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
4.72 120	M76 x 4	23.62 600	P783648	Air Primary, Special

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
6.94 176	3.63 92	4.95 126	P902298	Air Primary, Special

Width IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
7.01 178	9.02 229	P780164	Air Primary, Special

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
7.09 180	3.70 94	8.62 219	P902299	Air Primary, Special
8.62 219	4.29 109	5.67 144	P902296	Air Primary, Special
9.09 231	4.60 117	10.70 272	P902736	Air Primary, Special

Air Specials - continued

Width IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
9.75 248	24.00 610	P524837	Air Primary, Special

Width IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
10.50 267	28.00 711	P136400	Air Primary, Special

Width IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
11.00 279	25.75 654	P154927	Air Primary, Special
13.50 343	24.00 610	P524838	Air Primary, Special
20.10 511	9.84 250	P521685	Air Primary, Wrap
22.90 582	23.97 609	P521686	Air Primary, Wrap

Width IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
24.00 610	26.00 660	0.50 13	P607314	Air Primary, Special

Air Vee-Pac™

Width IN MM	Depth IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
14.00 356	6.21 158	36.12 917	P125310	AIR Vee-Pac™
18.00 457	10.84 275	30.94 786	P107266	AIR Vee-Pac™
18.00 457	10.84 275	35.44 900	P114101	AIR Vee-Pac™

Coolant Filters

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
3.66 93	11/16-16	4.21 107	P554071	Coolant Spin-on
3.66 93	11/16-16	4.21 107	P554072	Coolant Spin-on
3.66 93	11/16-16	5.33 135	ECF4085	Coolant Spin-on
3.66 93	11/16-16	5.35 136	P554073	Coolant Spin-on
3.66 93	11/16-16	5.35 136	P554074	Coolant Spin-on
3.66 93	11/16-16	5.35 136	P554075	Coolant Spin-on
3.66 93	11/16-16	5.35 136	P554685	Coolant Spin-on
3.66 93	11/16-16	7.87 200	P552055	Coolant Spin-on
3.66 93	11/16-16	7.87 200	P552076	Coolant Spin-on
3.66 93	3/4-20	5.35 136	P554860	Coolant Spin-on
3.66 93	M16 x 1.5	4.20 107	ECF4081	Coolant Spin-on
3.66 93	M16 x 1.5	5.35 136	ECF4086	Coolant Spin-on
3.66 93	M16 x 1.5	5.35 136	ECF4089	Coolant Spin-on
3.66 93	M16 x 1.5	5.35 136	P552096	Coolant Spin-on
3.66 93	M16 x 1.5	5.35 136	P554019	Coolant Spin-on
3.67 93	11/16-16	5.35 136	ECF4088	Coolant Spin-on
3.67 93	3/4-20	5.32 135	P551309	Coolant Spin-on
3.68 94	M36 X 2	5.79 147	P550866	Coolant Spin-on
3.68 93	M36 X 2	5.79 147	P550867	Coolant Spin-on
3.69 94	11/16-16	4.20 107	P552071	Coolant Spin-on
3.69 94	11/16-16	5.35 136	P552106	Coolant Spin-on
3.69 94	11/16-16	5.44 138	P552088	Coolant Spin-on
3.69 94	M36 x 2	5.76 146	P552126	Coolant Spin-on
3.70 94	11/16-16	4.20 107	P552070	Coolant Spin-on
3.70 94	11/16-16	4.20 107	P552072	Coolant Spin-on
3.70 94	11/16-16	5.35 136	P552073	Coolant Spin-on
3.70 94	11/16-16	5.35 136	P552074	Coolant Spin-on
3.70 94	11/16-16	5.35 136	P552075	Coolant Spin-on
3.77 96	M36 x 2	5.76 146	P550585	Coolant Spin-on

Coolant Filters - continued
Fuel Box

Width IN MM	Height IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
2.64 67	2.59 66	4.38 111	P552387	Fuel Box Primary
2.83 72	2.43 62	4.61 117	P550955	Fuel Box Primary
2.83 72	2.46 62	4.62 117	P556285	Fuel Box Primary
2.83 72	2.46 62	4.62 117	P556286	Fuel/Water Separator Box
2.83 72	2.46 62	4.62 117	P557264	Fuel/Water Separator Box
3.28 83	2.64 67	6.31 160	P551049	Fuel Box Primary

Length IN MM	Depth IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION
3.46 88	3.46 88	2.00 51	P502392	Fuel Box Primary

Width IN MM	Height IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
3.71 94	3.15 80	4.95 126	P551130	Fuel Box Primary
3.71 94	3.28 83	5.04 128	P556745	Fuel Box Primary
3.71 94	3.34 85	4.95 126	P559803	Fuel Box Primary

Fuel Cartridge

Outer Diameter IN MM	Inner Diameter	Length IN MM	PART NUMBER	PART DESCRIPTION
0.64 16		0.79 20	P552373	Fuel Cartridge Secondary
0.70 18	0.20 5	2.01 51	P550559	Fuel Cartridge
1.12 28	G 8-36	1.72 44	P502136	Fuel Cartridge
1.14 29	0.51 13	3.35 85	P502138	Fuel Cartridge
1.14 29	0.52 13	2.27 58	P552378	Fuel Cartridge
1.15 29	0.30 8	3.31 84	P502360	Fuel Cartridge
1.38 35	0.43 11	1.85 47	P502406	Fuel Cartridge
1.38 35	0.43 11	2.44 62	P502134	Fuel Cartridge
1.38 35	0.43 11	3.39 86	P502166	Fuel Cartridge
1.38 35	0.47 12	3.43 87	P502135	Fuel Cartridge
1.38 35	0.47 12	3.81 97	P502133	Fuel Cartridge
1.38 35	1.73 44	0.45 11	P502115	Fuel Cartridge
1.39 35	0.50 13	1.88 48	P550007	Fuel Cartridge
1.42 36	0.49 12	3.54 90	P550645	Fuel Cartridge
1.45 37	0.70 18	3.82 97	P552395	Fuel Cartridge
1.78 45	0.50 13	2.68 68	P552000	Fuel/Water Separator Cartridge
1.87 47	0.51 13	1.77 45	P551769	Fuel Cartridge
1.97 50	0.79 20	3.50 89	P502161	Fuel Cartridge
2.14 54	0.44 11	3.47 88	P550214	Fuel Cartridge
2.19 56	0.26 7	1.47 37	P550364	Fuel Cartridge
2.19 56	0.91 23	2.48 63	P550567	Fuel Cartridge
2.22 56	0.53 13	4.49 114	P550860	Fuel Cartridge
2.24 57	0.38 10	2.99 76	P552341	Fuel Cartridge
2.32 59		2.60 66	P550527	Fuel Cartridge

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
2.38 60	1/4-18	37.25 946	P552383	Fuel Cartridge

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
2.44 62	0.43 11	2.36 60	P550038	Fuel Cartridge
2.56 65	1.50 38	6.38 162	P550653	Fuel Cartridge

Fuel Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
2.59	66	0.62 16	4.47 114	P550120 Fuel Cartridge
2.60	66	0.55 14	4.30 109	P550060 Fuel Cartridge
2.75	70	0.52 13	4.52 115	P550481 Fuel Cartridge
2.75	70	0.81 21	3.37 86	P551167 Fuel Cartridge
2.83	72	0.43 11	1.73 44	P502113 Fuel Cartridge
2.83	72	0.43 11	3.54 90	P550056 Fuel Cartridge
2.83	72	0.57 14	3.35 85	P552563 Fuel Cartridge
2.87	73	0.46 12	3.14 80	P550745 Fuel Cartridge
2.87	73	0.55 14	3.39 86	P550837 Fuel Cartridge
2.87	73	1.38 35	3.50 89	P502362 Fuel Cartridge
2.90	74	1.10 28	2.37 60	P550560 Fuel Cartridge Sock
2.91	74	0.63 16	4.15 106	P550026 Fuel Cartridge
2.93	74	0.58 15	2.91 74	P551339 Fuel Cartridge
2.93	74	0.62 16	2.20 56	P550673 Fuel Cartridge
2.93	74	0.62 16	4.11 104	P550672 Fuel Cartridge
2.95	75	0.63 16	2.60 66	P502118 Fuel Cartridge
2.95	75	0.75 19	6.97 177	P502196 Fuel Cartridge
2.95	75	1.24 31	8.38 213	P550552 Fuel Cartridge Sock

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
2.96	75 1 1/8-12	5.23 133	P550674	Fuel/Water Separator Cartridge

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
2.98	76	1.03 26	7.81 198	P550540 Fuel Cartridge Secondary
2.99	76	1.08 27	7.95 202	P550627 Fuel Cartridge
3.00	76	1.02 26	6.00 152	P550522 Fuel Cartridge
3.01	76	1.04 26	4.41 112	P550686 Fuel/Water Separator Cartridge
3.01	76	1.04 26	7.34 186	P550685 Fuel/Water Separator Cartridge
3.01	76	1.04 26	9.70 246	P551162 Fuel Cartridge
3.13	80	0.72 18	5.44 138	P552423 Fuel Cartridge
3.15	80	.90 23	5.31 135	P551423 Fuel/Water Separator Cartridge
3.15	80	.90 23	5.31 135	P551426 Fuel/Water Separator Cartridge
3.15	80	.90 23	5.31 135	P551429 Fuel/Water Separator Cartridge
3.15	80	.90 23	5.31 135	P551436 Fuel/Water Separator Cartridge
3.15	80	.90 23	6.05 154	P551421 Fuel/Water Separator Cartridge
3.15	80	.90 23	6.05 154	P551424 Fuel/Water Separator Cartridge
3.15	80	.90 23	6.05 154	P551427 Fuel/Water Separator Cartridge
3.15	80	.90 23	6.05 154	P551430 Fuel/Water Separator Cartridge
3.15	80	.90 23	6.05 154	P551432 Fuel/Water Separator Cartridge
3.15	80	.90 23	6.05 154	P551434 Fuel/Water Separator Cartridge
3.15	80	.90 23	6.05 154	P551437 Fuel/Water Separator Cartridge
3.15	80	.90 23	7.71 196	P551422 Fuel/Water Separator Cartridge
3.15	80	.90 23	7.71 196	P551425 Fuel/Water Separator Cartridge
3.15	80	.90 23	7.71 196	P551428 Fuel/Water Separator Cartridge
3.15	80	.90 23	7.71 196	P551431 Fuel/Water Separator Cartridge
3.15	80	.90 23	7.71 196	P551433 Fuel/Water Separator Cartridge
3.15	80	.90 23	7.71 196	P551435 Fuel/Water Separator Cartridge
3.19	81	1.06 27	4.53 115	P550201 Fuel Cartridge Secondary
3.25	83	0.63 16	2.44 62	P552010 Fuel/Water Separator Cartridge
3.27	83	2.72 69	4.75 121	P550771 Fuel/Water Separator Cartridge
3.27	83	2.72 69	4.98 126	P550760 Fuel/Water Separator Cartridge
3.27	83	2.73 69	3.48 88	P550666 Fuel/Water Separator Cartridge
3.27	83	2.73 69	4.00 102	P550399 Fuel/Water Separator Cartridge

Fuel Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
3.27	83	2.73 69	4.03 102	P550351 Fuel/Water Separator Cartridge
3.27	83	2.73 69	4.03 102	P550570 Fuel/Water Separator Cartridge
3.27	83	2.73 69	4.75 121	P550401 Fuel/Water Separator Cartridge
3.27	83	2.73 69	4.75 121	P550434 Fuel/Water Separator Cartridge
3.27	83	2.73 69	4.75 121	P550502 Fuel/Water Separator Cartridge
3.27	83	2.73 69	4.75 121	P550503 Fuel/Water Separator Cartridge
3.27	83	2.73 69	4.75 121	P550772 Fuel/Water Separator Cartridge
3.27	83	2.73 69	4.98 126	P550759 Fuel/Water Separator Cartridge
3.27	83	2.73 69	5.02 128	P550397 Fuel/Water Separator Cartridge
3.27	83	2.73 69	5.02 128	P550398 Fuel/Water Separator Cartridge
3.27	83	2.73 69	5.23 133	P550352 Fuel/Water Separator Cartridge
3.27	83	2.73 69	5.50 140	P550506 Fuel/Water Separator Cartridge
3.27	83	2.73 69	6.04 153	P551723 Fuel/Water Separator Cartridge
3.27	83	2.73 69	6.41 163	P550435 Fuel/Water Separator Cartridge
3.27	83	2.73 69	6.41 163	P550773 Fuel/Water Separator Cartridge
3.27	83	2.73 69	6.65 169	P550667 Fuel/Water Separator Cartridge
3.27	83	2.73 69	6.65 169	P550754 Fuel/Water Separator Cartridge
3.27	83	2.73 69	6.65 169	P550756 Fuel/Water Separator Cartridge
3.28	83		5.54 141	P550824 Fuel Cartridge
3.28	83	0.35 9	3.00 76	P550973 Fuel Cartridge
3.30	84	0.47 12	5.50 140	P550861 Fuel Cartridge
3.30	84	0.47 12	5.53 140	P550349 Fuel Cartridge
3.30	84	0.53 13	5.30 135	P550061 Fuel Cartridge
3.33	84	0.58 15	2.88 73	P552470 Fuel Cartridge
3.34	85	0.75 19	2.80 71	P502420 Fuel Cartridge
3.35	85	1.50 38	7.11 180	P550628 Fuel Cartridge
3.36	85	0.52 13	5.70 145	P550489 Fuel Cartridge
3.37	86	0.75 19	4.12 105	P551748 Fuel Cartridge
3.37	86	1.12 28	6.50 165	P558792 Fuel Cartridge
3.38	86	0.81 21	4.94 125	P550430 Fuel/Water Separator Cartridge
3.39	86	0.83 21	4.09 104	P550785 Fuel/Water Separator Cartridge
3.40	86	1.10 28	3.27 83	P553261 Fuel Cartridge Secondary
3.41	87	0.74 19	2.80 71	P556245 Fuel Cartridge
3.41	87	0.82 21	4.10 104	P550800 Fuel/Water Separator Cartridge
3.44	87	0.75 19	3.41 87	P502169 Fuel Cartridge
3.45	88	0.66 17	4.44 113	P550460 Fuel Cartridge
3.46	88	1.53 39	4.45 113	P556287 Fuel Cartridge
3.48	88	1.32 34	4.80 122	P550501 Fuel Cartridge
3.50	89	0.63 16	6.42 163	P550366 Fuel/Water Separator Cartridge
3.50	89	0.74 19	5.28 134	P550394 Fuel Cartridge
3.50	89	0.75 19	2.76 70	P551168 Fuel Cartridge
3.50	89	0.75 19	2.80 71	P557111 Fuel Cartridge
3.50	89	1.81 46	8.62 219	P785770 Fuel Cartridge
3.53	90	0.57 14	5.31 135	P550040 Fuel Cartridge
3.54	90		6.22 158	P550908 Fuel/Water Separator Cartridge
3.54	90	0.57 14	5.52 140	P550044 Fuel Cartridge
3.54	90	0.74 19	4.33 110	P502425 Fuel Cartridge
3.56	90	0.56 14	3.99 101	P550966 Fuel/Water Separator Cartridge
3.58	91		3.94 100	P550808 Fuel Cartridge
3.58	91	0.59 15	5.43 138	P502116 Fuel Cartridge
3.58	91	0.75 19	5.13 131	P502391 Fuel Cartridge
3.60	91	0.59 15	6.38 162	P551338 Fuel Cartridge
3.61	92	0.59 15	5.28 134	P550055 Fuel Cartridge
3.62	92	0.59 15	4.33 110	P550054 Fuel Cartridge
3.62	92	0.59 15	5.31 135	P550023 Fuel Cartridge

Specs By Part Type

Fuel Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
3.62 92	0.73 19	5.51 140	P502114	Fuel Cartridge
3.62 92	1.06 27	3.98 101	P550632	Fuel Cartridge
3.70 94	0.86 22	5.11 130	P502371	Fuel Cartridge
3.70 94	0.98 25	7.19 183	P550347	Fuel Cartridge
3.70 94	1.02 26	3.34 85	P502378	Fuel Cartridge
3.70 94	1.02 26	5.11 130	P502377	Fuel Cartridge
3.74 95	0.55 14	7.97 202	P550762	Fuel Cartridge
3.74 95	0.82 21	5.59 142	P550657	Fuel/Water Separator Cartridge
3.74 95	1.07 27	3.72 95	P502226	Fuel Cartridge
3.74 95	1.07 27	7.44 189	P502426	Fuel/Water Separator Cartridge
3.74 95	1.77 45	5.67 144	P550821	Fuel Cartridge
3.74 95	1.81 46	6.79 173	P785373	Fuel Cartridge
3.81 97	0.50 13	2.85 72	P550437	Fuel Cartridge
3.81 97	0.66 17	7.03 179	P550796	Fuel/Water Separator Cartridge
3.82 97	0.66 17	6.74 171	P550463	Fuel/Water Separator Cartridge
3.82 97	0.66 17	6.74 171	P550467	Fuel/Water Separator Cartridge
3.82 97	0.66 17	7.00 178	P550736	Fuel/Water Separator Cartridge
3.82 97	0.66 17	7.00 178	P550737	Fuel/Water Separator Cartridge
3.82 97	0.66 17	7.00 178	P550757	Fuel/Water Separator Cartridge
3.86 98	0.87 22	6.35 161	P502132	Fuel Cartridge
3.90 99	1.61 41	9.23 234	P551317	Fuel Cartridge
3.93 100	0.46 12	3.77 96	P502427	Fuel Cartridge
3.93 100	1.62 41	9.25 235	P559850	Fuel Cartridge
3.97 101	0.54 14	5.00 127	P551164	Fuel Cartridge
3.98 101	0.77 19	4.78 121	P552473	Fuel Cartridge
4.00 102	0.57 14	6.32 161	P550042	Fuel Cartridge
4.00 102	1.12 28	8.75 222	P550541	Fuel Cartridge Sock
4.09 104	0.59 15	4.09 104	P550392	Fuel Cartridge
4.11 104	1.14 29	4.35 111	P502414	Fuel Cartridge
4.13 105	1.81 46	8.06 205	P550631	Fuel Cartridge
4.21 107	.66 17	7.00 178	P550849	Fuel/Water Separator Cartridge
4.21 107	.66 17	7.00 178	P550851	Fuel/Water Separator Cartridge
4.21 107	.66 17	7.00 178	P550853	Fuel/Water Separator Cartridge
4.21 107	0.66 17	6.74 171	P550510	Fuel/Water Separator Cartridge
4.21 107	0.66 17	7.00 178	P550852	Fuel/Water Separator Cartridge
4.23 107	0.75 19	4.34 110	P551310	Fuel/Water Separator Cartridge
4.25 108	0.78 20	6.73 171	P502131	Fuel Cartridge
4.25 108	0.83 21	6.46 164	P502383	Fuel Cartridge
4.28 109	0.81 21	4.63 118	P552040	Fuel/Water Separator Cartridge
4.28 109	0.81 21	9.63 245	P552020	Fuel/Water Separator Cartridge
4.31 109	0.65 17	6.47 164	P550447	Fuel/Water Separator Cartridge
4.33 110	1.02 26	7.91 201	P551337	Fuel Cartridge
4.33 110	2.04 52		P502356	Fuel Cartridge
4.37 111	0.59 15	5.51 140	P550028	Fuel Cartridge
4.37 111	3.75 95	5.25 133	P564393	Fuel/Water Separator Cartridge
4.37 111	3.75 95	9.25 235	P564278	Fuel/Water Separator Cartridge
4.37 111	3.75 95	9.25 235	P564392	Fuel/Water Separator Cartridge
4.37 111	3.75 95	9.25 235	P564430	Fuel/Water Separator Cartridge
4.52 115	0.69 18	8.10 206	P551624	Fuel Cartridge Secondary
4.62 117	6.47 164	0.65 17	P550752	Fuel/Water Separator Cartridge
4.64 118	0.87 22	8.39 213	P550125	Fuel Cartridge
4.81 122	1.12 28	9.13 232	P550547	Fuel/Water Separator Cartridge
4.81 122	1.12 28	9.13 232	P550607	Fuel/Water Separator Cartridge
5.00 127	0.97 25	9.75 248	P558600	Fuel Cartridge
5.50 140	2.46 62	10.00 254	P550032	Fuel Cartridge Sock

Fuel Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
5.81 148	1.00 25	9.37 238	P550043	Fuel Cartridge
5.83 148	0.98 25	8.07 205	P550316	Fuel/Water Separator Cartridge
5.83 148	1.02 26	8.00 203	P550854	Fuel/Water Separator Cartridge
6.09 155	2.63 67	17.85 454	P502411	Fuel Cartridge
6.09 155	2.63 67	17.85 454	P502412	Fuel Cartridge

Fuel In-line

Outer Diameter IN MM	Inlet Size	Overall Length IN MM	PART NUMBER	PART DESCRIPTION
0.78 20	5/16	2.17 55	P550593	Fuel In-Line
0.94 24	5/16	2.87 73	P550454	Fuel In-Line
1.06 27	5/16	2.86 73	P550091	Fuel In-Line
1.33 34	5/16	2.71 69	P550016	Fuel In-Line
1.88 48	1/2	4.34 110	P551770	Fuel In-Line
1.94 49	1/4	4.06 103	P550094	Fuel In-Line
1.94 49	3/8	3.88 99	P550090	Fuel In-Line
1.94 49	3/8	3.88 99	P550433	Fuel In-Line
1.94 49	3/8	3.93 100	P550974	Fuel In-Line
1.94 49	5/16	4.17 106	P550012	Fuel In-Line
1.94 49	9/16-18	3.65 93	P552482	Fuel In-Line
2.00 51	1/2	4.35 110	P551771	Fuel In-Line
2.00 51	1/8-27	3.38 86	P550457	Fuel In-Line
2.00 51	5/8-24	3.54 90	P550446	Fuel In-Line
2.05 52	5/16	2.11 53	P552399	Fuel In-Line
2.07 53	5/16	2.82 72	P552401	Fuel In-Line
2.15 55	5/16	6.22 158	P552439	Fuel In-Line
2.16 55	3/8	6.37 162	P551759	Fuel In-Line
2.17 55	3/8	5.47 137	P552371	Fuel In-Line
2.17 55	M16 x 1.5	4.29 109	P550209	Fuel In-Line

Outer Diameter IN MM	Thread Size	Overall Length IN MM	PART NUMBER	PART DESCRIPTION
2.17 55	M16 x 1.5	4.75 121	P552391	Fuel In-Line

Outer Diameter IN MM	Inlet Size	Length IN MM	PART NUMBER	PART DESCRIPTION
2.18 55	5/16	4.74 120	P552403	Fuel In-Line

Outer Diameter IN MM	Height IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
2.22 56	2.40 61	1.97 50	P550404	Fuel In-Line

Outer Diameter IN MM	Inlet Size	Overall Length IN MM	PART NUMBER	PART DESCRIPTION
2.22 56	3/8	7.00 178	P550556	Fuel In-Line
2.28 58	3/8	6.37 162	P552448	Fuel In-Line
2.28 58	3/8	6.38 162	P550504	Fuel In-Line
2.28 58	3/8	6.47 164	P552397	Fuel In-Line
2.28 58	5/8-18	4.75 121	P552366	Fuel In-Line
2.28 58	M16 x 1.5	5.35 136	P550508	Fuel In-Line
2.30 58	5/16	7.00 178	P551772	Fuel In-Line
2.32 59	5/16	5.47 139	P551760	Fuel In-Line

Fuel In-line - continued

Outer Diameter IN MM	Height IN MM	PART NUMBER	PART DESCRIPTION	
2.36 60	3.81 97	P502329	Fuel In-Line	
Outer Diameter IN MM	Inlet Size	Overall Length IN MM	PART NUMBER	PART DESCRIPTION
2.50 64	5/16	5.00 127	P552437	Fuel In-Line
Outer Diameter IN MM	Inlet Size	Length IN MM	PART NUMBER	PART DESCRIPTION
2.80 71	M12 x 1.25	5.04 128	P552400	Fuel In-Line
Outer Diameter IN MM	Inlet Size	Overall Length IN MM	PART NUMBER	PART DESCRIPTION
2.80 71	M14 x 1.5	4.37 111	P552398	Fuel In-Line
2.97 75	5/16	5.82 148	P550126	Fuel In-Line
3.07 78	3/8	6.06 154	P552376	Fuel In-Line
3.08 78	5/16	6.77 172	P550967	Fuel In-Line
Outer Diameter IN MM	Outlet Size	Inlet Size	PART NUMBER	PART DESCRIPTION
3.14 80	SAE 5/16	SAE 3/8	P765325	Fuel In-Line
Outer Diameter IN MM	Inlet Size	Overall Length IN MM	PART NUMBER	PART DESCRIPTION
3.19 81	5/16	6.26 159	P552392	Fuel In-Line
3.41 87	5/16	6.61 168	P552440	Fuel In-Line
3.46 88	M14 x 1.5	5.86 149	P552442	Fuel In-Line
Outer Diameter IN MM	Inlet Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
3.59 91	0.44 11	4.78 121	P550780	Fuel In-Line
Outer Diameter IN MM	Inlet Size	Overall Length IN MM	PART NUMBER	PART DESCRIPTION
4.05 103	9/32	2.31 59	P552394	Fuel In-Line

Fuel Spin-on

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
2.62 67	1-14	4.34 110	P551751	Fuel/Water Separator Spin-on
2.99 76	M14 x 1.5	4.72 120	P550526	Fuel/Water Separator Spin-on
2.99 76	M16 x 1.5	4.72 120	P553004	Fuel Spin-on
2.99 76	M16 x 1.5	5.12 130	P550440	Fuel Spin-on Secondary
2.99 76	M16 x 1.5	5.71 145	P550248	Fuel/Water Separator Spin-on
3.00 76	M16 x 1.5	6.50 165	P550587	Fuel/Water Separator Spin-on
3.00 76	M18 x 1.5	2.40 62	P551768	Fuel/Water Separator Spin-on
3.00 76	M20 x 1.5	3.40 86	P550127	Fuel/Water Separator Spin-on
3.01 76	3/4-16	3.46 88	P553240	Fuel/Water Separator Spin-on
3.01 77	3/4-16	5.31 135	P502418	Fuel Spin-on
3.01 76	3/4-16	5.75 146	P550410	Fuel/Water Separator Spin-on
3.01 76	M16 x 1.5	3.46 88	P555095	Fuel/Water Separator Spin-on
3.02 77	M16 x 1.5	3.37 86	P552374	Fuel/Water Separator Spin-on
3.02 77	M16 x 1.5	3.79 96	P551039	Fuel/Water Separator Spin-on
3.02 77	M16 x 1.5	5.55 141	P550588	Fuel/Water Separator Spin-on
3.03 77	7/16-20	4.87 124	P550325	Fuel/Water Separator Spin-on
3.03 77	M16 x 1.5	2.49 63	P550678	Fuel/Water Separator Spin-on

Fuel Spin-on - continued

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
3.03 77	M16 x 1.5	3.15 80	P550345	Fuel/Water Separator Spin-on
3.03 77	M16 x 1.5	4.40 112	P550690	Fuel/Water Separator Spin-on
3.03 77	M16 x 1.5	4.51 115	P550249	Fuel/Water Separator Spin-on
3.03 77	M16 x 1.5	4.87 124	P550943	Fuel Spin-on Secondary
3.05 77	7/8-14	5.83 148	P550368	Fuel/Water Separator Spin-on
3.06 78	M16 x 1.5	6.74 171	P550688	Fuel/Water Separator Spin-on
3.07 78	M14 x 1.5	5.03 128	P553287	Fuel/Water Separator Spin-on
3.11 79	3/4-16	5.59 142	P550550	Fuel/Water Separator Spin-on
3.14 80	M16 x 1.5	4.88 124	P550491	Fuel/Water Separator Spin-on
3.14 80	M20 x 1.5	2.95 75	P502386	Fuel/Water Separator Spin-on
3.15 80	3/4-16	3.31 84	P502177	Fuel/Water Separator Spin-on
3.15 80	3/4-16	4.50 114	P502163	Fuel/Water Separator Spin-on
3.15 80	3/4-16	6.89 175	P502167	Fuel/Water Separator Spin-on
3.15 80	7/8-14	6.93 176	P551315	Fuel Spin-on
3.15 80	M16 x 1.5	5.74 146	P550498	Fuel/Water Separator Spin-on
3.15 80	M20 x 1.5	3.93 100	P502143	Fuel/Water Separator Spin-on
3.16 80	M20 x 1.5	4.72 120	P502142	Fuel/Water Separator Spin-on
3.18 81	M16 x 1.5	6.93 176	P550782	Fuel/Water Separator Spin-on
3.18 81	M16 x 1.5	6.93 176	P550783	Fuel/Water Separator Spin-on
3.24 82	3/4-16	3.20 81	P5505951	Fuel/Water Separator Spin-on
3.30 84	3/4-16	3.39 86	P550057	Fuel/Water Separator Spin-on
3.31 84	3/4-16	3.94 100	P550225	Fuel Spin-on Secondary
3.31 84	M16 x 1.5	3.89 99	P550081	Fuel/Water Separator Spin-on
3.34 85	1-14	7.09 180	P551740	Fuel/Water Separator Spin-on
3.50 89	M12 x 1.5	8.16 207	P550473	Fuel/Water Separator Spin-on
3.58 91	M72 x 2	9.00 228	P552200	Fuel Spin-on Secondary
3.62 91	M92 x 2.5	6.10 155	P566310	Fuel Spin-on
3.66 93	1" - 14	6.86 174	P502367	Fuel/Water Separator Spin-on
3.66 93	1-12	5.35 136	P550936	Fuel/Water Separator Spin-on
3.66 93	1-12	5.72 146	P502404	Fuel/Water Separator Spin-on
3.66 93	1-12	6.85 174	P554347	Fuel/Water Separator Spin-on
3.66 93	1-12	8.64 219	P553202	Fuel/Water Separator Spin-on
3.66 93	1-12	8.64 219	P553212	Fuel/Water Separator Spin-on
3.66 93	1-14	5.35 136	P550105	Fuel/Water Separator Spin-on
3.66 93	1-14	5.35 136	P552251	Fuel Spin-on
3.66 93	1-14	6.09 155	P550569	Fuel/Water Separator Spin-on
3.66 93	1-14	6.11 155	P550828	Fuel/Water Separator Spin-on
3.66 93	1-14	6.85 174	P502384	Fuel/Water Separator Spin-on
3.66 93	1-14	6.85 174	P553854	Fuel/Water Separator Spin-on
3.66 93	1-14	6.85 174	P557440	Fuel Spin-on
3.66 93	1-14	7.37 187	P550847	Fuel/Water Separator Spin-on
3.66 93	1-14	7.40 188	P558000	Fuel/Water Separator Spin-on
3.66 93	1-14	7.61 193	P553203	Fuel/Water Separator Spin-on
3.66 93	1-14	7.61 193	P553213	Fuel/Water Separator Spin-on
3.66 93	1-14	7.61 193	P553215	Fuel/Water Separator Spin-on
3.66 93	1-14	7.62 194	P553205	Fuel/Water Separator Spin-on
3.66 93	1-14	7.87 200	P555627	Fuel/Water Separator Spin-on
3.66 93	1-14	8.40 213	P550848	Fuel/Water Separator Spin-on
3.66 93	1-14	8.40 213	P552565	Fuel/Water Separator Spin-on
3.66 93	1-14	8.64 219	P553201	Fuel/Water Separator Spin-on
3.66 93	1-14	8.64 219	P553204	Fuel/Water Separator Spin-on
3.66 93	1-14	8.64 219	P553207	Fuel/Water Separator Spin-on
3.66 93	1-14	8.64 219	P553211	Fuel/Water Separator Spin-on
3.66 93	1-14	8.64 219	P553214	Fuel/Water Separator Spin-on
3.66 93	1-14	8.64 219	P553217	Fuel/Water Separator Spin-on

Fuel Spin-on - continued

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
3.66	93	1-14	9.01 229	P551122 Fuel/Water Separator Spin-on
3.66	93	1-14	9.22 234	P552032 Fuel/Water Separator Spin-on
3.66	93	1-14	9.40 239	P551103 Fuel/Water Separator Spin-on
3.66	93	1-14	9.70 246	P551000 Fuel/Water Separator Spin-on
3.66	93	1-14	9.71 247	P550901 Fuel/Water Separator Spin-on
3.66	93	13/16-12	4.21 107	P550928 Fuel Spin-on Secondary
3.66	93	13/16-12	6.85 174	EFF7917 Fuel Spin-on Secondary
3.66	93	13/16-12	6.85 174	P556916 Fuel Spin-on Secondary
3.66	93	13/16-12	6.85 174	P556917 Fuel Spin-on Secondary
3.66	93	13/16-18	5.67 144	P558712 Fuel/Water Separator Spin-on
3.66	93	13/16-18	5.85 149	P551329 Fuel/Water Separator Spin-on
3.66	93	15/16-16	5.55 141	P559100 Fuel/Water Separator Spin-on
3.66	93	3/4-16	5.19 132	P552405 Fuel/Water Separator Spin-on
3.66	93	7/8-14	6.85 174	P550774 Fuel Spin-on
3.66	93	7/8-14	6.89 175	P550879 Fuel Spin-on
3.66	93	M20 X 1.5	6.85 174	P550880 Fuel Spin-on
3.66	93	M20 X 1.5	6.85 174	P550881 Fuel Spin-on
3.66	93	M20 x 1.5	7.37 187	P502421 Fuel/Water Separator Spin-on
3.66	93	M20 X 1.5	7.96 202	P550929 Fuel/Water Separator Spin-on
3.66	93	M24 x 1.5	6.77 172	P550391 Fuel/Water Separator Spin-on
3.67	93	1 3/8-12	7.50 190	P551752 Fuel/Water Separator Spin-on
3.67	93	1-14	6.95 177	P169096 Fuel/Water Separator Spin-on
3.67	93	13/16-12	6.89 175	P169091 Fuel Spin-on Secondary
3.68	93	1-14	6.85 174	P551178 Fuel/Water Separator Spin-on
3.68	93	1-14	6.95 177	P551313 Fuel Spin-on Secondary
3.68	93	1-14	7.98 203	P551001 Fuel/Water Separator Spin-on
3.68	93	1-14	8.63 219	P550659 Fuel/Water Separator Spin-on
3.68	93	1-14	9.43 240	P551311 Fuel Spin-on
3.68	93	7/8-14	9.43 240	P551312 Fuel/Water Separator Spin-on
3.68	94	M16 x 1.5	4.25 108	P550662 Fuel/Water Separator Spin-on
3.68	93	M20 x 1.5	3.94 100	P550049 Fuel/Water Separator Spin-on
3.68	93	M20 x 1.5	6.30 93	P550643 Fuel/Water Separator Spin-on
3.69	94	1-12	5.37 136	P550115 Fuel/Water Separator Spin-on
3.69	94	1-12	5.37 136	P550215 Fuel/Water Separator Spin-on
3.69	94	1-12	7.44 189	P551915 Fuel Spin-on
3.69	94	1-14	5.52 140	P551744 Fuel/Water Separator Spin-on
3.69	94	1-14	5.68 144	P550108 Fuel/Water Separator Spin-on
3.69	94	1-14	5.85 149	P550691 Fuel/Water Separator Spin-on
3.69	94	1-14	8.69 221	P552253 Fuel Spin-on Secondary
3.69	94	1-14	9.38 238	P551022 Fuel/Water Separator Spin-on
3.69	94	1-14	9.71 247	P551003 Fuel/Water Separator Spin-on
3.69	94	M20 x 1.5	5.75 146	P550549 Fuel/Water Separator Spin-on
3.69	93	M20 X 1.5	7.56 192	P550899 Fuel/Water Separator Spin-on
3.69	94	M20 x 1.5	7.58 193	P550660 Fuel/Water Separator Spin-on
3.69	93	M22 X 1.5	4.98 126	P550834 Fuel/Water Separator Spin-on
3.69	94	M22 x 1.5	6.42 163	P550733 Fuel/Water Separator Spin-on
3.70	94	1-14	10.75 273	P550625 Fuel/Water Separator Spin-on
3.70	94	15/16-16	8.42 214	P552432 Fuel/Water Separator Spin-on
3.70	94	3/4-16	5.43 138	P550385 Fuel/Water Separator Spin-on
3.70	94	M20 x 1.5	4.72 120	P552561 Fuel/Water Separator Spin-on
3.70	94	M24 x 1.5	5.59 142	P550515 Fuel/Water Separator Spin-on
3.71	94	3/4-16	4.92 125	P552564 Fuel/Water Separator Spin-on
3.71	94	M18 x 1.5	8.13 207	P550372 Fuel Spin-on
3.72	94		3.79 96	P505981 Fuel/Water Separator Spin-on
3.72	95	1-14	5.78 147	P552203 Fuel/Water Separator Spin-on

Fuel Spin-on - continued

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
3.72	95	1-14	9.43 240	P551712 Fuel/Water Separator Spin-on
3.72	95	M20 x 1.5	4.72 120	P502157 Fuel/Water Separator Spin-on
3.72	95	M20 x 1.5	5.17 131	P502158 Fuel/Water Separator Spin-on
3.73	95	1-14	5.69 145	P550683 Fuel/Water Separator Spin-on
3.74	95	M20 x 1.5	3.15 80	P550048 Fuel/Water Separator Spin-on
3.75	95	1-14	4.12 105	P550088 Fuel/Water Separator Spin-on
3.77	96	M16 x 1.5	5.66 144	P550494 Fuel/Water Separator Spin-on
3.77	96	M16 x 1.5	8.34 211	P550472 Fuel/Water Separator Spin-on
3.77	96	M24 x 1.5	5.66 144	P550495 Fuel Spin-on
3.78	96	1 1/2-16	7.35 187	P550735 Fuel/Water Separator Spin-on
3.78	96	7/8-14	8.70 221	P553855 Fuel Spin-on Secondary
3.78	96	M16 x 1.5	5.66 144	P550496 Fuel/Water Separator Spin-on
3.78	96	M18 x 1.5	5.59 142	P550004 Fuel/Water Separator Spin-on
3.78	96	M20 x 1.5	4.65 118	P550968 Fuel/Water Separator Spin-on
3.78	96	M24 x 1.5	7.00 178	P550365 Fuel/Water Separator Spin-on
3.79	96		5.59 142	P505982 Fuel/Water Separator Spin-on
3.79	96	1-14	6.22 158	P550553 Fuel/Water Separator Spin-on
3.80	97	11/16-16	4.16 106	P550677 Fuel/Water Separator Spin-on
3.81	97	1-12	4.25 108	P550089 Fuel/Water Separator Spin-on
3.81	97	1-12	6.08 154	P550944 Fuel/Water Separator Spin-on
3.81	97	1-12	7.36 187	P558010 Fuel/Water Separator Spin-on
3.81	97	1-12	7.40 188	P555020 Fuel/Water Separator Spin-on
3.81	97	1-12	7.97 202	P556915 Fuel/Water Separator Spin-on
3.81	97	1-12	9.94 252	P555002 Fuel/Water Separator Spin-on
3.81	97	1-14	4.22 107	P550104 Fuel/Water Separator Spin-on
3.81	97	1-14	5.70 145	P550109 Fuel/Water Separator Spin-on
3.81	97	1-14	7.40 188	P550106 Fuel/Water Separator Spin-on
3.81	97	1-14	7.40 188	P555010 Fuel/Water Separator Spin-on
3.81	97	1-14	8.06 205	P555003 Fuel/Water Separator Spin-on
3.81	97	1-14	9.94 252	P555001 Fuel/Water Separator Spin-on
3.81	97	13/16-18	4.50 114	P550868 Fuel/Water Separator Spin-on
3.81	97	15/16-16	4.75 121	P550110 Fuel Spin-on Secondary
3.81	97	15/16-16	5.61 142	P551127 Fuel Spin-on Secondary
3.81	97	7/8-14	5.22 133	P553693 Fuel Spin-on Secondary
3.82	97	M14 x 1.5	7.60 193	P550665 Fuel/Water Separator Spin-on
3.82	97	M16 x 1.5	5.47 139	P554620 Fuel/Water Separator Spin-on
3.82	97	M16 x 1.5	8.27 210	P559624 Fuel/Water Separator Spin-on
3.82	97	M92 x 2.5	6.10 155	P566311 Fuel Spin-on
3.82	97	M92 x 2.5	6.88 174	P566312 Fuel/Water Separator Spin-on
3.85	98	3/4-16	5.47 139	P551351 Fuel/Water Separator Spin-on
3.86	98	M20 X 1.5	5.46 139	P505960 Fuel/Water Separator Spin-on
3.90	99	M20 x 1.5	5.43 138	P502149 Fuel/Water Separator Spin-on
3.90	99	M20 x 1.5	5.43 138	P550390 Fuel/Water Separator Spin-on
4.02	102	3 3/8-8	5.60 142	P550743 Fuel/Water Separator Spin-on
4.02	102	3 3/8-8	6.39 162	P550833 Fuel/Water Separator Spin-on
4.21	107	1 1/8-16	7.88 200	P502233 Fuel/Water Separator Spin-on
4.22	107	7/8-14	5.84 148	P551773 Fuel Spin-on Secondary
4.23	107	M30 x 1.5	7.95 202	P554476 Fuel Spin-on Secondary
4.24	108	1-12	8.90 226	P551774 Fuel/Water Separator Spin-on
4.24	108	1-12	10.38 264	P550753 Fuel/Water Separator Spin-on
4.24	108	7/8 - 14	4.62 118	P502355 Fuel/Water Separator Spin-on
4.24	108	7/8-14	6.74 171	P550669 Fuel/Water Separator Spin-on
4.24	108	7/8-14	7.14 181	P551318 Fuel Spin-on
4.25	108		11.34 288	P925683 Fuel/Water Separator Spin-on
4.25	108	1-12	10.85 276	P551360 Fuel/Water Separator Spin-on

Hydraulic Cartridge - continued

Outer Diameter IN MM	Inner Diameter MM	Length IN MM	PART NUMBER	PART DESCRIPTION
1.69	43	0.89 23	3.54 90	P171702 Hydraulic Cartridge
1.69	43	0.89 23	3.54 90	P171703 Hydraulic Cartridge
1.73	44	0.87 22	3.54 90	P171706 Hydraulic Cartridge
1.73	44	0.91 23	7.99 203	P764660 Hydraulic Cartridge
1.73	44	1.02 26	1.97 50	P561243 Hydraulic Cartridge
1.75	44	1.00 25	4.44 113	P167180 Hydraulic Cartridge
1.75	44	1.00 25	4.44 113	P167181 Hydraulic Cartridge
1.75	44	1.00 25	8.12 206	P167182 Hydraulic Cartridge
1.75	44	1.00 25	8.12 206	P167183 Hydraulic Cartridge
1.77	45	0.95 24	3.27 83	P561323 Hydraulic Cartridge
1.77	45	0.95 24	3.27 83	P561326 Hydraulic Cartridge
1.77	45	0.95 24	3.86 98	P561327 Hydraulic Cartridge
1.77	45	0.95 24	3.86 98	P561328 Hydraulic Cartridge
1.77	45	0.95 24	3.86 98	P561330 Hydraulic Cartridge
1.77	45	0.95 24	6.18 157	P561337 Hydraulic Cartridge
1.77	45	0.95 24	6.18 157	P561338 Hydraulic Cartridge
1.77	45	0.95 24	6.18 157	P561339 Hydraulic Cartridge
1.77	45	0.95 24	6.22 158	P561336 Hydraulic Cartridge
1.77	45	0.96 25	3.27 83	P561324 Hydraulic Cartridge
1.77	45	1.00 25	4.31 109	P165006 Hydraulic Cartridge
1.77	45	1.00 25	4.31 109	P165041 Hydraulic Cartridge
1.77	45	1.00 25	4.31 109	P165136 Hydraulic Cartridge
1.77	45	1.00 25	4.31 109	P169429 Hydraulic Cartridge
1.77	45	1.00 25	7.94 202	P165015 Hydraulic Cartridge
1.77	45	1.00 25	7.94 202	P165043 Hydraulic Cartridge
1.77	45	1.00 25	7.94 202	P165138 Hydraulic Cartridge
1.77	45	1.00 25	7.94 202	P167838 Hydraulic Cartridge
1.81	46	0.70 18	5.98 152	P760327 Hydraulic Cartridge
1.81	46	0.72 18	2.05 52	P561418 Hydraulic Cartridge
1.81	46	0.72 18	2.05 52	P562025 Hydraulic Cartridge
1.81	46	0.72 18	3.23 82	P565930 Hydraulic Cartridge
1.81	46	0.80 20	4.05 103	P175101 Hydraulic Cartridge
1.81	46	0.80 20	7.87 200	P175104 Hydraulic Cartridge
1.81	46	0.87 22	7.60 193	P760943 Hydraulic Cartridge
1.81	46	1.02 26	3.43 87	P171713 Hydraulic Cartridge
1.81	46	1.02 26	3.43 87	P171714 Hydraulic Cartridge
1.81	46	1.02 26	3.43 87	P171715 Hydraulic Cartridge
1.85	47	0.87 22	3.31 84	P170586 Hydraulic Cartridge
1.85	47	0.87 22	3.31 84	P170587 Hydraulic Cartridge
1.85	47	0.87 22	3.31 84	P170600 Hydraulic Cartridge
1.85	47	0.87 22	3.31 84	P170601 Hydraulic Cartridge
1.85	47	0.87 22	6.02 153	P170602 Hydraulic Cartridge
1.85	47	0.87 22	6.02 153	P170604 Hydraulic Cartridge
1.85	47	0.87 22	6.02 153	P177001 Hydraulic Cartridge
1.85	47	0.87 22	6.06 154	P170588 Hydraulic Cartridge
1.85	47	0.87 22	6.06 154	P170589 Hydraulic Cartridge
1.88	48	0.87 22	3.27 83	P173190 Hydraulic Cartridge
1.88	48	0.87 22	3.31 84	P173189 Hydraulic Cartridge
1.88	48	0.87 22	6.02 153	P173191 Hydraulic Cartridge
1.88	48	0.87 22	6.02 153	P173192 Hydraulic Cartridge

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
1.92	49	3/4 NPT	5.87 149	P763889 Hydraulic Cartridge

Hydraulic Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
1.97	50	0.94 24	4.45 113	P169445 Hydraulic Cartridge
1.97	50	0.94 24	4.45 113	P176947 Hydraulic Cartridge
1.97	50	0.94 24	4.45 113	P761387 Hydraulic Cartridge
1.97	50	0.94 24	6.22 158	P762860 Hydraulic Cartridge
1.97	50	0.96 24	4.31 109	P169447 Hydraulic Cartridge
1.97	50	1.02 26/29	2.76 70	P171644 Hydraulic Cartridge
1.97	50	1.97 50	11.02 280	P763187 Hydraulic Cartridge
1.97	50	2.50 64	11.02 280	P173476 Hydraulic Cartridge
1.99	51	0.94 24	12.91 328	P169453 Hydraulic Cartridge
1.99	51	0.96 24	4.31 109	P169446 Hydraulic Cartridge
1.99	51	0.96 24	4.31 109	P169797 Hydraulic Cartridge
1.99	51	0.96 24	7.94 202	P169448 Hydraulic Cartridge
1.99	51	0.96 24	7.94 202	P169449 Hydraulic Cartridge
1.99	51	0.96 24	7.94 202	P169450 Hydraulic Cartridge
1.99	51	0.96 24	7.94 202	P169798 Hydraulic Cartridge
1.99	51	0.96 24	12.93 328	P169452 Hydraulic Cartridge
2.00	51	0.94 24	4.56 116	P167270 Hydraulic Cartridge
2.00	51	0.94 24	4.56 116	P167413 Hydraulic Cartridge
2.00	51	0.94 24	8.23 209	P167414 Hydraulic Cartridge
2.00	51	0.94 24	8.23 209	P167415 Hydraulic Cartridge
2.00	51	0.94 24	12.87 327	P167417 Hydraulic Cartridge
2.01	51	0.91 23	2.95 75	P551347 Hydraulic Cartridge
2.01	51	0.91 23	5.73 146	P173238 Hydraulic Cartridge
2.03	52	0.87 22	4.06 103	P170613 Hydraulic Cartridge
2.03	52	0.87 22	4.06 103	P173159 Hydraulic Cartridge
2.03	52	0.87 22	6.71 170	P170614 Hydraulic Cartridge
2.03	52	0.87 22	6.73 171	P173162 Hydraulic Cartridge
2.03	52	0.89 22	5.56 141	P552408 Hydraulic Cartridge
2.03	52	0.94 24	4.06 103	P173158 Hydraulic Cartridge
2.05	52	0.94 24	6.73 171	P173161 Hydraulic Cartridge
2.05	52	1.00 25	2.59 66	P171502 Hydraulic Cartridge
2.05	52	1.00 25	2.60 66	P171503 Hydraulic Cartridge
2.05	52	1.00 25	2.64 67	P171503 Hydraulic Cartridge
2.05	52	1.00 25	2.64 67	P171504 Hydraulic Cartridge
2.05	52	1.02 26	2.64 67	P171500 Hydraulic Cartridge
2.05	52	1.02 26	2.64 67	P171501 Hydraulic Cartridge
2.05	52	1.14 29	2.76 70	P171646 Hydraulic Cartridge
2.09	53	0.96 24	3.70 94	P561459 Hydraulic Cartridge
2.09	53	0.96 24	3.70 94	P561461 Hydraulic Cartridge
2.09	53	0.96 24	3.70 94	P561462 Hydraulic Cartridge
2.09	53	0.96 24	3.70 94	P561463 Hydraulic Cartridge
2.09	53	0.96 24	3.70 94	P561464 Hydraulic Cartridge
2.09	53	0.96 24	3.70 94	P561466 Hydraulic Cartridge
2.09	53	0.96 24	3.70 94	P561468 Hydraulic Cartridge
2.09	53	0.96 24	3.70 94	P561470 Hydraulic Cartridge
2.09	53	0.96 24	5.87 149	P561475 Hydraulic Cartridge
2.09	53	0.96 24	5.87 149	P561480 Hydraulic Cartridge
2.09	53	0.96 24	5.87 149	P561482 Hydraulic Cartridge
2.09	53	0.96 24	5.87 149	P562034 Hydraulic Cartridge
2.09	53	1.30 33	3.62 92	P561271 Hydraulic Cartridge
2.13	54		1.97 50	P171783 Hydraulic Cartridge
2.13	54	0.95 24	6.06 154	P561476 Hydraulic Cartridge
2.13	54	1.06 27	3.43 87	P171732 Hydraulic Cartridge
2.13	54	1.06 27	3.43 87	P171733 Hydraulic Cartridge
2.13	54	1.08 27	4.80 122	P171734 Hydraulic Cartridge

Hydraulic Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
2.13 54	1.08 27	4.80 122	P171735	Hydraulic Cartridge
2.13 54	1.08 27	4.80 122	P171736	Hydraulic Cartridge
2.13 54	1.08 27	9.06 230	P171737	Hydraulic Cartridge
2.13 54	1.08 27	9.06 226	P171738	Hydraulic Cartridge
2.13 54	1.08 27	9.06 230	P171739	Hydraulic Cartridge
2.17 55	1.07 27	12.31 313	P565105	Hydraulic Cartridge
2.18 55	0.77 20	2.62 67	P560705	Hydraulic Cartridge
2.18 55	0.77 20	2.62 67	P560706	Hydraulic Cartridge
2.18 55	0.77 20	4.82 123	P560707	Hydraulic Cartridge
2.18 55	0.77 20	4.82 123	P560708	Hydraulic Cartridge
2.20 56	0.74 19	2.63 67	P763034	Hydraulic Cartridge
2.20 56	0.93 24	6.69 170	P763866	Hydraulic Cartridge
2.20 56	1.00 25	4.02 102	P763960	Hydraulic Cartridge
2.20 56	1.00 25	6.69 170	P564860	Hydraulic Cartridge
2.20 56	1.12 28	2.66 68	P762904	Hydraulic Cartridge
2.20 56	1.27 32	7.00 178	P173008	Hydraulic Cartridge
2.20 56	1.27 32	7.00 178	P173009	Hydraulic Cartridge
2.24 57	0.87 22	2.91 74	P171510	Hydraulic Cartridge
2.24 57	0.87 22	3.74 95	P171516	Hydraulic Cartridge
2.32 59	1.04 26	7.87 200	P173486	Hydraulic Cartridge
2.36 60		8.82 224	P173478	Hydraulic Cartridge
2.36 60	0.71 18	3.94 100	P550309	Hydraulic Cartridge
2.36 60	1.12 28	7.91 201	P175108	Hydraulic Cartridge
2.36 60	1.14 29	7.91 201	P764618	Hydraulic Cartridge
2.36 60	1.35 34	3.94 100	P561201	Hydraulic Cartridge
2.36 60	1.35 34	6.89 175	P561347	Hydraulic Cartridge
2.36 60	1.35 34	6.89 175	P561351	Hydraulic Cartridge
2.36 60	1.35 34	8.46 215	P564859	Hydraulic Cartridge
2.44 62	1.00 25	5.00 127	P164556	Hydraulic Cartridge
2.44 62	1.02 26	5.00 127	P170065	Hydraulic Cartridge
2.44 62	1.02 26	5.00 127	P170066	Hydraulic Cartridge
2.44 62	1.02 26	5.00 127	P170068	Hydraulic Cartridge
2.44 62	1.02 26	5.00 127	P170069	Hydraulic Cartridge
2.44 62	1.02 26	9.25 235	P170073	Hydraulic Cartridge
2.44 62	1.02 26	9.25 235	P170084	Hydraulic Cartridge
2.44 62	1.02 26	9.25 235	P170085	Hydraulic Cartridge
2.44 62	1.53 39	3.69 94	P173579	Hydraulic Cartridge
2.44 62	1.53 39	3.69 94	P173580	Hydraulic Cartridge
2.52 64	1.06 27	3.70 94	P557841	Hydraulic Cartridge
2.52 64	1.10 28	8.98 228	P175111	Hydraulic Cartridge
2.52 64	1.16 29	9.09 231	P175112	Hydraulic Cartridge
2.56 65	1.00 25	10.94 278	P550082	Hydraulic Cartridge
2.56 65	1.07 27	5.62 143	P550085	Hydraulic Cartridge
2.61 66	1.25 32	4.80 122	P550232	Hydraulic Cartridge
2.63 67	1.25 32	7.25 184	P550133	Hydraulic Cartridge
2.64 67	1.00 25	4.33 110	P173211	Hydraulic Cartridge
2.69 68	1.01 26	4.56 116	P171310	Hydraulic Cartridge
2.69 68	1.01 26	4.56 116	P171311	Hydraulic Cartridge
2.69 68	1.01 26	4.56 116	P171312	Hydraulic Cartridge
2.69 68	1.01 26	9.31 236	P171314	Hydraulic Cartridge
2.69 68	1.01 26	9.31 236	P171315	Hydraulic Cartridge
2.69 68	1.01 26	9.31 236	P171316	Hydraulic Cartridge
2.72 69	1.06 27	7.78 198	P552459	Hydraulic Cartridge
2.72 69	1.34 34	4.09 104	P762756	Hydraulic Cartridge
2.72 69	1.34 34	4.53 115	P170590	Hydraulic Cartridge

Hydraulic Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
2.72 69	1.34 34	4.53 115	P170591	Hydraulic Cartridge
2.72 69	1.34 34	4.53 115	P170605	Hydraulic Cartridge
2.72 69	1.34 34	4.53 115	P170606	Hydraulic Cartridge
2.72 69	1.34 34	6.81 173	P177002	Hydraulic Cartridge
2.72 69	1.34 34	6.85 174	P170592	Hydraulic Cartridge
2.72 69	1.34 34	6.85 174	P170593	Hydraulic Cartridge
2.72 69	1.34 34	6.85 174	P170607	Hydraulic Cartridge
2.72 69	1.34 34	6.85 174	P170608	Hydraulic Cartridge
2.72 69	1.34 34	6.85 174	P173196	Hydraulic Cartridge
2.72 69	1.34 34	47.00 127	P765281	Hydraulic Cartridge
2.72 69	1.50 38	5.71 145	P175143	Hydraulic Cartridge
2.73 69	1.68 43	5.56 141	P165112	Hydraulic Cartridge
2.73 69	1.68 43	8.69 221	P171248	Hydraulic Cartridge
2.75 70	0.31 8	3.36 85	P551200	Hydraulic Cartridge
2.75 70	0.98 25	7.87 200	P764554	Hydraulic Cartridge
2.75 70	1.35 34	4.53 115	P173193	Hydraulic Cartridge
2.75 70	1.35 34	4.53 115	P173194	Hydraulic Cartridge
2.75 70	1.35 34	6.81 173	P173195	Hydraulic Cartridge
2.75 70	1.35 34	13.98 355	P560141	Hydraulic Cartridge
2.75 70	1.69 43	2.25 57	P173596	Hydraulic Cartridge
2.75 70	1.69 43	2.25 57	P173597	Hydraulic Cartridge
2.76 70	1.00 25	8.22 209	P173138	Hydraulic Cartridge
2.76 70	1.14 29	2.95 75	P171520	Hydraulic Cartridge
2.76 70	1.14 29	2.95 75	P171522	Hydraulic Cartridge
2.76 70	1.14 29	2.95 75	P171523	Hydraulic Cartridge
2.76 70	1.14 29	3.23 82	P171524	Hydraulic Cartridge
2.76 70	1.14 29	3.23 82	P171525	Hydraulic Cartridge
2.76 70	1.14 29	3.23 82	P171526	Hydraulic Cartridge
2.76 70	1.14 29	3.23 82	P171527	Hydraulic Cartridge
2.76 70	1.14 29	3.23 82	P171528	Hydraulic Cartridge
2.76 70	1.14 29	3.23 82	P171529	Hydraulic Cartridge
2.76 70	1.14 29	5.04 128	P171530	Hydraulic Cartridge
2.76 70	1.14 29	5.04 128	P171531	Hydraulic Cartridge
2.76 70	1.14 29	5.04 128	P171532	Hydraulic Cartridge
2.76 70	1.14 29	5.04 128	P171533	Hydraulic Cartridge
2.76 70	1.14 29	5.04 128	P171534	Hydraulic Cartridge
2.76 70	1.14 29	5.04 128	P171535	Hydraulic Cartridge
2.76 70	1.14 29	5.04 128	P173418	Hydraulic Cartridge
2.76 70	1.14 29	6.65 169	P173048	Hydraulic Cartridge
2.76 70	1.14 29	6.65 169	P177655	Hydraulic Cartridge
2.76 70	1.18 30	2.95 29	P171519	Hydraulic Cartridge
2.76 70	1.18 30	2.95 75	P171521	Hydraulic Cartridge
2.76 70	1.37 35	3.34 85	P171656	Hydraulic Cartridge
2.76 70	1.37 35	5.11 130	P171657	Hydraulic Cartridge
2.76 70	1.37 35	5.11 130	P171663	Hydraulic Cartridge
2.76 70	1.38 35	3.35 85	P171651	Hydraulic Cartridge
2.76 70	1.38 35	3.35 85	P171653	Hydraulic Cartridge
2.76 70	1.38 35	5.12 130	P171658	Hydraulic Cartridge
2.76 70	1.38 35	5.12 130	P171660	Hydraulic Cartridge
2.76 70	1.50 38	5.32 135	P175485	Hydraulic Cartridge
2.76 70	1.57 40	8.27 210	P171834	Hydraulic Cartridge
2.76 70	1.57 40	8.27 210	P171837	Hydraulic Cartridge
2.76 70	1.57 40	8.27 210	P171840	Hydraulic Cartridge
2.76 70	1.57 40	8.27 210	P171846	Hydraulic Cartridge
2.76 70	1.65 42	5.08 129	P175238	Hydraulic Cartridge

Specs By Part Type

Hydraulic Cartridge - continued

Outer Diameter IN	MM	Inner Diameter IN	MM	Length IN	MM	PART NUMBER	PART DESCRIPTION
2.76	70	1.65	42	7.64	194	P760155	Hydraulic Cartridge
2.76	70	1.65	42	8.27	210	P171831	Hydraulic Cartridge
2.76	70	1.65	42	8.27	210	P761189	Hydraulic Cartridge
2.76	70	1.65	42	8.27	210	P761996	Hydraulic Cartridge
2.76	70	8.27	210	1.65	42	P171843	Hydraulic Cartridge
2.82	72	0.31	8	4.17	106	P171801	Hydraulic Cartridge
2.82	72	0.31	8	4.17	106	P171815	Hydraulic Cartridge
2.82	72	0.31	8	7.87	200	P171789	Hydraulic Cartridge
2.82	72	0.31	8	7.87	200	P171796	Hydraulic Cartridge
2.82	72	0.31	8	11.81	300	P171797	Hydraulic Cartridge
2.82	72	0.31	8	11.81	300	P171804	Hydraulic Cartridge
2.82	72	0.32	8	5.91	150	P174565	Hydraulic Cartridge
2.82	72	0.32	8	7.87	200	P174566	Hydraulic Cartridge
2.82	72	0.32	8	11.80	300	P174567	Hydraulic Cartridge
2.82	72	1.77	45	4.17	106	P171794	Hydraulic Cartridge
2.82	72	1.77	45	4.17	106	P171808	Hydraulic Cartridge
2.82	72	1.77	45	4.17	106	P171822	Hydraulic Cartridge
2.82	72	1.77	45	5.91	150	P171795	Hydraulic Cartridge
2.82	72	1.77	45	5.91	150	P171802	Hydraulic Cartridge
2.82	72	1.77	45	5.91	150	P171809	Hydraulic Cartridge
2.82	72	1.77	45	5.91	150	P171816	Hydraulic Cartridge
2.82	72	1.77	45	5.91	150	P171823	Hydraulic Cartridge
2.82	72	1.77	45	7.87	200	P171803	Hydraulic Cartridge
2.82	72	1.77	45	7.87	200	P171810	Hydraulic Cartridge
2.82	72	1.77	45	7.87	200	P171817	Hydraulic Cartridge
2.82	72	1.77	45	7.87	200	P171824	Hydraulic Cartridge
2.82	72	1.77	45	11.81	300	P171811	Hydraulic Cartridge
2.82	72	1.77	45	11.81	300	P171818	Hydraulic Cartridge
2.82	72	1.77	45	11.81	300	P171825	Hydraulic Cartridge
2.83	72	1.77	45	10.24	260	P765634	Hydraulic Cartridge
2.83	72	1.77	45	13.78	350	P763185	Hydraulic Cartridge
2.84	72	2.44	62	6.50	165	P171244	Hydraulic Cartridge
2.84	72	2.44	62	6.50	165	P171245	Hydraulic Cartridge
2.87	73	0.47	12	4.37	111	P558467	Hydraulic Cartridge
2.87	73	1.18	30	8.44	214	P551331	Hydraulic Cartridge
2.87	73	1.26	32	3.50	89	P763756	Hydraulic Cartridge
2.87	73	1.26	32	3.90	99	P173027	Hydraulic Cartridge
2.87	73	1.26	32	3.90	99	P173028	Hydraulic Cartridge
2.87	73	1.26	32	3.90	99	P173029	Hydraulic Cartridge
2.87	73	1.26	32	3.90	99	P173030	Hydraulic Cartridge
2.87	73	1.26	32	7.09	180	P763757	Hydraulic Cartridge
2.87	73	1.26	32	9.13	232	P173031	Hydraulic Cartridge
2.87	73	1.26	32	9.13	232	P173032	Hydraulic Cartridge
2.87	73	1.26	32	9.13	232	P173033	Hydraulic Cartridge
2.87	73	1.26	32	9.13	232	P173034	Hydraulic Cartridge
2.87	73	1.35	34	5.67	144	P170615	Hydraulic Cartridge
2.87	73	1.35	34	5.67	144	P170889	Hydraulic Cartridge
2.87	73	1.35	34	7.99	203	P170617	Hydraulic Cartridge
2.87	73	1.38	35	8.27	210	P551245	Hydraulic Cartridge
2.87	73	1.41	36	4.45	113	P502172	Hydraulic Cartridge
2.88	73	1.06	27	3.00	76	P551775	Hydraulic Cartridge
2.89	74	1.35	34	5.67	144	P173163	Hydraulic Cartridge
2.89	74	1.35	34	5.67	144	P173164	Hydraulic Cartridge
2.89	74	1.35	34	7.99	203	P173166	Hydraulic Cartridge
2.89	74	1.35	34	7.99	203	P173167	Hydraulic Cartridge

Hydraulic Cartridge - continued

Outer Diameter IN	MM	Inner Diameter IN	MM	Length IN	MM	PART NUMBER	PART DESCRIPTION
2.89	74	1.35	34	8.00	203	P173165	Hydraulic Cartridge
2.90	74	1.12	28	3.62	92	P169079	Hydraulic Cartridge
2.90	74	1.13	29	7.39	188	P167847	Hydraulic Cartridge
2.91	74	1.06	27	5.68	144	P551753	Hydraulic Cartridge
2.91	74	1.59	40	5.98	152	P561379	Hydraulic Cartridge
2.91	74	1.59	40	5.98	152	P561380	Hydraulic Cartridge
2.91	74	1.59	40	5.98	152	P561383	Hydraulic Cartridge
2.91	74	1.59	40	5.98	152	P561388	Hydraulic Cartridge
2.91	74	1.59	40	5.98	152	P561389	Hydraulic Cartridge
2.91	74	1.59	40	5.98	152	P561392	Hydraulic Cartridge
2.91	74	1.59	40	5.98	152	P561393	Hydraulic Cartridge
2.91	74	1.59	40	5.98	152	P561394	Hydraulic Cartridge
2.91	74	1.59	40	5.98	152	P561397	Hydraulic Cartridge
2.91	74	1.59	40	8.86	225	P561407	Hydraulic Cartridge
2.91	74	1.59	40	8.86	225	P561417	Hydraulic Cartridge
2.91	74	1.59	40	8.86	225	P562024	Hydraulic Cartridge
2.91	74	1.59	40	10.83	275	P561441	Hydraulic Cartridge
2.91	74	1.59	40	10.83	275	P561444	Hydraulic Cartridge
2.91	74	1.59	40	10.83	275	P561445	Hydraulic Cartridge
2.91	74	1.60	41	5.98	152	P561386	Hydraulic Cartridge
2.97	75	1.02	26	5.67	143	P550700	Hydraulic Cartridge
2.99	76	1.04	26	4.75	121	P164814	Hydraulic Cartridge
2.99	76	1.04	26	4.75	121	P164816	Hydraulic Cartridge
3.00	76	1.04	26	4.75	121	P167520	Hydraulic Cartridge
3.00	76	1.04	26	4.75	121	P167522	Hydraulic Cartridge
3.00	76	1.04	26	4.75	121	P169477	Hydraulic Cartridge
3.04	77	1.0	26	8.18	208	P550927	Hydraulic Cartridge
3.07	78	1.58	40	6.14	156	P561391	Hydraulic Cartridge
3.07	78	1.58	40	6.14	156	P561395	Hydraulic Cartridge
3.07	78	1.58	40	9.09	231	P561410	Hydraulic Cartridge
3.07	78	1.58	40	11.06	280	P561439	Hydraulic Cartridge
3.07	78	1.58	40	11.06	281	P561442	Hydraulic Cartridge
3.07	78	1.58	40	14.96	380	P176635	Hydraulic Cartridge
3.07	78	1.58	40	15.00	381	P563030	Hydraulic Cartridge
3.07	78	1.59	40	5.51	140	P171742	Hydraulic Cartridge
3.07	78	1.59	40	9.45	240	P171743	Hydraulic Cartridge
3.07	78	1.59	40	9.45	240	P171744	Hydraulic Cartridge
3.07	78	1.59	40	9.45	240	P171745	Hydraulic Cartridge
3.07	78	1.59	40	10.12	257	P763592	Hydraulic Cartridge
3.07	78	1.59	40	14.96	380	P171746	Hydraulic Cartridge
3.07	78	1.59	40	14.96	380	P171747	Hydraulic Cartridge
3.07	78	1.59	40	14.96	380	P171748	Hydraulic Cartridge
3.07	78	1.59	40	15.63	397	P569553	Hydraulic Cartridge
3.07	78	1.63	41	12.87	327	P560404	Hydraulic Cartridge
3.07	78	1.63	41	18.81	478	P560403	Hydraulic Cartridge
3.07	78	1.66	42	5.51	140	P171741	Hydraulic Cartridge
3.10	79	1.68	43	4.45	113	P169431	Hydraulic Cartridge
3.10	79	1.68	43	8.03	204	P167842	Hydraulic Cartridge
3.10	79	1.68	43	8.03	204	P169435	Hydraulic Cartridge
3.10	79	1.68	43	12.76	324	P169432	Hydraulic Cartridge
3.10	79	1.68	43	16.67	423	P169433	Hydraulic Cartridge
3.10	79	1.68	43	16.67	423	P169436	Hydraulic Cartridge
3.10	79	1.69	43	4.21	107	P173578	Hydraulic Cartridge
3.10	79	1.71	43	4.45	113	P164164	Hydraulic Cartridge
3.10	79	1.71	43	4.45	113	P164172	Hydraulic Cartridge

Hydraulic Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
3.10	79	1.71 43	4.45 113	P164364 Hydraulic Cartridge
3.10	79	1.71 43	4.45 113	P164592 Hydraulic Cartridge
3.10	79	1.71 43	4.62 117	P164368 Hydraulic Cartridge
3.10	79	1.71 43	8.03 204	P162233 Hydraulic Cartridge
3.10	79	1.71 43	8.03 204	P164166 Hydraulic Cartridge
3.10	79	1.71 43	8.03 204	P164365 Hydraulic Cartridge
3.10	79	1.71 43	8.03 204	P164594 Hydraulic Cartridge
3.10	79	1.71 43	8.03 204	P164601 Hydraulic Cartridge
3.10	79	1.71 43	8.03 204	P165319 Hydraulic Cartridge
3.10	79	1.71 43	8.16 207	P569528 Hydraulic Cartridge
3.10	79	1.71 43	8.20 208	P164174 Hydraulic Cartridge
3.10	79	1.71 43	8.37 213	P165584 Hydraulic Cartridge
3.10	79	1.71 43	8.37 213	P165585 Hydraulic Cartridge
3.10	79	1.71 43	8.37 213	P165586 Hydraulic Cartridge
3.10	79	1.71 43	12.76 324	P164168 Hydraulic Cartridge
3.10	79	1.71 43	12.76 324	P164596 Hydraulic Cartridge
3.10	79	1.71 43	12.89 327	P569529 Hydraulic Cartridge
3.10	79	1.71 43	12.93 328	P164176 Hydraulic Cartridge
3.10	79	1.71 43	16.67 423	P164170 Hydraulic Cartridge
3.10	79	1.71 43	16.67 423	P164367 Hydraulic Cartridge
3.10	79	1.71 43	16.67 423	P164598 Hydraulic Cartridge
3.10	79	1.71 43	16.67 423	P164603 Hydraulic Cartridge
3.10	79	1.71 43	16.67 423	P165587 Hydraulic Cartridge
3.10	79	1.71 43	16.67 423	P165588 Hydraulic Cartridge
3.10	79	1.71 43	16.67 423	P165589 Hydraulic Cartridge
3.10	79	1.71 43	16.80 427	P569530 Hydraulic Cartridge
3.10	79	1.71 43	16.84 428	P164178 Hydraulic Cartridge
3.10	79	1.73 44	8.00 203	P162953 Hydraulic Cartridge
3.10	79	1.73 44	8.00 203	P162957 Hydraulic Cartridge
3.10	79	1.73 44	8.00 203	P163244 Hydraulic Cartridge
3.10	79	1.74 44	8.00 203	P162955 Hydraulic Cartridge
3.12	79	1.70 43	4.55 116	P167184 Hydraulic Cartridge
3.12	79	1.70 43	8.20 208	P167185 Hydraulic Cartridge
3.12	79	1.70 43	8.20 208	P167186 Hydraulic Cartridge
3.12	79	1.70 43	8.20 208	P169424 Hydraulic Cartridge
3.12	79	1.70 43	8.20 208	P169426 Hydraulic Cartridge
3.12	79	1.70 43	12.95 329	P167411 Hydraulic Cartridge
3.12	79	1.70 43	12.95 329	P167412 Hydraulic Cartridge
3.12	79	1.70 43	16.81 427	P167187 Hydraulic Cartridge
3.12	79	1.70 43	16.81 427	P167188 Hydraulic Cartridge
3.12	79	1.70 43	17.06 433	P169425 Hydraulic Cartridge
3.12	79	1.86 47	8.00 203	P550264 Hydraulic Cartridge
3.12	79	2.01 51	16.56 421	P564556 Hydraulic Cartridge
3.12	79	2.01 51	16.56 421	P564557 Hydraulic Cartridge
3.15	80	1.18 30	5.04 128	P172448 Hydraulic Cartridge
3.15	80	1.59 40	6.29 160	P567882 Hydraulic Cartridge
3.15	80	1.66 42	6.18 157	P562005 Hydraulic Cartridge
3.15	80	1.66 42	6.18 157	P562006 Hydraulic Cartridge
3.15	80	1.66 42	6.22 158	P561354 Hydraulic Cartridge
3.15	80	1.66 42	9.76 248	P561363 Hydraulic Cartridge
3.15	80	1.66 42	9.76 248	P562007 Hydraulic Cartridge
3.15	80	1.66 42	9.84 250	P561208 Hydraulic Cartridge
3.15	80	1.66 42	15.63 397	P561370 Hydraulic Cartridge
3.15	80	1.66 42	15.67 398	P561368 Hydraulic Cartridge
3.15	80	1.66 42	15.67 398	P562011 Hydraulic Cartridge

Hydraulic Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
3.15	80	1.72 44	4.61 117	P167843 Hydraulic Cartridge
3.19	81	1.63 41	9.19 233	P560398 Hydraulic Cartridge
3.19	81	1.63 41	9.19 233	P560399 Hydraulic Cartridge
3.23	82	0.75 19	4.33 110	P550310 Hydraulic Cartridge
3.27	83	1.57 40	7.72 196	P173481 Hydraulic Cartridge
3.27	83	1.69 43	7.67 195	P175115 Hydraulic Cartridge
3.27	83	1.97 50	8.94 227	P173489 Hydraulic Cartridge
3.29	84	1.87 48	5.59 142	P560709 Hydraulic Cartridge
3.29	84	1.87 47	5.59 142	P560710 Hydraulic Cartridge
3.29	84	1.87 48	5.59 142	P560711 Hydraulic Cartridge
3.29	84	1.87 47	10.04 255	P560713 Hydraulic Cartridge
3.29	84	1.87 47	10.04 255	P560714 Hydraulic Cartridge
3.29	84	1.87 48	10.04 255	P560715 Hydraulic Cartridge
3.29	84	1.87 47	14.69 373	P560716 Hydraulic Cartridge
3.29	84	1.87 48	14.69 373	P560717 Hydraulic Cartridge
3.29	84	1.87 48	14.69 373	P560718 Hydraulic Cartridge
3.32	84	1.87 47	5.56 141	P174290 Hydraulic Cartridge
3.32	84	1.87 47	5.56 141	P174292 Hydraulic Cartridge
3.32	84	1.87 47	5.56 141	P174293 Hydraulic Cartridge
3.32	84	1.87 47	10.12 257	P174294 Hydraulic Cartridge
3.32	84	1.87 47	10.12 257	P174295 Hydraulic Cartridge
3.32	84	1.87 47	10.12 257	P174296 Hydraulic Cartridge
3.32	84	1.87 47	10.12 257	P174297 Hydraulic Cartridge
3.32	84	1.87 47	14.62 371	P174298 Hydraulic Cartridge
3.32	84	1.87 47	14.62 371	P174299 Hydraulic Cartridge
3.32	84	1.87 47	14.62 371	P174300 Hydraulic Cartridge
3.32	84	1.87 47	14.62 371	P174301 Hydraulic Cartridge
3.34	85	1.86 47	9.00 229	P164203 Hydraulic Cartridge
3.35	85	3.30 84	3.34 85	P762877 Hydraulic Cartridge
3.36	85	1.81 46	9.06 230	P502178 Hydraulic Cartridge
3.36	85	1.90 48	3.90 99	P173035 Hydraulic Cartridge
3.38	86	1.53 39	8.03 204	P174538 Hydraulic Cartridge
3.38	86	1.53 39	8.03 204	P174539 Hydraulic Cartridge
3.38	86	2.00 51	2.73 69	P550830 Hydraulic Cartridge
3.39	86	1.73 44	2.36 60	P171784 Hydraulic Cartridge
3.39	86	1.73 44	2.36 60	P761045 Hydraulic Cartridge
3.39	86	1.74 44	8.06 205	P174790 Hydraulic Cartridge
3.39	86	1.74 44	12.86 327	P174791 Hydraulic Cartridge
3.39	86	1.74 44	16.86 428	P174792 Hydraulic Cartridge
3.39	86	1.74 44	25.66 652	P174793 Hydraulic Cartridge
3.39	86	1.96 50	8.03 204	P174527 Hydraulic Cartridge
3.39	86	1.96 50	12.76 324	P174531 Hydraulic Cartridge
3.39	86	1.96 50	12.76 324	P174533 Hydraulic Cartridge
3.39	86	1.96 50	12.76 324	P174534 Hydraulic Cartridge
3.39	86	1.96 50	16.67 423	P170481 Hydraulic Cartridge
3.39	86	1.96 50	16.67 423	P174535 Hydraulic Cartridge
3.39	86	1.96 50	16.67 423	P174536 Hydraulic Cartridge
3.39	86	1.96 50	16.67 423	P174537 Hydraulic Cartridge
3.45	88	1.13 29	5.51 139	P550699 Hydraulic Cartridge
3.46	88	2.44 62	16.96 431	P765457 Hydraulic Cartridge
3.47	88	1.39 35	2.72 69	P550487 Hydraulic Cartridge
3.48	88	1.14 29	5.50 140	P550694 Hydraulic Cartridge
3.48	88	1.36 35	9.27 235	P550696 Hydraulic Cartridge
3.50	89	1.53 39	12.78 325	P174542 Hydraulic Cartridge
3.50	89	1.53 39	12.78 325	P174544 Hydraulic Cartridge

Hydraulic Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
3.76 96	1.72 44	8.05 204	P165158	Hydraulic Cartridge
3.76 96	1.72 44	12.80 325	P164919	Hydraulic Cartridge
3.76 96	1.72 44	12.80 325	P165160	Hydraulic Cartridge
3.76 96	1.72 44	12.80 325	P165166	Hydraulic Cartridge
3.76 96	1.72 44	25.57 649	P164921	Hydraulic Cartridge
3.76 96	1.72 44	25.57 649	P165162	Hydraulic Cartridge
3.76 96	1.72 44	25.57 649	P165168	Hydraulic Cartridge
3.76 96	1.70 69	13.11 333	P173760	Hydraulic Cartridge
3.78 96	2.92 49	10.00 254	P551369	Hydraulic Cartridge
3.80 97	2.19 56	25.90 658	P171037	Hydraulic Cartridge
3.80 97	2.20 56	16.80 427	P560405	Hydraulic Cartridge
3.80 97	2.20 56	16.81 427	P565150	Hydraulic Cartridge
3.80 97	2.20 56	25.71 653	P560406	Hydraulic Cartridge
3.83 97		18.19 462	P568093	Hydraulic Cartridge
3.83 97	1.90 48	9.19 233	P568081	Hydraulic Cartridge
3.83 97	1.90 48	9.19 233	P568091	Hydraulic Cartridge
3.83 97	1.90 48	18.19 462	P568094	Hydraulic Cartridge
3.85 98	1.61 41	9.02 229	P163903	Hydraulic Cartridge
3.85 98	1.61 41	9.02 229	P163910	Hydraulic Cartridge
3.85 98	1.61 41	9.02 229	P167410	Hydraulic Cartridge
3.85 98	1.61 41	9.02 229	P167425	Hydraulic Cartridge
3.85 98	1.61 41	9.02 229	P167514	Hydraulic Cartridge
3.85 98	1.61 41	9.02 229	P169341	Hydraulic Cartridge
3.85 98	1.61 41	9.02 229	P169344	Hydraulic Cartridge
3.85 98	1.62 41	9.02 229	P174622	Hydraulic Cartridge
3.85 98	1.62 41	9.02 229	P174623	Hydraulic Cartridge
3.85 98	1.62 41	9.02 229	P174624	Hydraulic Cartridge
3.85 98	1.62 41	9.22 234	P569527	Hydraulic Cartridge
3.85 98	1.62 41	18.25 464	P174243	Hydraulic Cartridge
3.85 98	1.62 41	18.25 464	P174244	Hydraulic Cartridge
3.85 98	1.62 41	18.25 464	P174245	Hydraulic Cartridge
3.85 98	1.62 41	18.25 464	P174247	Hydraulic Cartridge
3.85 98	1.62 41	18.25 464	P174249	Hydraulic Cartridge
3.85 98	1.62 41	18.25 464	P174260	Hydraulic Cartridge
3.85 98	1.62 41	27.81 706	P174248	Hydraulic Cartridge
3.85 98	1.62 41	27.81 706	P174250	Hydraulic Cartridge
3.85 98	1.62 41	27.81 706	P174268	Hydraulic Cartridge
3.86 86	1.22 31	7.01 178	P176792	Hydraulic Cartridge
3.86 98	2.53 64	16.03 407	P564563	Hydraulic Cartridge
3.88 99	2.53 64	12.31 313	P564849	Hydraulic Cartridge
3.89 99	1.96 50	10.84 275	P761490	Hydraulic Cartridge
3.89 99	2.59 66	1.96 50	P764183	Hydraulic Cartridge
3.90 99	1.61 41	18.31 465	P560402	Hydraulic Cartridge
3.90 99	2.03 52	8.27 210	P560719	Hydraulic Cartridge
3.90 99	2.26 57	18.50 470	P560401	Hydraulic Cartridge
3.93 100	2.05 52	8.27 210	P171670	Hydraulic Cartridge
3.94 100	1.62 41	9.12 232	P551290	Hydraulic Cartridge
3.94 100	1.65 42	9.12 232	P551158	Hydraulic Cartridge
3.94 100	1.85 47	13.74 349	P173491	Hydraulic Cartridge
3.94 100	1.95 50	9.11 231	P174610	Hydraulic Cartridge
3.94 100	1.95 50	9.11 231	P174611	Hydraulic Cartridge
3.94 100	2.05 52	4.72 120	P171681	Hydraulic Cartridge
3.94 100	2.05 52	8.27 210	P171666	Hydraulic Cartridge
3.94 100	2.05 52	8.27 210	P171667	Hydraulic Cartridge
3.94 100	2.05 52	8.27 210	P171668	Hydraulic Cartridge

Hydraulic Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
3.94 100	2.32 59	7.01 178	P173060	Hydraulic Cartridge
3.94 100	2.32 59	10.94 278	P551160	Hydraulic Cartridge
3.94 100	2.34 59	8.27 210	P551054	Hydraulic Cartridge
3.94 100	2.34 59	8.31 211	P551778	Hydraulic Cartridge
3.94 100	2.48 63	18.27 464	P173490	Hydraulic Cartridge
3.98 101	1.10 28	5.06 129	P550781	Hydraulic Cartridge
3.98 101	1.42 36	5.00 127	P550698	Hydraulic Cartridge

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
3.98 101	1 NPT	9.92 252	P177293	Hydraulic Cartridge
3.98 101	G2	9.65 245	P173370	Hydraulic Cartridge

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
4.00 102	1.06 27	6.00 152	P163437	Hydraulic Cartridge
4.00 102	1.56 40	14.81 376	P163447	Hydraulic Cartridge
4.00 102	1.56 40	14.81 376	P164277	Hydraulic Cartridge
4.00 102	2.23 57	9.00 229	P550284	Hydraulic Cartridge
4.00 102	2.23 57	18.00 457	P550267	Hydraulic Cartridge
4.00 102	2.27 58	9.25 235	P559740	Hydraulic Cartridge
4.00 102	2.30 58	9.25 235	P164200	Hydraulic Cartridge
4.00 102	2.30 58	9.25 235	P165238	Hydraulic Cartridge
4.00 102	2.42 61	4.21 107	P550601	Hydraulic Cartridge
4.00 102	2.90 74	6.25 159	P173581	Hydraulic Cartridge
4.00 102	2.90 74	6.25 159	P173583	Hydraulic Cartridge
4.00 102	2.90 74	6.25 159	P173584	Hydraulic Cartridge
4.01 102	2.48 63	12.99 330	P764126	Hydraulic Cartridge
4.02 102	1.78 45	8.98 228	P550648	Hydraulic Cartridge
4.02 102	2.38 60	9.21 234	P561260	Hydraulic Cartridge
4.02 102	2.48 63	9.09 231	P561253	Hydraulic Cartridge
4.17 106	0.39 10	7.48 190	P171798	Hydraulic Cartridge
4.17 106	0.39 10	10.24 260	P171799	Hydraulic Cartridge
4.17 106	0.39 10	18.31 465	P171800	Hydraulic Cartridge
4.17 106	0.39 10	18.31 465	P171821	Hydraulic Cartridge
4.17 106	0.41 10	7.48 190	P174568	Hydraulic Cartridge
4.17 106	0.41 10	18.31 465	P174570	Hydraulic Cartridge
4.17 106	2.52 64	7.48 190	P171805	Hydraulic Cartridge
4.17 106	2.52 64	7.48 190	P171812	Hydraulic Cartridge
4.17 106	2.52 64	7.48 190	P171819	Hydraulic Cartridge
4.17 106	2.52 64	7.48 190	P171826	Hydraulic Cartridge
4.17 106	2.52 64	10.20 259	P763010	Hydraulic Cartridge
4.17 106	2.52 64	10.24 260	P171806	Hydraulic Cartridge
4.17 106	2.52 64	10.24 260	P171813	Hydraulic Cartridge
4.17 106	2.52 64	10.24 260	P171820	Hydraulic Cartridge
4.17 106	2.52 64	10.24 260	P171827	Hydraulic Cartridge
4.17 106	2.52 64	18.30 465	P171814	Hydraulic Cartridge
4.17 106	2.52 64	18.30 465	P171828	Hydraulic Cartridge
4.17 106	2.52 64	18.31 465	P171807	Hydraulic Cartridge
4.17 106	2.52 64	18.31 465	P763014	Hydraulic Cartridge
4.18 106	0.41 10	10.29 261	P174569	Hydraulic Cartridge
4.22 107	1.78 45	9.00 229	P550084	Hydraulic Cartridge
4.25 108	3.12 79	9.50 241	P173613	Hydraulic Cartridge
4.25 108	3.12 79	9.50 241	P173617	Hydraulic Cartridge
4.25 108	3.12 79	9.50 241	P173618	Hydraulic Cartridge

Hydraulic Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
4.25	108	3.12 79	9.56 243	P552412 Hydraulic Cartridge
4.33	110	3.23 82	P171785 Hydraulic Cartridge	
4.33	110	2.95 75	3.23 82	P761054 Hydraulic Cartridge
4.38	111	1.98 50	8.00 203	P165251 Hydraulic Cartridge
4.38	111	2.44 62	5.00 127	P160105 Hydraulic Cartridge
4.38	111	2.44 62	5.00 127	P160605 Hydraulic Cartridge
4.38	111	2.44 62	8.00 203	P160558 Hydraulic Cartridge
4.38	111	2.44 62	8.00 203	P161402 Hydraulic Cartridge
4.38	111	2.44 62	8.00 203	P161413 Hydraulic Cartridge
4.38	111	2.44 62	8.00 203	P162368 Hydraulic Cartridge
4.38	111	2.44 62	8.00 203	P163172 Hydraulic Cartridge
4.38	111	2.44 62	8.00 203	P165626 Hydraulic Cartridge
4.38	111	2.44 62	8.00 203	P166460 Hydraulic Cartridge
4.38	111	2.44 62	8.00 203	P166461 Hydraulic Cartridge
4.38	111	2.44 62	10.00 254	P161908 Hydraulic Cartridge
4.38	111	2.44 62	13.00 330	P161917 Hydraulic Cartridge
4.38	111	2.44 62	13.00 330	P161969 Hydraulic Cartridge
4.38	111	2.44 62	13.00 330	P162181 Hydraulic Cartridge
4.38	111	2.44 62	13.00 330	P164884 Hydraulic Cartridge
4.38	111	2.44 62	13.00 330	P165378 Hydraulic Cartridge
4.38	111	2.44 62	16.00 406	P160116 Hydraulic Cartridge
4.38	111	2.44 62	16.00 406	P160516 Hydraulic Cartridge
4.38	111	2.44 62	16.00 406	P160616 Hydraulic Cartridge
4.38	111	2.44 62	16.00 406	P160700 Hydraulic Cartridge
4.38	111	2.44 62	16.00 406	P160807 Hydraulic Cartridge
4.38	111	2.44 62	16.00 406	P161016 Hydraulic Cartridge
4.38	111	2.44 62	16.00 406	P161222 Hydraulic Cartridge
4.38	111	2.44 62	16.00 406	P161571 Hydraulic Cartridge
4.38	111	2.44 62	16.00 406	P164266 Hydraulic Cartridge
4.38	111	2.44 62	16.00 406	P164697 Hydraulic Cartridge
4.38	111	2.44 62	16.00 406	P164699 Hydraulic Cartridge
4.38	111	2.44 62	16.00 406	P165249 Hydraulic Cartridge
4.38	111	2.44 62	16.00 406	P165628 Hydraulic Cartridge
4.38	111	2.44 62	16.00 406	P166246 Hydraulic Cartridge
4.38	111	2.44 62	16.00 406	P166597 Hydraulic Cartridge
4.39	112	1.75 44	12.75 324	P559434 Hydraulic Cartridge
4.39	112	2.22 56	14.47 368	P171454 Hydraulic Cartridge
4.39	112	2.24 57	19.05 484	P502269 Hydraulic Cartridge
4.39	112	2.44 62	5.00 127	P560526 Hydraulic Cartridge
4.39	112	2.44 62	8.00 203	P161650 Hydraulic Cartridge
4.39	112	2.44 62	8.00 203	P162104 Hydraulic Cartridge
4.39	112	2.44 62	8.00 203	P176220 Hydraulic Cartridge
4.39	112	2.44 62	12.25 311	P162855 Hydraulic Cartridge
4.39	112	2.44 62	16.00 406	P176221 Hydraulic Cartridge
4.39	112	2.45 62	5.00 127	P560524 Hydraulic Cartridge
4.39	112	2.45 62	5.00 127	P560525 Hydraulic Cartridge
4.39	112	2.45 62	8.00 203	P560527 Hydraulic Cartridge
4.39	112	2.45 62	13.00 330	P560528 Hydraulic Cartridge
4.41	112	1.42 36	7.32 186	P177661 Hydraulic Cartridge
4.41	112	1.42 36	7.32 186	P763186 Hydraulic Cartridge
4.41	112	1.81 46	7.09 180	P171596 Hydraulic Cartridge
4.41	112	1.81 46	7.09 180	P171599 Hydraulic Cartridge
4.41	112	1.81 46	7.09 180	P171600 Hydraulic Cartridge
4.41	112	1.81 46	7.09 180	P171601 Hydraulic Cartridge
4.41	112	2.72 69	17.24 438	P173207 Hydraulic Cartridge

Hydraulic Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
4.41	112	2.76 70	11.50 292	P550083 Hydraulic Cartridge
4.42	112	1.66 42	9.00 229	P170090 Hydraulic Cartridge
4.42	112	1.66 42	9.00 229	P170092 Hydraulic Cartridge
4.45	113	.41 62	7.91 201	P177424 Hydraulic Cartridge
4.45	113	1.89 48	5.79 147	P762091 Hydraulic Cartridge
4.47	114	2.87 73	14.72 374	P550037 Hydraulic Cartridge
4.49	114	2.70 69	13.11 333	P170619 Hydraulic Cartridge
4.49	114	2.70 69	13.11 333	P170888 Hydraulic Cartridge
4.50	114	0.53 13	5.00 127	P556004 Hydraulic Cartridge
4.50	114	0.53 13	9.06 230	P556001 Hydraulic Cartridge
4.50	114	1.78 45	7.00 178	P550138 Hydraulic Cartridge
4.50	114	2.22 56	7.25 184	P555150 Hydraulic Cartridge
4.50	114	2.24 57	9.53 242	P165314 Hydraulic Cartridge
4.50	114	2.28 58	7.18 182	P551754 Hydraulic Cartridge
4.50	114	2.70 69	13.11 333	P173175 Hydraulic Cartridge
4.50	114	2.70 69	13.11 333	P173176 Hydraulic Cartridge
4.50	114	2.70 69	16.22 412	P173178 Hydraulic Cartridge
4.50	114	2.70 69	16.22 412	P173179 Hydraulic Cartridge
4.50	114	2.70 69	16.22 412	P173180 Hydraulic Cartridge
4.51	115	0.66 17	7.06 179	P551183 Hydraulic Cartridge
4.51	115	2.30 58	7.04 179	P550140 Hydraulic Cartridge
4.51	115	2.30 58	9.02 229	P550079 Hydraulic Cartridge
4.52	115	0.54 14	9.00 229	P551216 Hydraulic Cartridge
4.52	115	1.75 44	7.18 182	P551213 Hydraulic Cartridge
4.52	115	1.75 44	9.10 231	P550654 Hydraulic Cartridge
4.52	115	1.80 46	7.05 179	P553293 Hydraulic Cartridge
4.52	115	2.22 56	7.44 189	P551222 Hydraulic Cartridge
4.52	115	2.27 58	7.12 181	P551193 Hydraulic Cartridge
4.52	115	2.27 58	7.97 202	P551187 Hydraulic Cartridge
4.52	115	2.27 58	9.00 229	P551215 Hydraulic Cartridge
4.61	117	2.19 56	5.29 134	P165231 Hydraulic Cartridge
4.61	117	2.19 56	7.79 198	P164904 Hydraulic Cartridge
4.61	117	2.19 56	7.79 198	P164906 Hydraulic Cartridge
4.61	118	2.20 56	5.29 134	P555603 Hydraulic Cartridge
4.61	117	2.32 59	19.49 495	P763191 Hydraulic Cartridge
4.61	117	3.34 85	6.41 163	P175120 Hydraulic Cartridge
4.65	118	2.32 59	6.50 165	P173485 Hydraulic Cartridge
4.65	118	2.40 61	6.50 165	P550308 Hydraulic Cartridge
4.84	123	3.94 100	11.14 283	P762865 Hydraulic Cartridge
4.96	126		11.42 290	P172464 Hydraulic Cartridge
4.96	126	0.39 10	8.31 211	P172461 Hydraulic Cartridge
4.96	126	0.39 10	8.31 211	P172462 Hydraulic Cartridge
4.96	126	0.39 10	8.31 211	P173052 Hydraulic Cartridge
4.96	126	0.39 10	11.42 290	P173056 Hydraulic Cartridge
4.96	126	0.39 10	15.35 390	P173100 Hydraulic Cartridge
4.96	126	0.39 10	18.90 480	P172467 Hydraulic Cartridge
4.96	126	0.41 10	11.42 290	P174572 Hydraulic Cartridge
4.96	126	0.41 10	18.90 480	P174573 Hydraulic Cartridge
4.96	126	3.31 84	18.31 465	P560400 Hydraulic Cartridge
4.96	126	3.31 84	22.83 580	P763873 Hydraulic Cartridge
4.96	126	3.62 92	8.31 211	P172460 Hydraulic Cartridge
4.96	126	3.62 92	11.42 290	P172463 Hydraulic Cartridge
4.96	126	3.62 92	11.42 290	P172465 Hydraulic Cartridge
4.96	126	3.62 92	11.42 290	P173055 Hydraulic Cartridge
4.96	126	3.62 92	11.42 290	P763018 Hydraulic Cartridge

Hydraulic Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
4.96 126	3.62 92	15.35 390	P173096	Hydraulic Cartridge
4.96 126	3.62 92	15.35 390	P173097	Hydraulic Cartridge
4.96 126	3.62 92	15.35 390	P173098	Hydraulic Cartridge
4.96 126	3.62 92	18.90 480	P172466	Hydraulic Cartridge
4.96 126	3.62 92	18.90 480	P172468	Hydraulic Cartridge
4.96 126	3.62 92	18.90 480	P173057	Hydraulic Cartridge
4.96 126	3.62 92	18.90 480	P173058	Hydraulic Cartridge
4.96 126	3.62 92	18.90 480	P763016	Hydraulic Cartridge
5.00 127	1.50 38	4.12 105	P550637	Hydraulic Cartridge
5.00 127	2.50 64	11.87 301	P557373	Hydraulic Cartridge
5.00 127	2.56 65	9.84 250	P763272	Hydraulic Cartridge
5.00 127	2.81 71	6.12 155	P554636	Hydraulic Cartridge
5.00 127	3.00 76	3.00 76	P550128	Hydraulic Cartridge
5.03 128	2.22 56	10.39 264	P502357	Hydraulic Cartridge
5.07 129	2.28 58	10.29 261	P554056	Hydraulic Cartridge
5.07 129	3.34 85	7.00 178	P550523	Hydraulic Cartridge
5.07 129	3.34 85	9.00 229	P163448	Hydraulic Cartridge
5.07 129	3.34 85	9.00 229	P164205	Hydraulic Cartridge
5.07 129	3.34 85	9.00 229	P165239	Hydraulic Cartridge
5.07 129	3.34 85	11.00 279	P164241	Hydraulic Cartridge
5.07 129	3.34 85	18.50 470	P165744	Hydraulic Cartridge
5.07 129	3.35 85	9.00 229	P165242	Hydraulic Cartridge
5.07 129	3.35 85	9.00 229	P166549	Hydraulic Cartridge
5.07 129	3.35 85	9.45 240	P763182	Hydraulic Cartridge
5.07 129	3.35 85	9.45 240	P763190	Hydraulic Cartridge
5.07 129	3.35 85	9.84 250	P763184	Hydraulic Cartridge
5.07 129	3.58 91	11.00 279	P555461	Hydraulic Cartridge
5.08 129	2.05 52	5.35 136	P763274	Hydraulic Cartridge
5.08 129	2.05 52	5.35 126	P763275	Hydraulic Cartridge
5.08 129	2.05 52	5.35 136	P763276	Hydraulic Cartridge
5.08 129	2.05 52	5.35 136	P763277	Hydraulic Cartridge
5.08 129	2.05 52	5.35 136	P763278	Hydraulic Cartridge
5.08 129	2.56 65	7.99 203	P173065	Hydraulic Cartridge
5.08 129	2.56 65	9.84 250	P763264	Hydraulic Cartridge
5.08 129	2.56 65	9.84 250	P763265	Hydraulic Cartridge
5.08 129	2.56 65	9.84 250	P763267	Hydraulic Cartridge
5.08 129	2.56 65	9.84 250	P763269	Hydraulic Cartridge
5.08 129	2.56 65	15.74 400	P763260	Hydraulic Cartridge
5.08 129	2.56 65	15.75 400	P763258	Hydraulic Cartridge
5.08 129	2.56 65	15.75 400	P763259	Hydraulic Cartridge
5.08 129	2.56 65	15.75 400	P763263	Hydraulic Cartridge
5.08 129	2.81 71	8.97 228	P551197	Hydraulic Cartridge
5.08 129	3.35 85	8.98 228	P173093	Hydraulic Cartridge
5.08 129	3.35 85	9.02 229	P556064	Hydraulic Cartridge
5.12 130	2.56 65	9.84 250	P763266	Hydraulic Cartridge
5.12 130	2.56 65	9.84 250	P763268	Hydraulic Cartridge
5.12 130	2.56 65	9.84 250	P763270	Hydraulic Cartridge
5.12 130	2.56 65	9.84 250	P763271	Hydraulic Cartridge
5.12 130	2.56 65	9.84 250	P763273	Hydraulic Cartridge
5.12 130	2.99 76	9.84 250	P560720	Hydraulic Cartridge
5.12 130	3.34 85	11.06 281	P550575	Hydraulic Cartridge
5.12 130	3.37 86	6.00 152	P558877	Hydraulic Cartridge
5.12 130	3.40 86	11.50 292	P557380	Hydraulic Cartridge
5.22 133	3.24 82	18.13 461	P550582	Hydraulic Cartridge
5.39 137	2.99 76	9.84 250	P171671	Hydraulic Cartridge

Hydraulic Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
5.39 137	2.99 76	9.84 250	P171672	Hydraulic Cartridge
5.39 137	2.99 76	9.84 250	P171674	Hydraulic Cartridge
5.39 137	2.99 76	9.84 250	P171675	Hydraulic Cartridge
5.39 137	2.99 76	9.84 250	P171677	Hydraulic Cartridge
5.50 140	4.03 102	8.63 219	P173585	Hydraulic Cartridge
5.51 140		9.72 247	P762811	Hydraulic Cartridge
5.51 140		10.12 257	P173074	Hydraulic Cartridge
5.51 140		13.58 345	P762806	Hydraulic Cartridge
5.51 140		15.75 400	P176892	Hydraulic Cartridge
5.51 140	2.04 52	5.39 137	P171550	Hydraulic Cartridge
5.51 140	2.05 52	5.35 136	P171549	Hydraulic Cartridge
5.51 140	2.05 52	5.35 136	P171551	Hydraulic Cartridge
5.51 140	2.05 52	5.35 136	P171552	Hydraulic Cartridge
5.51 140	2.05 52	5.35 136	P171553	Hydraulic Cartridge
5.51 140	2.05 52	7.99 203	P171554	Hydraulic Cartridge
5.51 140	2.05 52	7.99 203	P171555	Hydraulic Cartridge
5.51 140	2.05 52	7.99 203	P171556	Hydraulic Cartridge
5.51 140	2.05 52	7.99 203	P171557	Hydraulic Cartridge
5.51 140	2.05 52	7.99 203	P171558	Hydraulic Cartridge
5.51 140	2.05 52	7.99 203	P171559	Hydraulic Cartridge
5.51 140	2.05 52	8.27 210	P171665	Hydraulic Cartridge
5.51 140	2.55 65	5.35 136	P171591	Hydraulic Cartridge
5.51 140	2.56 65	5.35 136	P171595	Hydraulic Cartridge
5.51 140	2.56 65	5.35 136	P173416	Hydraulic Cartridge
5.51 140	2.56 65	5.35 136	P761997	Hydraulic Cartridge
5.51 140	2.56 65	7.99 203	P171560	Hydraulic Cartridge
5.51 140	2.56 65	7.99 203	P171561	Hydraulic Cartridge
5.51 140	2.56 65	7.99 203	P171562	Hydraulic Cartridge
5.51 140	2.56 65	7.99 203	P171563	Hydraulic Cartridge
5.51 140	2.56 65	7.99 203	P171564	Hydraulic Cartridge
5.51 140	2.56 65	7.99 203	P171565	Hydraulic Cartridge
5.51 140	2.56 65	7.99 203	P171566	Hydraulic Cartridge
5.51 140	2.56 65	7.99 203	P171567	Hydraulic Cartridge
5.51 140	2.56 65	7.99 203	P171568	Hydraulic Cartridge
5.51 140	2.56 65	7.99 203	P171569	Hydraulic Cartridge
5.51 140	2.56 65	7.99 203	P171570	Hydraulic Cartridge
5.51 140	2.56 65	7.99 203	P171571	Hydraulic Cartridge
5.51 140	2.56 65	7.99 203	P173417	Hydraulic Cartridge
5.51 140	2.56 65	7.99 203	P175357	Hydraulic Cartridge
5.51 140	2.56 65	7.99 203	P762880	Hydraulic Cartridge
5.51 140	2.56 65	9.84 250	P171572	Hydraulic Cartridge
5.51 140	2.56 65	9.84 250	P171573	Hydraulic Cartridge
5.51 140	2.56 65	9.84 250	P171574	Hydraulic Cartridge
5.51 140	2.56 65	9.84 250	P171575	Hydraulic Cartridge
5.51 140	2.56 65	9.84 250	P171576	Hydraulic Cartridge
5.51 140	2.56 65	9.84 250	P171577	Hydraulic Cartridge
5.51 140	2.56 65	9.84 250	P173334	Hydraulic Cartridge
5.51 140	2.56 65	9.84 250	P177577	Hydraulic Cartridge
5.51 140	2.56 65	9.88 251	P762810	Hydraulic Cartridge
5.51 140	2.56 65	15.74 400	P171582	Hydraulic Cartridge
5.51 140	2.56 65	15.74 400	P171583	Hydraulic Cartridge
5.51 140	2.56 65	15.75 400	P761995	Hydraulic Cartridge
5.51 140	2.56 65	16.02 407	P171578	Hydraulic Cartridge
5.51 140	2.56 65	16.02 407	P173091	Hydraulic Cartridge
5.51 140	2.58 66	15.74 400	P171579	Hydraulic Cartridge

Hydraulic Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
5.51 140	2.58 66	15.74 400	P171580	Hydraulic Cartridge
5.51 140	2.58 66	15.74 400	P171581	Hydraulic Cartridge
5.51 140	2.63 67	7.83 199	P165233	Hydraulic Cartridge
5.51 140	2.87 73	15.75 400	P564085	Hydraulic Cartridge
5.51 140	3.84 98	16.75 425	P550577	Hydraulic Cartridge

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
5.51 140	G2	8.66 220	P171899	Hydraulic Cartridge
5.51 140	G2-1/2	12.48 317	P171906	Hydraulic Cartridge
5.51 140	G2-1/2	12.48 317	P171907	Hydraulic Cartridge

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
5.59 142	3.70 94	10.35 263	P561269	Hydraulic Cartridge
5.59 142	3.70 94	15.20 386	P561276	Hydraulic Cartridge
5.62 143	3.72 95	12.00 305	P166204	Hydraulic Cartridge
5.62 143	3.72 95	12.00 305	P170061	Hydraulic Cartridge
5.62 143	3.72 95	12.00 305	P170062	Hydraulic Cartridge
5.62 143	3.72 95	12.00 305	P170063	Hydraulic Cartridge
5.62 143	3.72 95	12.00 305	P171241	Hydraulic Cartridge
5.62 143	3.72 95	12.00 305	P171243	Hydraulic Cartridge
5.62 143	3.72 95	24.19 614	P165786	Hydraulic Cartridge
5.63 143	3.78 96	14.30 363	P170885	Hydraulic Cartridge
5.63 143	3.78 96	18.99 482	P170886	Hydraulic Cartridge
5.63 143	3.78 96	18.99 482	P170890	Hydraulic Cartridge
5.63 143	3.80 97	14.29 363	P170891	Hydraulic Cartridge
5.63 143	3.80 97	19.02 483	P170620	Hydraulic Cartridge
5.65 143	3.80 97	14.29 363	P173182	Hydraulic Cartridge
5.65 144	3.80 97	36.26 921	P560438	Hydraulic Cartridge
5.65 144	3.80 97	36.26 921	P560703	Hydraulic Cartridge
5.65 144	3.80 97	36.26 921	P560704	Hydraulic Cartridge
5.82 148	1.97 50	13.85 352	P763950	Hydraulic Cartridge
5.90 150	4.34 110	11.81 300	P551142	Hydraulic Cartridge
5.90 150	4.34 110	17.72 450	P551210	Hydraulic Cartridge
5.90 150	4.34 110	17.72 450	P551333	Hydraulic Cartridge
5.90 150	4.34 110	17.72 450	P551334	Hydraulic Cartridge
5.91 150		12.99 330	P761093	Hydraulic Cartridge
5.91 150	3.35 85	9.25 235	P173094	Hydraulic Cartridge
5.91 150	3.35 85	9.45 240	P762563	Hydraulic Cartridge
5.91 150	3.62 92	7.87 200	P550787	Hydraulic Cartridge
5.91 150	3.62 92	7.87 200	P764626	Hydraulic Cartridge
5.91 150	3.74 95	17.71 450	P173237	Hydraulic Cartridge
5.91 150	3.80 97	17.76 451	P763257	Hydraulic Cartridge
5.91 150	4.33 110	17.72 450	P550702	Hydraulic Cartridge

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
5.91 150	M10	26.57 675	P764679	Hydraulic Cartridge

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
5.93 151	2.16 55	17.00 432	P167766	Hydraulic Cartridge
5.94 151	1.75 44	7.12 181	P163438	Hydraulic Cartridge
5.94 151	1.75 44	7.12 181	P163439	Hydraulic Cartridge
5.97 152	4.14 105	38.62 981	P565308	Hydraulic Cartridge

Hydraulic Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
5.97 152	4.14 105	38.62 981	P565309	Hydraulic Cartridge
5.97 152	4.14 105	38.62 981	P565310	Hydraulic Cartridge

Outer Diameter IN MM	Inlet Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
5.97 152	4.14 105	38.62 981	P565311	Hydraulic Cartridge

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
5.97 152	4.14 106	38.62 981	P565312	Hydraulic Cartridge
5.97 152	4.14 105	38.62 981	P565313	Hydraulic Cartridge
5.98 152	3.35 85	16.34 415	P173483	Hydraulic Cartridge
5.98 152	3.35 85	24.57 624	P173484	Hydraulic Cartridge
5.98 152	3.52 89	3.97 101	P550581	Hydraulic Cartridge
5.98 152	3.54 90	32.68 830	P173482	Hydraulic Cartridge
6.00 152	2.60 66	1.88 48	P566903	Hydraulic Cartridge
6.00 152	2.60 66	8.00 203	P566904	Hydraulic Cartridge
6.00 152	2.60 66	18.00 457	P170102	Hydraulic Cartridge
6.00 152	2.60 66	18.00 457	P170103	Hydraulic Cartridge
6.00 152	2.60 66	18.00 457	P178729	Hydraulic Cartridge
6.00 152	2.60 66	18.00 457	P550212	Hydraulic Cartridge
6.00 152	2.60 66	18.00 457	P550213	Hydraulic Cartridge
6.00 152	2.60 66	18.00 457	P550216	Hydraulic Cartridge
6.00 152	2.60 66	18.00 457	P569532	Hydraulic Cartridge
6.00 152	2.62 67	17.94 456	P557826	Hydraulic Cartridge
6.00 152	2.63 67	9.00 229	P552407	Hydraulic Cartridge
6.00 152	3.19 81	18.00 457	P176202	Hydraulic Cartridge
6.00 152	3.19 81	18.00 457	P176203	Hydraulic Cartridge
6.00 152	3.19 81	18.00 457	P176204	Hydraulic Cartridge
6.00 152	3.19 81	18.00 457	P176205	Hydraulic Cartridge
6.00 152	3.41 87	18.00 457	P161365	Hydraulic Cartridge
6.00 152	3.41 87	18.00 457	P163945	Hydraulic Cartridge
6.00 152	3.41 87	18.00 457	P164405	Hydraulic Cartridge
6.00 152	3.41 87	18.00 457	P164701	Hydraulic Cartridge
6.00 152	3.41 87	18.00 457	P164703	Hydraulic Cartridge
6.00 152	3.41 87	18.00 457	P165171	Hydraulic Cartridge
6.00 152	3.41 87	18.00 457	P166462	Hydraulic Cartridge
6.00 152	3.41 87	18.00 457	P166901	Hydraulic Cartridge
6.00 152	3.41 87	18.00 457	P173573	Hydraulic Cartridge
6.00 152	3.41 87	18.00 457	P176222	Hydraulic Cartridge
6.00 152	3.52 89	8.50 216	P550427	Hydraulic Cartridge
6.00 152	3.94 100	25.40 645	P173081	Hydraulic Cartridge
6.00 152	3.96 101	11.92 303	P163446	Hydraulic Cartridge
6.00 152	4.12 105	13.83 351	P171053	Hydraulic Cartridge
6.00 152	4.12 105	13.83 351	P171054	Hydraulic Cartridge
6.00 152	4.12 105	13.83 351	P171055	Hydraulic Cartridge
6.00 152	4.12 105	13.83 351	P171056	Hydraulic Cartridge
6.00 152	4.12 105	15.95 405	P569533	Hydraulic Cartridge
6.00 152	4.12 105	35.68 906	P171045	Hydraulic Cartridge
6.00 152	4.12 105	35.68 906	P171046	Hydraulic Cartridge
6.00 152	4.12 105	35.68 906	P171047	Hydraulic Cartridge
6.00 152	4.12 105	35.68 906	P171048	Hydraulic Cartridge
6.00 152	4.12 105	37.80 960	P569534	Hydraulic Cartridge
6.02 153	3.28 83	8.13 207	P165149	Hydraulic Cartridge
6.02 153	3.28 83	8.13 207	P169437	Hydraulic Cartridge

Hydraulic Cartridge - continued

Outer Diameter IN	MM	Inner Diameter IN	MM	Length IN	MM	PART NUMBER	PART DESCRIPTION
6.02	153	3.28	83	16.77	426	P164852	Hydraulic Cartridge
6.02	153	3.28	83	16.77	426	P165142	Hydraulic Cartridge
6.02	153	3.28	83	16.77	426	P165151	Hydraulic Cartridge
6.02	153	3.28	83	16.77	426	P169438	Hydraulic Cartridge
6.02	153	3.28	83	25.62	651	P164853	Hydraulic Cartridge
6.02	153	3.28	83	25.62	651	P165144	Hydraulic Cartridge
6.02	152	3.50	88	3.94	100	P567460	Hydraulic Cartridge
6.02	153	4.12	105	8.13	207	P164215	Hydraulic Cartridge
6.02	153	4.12	105	8.13	207	P164217	Hydraulic Cartridge
6.02	153	4.12	105	8.13	207	P164574	Hydraulic Cartridge
6.02	153	4.12	105	8.13	207	P164580	Hydraulic Cartridge
6.02	153	4.12	105	38.62	981	P167836	Hydraulic Cartridge
6.02	153	4.16	106	38.62	981	P164565	Hydraulic Cartridge
6.02	153	4.17	106	16.77	426	P164219	Hydraulic Cartridge
6.02	153	4.17	106	16.77	426	P164221	Hydraulic Cartridge
6.02	153	4.17	106	16.77	426	P164576	Hydraulic Cartridge
6.02	153	4.17	106	16.77	426	P167835	Hydraulic Cartridge
6.08	154	1.75	44	31.00	787	P568532	Hydraulic Cartridge
6.14	156	3.16	80	24.84	631	P784036	Hydraulic Cartridge
6.14	156	3.16	80	24.84	631	P784037	Hydraulic Cartridge
6.14	156	3.86	98	16.97	431	P502270	Hydraulic Cartridge
6.28	160	3.76	96	15.69	398	P568449	Hydraulic Cartridge
6.30	160	3.71	94	38.98	990	P561229	Hydraulic Cartridge
6.30	160	3.71	94	38.98	990	P561230	Hydraulic Cartridge
6.50	165	3.00	76	18.50	470	P166474	Hydraulic Cartridge
6.50	165	3.54	90	15.12	384	P166446	Hydraulic Cartridge
6.50	165	5.50	140	12.16	309	P556219	Hydraulic Cartridge
6.84	174	3.94	100	9.00	229	P556700	Hydraulic Cartridge
6.84	174	4.23	107	9.00	229	P164207	Hydraulic Cartridge
6.84	174	4.23	107	9.00	229	P165240	Hydraulic Cartridge
6.89	175	4.33	110	17.71	450	P762921	Hydraulic Cartridge
7.09	180	4.33	110	7.87	200	P502443	Hydraulic Cartridge
7.24	184	1.49	38	2.48	63	P551196	Hydraulic Cartridge
7.24	184	1.49	38	3.23	82	P551189	Hydraulic Cartridge
7.44	189	4.76	121	22.00	559	P569531	Hydraulic Cartridge
7.44	189	4.85	123	18.00	457	P161010	Hydraulic Cartridge
7.44	189	4.85	123	18.00	457	P161632	Hydraulic Cartridge
7.44	189	4.85	123	18.00	457	P164270	Hydraulic Cartridge
7.44	189	4.85	123	22.00	559	P160078	Hydraulic Cartridge
7.44	189	4.85	123	22.00	559	P160896	Hydraulic Cartridge
7.44	189	4.85	123	22.00	559	P163472	Hydraulic Cartridge
7.44	189	4.85	123	22.00	559	P164413	Hydraulic Cartridge
7.44	189	4.85	123	22.00	559	P164707	Hydraulic Cartridge
7.44	189	4.85	123	22.00	559	P165449	Hydraulic Cartridge
7.44	189	4.85	123	22.00	559	P171279	Hydraulic Cartridge
7.44	189	4.85	123	22.00	559	P176417	Hydraulic Cartridge
7.44	189	4.86	123	22.00	559	P176223	Hydraulic Cartridge
7.44	189	4.86	123	22.00	559	P560837	Hydraulic Cartridge
7.95	202	0.06	2	12.99	330	P761354	Hydraulic Cartridge
7.95	202	0.06	2	17.32	440	P761207	Hydraulic Cartridge
7.95	202	6.18	157	25.98	660	P763874	Hydraulic Cartridge
2.76	70	1.38	35	3.35	85	P171654	Hydraulic Cartridge

Hydraulic In-line

Outer Diameter IN	MM	Inlet Size	Overall Length IN	MM	PART NUMBER	PART DESCRIPTION
2.71	69	1.53	5.74	146	P175181	Hydraulic In-Line
3.95	100	0.09	4.72	120	P550478	Hydraulic In-Line
3.95	100	1.06	4.72	120	P550476	Hydraulic In-Line
3.95	100	1.08	4.72	120	P550477	Hydraulic In-Line
3.95	100	1.08	4.72	120	P550488	Hydraulic In-Line
3.95	100	1.62	6.89	175	P550479	Hydraulic In-Line
5.51	140	0.79 x 1.16	12.01	305	P550532	Hydraulic In-Line

Hydraulic Spin-on

Outer Diameter IN	MM	Thread Size	Length IN	MM	PART NUMBER	PART DESCRIPTION
2.99	76	3/4-16	3.39	86	P550426	Hydraulic Spin-on
2.99	76	3/4-16	3.39	86	P550464	Hydraulic Spin-on
3.00	76	3/4-16	3.53	90	P550589	Hydraulic Spin-on
3.05	77	13/16-16	5.50	140	P550486	Hydraulic Spin-on
3.07	73	3/4-20	3.00	76	P550606	Hydraulic Spin-on
3.11	79	2-12	9.52	242	P176107	Hydraulic Spin-on, Duramax®
3.13	80	2	5.52	140	P170308	Hydraulic Spin-on, Duramax®
3.13	80	2-12	5.52	140	P170306	Hydraulic Spin-on, Duramax®
3.13	80	2-12	5.52	140	P170310	Hydraulic Spin-on, Duramax®
3.13	80	2-12	5.52	140	P170312	Hydraulic Spin-on, Duramax®
3.13	80	2-12	5.52	140	P170480	Hydraulic Spin-on, Duramax®
3.13	80	2-12	9.52	242	P170089	Hydraulic Spin-on, Duramax®
3.13	80	2-12	9.52	242	P170307	Hydraulic Spin-on, Duramax®
3.13	80	2-12	9.52	242	P170309	Hydraulic Spin-on, Duramax®
3.13	80	2-12	9.52	242	P170311	Hydraulic Spin-on, Duramax®
3.13	80	2-12	9.52	242	P170313	Hydraulic Spin-on, Duramax®
3.13	80	2-12	9.52	242	P173702	Hydraulic Spin-on, Duramax®
3.55	90	M20 x 1.5	2.60	66	P502407	Hydraulic Spin-on
3.66	923	1 1/12-16	5.78	147	P566919	Hydraulic Spin-on
3.66	93	1 1/2-16	5.78	147	P566920	Hydraulic Spin-on
3.66	923	1 1/2-16	5.78	147	P566921	Hydraulic Spin-on
3.66	923	1 1/2-16	5.78	147	P566922	Hydraulic Spin-on
3.66	923	1 1/2-16	8.06	205	P569380	Hydraulic Spin-on
3.66	923	1 1/2-16	8.06	205	P569381	Hydraulic Spin-on
3.66	923	1 1/2-16	8.06	205	P569382	Hydraulic Spin-on
3.66	923	1 1/2-16	8.06	205	P569383	Hydraulic Spin-on
3.66	923	1 1/2-16	8.06	205	P569402	Hydraulic Spin-on
3.66	93	1 1/8-16	6.48	164	P552409	Hydraulic Spin-on
3.66	93	1 1/8-16	6.81	173	P551348	Hydraulic Spin-on
3.66	93	1-12	3.79	96	P551756	Hydraulic Spin-on
3.66	93	1-12	5.35	136	P551550	Hydraulic Spin-on
3.66	93	1-12	5.35	136	P551553	Hydraulic Spin-on
3.66	93	1-12	5.35	136	P560693	Hydraulic Spin-on
3.66	93	1-12	5.35	136	P560694	Hydraulic Spin-on
3.66	93	1-12	5.35	136	P562198	Hydraulic Spin-on
3.66	93	1-12	5.35	136	P562199	Hydraulic Spin-on
3.66	93	1-12	5.35	136	P563762	Hydraulic Spin-on
3.66	93	1-12	5.35	136	P564967	Hydraulic Spin-on
3.66	93	1-12	5.35	136	P565061	Hydraulic Spin-on
3.66	93	1-12	5.35	136	P565062	Hydraulic Spin-on
3.66	93	1-12	5.35	136	P566040	Hydraulic Spin-on

Specs By Part Type

Hydraulic Spin-on - continued

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
3.66	93 1-12	5.35 136	P566041	Hydraulic Spin-on
3.66	93 1-12	7.87 200	P179089	Hydraulic Spin-on
3.66	93 1-12	7.87 200	P564357	Hydraulic Spin-on
3.66	93 1-12	7.87 200	P565059	Hydraulic Spin-on
3.66	93 1-12	7.87 200	P565060	Hydraulic Spin-on
3.66	93 1-12	7.87 200	P566042	Hydraulic Spin-on
3.66	93 1-12	8.23 209	P552410	Hydraulic Spin-on
3.66	93 1-12	8.60 218	P550255	Hydraulic Spin-on
3.66	93 1-12	8.60 218	P550256	Hydraulic Spin-on
3.66	93 3/4-16	3.66 93	P550940	Hydraulic/Lube Spin-on
3.66	93 3/4-16	5.37 136	P550222	Hydraulic Spin-on
3.66	93 3/4-BSP	5.36 136	P565242	Hydraulic Spin-on
3.66	93 3/4-BSP	5.36 136	P565243	Hydraulic Spin-on
3.66	93 31/32-20	5.35 136	P565149	Hydraulic Spin-on
3.66	93 M20 x 1.5	8.40 214	P502231	Hydraulic Spin-on
3.66	93 M24 x 2	5.50 140	P552476	Hydraulic Spin-on
3.67	93 1-12	3.75 95	P551204	Hydraulic Spin-on
3.67	93 1-12	5.66 144	P551234	Hydraulic Spin-on
3.67	93 1-12	7.35 187	P551780	Hydraulic Spin-on
3.68	93 1-12	8.00 203	P551205	Hydraulic Spin-on
3.68	93 1-12	8.29 211	P550591	Hydraulic Spin-on
3.68	93 2-16	6.89 175	P550445	Hydraulic Spin-on
3.69	94 1 1/4-12	5.37 136	P162766	Hydraulic Spin-on
3.69	94 1 1/4-12	5.37 136	P164348	Hydraulic Spin-on
3.69	94 1 1/4-12	8.69 221	P164351	Hydraulic Spin-on
3.69	94 1 1/4-12	8.69 221	P164352	Hydraulic Spin-on
3.69	94 1 1/4-12	8.76 223	P169083	Hydraulic Spin-on
3.69	94 1 1/8-16	5.26 134	P551323	Hydraulic Spin-on
3.69	94 1 1/8-16	5.37 136	P556005	Hydraulic Spin-on
3.69	94 13/16-16	5.27 134	P552444	Hydraulic Spin-on
3.69	94 2-16	5.56 141	P552850	Hydraulic Spin-on
3.69	94 M24 x 1.5 Male	8.88 226	P550416	Hydraulic Spin-on
3.70	94 1 1/8-16	4.38 111	P550573	Hydraulic Spin-on
3.70	94 1 3/8-12	9.44 240	P163434	Hydraulic Spin-on, Duramax®
3.70	94 1-3/8-12	7.13 181	P764831	Hydraulic Spin-on
3.70	94 3/4-16	4.35 110	P551758	Hydraulic Spin-on
3.70	94 M24 x 1.5	5.96 151	P551757	Hydraulic Spin-on
3.70	94 M24 x1.5	7.12 181	P764729	Hydraulic Spin-on, Duramax®
3.71	94 1 1/4-12	5.97 152	P566050	Hydraulic Spin-on
3.71	94 1 1/4-12	9.67 246	P564042	Hydraulic Spin-on
3.71	94 1 1/8-16	5.59 142	P552472	Hydraulic Spin-on
3.71	94 1 3/8-12	4.47 114	P178619	Hydraulic Spin-on, Duramax®
3.71	94 1 3/8-12	9.44 240	P177047	Hydraulic Spin-on, Duramax®
3.71	94 1-12	5.97 152	P550786	Hydraulic Spin-on
3.71	94 1-3/8-12	4.68 119	P765352	Hydraulic Spin-on
3.71	94 1-3/8-12	5.97 152	P566047	Hydraulic Spin-on
3.71	94 1-3/8-12	9.44 240	P566048	Hydraulic Spin-on
3.71	94 1-3/8-12	9.65 245	P569401	Hydraulic Spin-on
3.71	94 2-16	5.97 152	P174675	Hydraulic Spin-on
3.72	95 1 1/2-16	5.82 148	P167829	Hydraulic Spin-on
3.72	95 1 1/2-16	8.02 204	P169392	Hydraulic Spin-on
3.72	95 2-16	6.81 173	P550701	Hydraulic Spin-on
3.73	95 1 1/8-16	7.02 178	P551779	Hydraulic Spin-on
3.73	95 1-12	5.76 146	P550274	Hydraulic Spin-on

Hydraulic Spin-on - continued

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
3.73	95 1-12	6.83 173	P550695	Hydraulic Spin-on
3.75	95 1 1/2-16	5.82 148	P167830	Hydraulic Spin-on
3.75	95 1 1/2-16	8.00 203	P550705	Hydraulic Spin-on
3.75	95 1 1/2-16	8.02 204	P169393	Hydraulic Spin-on
3.75	95 13/16-16	4.57 116	P551324	Hydraulic Spin-on
3.78	96 1 1/8-16	5.67 144	P765543	Hydraulic Spin-on
3.78	96 1-12	6.69 170	P763956	Hydraulic Spin-on
3.78	96 3/4-BSP	8.22 209	P171608	Hydraulic Spin-on
3.78	96 3/4-BSP	8.22 209	P171609	Hydraulic Spin-on
3.78	96 3/4-BSP	8.22 209	P171610	Hydraulic Spin-on
3.78	96 G 3/4	5.83 149	P171602	Hydraulic Spin-on
3.78	96 G 3/4	5.83 148	P171625	Hydraulic Spin-on
3.78	96 G 3/4	5.86 149	P171604	Hydraulic Spin-on
3.78	96 G 3/4	5.86 149	P171606	Hydraulic Spin-on
3.78	96 M24 x 1.5	6.93 176	P763758	Hydraulic Spin-on
3.81	97 1 3/8-12	9.44 240	P171298	Hydraulic Spin-on, Duramax®
3.81	97 1 3/8-12	9.45 240	P173133	Hydraulic Spin-on
3.81	97 1-12	8.15 207	P763577	Hydraulic Spin-on
3.81	97 13/16-16	4.22 107	P550159	Hydraulic/Lube Spin-on
3.82	97 1 1/4-12	5.97 152	P560725	Hydraulic Spin-on
3.82	97 1 1/8-16	5.95 151	P550542	Hydraulic Spin-on
3.82	97 1 3/8-12	3.98 101	P763558	Hydraulic Spin-on
3.82	97 1 3/8-12	4.47 114	P169078	Hydraulic Spin-on
3.82	97 1 3/8-12	5.97 152	P163315	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	5.97 152	P163405	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	5.97 152	P163412	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	5.97 152	P163419	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	5.97 152	P163428	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	5.97 152	P163496	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	5.97 152	P163542	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	5.97 152	P164375	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	5.97 152	P164381	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	5.97 152	P165335	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	5.97 152	P165354	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	5.97 152	P173736	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	5.97 152	P176565	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	6.22 158	P764668	Hydraulic Spin-on
3.82	97 1 3/8-12	7.08 180	P764367	Hydraulic Spin-on
3.82	97 1 3/8-12	7.88 200	P174552	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	9.41 239	P763535	Hydraulic Spin-on
3.82	97 1 3/8-12	9.44 240	P163322	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	9.44 240	P163323	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	9.44 240	P163324	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	9.44 240	P163425	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	9.44 240	P163555	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	9.44 240	P163558	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	9.44 240	P163567	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	9.44 240	P164056	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	9.44 240	P164059	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	9.44 240	P164378	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	9.44 240	P164384	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	9.44 240	P165185	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	9.44 240	P165332	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	9.44 240	P165338	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	9.44 240	P167590	Hydraulic Spin-on, Duramax®

Hydraulic Spin-on - continued

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
3.82	97 1 3/8-12	9.44 240	P170950	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	9.44 240	P173737	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	9.44 240	P176566	Hydraulic Spin-on, Duramax®
3.82	97 1 3/8-12	9.44 240	P560584	Hydraulic Spin-on, Duramax®
3.82	97 1-12	7.01 178	P550229	Hydraulic Spin-on
3.82	97 1-12	8.23 209	P550230	Hydraulic Spin-on
3.82	97 13/16-16	5.95 151	P763761	Hydraulic Spin-on
3.82	97 13/16-16	5.97 152	P179342	Hydraulic Spin-on, Duramax®
3.82	97 2-16	7.09 180	P765075	Hydraulic Spin-on
3.82	97 3/4-16	5.56 141	P551327	Hydraulic Spin-on
3.82	97 7/8-14	3.93 100	P173739	Hydraulic Spin-on, Duramax®
3.82	97 7/8-14	5.97 152	P173738	Hydraulic Spin-on
3.82	97 M22 X 1.5	5.94 151	P765663	Hydraulic Spin-on
3.82	97 M23 x 1.5	4.45 113	P761108	Hydraulic Spin-on, Duramax®
3.86	98 1 1/2-16	9.50 241	P551235	Hydraulic Spin-on
3.86	98 3/4-14	5.80 147	P550268	Hydraulic Spin-on
3.87	98 1 1/8-16	8.15 207	P552483	Hydraulic Spin-on
3.88	99 1 5/16-12	5.75 146	P165243	Hydraulic Spin-on
3.88	99 3/4-16	3.80 97	P550210	Hydraulic/Lube Spin-on
4.25	108	7.20 183	P764638	Hydraulic Spin-on
4.25	108 M40 X 2	9.06 230	P763987	Hydraulic Spin-on
4.28	109 1 1/8-16	8.09 206	P552452	Hydraulic Spin-on
4.57	116 1 3/8-12	11.57 294	P763529	Hydraulic Spin-on
4.59	117 1 3/4-12	11.63 295	P567580	Hydraulic Spin-on
4.60	117 1 3/4-12	14.24 362	P564468	Hydraulic Spin-on, Duramax®
4.60	117 1-3/4-12	11.65 296	P566049	Hydraulic Spin-on
4.63	118 1 1/4 BSP	6.27 159	P176324	Hydraulic Spin-on
4.63	118 1 1/4 BSP	11.27 286	P176325	Hydraulic Spin-on
4.65	118 1 1/2-16	6.29 160	P550755	Hydraulic Spin-on
4.66	118 1 1/4-11 BSP	6.22 158	P565245	Hydraulic Spin-on
4.67	119 1 5/16-12	10.30 262	P551227	Hydraulic Spin-on
4.76	121 1 1/2-16	10.66 271	P560514	Hydraulic Spin-on
4.76	121 1 1/2-16	10.66 271	P562204	Hydraulic Spin-on
4.76	121 1 1/2-16	10.66 271	P562205	Hydraulic Spin-on
4.76	121 1 3/8-12	11.61 295	P764737	Hydraulic Spin-on
4.77	121 1 3/4-12	7.60 193	P176207	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	7.60 193	P176208	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	11.62 295	P176779	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	11.63 295	P165569	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	11.63 295	P165659	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	11.63 295	P165672	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	11.63 295	P165675	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	11.63 295	P165705	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	11.63 295	P170906	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	11.63 295	P171273	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	11.63 295	P171274	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	11.63 295	P171275	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	11.63 295	P171276	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	11.63 295	P173521	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	11.63 295	P173943	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	11.63 295	P176567	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	11.63 295	P179075	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	11.63 295	P179518	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	11.63 295	P561013	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	12.64 321	P179763	Hydraulic Spin-on, Duramax®

Hydraulic Spin-on - continued

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
4.77	121 1 3/4-12	14.24 362	P170546	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	14.24 362	P170949	Hydraulic Spin-on, Duramax®
4.77	121 1 3/4-12	14.24 362	P173789	Hydraulic Spin-on, Duramax®
4.77	121 1 3/8-12	11.63 295	P173689	Hydraulic Spin-on, Duramax®
4.77	121 1 3/8-12	11.63 295	P179343	Hydraulic Spin-on, Duramax®
4.78	121 1 1/2-16	10.66 271	P167945	Hydraulic Spin-on
4.78	121 1 1/2-16	10.66 271	P563767	Hydraulic Spin-on
4.78	121 1 1/2-16	10.66 271	P564041	Hydraulic Spin-on
4.78	121 1 1/2-16	10.66 271	P566044	Hydraulic Spin-on
4.78	121 1 1/2-16	10.66 271	P566046	Hydraulic Spin-on
4.78	121 1 1/2-16	10.93 278	P557222	Hydraulic Spin-on
4.80	122 1 1/2-16	11.75 298	P550592	Hydraulic Spin-on
4.84	123 1 1/2-16	11.41 290	P550415	Hydraulic Spin-on
4.84	123 1 1/2-16	11.41 290	P550417	Hydraulic Spin-on
4.86	123 1 1/2-16	6.66 169	P562200	Hydraulic Spin-on
4.86	123 1 1/2-16	6.66 169	P562202	Hydraulic Spin-on
4.86	123 1 1/2-16	6.66 169	P562203	Hydraulic Spin-on
4.86	123 1 1/2-16	6.66 169	P562207	Hydraulic Spin-on
4.86	123 1 1/2-16	7.85 199	P560653	Hydraulic Spin-on
4.86	123 1 1/2-16	10.66 271	P562208	Hydraulic Spin-on
4.87	124 1 1/2-16	5.00 127	P566043	Hydraulic Spin-on
4.87	124 1 1/2-16	6.66 169	P167944	Hydraulic Spin-on
4.87	124 1 1/2-16	6.66 169	P566045	Hydraulic Spin-on
4.87	124 1 5/16-12	10.23 260	P550223	Hydraulic Spin-on
4.89	124 1 1/2-16	8.22 209	P551242	Hydraulic Spin-on
4.91	125 1 1/2-16	6.66 169	P550388	Hydraulic Spin-on
4.91	125 1 1/2-16	7.06 179	P550387	Hydraulic Spin-on
4.96	126 1 1/4 BSP	9.25 235	P171621	Hydraulic Spin-on
4.96	126 1 1/4-12	7.04 179	P171616	Hydraulic Spin-on
4.96	126 G 1 1/4	7.05 179	P171613	Hydraulic Spin-on
4.96	126 G 1 1/4	9.29 236	P171640	Hydraulic Spin-on
4.99	127 1 1/2-16	8.22 209	P551244	Hydraulic Spin-on
4.99	127 M48 x 2	6.85 174	P502382	Hydraulic Spin-on
5.00	127	11.50 292	P550615	Hydraulic Spin-on
5.00	127 1 1/2-16	6.85 174	P550386	Hydraulic Spin-on
5.00	127 1 1/2-16	6.87 174	P550590	Hydraulic Spin-on
5.00	127 1 1/2-16	8.22 209	P552461	Hydraulic Spin-on
5.00	127 1 1/2-16	10.66 271	P550250	Hydraulic Spin-on
5.00	127 1 1/2-16	10.66 271	P550251	Hydraulic Spin-on
5.00	127 1 1/2-16	10.66 271	P550252	Hydraulic Spin-on
5.00	127 1 1/2-16	11.71 298	P550320	Hydraulic Spin-on
5.00	127 3-8	8.81 224	P162205	Hydraulic Spin-on
5.00	127 3-8	12.25 311	P163435	Hydraulic Spin-on
5.03	128 1 1/4-12	7.04 179	P173062	Hydraulic Spin-on
5.03	128 G 1 1/4	7.04 179	P171635	Hydraulic Spin-on
5.04	128 1 1/2-16	6.87 174	P550584	Hydraulic Spin-on
5.04	128 1 1/2-16	10.66 271	P561183	Hydraulic Spin-on
5.04	128 1 1/4 BSP	7.00 178	P550148	Hydraulic Spin-on
5.04	128 1 1/4-12	9.29 236	P171620	Hydraulic Spin-on
5.04	128 M42 x 2	3.94 100	P764260	Hydraulic Spin-on
5.04	128 M45 x 2	7.09 180	P764259	Hydraulic Spin-on
5.06	129 1 1/2-16	6.63 169	P550275	Hydraulic Spin-on
5.06	129 1 1/2-16	10.63 270	P550276	Hydraulic Spin-on
5.06	129 1 1/2-16	10.66 271	P167796	Hydraulic Spin-on
5.08	129 1 1/2-16	6.66 169	P165875	Hydraulic Spin-on

Specs By Part Type

Hydraulic Spin-on - continued

Outer Diameter IN	Thread Size	Length IN	Length MM	PART NUMBER	PART DESCRIPTION
5.08	129 1 1/2-16	6.66	169	P165877	Hydraulic Spin-on
5.08	129 1 1/2-16	6.66	169	P165879	Hydraulic Spin-on
5.08	129 1 1/2-16	6.66	169	P167162	Hydraulic Spin-on
5.08	129 1 1/2-16	6.66	169	P169430	Hydraulic Spin-on
5.08	129 1 1/2-16	10.66	271	P165762	Hydraulic Spin-on
5.08	129 1 1/2-16	10.66	271	P165876	Hydraulic Spin-on
5.08	129 1 1/2-16	10.66	271	P165878	Hydraulic Spin-on
5.08	129 1 1/2-16	10.66	271	P165880	Hydraulic Spin-on
5.08	129 1 1/2-16	10.66	271	P167832	Hydraulic Spin-on
5.08	129 1 1/2-16	10.66	271	P169077	Hydraulic Spin-on
5.08	129 1 1/2-16	10.66	271	P169084	Hydraulic Spin-on
5.08	129 G 1 1/4	7.05	179	P763835	Hydraulic Spin-on
5.35	136 1 1/2-16	12.04	306	P763668	Hydraulic Spin-on
5.35	136 1 1/2-16	12.04	306	P764409	Hydraulic Spin-on
5.35	136 1 3/4-12	6.89	175	P765662	Hydraulic Spin-on
5.35	136 1 3/4-16	9.57	243	P502224	Hydraulic Spin-on
5.35	136 1 3/4-16	9.61	244	P765704	Hydraulic Spin-on
5.50	140 1 1/2-16	7.00	178	P550605	Hydraulic Spin-on

Hydraulic Strainers - continued

Outer Diameter IN	Thread Size	Length IN	Length MM	PART NUMBER	PART DESCRIPTION
1.90	48 1 3/8 NPT	4.20	107	P562235	Strainer
1.90	48 1/2 NPT	4.30	109	P562240	Strainer
1.90	48 3/8-18	2.50	64	P562221	Strainer
2.05	52 G2	3.03	77	P171861	Strainer
2.12	54 1 5/8-12	9.04	230	P562251	Strainer
2.12	54 1 5/8-12	9.04	230	P562252	Strainer
2.12	54 Outer 2 NPTM, Inner 1-1/4 NPT	9.04	230	P562266	Strainer
2.12	54 Outer 2 NPTM, Inner 1-1/4 NPT	9.04	230	P562267	Strainer
2.12	54 Outer 2 NPTM, Inner 1-1/4 NPT	9.04	230	P562269	Strainer
2.63	67 1 NPT	5.35	136	P169014	Strainer
2.63	67 1 NPT	5.35	136	P173911	Strainer
2.63	67 1/2 NPT	3.10	79	P169012	Strainer
2.63	67 3/4 NPT	3.55	90	P169013	Strainer
2.63	67 3/4-14	3.55	90	P173910	Strainer

Hydraulic Strainers

Inner Diameter IN	Length IN	Length MM	PART NUMBER	PART DESCRIPTION	
0.71	18	0.22	5	P161269	Hydraulic Strainer

Outer Diameter IN	Thread Size	Length IN	Length MM	PART NUMBER	PART DESCRIPTION
0.87	22 Outer 3/4 NPTM, Inner 3/8 NPT	4.00	102	P562270	Strainer
1.17	30 3/4-16	5.34	136	P562253	Strainer
1.17	30 3/4-16	5.34	136	P562254	Strainer
1.17	30 Outer 1 NPTM, Inner 1/2 NPT	5.34	136	P562274	Strainer
1.17	30 Outer 1 NPTM, Inner 1/2 NPT	5.34	136	P562275	Strainer
1.36	35 1 1/16-12	8.17	208	P562247	Strainer
1.36	35 1 1/16-12	8.17	208	P562248	Strainer
1.36	35 Outer 1-1/4 NPTM, Inner 3 NPT	8.17	208	P562257	Strainer
1.36	35 Outer 1-1/4 NPTM, Inner 3 NPT	8.17	208	P562259	Strainer
1.36	35 Outer 1-1/4 NPTM, Inner 3/4 NPT	8.17	208	P562256	Strainer
1.63	41 M16 X 1.5	2.48	63	P561534	Hydraulic Cartridge
1.63	41 M16 X 1.5	2.99	76	P561541	Hydraulic Cartridge
1.63	41 M16 X 1.5	2.99	76	P561542	Hydraulic Cartridge
1.66	35 1 5/16-12	8.20	208	P562249	Strainer
1.66	35 1 5/16-12	8.20	208	P562250	Strainer
1.66	42 Outer 1-1/2 NPTM, Inner 1 NPT	8.20	208	P562260	Strainer
1.66	42 Outer 1-1/2 NPTM, Inner 1 NPT	8.20	208	P562264	Strainer
1.66	42 Outer 1-1/2 NPTM, Inner 1 NPT	8.20	208	P562265	Strainer

Outer Diameter IN	Inner Diameter IN	Length IN	Length MM	PART NUMBER	PART DESCRIPTION		
2.68	68	1.50	38	8.19	208	P761040	Strainer

Outer Diameter IN	Inlet Diameter IN	Length IN	Length MM	PART NUMBER	PART DESCRIPTION		
2.70	68	1.60	41	5.60	142	P562226	Strainer

Outer Diameter IN	Thread Size	Length IN	Length MM	PART NUMBER	PART DESCRIPTION
2.70	68 1 NPT	4.30	109	P562244	Strainer
2.70	68 1 NPT	5.60	142	P562226	Strainer
2.70	68 1 NPT	5.60	142	P562227	Strainer
2.70	68 3/4-14 NPT	4.30	109	P562245	Strainer
2.70	68 3/4-14 NPT	4.30	109	P562246	Strainer

Outer Diameter IN	Inner Diameter IN	Length IN	Length MM	PART NUMBER	PART DESCRIPTION		
2.76	70	1.10	28	5.75	146	P175142	Strainer

Outer Diameter IN	Inlet Diameter IN	Length IN	Length MM	PART NUMBER	PART DESCRIPTION		
2.91	74	0.71	18	3.94	100	P176903	Strainer

Outer Diameter IN	Thread Size	Length IN	Length MM	PART NUMBER	PART DESCRIPTION
2.95	75 1 NPT	5.16	131	P175336	Strainer
2.95	75 3/4 NPT	3.27	83	P175334	Strainer
2.95	75 G2	7.09	180	P177402	Hydraulic Cartridge
2.95	75 GAS 1	7.09	180	P763081	Strainer
3.00	76 Outer 3 NPTM, Inner: 2 NPT	9.70	246	P562271	Strainer
3.00	76 Outer 3 NPTM, Inner: 2 NPT	9.70	246	P562272	Strainer
3.00	76 Outer 3 NPTM, Inner: 2 NPT	9.70	246	P562273	Strainer

Hydraulic Strainers - continued

Outer Diameter IN MM	Inlet Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
3.15 80	2.01 51	7.01 178	P176904	Strainer

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
3.31 84	G1-1/2	5.12 130	P764370	Strainer
3.31 84	G1-1/2	5.12 130	P764371	Strainer
3.36 86	G 2	10.15 258	P763954	Hydraulic Cartridge
3.38 86	1 1/2 NPT	8.01 203	P169016	Strainer
3.38 86	1 1/2 NPT	8.01 203	P173913	Strainer
3.38 86	1 1/4 NPT	6.85 174	P169015	Strainer
3.38 86	1 1/4 NPT	6.85 174	P173912	Strainer
3.39 86	1 1/2 NPT	5.12 130	P175340	Strainer
3.40 86	1 1/2 NPT	5.60 142	P562232	Strainer
3.40 86	1 1/2 NPT	5.60 142	P562233	Strainer
3.40 86	1 1/2-11 BSP	12.20 310	P550825	Hydraulic Strainer
3.40 86	1 1/4 NPT	5.60 142	P562228	Strainer
3.40 86	1 1/4 NPT	5.60 142	P562229	Strainer
3.40 86	1 1/4 NPT	5.60 142	P562231	Strainer
3.74 95	1 1/4 NPT	6.77 172	P175337	Strainer
3.74 95	1 NPT	3.27 83	P175335	Strainer
3.74 95	1-1/2 NPT	7.99 203	P175338	Hydraulic Cartridge
3.74 95	G 1-1/4	7.24 184	P762808	Strainer
3.90 99	G2	8.62 219	P760173	Hydraulic Cartridge
3.94 100	1 1/2 NPT	9.85 250	P169017	Strainer
3.94 100	1 1/2 NPT	9.85 250	P173914	Strainer
3.94 100	2 NPT	9.85 250	P169018	Strainer
3.94 100	2 NPT	9.85 250	P173915	Strainer
3.98 101	G2	8.62 219	P760175	Strainer
4.00 102	1 1/2 NPT	8.00 203	P562236	Strainer
4.00 102	1 1/2 NPT	8.00 203	P562237	Strainer
4.00 102	1 1/2 NPT	10.00 254	P562222	Strainer
4.00 102	2 NPT	10.40 264	P562238	Strainer
4.00 102	2 NPT	10.40 264	P562239	Strainer
4.00 102	Outer 4 NPTM, Inner 3 NPT	11.30 287	P562255	Strainer

Outer Diameter IN MM	Inlet Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
5.12 130	4.00 102	11.80 300	P562211	Strainer
5.12 130	4.00 102	11.80 300	P562212	Strainer

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
5.12 130	2 1/2 NPT	10.10 257	P169019	Strainer
5.12 130	2 1/2 NPT	10.10 257	P173916	Strainer
5.12 130	3 NPT	11.78 299	P169020	Strainer
5.12 130	3 NPT	11.78 299	P173917	Strainer
5.12 130	3 NPT	11.80 300	P562211	Strainer
5.12 130	3 NPT	11.80 300	P562212	Strainer
5.20 132	2 1/2 NPT	8.50 216	P562242	Strainer
5.20 132	2 1/2 NPT	8.50 216	P562243	Strainer
5.20 132	3-8	11.50 292	P562223	Strainer
5.20 132	3-8	11.50 292	P562224	Strainer
5.20 132	3-8	11.50 292	P562225	Strainer
5.51 140	2 1/2 NPT	11.85 301	P175342	Strainer

Hydraulic Strainers - continued

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
5.51 140	2 NPT	8.07 205	P175339	Strainer
5.51 140	3 NPT	11.85 301	P175343	Strainer
5.51 140	G2	8.66 220	P175466	Strainer
5.51 140	G3	12.48 317	P171910	Strainer

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
5.90 150	3.43 87	5.32 135	P502244	Hydraulic Strainer

Outer Diameter IN MM	Inlet Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
8.10 206	4.00 102	11.30 287	P562213	Strainer
8.10 206	5.00 127	15.00 381	P562214	Strainer

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
8.10 206	3 NPT	11.30 287	P562213	Strainer
8.10 206	4 NPT	15.00 381	P562214	Strainer

Lube Cartridge

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
1.61 41	0.97 25	1.29 33	P502380	Lube Cartridge
1.97 50	0.46 12	1.48 38	P552421	Lube Cartridge Full Flow
2.00 51	0.81 21	2.12 54	P555400	Lube Cartridge Full Flow
2.09 53	0.77 20	3.86 98	P552361	Lube Cartridge Full Flow
2.30 58	0.44 11	4.63 118	P551294	Lube Cartridge Full Flow
2.35 60	0.70 18	3.90 99	P550396	Lube Cartridge Full Flow
2.36 60	0.63 16	3.94 100	P550744	Lube Cartridge
2.44 62	0.86 21	6.20 157	P550521	Lube Cartridge Full Flow
2.48 63	1.08 27	3.53 90	P552419	Lube Cartridge Full Flow
2.50 65	1.22 32	4.53 116	P550564	Lube Cartridge Full Flow
2.50 64	1.22 31	5.91 150	P550633	Lube Cartridge
2.59 66	1.22 31	4.52 115	P550798	Lube Cartridge
2.75 70	1.10 28	4.56 116	P550988	Lube Cartridge
2.75 70	1.31 33	3.33 85	P551291	Lube Cartridge Full Flow
2.75 70	1.31 33	6.00 152	P550183	Lube Cartridge Full Flow
2.79 71	1.22 31	3.74 95	P550797	Lube Cartridge
2.83 72	0.83 21	4.47 114	P550184	Lube Cartridge Full Flow
2.85 72	1.30 33	5.39 137	P502193	Lube Cartridge Full Flow
2.85 72	1.30 33	5.39 137	P550052	Lube Cartridge Full Flow
2.87 73	0.93 24	4.02 102	P550978	Lube Cartridge
2.90 74	1.12 28	5.53 140	P552382	Lube Cartridge Full Flow
2.97 75	1.07 27	5.64 143	P551296	Lube Cartridge Full Flow
2.98 76	0.78 20	4.07 103	P551279	Lube Cartridge Full Flow
3.03 77	1.02 26	8.19 208	P550429	Lube Cartridge Full Flow
3.09 79	1.03 26	1.56 40	P552402	Lube Cartridge Full Flow
3.11 79	0.75 19	9.37 238	P550311	Lube Cartridge Full Flow
3.11 79	1.38 35	9.04 230	P550165	Lube Cartridge Full Flow
3.11 79	1.56 40	5.35 136	P502203	Lube Cartridge Full Flow
3.12 79	1.83 46	9.00 229	P550816	Lube Cartridge Full Flow
3.22 82	1.50 38	7.89 200	P550451	Lube Cartridge
3.24 83	1.41 36	6.65 169	P550563	Lube Cartridge Full Flow
3.25 83		7.13 181	P550528	Lube Cartridge Full Flow

Specs By Part Type

Lube Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
3.26 83	0.48 12	7.58 193	P550181	Lube Cartridge
3.26 83	2.20 56	7.59 193	P550763	Lube Cartridge Full Flow
3.27 83		5.39 137	P550766	Lube Cartridge Full Flow
3.27 83	0.83 21	5.16 131	P550767	Lube Cartridge Full Flow
3.27 83	0.83 21	7.60 193	P550764	Lube Cartridge Full Flow
3.27 83	0.94 24	5.12 130	P550354	Lube Cartridge Full Flow
3.27 83	1.49 38	6.36 161	P552422	Lube Cartridge Full Flow
3.27 83	1.59 40	5.80 147	P550768	Lube Cartridge Full Flow
3.27 83	2.00 51	8.24 209	P550761	Lube Cartridge Full Flow
3.30 84	0.93 24	7.50 190	P550315	Lube Cartridge Full Flow
3.31 84	0.65 17	5.63 143	P550015	Lube Cartridge Full Flow
3.31 84	0.75 19	4.21 107	P550220	Lube Cartridge Full Flow
3.34 85	1.62 41	6.50 165	P555088	Lube Cartridge Full Flow
3.35 85	0.90 23	5.08 129	P502189	Lube Cartridge Full Flow
3.35 85	1.57 40	5.63 143	P502194	Lube Cartridge Full Flow
3.37 86	1.13 29	4.25 108	P552465	Lube Cartridge
3.47 88	0.43 11	7.61 193	P552471	Lube Cartridge Full Flow
3.47 89	0.94 24	5.53 141	P550186	Lube Cartridge
3.50 89	1.34 34	3.78 96	P551285	Lube Cartridge Full Flow
3.52 89	0.69 18	4.16 106	P550179	Lube Cartridge
3.54 90	1.92 49	4.09 104	P502202	Lube Cartridge Full Flow
3.56 90	1.28 33	5.69 145	P550141	Lube Cartridge Full Flow
3.56 90	1.28 33	8.44 214	P550190	Lube Cartridge Full Flow
3.58 91	0.47 12	6.42 163	P550361	Lube Cartridge Combination
3.59 91	1.28 33	6.37 162	P552415	Lube Cartridge Full Flow
3.62 92	0.51 13	5.83 148	P550359	Lube Cartridge Full Flow
3.62 92	0.69 18	4.33 110	P502179	Lube Cartridge Full Flow
3.62 92	0.69 18	6.30 160	P502180	Lube Cartridge Full Flow
3.63 92	1.31 33	7.88 200	P552375	Lube Cartridge Sock
3.74 95	1.91 49	7.05 179	P502225	Lube Cartridge Full Flow
3.75 95	1.04 26	5.94 151	P550092	Lube Cartridge Full Flow
3.78 96	1.10 28	5.96 151	P552458	Lube Cartridge Full Flow
3.78 96	1.10 28	6.09 155	P552455	Lube Cartridge Full Flow
3.82 97	0.55 14	4.57 116	P550663	Lube Cartridge
3.82 97	1.35 34	4.41 112	P550185	Lube Cartridge Full Flow
3.82 97	1.73 44	5.74 146	P550076	Lube Cartridge
3.84 98		7.00 178	P552206	Lube Cartridge
3.87 98	0.49 13	4.58 116	P550287	Lube Cartridge
3.87 98	0.64 16	4.58 116	P550286	Lube Cartridge
3.89 99	0.66 17	5.67 144	P550074	Lube Cartridge
3.91 99	0.57 15	4.37 111	P550203	Lube Cartridge Full Flow
3.93 100	0.87 22	4.81 122	P551475	Lube Cartridge Full Flow
3.94 100	1.56 40	7.19 183	P502206	Lube Cartridge Full Flow
3.94 100	1.73 44	7.24 184	P550077	Lube Cartridge Full Flow
3.97 101	1.20 30	9.21 234	P502183	Lube Cartridge Full Flow
3.98 101	0.65 17	7.68 195	P550070	Lube Cartridge Full Flow
3.98 101	1.10 28	9.25 235	P550068	Lube Cartridge Full Flow
3.98 101	1.22 31	7.64 194	P550069	Lube Cartridge Full Flow
3.98 101	1.27 32	2.78 71	P551761	Lube Cartridge Full Flow
3.98 101	1.63 41	9.29 236	P550484	Lube Cartridge Full Flow
4.02 102	0.55 14	8.00 203	P550117	Lube Cartridge
4.02 102	1.76 45	9.92 252	P550629	Lube Cartridge
4.03 102	0.66 17	4.67 119	P551277	Lube Cartridge
4.05 103		7.04 179	P502353	Lube Cartridge
4.06 103		5.80 146	P550793	Lube Cartridge

Lube Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
4.06 103	1.62 41	5.50 140	P553335	Lube Cartridge Full Flow
4.09 102	0.55 14	5.00 127	P550170	Lube Cartridge Full Flow
4.09 104	0.55 14	5.00 127	P550171	Lube Cartridge
4.09 104	0.59 15	5.67 144	P550062	Lube Cartridge Full Flow
4.09 104	1.26 32	6.69 170	P550080	Lube Cartridge Full Flow
4.09 104	1.26 32	7.09 180	P550379	Lube Cartridge Full Flow
4.09 104	1.92 49	4.05 103	P502373	Lube Cartridge
4.09 104	1.92 49	6.30 160	P550010	Lube Cartridge Full Flow
4.09 104	1.92 49	7.05 179	P502365	Lube Cartridge
4.09 104	1.93 49	7.08 180	P502387	Lube Cartridge
4.09 104	1.93 49	7.08 180	P502389	Lube Cartridge
4.10 104	0.59 15	9.13 232	P550059	Lube Cartridge Full Flow
4.17 106	0.59 15	4.17 106	P550017	Lube Cartridge Full Flow
4.17 106	0.59 15	7.30 185	P550018	Lube Cartridge Full Flow
4.25 108	1.25 32	16.38 416	P552427	Lube Cartridge Sock
4.25 108	1.67 42	32.00 813	P550614	Lube Cartridge
4.29 109		7.44 189	P552231	Lube Cartridge
4.30 109	1.45 37	8.90 226	P550132	Lube Cartridge Full Flow
4.33 110	0.75 19	7.56 192	P550378	Lube Cartridge Full Flow
4.33 110	2.04 52	8.11 206	P502205	Lube Cartridge Full Flow
4.37 111	3.62 92	9.56 243	P552469	Lube Cartridge Full Flow
4.38 111	1.44 37	5.75 146	P550147	Lube Cartridge Sock
4.41 112	2.22 56	5.91 150	P550630	Lube Cartridge Full Flow
4.41 112	2.67 68	8.66 220	P550661	Lube Cartridge
4.44 113	2.31 59	8.66 220	P550812	Lube Cartridge Full Flow
4.47 114	1.75 44	9.06 230	P558462	Lube Cartridge Full Flow
4.48 114	2.84 72	10.83 275	P502184	Lube Cartridge Full Flow
4.50 114	1.45 37	16.00 406	P552428	Lube Cartridge Sock
4.50 114	1.56 39	31.00 787	P550807	Lube Cartridge
4.53 115	2.24 57	7.68 195	P554925	Lube Cartridge Full Flow
4.57 116	2.12 54	12.68 322	P550071	Lube Cartridge Full Flow
4.59 117	0.75 19	4.87 124	P551014	Lube Cartridge Full Flow
4.59 117	2.25 57	7.00 178	P550174	Lube Cartridge Full Flow
4.61 117	1.89 48	8.70 221	P502358	Lube Cartridge
4.64 118	1.78 45	11.77 299	P550453	Lube Cartridge
4.70 119	2.16 55	7.60 193	P558425	Lube Cartridge Full Flow
4.72 120		8.07 205	P502332	Lube Cartridge
4.72 120	2.24 57	7.95 202	P550820	Lube Cartridge
4.76 121	0.56 14	10.37 264	ELF7690	Lube Cartridge
4.76 121	1.50 38	7.44 189	P550613	Lube Cartridge Full Flow
4.76 121	2.20 56	5.67 144	P550765	Lube Cartridge Full Flow
4.76 121	2.20 56	9.60 244	P550041	Lube Cartridge Full Flow
4.76 121	2.24 57	9.76 248	P550769	Lube Cartridge Full Flow
4.80 122	0.67 17	8.62 219	P502190	Lube Cartridge Full Flow
4.80 122	0.67 17	9.80 249	P502191	Lube Cartridge Full Flow
4.81 122	0.66 17	8.86 225	P550058	Lube Cartridge
4.84 123	0.79 20	5.43 138	P502186	Lube Cartridge Full Flow
4.84 123	2.25 57	8.86 225	P553925	Lube Cartridge Full Flow
4.92 125	0.61 16	6.33 161	P502370	Lube Cartridge
4.92 125	0.61 16	8.20 208	P502368	Lube Cartridge Kit
4.92 125	2.28 58	5.64 144	P502369	Lube Cartridge Full Flow
5.00 127	0.69 18	7.88 200	P551781	Lube Cartridge
5.00 127	0.77 19	8.22 209	P552462	Lube Cartridge Full Flow
5.00 127	1.50 38	9.62 244	P550516	Lube Cartridge Full Flow
5.00 127	2.51 64	8.29 211	P550492	Lube Cartridge

Lube Cartridge - continued

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
5.02 128	2.26 57	5.59 142	P550066	Lube Cartridge Full Flow
5.04 128	0.61 15	6.30 160	P550021	Lube Cartridge Full Flow
5.04 128	0.79 20	7.91 201	P550380	Lube Cartridge Full Flow
5.04 128	2.22 56	9.10 231	P550087	Lube Cartridge Full Flow
5.06 127	0.07 2	12.13 305	P552377	Lube Cartridge Full Flow
5.06 129	2.94 75	9.00 229	P552380	Lube Cartridge Full Flow
5.07 129	3.34 85	9.00 229	P166481	Lube Cartridge Full Flow
5.08 129	3.37 86	8.94 227	P550485	Lube Cartridge Full Flow
5.11 130	0.67 17	7.46 190	P502352	Lube Cartridge
5.12 130	0.59 15	9.17 233	P550034	Lube Cartridge Full Flow
5.12 130	0.59 15	11.79 299	P550065	Lube Cartridge Kit
5.12 130	0.62 16	6.37 162	P502405	Lube Cartridge
5.51 140	0.67 17	8.14 207	P502390	Lube Cartridge
5.51 140	1.34 34	7.60 193	P502200	Lube Cartridge Full Flow
6.01 153	3.50 89	14.50 368	P551336	Lube Cartridge Full Flow
6.30 160	0.28 7	5.20 132	P551345	Lube Cartridge
6.30 160	0.67 17	10.51 267	P550423	Lube Cartridge
6.42 163	1.47 37	30.08 764	P550910	Lube Cartridge
6.50 165		11.02 280	P550382	Lube Cartridge
6.50 165	1.47 37	29.38 746	P550636	Lube Cartridge
6.50 165	1.69 43	7.56 192	P551344	Lube Cartridge
6.50 165	6.50 165	13.00 330	P550381	Lube Cartridge
6.50 165	11.02 280	12.95 329	P550384	Lube Cartridge

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
6.50 165	3/8-24	8.75 222	P552041	Lube Cartridge

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
6.75 171	2.47 63	17.75 451	P552414	Lube Cartridge Sock
7.42 188	2.63 67	10.00 254	P557500	Lube Cartridge Full Flow
7.42 188	3.43 87	13.38 340	P554136	Lube Cartridge Full Flow
7.64 194	4.65 118	6.71 170	P502223	Lube Cartridge Full Flow
7.72 196	0.86 22	10.06 256	P550500	Lube Cartridge
7.72 196	0.86 22	15.06 383	P550750	Lube Cartridge
7.72 196	0.86 22	15.06 383	P550751	Lube Cartridge
7.87 200	0.86 22	10.03 255	P550493	Lube Cartridge

Lube Spin-on

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
2.56 65	3/4-16	2.80 71	P502015	Lube Spin-on Full Flow
2.56 65	3/4-16	2.80 71	P550534	Lube Spin-on Full Flow
2.56 65	3/4-16	3.35 85	P502070	Lube Spin-on Full Flow
2.56 65	3/4-16	3.54 90	P502019	Lube Spin-on Full Flow
2.68 68	3/4-16	2.56 65	P502024	Lube Spin-on Full Flow
2.68 68	M20 x 1.5	2.56 65	P502062	Lube Spin-on Full Flow
2.68 68	M20 x 1.5	2.56 65	P502067	Lube Spin-on Full Flow
2.68 68	M20 x 1.5	3.34 85	P502007	Lube Spin-on Full Flow
2.68 68	M20 x 1.5	3.35 85	P502047	Lube Spin-on Full Flow
2.68 68	M20 x 1.5	3.35 85	P502057	Lube Spin-on Bypass
2.68 68	M20 x 1.5	3.35 85	P502063	Lube Spin-on Full Flow
2.69 68	M20 x 1.5	2.78 71	P551783	Lube Spin-on Full Flow

Lube Spin-on - continued

Outer Diameter IN MM	Thread Size	Length IN MM	PART NUMBER	PART DESCRIPTION
2.91 74	3/4-16	3.31 84	P502016	Lube Spin-on Full Flow
2.92 74	13/16-16	4.83 123	P550598	Lube Spin-on Full Flow
2.92 74	3/4-16	3.40 86	P552430	Lube Spin-on Full Flow
2.92 74	3/4-16	4.53 115	P551763	Lube Spin-on Full Flow
2.96 75	13/16-16	4.45 113	P550505	Lube Spin-on Full Flow
2.96 75	M20 x 1.5	3.40 86	P552849	Lube Spin-on Full Flow
2.99 76	13/16-16	3.41 87	P551307	Lube Spin-on Full Flow
2.99 76	3/4-16	4.72 120	P554770	Lube Spin-on Full Flow
2.99 76	M20 x 1.5	3.44 88	P502050	Lube Spin-on Full Flow
3.00 76	13/16-16	4.74 120	P550045	Lube Spin-on Full Flow
3.00 76	3/4-16	3.40 86	P550335	Lube Spin-on Full Flow
3.00 76	3/4-16	3.42 87	P551251	Lube Spin-on Full Flow
3.00 76	3/4-16	3.46 88	P502107	Lube Spin-on Full Flow
3.00 76	3/4-16	4.74 120	P550400	Lube Spin-on Full Flow
3.00 76	3/4-16	5.53 140	P554408	Lube Spin-on Full Flow
3.00 76	M18 x 1.5	3.40 86	P550047	Lube Spin-on Full Flow
3.00 76	M18 x 1.5	5.09 129	P550051	Lube Spin-on Full Flow
3.00 76	M20 x 1.5	2.52 64	P502010	Lube Spin-on Full Flow
3.00 76	M22 x 1.5	3.26 83	P550794	Lube Spin-on Full Flow
3.12 79	M20 x 1.5	3.87 98	P555522	Lube Spin-on Full Flow
3.14 80	3/4-16	3.87 98	P550971	Lube Spin-on Full Flow
3.15 80	3/4-16	2.72 69	P502069	Lube Spin-on Full Flow
3.15 80	3/4-16	2.95 75	P502022	Lube Spin-on Full Flow
3.15 80	3/4-16	3.15 80	P502020	Lube Spin-on Full Flow
3.15 80	M 20 x 1.5	2.76 70	P502071	Lube Spin-on Full Flow
3.15 80	M 20 x 1.5	2.95 75	P502098	Lube Spin-on Full Flow
3.15 80	M20 X 1.5		P502361	Lube Spin-on Bypass
3.15 80	M20 x 1.5	2.52 64	P502009	Lube Spin-on Full Flow
3.15 80	M20 x 1.5	3.15 80	P502049	Lube Spin-on Full Flow
3.15 80	M20 x 1.5	3.15 80	P550776	Lube Spin-on Full Flow
3.15 80	M20 x 1.5	3.94 100	P502015	Lube Spin-on Full Flow
3.15 80	M20 x 1.5	3.98 101	P550405	Lube Spin-on Full Flow
3.15 80	M22 x 1.5	3.17 81	P550600	Lube Spin-on Full Flow
3.15 80	M22 x 1.5	3.94 100	P550389	Lube Spin-on Full Flow
3.16 80	M20 x 1.5	5.64 143	P502056	Lube Spin-on Full Flow
3.18 81	M20 x 1.5	3.39 86	P550162	Lube Spin-on Full Flow
3.23 82	3/4-16	3.19 81	P552454	Lube Spin-on Full Flow
3.24 82	3/4-16	3.90 99	P550711	Lube Spin-on Full Flow
3.24 82	3/4-16	4.40 112	P550715	Lube Spin-on Full Flow
3.28 83	M20 x 1.5	2.78 71	P550726	Lube Spin-on Full Flow
3.31 84	3/4-16	3.93 100	P550227	Lube Spin-on Full Flow
3.31 84	3/4-16	4.92 125	P550078	Lube Spin-on Full Flow
3.33 85	2 3/4-5	4.84 123	P552451	Lube Spin-on Bypass
3.34 86	M18 x 1.5	3.46 88	P502075	Lube Spin-on Full Flow
3.43 87	M20 x 1.5	3.50 89	P502076	Lube Spin-on Full Flow
3.52 89	M20 x 1.5	3.23 82	P502092	Lube Spin-on Full Flow
3.54 90	2 3/4-4	4.86 123	P558717	Lube Spin-on Bypass
3.54 90	3/4"- 16	5.12 130	P502235	Lube Spin-on Full Flow
3.54 90	M 20 x 1.5	4.92 125	P502025	Lube Spin-on Full Flow
3.54 90	M20 x 1.5	3.93 100	P502039	Lube Spin-on Full Flow
3.54 90	M20 x 1.5	4.92 125	P550718	Lube Spin-on Full Flow
3.54 90	M22 x 1.5	3.18 81	P502048	Lube Spin-on Full Flow
3.54 90	M26 x 1.5	4.92 125	P502043	Lube Spin-on Combination
3.58 91	M26 x 1.5	4.92 125	P502058	Lube Spin-on Combination
3.64 92	M20 x 1.5	4.92 125	P550412	Lube Spin-on Bypass

Lube Spin-on - continued

Outer Diameter IN	MM	Thread Size	Length IN	MM	PART NUMBER	PART DESCRIPTION
3.64	92	M22 x 1.5	5.47	139	P502072	Lube Spin-on Full Flow
3.66	93	1 1/8-12	6.85	174	P550835	Lube Spin-on Full Flow
3.66	93	1 1/8-16	6.85	174	P550428	Lube Spin-on Full Flow
3.66	93	1-12	5.08	129	P502068	Lube Spin-on Combination
3.66	93	1-12	5.35	136	P552819	Lube Spin-on Full Flow
3.66	93	1-12	5.35	136	P555680	Lube Spin-on Full Flow
3.66	93	1-12	6.85	174	P553712	Lube Spin-on Full Flow
3.66	93	1-12	6.85	174	P555616	Lube Spin-on Full Flow
3.66	93	1-12	6.85	174	P557207	Lube Spin-on Full Flow
3.66	93	1-12	7.87	200	P553771	Lube Spin-on Full Flow
3.66	93	1-16	5.35	136	ELF7345	Lube Spin-on Full Flow
3.66	93	1-16	5.35	136	P177345	Lube Spin-on Full Flow
3.66	93	1-16	5.35	136	P558616	Lube Spin-on Full Flow
3.66	93	1-16	6.85	174	ELF7349	Lube Spin-on Full Flow
3.66	923	1-16	6.85	174	P177349	Lube Spin-on Full Flow
3.66	93	1-16	6.85	174	P558615	Lube Spin-on Full Flow
3.66	93	1-16	6.94	176	P550909	Lube Spin-on Full Flow
3.66	93	13/16-16	4.34	110	P550551	Lube Spin-on Bypass
3.66	93	13/16-16	4.34	110	P550599	Lube Spin-on Full Flow
3.66	93	13/16-16	5.18	132	P550024	Lube Spin-on Full Flow
3.66	93	13/16-16	5.47	139	P502091	Lube Spin-on Full Flow
3.66	93	13/16-16	7.87	200	P550832	Lube Spin-on Full Flow
3.66	93	15/16-16	7.87	200	P550920	Lube Spin-on Full Flow
3.66	93	3/4-16	3.30	84	P551042	Lube Spin-on Full Flow
3.66	93	3/4-16	3.39	86	P550939	Lube Spin-on Full Flow
3.66	93	3/4-16	3.57	91	P550572	Lube Spin-on Full Flow
3.66	97	3/4-16	3.58	91	P550882	Lube Spin-on Full Flow
3.66	93	3/4-16	4.21	107	P550941	Lube Spin-on Full Flow
3.66	93	3/4-16	4.21	107	P550942	Lube Spin-on Full Flow
3.66	93	3/4-16	4.21	107	P552518	Lube Spin-on Full Flow
3.66	93	3/4-16	5.35	136	P550008	Lube Spin-on Full Flow
3.66	93	3/4-16	5.35	136	P554403	Lube Spin-on Full Flow
3.66	93	3/4-16	5.35	136	P557780	Lube Spin-on Full Flow
3.66	93	3/4-16	5.87	149	P550006	Lube Spin-on Full Flow
3.66	93	3/4-16	6.85	174	P550299	Lube Spin-on Full Flow
3.66	93	3/4-16	6.86	174	P554407	Lube Spin-on Full Flow
3.66	93	M20 X 1.5	5.35	136	P550934	Lube Spin-on Full Flow
3.66	93	M24 x 1.5	5.35	136	P550758	Lube Spin-on Full Flow
3.66	93	M26 x 1.5	6.92	176	P557382	Lube Spin-on Combination
3.66	93	M92 x 2.5	6.10	155	P550779	Lube Spin-on Full Flow
3.67	93	1-12	6.88	175	P551297	Lube Spin-on Full Flow
3.67	93	1-12	8.00	203	P551262	Lube Spin-on Full Flow
3.67	93	1-16	6.87	174	P551265	Lube Spin-on Full Flow
3.67	93	3/4-16	2.22	56	P551784	Lube Spin-on Full Flow
3.67	93	3/4-16	3.39	86	P551268	Lube Spin-on Full Flow
3.67	93	3/4-16	5.32	135	P169071	Lube Spin-on Full Flow
3.67	93	7/8-14	3.75	95	P551287	Lube Spin-on Full Flow
3.67	93	M20 x 1.5	3.16	80	P550173	Lube Spin-on Full Flow
3.67	93	M20 x 1.5	3.16	80	P551306	Lube Spin-on Full Flow
3.67	93	M22 x 1.5	3.58	91	P550965	Lube Spin-on Full Flow
3.67	93	M22 x 1.5	5.42	138	P550166	Lube Spin-on Full Flow
3.68	93	13/16-16	5.44	138	P550188	Lube Spin-on Full Flow
3.69	94	13/16-16	5.20	132	P551764	Lube Spin-on Full Flow
3.69	94	13/16-16	5.36	136	P550518	Lube Spin-on Full Flow
3.69	94	3/4-16	4.36	111	P552290	Lube Spin-on Full Flow

Lube Spin-on - continued

Outer Diameter IN	MM	Thread Size	Length IN	MM	PART NUMBER	PART DESCRIPTION
3.69	94	3/4-16	5.54	141	P553411	Lube Spin-on Full Flow
3.69	94	3/4-20	5.43	138	P552363	Lube Spin-on Bypass
3.69	94	M20 x 1.5	5.37	136	P550158	Lube Spin-on Full Flow
3.70	94	1 1/2-16	5.51	140	P551352	Lube Spin-on Full Flow
3.70	94	1-12	3.75	95	P550710	Lube Spin-on Full Flow
3.70	94	1-12	8.30	211	P550562	Lube Spin-on Full Flow
3.70	94	3/4-16	4.33	110	P551300	Lube Spin-on Full Flow
3.70	94	M18 x 1.5	3.72	95	P550242	Lube Spin-on Bypass
3.72	95	3/4-16	3.95	100	P550963	Lube Spin-on Full Flow
3.73	95	1-12	4.22	107	P550719	Lube Spin-on Full Flow
3.73	95	13/16-16	5.37	136	P166564	Lube Spin-on Full Flow
3.73	95	5/8-18	4.31	109	P550154	Lube Spin-on Bypass
3.74	95	1-12	5.47	139	P559418	Lube Spin-on Full Flow
3.74	95	1-12	8.31	211	P550317	Lube Spin-on Full Flow
3.74	95	3/4-16	3.62	92	P550318	Lube Spin-on Full Flow
3.75	95	1-12	6.99	178	P550362	Lube Spin-on Full Flow
3.75	95	M24 x 1.5	6.88	175	P550975	Lube Spin-on Full Flow
3.77	96	13/16-16	3.08	78	P550507	Lube Spin-on Full Flow
3.77	96	3/4-16	3.93	100	P502408	Lube Spin-on Full Flow
3.78	96	13/16-16	5.14	131	P550964	Lube Spin-on Full Flow
3.78	96	M22 x 1.5	3.78	96	P550357	Lube Spin-on Full Flow
3.79	96	2 3/4-4	6.02	153	P552404	Lube Spin-on Bypass
3.79	96	2 3/4-4	8.13	206	P552464	Lube Spin-on Full Flow
3.81	97	1 1/8-16	5.22	133	P555570	Lube Spin-on Full Flow
3.81	97	1-12	6.78	172	P558250	Lube Spin-on Full Flow
3.81	97	13/16-16	4.22	107	P550025	Lube Spin-on Full Flow
3.81	97	13/16-16	5.12	130	P550035	Lube Spin-on Full Flow
3.81	97	13/16-16	5.53	140	P550020	Lube Spin-on Full Flow
3.81	97	3/4-16	3.72	95	P550095	Lube Spin-on Full Flow
3.81	97	5/8-18	5.22	133	P550050	Lube Spin-on Bypass
3.81	97	5/8-18	5.68	144	P550194	Lube Spin-on Full Flow
3.81	97	5/8-18	7.91	201	P553404	Lube Spin-on Bypass
3.82	97	3/4-16	3.98	101	P551201	Lube Spin-on Full Flow
3.82	97	M22 x 1.5	5.51	140	P553315	Lube Spin-on Full Flow
3.85	98	M27 x 2	6.89	175	P550520	Lube Spin-on Full Flow
3.93	100	M24 x 1.5	3.30	84	P502017	Lube Spin-on Combination
3.94	100	M 24 x 1.5	4.72	120	P502234	Lube Spin-on Full Flow
3.94	100	M24 x 1.5	4.74	120	P550413	Lube Spin-on Full Flow
3.96	101	1-12	4.92	125	P502060	Lube Spin-on Full Flow
3.96	101	1-12	4.92	125	P550411	Lube Spin-on Full Flow
4.00	102	1-12	5.92	150	P550422	Lube Spin-on Full Flow
4.01	102	1" - 12	5.90	150	P502374	Lube Spin-on Combination
4.01	102	1" - 12	5.90	150	P502413	Lube Spin-on Full Flow
4.02	102	1-12	5.91	150	P502080	Lube Spin-on Full Flow
4.02	102	1-12	5.91	150	P550409	Lube Spin-on Full Flow
4.02	102	M26 x 1.5	4.92	125	P502061	Lube Spin-on Combination
4.02	102	M26 x 1.5	5.31	135	P551343	Lube Spin-on Bypass
4.02	102	M26 x 1.5	6.02	153	P550406	Lube Spin-on Full Flow
4.13	105	M20 x 1.5	3.15	80	P550383	Lube Spin-on Full Flow
4.13	105	M24 x 1.5	4.81	122	P550597	Lube Spin-on Combination
4.20	107	M20 x 1.5	4.98	126	P550067	Lube Spin-on Full Flow
4.21	107	1-12	3.96	101	P502085	Lube Spin-on Full Flow
4.21	107	M26 x 1.5	5.90	150	P502008	Lube Spin-on Combination
4.23	107	1 1/2-16	5.79	147	P559127	Lube Spin-on Full Flow
4.23	107	1 1/8-16	5.79	147	P559128	Lube Spin-on Full Flow

Lube Spin-on - continued

Outer Diameter IN	MM	Thread Size	Length IN	MM	PART NUMBER	PART DESCRIPTION
4.23	107	1 1/8-16	10.31	262	ELF2504	Lube Spin-on Full Flow
4.23	107	7/8-16 UN-2B	7.95	202	P559130	Lube Spin-on Full Flow
4.23	107	M30 X 1.5	6.61	168	P559129	Lube Spin-on Full Flow
4.23	107	M30 x 2	6.95	177	P550945	Lube Spin-on Full Flow
4.24	108	1 1/2-16	5.63	143	P550784	Lube Spin-on Full Flow
4.24	108	1 1/8-16	6.56	167	P550708	Lube Spin-on Full Flow
4.24	108	1 1/8-16	6.73	171	P551266	Lube Spin-on Full Flow
4.24	108	1 1/8-16	7.02	178	P551263	Lube Spin-on Full Flow
4.24	108	1 1/8-16	10.32	262	P553191	Lube Spin-on Full Flow
4.24	108	3/4-16	6.59	167	P551267	Lube Spin-on Full Flow
4.24	108	7/8-16	8.05	204	P551304	Lube Spin-on Full Flow
4.24	108	M20 x 1.5	5.62	143	P551264	Lube Spin-on Full Flow
4.24	108	M30 x 1.5	7.48	190	P551253	Lube Spin-on Full Flow
4.25	108	1 1/2-12	10.42	265	P502081	Lube Spin-on Full Flow
4.25	108	1 1/8-16	10.24	260	P550519	Lube Spin-on Full Flow
4.25	108	1 1/8-16	10.31	262	ELF7483	Lube Spin-on Full Flow
4.25	108	1 1/8-16	10.31	262	ELF7739	Lube Spin-on Full Flow
4.25	108	1 1/8-16	10.31	262	P552504	Lube Spin-on Full Flow
4.25	108	1 1/8-16	10.31	262	P554004	Lube Spin-on Full Flow
4.25	108	1 1/8-16	10.32	262	P551807	Lube Spin-on Full Flow
4.25	108	1-12	5.14	131	P502032	Lube Spin-on Combination
4.25	108	1-12	6.00	152	P550731	Lube Spin-on Full Flow
4.25	108	1-12	6.61	168	P553871	Lube Spin-on Full Flow
4.25	108	1-12	9.13	232	P551604	Lube Spin-on Full Flow
4.25	108	M30 x 1.5	5.51	140	P550707	Lube Spin-on Full Flow
4.25	108	M30 x 2	5.62	143	P502222	Lube Spin-on Full Flow
4.25	108	M32 x 1.5	8.77	223	P502093	Lube Spin-on Combination
4.26	108	1 1/8-16	6.57	167	P550086	Lube Spin-on Full Flow
4.26	108	3/4-16	7.25	184	P551603	Lube Spin-on Full Flow
4.27	108	1 1/2-16	8.02	204	P550371	Lube Spin-on Full Flow
4.27	108	1-12	8.00	203	P550319	Lube Spin-on Full Flow
4.27	108	1-12	9.09	231	P550393	Lube Spin-on Full Flow
4.27	108	7/8-16	8.06	205	P550714	Lube Spin-on Full Flow
4.27	108	M30 x 2	9.00	229	P550712	Lube Spin-on Full Flow
4.28	109	1 1/8-16	5.78	147	P556007	Lube Spin-on Full Flow
4.28	109	1-16	5.78	147	P550152	Lube Spin-on Full Flow
4.28	109	1-16	7.33	186	P552474	Lube Spin-on Full Flow
4.28	109	3/4-16	3.77	96	P550580	Lube Spin-on Full Flow
4.28	109	3/4-20	7.89	200	P553746	Lube Spin-on Bypass
4.29	109	1 3/8-16	10.36	263	P550425	Lube Spin-on Bypass
4.29	109	M30 x 2	9.06	230	P550342	Lube Spin-on Full Flow
4.33	110	1 1/8-16	6.38	162	P550420	Lube Spin-on Full Flow
4.33	110	1 1/8-16	6.73	171	P502088	Lube Spin-on Full Flow
4.33	110	1 1/8-16	10.08	256	P551102	Lube Spin-on Full Flow
4.33	110	1 1/8-16	10.20	260	P550490	Lube Spin-on Full Flow
4.33	110	3/4-16	4.82	123	P502089	Lube Spin-on Full Flow
4.33	110	M20 x 1.5	6.38	162	P551257	Lube Spin-on Full Flow
4.33	110	M36 x 2	6.91	176	P502376	Lube Spin-on Combination
4.40	112	3/4-16	5.70	145	P550226	Lube Spin-on Full Flow
4.45	113	1 1/8-16	6.73	171	P502083	Lube Spin-on Full Flow
4.45	113	M30 x 2	8.92	227	P550639	Lube Spin-on Full Flow
4.50	114	1 1/8-16	8.50	216	P550073	Lube Spin-on Full Flow
4.64	118	1 1/2-12	11.25	286	P502401	Lube Spin-on Full Flow
4.64	118	M95 X 2	11.53	293	P552025	Lube Spin-on Full Flow
4.65	118	1 1/2-12	6.22	158	ELF7947	Lube Spin-on Full Flow

Lube Spin-on - continued

Outer Diameter IN	MM	Thread Size	Length IN	MM	PART NUMBER	PART DESCRIPTION
4.65	118	1 1/2-12	8.09	205	P550596	Lube Spin-on Full Flow
4.65	118	1 1/2-12	10.24	260	ELF7670	Lube Spin-on Full Flow
4.65	118	1 1/2-12	10.24	260	P551670	Lube Spin-on Full Flow
4.65	118	1 1/2-16	7.83	199	P552050	Lube Spin-on Full Flow
4.65	118	1 1/2-16	11.73	298	ELF7405	Lube Spin-on Full Flow
4.65	118	1 3/8-16	10.24	260	P550777	Lube Spin-on Bypass
4.65	118	1 5/8-12	10.24	260	ELF2500	Lube Spin-on Full Flow
4.65	118	1 5/8-12	10.24	260	ELF3998	Lube Spin-on Full Flow
4.65	118	1 5/8-12	10.24	260	P552100	Lube Spin-on Full Flow
4.65	118	2 1/4-12	8.94	227	P553548	Lube Spin-on Combination
4.65	118	2 1/4-12	11.70	297	P553000	Lube Spin-on Combination
4.65	118	2 1/4-12	11.75	298	ELF7300	Lube Spin-on Combination
4.65	118	M95 X 2	13.67	347	P550656	Lube Spin-on Combination
4.65	118	M95 x 2.5	11.70	297	ELF7900	Lube Spin-on Full Flow
4.66	118	1 3/8-16	9.91	252	P550421	Lube Spin-on Full Flow
4.66	118	M52 x 1.5	11.70	297	P550595	Lube Spin-on Combination
4.66	118	M95 x 2.5	11.70	297	P559000	Lube Spin-on Combination
4.67	119	1 1/2-12	6.28	159	P550947	Lube Spin-on Full Flow
4.67	119	1 1/2-12	7.85	199	P551381	Lube Spin-on Full Flow
4.67	119	1 1/2-12	8.94	227	P550671	Lube Spin-on Full Flow
4.67	119	1 1/2-16	11.75	298	P554105	Lube Spin-on Full Flow
4.67	119	M95 x 2.5	11.70	297	ELF2501	Lube Spin-on Full Flow
4.72	120	1 1/2-12	8.26	210	P502363	Lube Spin-on Full Flow
4.72	120	1 1/2-16	8.27	210	P502364	Lube Spin-on Combination
4.79	122	M90 x 2.0	11.85	301	P550775	Lube Spin-on Full Flow
4.86	123	1 1/2-12	5.87	149	P550973	Lube Spin-on Combination
4.88	124	1 1/2-12	4.72	120	P502042	Lube Spin-on Combination
4.88	124	1 1/2-12	4.72	120	P502046	Lube Spin-on Combination
4.92	125	1 1/2-12	9.84	250	P502385	Lube Spin-on Full Flow
4.92	125	1 3/8-16	9.84	250	P502359	Lube Spin-on Bypass
5.00	127	1 1/2-16	6.85	174	P553634	Lube Spin-on Full Flow
5.04	128	M36 x 1.5	8.67	220	P552562	Lube Spin-on Combination
5.06	129	1 1/2-12	6.72	171	P558329	Lube Spin-on Full Flow
5.32	135	1 1/2-16	9.61	244	P550788	Lube Spin-on Full Flow
5.32	135	1 1/2-16	12.13	308	P551808	Lube Spin-on Full Flow
5.32	136	M36 x 1.5	12.10	307	P550367	Lube Spin-on Full Flow
5.33	135	1 1/2-16	12.13	308	ELF2502	Lube Spin-on Full Flow
5.33	135	1 1/2-16	12.13	308	P551402	Lube Spin-on Full Flow
5.33	135	1 1/2-16	12.13	308	P554005	Lube Spin-on Full Flow
5.33	135	M36 x 1.5	12.10	308	P550512	Lube Spin-on Full Flow
5.33	135	M36 x 1.5	12.13	308	ELF7367	Lube Spin-on Full Flow
5.33	135	M45 x 1.5	12.13	308	P551400	Lube Spin-on Full Flow
5.35	136	1 1/2-16	9.68	246	P554206	Lube Spin-on Full Flow
5.35	136	M46 x 2	10.03	255	P502444	Lube Spin-on Full Flow
5.38	137	1 1/2-16	8.16	207	P550713	Lube Spin-on Full Flow
5.48	139	M60 x 3	6.62	168	P550356	Lube Spin-on Combination
5.51	140	M42 x 2	11.89	302	P550452	Lube Spin-on Full Flow
5.55	141	1 1/2-16	12.20	310	P550341	Lube Spin-on Full Flow
5.56	141	1 1/8-16	6.00	152	P550157	Lube Spin-on Full Flow

Seals, Gaskets, Washers

Outer Diameter IN MM	Inner Diameter IN MM	Cross Section IN MM	PART NUMBER	PART DESCRIPTION
4.30 109	8.00 203	0.27 7	P167575	Gasket, Cover
Outlet Diameter IN MM	Inlet Diameter IN MM	Cross Section IN MM	PART NUMBER	PART DESCRIPTION
5.50 140	5.20 132	0.13 3	P174997	Gasket, Liquid Filter
Outer Diameter IN MM	Inner Diameter IN MM	Cross Section IN MM	PART NUMBER	PART DESCRIPTION
8.97 228	8.47 215	0.25 6	P167574	Gasket Cover
Outer Diameter IN MM	Inlet Diameter IN MM	Cross Section IN MM	PART NUMBER	PART DESCRIPTION
11.51 292	10.79 274	0.69 18	P154686	Gasket

Transmission

Outer Diameter IN MM	Inner Diameter IN MM	Length IN MM	PART NUMBER	PART DESCRIPTION
3.09 79	1.52 39	8.03 204	P170737	Transmission Cartridge
3.10 79	2.18 55	16.68 424	P166135	Transmission Cartridge
3.10 79	2.18 55	16.68 424	P166136	Transmission Cartridge
3.12 79	1.71 43	12.76 324	P166255	Transmission Cartridge
3.21 82		4.21 107	P560972	Transmission Filter Kit
3.21 82		5.98 152	P560971	Transmission Filter Kit
3.75 95	1.40 36	8.90 226	P166376	Transmission Cartridge
4.30 109	1.40 36	8.90 226	P166375	Transmission Cartridge
4.30 109	1.41 36	5.70 145	P166167	Transmission Cartridge
4.30 109	1.44 37	9.06 230	P550951	Transmission Cartridge
4.30 79	1.71 43	12.76 324	P166254	Transmission Cartridge
Width IN MM	Height IN MM		PART NUMBER	PART DESCRIPTION
6.90 175	10.72 272		P551766	Transmission Filter Kit
Width IN MM	Height IN MM	C IN MM	PART NUMBER	PART DESCRIPTION
7.00 178	8.53 217	6.58 167	P550960	Transmission Filter Kit

Liquid Spin-ons by Thread Size

To help find the filter type by thread size, this section will lead you to part numbers that have the same spin-on thread size.

A word of caution, just because the physical fit may be the same from one part to another a filter should never be applied using just by physical fit.

This information is intended to help guide you to a part number(s) for further review of dimensional characteristics and primary application in the by Part No. Section of this document.

Thread Sizes	Page No.	Thread Sizes	Page No.
1 1/4	338	3 3/8-8.....	342
2	338	3/4-BSP	342
1-3/8.....	338	31/32-20.....	342
1-12.....	338		
1-14.....	338-339	G 1 1/4.....	342
1-16.....	339	G 3/4.....	342
2-12.....	339	M12 x 1.5.....	342
2-16.....	339	M14 x 1.5.....	342
3-8.....	339	M16 x 1.5.....	342
11/4-12.....	339	M18 x 1.5.....	342
3/4-14.....	339	M20 x 1.5.....	342
7/8-14.....	339		
3/4-16.....	339	M22 x 1.5.....	343
3/4 - 16.....	339	M23 x 1.5.....	343
7/8-16.....	339	M24 x 1.5.....	343
11/2-16.....	339	M24 x 2.....	343
		M24 x1.5.....	343
11/16-16.....	340	M26 x 1.5.....	343
5/8-18.....	340	M27 x 2.....	343
3/4-20.....	340		
7/16-20.....	340	M30 x 1.5.....	343
1 1/16-16.....	340	M30 x 2.....	343
1 1/2-12.....	340	M32 x 1.5.....	343
1 1/2-16.....	340	M36 x 1.5.....	343
1 1/4-11 BSP.....	340	M36 x 2.....	343
1 1/4-12.....	340	M39 x 1,5.....	343
1 1/8-12.....	341	M40 X 2	343
1 1/8-16.....	341	M42 x 2.....	343
1 3/4-12.....	341	M45 x 1.5.....	343
1 3/4-16.....	341	M45 x 2.....	343
1 3/8-12.....	341	M46 x 2.....	343
1 3/8-16.....	341	M48 x 2.....	343
1 5/16-12.....	341		
1 5/8-12.....	341	M52 x 1.5.....	343
1-1/2-16	341		
		M60 x 3.....	343
13/16-12.....	342		
13/16-16.....	342	M72 x 2.....	343
13/16-18.....	342	M76 x 4.....	343
1-3/8-12	342		
15/16-16.....	342	M85 x 2.....	343
2 1/4-12.....	342	M90 x 2.0.....	343
2 3/4-4.....	342	M92 X 2.5	343
2 3/4-5.....	342	M95 X 2	343
		M95 x 2.5.....	343

Thread Size	Length IN	Length MM	Outer Dia. IN	Outer Dia. MM	Part Number	Filter Type	Thread Size	Length IN	Length MM	Outer Dia. IN	Outer Dia. MM	Part Number	Filter Type								
1 1/4	7.04	179	4.96	126	P171616	Hydraulic Spin-on		8.23	209	3.66	93	P552410	Hydraulic Spin-on								
	7.04	179	5.03	128	P173062	Hydraulic Spin-on		8.23	209	3.82	97	P550230	Hydraulic Spin-on								
2	5.52	140	3.13	80	P170308	Hydraulic Spin-on		8.29	211	3.68	93	P550591	Hydraulic Spin-on								
								8.30	211	3.70	94	P550562	Lube Spin-on								
1-3/8	5.97	152	3.71	94	P566047	Hydraulic Spin-on		8.31	211	3.74	95	P550317	Lube Spin-on								
								8.64	219	3.66	93	P553202	Fuel Spin-on								
1-12	3.75	95	3.67	93	P551204	Hydraulic Spin-on		8.90	226	4.24	108	P551774	Fuel Spin-on								
								9.09	231	4.27	108	P550393	Lube Spin-on								
								9.13	232	4.25	108	P551604	Lube Spin-on								
								9.94	252	3.81	97	P555002	Fuel Spin-on								
								10.38	264	4.24	108	P550753	Fuel Spin-on								
								10.85	275.5	4.25	108	P551360	Fuel Spin-on								
								1-14	3.50	89	4.25	108	P550746	Fuel Spin-on							
									4.02	102	4.39	112	P553375	Fuel Spin-on							
									4.12	105	3.75	95	P550088	Fuel Spin-on							
									4.22	107	3.81	97	P550104	Fuel Spin-on							
									4.34	110	2.62	67	P551751	Fuel Spin-on							
									5.04	128	4.36	111	P550436	Fuel Spin-on							
									5.05	128	4.36	111	P550729	Fuel Spin-on							
									5.10	130	4.36	111	P550730	Fuel Spin-on							
									5.35	136	3.66	93	P552251	Fuel Spin-on							
									5.35	136	3.66	93	P550105	Fuel Spin-on							
									5.35	136	3.66	93	P551744	Fuel Spin-on							
	5.35	136	3.66	93	P562199	Hydraulic Spin-on															
	5.35	136	3.66	93	P566041	Hydraulic Spin-on															
	5.35	136	3.66	93	P566040	Hydraulic Spin-on															
	5.35	136	3.66	93	P563762	Hydraulic Spin-on															
	5.35	136	3.66	93	P565062	Hydraulic Spin-on															
	5.35	136	3.66	93	P565061	Hydraulic Spin-on															
	5.35	136	3.66	93	P564967	Hydraulic Spin-on															
	5.35	136	3.66	93	P562198	Hydraulic Spin-on															
	5.35	136	3.66	93	P555680	Lube Spin-on															
	5.35	136	3.66	93	P552819	Lube Spin-on															
	5.37	136	3.69	94	P550215	Fuel Spin-on															
	5.37	136	3.69	94	P550115	Fuel Spin-on															
	5.47	139	3.74	95	P559418	Lube Spin-on															
	5.66	144	3.67	93	P551234	Hydraulic Spin-on															
	5.72	145.5	3.66	93	P502404	Fuel Spin-on															
	5.76	146	3.73	95	P550274	Hydraulic Spin-on															
	5.90	150	4.01	102	P502374	Lube Spin-on															
	5.90	150	4.01	102	P502413	Lube Spin-on															
	5.91	150	4.02	102	P550409	Lube Spin-on															
	5.91	150	4.02	102	P502080	Lube Spin-on															
	5.92	150	4.00	102	P550422	Lube Spin-on															
	5.97	152	3.71	94	P550786	Hydraulic Spin-on															
	6.00	152	4.25	108	P550731	Lube Spin-on															
	6.08	154	3.81	97	P550944	Fuel Spin-on															
	6.61	168	4.25	108	P553871	Lube Spin-on															
	6.78	172	3.81	97	P558250	Lube Spin-on															
	6.83	173	3.73	95	P550695	Hydraulic Spin-on															
	6.85	174	3.66	93	P554347	Fuel Spin-on															
	6.85	174	3.66	93	P553712	Lube Spin-on															
	6.85	174	3.66	93	P555616	Lube Spin-on															
	6.85	174	3.66	93	P557207	Lube Spin-on															
	6.88	175	3.67	93	P551297	Lube Spin-on															
	6.99	178	3.75	95	P550362	Lube Spin-on															
	7.01	178	3.82	97	P550229	Hydraulic Spin-on															
	7.35	187	3.67	93	P551780	Hydraulic Spin-on															
	7.36	187	3.81	97	P558010	Fuel Spin-on															
	7.40	188	3.81	97	P555020	Fuel Spin-on															
	7.44	189	3.69	94	P551915	Fuel Spin-on															
	7.87	200	3.66	93	P566042	Hydraulic Spin-on															
	7.87	200	3.66	93	P179089	Hydraulic Spin-on															
	7.87	200	3.66	93	P565059	Hydraulic Spin-on															
	7.87	200	3.66	93	P565060	Hydraulic Spin-on															
	7.87	200	3.66	93	P564357	Hydraulic Spin-on															
	7.87	200	3.66	93	P553771	Lube Spin-on															
	7.97	202	3.81	97	P556915	Fuel Spin-on															
	8.00	203	3.67	93	P551262	Lube Spin-on															
	8.00	203	4.27	108	P550319	Lube Spin-on															
	8.15	207	3.81	97	P763577	Hydraulic Spin-on															
								9.43	240	3.68	93	P551311	Fuel Spin-on								

Liquid Filters by Thread Size

Thread Size	Length IN	Length MM	Outer Dia. IN	Outer Dia. MM	Part Number	Filter Type	Thread Size	Length IN	Length MM	Outer Dia. IN	Outer Dia. MM	Part Number	Filter Type
	9.43	240	3.72	95	P551712	Fuel Spin-on		3.15	80	3.15	80	P502020	Lube Spin-on
	9.70	246	3.66	93	P551000	Fuel Spin-on		3.20	81	3.24	82	P505951	Fuel Spin-on
	9.71	247	3.66	93	P550901	Fuel Spin-on		3.30	84	3.66	93	P551042	Lube Spin-on
	9.94	252	3.81	97	P555001	Fuel Spin-on		3.31	84	2.91	74	P502016	Lube Spin-on
	10.31	262	4.25	108	EFF9092	Fuel Spin-on		3.31	84	3.15	80	P502177	Fuel Spin-on
	10.60	269	4.31	109	P555823	Fuel Spin-on		3.35	85	2.56	65	P502070	Lube Spin-on
	10.75	273	3.70	94	P550625	Fuel Spin-on		3.39	86	2.99	76	P550464	Hydraulic Spin-on
	10.85	275.5	4.25	108	P551361	Fuel Spin-on		3.39	86	2.99	76	P550426	Hydraulic Spin-on
	11.30	287	4.38	111	P551746	Fuel Spin-on		3.39	86	3.30	84	P550057	Fuel Spin-on
	11.38	289	4.38	111	P555006	Fuel Spin-on		3.39	86	3.67	93	P551268	Lube Spin-on
	11.88	302	4.25	108	P550668	Fuel Spin-on		3.40	86	2.92	74	P552430	Lube Spin-on
								3.40	86	3.00	76	P550335	Lube Spin-on
1-16	5.35	136	3.66	93	ELF7345	Lube Spin-on		3.42	87	3.00	76	P551251	Lube Spin-on
	5.35	136	3.66	93	P558616	Lube Spin-on		3.46	88	3.00	76	P502107	Lube Spin-on
	5.35	136	3.66	93	P177345	Lube Spin-on		3.46	88	3.01	76	P553240	Fuel Spin-on
	6.85	174	3.66	93	P558615	Lube Spin-on		3.53	90	3.00	76	P550589	Hydraulic Spin-on
	6.85	174	3.66	93	ELF7349	Lube Spin-on		3.54	90	2.56	65	P502019	Lube Spin-on
	6.94	176	3.66	93	P550909	Lube Spin-on		3.57	91	3.66	93	P550572	Lube Spin-on
	6.87	174	3.67	93	P551265	Lube Spin-on		3.58	91	3.66	97	P550882	Lube Spin-on
	5.78	147	4.28	109	P554422	Coolant Filters		3.62	92	3.74	95	P550318	Lube Spin-on
	5.78	147	4.28	109	P550152	Lube Spin-on		3.72	95	3.81	97	P550095	Lube Spin-on
	7.33	186	4.28	109	P552474	Lube Spin-on		3.77	96	4.28	109	P550580	Lube Spin-on
								3.80	97	3.88	99	P550210	Hydraulic Spin-on
2-12	5.52	140	3.13	80	P170312	Hydraulic Spin-on		3.90	99	3.24	82	P550711	Lube Spin-on
	5.52	140	3.13	80	P170306	Hydraulic Spin-on		3.93	100	3.31	84	P550227	Lube Spin-on
	5.52	140	3.13	80	P170310	Hydraulic Spin-on		3.93	100	3.77	96	P502408	Lube Spin-on
	5.52	140	3.13	80	P170480	Hydraulic Spin-on		3.94	100	3.31	84	P550225	Fuel Spin-on
	9.52	242	3.11	79	P176107	Hydraulic Spin-on		3.95	100	3.72	95	P550963	Lube Spin-on
	9.52	242	3.13	80	P170089	Hydraulic Spin-on		3.98	101	3.82	97	P551201	Lube Spin-on
	9.52	242	3.13	80	P173702	Hydraulic Spin-on		4.21	107	3.66	93	P552518	Lube Spin-on
	9.52	242	3.13	80	P170313	Hydraulic Spin-on		4.33	110	3.70	94	P551300	Lube Spin-on
	9.52	242	3.13	80	P170311	Hydraulic Spin-on		4.35	110	3.70	94	P551758	Hydraulic Spin-on
	9.52	242	3.13	80	P170309	Hydraulic Spin-on		4.36	111	3.69	94	P552290	Lube Spin-on
	9.52	242	3.13	80	P170307	Hydraulic Spin-on		4.40	112	3.24	82	P550715	Lube Spin-on
								4.50	114	3.15	80	P502163	Fuel Spin-on
2-16	5.56	141	3.69	94	P552850	Hydraulic Spin-on		4.53	115	2.92	74	P551763	Lube Spin-on
	5.97	152	3.71	94	P174675	Hydraulic Spin-on		4.72	120	2.99	76	P554770	Lube Spin-on
	6.81	173	3.72	95	P550701	Hydraulic Spin-on		4.74	120	3.00	76	P550400	Lube Spin-on
	6.89	175	3.68	93	P550445	Hydraulic Spin-on		4.82	123	4.33	110	P502089	Lube Spin-on
	7.09	180	3.82	97	P765075	Hydraulic Spin-on		4.92	125	3.31	84	P550078	Lube Spin-on
								4.92	125	3.71	94	P552564	Fuel Spin-on
3-8	8.81	224	5.00	127	P162205	Hydraulic Spin-on		5.19	132	3.66	93	P552405	Fuel Spin-on
	12.25	311	5.00	127	P163435	Hydraulic Spin-on		5.31	135	3.01	76.5	P502418	Fuel Spin-on
								5.32	135	3.67	93	P169071	Lube Spin-on
11/4-12	5.97	152	3.71	94	P566050	Hydraulic Spin-on		5.35	136	3.66	93	P554403	Lube Spin-on
3/4-14	5.80	147	3.86	98	P550268	Hydraulic Spin-on		5.35	136	3.66	93	P557780	Lube Spin-on
								5.35	136	3.66	93	P550008	Lube Spin-on
7/8-14	3.75	95	3.67	93	P551287	Lube Spin-on		5.37	136	3.66	93	P550222	Hydraulic Spin-on
	3.93	100	3.82	97	P173739	Hydraulic Spin-on		5.43	138	3.70	94	P550385	Fuel Spin-on
	4.60	117	4.28	109	P550811	Fuel Spin-on		5.47	139	3.85	98	P551351	Fuel Spin-on
	4.62	117.5	4.24	107.7	P502355	Fuel Spin-on		5.53	140	3.00	76	P554408	Lube Spin-on
	5.22	133	3.81	97	P553693	Fuel Spin-on		5.54	141	3.69	94	P553411	Lube Spin-on
	5.83	148	3.05	77	P550368	Fuel Spin-on		5.56	141	3.82	97	P551327	Hydraulic Spin-on
	5.84	148	4.22	107	P551773	Fuel Spin-on		5.59	142	3.11	79	P550550	Fuel Spin-on
	5.97	152	3.82	97	P173738	Hydraulic Spin-on		5.70	145	4.40	112	P550226	Lube Spin-on
	6.74	171	4.24	108	P550669	Fuel Spin-on		5.75	146	3.01	76	P550410	Fuel Spin-on
	6.85	174	3.66	93	P550774	Fuel Spin-on		5.87	149	3.66	93	P550006	Lube Spin-on
	6.89	175	3.66	93	P550879	Fuel Spin-on		6.59	167	4.24	108	P551267	Lube Spin-on
	6.93	176	3.15	80	P551315	Fuel Spin-on		6.85	174	3.66	93	P550299	Lube Spin-on
	7.14	181	4.24	108	P551318	Fuel Spin-on		6.86	174	3.66	93	P554407	Lube Spin-on
	7.98	203	4.28	109	P552603	Fuel Spin-on		6.89	175	3.15	80	P502167	Fuel Spin-on
	8.70	221	3.78	96	P553855	Fuel Spin-on		7.20	183	4.29	109	P551605	Fuel Spin-on
	9.43	240	3.68	93	P551312	Fuel Spin-on		7.25	184	4.26	108	P551603	Lube Spin-on
3/4-16	2.22	56	3.67	93	P551784	Lube Spin-on	7/8-16	7.89	200	4.28	109	P550218	Fuel Spin-on
	2.56	65	2.68	68	P502024	Lube Spin-on		8.05	204	4.24	108	P551304	Lube Spin-on
	2.72	69	3.15	80	P502069	Lube Spin-on		8.06	205	4.27	108	P550714	Lube Spin-on
	2.80	71	2.56	65	P502015	Lube Spin-on							
	2.80	71	2.56	65	P550534	Lube Spin-on	11/2-16	10.66	271	4.78	121	P566046	Hydraulic Spin-on
	2.95	75	3.15	80	P502022	Lube Spin-on							

Thread Size	Length IN	Length MM	Outer Dia. IN	Outer Dia. MM	Part Number	Filter Type	Thread Size	Length IN	Length MM	Outer Dia. IN	Outer Dia. MM	Part Number	Filter Type
	10.24	260	4.66	118	P550202	Fuel Spin-on	1 3/4-16	9.57	243	5.35	136	P502224	Hydraulic Spin-on
	11.25	286	4.64	118	P502381	Fuel Spin-on							
	11.75	298	4.38	111	P920683	Fuel Spin-on	1 3/8-12	3.98	101	3.82	97	P763558	Hydraulic Spin-on
	11.80	300	4.65	118	P550687	Fuel Spin-on		4.47	114	3.71	94	P178619	Hydraulic Spin-on
	12.32	313	4.65	118	P551006	Fuel Spin-on		4.47	114	3.82	97	P169078	Hydraulic Spin-on
1 1/8-12	6.85	174	3.66	93	P550835	Lube Spin-on		5.97	152	3.82	97	P173736	Hydraulic Spin-on
								5.97	152	3.82	97	P163405	Hydraulic Spin-on
1 1/8-16	4.38	111	3.70	94	P550573	Hydraulic Spin-on		5.97	152	3.82	97	P163412	Hydraulic Spin-on
	5.22	133	3.81	97	P555570	Lube Spin-on		5.97	152	3.82	97	P163542	Hydraulic Spin-on
	5.26	134	3.69	94	P551323	Hydraulic Spin-on		5.97	152	3.82	97	P163428	Hydraulic Spin-on
	5.37	136	3.69	94	P556005	Hydraulic Spin-on		5.97	152	3.82	97	P163419	Hydraulic Spin-on
	5.59	142	3.71	94	P552472	Hydraulic Spin-on		5.97	152	3.82	97	P165354	Hydraulic Spin-on
	5.78	147	4.28	109	P556007	Lube Spin-on		5.97	152	3.82	97	P163315	Hydraulic Spin-on
	5.95	151	3.82	97	P550542	Hydraulic Spin-on		5.97	152	3.82	97	P165335	Hydraulic Spin-on
	6.00	152	5.56	141	P550157	Lube Spin-on		5.97	152	3.82	97	P164375	Hydraulic Spin-on
	6.38	162	4.33	110	P550420	Lube Spin-on		5.97	152	3.82	97	P164381	Hydraulic Spin-on
	6.48	164	3.66	93	P552409	Hydraulic Spin-on		5.97	152	3.82	97	P176565	Hydraulic Spin-on
	6.56	167	4.24	108	P550708	Lube Spin-on		6.22	158	3.82	97	P764668	Hydraulic Spin-on
	6.57	167	4.26	108	P550086	Lube Spin-on		7.08	180	3.82	97	P764367	Hydraulic Spin-on
	6.73	171	4.24	108	P551266	Lube Spin-on		7.50	190	3.67	93	P551752	Fuel Spin-on
	6.73	171	4.33	110	P502088	Lube Spin-on		7.88	200	3.82	97	P174552	Hydraulic Spin-on
	6.73	171	4.45	113	P502083	Lube Spin-on		9.41	239	3.82	97	P763535	Hydraulic Spin-on
	6.81	173	3.66	93	P551348	Hydraulic Spin-on		9.44	240	3.71	94	P177047	Hydraulic Spin-on
	6.85	174	3.66	93	P550428	Lube Spin-on		9.44	240	3.81	97	P171298	Hydraulic Spin-on
	7.02	178	3.73	95	P551779	Hydraulic Spin-on		9.44	240	3.82	97	P163567	Hydraulic Spin-on
	7.02	178	4.24	108	P551263	Lube Spin-on		9.44	240	3.82	97	P176566	Hydraulic Spin-on
	7.88	200	4.21	107	P502233	Fuel Spin-on		9.44	240	3.82	97	P163324	Hydraulic Spin-on
	8.09	206	4.28	109	P552452	Hydraulic Spin-on		9.44	240	3.82	97	P173737	Hydraulic Spin-on
	8.15	207	3.87	98	P552483	Hydraulic Spin-on		9.44	240	3.82	97	P163558	Hydraulic Spin-on
	8.50	216	4.50	114	P550073	Lube Spin-on		9.44	240	3.82	97	P163555	Hydraulic Spin-on
	10.08	256	4.33	110	P551102	Lube Spin-on		9.44	240	3.82	97	P170950	Hydraulic Spin-on
	10.20	260	4.33	110	P550490	Lube Spin-on		9.44	240	3.82	97	P560584	Hydraulic Spin-on
	10.24	260	4.25	108	P550519	Lube Spin-on		9.44	240	3.82	97	P164384	Hydraulic Spin-on
	10.31	262	4.23	107	ELF2504	Lube Spin-on		9.44	240	3.82	97	P165185	Hydraulic Spin-on
	10.31	262	4.25	108	ELF7739	Lube Spin-on		9.44	240	3.82	97	P165338	Hydraulic Spin-on
	10.31	262	4.25	108	ELF7483	Lube Spin-on		9.44	240	3.82	97	P167590	Hydraulic Spin-on
	10.31	262	4.25	108	P554004	Lube Spin-on		9.44	240	3.82	97	P165332	Hydraulic Spin-on
	10.32	262	4.24	108	P553191	Lube Spin-on		9.44	240	3.82	97	P164056	Hydraulic Spin-on
	10.32	262	4.25	108	P551807	Lube Spin-on		9.44	240	3.82	97	P164378	Hydraulic Spin-on
1 3/4-12	7.60	193	4.77	121	P176207	Hydraulic Spin-on		9.44	240	3.82	97	P164059	Hydraulic Spin-on
	7.60	193	4.77	121	P176208	Hydraulic Spin-on		9.44	240	3.82	97	P163323	Hydraulic Spin-on
	11.62	295	4.77	121	P176779	Hydraulic Spin-on		9.45	240	3.81	97	P173133	Hydraulic Spin-on
	11.63	295	4.59	117	P567580	Hydraulic Spin-on		9.91	252	4.66	118	P550421	Lube Spin-on
	11.63	295	4.77	121	P165705	Hydraulic Spin-on		10.24	260	4.65	118	P550777	Lube Spin-on
	11.63	295	4.77	121	P171276	Hydraulic Spin-on		10.36	263	4.29	109	P550425	Lube Spin-on
	11.63	295	4.77	121	P171274	Hydraulic Spin-on		11.61	295	4.76	121	P764737	Hydraulic Spin-on
	11.63	295	4.77	121	P173521	Hydraulic Spin-on		11.63	295	4.77	121	P173689	Hydraulic Spin-on
	11.63	295	4.77	121	P173943	Hydraulic Spin-on		11.63	295	4.77	121	P179343	Hydraulic Spin-on
	11.63	295	4.77	121	P165569	Hydraulic Spin-on	1 3/8 - 16	9.84	250	4.92	125	P502359	Lube Spin-on
	11.63	295	4.77	121	P165659	Hydraulic Spin-on		11.77	299	5.38	137	P550348	Fuel Spin-on
	11.63	295	4.77	121	P165672	Hydraulic Spin-on		12.13	308	5.38	137	P553080	Fuel Spin-on
	11.63	295	4.77	121	P165675	Hydraulic Spin-on		12.19	310	5.34	136	P551316	Fuel Spin-on
	11.63	295	4.77	121	P561013	Hydraulic Spin-on	1 5/16-12	5.75	146	3.88	99	P165243	Hydraulic Spin-on
	11.63	295	4.77	121	P171275	Hydraulic Spin-on		10.23	260	4.87	124	P550223	Hydraulic Spin-on
	11.63	295	4.77	121	P171273	Hydraulic Spin-on		10.30	262	4.67	119	P551227	Hydraulic Spin-on
	11.63	295	4.77	121	P179518	Hydraulic Spin-on	1 5/8-12	10.24	260	4.65	118	P552100	Lube Spin-on
	11.63	295	4.77	121	P179075	Hydraulic Spin-on		10.24	260	4.65	118	ELF2500	Lube Spin-on
	11.63	295	4.77	121	P176567	Hydraulic Spin-on		10.24	260	4.65	118	ELF3998	Lube Spin-on
	11.63	295	4.77	121	P170906	Hydraulic Spin-on		11.00	279.4	4.65	118	P553500	Fuel Spin-on
	11.65	296	4.60	117	P566049	Hydraulic Spin-on	1-1/2-16	5.00	127	4.87	124	P566043	Hydraulic Spin-on
	12.64	321	4.77	121	P179763	Hydraulic Spin-on		5.78	146	3.66	92.964	P566919	Hydraulic Spin-on
	14.24	362	4.60	117	P564468	Hydraulic Spin-on		5.78	146	3.66	92.964	P566922	Hydraulic Spin-on
	14.24	362	4.77	121	P173789	Hydraulic Spin-on		5.78	146	3.66	92.964	P566921	Hydraulic Spin-on
	14.24	362	4.77	121	P170546	Hydraulic Spin-on		5.78	147	3.66	93	P566920	Hydraulic Spin-on
	14.24	362	4.77	121	P170949	Hydraulic Spin-on		6.66	169	4.87	124	P566045	Hydraulic Spin-on
								8.06	204	3.66	92.964	P569383	Hydraulic Spin-on

Thread Size	Length IN	Length MM	Outer Dia. IN	Outer Dia. MM	Part Number	Filter Type	Thread Size	Length IN	Length MM	Outer Dia. IN	Outer Dia. MM	Part Number	Filter Type
	3.35	85	2.68	68	P502057	Lube Spin-on	M26 x 1.5	4.92	125	3.54	90	P502043	Lube Spin-on
	3.35	85	2.68	68	P502047	Lube Spin-on		4.92	125	3.58	91	P502058	Lube Spin-on
	3.39	86	3.18	81	P550162	Lube Spin-on		4.92	125	4.02	102	P502061	Lube Spin-on
	3.40	86	2.96	75	P552849	Lube Spin-on		5.31	135	4.02	102	P551343	Lube Spin-on
	3.40	86	3.00	76	P550127	Fuel Spin-on		5.90	150	4.21	107	P502008	Lube Spin-on
	3.44	87.5	2.99	76	P502050	Lube Spin-on		6.02	153	4.02	102	P550406	Lube Spin-on
	3.50	89	3.43	87	P502076	Lube Spin-on		6.92	176	3.66	93	P557382	Lube Spin-on
	3.87	98	3.12	79	P555522	Lube Spin-on	M27 x 2	6.89	175	3.85	98	P550520	Lube Spin-on
	3.93	100	3.15	80	P502143	Fuel Spin-on							
	3.93	100	3.54	90	P502039	Lube Spin-on	M30 x 1.5	5.51	140	4.25	108	P550707	Lube Spin-on
	3.94	100	3.15	80	P502051	Lube Spin-on		7.48	190	4.24	108	P551253	Lube Spin-on
	3.94	100	3.68	93	P550049	Fuel Spin-on		7.95	202	4.23	107	P554476	Fuel Spin-on
	3.98	101	3.15	80	P550405	Lube Spin-on		8.34	212	4.25	108	P554477	Fuel Spin-on
	4.65	118	3.78	96	P550968	Fuel Spin-on		10.30	262	4.25	108	P554471	Fuel Spin-on
	4.72	120	3.16	80	P502142	Fuel Spin-on							
	4.72	120	3.70	94	P552561	Fuel Spin-on	M30 x 2	5.62	143	4.25	108	P502222	Lube Spin-on
	4.72	120	3.72	95	P502157	Fuel Spin-on		6.95	17	4.23	107.4	P550945	Lube Spin-on
	4.92	125	3.54	90	P550718	Lube Spin-on		9.00	229	4.27	108	P550712	Lube Spin-on
	4.92	125	3.64	92	P550412	Lube Spin-on		9.06	230	4.29	109	P550342	Lube Spin-on
	4.98	126	4.20	107	P550067	Lube Spin-on							
	5.17	131	3.72	95	P502158	Fuel Spin-on	M32 x 1.5	8.77	223	4.25	108	P502093	Lube Spin-on
	5.37	136	3.69	94	P550158	Lube Spin-on		10.00	254	4.43	113	P550529	Fuel Spin-on
	5.43	138	3.90	99	P502149	Fuel Spin-on		10.31	262	4.25	108	P502403	Fuel Spin-on
	5.43	138	3.90	99	P550390	Fuel Spin-on							
	5.46	139	3.86	98	P505960	Fuel Spin-on	M36 x 1.5	8.67	220	5.04	128	P552562	Lube Spin-on
	5.62	143	4.24	108	P551264	Lube Spin-on		12.10	307	5.32	136	P550367	Lube Spin-on
	5.64	143	3.16	80	P502056	Lube Spin-on		12.10	308	5.33	135	P550512	Lube Spin-on
	5.75	146	3.69	94	P550549	Fuel Spin-on		12.13	308	5.33	135	ELF7367	Lube Spin-on
	6.30	93.04	3.68	93.4	P550643	Fuel Spin-on							
	6.38	162	4.33	110	P551257	Lube Spin-on	M36 X 2	5.79	147	3.68	93	P550867	Coolant Filters
	7.37	187.4	3.66	93	P502421	Fuel Spin-on		5.79	147	3.68	94	P550866	Coolant Filters
	7.56	192	3.69	93	P550899	Fuel Spin-on		5.76	146	3.69	94	P552126	Coolant Filters
	7.58	193	3.69	94	P550660	Fuel Spin-on		5.76	146	3.77	96	P550585	Coolant Filters
	7.60	193	3.66	93	P550881	Fuel Spin-on		6.91	175	4.33	110	P502376	Lube Spin-on
	8.40	213.5	3.66	93	P502231	Hydraulic Spin-on							
M22 x 1.5	3.17	81	3.15	80	P550600	Lube Spin-on	M39 x 1.5	12.05	306	5.35	136	P765199	Fuel Spin-on
	3.18	81	3.54	90	P502048	Lube Spin-on							
	3.26	83	3.00	76	P550794	Lube Spin-on	M42 x 2	3.94	100	5.04	128	P764260	Hydraulic Spin-on
	3.58	91	3.67	93	P550965	Lube Spin-on		11.89	302	5.51	140	P550452	Lube Spin-on
	3.78	96	3.78	96	P550357	Lube Spin-on							
	3.94	100	3.15	80	P550389	Lube Spin-on	M45 x 1.5	12.13	308	5.33	135	P551400	Lube Spin-on
	4.98	126	3.69	93	P550834	Fuel Spin-on							
	5.42	138	3.67	93	P550166	Lube Spin-on	M45 x 2	7.09	180	5.04	128	P764259	Hydraulic Spin-on
	5.47	139	3.64	92	P502072	Lube Spin-on							
	5.51	140	3.82	97	P553315	Lube Spin-on	M46 x 2	10.03	255	5.35	136	P502444	Lube Spin-on
	6.42	163	3.69	94	P550733	Fuel Spin-on							
	7.95	202	4.25	108	P554470	Fuel Spin-on	M48 x 2	6.71	170.5	4.92	125	P502292	Hydraulic Spin-on
	10.40	264	4.25	108	P554472	Fuel Spin-on		6.85	174	4.99	127	P502382	Hydraulic Spin-on
M23 x 1.5	4.45	113	3.82	97	P761108	Hydraulic Spin-on							
M24 x 1.5	3.30	84	3.93	100	P502017	Lube Spin-on	M52 x 1.5	11.70	297	4.66	118	P550595	Lube Spin-on
	4.74	120	3.94	100	P550413	Lube Spin-on							
	4.81	122	4.13	105	P550597	Lube Spin-on	M60 x 3	6.62	168	5.48	139	P550356	Lube Spin-on
	5.35	136	3.66	93	P550758	Lube Spin-on							
	5.66	144	3.77	96	P550495	Fuel Spin-on	M72 x 2	9.00	228	3.58	91	P552200	Fuel Spin-on
	5.96	151	3.70	94	P551757	Hydraulic Spin-on							
	6.77	172	3.66	93	P550391	Fuel Spin-on	M85 x 2	11.57	294	4.65	118	P551040	Fuel Spin-on
	6.88	175	3.75	95	P550975	Lube Spin-on							
	7.00	178	3.78	96	P550365	Fuel Spin-on	M90 x 2.0	11.85	301	4.79	122	P550775	Lube Spin-on
	7.12	181	3.70	94	P764729	Hydraulic Spin-on							
M24 x 1.5 Male	8.88	226	3.69	94	P550416	Hydraulic Spin-on	M92 X 2.5	6.10	155	3.62	91	P566310	Fuel Spin-on
								6.10	155	3.66	93	P550779	Lube Spin-on
M24 x 2	5.50	140	3.66	93	P552476	Hydraulic Spin-on		6.10	155	3.82	97.03	P566311	Fuel Spin-on
								6.88	174	3.82	97	P566312	Fuel Spin-on
							M95 X 2	11.53	293	4.64	118	P552025	Lube Spin-on
							M95 x 2.5	11.70	297	4.65	118	ELF7900	Lube Spin-on
								11.70	297	4.66	118	P559000	Lube Spin-on
								11.70	297	4.67	119	ELF2501	Lube Spin-on

Liquid Filters by Thread Size



Global Presence with Local Touch

Donaldson has established a global distribution network to serve our customers locally as well as worldwide. We operate as a global company with a network for primary distribution locations that support a mature hub of regional distribution centers and warehouses.

Donaldson distribution centers are strategically located to quickly and accurately deliver filtration and exhaust products wherever replacement products are needed. We work with a network of transportation, third part logistics companies, consolidators, and cross-docking facilities to meet or exceed our customers' requirements.

All regions of the world benefit from our global umbrella of distribution centers. We focus our efforts on local support and the capabilities of our staff. We continue to make significant investments in facilities, systems, supply chain relationships and staffing to offer the best order fulfillment options available.



Donaldson Company, Inc.
PO Box 1299
Minneapolis, MN
55440-1299

www.donaldsonfilters.com
www.donaldson.com

North America 800-374-1374
Mexico +52-449-910-6150
Latin Am. +52-449-910-6150
Brazil +55-11-2119-1604
Europe +32-16-38-3811

Catalog No. F110025 (07/10)

South Africa +27-11-997-6000
South East Asia 65-6311-7373
Greater China 852-2405-8388
Japan 81-42-540-4112
Australia 61-02-4350-2033
India +91-124-2290060

© 2010 Donaldson Company, Inc. All rights reserved. Donaldson Company, Inc. reserves the right to change or discontinue any model or specification at any time and without notice. Printed in the U.S.A.